

(51) International Patent Classification:
G05D 5/00 (2006.01)(21) International Application Number:
PCT/US2012/032942(22) International Filing Date:
10 April 2012 (10.04.2012)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/474,723 12 April 2011 (12.04.2011) US
13/440,952 5 April 2012 (05.04.2012) US
13/440,955 5 April 2012 (05.04.2012) US(71) Applicant (for all designated States except US):
AUTODESK, INC. [US/US]; 111 McInnis Parkway, San
Rafael, California 94903 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **GOLDSTEIN, Rhys**
[CA/CA]; 172 Madison Avenue, Toronto, Ontario M5R
2S5 (CA). **KHAN, Azam** [CA/CA]; 15 Babcock
Boulevard, Aurora, Ontario L4G 3G8 (CA). **TESSIER,**
Alexander [CA/CA]; 7 Ellerbeck St., Toronto, Ontario
Canada (CA).(74) Agents: **CAREY, John C.** et al.; Patterson & Sheridan,
LLP, 3040 Post Oak Blvd., Suite 1500, Houston, Texas
77056 (US).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD,

[Continued on next page]

(54) Title: GENERATION OF OCCUPANT ACTIVITIES BASED ON RECORDED OCCUPANT BEHAVIOR




Figure 2

(57) Abstract: A method and apparatus for simulating occupant behavior in buildings may be used to predict the energy use of a building structure. The activities of actual building occupants are recorded and provided as an input to the occupant behavior simulation. The occupant behavior simulation generates simulated occupant schedules with similar behavioral patterns. An arbitrary set of factors can be used to select plausible activity types, durations, and numbers of participants during an occupant behavior simulation. The simulated occupant schedules may then be incorporated into a building performance simulation to help architects predict the energy demand associated with different building design options.



SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD,
RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ,

DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT,
LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS,
SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

GENERATION OF OCCUPANT ACTIVITIES BASED ON RECORDED OCCUPANT BEHAVIOR

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims benefit of United States provisional patent application serial number 61/474,723, filed April 12, 2011, United States patent application serial number 13/440,952, filed April 5, 2012, and United States patent application serial number 13/440,955, filed April 5, 2012. Each of these applications is hereby incorporated herein by reference.

BACKGROUND OF THE INVENTION

10 Field of the Invention

[0002] Embodiments of the present invention generally relate to the modeling of building occupant behavior, and, more specifically, to generation of occupant activities based on recorded schedules. These figures in no way limit or are intended to limit the scope of the present invention.

15 Description of the Related Art

[0003] Buildings consume vast amounts of energy. Some estimate that they account for 72% of electricity use in the US. It has been suggested that appropriate design improvements, selected with the aid of decision-support software, could reduce energy use by about 30% in existing buildings and 50% to 75% in new buildings. This is the motivation for building performance simulation. The idea is to model a building's many interacting subsystems, including its occupants, electrical equipment, and indoor and outdoor climate. With simulation results in hand, an architect is better able to predict the energy demand associated with various designs and can choose from among the more sustainable options.

25 [0004] A building's energy consumption patterns depend largely on the behavior of the people that occupy it, a fact observed by comparing the timing of daily activities with profiles of energy use. Quantifying this behavior is a prerequisite for predicting when a building's equipment is likely to be in use, and assessing the adequacy of its lighting conditions, air temperature, and air quality. Many existing building
30 performance simulation tools use fixed schedules to account for the presence of occupants but such schedules do not yield realistic results.

[0005] As the foregoing illustrates, there is a need in the art for more detailed and realistic occupancy models for accurate energy demand predictions.

SUMMARY OF THE INVENTION

[0006] The present invention generally provides a system and method for the generation of occupant activities based on recorded schedules. The activities of occupants of a representative building structure are recorded and provided as an input to the occupant behavior simulation. The occupant behavior simulation generates fictional schedules with similar behavioral patterns. An arbitrary set of factors can be used to select plausible activity types (tasks), durations, and numbers of participants during an occupant behavior simulation.

[0007] One embodiment of the present invention sets forth a method for generating one or more attributes of occupant behavior for a target building structure. The method includes the steps of receiving recorded occupant behavior data associated with a representative building structure and constructing a histogram of at least two dimensions that is populated with the recorded occupant behavior data. Normalized arrays of occupant behavior feature values are computed based on the histogram. One or more attributes of occupant behavior for a simulated occupant of the target building structure are generated based on the normalized arrays of occupant behavior feature values.

[0008] Occupant behavior simulation may be used to predict the energy use of a building structure. One advantage of the disclosed method is that building performance simulation may be used to reduce the impact of buildings on the environment by helping architects predict the energy demand associated with different design options.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] So that the manner in which the above recited features of the present invention can be understood in detail, a more particular description of the invention, briefly summarized above, may be had by reference to embodiments, some of which are illustrated in the appended drawings. It is to be noted, however, that the appended drawings illustrate only typical embodiments of this invention and are

therefore not to be considered limiting of its scope, for the invention may admit to other equally effective embodiments.

[0010] Figure 1 illustrates a computer system configured to implement one or more aspects of the present invention;

5 [0011] Figure 2 illustrates the application components shown in Figure 1, according to one embodiment of the invention;

[0012] Figure 3A illustrates histograms populated with recorded occupant behavior data, according to one embodiment of the invention;

10 [0013] Figure 3B illustrates the histograms shown in Figure 3A after smoothing operations, according to one embodiment of the invention;

[0014] Figure 3C illustrates normalized arrays generated using the histograms shown in Figure 3B, according to one embodiment of the invention;

[0015] Figure 3D is a illustrates recorded and simulated desk work probability profiles for building occupants, according to one embodiment of the invention;

15 [0016] Figure 4A is a flow diagram of method steps for generating occupant behavior, according to one embodiment of the invention; and

[0017] Figure 4B is a flow diagram of a method step shown in Figure 4A, according to one embodiment of the invention.

DETAILED DESCRIPTION

20 [0018] In the following description, numerous specific details are set forth to provide a more thorough understanding of the present invention. However, it will be apparent to one of skill in the art that the present invention may be practiced without one or more of these specific details. In other instances, well-known features have not been described in order to avoid obscuring the present invention.

25 [0019] Figure 1 illustrates a computer system 100 configured to implement one or more aspects of the present invention. The computer system 100 includes, without limitation, a central processing unit (CPU) 130, a system memory 110, a graphics processing unit (GPU) 134, a GPU memory 120, a memory bridge 105, a display

device 136, a system disk 140, a device bridge 142, a network interface 144, and input devices 146, e.g., a mouse, keyboard, touchpad, and the like. The display device 136 or a touchpad may be configured to use a capacitive sensing, camera generated images, or any other technology known to those skilled in the art to sense stylus and/or multi-finger input. In one embodiment, system memory 110 is configured to store application components 112 that are configured to generate attributes of occupant behavior that can be used to predict energy demand for a building structure.

[0020] The CPU 130 communicates with the system memory 110 via the memory bridge 105, which may be, e.g., a Northbridge device or subsystem. System memory 110 is configured to store application programs, as well as data used by or generated by the CPU 130. System memory 110 is coupled to the memory bridge 105 via a system memory bus 150. The memory bridge 105 is coupled to the GPU 134 via a GPU system bus 152. The GPU system bus 152 may comprise any technically feasible data interconnect, such as the well-known personal computer interconnect (PCI) express bus. The memory bridge 105 is also coupled to the device bridge 142 using an interconnect system such as PCI. The GPU 134 conventionally incorporates real time image rendering means for rendering both three-dimensional (3D) and two-dimensional (2D) images. The GPU 134 delivers pixel data to display device 136, which may comprise a conventional CRT (cathode ray tube) or LCD (liquid crystal display). The GPU 134 is coupled to the GPU memory 120 using a GPU memory bus 154. The GPU memory 120 may be configured to store data used by or generated by the GPU 134. Data stored within the GPU memory 120 passes through the GPU 134 and the memory bridge 105 when accessed by the CPU 130. In some embodiments, the integrated circuit implementing the CPU 130 may incorporate additional functional blocks, such as the memory bridge 105 and the device bridge 142. In alternative embodiments, the integrated circuit implementing the GPU 134 may incorporate additional functional blocks, such as the memory bridge 105 and the device bridge 142.

[0021] The device bridge 142 is coupled to a hard drive 140, a network interface 144, and input devices 146. The hard drive 140 provides mass storage of programs and data. The network interface 144 provides network connectivity to other computers using a local area network (LAN) interface using any suitable technology,

such as Ethernet. The input devices 146 provide user input. Other components (not explicitly shown), including USB or other port connections, CD drives, DVD drives, film recording devices, and the like, may also be connected to I/O bridge 107.

Communication paths interconnecting the various components in Figure 1 may be implemented using any suitable protocols, such as PCI (Peripheral Component Interconnect), PCI Express (PCI-E), AGP (Accelerated Graphics Port), HyperTransport, Quick Path Interconnect, or any other bus or point-to-point communication protocol(s), and connections between different devices may use different protocols as is known in the art.

[0022] As used herein, the phrase “occupant behavior simulation” refers to a computer simulation performed by the application components 112 that generates fictional occupant schedules. An “occupant schedule” is a description of the behavior of a building occupant over the course of a single day. Each of these schedules takes the form of a chronological sequence of consecutive activities, with an “activity” being a description of an occupant’s behavior during a specific time interval. Each activity has several associated attributes. The attributes include at least the “task”, which identifies the type of activity. Each task may be selected from a pre-defined list of possible tasks through a user-interface. For example, to generate an attribute of an office building, there would likely be one possible task representing desk work, another possible task for meetings, and the like.

[0023] Figure 2 illustrates the application components 112 shown in Figure 1, according to one embodiment of the invention. The application components 112 include an occupant behavior simulation engine 200, recorded occupant behavior data 212, and generated occupant behavior 225. The occupant behavior simulation engine 200 receives the recorded occupant behavior data 212 and generates the generated occupant behavior 225 that includes one or more attributes, e.g., task performed, number of participants, and/or duration. The occupant behavior simulation engine 200 includes a histogram module 205, a smoothing module 210, a normalization module 215, and an occupant behavior generation module 220.

[0024] The occupant behavior simulation engine 200 implements a schedule-calibrated technique to produce the generated occupant behavior 225. In contrast with prior art techniques, the occupant behavior simulation engine 200 allows past behavior of occupants (actual and generated) to influence the future behavior that is

generated for simulated occupants. For example, if a first simulated occupant has taken a lunch break only three minutes ago, as opposed to three hours ago, the occupant behavior simulation engine 200 may be less likely to generate a meal attribute in the next three minutes of a schedule for the first simulated occupant.

- 5 [0025] The activities defined in the recorded occupant behavior data 212 include attributes such as the task, number of participants, and duration. The occupant behavior simulation engine 200 generates attributes one at a time using a mathematical technique where each attribute depends on an arbitrary set of factors that influence the generated attributes. The generated behavior for an occupant
- 10 should depend in part on the time of day, so the time of day is a factor. Other factors, such as the previous task performed by the occupant, time elapsed since the previous or same task was performed, and the number of occupants participating in a task may also be used to influence the generated behavior. Once a particular attribute is generated from a set of factors, that attribute can itself become a factor for the
- 15 generation of another attribute. For example, if the time of day is used as a factor to generate a task, the generated task may then be used as a factor that influences the activity duration. The ability of the occupant behavior simulation engine 200 to generate one or more activity attributes based on a variety of factors and/or tasks produces a detailed representation of occupant behavior.
- 20 [0026] The occupant behavior simulation engine 200 receives the recorded occupant behavior data 212 that includes schedules of actual occupants of a representative building structure. The histogram module 205 constructs histograms, having bins for each activity attribute during different time intervals, that are populated with the recorded occupant behavior data 212. The recorded occupant behavior data
- 25 212 may not fully populate the histograms. Therefore, the smoothing module 210 is applied for one or more iterations to complete the population of the histogram. The smoothing module 210 extrapolates the occupant behavior data across the bins to produce additional occupant behavior data as need to fully populate the histograms. The normalization module 215 then normalizes the feature values in the smoothed
- 30 histograms to compute normalized arrays for each feature over the time intervals. The occupant behavior generation module 220 extracts the attribute values based on the normalized arrays and produces the generated occupant behavior for one or more occupants. Together, the histogram module 205, the smoothing module 210, and the

normalization module 215 perform a calibration process for the simulation based on the recorded occupant behavior data 212.

[0027] Throughout the following description, a first example is described in which a single activity attribute: the task, is generated by the occupant behavior simulation engine 200. In the first example, four possible tasks, named “off”, “work”, “meet”, and “eat” and two factors, the time of day (TOD) and the previous task (PVT) are used. TABLE 1 includes two days of recorded occupant behavior data for an actual occupant of a representative building structure. Each row of TABLE 1 specifies a separate activity. An activity occurs during a time interval that begins at an initial time and ends at the time when the subsequent activity begins. The “NPO” column lists the “number of participating occupants” for each task. On day 0, for example, the occupant had a meeting with four other occupants at 10:02 AM.

TABLE 1 Recorded occupant schedule data for a representative building

Day 0			Day 1		
Time	Task	NPO	Time	Task	NPO
8:45AM	Work	1	9:13AM	Work	1
10:02AM	Meet	5	10:41AM	Meet	2
11:17AM	Work	1	11:02AM	Work	1
12:10AM	Eat	3	1:16PM	Eat	1
1:01PM	Work	1	1:55PM	Work	1
5:46PM	Off	1	4:32PM	Meet	2
			4:51PM	Work	1
			4:59PM	Off	1

The goal of the occupant behavior simulation engine 200 is to automatically generate attributes, tasks in this first example, during a simulation, where the generated occupant behavior that resembles the occupant schedule data in TABLE 1. The first

step of the simulation technique performed by the occupant behavior simulation engine 200 is to populate a set of histograms with the recorded occupant behavior data 212.

[0028] Figure 3A illustrates histograms populated with the recorded occupant behavior data shown in TABLE 1, according to one embodiment of the invention. The histograms are two-dimensional because two factors (TOD and PVT) are used for the example. Each histogram includes one column for each of the four possible previous tasks, and the time of day factor is discretized such that each hour of the day has a corresponding set of histogram bins.

[0029] Every activity shown in TABLE 1 contributes a value of 1 to both A_0 and one of the other four B_0 histograms shown in histograms populated with recorded occupant behavior data 300. Each B_0 histogram is associated with a single “feature”, and in this specific example there is one feature per possible task. The general mathematical technique allows for any number of features to be selected and each feature can be associated with any quantity of occupants. For the first activity of Day 0, the time (8:45 AM) fits into the “8 AM to 9AM” slot and the previous task is assumed to be “off”. Thus $A_0[“8 AM”; “off”] = 1$, as shown just under the top-left corner cell of histograms populated with recorded occupant behavior data 300. Because the task performed at 8:45AM is “work”, 1 is added to the corresponding bin of the “work”-specific feature histogram ($B_0[“8 AM”; “off”][“work”]$). On both Day 0 and Day 1, the occupant transitions from the “work” task to the “meet” task between 10AM and 11 AM. Therefore, $A_0[“10 AM”; “work”] = B_0[“10 AM”; “work”][“meet”] = 2$. On Day 1, the occupant transitioned away from the “work” task at 4:32 PM and 4:59PM, giving $A_0[“4 PM”; “work”] = 2$. Note that the 4:32 PM activity contributes to $B_0[“4 PM”; “work”][“meet”]$, whereas the 4:59 PM activity affects $B_0[“4 PM”; “work”][“off”]$.

[0030] Many bins of the histograms are empty after the histograms are populated with the recorded occupant schedule data from TABLE 1. This problem of sparsely populated histograms may occur, even if hundreds of actual occupant schedules are used to populate the histograms, because when additional factors are used and discretized at higher resolutions, the total number of bins increases. In order to produce the generated occupant behavior 225, the occupant behavior simulation engine 200 extracts information computed based on the bins that are currently empty.

Consequently, it is necessary to “smooth” the data populating the bins, propagating values across empty neighboring bins to reduce the sparseness.

[0031] In one embodiment the smoothing module 210 performs a smoothing algorithm requiring one “smoothing parameter” $\alpha_{\langle factor \rangle}$ for each factor $\langle factor \rangle$. The smoothing parameters are all non-negative, and the sum of the smoothing parameters is at most 1. The larger a smoothing parameter for a certain factor, the smoother the final data across neighboring bins along the axis associated with that factor. The first step in each smoothing iteration i is to define a set of coefficients C_i using equation (1), one for each histogram bin (identified by $\langle bin \rangle$) and each factor.

$$C_i[\langle bin \rangle][\langle factor \rangle] = \frac{\frac{\alpha_{\langle factor \rangle}}{n_{\langle factor \rangle}} \cdot \sum_{\langle factor \rangle} \alpha_{\langle factor \rangle}}{\sum_{\langle factor \rangle} \alpha_{\langle factor \rangle} + \sqrt{A_i[\langle bin \rangle]}} \quad \text{Equation (1)}$$

If a bin has been heavily populated, the information within the bin is trusted and the effect of the smoothing is lessened by including $\left[\sqrt{A_i[\langle bin \rangle]} \right]$ in the denominator. The variable $n_{\langle factor \rangle}$ is the number of neighboring bins along the axis associated with $\langle factor \rangle$. For factors having continuous values, such as the time of day, the neighboring bins are the two adjacent bins (or the one adjacent bin at the edge of a histogram). For discrete factors like tasks, all other bins along the axis are neighbors.

[0032] A value c_i is the fraction of each bin’s value that will be preserved through the smoothing iteration. While the coefficients C_i are dependent on $\langle factor \rangle$, c_i is not dependent on $\langle factor \rangle$. c_i is computed using equation (2).

$$c_i[\langle bin \rangle] = 1 - \sum_{\langle factor \rangle} (n_{\langle factor \rangle} \cdot C_i[\langle bin \rangle][\langle factor \rangle]) \quad \text{Equation (2)}$$

[0033] In a single iteration, convolutions are performed separately for each histogram using the same set of coefficients. The coefficients C_i that are in the set and the fractions c_i are recalculated for each iteration, where $i=0$ for the first iteration, $i=1$ for the second iteration, and so forth. In equation (3) shown below, X_i represents

any of the histograms for iteration i . We use $\langle bin^* \rangle$ to denote the neighboring bin located at a displacement $\langle offset \rangle$ along the axis associated with $\langle factor \rangle$.

$$X_{i+1}[\langle bin \rangle] = c_i[\langle bin \rangle] \cdot X_i[\langle bin \rangle] + \sum_{\langle factor \rangle} \sum_{\langle offset \rangle} (C_i[\langle bin \rangle \langle factor \rangle] \cdot X_i[\langle bin^* \rangle]) \quad \text{Equation (3)}$$

[0034] Continuing with the simplified task generation example, $\alpha_{TOD} = 0.14$ and

5 $\alpha_{PVT} = 0.06$. Figure 3B illustrates the histograms shown in Figure 3A after one iteration of the smoothing operation, according to one embodiment of the invention. Serving as a demonstration of the algorithm performed by the smoothing module 210, the following is a derivation of $A_1["4 PM"; "work"]$. Note that the computed value 1.96, resulting from smoothing, in the bin of histograms after smoothing 320 of Figure 3B.

10 [0035] First, the smoothing coefficient associated with the time of day factor is computed. Because this factor is continuous, there are two neighbors ($n_{TOD} = 2$).

$$\begin{aligned} C_0["4 PM"; "work"] &= \frac{\alpha_{TOD}}{n_{TOD}} \cdot \frac{\alpha_{TOD} + \alpha_{PVT}}{\alpha_{TOD} + \alpha_{PVT} + \sqrt{A_0["4 PM", "work"]}} \\ &= \frac{0.14}{2} \cdot \frac{0.14 + 0.06}{0.14 + 0.06 + \sqrt{2}} \end{aligned}$$

15 = 0.0086730...

[0036] The smoothing coefficient associated with the previous task is calculated in a similar fashion. In this case, because tasks are discrete and there are four in total, there are three neighbors ($n_{PVT} = 3$).

$$C_0["4 PM", "work"] = 0.0024780...$$

20 [0037] The c_0 value is obtained as follows.

$$\begin{aligned} c_0["4 PM"; "work"] &= 1 \\ &- n_{TOD} \cdot C_0["4 PM", "work"] \\ &- n_{PVT} \cdot C_0["4 PM", "work"] \end{aligned}$$

$$= 0.97522...$$

[0038] Using A_1 in place of X_{i+1} , the convolution equation computes the value shown in Figure 3A.

$$\begin{aligned}
 & A_1["4 \text{ PM}"; "work"] \\
 5 \quad & = c_0["4 \text{ PM}"; "work"] \cdot A_0["4 \text{ PM}"; "work"] \\
 & + C_0["4 \text{ PM}"; "work"]["TOD"] \cdot A_0["3 \text{ PM}"; "work"] \\
 & + C_0["4 \text{ PM}"; "work"]["TOD"] \cdot A_0["5 \text{ PM}"; "work"] \\
 & + C_0["4 \text{ PM}"; "work"]["PVT"] \cdot A_0["4 \text{ PM}"; "off"] \\
 & + C_0["4 \text{ PM}"; "work"]["PVT"] \cdot A_0["4 \text{ PM}"; "meet"] \\
 10 \quad & + C_0["4 \text{ PM}"; "work"]["PVT"] \cdot A_0["4 \text{ PM}"; "eat"] \\
 & \\
 & = 1.9616...
 \end{aligned}$$

[0039] The smoothing processes are terminated by the smoothing module 210 after a pre-defined number of iterations n . If empty bins still remain, a greater number of smoothing iterations may be used, lower resolutions on the continuous factors may be selected, or more occupant behavior data may be provided.

[0040] After smoothing the histograms, the feature values B_n are normalized to yield a set of arrays of normalized feature values collectively named D . Normalization is the last step in the calibration process performed by the occupant behavior simulation engine 200. Figure 3C illustrates normalized arrays 340 generated using the histograms shown in Figure 3A after 9 iterations of smoothing, according to one embodiment of the invention.

[0041] Continuing with the first example, normalization divides the B_n values by corresponding A_n values.

$$D[\langle bin \rangle \langle feature \rangle] = \frac{B_n[\langle bin \rangle][\langle feature \rangle]}{A_n[\langle bin \rangle]}$$

[0042] The information shown in the normalized arrays 340 may be used by the occupant behavior generation module 220 to perform a process called extraction during a simulation to generate plausible attributes, such as tasks. Suppose that the current simulated time is 11:30AM, and a simulated occupant has just completed a

“work” activity. To select the next task, the occupant behavior generation module 220 determines the normalized feature values associated with the following TOD and PVT factors.

$D["11 \text{ AM}"; "work"]["off"] = 0.00...$

5 $D["11 \text{ AM}"; "work"]["work"] = 0.17...$

$D["11 \text{ AM}"; "work"]["meet"] = 0.55...$

$D["11 \text{ AM}"; "work"]["eat"] = 0.28...$

[0043] In this case there is roughly a 17% chance that the occupant will continue working, a 55% chance he/she will meet with other occupants, a 28% chance of taking a break for food, and very little chance he/she will leave for the day. In one embodiment, the occupant behavior generation module 220 selects the next task at random according to the probabilities computed by the occupant behavior generation module 220 using the normalized arrays of feature values. The occupant behavior generation module 220 computes a probability table for each task transition over the time intervals to enable the selection.

[0044] Suppose that the occupant completes the “work” activity at 11:45 AM instead of 11:30 AM. In this case, the probabilities may be interpolated. The center of the “11 AM to 12PM” slot is 11:30 AM, a quarter of an hour before the simulated time, and the center of the “12 PM to 1 PM” slot is 12:30PM, three quarters of an hour after the simulated time. Using a linear interpolation, the probability that the occupant begins eating is $(3/4) \cdot 0.28 + (1/4) \cdot 0.95$, or 44.75%. The other probabilities may be interpolated in a similar fashion.

[0045] Figure 3D illustrates recorded and simulated desk work probability profiles for building occupants, according to one embodiment of the invention. The jagged line was produced by counting, for each minute of the day, the number of times the actual occupant was recorded performing desk work, then dividing by the total number of recorded schedules (27). The smoother line was calculated in the same fashion, but using 10000 schedules of simulated occupant behavior generated by the occupant behavior simulation engine 200. The real and simulated profiles follow roughly the same path, though evidently the occupant behavior generation module 220 overestimates the probability of desk work around lunch and underestimates the probability of desk work before and after.

[0046] Despite the differences between the profiles at certain hours of the day, the real and simulated time-averaged probabilities of desk work are in fairly close agreement. On average, the actual occupant worked at their desk only 3.4 minutes longer per day than the simulated occupant (411.6 minutes total compared with
5 408.2).

[0047] While desk work is typically performed several times per day, the occurrence of certain other tasks is best measured over several days. The actual occupant took a break outside on 14 of 27 days, and so the desired probability that the “break@outside” task occurs in a day is about 51.9%. From 10000 generated
10 schedules, the result was roughly 53.6%. Given that the goal of the occupant behavior simulation engine 200 is to predict human behavior, the error of 1.7% is tolerable.

[0048] Different models of occupant behavior may be defined using the application components 112, but with alternative sets of attributes, factors, and features. In a
15 second example, a task, number of participating occupants (NPO), and duration may be generated for each activity. The same smoothing algorithm described in conjunction with the first example is applied to histograms and multi-dimensional histograms and arrays are used to support an arbitrary number of factors. The histogram population, normalization, and extraction procedures performed by the
20 histogram module 205, smoothing module 210, normalization module 215, and occupant behavior generation module 220, respectively, differ somewhat between the three generated attributes, as explained below.

[0049] The tasks are generated using three factors, the time of day (TOD), the previous task (PVT), and the task suspension interval (TSI). Two of these, the TOD
25 and the PVT, were used in the first example. The rationale for using TOD as a factor is that the timing of arrivals, departures, and lunch breaks is highly dependent on the time of day. The TOD is discretized into 15-minute intervals, providing a higher resolution than the 60-minute intervals used in the first example. $\alpha_{TOD} = 0.23$ in this example.

[0050] The rationale for the PVT factor is that certain transitions between tasks are
30 more likely to occur than others. In this example, $\alpha_{PVT} = 0$, which prevents a transition

from occurring in the simulated schedules if it is not found in the real schedules. With a $\alpha_{PVT} = 0$, one would not expect two washroom breaks to be generated back-to-back.

[0051] The TSI measures the time elapsed since a task was last performed. Inclusion of the TSI as a factor during the generation of occupant behavior simulation helps reproduce intervals between tasks. This is useful to spread out washroom breaks, or coffee/lunch breaks, for example. A logarithmic discretization may be used, with separate bins for task suspension intervals of 0 to 15 minutes, 15 to $15 \cdot \sqrt{2}$ minutes, $15 \cdot \sqrt{2}$ to 30 minutes, 30 to $30 \cdot \sqrt{2}$ minutes, etc. $\alpha_{TOD} = 0:02$.

[0052] Whereas the TOD and PVT factors are scalar values, the TSI factor requires a separate time interval for each possible task. This complicates the mathematical procedure demonstrated in smoothing and normalization. When populating a histogram with a single activity, or when extracting a set of probabilities, multiple TSI values must be used to reference histogram bins.

[0053] To generate the numbers of participating occupants for each activity, the TOD factor is used. Because an activity's NPO is generated after generating the task for the activity, the current task (TSK) may be used as the other factor. The TOD might well influence the NPO, as an occupant taking a break is more likely to have company around noon than in mid-afternoon. Again, the TOD is discretized at 15-minute intervals, but now $\alpha_{TOD} = 0:25$.

[0054] The NPO may depend on the TSK, as a task representing meetings is more likely to be collaborative than, for example, a washroom break. A α_{TSK} value of 0 ensures that washroom breaks are always treated as individual activities.

[0055] When generating the simulated occupant behavior for the first example, one task was generated per time interval. When generating the NPO, there are far more possible values for each time interval. Therefore, two features, one called "sums" and another called "square sums" are computed. For each activity in the recorded occupant schedules, $\frac{1}{2}$ is subtracted from the number of participants npo . Then $(npo - \frac{1}{2})$ is added to the correct bin in the "sums" feature histogram, and $(npo - \frac{1}{2})^2$ is added to the same bin in the "square_sums" histogram. After n iterations of

smoothing, each bin $\langle bin \rangle$ has the values $A_n[\langle bin \rangle]$, $B_n[\langle bin \rangle]$ ["sums"], and $B_n[\langle bin \rangle]$ ["square_sums"].

[0056] The normalization equations that are applied by the normalization module 215 are as follows.

$$D[\langle bin \rangle][\text{"mean"}] = \frac{B_n[\langle bin \rangle][\text{"sums"}]}{A_n[\langle bin \rangle]}$$

$$D[\langle bin \rangle][\text{"variance"}] = \frac{B_n[\langle bin \rangle][\text{"square\_sums"}]}{A_n[\langle bin \rangle]} - D[\langle bin \rangle][\text{"mean"}]^2$$

[0057] During a simulation, with the time of day and the current task known, appropriate distribution parameters, e.g., mean and standard deviation values, can be interpolated from D . A gamma distribution is formulated using the time of day and the current task properties, a positive value may be randomly selected from the gamma distribution, summed with 1, and then converted to a positive integer by rounding down to generate the NPO.

[0058] In one embodiment, the duration of an activity depends on the time of day (TOD), the task (TSK), and the number of participating occupants (NPO). The rationale for using the TOD factor is that, for example, an occupant is less likely to work for several hours continuously if it is nearly time to leave the office. 15-minute intervals are selected and $\alpha_{TOD} = 0:23$. An activity's duration is highly dependent on the task, therefore $\alpha_{TSK} = 0$. A positive α_{TSK} leads to absurdly long washroom breaks, as the durations of the washroom breaks become influenced by the durations of other types of activities.

[0059] The NPO factor is used because an occupant may take a longer lunch break if he/she is not by himself/herself. We use separate bins for activities with 1 participant, 2 or 3 participants, 4 to 7, 8 to 15, 16 to 31, 32 to 63, and 64 or more participants. For smoothing, $\alpha_{NPO} = 0:02$.

[0060] Duration generation is similar to NPO generation. Again, two features are used, adding recorded durations to one feature and squares of the recorded durations to the other feature. Durations may then be randomly generated using gamma

distributions. Because a duration is a continuous quantity, offsetting and rounding off of values that was needed to generate an NPO, is not needed to generate a duration.

[0061] Ideally, the fictional schedules generated by the occupant behavior simulation engine 200 would be indistinguishable from the recorded occupant schedules used to calibrate the occupant behavior simulation engine 200. In a third example, the occupant behavior simulation engine 200 is calibrated using the same 27 actual occupant schedules. Generated occupant behavior 225 produced by the occupant behavior simulation engine 200 is represented as a schedule shown in TABLE 2. The generated schedule appears plausible in several regards: the arrival and departure times; the fact that the occupant spends most of the day doing desk work; the 6-minute “desk meeting” in the morning; and the fact that the washroom breaks are spread out and range from 1 to 4 minutes in duration. The 13-person lunch break outside the building happens to be consistent with a few of the 27 recorded occupant schedules that were input to the occupant behavior simulation engine 200 as occupant behavior data 212.

TABLE 2 A generated occupant schedule

Time	Task	NPO
9:57AM	work@desk	1
10:19AM	meet@desk	2
10:24AM	work@desk	1
11:37AM	break@washroom	1
11:41AM	work@desk	1
12:01PM	break@sharedroom	1
12:12PM	break@washroom	1
12:13PM	work@desk	1
12:28PM	break@outside	13
1:31PM	break@washroom	1
1:34PM	work@desk	1
2:42PM	break@washroom	1
2:44PM	work@desk	1
4:08PM	break@sharedroom	1
4:13PM	work@desk	1
6:13PM	off@outside	1

[0062] The actual occupant never left the building and returned twice in a single day. This pattern of behavior appears to be reflected in the generated schedules, presumably due to the TSI factor that measures the time elapsed since a task was last performed. But because breaks outside the building (“break@outside”) were classified as separate tasks from breaks on site (“break@sharedroom”), the TSI factor did nothing to prevent the outside break in Table 2 from being preceded by the break at 12:01 PM. By combining “break@outside” and “break@sharedroom” into a single task, the generation of multiple breaks around noon may be discouraged. But on the other hand, the tendency for a 13-person “team lunch” to take place at a restaurant, or the trend that 5-minute breaks around 4:08PM tend to occur on site may be lost. The more general point is that different classification schemes will reproduce different behavioral patterns, while no single classification scheme may be ideal.

[0063] Figure 4A is a flow diagram of method steps for generating occupant behavior, according to one embodiment of the invention. Although the method steps are described in conjunction with the system of Figures 1 and 2, persons skilled in the art will understand that any system configured to perform the method steps, in any order, is within the scope of the invention.

[0064] The method begins in step 405, when the occupant behavior simulation engine 200 receives the recorded occupant data 212 for a representative building structure. At step 410 the histogram module 205 constructs histograms populated with the recorded occupant data 212. At step 415 the smoothing module 210 performs smoothing operations over one or more iterations to smooth the histograms. At step 420 the normalization module 215 computes normalized arrays using the smoothed histograms. At step 425 the occupant behavior generation module 220 generates one or more attributes of occupant behavior from the normalized arrays.

[0065] Figure 4B is a flow diagram of method step 425 shown in Figure 4A, according to one embodiment of the invention. At step 430 the occupant behavior generation module 220 generates probability table(s) from the normalized arrays of feature values. At step 440 the occupant behavior generation module 220 computes gamma distribution parameters using the normalized arrays of occupant behavior feature values. At step 445 the occupant schedule generation module 220 generates an occupant behavior attribute for a time interval using the probability tables or the distribution parameters. At step 450 the occupant schedule generation module 220 determines if another occupant behavior attribute should be generated for the time interval, and, if so, the occupant schedule generation module 220 returns to step 445.

[0066] Otherwise, at step 455 the occupant schedule generation module 220 stores the generated occupant behavior attributes for the current time interval. At step 460 the occupant schedule generation module 220 determines if occupant behavior attributes should be generated for another time interval, and, if so, the occupant schedule generation module 220 returns to step 445. Otherwise, at step 465 the occupant schedule generation module 220 is done generating occupant behavior attributes.

[0067] A number of techniques have previously been developed to simulate the behavior of building occupants based on the recorded schedules of actual occupants.

The schedule calibrated method described herein differs from previous technique in that the level of detail may be specified, occupant behavior is modeled by selecting various activity attributes, and the behavioral patterns that are generated by the occupant behavior simulation may be altered by selecting different sets of factors.

- 5 When tested with selected attributes and factors, the occupant behavior simulation engine 200 generated plausible fictional occupant behavior represented by schedules with acceptable statistical accuracy. The generated occupant behavior 225 may be incorporated into building performance simulation to address the need for improved decision-support in building design, allowing architects to conveniently and accurately
10 predict the energy use associated with different design options for a target building structure.

- [0068] One embodiment of the invention may be implemented as a program product for use with a computer system. The program(s) of the program product define functions of the embodiments (including the methods described herein) and
15 can be contained on a variety of computer-readable storage media. Illustrative computer-readable storage media include, but are not limited to: (i) non-writable storage media (e.g., read-only memory devices within a computer such as CD-ROM disks readable by a CD-ROM drive, flash memory, ROM chips or any type of solid-state non-volatile semiconductor memory) on which information is permanently
20 stored; and (ii) writeable storage media (e.g., floppy disks within a diskette drive or hard-disk drive or any type of solid-state random-access semiconductor memory) on which alterable information is stored.

- [0069] While the foregoing is directed to embodiments of the present invention, other and further embodiments of the invention may be devised without departing
25 from the basic scope thereof, and the scope thereof is determined by the claims that follow.

Claims:

1. A computer-implemented method for generating one or more attributes of simulated occupant behavior for a target building structure, the method comprising:
 - 5 receiving recorded occupant behavior data associated with a representative building structure;
 - constructing a histogram of at least two dimensions that is populated with the recorded occupant behavior data;
 - computing normalized arrays of occupant behavior feature values based on the
 - 10 histogram; and
 - generating one or more attributes of occupant behavior for a simulated occupant of the target building structure based on the normalized arrays of occupant behavior feature values.
- 15 2. The method of claim 1, wherein the one or more attributes include a task performed by the simulated occupant of the target building structure.
3. The method of claim 1, wherein the one or more attributes include a time duration during which a task is performed by the simulated occupant of the target
- 20 building structure.
4. The method of claim 1, wherein the one or more attributes include a number of participants associated with a simulated task performed by the simulated occupant of the target building structure.
- 25 5. The method of claim 1, further comprising, prior to computing the normalized arrays, smoothing the recorded occupant behavior data of the histogram across a plurality of empty bins.
- 30 6. The method of claim 5, wherein smoothing comprises:
 - determining a smoothing parameter for each factor that influences the one or more attributes; and
 - computing a smoothing coefficient for each of the bins based on the smoothing parameter and a number of neighboring bins.

7. The method of claim 1, wherein generating one or more attributes comprises:
computing a probability table based on the normalized arrays of occupant
behavior feature values;

5 computing one or more gamma distribution parameters based on the
normalized arrays of occupant behavior feature values; and
generating a first occupant behavior attribute for a time interval based on the
probability table or the gamma distribution parameters.

10 8. The method of claim 1, wherein a number of dimensions of the histogram
equals a number of factors that influence the one or more attributes.

9. The method of claim 8, wherein the factors comprise at least one of time of
day, a previous task performed by an actual occupant, time elapsed since a task was
15 performed by the actual occupant, and a number of occupants participating in a task.

10. A computer-readable storage medium storing instructions that, when executed
by a processing unit, cause a computer system to perform an operation for generating
one or more attributes of simulated occupant behavior for a target building structure,
20 the operation comprising:

receiving recorded occupant behavior data associated with a representative
building structure;

constructing a histogram of at least two dimensions that is populated with the
recorded occupant behavior data;

25 computing normalized arrays of occupant behavior feature values based on the
histogram; and

generating one or more attributes of occupant behavior for a simulated
occupant of the target building structure based on the normalized arrays of occupant
behavior feature values.

30 11. A computer-implemented method for generating an attribute of simulated
occupant behavior for a target building structure, the method comprising:

receiving recorded occupant behavior data associated with a representative building structure, wherein the recorded occupant behavior data includes actual tasks performed during a plurality of time intervals;

generating the attribute of the simulated occupant behavior that is performed during a first time interval for the target building structure based on the recorded occupant behavior data; and

generating the attribute of the simulated occupant behavior that is performed during a second time interval for the target building structure based on an actual task performed during the first time interval.

10

12. The method of claim 11, further comprising generating an additional attribute of the simulated occupant behavior that is performed during the first time interval for the target building structure based on the recorded occupant behavior data.

13. The method of claim 12, wherein the additional attribute comprises a task performed by the simulated occupant of the target building structure.

14. The method of claim 12, wherein the additional attribute is a time duration during which a task is performed by the simulated occupant of the target building structure.

20

15. The method of claim 12, wherein the additional attribute comprises a number of participants associated with a simulated task performed by the simulated occupant of the target building structure.

25

16. The method of claim 11, further comprising constructing a histogram populated with the recorded occupant behavior data.

17. The method of claim 16, further comprising computing normalized arrays of occupant behavior feature values based on the histogram.

30

18. The method of claim 16, further comprising smoothing the recorded occupant behavior data of the histogram across a plurality of empty bins.

19. The method of claim 11, further comprising generating an additional attribute of the simulated occupant behavior that is performed during the first time interval for the target building structure based on the generated attribute.

5 20. A computer-readable storage medium storing instructions that, when executed by a processing unit, cause a computer system to perform an operation for generating an attribute of simulated occupant behavior for a target building structure, the operation comprising:

10 receiving recorded occupant behavior data associated with a representative building structure, wherein the recorded occupant behavior data includes actual tasks performed during time intervals;

generating the attribute of the simulated occupant behavior that is performed during a first time interval for the target building structure based on the recorded occupant behavior data; and

15 generating the attribute of the simulated occupant behavior that is performed during a second time interval for the target building structure based on an actual task performed during the first time interval.




Figure 1




Figure 2

Histograms populated with
occupant behavior data

300

PVT TOD	A ₀ [...]				B ₀ [...][“off”]				B ₀ [...][“work”]				B ₀ [...][“meet”]				B ₀ [...][“eat”]			
	off	work	meet	eat	off	work	meet	eat	off	work	meet	eat	off	work	meet	eat	off	work	meet	eat
7 AM																				
8 AM	1								1											
9 AM	1								1											
10 AM		2											2							
11 AM			2								2									
12 PM		1																1		
1 PM		1		2								2						1		
2 PM																				
3 PM																				
4 PM		2	1			1					1									
5 PM		1				1														
6 PM																				

Figure 3A

Histograms after
smoothing
320

PVT TOD	A ₁ [...]				B ₁ [...]"off"]				B ₁ [...]"work"]				B ₁ [...]"meet"]				B ₁ [...]"eat"]			
	off	work	meet	eat	off	work	meet	eat	off	work	meet	eat	off	work	meet	eat	off	work	meet	eat
7 AM	0.07								0.07											
8 AM	0.98	0.02	0.02	0.02					0.98	0.02	0.02	0.02								
9 AM	0.98	0.16	0.02	0.02					0.98	0.02	0.02	0.02		0.14						
10 AM	0.11	1.95	0.18	0.04					0.07		0.14		0.04	1.95	0.04	0.04				
11 AM	0.04	0.25	1.95	0.04					0.04	0.04	1.95	0.04		0.14			0.07			
12 PM	0.02	0.98	0.16	0.16							0.14	0.14					0.02	0.98	0.02	0.02
1 PM	0.06	0.99	0.06	1.95					0.04	0.01	0.04	1.95					0.02	0.98	0.02	0.00
2 PM		0.07		0.14								0.14						0.07		
3 PM		0.14	0.07								0.07			0.07						
4 PM	0.06	1.96	0.97	0.06	0.02	0.98	0.00	0.02	0.02	0.00	0.97	0.02	0.02	0.98	0.00	0.02				
5 PM	0.02	0.99	0.09	0.02	0.02	0.98	0.02	0.02			0.07			0.01						
6 PM		0.07				0.07														

Figure 3B

Normalized Arrays
340

PVT TOD	D[...]"off"]				D[...]"work"]				D[...]"meet"]				D[...]"eat"]			
	off	work	meet	eat	off	work	meet	eat	off	work	meet	eat	off	work	meet	eat
7 AM	0.00	0.00	0.00	0.00	1.00	0.81	0.98	0.98	0.00	0.19	0.02	0.02	0.00	0.00	0.00	0.00
8 AM	0.00	0.00	0.00	0.00	1.00	0.62	0.96	0.95	0.00	0.38	0.04	0.05	0.00	0.00	0.00	0.00
9 AM	0.00	0.00	0.00	0.00	0.98	0.15	0.81	0.72	0.02	0.85	0.19	0.28	0.00	0.00	0.00	0.00
10 AM	0.00	0.00	0.00	0.00	0.65	0.01	0.77	0.27	0.35	0.99	0.23	0.72	0.00	0.00	0.00	0.01
11 AM	0.00	0.00	0.00	0.00	0.79	0.17	0.99	0.81	0.13	0.55	0.01	0.13	0.08	0.28	0.00	0.06
12 PM	0.00	0.00	0.00	0.00	0.45	0.02	0.86	0.87	0.02	0.02	0.00	0.00	0.54	0.95	0.14	0.13
1 PM	0.00	0.00	0.00	0.00	0.64	0.06	0.71	0.99	0.00	0.00	0.00	0.00	0.35	0.94	0.29	0.01
2 PM	0.04	0.08	0.02	0.00	0.62	0.08	0.76	0.97	0.04	0.08	0.02	0.00	0.30	0.77	0.21	0.02
3 PM	0.30	0.47	0.04	0.17	0.38	0.02	0.90	0.66	0.28	0.46	0.04	0.16	0.04	0.05	0.01	0.01
4 PM	0.37	0.51	0.04	0.36	0.31	0.01	0.93	0.33	0.32	0.48	0.03	0.31	0.00	0.00	0.00	0.00
5 PM	0.74	0.90	0.25	0.74	0.15	0.00	0.73	0.15	0.11	0.09	0.02	0.11	0.00	0.00	0.00	0.00
6 PM	0.85	0.96	0.39	0.84	0.10	0.01	0.59	0.10	0.05	0.04	0.01	0.05	0.00	0.00	0.00	0.00

Figure 3C





Figure 3D

**Figure 4A**




Figure 4B

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 12/32942

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - G05D 5/00 (2012.01)

USPC - 700/291

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

USPC: 700/291

IPC(8): G05D 5/00 (2012.01)

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

USPC: 700/708,257,291 | 703/1,4

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

PubWEST(PGPB,USPT,EPAB,JPAB); Google Scholar; Histogram, smooth, array, behavior, task, activities, simulation, normalization, occupancy, building, attributes

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	Goldstein et al. "Schedule-Calibrated Occupant Behavior Simulation." [online] Autodesk Research, published 2010. [retrieved on 16 June 2012 (16.06.2012)] Retrieved from the Internet<URL:http://autodeskresearch.com/pdf/simaud2010_occupant.pdf> entire document (especially pg. 2, col. 1 to col. 2; pg. 3, col. 2; pg. 5, col. 2; pg. 6, col. 1 to col. 2)	1-20
A	US 2010/0121613 A1 (Rosca et al.) 13 May 2010 (13.05.2010) entire document	1-20
A	US 2010/0025483 A1 (Hoeynck et al.) 04 February 2010 (04.02.2010) entire document	1-20

☐ Further documents are listed in the continuation of Box C.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

17 June 2012 (17.06.2012)

Date of mailing of the international search report

22 JUN 2012

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents
P.O. Box 1450, Alexandria, Virginia 22313-1450

Facsimile No. 571-273-3201

Authorized officer:

Lee W. Young

PCT Helpdesk: 571-272-4300

PCT OSP: 571-272-7774