

(43) International Publication Date
15 December 2011 (15.12.2011)(10) International Publication Number
WO 2011/155845 A1(51) International Patent Classification:
A63C 5/03 (2006.01) *A63C 5/04* (2006.01)(21) International Application Number:
PCT/NO2011/000164(22) International Filing Date:
7 June 2011 (07.06.2011)

(25) Filing Language: Norwegian

(26) Publication Language: English

(30) Priority Data:
20100817 7 June 2010 (07.06.2010) NO
20110815 6 June 2011 (06.06.2011) NO(71) Applicant (for all designated States except US): **HITURN AS** [NO/NO]; Sagvollvn. 1, N-2830 Raufoss (NO).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **KARLSEN, Jørgen** [NO/NO]; Helmerveien 5, N-1363 Høvik (NO).(74) Agents: **ONSAGERS AS** et al.; P.O.Box 6963 St. Olavs plass, N-0130 Oslo (NO).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: SNOWBOARD



(57) Abstract: The present invention is based on the combination of a snowboard with a 3- dimensional sole which wholly or partly has a tripartite sliding surface in the portion between the transition to the tip(s) and the binding fastening(s), in addition to which the board is equipped with an additional special 3 -dimensional geometry in the tip(s), in order to continue the existing uplift in the lateral sliding surface (5), thereby ensuring better uplift and thus better glide and greater speed in loose snow, a combination which provides quite unique riding characteristics. The tip of the snowboard is designed in such a manner that it presses the snow under the board more efficiently, lifting it further up from the snow than an ordinary tip. When riding straight ahead, this is best accomplished by using what is called here a skate plate, with an almost straight portion in the tip, providing an extended tip at a moderate angle to the surface and thereby extremely careful treatment of the snow while keeping the tip above the snow. When turning, an improved uplift in the tip is achieved by successively increasing the angle between the central sole surface (2) and the lateral sole surface (6) in the tip from the end of the sliding surface a few cm forwards in the tip, with the result that during edging the lateral sole surface lies substantially flatter against the snow further forward in the tip than at the transition to the tip, thereby more efficiently pressing the snow under the snowboard and not to the side, thus causing the board to also glide better during turning. Skate plate (3) is only used where the board is to be used principally on rails

[Continued on next page]

and boxes in parks, and good riding characteristics also require to be retained during normal riding on the ground. Thus the solution is to integrate a plateau (3) between the ordinary sliding surface (1) and a somewhat more modest front tip (4) on the board, the point being that when riding on snow this plateau (3) should function as a part of the nose, while during active use of the plateau on rails and boxes it has a separate function as contact surface against the surface when on other snowboards the trick in question normally involves the use of the front part of the sliding surface (1). This concept can best be employed with a certain degree of regular camber between E-E and V-V. However, it may also be envisaged used in combination with boards without camber, or even reverse camber in this area. The characteristics will be further improved by exploiting the concept of a tripartite sliding surface, with the result that the steel edges are already raised on the inside of the tip(s), thereby ensuring a gentler rate of increase in the lateral sole surfaces (6) in the tip(s) and enabling the tip to glide with less resistance, particularly during turning.

Snowboard

The present invention relates to a snowboard, consisting of a board on which two bindings are mounted on the surface of the board at a distance apart approximately corresponding to $1/3$ of the length of the board. The board is provided with inwardly curved edge portions, the board having a greater width at both ends at the transition to the tips than at its narrowest point. The board is assumed to have a sliding surface with a 3-dimensional sole where the steel edges are lifted relative to the flat sole in a very particular manner, this then being combined with tips with a very special geometry and function. The invention is based on the combination of a snowboard with a 3-dimensional sole which wholly or partly has a tripartite sliding surface in the portion between the transition to the tips and the binding fastenings, in addition to which the board is equipped with an additional particular 3-dimensional geometry in the tips, altogether providing quite unique riding characteristics.

Today's snowboards are usually designed with a flat sole surface between the tips at the two ends. For manoeuvring, the board is edged and the weight is distributed from the two bindings on the steel edges between the two transitions to the tips.

From Norwegian patent application no. 981056 a snowboard is known which has a sole divided wholly or partly into three sliding surfaces. The object of this invention is to provide the best possible dynamic when riding the board on snow. However, it is apparent from the patent that the uplift does not increase substantially into the tip, nor does it have any other specially prescribed geometry in the tip than the phase-out of the tripartite geometry which is in the sliding surface.

The present invention is based on the desire to combine the properties of a snowboard which in the sliding surface towards the transition to the tips has an increasing uplift of the steel edges relative to a plane defined in the middle of the board, where the tip is designed so as to provide extra good functionality in deep snow and on soft surfaces in general. This is achieved by designing the tip in such a manner that it presses the snow under the board more efficiently, lifting it further up from the snow than an ordinary tip. When riding straight ahead, this is best accomplished by using what is called here a skate plate, where the skate plate is like an almost straight portion in the snowboard's tip, thus providing an extended tip at a moderate angle relative to the surface and thereby extremely careful treatment of the snow while keeping the tip above the snow. When turning, an improved uplift in the tip is achieved, by increasing the angle between the central sole surface and the lateral sole surface in the tip successively from the end of the sliding surface a few cm forwards in the tip, with the result that during edging the lateral sole surface lies substantially flatter against the snow in the tip than at the transition to the tip, thereby more efficiently pressing the snow under the snowboard and not to the side,

thus causing the board to also glide better during turning. In order for this to provide the best possible effect, the upward curve in the lateral sole surface(s) will preferably be increased more rapidly in the tip than in the central sole surface.

5 A special use for the skate plate is achieved if the snowboard is to be used principally on rails and boxes in parks, but there is also a requirement to retain good riding characteristics for normal riding on the ground. The solution is therefore to integrate a plateau (skate plate) between the ordinary sliding surface (the central sole surface) and the front tip of the snowboard, the point being that when riding on snow, this plateau should function as part of the tip, while during active use of the plateau on rails and boxes and during so-called "buttering" it has a special function as contact surface against the ground when the tricks concerned normally involve use of the front part of the sliding surface.

15 This differs substantially from today's boards with reversed camber since the front portion is so clearly defined as a part of the nose when riding on snow and only acts as a part of the classic sliding surface when performing special tricks.

The skate plate is a part of a specially-designed tip which consists of a few cm in the longitudinal direction in front of the ordinary sliding surface (central sole surface) where the sole is curved slightly upwards, whereupon an approximately flat portion is provided over a certain length of the tip, with the result that the tip now turns upwards at a substantially uniform angle relative to the sliding surface, although in such a manner that the angle may be slightly varied, but it substantially provides a sole piece which is functionally approximately flat. This is followed by a short additional tip where the sole is curved upwards to that the angle to the sliding surface increases further. This almost flat portion is called a skate plate and forms a part of the tip when riding on snow, but for certain tricks it functions as a part of the ordinary sliding surface on normal snowboards.

25 This concept can best be employed with a certain degree of normal camber between a transition E and V in the snowboard. However, it may also be envisaged for use in combination with a snowboard without camber, or even reversed camber in this area.

30 The design of the tip in order to improve the riding characteristics when the board is flat, and the design of the tip in order to improve the riding characteristics when turning may be employed separately or in combination. In any case the invention assumes that these special functions in the tip are employed together with a dynamic geometrical three-dimensional design of the snowboard's sliding surface, where steel edges are given an essentially increasing uplift relative to the middle of the sliding surface, when viewed in cross section, towards the transition to the tip(s). A further improvement is thereby achieved in dynamic by employing the concept with

a specific tripartite sliding surface. The improvements according to the invention are achieved by means of a combination of two or more of the following elements:

- 5 • Behind the transition to the tip a sliding surface is employed in the area E – V as described in Norwegian patent application no. 981056 or PCT/NO2006/000014, where in principle the sliding surface is divided into three parts with a flat, central sliding surface and raised sliding surfaces with raised steel edges on each side,
- 10 • Against the steel edge of the almost flat skate plate portion, when viewed in cross section, the concept is employed with trisection of the sole surface so that the skate plate portion consists of three parts, comprising a flat and fairly wide central part, and on both sides of the central part out towards the steel edges there are raised sole surfaces giving a geometry which ensures that the steel edges are located higher than the flat skate plate portion when viewed across the board.
- 15 • Because the tip with the skate plate is first given an extremely moderate upward curve and then a flat portion, the rest of the tip may advantageously be fairly short. To avoid this resulting in problems with a tip which is too small when edging in normal snow, a tripartite sliding surface may advantageously be employed in order to ensure a better tip function, thereby causing the snow to go under the sole and avoiding the edge of the tip cutting too far down into the snow. This is achieved by letting the raised sliding surfaces (lateral sole surfaces) out towards the edges turn progressively upwards from a transition E to C, thereby raising the steel edge relative to the skate plate, at any rate to approximately the middle of the tip.
- 25 • A tip which has to press as much snow as possible under the snowboard during turning should lie as flat as possible against the snow when the board is edged, when viewed in cross section, but with an upward curve forwards as a tip viewed in the longitudinal direction. Until the angle which the lateral sole surface in the tip forms with the central sole surface is equal to the angle at which the snowboard is tilted during turning, the tip's ability to lift the snowboard out of the snow during turning increases. Since the angle at which the rider tilts the snowboard varies greatly, this places certain limits on how many degrees it is optimal to curve the raised sliding surfaces (the lateral sole surfaces) upwards.
- 30 • A tip which has to press as much snow as possible under the snowboard during turning should lie as flat as possible against the snow when the board is edged, when viewed in cross section, but with an upward curve forwards as a tip viewed in the longitudinal direction. Until the angle which the lateral sole surface in the tip forms with the central sole surface is equal to the angle at which the snowboard is tilted during turning, the tip's ability to lift the snowboard out of the snow during turning increases. Since the angle at which the rider tilts the snowboard varies greatly, this places certain limits on how many degrees it is optimal to curve the raised sliding surfaces (the lateral sole surfaces) upwards.
- 35 • The angle which the raised sliding surfaces (lateral sole surfaces) in the tip forms with the central sole surface cannot be increased too rapidly without creating too abrupt a break upwards in the tip, but this may be improved in two ways: either by combining with a skate plate in the central part of the tip

(figs. 4 and 5 show two possible examples of this), or by beginning the upward curve to the tip slightly further in towards the middle of the lateral sole surface than in the central sole surface. Figs. 9, 11 and 12 show possible examples of this, where the transitions F and U between the lateral sole surfaces 5 and 6 are located closer to the middle than the transitions E and V between the first sole surfaces 1 and 2.

- In order to optimise the tip's ability to lift the snowboard up from loose snow during turning, a wider lateral sole surface will increase this functionality. The part of the tip's sole surface, which contacts the snow at a smaller angle than the central sole surface does, increases with a wider lateral sole surface. Figs. 11, 12 and 13 show examples of wider lateral sole surfaces.

Since there is no essential difference between the front and rear of most snowboards, the board will normally be provided with the same geometry at the front and rear, but without this being an absolute requirement. This type of tip may very well be envisaged in front combined with a sliding surface at the rear which transitions to a normal rear tip without any of the said geometries, and particularly in the case of more directional snowboards this kind of asymmetry is to be expected. Nor do the lines j, k and l, m need to be placed symmetrically about the longitudinal centre line of the board, as one stands asymmetrically on the board.

For use on rails the flat skate plate portion should be as wide as possible in order to achieve maximum stability, while the lateral sole surfaces must be wide enough for the steel edge to be raised slightly from the rail, thereby preventing the steel edge from being caught in any small rough patches in the rail. Figs. 1, 3 and 7 exemplify this point.

The object of the present invention is to provide an improved snowboard specially adapted to achieve increased functionality in loose snow and on rails with a view to performing tricks, which in style and function derive their inspiration from skateboarding. A great many snowboard tricks are performed in low-lying country with a minimum of snow, which in addition is often wet and soft, with the result that lift is important. However, the improved lift described herein may also be employed in powder snow, but in this case the best variant is often to use a wider lateral sole surface than that which is considered optimal on rails and boxes. Figs. 9-13 exemplify this point. The described functionality is achieved by a snowboard which is characterised by the features which appear in the patent claims.

The present invention solves this special challenge for snowboards by means of the special design of the tip. For using the snowboard flat against the surface, it is the placing of a skate plate as an intermediate piece between the ordinary sole and an additional front tip which provides both increased lift in loose snow as well as the

extra functionality intended for use on rails and boxes. The skate plate may be considered to be a part of the tip when riding on snow, and as a functional part of the sole when performing tricks, in comparison with where corresponding tricks have their point of contact on normal snowboards, whether they have regular
5 camber or reversed camber.

The present invention will now be described in greater detail by means of embodiments which are illustrated in the drawings. The cross sections show how this functions on snow, where the design of the tips contributes towards better lift and thereby greater speed. It is easy to understand that a wider central sole surface
10 provides greater stability along or across pipes, which are a common type of rails, while it is only when sliding across the rail that a positive safety effect is obtained from the raised steel edges which thereby do not easily become caught in rough patches in the rail. The steel edges are raised because the lateral sliding surfaces and the tip's lateral sole surfaces are curved upwards relative to the central sole surface.

15 Figure 1 illustrates a snowboard according to a first embodiment of the present invention, in which

- i) illustrates the snowboard viewed from the underside, where the snowboard is provided with a skate plate,
- ii) illustrates the snowboard from the side, where uplift in steel edges is shown in a
20 somewhat exaggerated manner,
- iii) illustrates a cross section of the snowboard in different transitions, and
- iv) illustrates the angle between the tip's sole surfaces continued right up to the tip, where the snowboard is viewed from in front.

25 Figures 2-13 illustrate further details and embodiments of the snowboard according to figure 1.

Figure 1 i) illustrates the underside of a snowboard with skate plate, where the transition between the central sole surfaces 1, 2, 3 and lateral sole surfaces 5, 6 is depicted by dotted line j, k, l, m. In an area 2 (the area between transitions D and E, F) the tip is curved slightly upwards. A skate plate 3 is marked as area 3, in which
30 case the skate plate 3 extends substantially with a uniform upward gradient. The small front tip is marked by an area 4. Lateral sliding surfaces 5 are arranged along the primary sole surface 1 from transition F some distance in towards the middle of the snowboard (i.e. in towards area I). Outside the skate plate 3 secondary lateral areas 6 are arranged, and in this version we have chosen to let the width of the
35 secondary lateral areas (the lateral sole surfaces) 6 be substantially narrower than the lateral sliding surfaces 5 in order to give the skate plate 3 a larger flat area. ii) shows the snowboard viewed from the side, and under the snowboard a straight line

8 is drawn for the surface, which may be snow, a box or rails. iii) shows a cross section of the snowboard, where it will be noted that steel edges 7 in the cross sections or transitions G, E, C and T, V, X are raised relative to the central portion, while the cross sections or transitions H, I, S depict a flat sole between the steel edges 7.

Figure 2 i) illustrates the underside of a snowboard, where the raised lateral areas 5 6 are depicted with approximately constant width. There are secondary lateral areas 5 along the primary sole surface from transition H up to the tip, and correspondingly on the rear half of the board from transition S. Outside the skate plate 3 there are secondary lateral areas 6, and in this version we have chosen to let the secondary lateral areas 5, 6 form an essentially increasing angle with the central sole surfaces 1, 2, 3 all the way from transition H up to transition C, and correspondingly, but inverted on the rear half. This is best seen in the cross sections iii).

Figure 3 i) illustrates the underside of a snowboard, where the transition between the central sole surface 1, 2, 3 and the transition to the secondary lateral areas 5, 6 is depicted by dotted line j, k, l, m. Here the skate plate 3 is slightly longer than in the two preceding examples. It should also be noted that the secondary lateral area 6 is continued round the tip, thereby forming the additional tip 4 in front of the skate plate 3 in a sliding transition from lateral area 6 to front tip 4. There are secondary lateral areas 5 along the primary sole surface 1 from transition E and a distance in towards the middle of the snowboard (i.e. in towards area I). Outside the skate plate 3 secondary lateral areas 6 are arranged, and in this version we have chosen to let the width of lateral area 6 be substantially narrower than lateral area 5 in order to provide the skate plate 3 with a larger flat area. In order to illustrate that it is not necessary to have symmetry at the front and rear, the secondary areas 5 outside the sliding surface are omitted on the rear half.

Figure 4 i) illustrates the underside of a snowboard with a combination of skate plate 3 and an increasing angle from cross section or transition E to C, when viewed in cross section iii), between skate plate 3 and the tip's secondary lateral areas 6. The central sliding surface 1 extends all the way out to the steel edge 7 at transition H, where the sliding surface divides into right and left lateral sliding surface 5 on each side of the central sliding surface 1. From transition H the uplift in the steel edge 7 increases relative to the central sliding surface 1 cautiously accelerating up to transition E, wherefrom the uplift increases more rapidly up to transition C, and from transition C up to the point A the angle is adapted in order to achieve a decent rounding in the tip. The same principle is followed in the rear tip. The angles shown are somewhat exaggerated, but the intention is to demonstrate that with constant width in the lateral areas 5, 6, the angle will increase more rapidly per cm from transition E to C than from transition H to E.

Figure 5 i) illustrates the underside of a snowboard with a combination of a fairly narrow skate plate 3 and a progressively increasing angle between the central sole surfaces 1, 2, 3 and the lateral sole surfaces 5, 6 forwards in the tip from transition E to C. By progressively increasing angle we refer, for example, to the case where the angle increases from 0-3 degrees from transition H-E before increasing from transition E to C by a further 2 degrees, to 5 degrees, on the shorter distance. From transition C to A a uniform uplift is maintained in the steel edge 7 in the forward direction, as illustrated from the front in iv).

Figure 6 illustrates two different transitions between lateral area 6 and the front part of the tip 4. At transition B there is a fluent transition between the lateral area 6 and front tip 4, while on the rear part of the board transition Y defines the start of the upward curve of the rear part of the tip 4.

Figure 7 illustrates a variant with additional lateral areas 5 all the way between transition E and V. In this case moderate uplift of the secondary areas 5 will normally be employed in some areas, in order to retain sufficient edge grip. The uplift in the lateral areas 5 between the bindings is so modest here that it is not shown viewed from the side ii). Skate plate 3 may be envisaged designed here as in all the previously illustrated versions, and a random version has been chosen.

Figure 8 illustrates an embodiment with additional lateral areas 5 in front of and behind the bindings, see the transitions G and T. The sole is then flat all the way between the steel edges 7 in the area of the bindings, see the transitions H and S, in order to also have normal edge grip there when the snowboard is run flat. Towards the middle of the snowboard there is a narrow, additional lateral area 5 whose function is to raise the steel edges 7 in order to prevent them from being caught in rough patches on rails or boxes, see cross section I.

Figure 9 illustrates a snowboard according to the invention specially designed for improving lift during turning. The tips have fairly wide lateral sole surfaces 6 and there is a uniform curve upwards in the tip's central sole surface 2 without any skate plate. Viewed in cross section iii) the angle between the tip's central sole surface 2 and the tip's raised lateral sole surfaces 6 increases from the transition F forwards in the tip to approximately halfway up to the point C, and a corresponding process is illustrated in the rear tip (a snowboard of this kind may well be envisaged without any substantial rear tip, or without this functionality in the rear tip). In order to illustrate the increasing angle forwards in the tip, many cross sections are shown, which should only be regarded as examples of one of many ways of increasing the angle outwards from the transition F, U between sliding surface and tip. Left lateral sliding surface 5 is wider than right lateral sliding surface 5 in order to provide more lift on the heel side. This asymmetry is also included in the tips. The sharply increasing lift in the lateral sole surface already begins in transition F and U

respectively, even though the tip in the central area begins in transition E and V respectively. The uplift measured in mm in the steel edges 7 relative to the lines j, k increases more rapidly from transition F to C than from transition H to F.

Figure 10 illustrates a directional snowboard specially designed for improving lift during turning in loose snow. The board has extra wide lateral sole surfaces 5, 6 and a uniform curvature upwards in the tip's central sole surface 2. The transition E, F to the tip is the same between the central sole surfaces 1, 2 and the lateral sole surfaces 5, 6. The angle between the tip's central sole surface and the tip's raised lateral sole surfaces increases from the transition E, F forwards in the tip right to the edge at the front of the tip, with the result that the snowboard's edge in the tip appears with two breaks in the transition between central sole surface 2 and the lateral sole surfaces 6 viewed from in front iv). In this case the rear tip is short and benefits less from an accelerated upward curve of the lateral sole surface behind transition V, but the upward curve in transition V is kept constant backwards, with the result that the rear tip viewed from behind iv) also has two breaks in the upper edge. It is possible, however, to envisage anything from a symmetrically identical rear tip as front tip to more reduced rear tips with or without the special twisting of the lateral sole surfaces from the transition to the tip and outwards. The uplift measured in mm in the steel edges 7 relative to the lines j, k increases more rapidly from transition E to C than from transition H to E.

Figure 11 illustrates a snowboard specially designed for improving lift during turning. At the front a design of the tip is illustrated where the central sole surface 2 is reduced to a kind of keel forwards in the tip. In order to illustrate the possibilities for variation, a slightly different design is shown behind with slanting transitions and where the central sole area between transition M and L is a slightly rounded keel. The uplift measured in mm in the steel edges 7 relative to the lines increases more rapidly from transition F to C than from transition H to F.

Figure 12 illustrates a snowboard which has a central sliding surface defined by the flat portion between the bindings and the portion of the board which contacts the surface when the board is pressed against the surface so that the camber is pressed flat and central sliding surface 1 touches the ground from transition E to V. Viewed in cross section the transition between central sliding surface 1 and the secondary lateral sliding surfaces 5 is diffuse, or unclear since the transition is slow via a slight rounding of the central sliding surface 1 where there are lateral sliding surfaces 5. In such cases we define that portions located up to 0.5 mm above the ground when the longitudinal camber is depressed also belong to or are a part of the central sliding surface 1, while portions located more than 0.5 mm above the surface belong to or are a part of the lateral sliding surface 5. The lines j, k, l, m here mark the transition between the sole surfaces 1, 5 according to this definition. The slight curvature in the central sole 1 continues into the tip's central sole surface 2. The

dynamic of the snowboard is improved if the sole portions 5 closest to the steel edges are as flat as possible viewed in cross section, and therefore a cross section of the lateral sole surfaces 5 is shown here as straight for the last 2-4 cm nearest the steel edges 7, but a slight curvature does not make such a great difference from the dynamic point of view. The lift measured in mm in the steel edges 7 is measured relative to the middle of the central sliding surface 1, 2 if it is slightly curved. The up lift in the steel edges 7 increases more rapidly from transition F to C than from transition H to F. On the rear half of the snowboard the width of the central sole surface decreases successively backwards as indicated by the lines l, m. The cross sections iii) show a somewhat exaggerated curvature in order for it to be visible on a drawing how this increases from transition H to C and from transition S to X.

Fig 13 illustrates a snowboard specially designed for improving lift during turning. A design of the sliding surface is shown here where the width of the central sliding surface 1 is reduced to the point on a small break, thereby producing a splitting of the front part of the sliding surface into right and left lateral sliding surface 5 towards the transition E, F to the tip. This splitting continues in the tip, thereby providing a kind of keel forwards towards the point A. This is a directional snowboard, and therefore the same tip function is not required at the rear as at the front, in addition to which the width of the central sliding surface 1 is also almost half the board width towards the transition to the rear tip. The lift measured in mm in the steel edges 7 relative to the lines j, k increases more rapidly from transition E to C than from transition H to E.

The whole underside of a snowboard normally consists of a sole surface, which can be divided into front tip and rear tip and an intermediate sliding surface. Since the present invention assumes the use of a dynamic three-dimensional sliding surface, the sliding surface will be divided into central sliding surface 1 and lateral sliding surfaces 5. The lateral sliding surfaces transition to the tips, but are then described as lateral sole surfaces 6.

Designations in the figures:

- i. The underside, the sole of the snowboard illustrated by dotted lines in order to show smooth transitions between different portions
- ii. The snowboard viewed from the side. The uplift in the steel edge has to be slightly exaggerated here in order to make the point
- iii. Cross section of the snowboard, slightly enlarged relative to i).
- iv. On some snowboards the angle between the tip's sole surfaces is continued right up to the tip, and then the snowboard is viewed from in front in order to illustrate this variant.

1. Primary sliding surface (= central sliding surface)
 2. Area where the sole/snowboard is curved upwards forming the central sole surface in the tip, possibly only the first part of the tip if this also consists of a skate plate 3
 - 5 3. Skate plate, an almost level part of the central sole surface in the tip which always slants slightly upwards, viewed from the side.
 4. Front, upwardly curved part of the front tip or correspondingly at the rear.
 5. Lateral sliding surfaces between first sliding surface and steel edge 7
 - 10 6. Lateral sole surfaces between the tip's central sole surface 2, 3, 4 and steel edge 7
 7. Steel edges or other hard edges surrounding the snowboard's sole surfaces
 8. The surface; a pipe (= a type of rail) or a box or the ground (the snow).
- A and Z: Line marking the point on the snowboard
- 15 B. and Y: Cross section in the tip. In figures 1-8 the line marks the transition between skate plate 3 and front (rear) part of the small tip 4
- C and X: Cross section in the tip
- D and W: Cross section in the tip. In figures 1-8 the line marks the transition between skate plate 3 and the upwardly curved area 2
- 20 E and V: Cross section marking the transition between the ordinary sliding surface 1 and the tip 2
- F and U: Cross section marking the transition between the ordinary lateral sliding surface and the accelerated uplift of the lateral sole surface outwards in the tip
- 25 G and T: Cross section at a point between binding fastening and the transition to the tip
- H and S: Mark the point where the primary sliding surface extends right out to the steel edge
- I. Marks the middle of the board.

30 In all versions, the skate plate 3 is shown beginning at a line D (W) across the snowboard. There is room for variation here, since this line may also be slightly slanting without causing any substantial changes in the functionality of the skate

plate 3, with the result that a slanting transition in D is also covered by the invention. The same applies in the transition B (Y). In the same way the lines j and k need not start at the same point on the right and left sides, even though symmetry of this kind is shown here. The same applies for the lines m and l.

- 5 Four tables are now set up illustrating the snowboard according to the present invention with examples of the uplift in the steel edges 7 relative to primary sole surface 1, 2, when viewed in cross section. Uplift and geometry are deliberately varied in order to demonstrate different possibilities within the scope of the invention.

Cross

Section	A	B	C	D	F	G	H
890	248	248	248	0	0	0,00	The base is flat all the way between steel edges
900	249	249	249	0	0	0,00	
910	249	249	249	0	0	0,00	
920	250	250	250	0	0	0,00	
930	250	250	250	0	0	0,00	
940	251	251	251	0	0	0,00	
950	251	251	251	0	0	0,00	
960	252	252	252	0	0	0,00	
970	252	252	252	0	0	0,00	
980	253	253	253	0	0	0,00	
990	253	253	253	0	0	0,00	
1000	254	254	254	0	0	0,00	
1010	254	254	254	0	0	0,00	
1020	255	255	255	0	0	0,00	
1030	256	130	130	63	0,1	-0,10	Dynamically shaped secondary base surface in this area
1040	257	130	130	64	0,2	-0,10	
1050	257	130	130	64	0,3	-0,10	
1060	258	130	130	64	0,4	-0,10	
1070	259	130	130	65	0,5	-0,10	
1080	260	130	130	65	0,6	-0,10	
1090	260	130	130	65	0,7	-0,10	
1100	261	130	130	66	0,8	-0,10	
1110	262	130	130	66	1,0	-0,20	
1120	263	130	130	67	1,1	-0,10	
1130	264	130	130	67	1,2	-0,10	
1140	265	130	130	68	1,4	-0,20	Increased uplift towards transition to the tip
1150	266	130	130	68	1,5	-0,10	
1160	267	130	130	69	1,6	-0,10	
1170	268	130	130	69	1,8	-0,20	
1180	269	130	130	70	1,9	-0,10	
1190	270	130	130	70	2,1	-0,20	
1200	271	130	130	71	2,2	-0,10	
1210	272	130	130	71	2,4	-0,20	
1220	273	130	130	72	2,5	-0,10	
1230	274	130	130	72	2,7	-0,20	
1240	275	130	130	73	2,8	-0,10	
1250	276	130	130	73	2,8	0,00	Upbend radius of 330 mm
1260	277	150	150	64	2,8	0,00	
1270	278	170	170	54	2,8	0,00	
1280	279	190	190	45	2,8	0,00	
1290	280	210	210	35	2,8	0,00	Skate-plate 150 mm long
1300	281	231	231	25	2,8	0,00	
1310	281	231	231	25	2,8	0,00	
1320	282	232	232	25	2,8	0,00	
1330	282	232	232	25	2,8	0,00	
1340	282	232	232	25	2,8	0,00	
1350	282	232	232	25	2,8	0,00	
1360	282	232	232	25	2,8	0,00	
1370	282	232	232	25	2,8	0,00	
1380	281	231	231	25	2,8	0,00	
1390	279	229	229	25	2,8	0,00	
1400	276	226	226	25	2,8	0,00	Tail 80 mm long
1410	272	222	222	25	2,8	0,00	
1420	267	217	217	25	2,8	0,00	
1430	260	210	210	25	2,8	0,00	
1440	253			This special upbend of 2,8 mm follows around the tail			
1450	243						
1460	230						
1470	215						
1480	185						
1490	150						
1500	80					Upbend radius of 250 mm	

TABLE 01

Table 1 One possible example of a directional snowboard 1620 mm long according to invention

							Calculated Angle between primary and secondary sole (degrees)
Total width at E (mm)		Total width at I (mm)	Length E-I (mm)	Length I-V (mm)	Sidecut radius.		
305,0		250	660	600	7934		
Distance from the tip	Total width of the ski	Width of the primary sole (1,2) surface	Width of each of the secondary(5,6) sole surfaces	Uplift of steel edge(7) relative primary sole(1,2)	Steps of steel edge uplift	Cross section	
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		
0	0	0		0		A	
30	180	70	55	2,00			
60	240	70	85	4,50	-2,50		
90	270	70	100	7,00	-2,50		4,02
120	295	70	113	9,50	-2,50		4,85
150	302	70	116	11,00	-1,50	C	5,44
180	305	70	118	9,50	1,50	E	4,64
210	300	70	115	8,17	1,33	F	4,07
240	295	70	113	7,24	0,93		3,68
270	291	70	111	6,35	0,89		3,30
300	287	70	108	5,51	0,84		2,91
330	283	70	106	4,71	0,80		2,54
360	279	70	105	3,96	0,75	G	2,17
390	276	70	103	3,26	0,70		1,82
420	272	70	101	2,60	0,66		1,47
450	269	70	100	1,99	0,61		1,14
480	266	70	98	1,42	0,57		0,83
510	264	70	97	0,90	0,52		0,53
540	261	70	96	0,42	0,48		0,25
570	259	259	0	0	0,42	H	
600	257	257	0	0			If each part of the cross section of the ski's sole were totally straight, then the angle between the primary sole (1,2) and the secondary sole (5,6) would have these theoretical figures
630	256	256	0	0			
660	254	254	0	0			
690	253	253	0	0			
720	252	252	0	0			
750	251	251	0	0			
780	250	250	0	0			
810	250	250	0	0			
840	250	250	0	0		I	
870	250	250	0	0			
900	250	250	0	0			
930	251	251	0	0			
960	252	252	0	0			
990	253	253	0	0			
1020	254	254	0	0			
1050	256	256	0	0			
1080	257	257	0	0			
1110	259	259	0	0		S	
1140	261	90	86	0,34	-0,34		0,22
1170	264	90	87	0,72	-0,38		0,47
1200	266	90	88	1,13	-0,42		0,74
1230	269	90	90	1,59	-0,45		1,02
1260	272	90	91	2,08	-0,49		1,31
1290	276	90	93	2,61	-0,53		1,61
1320	279	90	95	3,17	-0,56	T	1,92
1350	283	90	96	3,77	-0,60		2,24
1380	287	90	98	4,41	-0,64		2,57
1410	291	90	101	5,08	-0,67		2,90
1440	295	90	103	5,79	-0,71		3,23
1470	300	90	105	6,54	-0,75	U,V	3,57
1500	300	90	105	7,50	-0,96	X	4,10
1530	290	90	100	7,00	0,50		4,02
1560	260	90	85	4,50	2,50		3,04
1590	190	90	50	2,00	2,50		2,29
1620	0	0	0	0	2,00	Z	

Table 2 One possible example of a twin tip snowboard 1590 mm long according to invention

Total width at E (mm)		Total width at I (mm)		Length E-I (mm)		Length I-V (mm)		Sidecut radius.	
310,0		258		630		630		7646	
Distance from the tip	Total width of the ski	Width of the primary sole (1,2) surface	Width of each of the secondary(5,6) sole surfaces	Uplift of steel edge(7) relative primary sole(1,2)	Steps of steel edge uplift	Cross section	Calculated Angle between primary and secondary sole (degrees)		
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)				
0	0	0		0		A			
30	180	10	85	2,00	-2,00				
60	240	20	110	4,00	-2,00				
90	270	30	120	6,00	-2,00		2,87		
120	295	40	128	8,00	-2,00		3,60		
150	305	50	128	8,50	-0,50	C	3,82		
180	310	60	125	7,50	1,00	E	3,44		
210	305	70	118	6,45	1,05	F	3,15		
240	301	80	110	5,76	0,69		3,00		
270	296	90	103	5,11	0,66		2,84		
300	292	100	96	4,49	0,62		2,68		
330	288	110	89	3,90	0,58		2,51		
360	285	120	82	3,36	0,55	G	2,34		
390	281	130	76	2,84	0,51		2,16		
420	278	140	69	2,37	0,48		1,97		
450	275	150	62	1,92	0,44		1,77		
480	272	160	56	1,52	0,41		1,55		
510	270	170	50	1,15	0,37		1,32		
540	268	180	44	0,81	0,34		1,06		
570	266	190	38	0,51	0,30				
600	264	200	32	0,25	0,26				
630	262	262	0	0	0,25	H	If each part of the cross section of the ski's sole were totally straight, then the angle between the primary sole (1,2) and the secondary sole (5,6) would have these theoretical figures		
660	261	261	0	0					
690	260	260	0	0					
720	259	259	0	0					
750	258	258	0	0					
780	258	258	0	0					
810	258	258	0	0					
840	258	258	0	0		I			
870	258	258	0	0					
900	259	259	0	0					
930	260	260	0	0					
960	261	261	0	0					
990	262	262	0	0		S			
1020	264	190	37	0,25	-0,25				
1050	266	180	43	0,51	-0,26				
1080	268	170	49	0,81	-0,30				
1110	270	160	55	1,15	-0,34				
1140	272	150	61	1,52	-0,37		1,42		
1170	275	140	67	1,92	-0,41		1,63		
1200	278	130	74	2,37	-0,44		1,83		
1230	281	120	81	2,84	-0,48	T	2,02		
1260	285	110	87	3,36	-0,51		2,21		
1290	288	100	94	3,90	-0,55		2,38		
1320	292	90	101	4,49	-0,58		2,55		
1350	296	80	108	5,11	-0,62		2,71		
1380	301	70	115	5,76	-0,66		2,87		
1410	305	60	123	6,45	-0,69		3,02		
1440	310	50	130	7,18	-0,73	U,V	3,17		
1470	305	40	133	7,20	-0,02	X	3,12		
1500	300	30	135	7,00	0,20		2,97		
1530	290	20	135	4,50	2,50		1,91		
1560	260	10	125	2,00	2,50		0,92		
1590	0	0	0	0	2,50	Z			

Table 3 One possible example of a skate plate snowboard 1530 mm long according to invention

		Total width at E (mm)	Total width at I (mm)	Length E-I (mm)	Length I-V (mm)	Sidecut radius.		
		300,0	252	615	615	7892		
Distance from the tip	Total width of the ski	Width of the primary sole (1,2) surface	Width of each of the secondary(5,6) sole surfaces	Uplift of steel edge(7) relative primary sole(1,2,3,4)	Steps of steel edge uplift	Cross section	Calculated Angle between primary and secondary sole (degrees)	
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)			
0	0	0	0	0	0,00	A		
30	180	170	5	0,31	-0,31		3,53	
60	240	170	35	2,15	-1,85	B	3,53	
90	280	170	55	3,38	-1,23		3,53	
120	295	170	63	3,85	-0,47		3,53	
150	300	170	65	4,00	-0,15	C	3,53	
180	295	170	63	3,54	0,46		3,24	
210	291	170	61	3,11	0,43		2,94	
240	287	170	58	2,70	0,41	D	2,64	
270	283	170	57	2,31	0,39		2,34	
300	279	170	55	1,94	0,37	E,F	2,04	
330	276	170	53	1,60	0,34		1,73	
360	273	170	51	1,28	0,32		1,43	
390	270	170	50	0,98	0,30	G	1,13	
420	267	170	49	0,71	0,27		0,84	
450	265	170	47	0,46	0,25		0,56	
480	262	170	46	0,23	0,23			
510	260	260	0	0	0,23	H	If each part of the cross section of the ski's sole were totally straight, then the angle between the primary sole (1,2) and the secondary sole (5,6) would have these theoretical figures	
540	258	258	0	0				
570	257	257	0	0				
600	255	255	0	0				
630	254	254	0	0				
660	253	253	0	0				
690	253	253	0	0				
720	252	252	0	0				
750	252	252	0	0		I		
780	252	252	0	0				
810	252	252	0	0				
840	253	253	0	0				
870	253	253	0	0				
900	254	254	0	0				
930	255	255	0	0				
960	257	257	0	0				
990	258	258	0	0				
1020	260	260	0	0				
1050	262	170	46	0,23	-0,23	S	0,29	
1080	265	170	47	0,46	-0,23		0,56	
1110	267	170	49	0,71	-0,25		0,84	
1140	270	170	50	0,98	-0,27	T	1,13	
1170	273	170	51	1,28	-0,30		1,43	
1200	276	170	53	1,60	-0,32		1,73	
1230	279	170	55	1,94	-0,34	U,V	2,04	
1260	283	170	57	2,31	-0,37		2,34	
1290	287	170	58	2,70	-0,39	W	2,64	
1320	291	170	61	3,11	-0,41		2,94	
1350	295	170	63	3,54	-0,43		3,24	
1380	300	170	65	4,00	-0,46	X	3,53	
1410	295	170	63	3,85	0,15		3,53	
1440	280	170	55	3,38	0,47		3,53	
1470	240	170	35	2,15	1,23	Y	3,53	
1500	180	170	5	0,31	1,85		3,53	
1530	0	0	0	0	0,31	Z		

The angle between soles 3,4 and 6 is here shown as constant from C to A, causing a double dip in the edge at the tip, as shown in fig. 5 iv.

Table 4 One possible example of a twin tip snowboard 1500 mm long according to invention

							Calculated Angle between primary and secondary sole (degrees)
Total width at E (mm)		Total width at I (mm)		Length E-I (mm)	Length I-V (mm)	Sidecut radius.	
296,0		249		600	570	7671	
Distance from the tip	Total width of the ski	Width of the primary sole (1,2) surface	Width of each of the secondary(5,6) sole surfaces	Uplift of steel edge(7) relative primary sole(1,2)	Steps of steel edge uplift	Cross section	
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		
0	0	0	0	0	0,00	A	
30	180	90	45	1,00	-1,00		1,27
60	240	120	60	2,50	-1,50		2,39
90	280	140	70	4,00	-1,50		3,28
120	291	146	73	4,85	-0,85	C	3,82
150	296	148	74	4,30	0,55	E	3,33
180	291	146	73	3,60	0,70		2,83
210	287	144	72	2,91	0,69	F	2,32
240	283	141	71	2,49	0,41		2,02
270	279	140	70	2,11	0,39		1,73
300	275	138	69	1,74	0,36		1,45
330	272	136	68	1,40	0,34	G	1,18
360	269	134	67	1,08	0,32		0,92
390	266	133	66	0,79	0,29		0,68
420	263	132	66	0,52	0,27		0,45
450	261	130	65	0,27	0,25		0,24
480	259	259	0	0	0,27	H	
510	257	257	0	0			If each part of the cross section of the ski's sole were totally straight, then the angle between the primary sole (1,2) and the secondary sole (5,6) would have these theoretical figures
540	255	255	0	0			
570	253	253	0	0			
600	252	252	0	0			
630	251	251	0	0			
660	250	250	0	0			
690	249	249	0	0			
720	249	249	0	0			
750	249	249	0	0		I	
780	249	249	0	0			
810	249	249	0	0			
840	250	250	0	0			
870	251	251	0	0			
900	252	252	0	0			
930	253	253	0	0			
960	255	255	0	0			
990	257	257	0	0			
1020	259	259	0	0			
1050	261	130	65	0,27	-0,27	S	0,24
1080	263	132	66	0,52	-0,25		0,45
1110	266	133	66	0,79	-0,27		0,68
1140	269	134	67	1,08	-0,29		0,92
1170	272	136	68	1,40	-0,32		1,18
1200	275	138	69	1,74	-0,34	Y	1,45
1230	279	140	70	2,11	-0,36		1,73
1260	283	141	71	2,49	-0,39		2,02
1290	287	144	72	2,91	-0,41	U	2,32
1320	291	146	73	3,60	-0,69		2,83
1350	296	148	74	4,30	-0,70	V	3,33
1380	291	146	73	4,85	-0,55	X	3,82
1410	280	140	70	4,00	0,85		3,28
1440	240	120	60	2,50	1,50		2,39
1470	180	90	45	1,00	1,50		1,27
1500	0	0	0	0	1,00	Z	

5 It is evident that most types of known shapes for the top of the board may be combined with this invention, which relates substantially to the geometry in the sole surfaces under the board. It may be mentioned that it might be of interest to have a flat top on the board round the bindings, thereby preventing the board's shape from being influenced by the bindings being mounted on the board. Different geometrical structures on the top of or internally in the board in order to increase or reduce stiffness and torsional rigidity may be adapted to suit the described geometry in the sole.

10 All the models illustrated here are reasonably symmetrical about a centre line drawn along the snowboard. Since a snowboard rider does not stand symmetrically on the board relative to this line, there is no reason to suppose that the ideal snowboard is symmetrical about this line. The functionality in the invention does not depend on such symmetry, with the result that the invention may equally well be implemented with considerable differences between the board's right and left sides.

15

CLAIMS

1. A snowboard comprising a board for mounting two bindings on the board's surface at a distance apart approximately corresponding to approximately 1/3 of the board's length, where the board is provided with inwardly curved edge portions, the board having greater width at both ends at the transition (E, V) to the tips than at the middle (I), characterised in that in the tip a skate plate (3) is inserted, which during normal running on snow functions as a part of the tip, but which when performing certain tricks functions as a part of a central sliding surface (1), where the skate plate (3) starts a few cm in front of the ordinary sliding surface (1), and where in an area (C) between the beginning of the skate plate (3) and the end of the ordinary sliding surface (D) there is a shorter area (2) where the sole surface (1) is curved upwards, where the skate plate (3) relative to the ordinary sole surface (1) has an approximately straight form so that the skate plate's (3) angle to the surface is essentially constantly rising over the skate plate (3), where the area (B) in front of the skate plate (3) is curved further upwards in a front tip (4), with the result that the sole in the front tip (4) creates an increasing angle with the surface again, viewed in the snowboard's longitudinal direction.
2. A snowboard according to claim 1, characterised in that skate plate (3) is used on the rear half of the snowboard according to the same principles as the front part, even though the design need not be identical.
3. A snowboard according to one of the preceding claims, characterised in that the skate plate (3) is at least 4 cm long between transition (B, D), preferably over 8 cm and most preferred over 12 cm long.
4. A snowboard according to one of the preceding claims, characterised in that the sliding surface of the snowboard has a three-dimensional sliding surface which means that the lateral sliding surfaces (5) and thereby also the steel edges towards the transition (E) to the tip have an increasing uplift relative to a plane defined by the central part of the sliding surface (1) when it is pressed down against the ground, i.e. when the snowboard is lying flat and without camber, and then this geometry in the sliding surface (1, 5) is combined with a design of the tip(s) where the tip(s) has lateral sole surfaces (6) which viewed in cross section gives steel edges (7) which are raised relative to the middle portion (2) of the tip and far advanced forward in the tip(s).

5. A snowboard according to the preceding claim,
characterised in that the sliding surface of the snowboard has a three-
dimensional sliding surface which is substantially tripartite, with a right
lateral sliding surface (5), a central sliding surface (1) and a left sliding
surface (5) towards the transition to the tips over a length which
altogether at both the ends of the board forms at least 10% of the sliding
surface's total length.
6. A snowboard according to one of the preceding claims,
characterised in that the steel edges (7), viewed in cross section, create an
increasing uplift relative to the central sole surface (1, 2 and possibly 3)
from the transition F between the secondary sliding surface (5) and the
tip's secondary sole surface (6) to a cross line C located in front of F,
where the uplift in C, measured in mm, is at least 25% greater than in F,
preferably at least 35% and most preferred at least 50%.
7. A snowboard according to one of the preceding claims,
characterised in that the steel edges (7), viewed in cross section, create an
increasing uplift relative to the central sole surface (1, 2 and possibly 3)
from the transition E between central sliding surface (1) and the tip's
central sole surface (2) to a cross line C located in front of E, where the
uplift in C, measured in mm, is at least 10% greater than in E, preferably
at least 15% and most preferred at least 20%.
8. A snowboard according to one of the preceding claims,
characterised in that the steel edges (7), viewed in cross section, create an
increasing uplift relative to the central sole surface (1, 2 and possibly 3)
from the transition between sliding surface and tip and a few cm
outwards in the tip, with the result that the uplift increases at least 1% of
the lateral sole surface's (6) width, and preferably more than 2% from the
transition (F) until maximum uplift in the steel edge is achieved in C.
9. A snowboard according to one of the preceding claims,
characterised in that the tips' lateral surfaces (6) start further in towards
the board's bindings than the transition between the central sliding
surface (1) and the tip's central sole surface (2) does in F and possibly U,
so that the accelerated upward curve in the steel edge already starts a few
cm earlier than the upward curve to the tip from the central sliding
surface in E and possibly in V.
10. A snowboard according to one of the preceding claims,
characterised in that a skate plate (3) is inserted in the tip(s), starting a
few cm in front of the ordinary sliding surface (1), and between the
beginning of skate plate (D) and the end of the ordinary sliding surface

- 5 (E) there is a shorter area (2) where the sole surface is curved upwards, while skate plate (3) has an approximately straight form relative to the ordinary sliding surface with the result that the angle of the tip with the surface is fairly constant in the skate plate. In front of the skate plate the tips are curved further upwards in a front tip (4), with the result that the sole in the front tip forms an increasing angle with the surface again, viewed in the board's longitudinal direction.
- 10 11. A snowboard according to one of the preceding claims, characterised in that the skate plate (3) is at least 4 cm long between B and D, preferably over 8 cm and most preferred over 12 cm long.
- 15 12. A snowboard according to one of the preceding claims, characterised in that the area between D and E where the board is curved upwardly between the sliding surface (1) and skate plate (3) is a maximum of 15 cm long, preferably shorter than 10 cm long, and most preferred shorter than 5 cm long.
- 20 13. A snowboard according to one of the preceding claims, characterised in that skate plate (3) forms a mean angle of maximum 12 degrees with the sliding surface, preferably under 9 degrees and most preferred less than 6 degrees and more than 3 degrees.
- 25 14. A snowboard according to one of the preceding claims, characterised in that the transition (D) to skate plate (3) starts at least 10 cm in front of the normal position of the bindings, preferably at least 15 cm and most preferred at least 20 cm, and in a corresponding fashion behind the rear binding.
- 30 15. A snowboard according to one of the preceding claims, characterised in that between the transitions to front tip E and rear tip V the snowboard is provided with additional sliding surfaces where the steel edges in the lateral sliding surfaces (5) are located higher above the central sliding surface (1) at E and possibly at V than in the middle I.
- 35 16. A snowboard according to one of the preceding claims, characterised in that some of the transitions (B, C, D, E, F) between the different areas of the snowboard are not perpendicular to the board's longitudinal direction, nor are they located symmetrically about the longitudinal axis.
17. A snowboard according to one of the preceding claims, characterised in that it is only the front tip which has a special design, and an ordinary rear tip is employed, or even a small or no rear tip.

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12





Fig. 13



INTERNATIONAL SEARCH REPORT

International application No.
PCT/NO2011/000164

A. CLASSIFICATION OF SUBJECT MATTER

IPC: see extra sheet

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC: A63C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE, DK, FI, NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, PAJ, WPI data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 2082787 A1 (ROSSIGNOL SA), 29 July 2009 (2009-07-29); abstract; figures 1, 3 --	1-17
A	US 20090256333 A1 (CANADAY TIM ET AL), 15 October 2009 (2009-10-15); abstract; figure 13B --	1-17
A	EP 1864696 A1 (SALOMON SA), 12 December 2007 (2007-12-12); abstract; figures 5, 6 --	1-17
A	WO 2007094690 A2 (HITURN AS ET AL), 23 August 2007 (2007-08-23); abstract; figure 1A -- -----	1-17



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

“A” document defining the general state of the art which is not considered to be of particular relevance

“E” earlier application or patent but published on or after the international filing date

“L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

“O” document referring to an oral disclosure, use, exhibition or other means

“P” document published prior to the international filing date but later than the priority date claimed

“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

“X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

“Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

“&” document member of the same patent family

Date of the actual completion of the international search

12-09-2011

Date of mailing of the international search report

29-09-2011

Name and mailing address of the ISA/SE

Patent- och registreringsverket
Box 5055
S-102 42 STOCKHOLM
Facsimile No. + 46 8 666 02 86

Authorized officer

Björn Lindkvist

Telephone No. + 46 8 782 25 00

Continuation of: second sheet

International Patent Classification (IPC)

A63C 5/03 (2006.01)

A63C 5/04 (2006.01)

Download your patent documents at www.prv.se

The cited patent documents can be downloaded:

- From "Cited documents" found under our online services at www.prv.se
(English version)
- From "Anförda dokument" found under "e-tjänster" at www.prv.se
(Swedish version)

Use the application number as username. The password is **DHZOBPRIUF**.

Paper copies can be ordered at a cost of 50 SEK per copy from PRV InterPat (telephone number 08-782 28 85).

Cited literature, if any, will be enclosed in paper form.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/NO2011/000164

EP	2082787 A1	29/07/2009	FR	2926734 A1	31/07/2009
US	20090256333 A1	15/10/2009	US	20110001306 A1	06/01/2011
			US	7798514 B2	21/09/2010
EP	1864696 A1	12/12/2007	FR	2902022 B1	29/08/2008
WO	2007094690 A2	23/08/2007	AT	505588 A2	15/02/2009
			DE	112007000387 T5	02/01/2009
			US	20090273162 A1	05/11/2009