

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 683 100 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
06.08.1997 Bulletin 1997/32

(51) Int. Cl.⁶: **B65C 9/04**, B65C 1/04

(21) Application number: **95201092.4**

(22) Date of filing: **27.04.1995**

(54) Method and device for applying a banderole to shaped cheeses

Verfahren und Vorrichtung zum Banderolieren von Käsen besonderer Form

Procédé et dispositif pour appliquer une banderole sur un fromage de forme particulière

(84) Designated Contracting States:
BE CH DE DK ES FR GB GR IT LI NL

(72) Inventor: **Derksen, Gerrit Pieter**
NL-6663 BB Lent (NL)

(30) Priority: **29.04.1994 NL 9400703**

(74) Representative: **Barendregt, Frank, Drs.**
van Exter Polak & Charlouis B.V.,
P.O. Box 3241
2280 GE Rijswijk (NL)

(43) Date of publication of application:
22.11.1995 Bulletin 1995/47

(73) Proprietor: **Machinefabriek Ledoux B.V.**
NL-6669 CB Dodewaard (NL)

(56) References cited:
EP-A- 0 132 862 **NL-A- 8 900 177**
US-A- 4 162 182

EP 0 683 100 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

The invention relates to a method and device for affixing a banderole to the periphery of a rotating, shaped cheese.

Such a method and device are known from, for example, NL-A-8900177. In the case of this known method a cheese standing on its side, and laterally centred, is rotated by moving supporting rollers. During the rotation of the cheese an adhesive is applied to the periphery of the cheese on the top side thereof, and the front end of a banderole strip to be affixed thereto is subsequently fed close to the periphery of the cheese, so that it is moved along by the cheese. Through further rotation thereof, the cheese pulls the next part of the strip along around the periphery of the cheese. The material strip which has been affixed is pressed onto the cheese by the moving supporting rollers.

A disadvantage of this method is that it can be used only for applying a banderole to round cheeses of constant diameter. A banderole cannot be applied in this way to other non-round cheeses. In fact, until now there have been no known methods for applying a banderole to non-round cheeses, in particular polygonal cheeses such as square, rectangular or hexagonal cheeses. Another disadvantage of the known method is that this method is difficult to use in existing production lines for the preparation of shaped cheeses, because cheeses are generally conveyed horizontally in such lines. In that case the cheeses therefore have to be positioned vertically prior to applying the banderole. After applying the banderole, the cheeses also have to be repositioned for conveyance to subsequent processing steps. These additional operations involve a considerable risk of damage to the banderole which has been affixed and to the plastic coat of the cheese, because the surface of the cheese and the moist banderole strip are not sufficiently strong to withstand great stresses. Damage to the surface of the cheese can lead to mould formation. Damage to the banderole strip which has been affixed can likewise lead to mould formation, and it also adversely affects the appearance of the cheeses.

The object of the invention is to avoid the above-described problems and to provide a method for applying a banderole which can be used for any shape of cheese, in particular in the case of polygonal cheeses.

A further object of the invention is to provide a method in which banderole strips are affixed with great accuracy and at high speed to cheeses supplied in succession.

The method of the above-described type according to the invention is characterized in that the banderole is affixed while maintaining an essentially constant peripheral speed of the cheese at its momentary position beside a banderole strip applicator, by determining the peripheral speed of the cheese at a point along the periphery of the cheese and regulating the speed of rotation of the cheese on the basis thereof.

Maintaining a virtually constant peripheral speed of

the momentary position of the cheese, i.e. the peripheral speed of the peripheral part situated at that moment beside the banderole strip to be affixed, relative to the speed of the likewise advancing banderole strip ensures uniform affixing of the banderole strip to the periphery of the shaped cheese. This means that when the banderole strip is being affixed to the peripheral part of the cheese there will be no additional stresses on the strip, owing to the small differences in speed, with the result that tearing of the banderole strip and wrinkling of the banderole strip affixed to the cheese are prevented.

Maintaining a constant peripheral speed relative to the supply speed of the banding strip is achieved by continuously adapting the peripheral speed to a generally constant supply speed of the banderole strip. The angular speed of the cheese can be set to the desired value through feedback of the measured peripheral speed to the desired peripheral speed of the momentary position of the cheese. It is simpler to adjust the speed of rotation of the cheese than the supply speed of the banderole strip, because the material of the latter is not strong enough for great forces to be exerted thereon.

The banderole strip is preferably affixed by supplying the banderole strip essentially at a tangent to the momentary position of the cheese. In this way the banderole strip is affixed to the periphery of the cheese correctly and uniformly, while undesirable stresses on the banderole strip are avoided.

The method according to the invention can be carried out with any cheese shape. It is particularly advantageous to use the method for cheeses of a polygonal shape. Examples of such cheeses are triangular, square, rectangular, hexagonal and octagonal cheeses. However, elliptical or irregularly shaped cheeses can also be banded by the method according to the invention.

The invention also relates to a device for affixing a banderole to the periphery of rotating, shaped cheeses, which device comprises a frame in which conveyor means for conveying the cheeses, and rotary means for rotating the cheeses and a strip applicator for affixing a banderole strip to the periphery of the rotating cheeses are disposed, which is characterized in that the device is provided with detection means for determining the peripheral speed of the cheese and a control unit interacting therewith, which adjust the speed of rotation of the rotation means in such a way that the peripheral speed of the cheese at its momentary position beside the strip applicator is kept constant.

In the case of the device according to the invention the detection means determine the peripheral speed of the cheese. On the basis of the measured peripheral speed of the cheese, a control unit interacting therewith sets the speed of rotation of the rotation means at a desired value, so that the peripheral speed of the momentary position of the cheese relative to the strip applicator is kept constant.

Detection means for determining the peripheral speed are generally known. A sensor is a suitable detection means for this purpose.

The rotation means advantageously comprise a rotary table which is adjustable in height, and drive elements interacting therewith which are controlled by the control unit. Such a table is easily incorporated in existing production lines. After a cheese has been received on the table from a supply belt, the table is raised, so that the periphery of the cheese moves into the vicinity of the strip applicator, following which the application of the banderole can be carried out.

The rotary table is advantageously also provided with a freely rotatable retaining element for positioning the cheese on the table, in order to prevent the force exerted by the banderole strip on the cheese from interfering with the peripheral speed of the cheese.

The strip applicator can be of a type which is known per se. The strip applicator advantageously comprises a mobile blow nozzle disposed along the periphery of a cheese to be banded. With such a blow nozzle the banderole strip can be affixed uniformly and correctly positioned on the periphery of the cheese.

In a preferred embodiment of the device a mobile pressure element is present, which element is disposed downstream of the strip applicator, viewed in the direction of rotation of the cheese. The mobile pressure element is capable of following the shape of the cheese, and thus pressing the banderole strip onto the cheese. This can be achieved by, for example, a spring mechanism.

In a further preferred embodiment of the device according to the invention, a metering element for moistening the cheese is present, which element is disposed upstream of the strip applicator, viewed in the direction of rotation of the cheese. Moistening of the cheese will cause the plastic coat of the cheese to soften slightly, with the result that it acquires adhesive properties. These properties are sufficient to fix the banderole strip to the surface of the cheese. Of course, it is also possible to provide an adhesive on the banderole strip to be affixed, which provides the adhesive action.

The device will generally also comprise a cutting element for cutting the banderole strip affixed to the cheese. The banderole strip can be severed by moving the strip applicator past the cutting element, for example a severing knife, after the banding strip has been affixed to the cheese.

The invention also relates to a device for preparing shaped cheeses, which device is provided with a device for affixing a banderole according to the invention.

The invention will be explained in greater detail below with reference to the appended drawing, in which the sole figure is a top view of an embodiment of a banding device according to the invention.

In this figure reference number 1 indicates a stock roll of a banderole, which is disposed on a driven mandrel 2. The banderole material can be selected from the usual materials used for this purpose, such as tissue

paper and teabag paper or plastic, which can be printed with, for example, information on the origin, type and quality. A banderole strip 3 unwound from this stock roll is guided by way of a pressure roll 4 and a supply roll 5 at constant speed to a blow nozzle 6. The supply roll 5 is electronically controlled, so that the length of overlap of the material strip 3 can be set. By means of the blow nozzle 6, the banderole strip 3 is pressed at a tangent to the peripheral part against a square cheese 7. The blow nozzle 6 is disposed in such a way that it can be moved past a severing knife 8, for severing the material strip 3. Reference number 9 indicates a spray head for moistening the cheese 7. The moisture to be applied to the cheese may be tap water, to which an adhesive has been added if desired. An example of a solution which can be used is a starch emulsion. A pressure roll 10 ensures that the banderole strip 3 affixed to a cheese 7 is pressed down. Said pressure roll 10 can make such a movement that the pressure roll 10 always follows the shapes of cheeses 7, and consequently presses the banderole strip 3 correctly onto the cheese 7. A rotary table 11, which is adjustable in height and is provided with a special speed regulator and drive elements (neither shown), is controlled by detection means 12 for measuring the peripheral speed of the cheese 7, so that the peripheral speed of the momentary position of the cheese 7 remains constant relative to the blow nozzle 6 (and consequently also relative to the banderole strip 3 supplied at constant speed). The table 11 also keeps the cheese 7 at a uniform height relative to the blow nozzle 6. The cheese 7 is positioned on the table 11 by means of a freely rotatable retaining element 13. After applying the banderole, the cheeses 7 are conveyed further by means of a discharge belt 14 to working stations situated downstream.

Instead of a banderole strip unwound from a stock roll, as represented in the drawing, banderole strips having a fixed length can be fed to the strip applicator. In such a case the cutting element can be omitted.

The above-described method and device for applying a banderole are particularly advantageous for affixing a banderole to polygonal cheeses, such as square or rectangular cheeses or cheese products of these shapes.

The device can be set up in a fixed position, but can also be a mobile type. This means that the banding device according to the invention can be used at several places in the preparation process of cheeses. Not only decorative banderoles, but also supporting sleeves can be affixed to the shaped cheese by means of the method and device according to the invention.

Claims

1. Method for affixing a banderole to the periphery of a rotating, shaped cheese, **characterized in that** the banderole (3) is affixed while maintaining an essentially constant peripheral speed of the cheese at its momentary position beside a banderole strip

- (3) applicator (6), by determining the peripheral speed of the cheese (7) at a point along the periphery of the cheese (7) and regulating the speed of rotation of the cheese (7) on the basis thereof.
2. Method according to claim 1, **characterized in that** the banderole strip (3) is affixed by supplying the banderole strip (3) essentially at a tangent to the momentary position of the cheese (7).
3. Method according to claim 1 or 2, **characterized in that** the cheeses (7) are polygonal in shape.
4. Method according to claim 1 or 2, **characterized in that** the cheeses (7) are elliptical in shape.
5. Banding device for affixing a banderole to the periphery of rotating, shaped cheeses (7), which device comprises a frame in which conveyor means (14) for conveying the cheeses (7), and rotary means (11) for rotating the cheeses (7) and a strip applicator (6) for affixing a banderole strip (3) to the periphery of the rotating cheeses (7) are disposed, **characterized in that** the device is provided with detection means (12) for determining the peripheral speed of the cheese (7) and a control unit interacting therewith, which adjust the speed of rotation of the rotation means (11) in such a way that the peripheral speed of the cheese at its momentary position beside the strip applicator (6) is kept constant.
6. Banding device according to claim 5, **characterized in that** the rotation means comprise a rotary table (11) which is adjustable in height, and drive elements interacting therewith which are controlled by the control unit.
7. Banding device according to claim 6, **characterized in that** the table (11) is also provided with a freely rotatable retaining element (13) for positioning the cheese (7) on the table (11).
8. Banding device according to one of claims 5 - 7, **characterized in that** the strip applicator comprises a mobile blow nozzle (6) disposed along the periphery of cheese (7) to be banded.
9. Banding device according to one of claims 5 - 8, **characterized in that** a mobile pressure element (10) is present, which element is disposed downstream of the strip applicator (6), viewed in the direction of rotation of the cheese (7).
10. Banding device according to one of claims 5 - 9, **characterized in that** a metering element (9) for moistening the cheese (7) is present, which element is disposed upstream of the strip applicator (6), viewed in the direction of rotation of the cheese

(7).

11. Banding device according to one of claims 5 - 10, **characterized in that** the device also comprises a cutting element (8) for severing the banderole strip (3) affixed to the cheese (7).
12. Device for preparing shaped cheeses, which device is provided with a device for affixing a banderole according to one of claims 5 - 11.

Patentansprüche

1. Verfahren zum Anbringen einer Banderole auf dem Umfang eines sich drehenden Formkäses, dadurch gekennzeichnet, daß die Banderole (3) befestigt wird, während eine im wesentlichen konstanten Umfangsgeschwindigkeit des Käses an seiner momentanen Position an einer Anbringvorrichtung (6) für Banderolenstreifen (3) aufrechterhalten wird, indem die Umfangsgeschwindigkeit des Käses (7) an einem Punkt längs des Umfangs des Käses (7) bestimmt wird und die Umdrehungsgeschwindigkeit des Käses (7) auf dieser Basis geregelt wird.
2. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß der Banderolenstreifen (3) angebracht wird durch Anlegen des Banderolenstreifens (3) im wesentlichen in einer Tangente zur momentanen Position des Käses (7).
3. Verfahren nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß der Käse (7) eine polygonale Form hat.
4. Verfahren nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß der Käse (7) eine elliptische Form hat.
5. Banderoliervorrichtung zum Anbringen einer Banderole am Umfang eines sich drehenden Formkäses (7), welche Vorrichtung ein Gestell aufweist, in welchem eine Fördervorrichtung (14) zur Beförderung des Käses (7), eine Drehvorrichtung (11) zum Drehen des Käses (7) und eine Anbringvorrichtung (6) zum Anbringen eines Banderolenstreifens (3) am Umfang des sich drehenden Käses (7) angeordnet sind, dadurch gekennzeichnet, daß eine Detektionsvorrichtung (12) vorgesehen ist, zur Bestimmung der Umfangsgeschwindigkeit des Käses (7), und eine damit zusammenwirkende Steuerung vorgesehen ist, welche die Umdrehungsgeschwindigkeit der Drehvorrichtung (11) regelt derart, daß die Umfangsgeschwindigkeit des Käses in seiner momentanen Position an der Anbringvorrichtung (6) konstant ist.

6. Banderoliervorrichtung nach Anspruch 5, dadurch gekennzeichnet, daß die Drehvorrichtung einen drehbaren Tisch (11) aufweist, welcher in seiner Höhe einstellbar ist, und damit zusammenwirkende Antriebselemente aufweist, welche durch die Steuerung eingestellt werden. 5
7. Banderoliervorrichtung nach Anspruch 6, dadurch gekennzeichnet, daß der Tisch (11) mit einem frei drehbaren Halteelement (13) zum Positionieren des Käses (7) auf dem Tisch (11) versehen ist. 10
8. Banderoliervorrichtung nach einem der Ansprüche 5 bis 7, dadurch gekennzeichnet, daß die Streifen-Anbringvorrichtung eine bewegliche Blasdüse (6) aufweist, welche längs des Umfangs des zu banderolierenden Käses (7) angeordnet ist. 15 20
9. Banderoliervorrichtung nach einem der Ansprüche 5 bis 8, dadurch gekennzeichnet, daß ein bewegliches Andrückelement (10) vorhanden ist, welches in Drehrichtung des Käses (7) gesehen flußabwärts zur Streifen-Anbringvorrichtung (6) angeordnet ist. 25 30
10. Banderoliervorrichtung nach einem der Ansprüche 5 bis 9, dadurch gekennzeichnet, daß ein Dosierelement (9) zur Befeuchtung des Käses (7) vorhanden ist, welches in Drehrichtung des Käses (7) gesehen flußaufwärts zur Streifen-Anbringvorrichtung (6) angeordnet ist. 35
11. Banderoliervorrichtung nach einem der Ansprüche 5 bis 10, dadurch gekennzeichnet, daß die Vorrichtung auch ein Schneidelement (8) aufweist, zum Abtrennen des am Käse (7) angebrachten Banderolenstreifens (3). 40
12. Vorrichtung zur Herstellung eines Formkäses, bei welcher eine Vorrichtung zur Anbringung einer Banderole nach einem der Ansprüche 5 bis 11 vorgesehen ist. 45 50

Revendications

1. Procédé pour appliquer une banderole sur la périphérie d'un fromage de forme particulière, en rotation, caractérisé en ce que la banderole (3) est appliquée tout en maintenant une vitesse périphérique essentiellement constante du fromage au niveau de sa position momentanée par rapport à un applicateur (6) de bande de banderole (3), en

déterminant la vitesse périphérique du fromage (7) au niveau d'un point le long de la périphérie du fromage (7) et en réglant la vitesse de rotation du fromage (7) en se basant sur celle-ci.

2. Procédé selon la revendication 1, caractérisé en ce que la bande de banderole (3) est appliquée en délivrant la bande de banderole (3) dans une direction essentiellement tangentielle à la position momentanée du fromage (7).
3. Procédé selon la revendication 1 ou 2, caractérisé en ce que les fromages (7) sont de forme polygonale.
4. Procédé selon la revendication 1 ou 2, caractérisé en ce que les fromages (7) sont de forme elliptique.
5. Dispositif de cerclage pour appliquer une banderole sur la périphérie de fromages (7) de forme particulière, en rotation, lequel dispositif comprend un cadre dans lequel sont disposés des moyens de transport (14) pour transporter les fromages (7), des moyens de rotation (11) pour faire tourner les fromages (7) et un applicateur de bande (6) pour appliquer une bande de banderole (3) sur la périphérie des fromages en rotation (7), caractérisé en ce que le dispositif est pourvu de moyens de détection (12) permettant de déterminer la vitesse périphérique du fromage (7) et d'une unité de commande en interaction avec ceux-ci, qui règlent la vitesse de rotation des moyens de rotation (11) de telle manière que la vitesse périphérique du fromage au niveau de sa position momentanée par rapport à l'applicateur de bande (6) soit maintenue constante.
6. Dispositif de cerclage selon la revendication 5, caractérisé en ce que les moyens de rotation comprennent une table rotative (11) réglable en hauteur, et des éléments d'entraînement en interaction avec celle-ci qui sont commandés par l'unité de commande.
7. Dispositif de cerclage selon la revendication 6, caractérisé en ce que la table (11) est également pourvue d'un élément de retenue librement rotatif (13) destiné à positionner le fromage (7) sur la table (11).
8. Dispositif de cerclage selon l'une quelconque des revendications 5 à 7, caractérisé en ce que l'applicateur de bande comprend une buse de soufflage mobile (6) disposée le long de la périphérie d'un fromage (7) à cercler.
9. Dispositif de cerclage selon l'une quelconque des revendications 5 à 8, caractérisé en ce qu'un élément de pression mobile (10) est présent, lequel

élément est disposé en aval de l'applicateur de bande (6), vu dans la direction de rotation du fromage (7).

10. Dispositif de cerclage selon l'une quelconque des revendications 5 à 9, caractérisé en ce qu'un élément de dosage (9) destiné à humidifier le fromage (7) est présent, lequel élément est disposé en amont de l'applicateur de bande (6), vu dans la direction de rotation du fromage (7). 5 10
11. Dispositif de cerclage selon l'une quelconque des revendications 5 à 10, caractérisé en ce que le dispositif comprend également un élément de coupe (8) destiné à couper la bande de banderole (3) appliquée au fromage (7). 15
12. Dispositif de préparation de fromages de forme particulière, lequel dispositif est pourvu d'un dispositif destiné à appliquer une banderole selon l'une quelconque des revendications 5 à 11. 20

25

30

35

40

45

50

55

