



(22) Date de dépôt/Filing Date: 2004/03/30

(41) Mise à la disp. pub./Open to Public Insp.: 2004/10/01

(30) Priorité/Priority: 2003/04/01 (10/404,708) US

(51) Cl.Int.⁷/Int.Cl.⁷ H04N 9/64, H04N 9/73


(71) Demandeur/Applicant:
AVID TECHNOLOGY, INC., US

(72) Inventeur/Inventor:
GONSALVES, ROBERT, US

(74) Agent: SMART & BIGGAR

(54) Titre : CORRECTION AUTOMATIQUE DE COULEUR POUR DES SEQUENCES D'IMAGES

(54) Title: AUTOMATIC COLOR CORRECTION FOR SEQUENCES OF IMAGES



(57) **Abrégé/Abstract:**

Automatic color correction is applied to a scene or clip, including a sequence of images, in a motion picture by selecting a representative image of the scene, analyzing the image and adjusting parameters of a color correction operation that is performed on the sequence of images included in the scene. This operation can be repeated automatically for all scenes or for selected scenes in the motion picture. The parameters may be adjusted to automatically color balance the image while maintaining substantially constant contrast. Analysis of the representative image may include identifying an offset of a peak in a two-dimensional histogram of the colors in the representative image from a white point. Parameters of a color correction operation are adjusted according to this offset. Separate histograms and offsets may be determined for shadows, midtones and highlight regions of the representative image. Analysis of the representative image may include determining a one-dimensional histogram of the luminance information in the representative image. The darkest level and the brightest level in the image are used to balance the image. In particular, the histograms for color channels in the image, such as red, green and blue, are adjusted to match the darkest level and brightest level identified by the luminance histogram.



77787-78

ABSTRACT

Automatic color correction is applied to a scene or clip, including a sequence of images, in a motion picture by selecting a representative image of the scene, analyzing the image and adjusting parameters of a color correction operation that is performed on the sequence of images included in the scene. This operation can be repeated automatically for all scenes or for selected scenes in the motion picture. The parameters may be adjusted to automatically color balance the image while maintaining substantially constant contrast. Analysis of the representative image may include identifying an offset of a peak in a two-dimensional histogram of the colors in the representative image from a white point. Parameters of a color correction operation are adjusted according to this offset. Separate histograms and offsets may be determined for shadows, midtones and highlight regions of the representative image. Analysis of the representative image may include determining a one-dimensional histogram of the luminance information in the representative image. The darkest level and the brightest level in the image are used to balance the image. In particular, the histograms for color channels in the image, such as red, green and blue, are adjusted to match the darkest level and brightest level identified by the luminance histogram.

77787-78

AUTOMATIC COLOR CORRECTION FOR SEQUENCES OF IMAGES

BACKGROUND

Images that are captured using a camera generally have several kinds of color problems. For example, if the camera is not properly white balanced, images tend to have a red or blue cast. If there is insufficient lighting in the scene, images tend to be dark and show little contrast. Also, if light reflects off objects in the scene, other objects tend to have a color cast associated with the reflected light.

These and other color problems commonly are fixed using color correction tools on a computer workstation. These tools allow a user to select one or more image processing functions to apply to an image and to adjust parameters of these functions. Currently available color correction tools are powerful, but tend to have a steep learning curve.

To reduce the learning curve and the time required to manipulate the image processing functions, there are some automatic tools for color correction. Such tools analyze an image and adjust parameters of a color correction operation to improve the color in the image. An example of such a tool is the PHOTOSHOP software from Adobe Systems Incorporated of Menlo Park, California. An example kind of function that may be provided is automatic color balancing. Using automatic color balancing, a histogram of the red, blue and green channels is created. The histogram is then stretched so that it matches the end points of the range of values for each channel or the minimum and maximum values from among the red, green and blue channels. Such automatic

77787-78

color balancing generally also improves the contrast of the image, which is generally desirable.

However, color correction for video, which is a sequence of images, is more complicated. Although it may be possible to analyze and correct separately every image in a sequence of images, such analysis and correction would consume significant processing resources. On the other hand, it may be undesirable to apply contrast modifications developed by analysis of one image to other images. A change in contrast in one image may not be appropriate to apply to another image. Also, the change in contrast to the other image may negatively impact its quality.

SUMMARY

Automatic color correction is applied to a scene or clip, including a sequence of images, in a motion picture by selecting a representative image of the scene, analyzing the image and adjusting parameters of a color correction operation that is performed on the sequence of images included in the scene. This operation can be repeated automatically for all scenes or for selected scenes in the motion picture. The parameters may be adjusted to automatically color balance the image while maintaining substantially constant contrast.

Analysis of the representative image may include identifying an offset of a peak in a two-dimensional histogram of the colors in the representative image from a white point. Parameters of a color correction operation are adjusted according to this offset. Separate histograms and offsets may be determined for shadows, midtones and highlight regions of the representative image.

77787-78

Analysis of the representative image may include determining a one dimensional histogram of the luminance information in the representative image. The darkest level and the brightest level in the image are used to balance the
5 image. In particular, the histograms for color channels in the image, such as red, green and blue, are adjusted to match the darkest level and brightest level identified by the luminance histogram.

Accordingly, in one aspect, a method, computer
10 program product and system are provided for automatic color correction of a sequence of images. An indication of one or more representative images in the sequence of images is received. Characteristics of the one or more representative images are analyzed. Parameters for a color correction
15 operation are determined according to the analyzed characteristics of the one or more representative images. The color correction operation is applied with the determined parameters to the sequence of images.

In another aspect, a method, computer program
20 product and system are provided for analyzing characteristics of one or more representative images from a sequence of images. A two-dimensional histogram of colors in the representative image is generated, wherein the two-dimensions include a white point. An offset between a peak
25 value in the two-dimensional histogram and the white point is determined.

In another aspect, a method, computer program product and system are provided for analyzing characteristics of one or more representative images from a
30 sequence of images. A histogram of luminance in the representative image is generated, whereby the histogram

77787-78

indicates a darkest value and a brightest value.

Adjustments to histograms of colors in the representative image are determined so as to match a darkest value and a brightest value for each color to the darkest value and
5 brightest value for the luminance.

In another aspect, a system is provided for automatic color correction of a sequence of images. The system includes an image analyzer having an input for receiving an indication of one or more representative images
10 in the sequence of images and an output for providing information indicative of characteristics of the one or more representative images. A parameter calculator has an input for receiving the information indicative of characteristics of the one or more representative images and an output for
15 providing parameters for a color correction operation according to the analyzed characteristics of the one or more representative images. A color corrector has a first input for receiving the parameters and a second input for receiving the sequence of images and an output for providing
20 the sequence of images color corrected according to the determined parameters.

In another aspect, a method, computer program product and system is provided for automatic color correction of a sequence of clips of video information. An
25 indication of a representative image for each clip in the sequence is received. Characteristics of the representative image for each clip are analyzed. Parameters for a color correction operation for each clip are determined according to the analyzed characteristics of the
30 representative image for the clip. The color correction operation with the parameters determined for the clip is applied to each clip.

77787-78

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a data flow diagram of an example system that performs automatic color correction on a clip of a motion picture.

5 Fig. 2 is a flow chart describing how automatic color correction may be performed on a set of clips.

Fig. 3 illustrates a vectorscope histogram display of an example input image.

10 Fig. 4 illustrates a vectorscope histogram display of an output image after automatic correction.

Fig. 5 illustrates a color wheel interface for setting color correction parameters.

Fig. 6 illustrates the color wheel interface of Fig. 5 with color correction parameters set.

15 Fig. 7 illustrates is a flowchart describing how a two-dimensional chrominance histogram of an image may be used to set color correction parameters.

Fig. 8 illustrates red, green and blue channel histograms of an example input image.

20 Fig. 9 illustrates red, green and blue channel histograms of an output image after automatic correction.

Fig. 10 illustrates a curves interface for setting color correction parameters.

25 Fig. 11 illustrates the curves interface of Fig. 10 with color correction parameters set.

77787-78

Fig. 12 illustrates is a flowchart describing how a one-dimensional luminance histogram of an image may be used to set color correction parameters.

DETAILED DESCRIPTION

5 Referring now to Fig. 1 a data flow diagram of an example system 100 that performs automatic color correction on a clip of a motion picture will now be described. A clip 102 represents a sequence of images. Typically, the sequence of images is stored in a data file. The clip
10 references the data file and a range of images within the data file to define what images are part of the clip in the motion picture. A motion picture is generally defined by a sequence of such clips.

To perform automatic color correction on a clip
15 102, one or more representative images 104 from among the images in the clip 102 is selected by an image selector 106. There are a variety of ways that the representative images 104 may be selected by the image selector 106. For example, but not limited to these examples, an image may be selected
20 from the middle of the clip. Every n-th image in the sequence may be selected. Every image in the clip also may be selected.

The representative image is input to an image analyzer 108. The image analyzer produces results 110 that
25 are used by a parameter calculator 112 to determine what parameters 114 to use for color correction. The image analyzer may generate, for example, but not limited to, a two-dimensional chrominance histogram (in a manner described below) or a one-dimensional luminance histogram (in a manner
30 described below). The parameter calculator may determine, for example, but not limited to, an offset between a peak in

77787-78

a chrominance histogram and a white point from which a corresponding offset for a color correction operation can be determined (in a manner described below).

Given the determined parameters 114 for an
5 appropriate color correction operation, a color corrector 116 uses those parameters and applies the color correction operation to all of the images in the clip 102. The color corrector thus produces the color corrected clip 118.

Referring now to Fig. 2, a flow chart describing
10 how automatic color correction may be performed on a set of clips, such as a sequence or clips or a selected set of clips, will now be described. The process involves receiving (200) the set of clips. One of the clips is selected (202). The selected clip is automatically
15 corrected (204), using the process described in connection with Fig. 1. After the selected clip is corrected, if any clips in the received set remain, as determined at 206, then the next clip is selected (202) and the process is repeated. Such automatic correction of a set of clips enables, for
20 example, an editing system to automatically process and correct a sequence of clips, perhaps even all clips in a program that is being edited.

An example technique for analyzing an image and generating color correction parameters will now be described
25 in connection with Figs. 3-7. This technique uses a two-dimensional chrominance histogram of the representative image and determines an offset of a peak in the histogram from a white point. The inverse of this offset may be applied to and displayed by, for example but not limited to,
30 color wheels for each of shadow, midtone and highlight regions of an image.

77787-78

Fig. 3 illustrates a vectorscope histogram display of an input image. In this display, the vectorscope 300 has a white point 302 at the center of the display. The vectorscope provides a two-dimensional histogram of the colors in the image, as indicated by 304. An approximate center of this histogram, however, is notably offset from the center 302 of the vectorscope and represents a color cast in the image. To correct this image, the vectorscope histogram of the corrected image would appear as shown in Fig. 4. Notably, the histogram 402 in the vectorscope 400 in Fig. 4 is approximately centered on the white point 404.

One way to correct an image is to use hue offsets (as specified using color wheels) as shown in the color wheel interface 500 of Fig. 5. This interface includes a color wheel 502 for shadow regions of an image, a color wheel 504 for midtone regions of the image and a color wheel 506 for highlight regions of an image. There are a variety of ways for specifying the shadow, midtone and highlight regions, and the invention is not limited thereby. The initial settings of the hue offsets on the color wheels, shown in Fig. 5, are zero, or no offset, and the crosshairs 508, 510 and 512 are at the centers of the respective color wheels 502, 504 and 506.

Fig. 6 illustrates a color wheel interface 600 with color correction parameters set to provide the correction that is illustrated by the vectorscope display in Fig. 4. The corrected settings of the hue offsets on the color wheels, shown in Fig. 6, are represented by the crosshairs 608, 610 and 612 which are at an offset from the centers of the respective color wheels 602, 604 and 606. Notably, the offset between the center of the histogram in the vectorscope of Fig. 3 and the white point is

77787-78

approximately the opposite direction and same magnitude of the hue offsets shown in Fig. 6. How such hue offsets are determined will now be described in connection with Fig. 7.

Fig. 7 illustrates is a flowchart describing how a two-dimensional chrominance histogram of an image may be used to set color correction parameters. Experimentation has revealed that a histogram for midtone values can be unreliable. Histograms are developed only for shadow and highlight values and a correction parameter for midtones is derived from the correction parameters for shadows and highlights.

In Fig. 7, shadow and highlight histograms are initialized (700) to zero. In particular, each value in a two-dimensional array indexed by the Cr, Cb values of a pixel is set to zero. Two such arrays are initialized, one for shadows and one for highlights. Each histogram is then populated (702) with the pixel values from the image. Each pixel value is converted to Y, Cr, Cb components, and the Cr, Cb components are used to access the arrays for both shadows and highlights. In general a histogram is simply a count of values. Instead of merely incrementing a count for the Cr, Cb value of the pixel, the luminance component (y) is used to weight the value added to the histogram. In general, a weight can be assigned to each luminance value y for each of the shadows, midtones and highlights. The weight should be a high value if the luminance value y indicates that the pixel is strongly in a shadow, midtone or highlight region. The weight should be a low value if the luminance value y indicates that the pixel is not strongly in the shadow, midtone or highlight region. In one implementation, the weight for the shadow histogram is $255-y$ and the weight for the highlight histogram is y.

77787-78

After the shadow and highlight histograms are created for the representative image, they may be filtered (704) to reduce the likelihood that noise affects the determination of the offset. Such a filter may be, for example but not limited to, a low-pass filter such as a three-by-three tent filter. Filtering also may be performed based on the distance of a pixel from the center. For example, each value for each cell in each two-dimensional histogram may be scaled by the sum of one less the distance from the center. Such filtering helps limit the effect of a large colored object in the image on the histogram.

After the shadow and highlight histograms are filtered, the Cr and Cb values corresponding to the largest value in each histogram are identified (706). These pairs of values (herein called Cr_shadow, Cb_shadow and Cr_highlight, Cb_highlight) represent the offset of the colors in the image from a white point for the shadow and highlight regions of the image. The midtone offset (Cr_midtone, Cb_midtone) may be estimated (708) from the offsets of the shadows and highlights. This offset may be estimated by, for example but not limited to, summing the shadow offset with the highlight offsets. In particular, $Cr_midtone = Cr_shadow + Cr_highlight$ and $Cb_midtone = Cb_shadow + Cb_highlight$.

These offsets are then converted to color correction parameters, depending on the color correction operation to be performed. For example, but not limited to this example, the color correction operations may be a hue offset applied to each of the luminance regions of shadows, midtones and highlights. Such offsets may be applied through and/or displayed in, for example but not limited to, a color wheel interface such as shown in Figs. 5 and 6. In

77787-78

automatic color correction of multiple clips the user interface, such as the color wheels, may be hidden from the user. To convert the offsets to hue and saturation adjustments, the offsets are first converted (710) to polar
5 coordinates to obtain the hue (an angle) and saturation (a magnitude) that correspond to each pair of Cr and Cb offset values. The hue is then inverted (712). For example, if the hue is represented in degrees, then 180 is added to the hue. The offsets for the color correction operation are
10 then set (714) to the computed saturation and inverted hue.

This particular form of color correction maintains the luminance substantially constant. The nonlinearity of the color correction operations performed using hue offsets on luminance regions may introduce a slight change in
15 luminance.

Another example technique for analyzing an image and generating color correction parameters will now be described in connection with Figs. 8-12. This technique uses a one-dimensional luminance histogram of the
20 representative image and determines the maximum and minimum luminance values. The red, green and blue channel values are then stretched and translated so that the minimum values for red, green and blue channels match the minimum and maximum luminance values. These values may be applied
25 through and/or displayed by, for example but not limited to, a curves interface that operates on red, green and blue channels, or on a levels interface (not shown).

Fig. 8 illustrates red, green and blue channel histograms of an example input image. In this display, a
30 histogram 800, 802 and 804 is provided, respectively for each of the red, green and blue channels. The histogram

77787-78

provides a one-dimensional histogram of each channel that defines the image. Each histogram indicates a number (by the y-axis) of pixels having a particular value (x-axis) for the corresponding component. In the green and blue
5 histograms in Fig. 8, a significant number of values exceed the highest legal value, and also are significantly higher than the red values. Therefore, a blue and green color cast can be expected.

To correct only the color balance in this image,
10 without modifying the contrast, the histogram of each channel 900, 902 and 904 would appear as shown in Fig. 9. Fig. 9 illustrates red, green and blue channel histograms of an output image after automatic correction. Notably, each histogram in Fig. 9 has the same maximum and minimum values,
15 as shown at 906 and 908 respectively. As described in more detail below, these minimum and maximum values 906 and 908 are determined according to the minimum and maximum values of a luminance histogram of the image.

One way to correct such an image is to use curves
20 that map input values of a channel to new output values of the same channel, for example by using a curves interface 1000 as shown in Fig. 10. This interface includes a curve 1002 for the red channel, a curve 1004 for the green channel and a curve 1006 for the blue channel. The initial settings
25 for the curves, shown in Fig. 10, provide an identity mapping.

Curves allow a user to manipulate one or more function curves that adjust individual components of pixels of an image, such as red, green, blue components. One or
30 more points may be added to the curve, or may be moved, to modify the function that it performs. Thus, the curves

77787-78

allow a user to perform a mathematically nonlinear adjustment to a color component. These curves are particularly useful for color correction because a large number of color problems in an image are nonlinear problems created at the time of acquisition of the image, and these problems are typically introduced in the red, green and blue components of pixels of the image.

Fig. 11 illustrates the curves interface of Fig. 10 with color correction parameters set to provide the correction that is illustrated by the histograms in Fig. 10. The corrected settings for the histograms, shown in Fig. 11, are represented by the points 1108, 1110 and 1112 of the curves 1102, 1104 and 1106, respectively, which are at an offset from the original endpoints of those curves in Fig. 10. How such modifications to the curves are determined will now be described in connection with Fig. 12.

Fig. 12 illustrates is a flowchart describing an example process for how a one-dimensional luminance histogram of an image may be used to set color correction parameters. Histograms for the red, green and blue channels and for luminance are initialized (1200). In particular, each value in a one-dimensional array, indexed by the possible values for each channel, or for luminance, is set to zero. Four such arrays are initialized, one for the red channel, one for the green channel, one for the blue channel and one for luminance. Each histogram is then populated (1202) with the pixel values from the image. If the input image is represented using red, green and blue values, the luminance value is computed for each pixel. These histograms represent a count of each pixel having a particular value for red, green, blue and luminance, and are not weighted.

77787-78

After generating the histograms, the minimum value and maximum value for each histogram is determined (1204). That is, the lowest red, green, blue and luminance value for which there is a pixel is identified. Also, the largest
 5 red, green, blue and luminance value for which there is a pixel also is identified. The minimum value and maximum value may be forced to correspond to a certain minimum number of pixels to avoid an anomalous pixel from causing an incorrect minimum or maximum to be obtained.

10 Given the minimum and maximum values for each of the red, green and blue channels and luminance, the color correction parameters may be determined (1206). For example, if the color correction operations is performed using curves, a slope and offset defining the curve for each
 15 channel is determined using the minimum and maximum values of the channel and the minimum and maximum luminance values. In particular, the following set of equations (Equation 1) may be used:

$$\text{RedSlope} = (\text{LumMax} - \text{LumMin}) / (\text{RedMax} - \text{RedMin})$$

20 $\text{RedOffset} = \text{LumMin} - \text{RedSlope} * \text{RedMin}$

$$\text{GreenSlope} = (\text{LumMax} - \text{LumMin}) / (\text{GreenMax} - \text{GreenMin})$$

$$\text{GreenOffset} = \text{LumMin} - \text{GreenSlope} * \text{GreenMin}$$

$$\text{BlueSlope} = (\text{LumMax} - \text{LumMin}) / (\text{BlueMax} - \text{BlueMin})$$

$$\text{BlueOffset} = \text{LumMin} - \text{BlueSlope} * \text{BlueMin}$$

25 These values may be used to create look up tables for performing the color correction operation.

In the processes of Figs. 7 and 12, it may be desirable to analyze an image, for example, generate a

77787-78

histogram, with only a portion of the image data. For example, image data in certain spatial or color ranges may be excluded. A test can be performed to determine if a pixel is in an excluded spatial or color range, and if the pixel is to be excluded from analysis it is not added to the histograms used in Figs. 7 or 12. A color range that may be excluded includes, but is not limited to, illegal or clipped values. A color range that is selected by a user, such as by manual specification or by specifying an image processing operation, also may be excluded from analysis. A spatial range that may be excluded includes, but is not limited to, the edges of the image, such as an 8-pixel boundary on the left, top, right and bottom of the image. Such a boundary eliminates black lines at the top and bottom and ramped values at the left and right sides of an image, which are typically found in a number of video formats. A spatial area that is selected by a user, such as by manual specification or by specifying an image processing operation, also may be excluded from analysis. Such spatial and color ranges also may be excluded from color correction as well as from the analysis.

A percentage value, between zero percent and one hundred percent, also can be used to control the extent of the changes through automatic balancing. A user interface could be provided for allowing a user to specify a percentage amount of balancing to be performed. The percentage value would limit the hue offset and saturation or curve slope and offset that are computed as the color correction parameters. For example, the RedMin, RedMax, GreenMin, GreenMax, BlueMin and BlueMax values may be adjusted prior to utilizing Equation 1, above, by the following set of equations (Equation 2), given a value (AB) between 0 and 1:

77787-78

$$\text{RedMin} = \text{AB} * \text{RedMin} + (1 - \text{AB}) * \text{LumMin}$$

$$\text{GreenMin} = \text{AB} * \text{GreenMin} + (1 - \text{AB}) * \text{LumMin}$$

$$\text{BlueMin} = \text{AB} * \text{BlueMin} + (1 - \text{AB}) * \text{LumMin}$$

$$\text{RedMax} = \text{AB} * \text{RedMax} + (1 - \text{AB}) * \text{LumMax}$$

$$5 \quad \text{GreenMax} = \text{AB} * \text{GreenMax} + (1 - \text{AB}) * \text{LumMax}$$

$$\text{BlueMax} = \text{AB} * \text{BlueMax} + (1 - \text{AB}) * \text{LumMax}$$

By using these kinds of operations for automatic balancing, the luminance and thus the contrast in the image remains substantially the same. Thus, a separate control
 10 for contrast adjustment may be combined with this automatic balancing.

As one example, a master curve interface may be provided in the interface of Figs. 10 and 11. The master curve allows the user to manipulate simultaneously all of
 15 the components of an image with a single function curve. A change to the master curve that would result in maximizing the breadth of all of the red, blue and green channel histograms would maximize the contrast of an image. Therefore, in addition to computing the changes to the red,
 20 green and blue curves, a change to the master curve can be computed. A percentage value can be used to control the amount of this change between zero percent and one hundred percent. The percentage could be a 50% contrast change, for example. A user interface could be provided for allowing a
 25 user to specify a percentage amount of contrast change. For example, such a percentage value (AC) that varies between 0 and 1 may be used to modify the LumaMin and LumaMax values used in Equations 1 and 2, above, using the following set of equations (Equation 3):

77787-78

$$\text{LumMin} = \text{AC} * \text{LumMin} + (1 - \text{AC}) * \text{LumMinLimit}; \text{ and}$$
$$\text{LumMax} = \text{AC} * \text{LumMax} + (1 - \text{AC}) * \text{LumMaxLimit},$$

where LumaMinLimit and LumaMaxLimit represent the limit of the range of legal values for luminance, and typically are 16 and 235 respectively.

A user interface could be provided to allow a user to set a percentage for both of the automatic balancing and automatic contrast adjustment, which could be treated as a default value for an automatic correction operation.

10 A user interface also could be provided to allow a user to cycle through viewing a clip using different amounts of balancing and/or contrast. For example, a user interface may have a button for performing an automatic correction function. If the button is pressed multiple times on the
15 same clip, each time would perform the automatic correction function with a different percentage of correction. For example, automatic correction could cycle through 100%, 75%, 50%, 25% and then no correction.

The various components of the system described
20 herein may be implemented as a computer program using a general-purpose computer system. Such a computer system typically includes a main unit connected to both an output device that displays information to a user and an input device that receives input from a user. The main unit
25 generally includes a processor connected to a memory system via an interconnection mechanism. The input device and output device also are connected to the processor and memory system via the interconnection mechanism.

One or more output devices may be connected to the
30 computer system. Example output devices include, but are

77787-78

not limited to, a cathode ray tube (CRT) display, liquid crystal displays (LCD) and other video output devices, printers, communication devices such as a modem, and storage devices such as disk or tape. One or more input devices may
5 be connected to the computer system. Example input devices include, but are not limited to, a keyboard, keypad, track ball, mouse, pen and tablet, communication device, and data input devices. The invention is not limited to the particular input or output devices used in combination with
10 the computer system or to those described herein.

The computer system may be a general purpose computer system which is programmable using a computer programming language, such as "C++", Visual Basic, JAVA or other language, such as a scripting language or even
15 assembly language. The computer system may also be specially programmed, special purpose hardware. In a general-purpose computer system, the processor is typically a commercially available processor, such as various processors available from Intel, AMD, Cyrix, Motorola, and
20 IBM. The general-purpose computer also typically has an operating system, which controls the execution of other computer programs and provides scheduling, debugging, input/output control, accounting, compilation, storage assignment, data management and memory management, and
25 communication control and related services. Example operating systems include, but are not limited to, the UNIX operating system and those available from Microsoft and Apple Computer.

A memory system typically includes a computer
30 readable medium. The medium may be volatile or nonvolatile, writeable or nonwriteable, and/or rewriteable or not rewriteable. A memory system stores data typically in

77787-78

binary form. Such data may define an application program to be executed by the microprocessor, or information stored on the disk to be processed by the application program. The invention is not limited to a particular memory system.

5 A system such as described herein may be implemented in software or hardware or firmware, or a combination of the three. The various elements of the system, either individually or in combination may be implemented as one or more computer program products in
10 which computer program instructions are stored on a computer readable medium for execution by a computer. Various steps of a process may be performed by a computer executing such computer program instructions. The computer system may be a multiprocessor computer system or may include multiple
15 computers connected over a computer network. The components shown in Fig. 1 may be separate modules of a computer program, or may be separate computer programs, which may be operable on separate computers. The data produced by these components may be stored in a memory system or transmitted
20 between computer systems.

 Having now described an example embodiment, it should be apparent to those skilled in the art that the foregoing is merely illustrative and not limiting, having been presented by way of example only. Numerous
25 modifications are within the capabilities of one of ordinary skill in the art and are contemplated as falling within the scope of the invention.

77787-78

CLAIMS:

1. A method for automatic color correction of a sequence of images, comprising:

receiving an indication of one or more
5 representative images in the sequence of images;

analyzing characteristics of the one or more
representative images;

determining parameters for a color correction
operation according to the analyzed characteristics of the
10 one or more representative images; and

applying the color correction operation with the
determined parameters to the sequence of images.

2. The method of claim 1, wherein analyzing
characteristics of the one or more representative images
15 comprises:

generating a two-dimensional histogram of colors
in the representative image, wherein the two-dimensions
include a white point; and

determining an offset between a peak value in the
20 two-dimensional histogram and the white point.

3. The method of claim 2, wherein determining
parameters comprises:

using the determined offset to determine an offset
for color correction of the image.

25 4. The method of claim 2, wherein generating the two-
dimensional histogram comprises:

77787-78

for each pixel, determining a weighting for the pixel with respect to its classification as a shadow or highlight;

generating a two-dimensional histogram for each of
5 shadows and highlights using the determined weightings for each pixel.

5. The method of claim 4, wherein determining parameters comprises:

using the determined offset for shadows to
10 determine an offset for color correction of shadows;

using the determined offset for highlights to determine an offset for color correction of highlights; and

using the determined offsets for shadows and highlights to determine an offset for color correction of
15 midtones.

6. The method of claim 1, wherein analyzing characteristics of the one or more representative images comprises:

generating a histogram of luminance in the
20 representative image, whereby the histogram indicates a darkest value and a brightest value.

7. The method of claim 6, wherein determining parameters comprises:

determining adjustments to histograms of colors in
25 the representative image to match a darkest value and a brightest value for each color to the darkest value and brightest value for the luminance.

77787-78

8. A computer program product, comprising:

a computer readable medium;

computer program instructions stored on the
computer readable medium that, when executed by a computer,
5 instruct the computer to perform a method for automatic
color correction of a sequence of images, comprising:

receiving an indication of one or more
representative images in the sequence of images;

analyzing characteristics of the representative
10 image;

determining parameters for a color correction
operation according to the analyzed characteristics of the
representative image; and

applying the color correction operation with the
15 determined parameters to the sequence of images.

9. The computer program product of claim 8, wherein
analyzing characteristics of the one or more representative
images comprises:

generating a two-dimensional histogram of colors
20 in the representative image, wherein the two-dimensions
include a white point; and

determining an offset between a peak value in the
two-dimensional histogram and the white point.

10. The computer program product of claim 9, wherein
25 determining parameters comprises:

using the determined offset to determine an offset
for color correction of the image.

77787-78

11. The computer program product of claim 10, wherein generating the two-dimensional histogram comprises:

for each pixel, determining a weighting for the pixel with respect to its classification as a shadow or
5 highlight; and

generating a two-dimensional histogram for each of shadows and highlights using the determined weightings for each pixel.

12. The computer program product of claim 11, wherein
10 determining parameters comprises:

using the determined offset for shadows to determine an offset for color correction of shadows;

using the determined offset for highlights to determine an offset for color correction of highlights; and

15 using the determined offsets for shadows and highlights to determine an offset for color correction of midtones.

13. The computer program product of claim 8, wherein analyzing characteristics of the one or more representative
20 images comprises:

generating a histogram of luminance in the representative image, whereby the histogram indicates a darkest value and a brightest value.

14. The computer program product of claim 13, wherein
25 determining parameters comprises:

determining adjustments to histograms of colors in the representative image to match a darkest value and a

77787-78

brightest value for each color to the darkest value and
brightest value for the luminance.

15. A method for analyzing characteristics of one or
more representative images from a sequence of images,

5 comprising:

generating a two-dimensional histogram of colors
in the representative image, wherein the two-dimensions
include a white point; and

determining an offset between a peak value in the
10 two-dimensional histogram and the white point.

16. The method of claim 15, wherein generating the
two-dimensional histogram comprises:

for each pixel, determining a weighting for the
pixel with respect to its classification as a shadow or
15 highlight; and

generating a two-dimensional histogram for each of
shadows and highlights using the determined weightings for
each pixel.

17. A computer program product, comprising:

20 a computer readable medium;

computer program instructions stored on the
computer readable medium that, when executed by a computer,
instruct the computer to perform a method for analyzing
characteristics of one or more representative images from a
25 sequence of images, comprising:

77787-78

generating a two-dimensional histogram of colors in the representative image, wherein the two-dimensions include a white point; and

5 determining an offset between a peak value in the two-dimensional histogram and the white point.

18. The computer program product of claim 17, wherein generating the two-dimensional histogram comprises:

for each pixel, determining a weighting for the pixel with respect to its classification as a shadow,
10 midtone or highlight; and

generating a two-dimensional histogram for each of shadows, midtones and highlights using the determined weightings for each pixel.

19. A method for analyzing characteristics of one or
15 more representative images from a sequence of images, comprising:

generating a histogram of luminance in the representative image, whereby the histogram indicates a darkest value and a brightest value; and

20 determining adjustments to histograms of colors in the representative image to match a darkest value and a brightest value for each color to the darkest value and brightest value for the luminance.

20. A computer program product, comprising:

25 a computer readable medium;

computer program instructions stored on the computer readable medium that, when executed by a computer,

77787-78

instruct the computer to perform a method for analyzing characteristics of one or more representative images from a sequence of images, comprising:

generating a histogram of luminance in the
5 representative image, whereby the histogram indicates a darkest value and a brightest value; and

determining adjustments to histograms of colors in the representative image to match a darkest value and a brightest value for each color to the darkest value and
10 brightest value for the luminance.

21. A system for automatic color correction of a sequence of images, comprising:

an image analyzer having an input for receiving an indication of one or more representative images in the
15 sequence of images and an output for providing information indicative of characteristics of the one or more representative images;

a parameter calculator having an input for receiving the information indicative of characteristics of
20 the one or more representative images and an output for providing parameters for a color correction operation according to the analyzed characteristics of the one or more representative images;

a color corrector having a first input for
25 receiving the parameters and a second input for receiving the sequence of images and an output for providing the sequence of images color corrected according to the determined parameters.

77787-78

22. A method for automatic color correction of a sequence of clips of video information, comprising:

receiving an indication of a representative image for each clip in the sequence;

5 analyzing characteristics of the representative image for each clip;

determining parameters for a color correction operation for each clip according to the analyzed characteristics of the representative image for the clip;

10 and

applying to each clip the color correction operation with the parameters determined for the clip.

23. A system for automatic color correction of a sequence of images, comprising:

15 means for receiving an indication of one or more representative images in the sequence of images and analyzing characteristics of the one or more representative images;

means for determining parameters for a color
20 correction operation according to the analyzed characteristics of the one or more representative images;
and

means for applying the color correction operation with the determined parameters to the sequence of images.

25 24. A system for analyzing characteristics of one or more representative images from a sequence of images, comprising:

77787-78

means for generating a two-dimensional histogram of colors in the representative image, wherein the two-dimensions include a white point; and

5 means for determining an offset between a peak value in the two-dimensional histogram and the white point.

25. A system for analyzing characteristics of one or more representative images from a sequence of images, comprising:

10 means for generating a histogram of luminance in the representative image, whereby the histogram indicates a darkest value and a brightest value; and

means for determining adjustments to histograms of colors in the representative image to match a darkest value and a brightest value for each color to the darkest value
15 and brightest value for the luminance.

26. A computer program product, comprising:

a computer readable medium;

computer program instructions stored on the computer readable medium that, when executed by a computer,
20 instruct the computer to perform a method for automatic color correction of a sequence of clips of video information, comprising:

receiving an indication of a representative image for each clip in the sequence;

25 analyzing characteristics of the representative image for each clip;

77787-78

determining parameters for a color correction operation for each clip according to the analyzed characteristics of the representative image for the clip; and

5 applying to each clip the color correction operation with the parameters determined for the clip.

27. A system for automatic color correction of a sequence of clips of video information, comprising:

 means for receiving an indication of a
10 representative image for each clip in the sequence;

 means for analyzing characteristics of the representative image for each clip;

 means for determining parameters for a color correction operation for each clip according to the analyzed
15 characteristics of the representative image for the clip; and

 means for applying to each clip the color correction operation with the parameters determined for the clip.

SMART & BIGGAR

OTTAWA, CANADA

PATENT AGENTS





FIG. 1

**FIG. 2**




FIG. 3





FIG. 4







FIG. 6

**FIG. 7**




FIG. 8







FIG. 9



**FIG. 12**

