Office de la Propriété Intellectuelle du Canada
Un organisme d'Industrie Canada

Canadian Intellectual Property Office
An agency of Industry Canada

CA 2670943 C 2015/05/05

(11)(21) 2 670 943

(12) BREVET CANADIEN
CANADIAN PATENT

(13) C

(86) Date de dépôt PCT/PCT Filing Date: 2007/12/10
(87) Date publication PCT/PCT Publication Date: 2008/11/27
(45) Date de délivrance/Issue Date: 2015/05/05
(85) Entrée phase nationale/National Entry: 2009/05/28
(86) N° demande PCT/PCT Application No.: IB 2007/055414
(87) N° publication PCT/PCT Publication No.: 2008/142496
(30) Priorité/Priority: 2006/12/08 (BE BE 2006/0606)

(51) Cl.Int./Int.Cl. *B07C 5/342* (2006.01)

(72) Inventeurs/Inventors:
ADAMS, DIRK, BE;
OP DE BEECK, PIETER, BE

(73) Propriétaire/Owner:
VISYS, BE

(74) Agent: GOWLING LAFLEUR HENDERSON LLP

(54) Titre : PROCEDE ET APPAREIL POUR INSPECTER ET TRIER UN FLUX DE PRODUITS
(54) Title: METHOD AND APPARATUS FOR INSPECTING AND SORTING A STREAM OF PRODUCTS



(57) Abrégé/Abstract:
The invention concerns a method and apparatus for sorting a stream of products by scanning this stream of products with a bundle of concentrated light and analyzing the light originating from the scanned products and a background element, wherein this

CA 2670943 C 2015/05/05

(11)(21) 2 670 943

(13) C

(57) Abrégé(suite)/Abstract(continued):
background element is chosen such that the corresponding detected light signal differs from the light signals originating from the products to be sorted in at least one parameter and wherein one or more control signals are generated by shifting the background level of the observed light signals to a signal level chosen such that, in the thus obtained signal, the signal level of the signal of a scanned product to be accepted distinguishes itself from the signal level of the signal of a scanned product to be rejected.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
27 November 2008 (27.11.2008)

PCT

(10) International Publication Number
WO 2008/142496 A3

(51) International Patent Classification:
B07C 5/342 (2006.01)

(21) International Application Number:
PCT/IB2007/055414

(22) International Filing Date:
10 December 2007 (10.12.2007)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
BE 2006/0606 8 December 2006 (08.12.2006) BE

(71) Applicant *(for all designated States except US)*: **VISYS** [BE/BE]; Kiewitstraat 242, B-3500 Hasselt (BE).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: **ADAMS, Dirk** [BE/BE]; Hasseltsesteenweg 113, B-3700 Tongeren (BE). **OP DE BEECK, Pieter** [BE/BE]; Heidestraat 23, B-3470 Kortenaken (BE).

(74) Agent: **PRONOVEM-OFFICE VAN MALDEREN**; Avenue Josse Goffin, 158, B-1082 Brussels (BE).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR INSPECTING AND SORTING A STREAM OF PRODUCTS

(57) Abstract: The invention concerns a method and apparatus for sorting a stream of products by scanning this stream of products with a bundle of concentrated light and analyzing the light originating from the scanned products and a background element, wherein this background element is chosen such that the corresponding detected light signal differs from the light signals originating from the products to be sorted in at least one parameter and wherein one or more control signals are generated by shifting the background level of the observed light signals to a signal level chosen such that, in the thus obtained signal, the signal level of the signal of a scanned product to be accepted distinguishes itself from the signal level of the signal of a scanned product to be rejected.

Figure 6a

Figure 6b

Figure 6c

Figure 6d

Figure 6e



Figure 6

WO 2008/142496 A3

WO 2008/142496 A3

Published:
— *with international search report*
— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:
15 January 2009

METHOD AND APPARATUS FOR INSPECTING AND SORTING A STREAM OF PRODUCTS

Field of the invention

[01] The current invention relates to a method and apparatus for inspecting a stream of products. This inspection can further result in a quality selection by means of a sorting step.

[02] The invention is applicable when removing certain degraded products and foreign objects from an incoming stream of products.

[03] The invention is particularly suited for sorting food products such as green beans, peas, nuts, raisins, cauliflowers, lettuce and such like for which non-food products such as wood, plastics, glass and others need to be removed from the stream of products.

[04] The invention is furthermore extremely suitable for sorting non-food products such as plastics from recycling garbage, sorting of glass and such like.

State of the art

[05] It is known from the international patent application WO 01/00333 that product objects in a stream of products can be illuminated with a concentrated beam of light. The reemitted light is captured by a detector whereupon it is analyzed. Based on this analysis a selection mechanism can be controlled to achieve a certain sorting result .

[06] In the absence of product, the light is reflected by a background element that needs to be chosen product dependently. More specifically, the background needs to be chosen such that it shows the optical characteristics of good product. In other words, the good product is invisible against the background. However, deviations in an analyzed product such as insect bytes, putrescent stains, foreign objects and such cause a deviation in the returned light signal. By adjusting a threshold one can make the difference between the light signal coming from the background and acceptable products on the one hand and the light signal coming from unacceptable product to be removed on the other hand.

[07] Similar background elements are described in the American patent US4723659 and the European patents EP1012582 and EP0443769. Generally speaking it concerns a background element positioned perpendicular to the direction of product movement, in the field of view of the detecting means. Usually the background element is a cylindrical roller. While rotating and with the aid of a scraper it becomes self-cleaning.

[08] A disadvantage of this method is that for each kind of product a specific background element needs to be available. Thus a background element for carrots should have an orange color, while for green beans it should

have a green color. During the sorting of food products and more specifically while switching from one product to another, it is required to switch the background element as well. Furthermore, the cost of a background element is not negligible.

[09] In certain applications the background element is given additional optical properties. Many fresh vegetables contain for example chlorophyll. A frequency shift towards the infra-red spectrum occurs within these molecules when illuminated with light having a wavelength between 640 and 680 nanometer. This emission phenomenon is called fluorescence. By giving the background element the same fluorescent properties one can, in the state of the art, additionally sort based on the presence of chlorophyll in the analyzed products. Other molecules, such as aflatoxin, show fluorescent properties as well and could in principle be detected in the analyzed products according to a similar technique.

[10] An important disadvantage is that over time these kinds of background elements loose their fluorescent properties. This has adverse effects on the sorting quality and is also uninteresting for the users of such equipment.

[11] For these reasons there is a need for a sorting device, in particular an inspection device, without the disadvantages of the devices known in the state of the art.

For these reasons there is need for a method not showing the disadvantages of the current state of the art.

Objects of the invention

[12] In general the object of the invention is a method and apparatus to carry out a selection between products in a large, continuous stream of products in a very effective, reliable and cost-effective way.

[13] More specifically, according to a number of preferred embodiments, the invention aims at an inspection method and inspection means avoiding the replacement of the background element during a product switch.

[14] In other words, the object of the invention is an inspection method and inspection means using a background reference which is at least product domain independent.

Summary of the invention

[15] The method of sorting products according to the invention is characterized at least by transporting the products to sort along a certain trajectory in the form of a product stream having a width; a background element extending along the width of the product stream; with a concentrated light beam illuminating along the width of the product stream, the products to sort and, in absence of said products, the background element; capturing the light reemitted by the products and the background element; based on said observed light carrying out a first selection between the background element on the one hand and all the products in the product stream on the other hand; carrying out a second selection between the products to sort on the one hand and the products to be rejected on the other hand and based on this second selection automatically carrying out a separation of the products in said product stream.

[16] Preferably the background element comprises a surface extending along the width of the product stream, whereby said surface reflects the incoming light at least partially.

[17] In a particularly useful embodiment the background element has the shape of a cylindrical roller.

[18] In an alternative embodiment the background element comprises means to capture and redirect the incoming light towards an opto-electrical convertor. In this case such a background element generates a signal having a progression from which the presence or absence of products in the scanning zone can be easily deduced. A thus obtained Boolean signal is particularly useful in the method according to the invention.

[19] The first selection is preferably done based on whether or not the intensity of the detected light or a derived signal thereof crosses a threshold value.

[20] In certain cases, more specifically when the total range of products features positive as well as negative peaks against the background signal, the first selection is done based on whether or not the intensity of the observed light emitted by the background element or a derived signal thereof falls within a zone, said zone further characterized by a maximum threshold value.

[21] The second selection is preferably done based on whether or not the intensity of the detected light or a derived signal thereof crosses a threshold value.

[22] In a preferred embodiment said crossing of a threshold value is exclusively defined within those zones which are labeled during the first selection step as originating from product.

[23] In an exceptionally preferred embodiment a new signal is generated after the first selection, further characterized by preserving the intensity of the observed light in those zones outlining product (the product zones) and subsequently changing the intensity in the zones where the background element can be observed to another level.

[24] Additionally it is preferable to filter said signal such that the high-frequency transitions at the product zones are flattened and a new signal is created. Said filter could for example be an adaptive filter specifically tuned to smooth the transition from product zone to background zone and vice versa.

[25] In the most practical embodiment according to the invention the second selection is done on said filtered signal.

[26] In any case the selection of the background element will be such that it leads to at least one corresponding signal having a path according to which a first selection can be carried out between said background element on the one hand and all products in the product stream on the other hand.

[27] In a practical embodiment of the method according to the invention the scanning is done using a rotating mirror, preferably a fast rotating polygonal mirror.

[28] In a very practical embodiment the scanning uses a laser beam.

[29] In a practical embodiment the products are transported on a vibrating table, belt or suchlike, towards an inspection installation.

[30] In some cases, more specifically in the case of free-fall sorting devices, the products are further guided during their free fall by a free-fall plate. Furthermore, the products to separate are segregated by means of a manifold of air valves positioned along the width of the product stream and opened based on the second selection step.

[31] In some cases, more specifically in those cases where defects are situated on both sides, it is advantageous to scan the products to sort from two sides, opposite from each other.

[32] The method could be combined with color sorting by sorting based on light reflections.

[33] Additionally different concentrated light beams having each a different wavelength, possibly combined into one bundle, could be utilized.

[34] In an important variant according to the invention two signals are combined in a two-dimensional graph such that each point in this graph corresponds with a specific intensity level according to the path of the first signal combined with a specific intensity level according to the path of the second signal; the points corresponding with the product to be accepted are grouped in first zone; the points corresponding with products to reject are grouped in a second zone; the points corresponding to the background element are outlined by a third zone; adjusting the level of the background signal is realized by repositioning the third zone to a new location.

[35] In this case moving said third zone can be achieved by visualizing this zone in a graph displayed in a graphical user interface and subsequently dragging this zone to a new location.

[36] In a preferred embodiment this said new location is chosen such that a separation can be made between the first and the third zone on the one hand and the second zone on the other hand using a separation plane.

[37] Additionally more than two signals can be combined into a more-dimensional graph.

[38] Apart from said method, the invention also refers to an apparatus to sort products using this method and such that it comprises at least a transport device to transport a stream of products, extending over a width, into a specific direction; means to scan the products to sort along the width of the product stream, further comprising means to generate a concentrated light and direct it towards means to cast this light beam onto the

products; means to capture the returning light; means to carry out a selection between the scanned products based on the observed light; means to separate the products based on this selection.

[39] In a preferred embodiment the means to generate the concentrated light is a laser generator.

[40] In a preferred embodiment the means to cast the light beam onto the products comprises optical means, more specifically a rotating polygonal mirror, moving the concentrated light transversely across the product stream. The current invention is however not limited to such a scanning arrangement. It could, by way of example, as well generate a row of concentrated light beams, possibly turned on and off in sequence.

[41] Additionally the means to carry out a selection based on the returning light could be based on digital electronic components, more specifically Field Programmable Gate Arrays and microprocessors, or could be based on analogue electronic components such as operational amplifier circuits, or it could be a combination of analogue and digital processing units.

[42] In a practical embodiment the means to make a separation between the products based on said selection are composed of a manifold of air valves, mounted transversely across the product stream.

[43] In an advantageous embodiment the background element is composed of a surface across the width of the product stream, such that the incident light is at least partially reflected by said surface.

[44] In an alternative embodiment the background element is composed of means that capture and channel the

incident light towards means to convert this light into an electric signal.

[45] In a preferred embodiment the means to capture the returning light are composed of an optical filter making the detection arrangement sensitive for a specific light spectrum, in operable communication with a spatial filter making the detection arrangement sensitive for a specific zone of the returning light, and in operable communication with both filters an opto-electrical converter transforming the light into a corresponding electric signal.

[46] A method for sorting a stream of products in products to be accepted and products to reject comprising the steps of moving through a scanning zone the products to sort, supplied in a product stream spanning a certain width and having a thickness of substantially a single layer of products, in this scanning zone linearly scanning one or more concentrated light beams across the width of this product stream, illuminating, in the absence of products, a background element positioned behind this product stream that extends over the width of it, whereby this light beam produces light signals at these scanned products and at this scanned background element, detecting these light signals whereby these light signals are converted in electric signals, generating one or more control signals on the basis of these converted signals whereby these control signals allow making a selection between the scanned products to be accepted on the one hand and the scanned products to be rejected on the other hand, and sorting the product stream by means of these one or more control signals, characterized in that this method further comprises; choosing this background element) such that the

corresponding detected light signal differs in at least 1 parameter from the light signals of the products to sort and whereby generating one or more control signals further comprises shifting the background level of the converted signals after detection of the light signals, towards a new signal level chosen such that, in the thus obtained signal, the signal level of the signal of a scanned product to be accepted differs from the signal level of a scanned product to be rejected. The parameter in which the background element can differentiate itself from the products to sort can be the signal level, a spatial aspect such as scattering or a frequency aspect such as color information.

[47] This method can further comprise, after moving the background level of the converted signals, comparing the thus obtained signal with one or more threshold values to generate in this way the one or more control signals.

[48] Moving the background level according to this method can further comprise generating a signal which is indicative of the location of the scanned products in the detected and converted signals and shifting the level of the converted signals to locations other than these of the scanned products such as have been indicated by this location signal.

[49] Generating the location signal according to this method can further comprise detecting and converting the light signals originating from the scanned background element and from the scanned products, in these converted signals separating the signal originating from the scanned background element from the signals of the scanned products such that a signal is obtained indicative of the location of the scanned products.

[50] Distinguishing the signal originating from the scanned background element according to this method can further comprise comparing the converted signals with one or more threshold values.

[51] In an alternative embodiment of these methods generating the location signal can further comprise detecting and converting that zone of the concentrated scanning light beam passed by the products, as such obtaining a signal that is indicative of the location of the scanned products.

[52] The location signal in the different embodiments of this method can be a Boolean signal. Shifting the signal level to a new signal level can then happen according to the formula $D = BC + s(C \oplus 1)$, in which B is the detected and converted light signals, s a real number chosen in function of the desired shift of the signal level, C the location signal, and $\oplus$ is defined as the modulo-2 addition.

[53] The location signal in the different embodiments of this method can be a Boolean signal. Shifting the signal level to a new signal level can then happen according to operation D = B when C = 1 and D = 0 when C = 0 and in which B is the detected light signal, and C is the location signal.

[54] The location signal in the different embodiments of this method can be an analogue or digital signal, whereby comparing the thus obtained signal with one or more threshold values happens only on the location of the scanned products as indicated by the location signal.

[55] The background level of the converted signals can be shifted towards a signal level according to that of a product to be accepted.

[56] The location signal in any embodiment can be generated on the basis of one or more first detected signals and afterwards used to indicate the location of the products in one or more second detected signals.

[57] The background element in any of the embodiments can consist of a surface that extends over the width of the product stream, whereby said surface at least partially reflects the incident light. Preferably this background element has the shape of a cylindrical roller.

[58] In an alternative embodiment this background element consists of means to capture and redirect the incident light towards a opto-electrical convertor. In this case the background element can be an optical fiber with a grooved surface to capture the incoming light. Such optical fiber can consist of segments, whereby for each segment the orientation of these grooves with respect to the longitudinal direction of the optical fiber is chosen in function of the position of this segment along the width of the product stream.

[59] In any embodiment according to this method the thus obtained signal can be filtered prior such that the high-frequency transitions near the product zones are flattened, generating a new filtered signal. This filter can be an adaptive filter which is adjusted specifically to smooth the transitions from a product zone to a background zone and vice versa.

[60] In any embodiment according to this method the linear scanning of the product stream can happen by means of a moving mirror, preferably a rapidly rotating polygonal mirror. The product stream can be scanned by several concentrated light beams by means of this moving mirror, whereby every light beam has a separate frequency. Preferably this concentrated light beam is a

laser beam. The products to sort can be scanned from both edges of the product stream.

[61] In any embodiment of this method the supply of the product stream can happen by means of a vibrating table, a conveyor belt or suchlike. The products can further be supplied by means of a free-fall plate which guides these products during their free fall towards the scanning zone.

[62] In any embodiment of this method the sorting of the product stream by means of these one or more control signals can happen by controlling a manifold of air valves positioned across the width of the product stream by means of these one or more control signals.

[63] In any embodiment, besides at the signal level, sorting the product stream can also happen on color, i.e., the frequency of the detected light signals.

[64] In an embodiment of aforementioned methods whereby generating one or more control signals by means of moving the background level of the converted signals to a new signal level chosen as such that, in the thus obtained signal, the signal level of the signal of a scanned product to be accepted differs from the signal level of the signal of a scanned product to be rejected, further comprising; combining two detected and converted signals in a two-dimensional graph, in which each point corresponds with a particular intensity level according to the path of the first signal combined with a particular intensity level according to the path of the second signal; the points which correspond to product to be accepted are grouped in a first zone; the points which correspond to product to be rejected are grouped in a second zone; the points which correspond to the background element are outlined by a third zone;

adjusting the level of the background signal is realized by repositioning the third zone to a new location. Moving said third zone can happen by visualizing this zone in a graph displayed in a graphical user interface and subsequently dragging this zone to a new location. This said new location can be chosen such that a separation can be made between the first and third zone on the one hand and the second zone on the other hand. This two-dimensional graph can have an additional dimension showing the histogram of appearing signal combinations. Furthermore, more than two detected signals can be combined with each other in more-dimensional graph so that, for every location in the scanning zone, as much as possible optical information is collected and depicted, allowing to make a better distinction between the location of the products to be sorted and these of the background on the one hand and between the products to be accepted and products to be rejected on the other hand. All or at least one of said first, second and third zones in such two or more-dimensional graph can be inferred by automatic clustering algorithms.

[65] An apparatus for sorting products according to the methods of any of the previous claims, characterized by at least consisting of a supply system transporting a single layer of the products to be sorted along a certain trajectory in the form of a product stream extended over a width; means to scan to products to be sorted over the width of this product stream, whereby these scanning means further comprise; means to generate a concentrated light beam and direct it towards the products via optical means; means to detect the returning light and convert it to an electric signal; means to generate control signals enabling to carry out a selection between the scanned products based on said detected light; and means to sort

the product stream based on said selection by means of said one or more control signals, characterized in that the sorting apparatus further comprises; a background element chosen such that the corresponding detected light signal differs in at least 1 parameter from the light signals of the products to be sorted and whereby the selection means comprise means to generate one or more control signals by shifting the background level of the light signals towards a signal level chosen such that, in the thus obtained signal, the signal level of a scanned product to be accepted differs from the signal level of a scanned product to be rejected.

[66] The selection means of such sorting device can further comprise means to generate a location signal based on one or more detected signals, means to obtain a signal based on this location signal and based on these or other one or more detected signals, such that the background level in these last signals is shifted to a new level enabling to differentiate products to be accepted from products to be rejected in said obtained signal.

[67] These selection means can further comprise means to compare the obtained signal with one or more threshold values, in this way generating the one or more control signals.

[68] These selection means can further comprise filters to priefilter the thus obtained signal so that the high-frequency transitions close to the product zones are flattened and thus obtain a new filtered signal. This filtering operation can be achieved by means of an adaptive filter specifically adjusted to smoothing the transitions from a product zone to a background zone and vice versa.

[69] In any of the aforementioned sorting apparatuses this background element can consist of a surface that extends over the width of the product stream, whereby said surface reflects the light at least partially. Preferably this background element has the shape of a cylindrical roller.

[70] In an alternative embodiment this background element can consist of means to capture and redirect the incident light towards an opto-electrical convertor. Such background element can be an optical fiber with a grooved surface to capture the incident light. Such optical fiber can consist of segments, whereby for each segment the orientation of these grooves with respect to the longitudinal direction of the optical fiber is chosen in function of the position of this segment along the width of the product stream.

[71] A laser can be used in such sorting apparatuses to capture the concentrated light beam. This laser can be moved across the width of the product stream by means of a rotating polygonal mirror.

[72] In such sorting apparatuses the means to make a selection between the scanned products in function of the observed light consist of a signal processing platform based on digital electronic components, more specifically Field Programmable Gate Arrays and microcomputer processors, or based on analogue electronic circuits, such as op-amp circuits, or a combination of analogue and digital processing units.

[73] In such sorting apparatuses the means to sort the product stream in function of said selection by means of these one or more control signals, consist of a manifold of air valves, positioned transversely across the product stream.

[74] In such sorting apparatuses the means to capture the light can consist of an optical filter making the detector sensitive to a particular light spectrum; in operational communication with a spatial filter making the detector sensitive to a particular zone of the returning light; in operational communication with both said filters an opto-electrical convertor converting the light to a corresponding electric signal.

Short description of the figures

[75] Figure 1 illustrates schematically the fundamental operation of a sorting apparatus according to the invention;

[76] Figure 2 illustrates schematically a possible embodiment of a scanning device;

[77] Figures 3a and 3b show alternative embodiments of the background element.

[78] Figure 4 illustrates schematically a detector device;

[79] Figure 5 illustrates schematically an apparatus with several detector devices;

[80] Figures 6a-e illustrate the method in several steps according to the current invention which results in a better or at least more advantageous inspection;

[81] Figures 7a-b illustrate this method in a two-dimensional representation;

[82] Figure 8 shows a sorting apparatus according to the invention in viewing perspective.

[83] Figures 9a-f illustrate schematically the signal processing in an inspection device when the background element generates a signal that deviates from a good product

[84] Figures 10a-d illustrate schematically the processing of the signal according to an embodiment of the invention

[85] Figures 11a-d illustrate schematically the processing of the signal according to an embodiment of the invention

[86] Figures 12a-d illustrate schematically the processing of the signal according to an embodiment of the invention

[87] Figures 13a-c illustrate schematically the processing of the signal according to an embodiment of the invention

[88] Figure 14 illustrates schematically the processing of the signal according to an embodiment of the invention

[89] Figures 15a-c illustrate schematically the processing of the signal according to an embodiment of the invention

Detailed description of the invention

[90] The current invention will be described by means of a few examples, referring to certain figures, without any restrictive kind. The figures are only schematic and not limiting. In the figures, the dimensions of certain elements can be exaggerated or not in true proportion. This is because of illustrative considerations. For this reason, the dimensions and relative dimensions do not necessarily correspond to reality.

[91] The current invention teaches a method and a mechanism for sorting products **2, 3**, to be precise, granular products like raisins, beans, berries, but also plastic grains, that are conveyed in large quantities and in a continuous stream.

[92] In addition, the method according to the invention is also suitable for inspecting larger products like broad beans, cauliflower, lettuce, etc.

[93] Figure 1 shows schematically a sorting apparatus **14** according to the current invention. This sorting apparatus contains an supply system **1**, at least one inspection unit **9,10** , a reject system **11** and possibly a free fall glide **4** that guides the product stream in free fall to the inspection unit **9,10** and the reject system **11**. The glide, however ,can also be a conveyor belt that conveys the products **2, 3**.

[94] The supply system **1** with width **W** can be a vibrating table, or any other conveyor system known in the current state of the art. In case supply system **1** is being executed as a conveyor belt, the use of a free fall glide **4** can be superfluous, as is well known by the person skilled in the art.

[95] In the scanning zone **28**, the inspection unit watches the falling product **2,3** by analyzing the returning light. In function of this analysis, a reject system **11** is being controlled. This results in a separation of the product stream in an accept stream **13** and a reject stream **12**.

[96] Behind the scanning zone **28**, a background element **5** is illuminated and observed while no product is present **2,3** in that zone **28**. The optical properties of the background element **5** are chosen in such a way that a proper distinction can be made between all products **2,3** in the product stream on the one hand and the background element on the other hand. These optical properties can refer to the frequency or to spatial properties of the background element **5**. The background element can generate a light signal with another frequency or reflect the incident light **34** in another way, or even scatter it. This method differs from the current state of the art, which tries to make a distinction between all the products to be rejected **3** from the product stream on the one hand and the background **5** together with the products to be accepted **2** on the other hand. For this reason, in the current invention the choice of the background element **5** becomes considerably less complicated and independent of the product domain. For instance, the background element **5** will be the same for green beans and orange carrots. As opposed to the current state of the art, in which a specific background element for every product has to be available which has optical properties identical to those of the products to be accepted **2**. In the case of green beans and carrots, the current state of the art would need two different background elements: one with a green color, and another with an orange color. When the products to be sorted **2,3** are transported by a conveyor belt **1**, this conveyor belt can be used as

background element to obtain a background signal that differs from the signal of all the products **2,3**, as is described in the embodiments of the invention.

[97] In a preferred embodiment of the current invention, the background element **5** is a cylindrical roller, to be precise, a rotating roller that cleans itself by means of a scraper that is placed against the roller.

[98] In a preferred set-up for the sorting of fresh vegetables such as green beans, carrots and peas, the background element **5** is implemented as a white, strongly scattering, not fluorescing, cylindrical roller. A signal **39**, measured by a detection unit **40**, only sensible to the scattered light, will in this case show a path **B** along which a proper distinction can be made between the background signal **19** on the one hand, and the peaks **20,21** originating from green beans, peas, carrots, wood, plastic, metal, glass etc. on the other hand.

[99] In an alternative version, the background element **5** is an intrinsic component of the mechanical construction and contains, besides the function of optical background, an additional function as mechanical support element. As a result, it can, as such, not be removed. Such greatly simplified mechanical embodiment according to the current invention is impossible to implement in the current state of the art.

[100] The inspection unit **9,10** consists of a scanning unit **43** and a detection unit **44**. The scanning unit illuminates the product stream along the entire width **W**. The detection unit **44** captures a zone of the returning light and will convert this returning light by at least one opto-electrical converter **38** to an electric signal that is afterwards analyzed in a processing unit **41**.

[101] Figure 2 illustrates a possible embodiment of an inspection unit **43**. A concentrated light beam **45**, preferably originating from a laser **29**, is directed towards a fast rotating, reflecting polygon wheel **30**. During the rotation, this polygon **30** generates a fast moving concentrated point of light directed towards the product stream. The scanning is performed along the entire width **W** with a scanning angle determined by the extreme light beams **31,31'**.

[102] When this light **32,33,34** incides on a product **2,3** **a** zone of the light **46, 47, 48** will be reflected according to the color of this product **2,3,** . This makes color sorting possible.

[103] Dependent on the light permeability of the illuminated product **2,3**, the concentrated light beam **32,33,34** will be reflected directly and/or scattered, as is elaborately described in the American patent US4634881. This makes structure sorting possible. Additionally, the presence of fluorescing molecules in the product **2,3** will cause a frequency shift in the reflected light, making it possible to sort on the presence of those molecules, like chlorophyll and aflatoxin.

[104] Entirely within the scope of this patent, various light beams with different wavelengths can be bundled, preferably by combining various lasers of different wavelengths by means of mirrors and optical filters.

[105] In figures 3a and 3b, an alternative version of the background element **5** is clarified, whereby this element consists of means to capture the incident light **34** and to direct it to a detection unit **40** that converts this light into an electric signal **39**.

[106] As is illustrated in figure 3a, the background element 5 can consist of an optical fiber 56, on which, by means of a closer specified mechanism 57, the incident light 34 can be further channeled to a detection unit 40 that generates an electric signal 39. The element 57 can for example consist of grooves or little mirrors attached to the fiber 56, so that the light gets bended towards the abovementioned filter 56.

[107] In international patent application WO 2007/062219 and in zone 2 "Design and fabrication" of the article "A fiber grating based distributed light source", by G. E. Carver, Proc. Of SPIE Vol. 6371, 63710H-2 (2006), a grooved optical fiber is used to obtain a linear uniform light source. Light injected in the optical fiber in its longitudinal direction, is redirected in a direction differing from the longitudinal through grooves in the side of the fiber. The redirected light can be further guided through a cylindrical optical system to obtain a more uniform light distribution within a restricted area. According to the choice of the geometric parameters of the grooves (cf. figure 5 of WO 2007/062219 or figure 2 of the SPIE article: width, pitch d, angle of the groove in relation to the normal direction perpendicular on the longitudinal direction, angle of the groove in relation to the longitudinal direction) and of the optical parameters (wavelength of the light source, refraction index of the optical fiber), the direction and the degree of the redirection can be determined. The grooves can be applied by means of a printer that uses laser light or UV light (cf. chapter 2, second paragraph of the SPIE article, p.9 third paragraph illustrated by figure 5 of WO 2007/062219) By varying the relative orientation of the optical fiber in relation to the printer, the angle

under which the grooves are formed in the side of the optical fiber can be determined.

[108] Such optical fiber can, however, also be used to capture light originating from a linearly moving concentrated light beam **34** and to redirect it in the longitudinal direction of the optical fiber to an exit as illustrated in figure 3a.

[109] As already mentioned in these publications, a grooved optical fiber of arbitrary length can be obtained by coupling separate segments (cf. SPIE article, chapter 2, last paragraph). Therefore, an optical fiber can be made that extends over de entire width **W** of the product stream. Accordingly, for every immediate position of the concentrated light beam, such a grooved optical fiber can capture the, in the absence of products, uninterrupted light **34** and redirect it to a detection unit **40**.

[110] Because the angle, formed by the uninterrupted light and the optical fiber used as background element **5** in figure 3a, depends on the position according to the width **W**, it can be necessary to vary the orientation of the grooves along the length of the optical fiber. After all, the uninterrupted light bundle **34** will enter the fiber substantially perpendicularly in the middle of the product stream, if the inspection unit **10** is set up symmetrically in relation to the width of the product stream. Moving to the edges of the product stream, the uninterrupted light beam **34** will, however, incide on the optical fiber **5** under a certain angle.

[111] This can be prevented in two manners. As mentioned above, the optical fiber can consist of coupled segments. For every segment of the optical fiber, the orientation of the grooves can be kept the same. This can lead to an efficient production of these segments. Every segment in

the optical fiber **5** can be placed under another angle, depending on the position according to the width of the product stream. A segment in the middle of the product stream will be placed in a substantially parallel position in relation to the product stream, while segments on the edges of the product stream are placed under an angle in relation to the product stream, correspondent to the angle formed by the light beam **34** and the product stream. Because of this variable orientation of the segments throughout the width of the product stream, the uninterrupted light **34** will always incide on the grooves under substantially the same angle and will be captured and redirected in the same way. Preferably, the segments are placed on an arc described by the concentrated light beam **45** when scanning the product stream.

[112] As mentioned above, the optical fiber can consist of coupled segments. For every segment of the optical fiber, the orientation of the grooves can be changed. After all, the orientation of the grooves can be chosen separately for every segment by setting the relative orientation of the printer accordingly. The orientation of the grooves of a segment can therefore be adapted according to its position in relation to width of the product stream and to the angle formed by the inciding light beam **34** and the product stream at that point. In this embodiment of figure 3a, all segments of the optical fiber will be placed substantially parallel to the product stream. The orientation of the grooves of a segment will, however, depend on the position along the width of the product stream according to the angle formed by the inciding uninterrupted light bundle **34** and this position. This way, the uninterrupted light **34** will each time form

substantially the same angle with the grooves. The light will also be captured and redirected in the same way.

[113] An alternative as illustrated in figure 3b, consists of implementing the background element **5** as a manifold of little detector units **40** that convert the incident light **34** in an electric signal **39**. In the embodiment illustrated in figure 3b, the background element can be constructed as a linear array or line of light sensitive elements, such as photodiodes or Photo Multiplier Tube (PMT) or other elements known to the person skilled in the art. Because such linear array is usually constructed as a line of separate light sensitive elements **40**, i.e. separated from each other, it is possible that an uninterrupted light bundle **34** does not incide on a light sensitive element **40**. One could wrongly conclude that a product **2,3** was present in the product stream that obstructed the concentrated light bundle. To avoid the discontinuous light detection, one could provide a limited light scattering effect when a uninterrupted light beam reaches the background element **5**. One can apply a coating on the background element that scatters the incident light when the background element **5** itself is being scanned. This light scattering coating can for example be a milky plastic layer or a glass plate. Using this limited light scattering one can make sure that two or more nearby light sensitive elements **40** get illuminated, even if the uninterrupted light beam **34** should reach the background element **5** between two such light sensitive elements **40**. After all, it is important to know whether an uninterrupted light beam **34** reaches the background element **5**, rather than the position where the background element **5** is illuminated. This position can be deduced from the known immediate position of the scanning light bundle and by correlating the time period

of the signal **47**, coming from the background element **5**, with the time period of the moving light bundle.

[114] The signal on the exit of the detecting background element **5**, as illustrated among others by figures 3a and 3b, can be processed further. The electric (figure 3b) or optical (figure 3a) signal at the exit of such a background detection element **5**, can be filtered to withhold only the signal components coming from the uninterrupted light beams **34**, while the ambient light is being filtered away. The signal components will typically have a higher frequency than signal components coming from background light. A DC-filter or high-pass filter can usually be enough for only allowing the wanted higher-frequency signal components, characteristic for the presence of a product **2,3**, passage for subsequent signal processing as discussed in this description.

[115] Figure 4 shows schematically a detector unit **40**, struck by the incident light or light cone **46, 47, 48**, and that subsequently converts said light, or a particular zone of it, into an electric signal by means of an opto-electrical convertor **38**. This electric signal **39** is given as input to a processing unit **41**, which by means of an analytic method generates a control signal **42** that controls a reject system **11**.

[116] According to the invention, optical filters **36** can be used to render the detector unit **40** sensitive to one specific wavelength by placing this filter **36** into operational communication with abovementioned opto-electrical convertor 38.

[117] According to the invention, a spatial filter **37** can be used to block or to let through certain zones of the returning light **46,47,48** . For instance, a spatial filter **36** can be used, which only lets through the scattered

light. Such spatial filters are described in the American patents US4634881 and US4723659.

[118] In a preferred embodiment, the spatial filter **36** consists of a diaphragm that is placed right before the opto-electrical convertor **38**.

[119] As is schematically illustrated in figure 5, more detector units **40, 40'** can be set up according to the invention.

[120] In a preferred embodiment, every detector unit **40, 40'** uses a different combination of optical **36** and spatial **37** filters. Because of this, every detector unit **40,40'** is sensitive to a specific zone of the returning light **46,47,48** having a specific wavelength. The output signals **39, 39'** are representative of a specific zone of the returning light **46,47,48** on a specific wavelength.

[121] The first detector unit **40** generates a first electric signal **39** with a level determined by the abovementioned optical and spatial filters chosen for that detector. The second detector unit **40'** generates a second electric signal **39'** with a level determined by the abovementioned optical and spatial filters chosen for that detector. The detector units **40,40'** are in operational communication with the processing unit **41** via the signals **39,39'**.

[122] The processing unit **41** will perform a selection between the scanned products **2,3** and the background element **5,** in function of the returning light **46,47,48,** more specifically based on the electric signals **39,39'**.

[123] In a preferred embodiment according to the invention, the processing unit **41** is a digital processing platform based on Field Programmable Gate Arrays or microprocessors. The processing unit **41** could, however,

also consist of analog op-amp circuits or a combination of analog and digital components as is known by the person skilled in the art.

[124] The method of the invention, as is illustrated in figure 6, consists of the light **45** having at least one wavelength, being sent out towards an inspection zone **28**. This zone **28** is being scanned and when the abovementioned light **45** strikes the product **2,3** or the background element **5**, the emission **46, 47, 48** will be captured by at least two detector units **40, 40'**.

[125] In the processing unit **41**, the incoming signals **39,39'** can be combined into new signals **A, B** according to the formula:

$$A = n39 + m39',$$
$$B = p39 + q39'$$

where n,m,p,q are real numbers and **39,39'** said input signals.

[126] In an advantageous embodiment of the invention, factors m and p are equal to zero. This means in principle that no combination is made. In this case, detector unit **40** generates the signal **A**, and detector unit **40'** the signal **B**.

[127] As an example, without any limitation to the scope, we consider a detector unit **40** having an optical filter **36** set to the light spectrum between 690 and 740 nanometers, more particularly the fluorescence spectrum of product **2** containing chlorophyll when illuminated between 540 and 680 nanometer. The signal **A** shows a possible path of such a set-up where a peak **16** is perceptible at the location of said product **2** containing chlorophyll.

[128] The problem occurs when the signal level in zone **17**, due to the products to be rejected **3**, does not show a noticeable difference with the background signal **15**. In that case, it is not directly feasible to make a distinction between the products to be rejected **3** on the one hand and the background element **5** together with the products to be accepted **2** on the other hand. Although this distinction must be made because only the products to be rejected **3** are allowed to give cause to a reject-action by means of a reject system **11**.

[129] In figure 6, signal **A** illustrates a path on which an emission phenomenon, that can only be attributed to the product to be accepted, is measurable. However, no selection is possible on such a signal because of the above mentioned problem.

[130] The signal **B**, as illustrated in figure 6, is shown in function of the width **W** of the scanning zone **28**. Zones **20,21** of the signal are the result of the emission that occurs on products **2,3**, particularly as a consequence of the emission of both the products to be accepted **2** and the products to be rejected **3**. Zone **19** is the result of emission of the background element **5**.

[131] On signal **B**, a zone **49** is defined in which the background signal **19** is situated. All zones **19** that are located within this zone **49**, are labeled by the processing unit **41** as coming from the background element **5**. To be precise, the zone 49 is determined by a maximum threshold value t_{max} and a minimum threshold value t_{min}. In an advantageous embodiment, these threshold values t_{max}, t_{min} can be adjusted by a user.

[132] In order to better represent the next steps in the method according to the current invention, a Boolean signal **C** is introduced, whereby the value **0** is adopted at

the locations of the background signal **54** and where the value **1** is adopted at the locations **18** outside the zone **49** on the signal **B**.

[133] The current invention does, however, not exclude that in an alternative method, the Boolean signal **C** is effectively being generated or is directly available in the processing unit **41**, for example in case of an embodiment as described in figures 3a en 3b, wherein the background element **5** generates a signal **39** according to the path of signal **B**, which can be transformed in a manner as described above to said signal **C**. However, one has to observe that in this case, the selection between the products **2,3** and the background element **5**, can take place using one threshold value t_{min} only because the peaks **20,21** where the products **2,3** are located, are all on the same side of the background signal **19**, all below (or all above) the background signal **19** to be precise.

[134] In a possible next step, according to the invention, a new signal **D** is being generated using the formula:

$$D = AC + s(C \oplus 1),$$

wherein $\oplus$ is being defined as the modulo-2 addition.

[135] In this way, the new signal **D** is an exact copy of the abovementioned signal **A** on places **20,21** of product **2,3**. On the places where the background element **5** is being observed, a new value *s* is being established so that the background signal **22** clearly separates itself from the products to be rejected **3**.

[136] In the example described above, the path of signal **A** was interpreted as coming from the emission peak of a product **2** containing chlorophyll, against a non-fluorescing background. By generating the signal **D**, a distinction can be made between the background element **5**

together with the products **2** containing chlorophyll on the one hand, and the products to be rejected **3** on the other hand, making it possible to automatically remove the latter products.

[137] In a preferred next step, the signal **D** will be additionally filtered by, for instance, a low-pass filter, generating a new signal **E**. The low-pass filter is constructed according to known principles, for instance by means of digital multi-tap FIR filter. The cut-off frequency will be chosen in a way that the high frequency transitions on the edges of the zones **20,21** in the signal **D** are flattened sufficiently, without losing the actual signal content. In this way, one obtains the zones **24, 25,** where the products **2,3** are, and zone **23,** where the background element **5** is.

[138] In an alternative form, the filtering is done by means of an adaptive filter that is tuned to apply a filtering to mainly only said transitions. In that case, the cut-off frequency chosen can be much smaller.

[139] The current invention is not restricted to the use of low-pass or adaptive filters to flatten out said transitions. To be precise, all methods to realize such a flattening fall within the scope of this invention.

[140] Based on the signal **E** is whether or not crossing a specific threshold value **g**, an automatic detection can be carried out at the locations **25** wherein the products to be rejected **3** are located.

[141] Instead of generating signals **D** and **E**, according to the invention, an automatic detection can be carried out at those locations **17** wherein the products to be rejected are located, based on whether or not the signal **A** crosses a threshold value **g**, by merely analyzing said crossing in

those zones wherein the products **2,3** are located according to signal **C**.

[142] The signals **A, A', B, C, D, E** are synchronized with each other. After all, these signals originate from the concentrated light beams **45**, scanning the product stream in temporal movement. Every immediate value of one of these signals can therefore be correlated to the corresponding immediate value of the other signals. This synchronization allows applying one signal to another signal or combining both, because at every single moment the signals are coming from the same scanned position. In figures 6a-e, signals $A(t_A)$, $B(t_B)$, $C(t_C)$, $D(t_D)$ and $E(t_E)$, whereby t_A, t_B, t_C, t_D, t_E depict the time dependence of these signals, can be correlated to each other because $t_A = t_B = t_C = t_D = t_E$,since all the signals are obtained through an light beam **45** temporally moving back and forth.

[143] To actually remove the products **3**, air valves **11** are opened so that, at the locations where these products **3** were detected, each such product **3** will be blown out of the product stream.

[144] The operation of the reject system **11** is carried out by comparing control signals generated by the signals **D, E**, to one or more threshold values g_i . These control signals only contain information about either the product to be rejected **3**, if this has to removed, or the product **2** to be accepted, if it has to be withheld.

[145] This method according to the current invention is, of course, not restricted to the use of two detectors. In the case of more than two detectors, the corresponding signals **42** can for instance be algebraically combined to abovementioned signals **A** and **B**.

[146] In an advantageous embodiment of the current invention, the zone **49**, in which the background signal is located, is defined on various signals **B**, to be precise on all the output signals **39** of all the present detector units **40**. The final Boolean signal **C** that determines where the background **19** is located and where the products **2,3** are located, is obtained by performing a logical-OR operation to all the separate signals **C** that are obtained according to the abovementioned method.

[147] In an alternative embodiment, the output signals **A, A'** of two detector units **40,40'** are combined in a two-dimensional graph. Both signals **A, A'** originate from the same position in the product stream, but can differ in one or more signal parameters, so that different optical properties of the scanned position at that moment can be analyzed. These signals **A, A'** can be obtained by filtering them out of a same detected light signal using spatial and/or frequency filters. Every point in this graph corresponds to a specific intensity level according to the path of the first signal **A**, combined with a specific intensity level according to the path of the second signal **A'** at a specific moment in time, or, in other words, for a known immediate position of the concentrated scanning light beam **45**. Specific signal combinations can occur several times if products **2,3** with the same optical properties are being scanned or every time the background element **5** is being scanned. By keeping these statistics, a two dimensional histogram can be created. Additionally, a color can be attributed to every histogram value. By attributing, for example, blue to the lowest value and gradually move up to red per rising value, a two-dimensional intensity map **55** can be created. On this map **55** contours of equal intensity can be drawn. As shown in figure 7a, zones can be determined

in which products with similar optical properties are clustered.

[148] Every point in the two-dimensional diagram of figure 7a is being characterized by the intensity levels of the respective signals **A, A'** and by the corresponding value of the location signal **C**. Depending on the value of this location signal, the signal levels of a point in the histogram correspond to those of a product **2,3** or to the background element **5**. Based on the information of the signal **C** for the individual signal combination **A, A'**, it can be determined whether or not a product is concerned .

[149] That way, in this perception, the zone **51** is being defined, in which the products to be accepted **2** are located, and the zone **52**, in which the products to be rejected **3** are located. The zone **50**, determined by the respective threshold values t_{max}, t_{min} **and** t'_{max}, t'_{min}, is represented by a square in said intensity map **55** containing the background as is illustrated in figure 7a. However, the signal combinations of a product to be rejected **3**, can be located in between the threshold values T'_{max}, T'_{min} and T_{max}, T_{min} containing the points corresponding to the scanned positions on the background element **5**. Figure 6b illustrates how the signal level of background signal **47** is located within a strip **49**, limited by one or both threshold values T_{max}, T_{min}. When the background element **5** would not show variation in the corresponding signal **47**, the background level would be one single line in figure 6b and one single point in figure 7a. In a realistic embodiment this background level can vary such that one obtains a matching set of points within the rectangle T'_{max}, T'_{min} and T_{max}, T_{min} that defines the strip **49** in figure 7a. As demonstrated in figure 7a, some points belonging to a product to be

rejected **3**, can have signal levels that cannot be distinguished from the background element **5**. This is illustrated in figure **7a** by the overlap between strip **50** and zone **52**. This is also illustrated in figure 6a wherein the signal on position **17** of a product **3** that is to be rejected, cannot be distinguished from the signal on position **15** coming from the background element **5**.

[150] In a graphical user interface one can, by means of a simple operation as is illustrated in figure 7b, for example by a dragging move, move the square **50** to another location with coordinates n'n, such that the zone **52** that matches the products **3** to be rejected, can be isolated by means of a separation plane **g'**. On the basis of the corresponding value of the positioning signal one can define for each point whether it refers to a product **2,3** or to the background element **5**, regardless of the corresponding levels of signals **A, A'**. As previously explained and also illustrated in figures 12a-d, this positioning signal **C** can be obtained starting from one or more observed light signals **A, B** whereby one can use this positioning signal **C** to indicate respectively, within this or other light signals, the position of the background **5** orthe products **2,3**.

[151] In a very advantageous embodiment the zones **50, 51** and **52** can be automatically calculated by means of known clustering algorithms, for example K-means.

[152] The invention is not restricted to one and twodimensional presentations, but can be easily extended to three and moredimensional presentations, be it by means of one, two or threedimensional projections in those cases.

[153] Hereafter a detailed description is given, as displayed in figure 8, of a possible practical

construction of an apparatus **26** for the realization of the method mentioned above.

[154] Figure 8 displays a complete sorting apparatus **26** in viewing perspective. This apparatus consists of a supply system **1**, more specifically a vibrating table transporting a stream of products **2,3** in a certain direction **27** through the sorting apparatus. During its free fall the product is additionally guided by a free-fall plate **4**.

[155] The structure **26** is furthermore equipped with 2 inspection devices **9, 10**. These inspection devices **9, 10** inspect an inspection zone **28** by means of a concentrated light beam that sweeps across the entire width **W** of the product stream. In the absence of products a background element is scanned that, according to the invention, may hold the optical characteristics of the products to be rejected.

[156] The products 3 to be rejected are blown out of the product stream via the air valves. The accepted products **2** are guided through a shaft **53** towards possible further production steps.

[157] During linear scanning of the product stream and the background element **5** signals are detected originating from this background element **5** and the product stream, notably the good products **2** and bad products **3**. By adjusting frequency and spatial filters one can generate control signals from the detected signals that enable to sort the supplied products according to previously stipulated criteria using the reject system **11**. Depending on the chosen background element **5** the background signal **47** will have a higher or lower intensity value: a white background gives a higher value, a black background gives a lower value as indicated in figure 9b. Signals

originating from good **46** and bad **48** products are superimposed on this background signal **47**. Each product **2, 3, 3'** gives a corresponding signal peak **46, 48, 48',** each characterized by a certain pulse width and pulse height or signal level. Figure 9b schematically reflects this combined signal **B,** obtained for a scan wherein two good **2** and two bad **3** products were scanned as in figure 9a. The desired products **2** are to be retained in the product stream, while the undesired products **3,3'** are to be rejected by the reject system **11.** When neither a good product **2** nor a bad product **3, 3'** is scanned, the reject system **11** must remain inactive. Although at that time no single product to be rejected is present in the system, the unnecessary activation of the reject system **11** could cause an undesired disturbance of the product stream. The reference level **70** in this combined signal **B** is situated on the level of the background signal **47.** In the current state of the art, based on this signal combination represented in figure 9c, one could identify the bad products **3** by determining a first "negative" threshold value **g1.** Those bad products **3** giving a signal peak **48** that exceeds the first threshold value **g1** may be removed from the product stream. This threshold value is specified as being negative throughout this description, because it is situated below the reference level **70** in the reference system of figure 9a-e. As the background signal **47** constitutes the reference **70** for determining the signal peak **48** and the threshold value **g1**, the level of this signal peak **48** will always be situated past this first threshold value **g1** as indicated by the hatched area in figure 9c. The good products **2** have a signal peak **46** that does not reach past the first threshold value **g1.** As long as the bad products **3** have a signal peak **48** that stays underneath the signal peaks **46** of the good products

and past the first threshold value **g1**, one can distinguish the good products **2** from the bad products **3** based on these signals **46**, **48**, which ultimately allows sorting the products in a stream of good products **13** and a stream of bad products **12**.

[158] In some cases, however, it is possible that a bad product **3'** generates a signal **48'** from which the peak is smaller than the signal **46** originating from a good product **2**. This issue has already been clarified in the embodiment illustrated by figure 6. The selection method presented in figure 9c does not allow distinguishing such bad products **3'** from the product stream just like that. After all, when one shifts the negative threshold value **g1** to the level of the reference value **70** of the background signal **47** in a manner that de signal peak of the bad product **3'** reaches past the threshold value g1, the good products **2** will be removed as well. The corresponding signals **46** have, after all, a peak value that is bigger than the one of such bad products **3'**.

[159] One could identify such bad products **3'** by defining a second, negative threshold value **g2**. The second threshold value **g2** is chosen in such a way that the signal peaks **46** of the good products **2** would reach past this second threshold value **g2**, whereas the signal peaks **48'** of such bad products **3'** would not reach past the second threshold value **g2**, as indicated by the hatched area in figure 9d. Signals that are situated below this threshold value **g2** then match products **3'** that are to be rejected from the product stream. Not only the signal peaks of the good products **2** but also the signal peaks **48** of the other, bad products **3** reach past the second threshold value **g2** and past the first threshold value **g1** as described above. A problem that can occur regarding

the choice of the threshold value **g2** in figure 9d is that all the signals, those of the good products **2** as well, pass partially underneath and partially above the threshold value **g2** and could in this way be wrongly interpreted as originating from a bad product. This is also illustrated in figure 9f, in which the signal peaks from a product to be rejected **3'** are situated within a strip limited by two threshold values **g2** and **g2'**, containing the signal peaks a product type to be rejected. Here also the signal peaks from the good products **2** will pass through such a strip and are possibly erroneously considered as originating from a product to be rejected **3'**

[160] By a suitable choice of the threshold values **g1** and **g2**, one can identify from the combined signal as indicated in figure 9e, bad products **3, 3'**, characterized respectively by a high signal peak **48** and a low signal peak **48'**. Only the signals **46** within the strip constituted by both threshold values **g1-g2** are considered as originating from a good product **2**. One could also describe these threshold values as respectively an upper limit **g1** and a lower limit **g2**, together limiting a signal strip locating the signal peaks to which the reject system **11** may not react.

[161] The selection method in the current state of the art as presented in figures 9a-f will, however, not work without error. Since the background signal **47** is to be used as a reference for determining the signal peaks **46,48,48'** and the threshold values **g1** and **g2**, this background signal **47** will always be situated above the second negative limit **g2**. Just like with the bad products **3'** the reject system **11** will react on the presence of the

background element **5**. Consequently the reject system **11** will react to:

- product signals **48** with a signal peak passing the first negative threshold value **g1;**
- product signals **48'** with a peak that does not reach past the second negative threshold value **g2;** and
- background signals **47** that by definition do not reach past the second, negative threshold value **g2.**

The good products are indeed situated in the strip between a first, negative threshold value **g1** and a second, negative threshold value **g2.** One could sort the good products using this procedure by well selecting the values. The problem with the background however is not resolved: this is, as illustrated by figure 9a-e, considered to be a bad product.

[162] In the current state of the art this problem is solved by physically constructing the background element **5** in such a way that it provides a signal **47** that is comparable, for the detected optical parameter, to the signal **46** originating from a good product **2** and is thus situated within the strip constituted by both threshold values **g1, g2.** As mentioned above, it is, however, difficult to construct a background element 5 in such a way that, for the measured optical parameter(s), it not only resembles the actual good product 2 sufficiently well, but that it can retain this resemblance of a specific product **2 to a** sufficient extent and over a considerable time. Furthermore the problem remains that one has to install for each product **2** a matching background element **5.**

[163] In the different embodiments of the invention the reference level **70** of the combined signal **B** is shifted using signal processing techniques to a new value **71** that preferably matches the signal level **46** of a good product **2**. The signal peaks **48, 48'** of the bad products **3,3'** are being referenced in the processed signal **D** to the new reference level **71.** To clarify the invention this new reference **71** is adjusted to the signal level **46** of a good product **2.** This is illustrated in figure 10c. Where originally the reference level **70** was situated on the background signal **47,** as is indicated for signal **B** in figure 10b, the reference level **71** for the new signal **D** is substantially equal to the signal level **46** of the good products **2.** Through this shift in reference level **71->71,** resulting from signal processing, the matching signal peaks **48** for some bad products **3** will still stretch out from the new reference level **71** downwards. These are the undesired products **3** that had, in the original reference framework of the signal **B** as illustrated in figure 10b, a signal peak **48** that stuck out past this one **46** of the desired products **2.** These undesired products **3** still give rise to a negative signal peak even in the new reference framework **71** of the signal **D.** For any other undesired products **3',** the corresponding signal peaks **48'** will now stretch out from the new reference level **71** upwards. These are the undesired products that in the original reference framework **70** illustrated in figure 10b, had a signal peak **48'** that did not stick out past ththis **46** of the desired products **2.** Instead of providing a negative signal peak, these undesired products **3'** provide a positive signal peak **48'** in the new reference framework 71. By shifting the level **71** with respect to whatever the different product signals were being referred to, it is now as if the given

background signal **47** with level **70** is removed from the detected signal **B** and replaced by a new signal with level **71** in the signal **D.** By this replacement of the reference level **71** a new signal D is obtained, as indicated in figure 10c, now containing information about the products **2, 3, 3'** in such a manner that these products can be distinguished from each other without the problems present in the state of the art.

[164] Now one can identify the good products **2** by defining an appropriate threshold value(s) for the new signal **D,** as demonstrated in figure 10d, while one must distinguish between 2 types of bad products **3,3'.** As for the product signals **46, 48, 48'** these threshold values are referred to the new reference level **71**, which, in this example, has been chosen such that it is substantially equal to the signal level **46** of the good products **2.** A first, negative threshold value **g1** has been chosen in such a manner that the undesired products **3**, provide a signal peak **48** till past this first threshold value **g1.** These products **3** may be rejected from the product stream by activating the reject system **11.** A second, now positive threshold value **g2** is chosen in such a manner that the undesired products **3'** provide a signal peak **48'** past the second threshold value **g2**. This threshold value is indicated as positive because in the given reference framework this threshold value **g2** is situated above the reference level 71. These products **3'** may be rejected from the product stream by activating the reject system **11.** As the signal level **70** of the background signal **47** according to the background element **5** is shifted to the new reference level **71**, in this case matching the signal from the good products **2**, the variations on the signal level of the background signal **47** will be situated within

both threshold values **g1, g2.** Therefore the reject system is not activated.

[165] The signal levels **46** of the good products **2** may show small variations, provided that these variations are situated around the reference level **71** within both threshold values **g1, g2.** The reject system is not activated in that case.

[166] By appropriately choosing the threshold values **g1** and **g2**, one can identify from a combined signal as indicated in figure 10d, bad products **3,3'** characterized by respectively a high signal peak **48** and a low signal peak **48'.** All signals **48, 48'** outside the strip defined by both threshold values **g1-g2** compared to the reference level **71** are considered as originating from a bad product **3, 3'**. Although in the embodiment illustrated by figures 10a-d a signal is shown with 2 types of bad products **3,3'** the invention is not limited to such signals. Also in signals **B** whereby only one bad product type, either **3,** or **3'** occurs, one can apply the signal processing technique as illustrated in the different embodiments of the invention. This is illustrated by figures 15a-c and figure 6, in which only one undesired product of the type **3'** occurs, namely with a signal peak **48'** compared to the original reference level **70** that is smaller than the signal peak **46** of the good product **2.** By shifting the reference level **71** one can unmistakably distinguish this signal peak **48'** from the signal peak **46** without the problems of the present state of the art, such as the undesired reaction of the reject system **11** on a background signal **47** or on a signal peak **46** that would reach past the lower limit **g2** when one would continue to use the original reference framework **70** for further signal processing.

[167] By shifting the reference level **70** to a suitable new value **71** one can better distinguish between the different products **2, 3** and/or **3'** and avoid the unnecessary activation of the reject system **11** either when detecting the background signal **47** and/or when a lower limit **g2** is passed by a signal **46.**

[168] Because one shifts the reference level **70** of the background **47** to a new level **71** in the embodiments according to the invention using signal processing techniques, one picks a background signal **47** that differs , preferably considerably, from any product signal **46, 48, 48'.** As one shifts the background reference level **47** via signal processing, preferably to the signal level **46** of a good product **2,** the accurate value of this background level **47** is not important, as long as the background element **5** provides a signal **47** that differs, preferably considerably, from the signals **46, 48, 48'** of any product **2, 3, 3'.** This choice of background signal **47** enables to clearly distinguish between the original reference level **70** and the product signals **46, 48, 48'** and, as such, refer these product signals to the new level **71.**

[169] In the state of the art, there are different ways to determine the level **70** of this background signal **47.** One can allow the inspection configuration(s) **9,10** to work without supplying any products. The selected signal **B** will substantially match the signal **47** of the background element **5.** One can also insert known products **2, 3,** and/or **3'** at known positions in the scanning beam of the inspection unit **10.** The immediate signal being detected, i.e. on the given moment t(s), matches a given immediate position of the scanning beam of light and thus with a given position x(mm) in the product stream. In this way

one can identify and correlate the different signals **47, 46, 48 and/or 48'** in the signal **B** with the background element **5** and with the transported products **2, 3** and/or **3'**. Instead of the above static tuning procedure, one can also proceed in a more flexible way. As illustrated in figure 1, a sorting system can operate in which the product stream is scanned and signals **B** are detected. Initially, all products are either accepted or rejected. By gradually adjusting the threshold values **g1** and/or **g2** a selection within the product stream will be made. One can continue adjusting the threshold values until clearly only the undesired products **3, 3'** are rejected. Figure 7 illustrates such a dynamic specification of the different signal levels and the corresponding adjustment of the threshold value(s).

[170] As indicated in the previous paragraphs, the invention aims at redefining **71** the reference level **70** of the detected signal **B** via signal processing in such a way that a new signal **D** is obtained that permits the products **2, 3 and/or 3'** to be distinguished from each other without the problems present in the state of the art. Preferably the signal **46** coming from the good products **2** and the signal **47** coming from the background element **5** will be shifted to a substantially equal signal level **71**, at least for the detected optical parameter.

[171] In order to determine which zone of the signal **B** corresponds to the background signal **47** and, therefore, in which zone one should replace the signal level **70** by a new suitable reference level **71** for the product signals **46,48 and 48'**, one can determine in the original signal **B** which zones **46,48 and 48'** indicate the presence of the products **2, 3, 3'** in the line scan and which zones **47**

indicate the absence of a product or, in other words, the presence of the background element **5** in the line scan.

[172] There are different embodiments to obtain a signal **C** based on one or more detected signals, of which the pulses are indicative of the location of a product **2, 3, 3'.** This location signal **C** thus contains information about both the desired products **2** and the undesired products **3, 3'.**

[173] Figures 11a-d illustrate a first embodiment. In the detected signal **B** one can distinguish zones corresponding to the background signal **47** from the zones corresponding to product signals **46, 48 and 48'.** As stipulated above, because the signal **47** originating from the background element **5** is chosen in such a way that it differs from the signals **46, 48 and 48'** of the products **2, 3, 3',** one can define one or more threshold values **g3 and g4** in the signal **B,** such that the signal levels **46, 48 and 48'** from the products **2, 3, 3'** are located outside these threshold values, e.g. on one side of this threshold value **g3** and the signal level **47** of the background element **5** is located within these threshold values, e.g. on the other side of this threshold value **g3.** Figure 6 illustrates the embodiment wherein one has determined two threshold values **g3/tmin** and **g4/tmax** containing the background signal **47.** Figure 11b illustrates an embodiment wherein one uses merely one threshold value **g3** to define the background signal **47** against the product signals **46, 48 and 48'.** In this signal analysis the signal peaks **46, 48 and 48'** and the threshold value **g3** are determined with respect to the original level **70** from the background signal **47.** Each peak **46, 48, 48'** that stretches past this threshold value **g3** thus indicates a presence of a product **2, 3, 3'.** One obtains a signal **C** having a pulse each time

a product **2, 3, 3'** is detected in the line scan. In figure 11c such a signal **C** is shown, whereby the product pulses **46, 48 and 48'** are already inverted compared to the original signal **B**. This signal **C** can also be a binary signal as shown in figure 11d. By converting the analogue signal into a digital signal one obtains a pulse train **C** of "1" and "0" pulses, whereby "1" indicates the presence of a product **2, 3, 3'** and "0" indicates the absence of a product **2, 3, 3'**.

[174] In this embodiment the same detected signal **B** is first used to generate a product location signal **C**, after that, as shown above, this detected signal **B** is combined with the signal **C** to shift the reference level as illustrated in figure 10a-d.

[175] Figures 12a-d give a schematic representation of different embodiments of this signal processing process. In the embodiment illustrated in figure 12a the detected signal **B** and threshold value **g3** are compared in a signal processing unit **60** to generate the product location signal. This signal **C** is then combined in a signal processing unit **61** with the detected signal **B** in order to determine which zones of this detected signal **B** match the signal **47** originating from the background element **5**. The reference level **70** of these background signals is then shifted to the desired level **71**, preferably the level **46** of the good products **2**, which thus generates a signal **D** with an adjusted reference level **71** that allows distinguishing signal peaks of the good products **2** from these of the undesired products **3, 3'** in the product stream. Due to the choice of the threshold values **g1** and **g2** one can distinguish between the signals **48, 48'** of the undesired elements in the product stream and the signals of the desired elements **2**.

[176] As discussed in the previous sections it is not required for the signals **C** and **B** to originate from the same detected signals **B**. Figure 12b illustrates a signal processing process in which a signal **C** is obtained based on a first signal **B**. This signal **C** is then being used for determining the position of the signal peaks **46, 48, 48'** within the second signal **B'**. The location signal **C** is obtained based on one or more first detected signals **B** after which this location signal **C** is being used to indicate the position of the products in one or more detected second signals **B'**. Both signals **B, B'** are detected during the same line scan because the light returning from the product stream is converted via suitable spatial and/or frequency filters into the distinct signals **B, B'**. As these signals are immediately correlated with each other, as mentioned earlier, one can combine them or apply information from one signal to another signal. In such a way one can use the product location obtained based on the first signal **B**, to indicate in another signal **B'** where the zones **16, 17** originating from the products **2, 3, 3'** and the zones **15** from the background element **5** are located.

[177] As illustrated in figures 12c and 12d the product location signal **C** can also originate from different signals **Bi**. By scanning the product stream in different ways, for instance with beams of light **45** that have different frequencies, or by analyzing the light that returns from the product stream in different ways, for instance by suitable spatial and/or frequency filters, one can obtain a more complete image of the product stream and avoid that a product remains unnoticed. First, one can combine these signals **Bi** in a signal processing unit **62** and transform **60** the combined signal **B** in a signal **C** as illustrated in figure 12c. The signal

processing unit **62** shall be able to combine these detected signals **Bi** in any possible manner: addition, subtraction, multiplication,… as shown in figure 12c. One can also first convert the different signals **Bi** into corresponding product location signals **Ci**, which are subsequently combined in a signal processing unit **62** into the desired product location signal **C**, as shown in figure 12d. Here the signal processing unit **62** will combine the different independent positioning signals **Ci** via an "OR" function so that no product location information is lost.

[178] Figures 13a-c illustrate another embodiment to obtain the product location signal **C**. In the embodiment illustrated by figures 11a-d, a signal **47** is generated during scanning by the background element **5**. This background signal can be a result of reflections of the incident optical signal **34**, or by fluorescence of this background element **5** due to this exposure. The background signal **47'** was captured in this embodiment together with the signals **46, 48, 48'** originating from the products **2, 3, 3'**. This line-up is also illustrated in figure 2.

[179] In the embodiment of figure 13a-c however, the background element 5 will not reemit any signal, but will only detect the immediate incidence of light on this background element **5**. The light **45** generated by the light source **29**, is being blocked by the products **2, 3, 3'** that are located between the background element **5** and the light bundle **45**. As illustrated in figure 13a and figure 2, when the products are scanned, they will emit a light signal **46, 48, 48'**, for example by reflection or by fluorescence. Only the light **34** that was not blocked by these products **2, 3, 3'** will strike at the posteriorly positioned background element **5**. When the background element **5** is provided with elements **57, 40** that allow

capturing and detecting the incoming light **34**, a signal **C** is obtained, that is indicative for the presence of products **2**, **3**, **3'** in the product stream for a given position of the scanning light bundle, or in other words, on a specific moment t(s) or yet in other words, for a specific position x (mm) according to the line scan. After all, the position of the light bundle **45** during the scan of the product stream is known, and it will therefore be no problem to correlate the time path of the signal **47'**, captured by the background element **5**, with the time path of the signals **46**, **48**, **48'**, originating from the products **2**, **3**, **3'** and thus with the position x (mm) of a product **2**, **3**, **3'** in the product stream. Figure 13c illustrates the obtained signal **C'**, this time only showing peaks where there is no product **2**, **3**, **3'** present in the scanned product stream. In figure 13c, these peaks are labeled by background reference **5**, namely the incidence of the light bundle **34** on the background element **5**. This analogue signal **C'** can also be transformed into a digital signal, thus a pulse train **C** of "1" and "0" signals is obtained, wherein "1" indicates the absence of a product **2**, **3**, **3'** and "0" indicates the presence of a product **2**, **3**, **3'**. The person skilled in the art will understand that this digital signal **C'**, if desired, can easily be transformed, using signal processing techniques, into a pulse train **C**, where "1" indicates the presence of a product **2**, **3**, **3'** and the "0" indicates the absence of a product **2**, **3**, **3'**, so that a signal as depicted in figure 11d is obtained.

[180] An advantage of the embodiment illustrated by figures 13 a-c en figures 3a and 3b, is that the background element **5** can be placed at a larger distance **d** from the product stream. This prevents the background element **5** from being polluted by the product stream. In

this set up, the only essential issue iswhether or not, for every immediate position of the moving light bundle, a signal on the background element **5** is obtained. Because one uses a concentrated light bundle **45**, such as a laser beam, the light will not substantially diverge once it has passed the product stream, even if the background element **5** is not being placed in direct proximity of the scanned product stream. Consequently, the solid angle at which the concentrated light bundle **34**, for an immediate position of the scanning light beam **45**, strikes the background element **5** is small enough to enable distinguishing, with sufficient accuracy, between the different positions of the moving light bundle in the scan line.

[181] Figure 14 gives a schematic presentation of this signal processing process, starting from the signal obtained as illustrated in figures 13a-c. The product location signal **C**, originating from the background element **5**, is being combined **61** with the detected signal **B** so as to determine which zones of this detected signal **B** correspond to a signal **47**, coming from the background element **5**. The level **70** of these background signals is shifted to the desired level **71**, preferably the level **46** of the good products **2**, thus generating a signal **D** with an adjusted reference level that allows distinguishing between the signal peaks of the good products **2** and those of the undesired elements **3, 3'** in the product stream. According to the choice of the threshold values **g1** and **g2**, the signals **48,48'** of the undesired elements in the product stream can be distinguished from the signals of the desired elements **2**, as illustrated in figures 10c-d.

[182] Figures 3a and 3b illustrate different embodiments of such a background element **5** that is capable of detecting uninterrupted light beams **34**.

[183] As illustrated in figures 12a-d, 14, the processing unit **41** comprises, according to the different embodiments, means **60, 62** for generating a location signal **C** based on one or more detected and converted signals **B**. Furthermore, this processing unit **41** comprises means **61** for genrerating, based on this location signal **C**, a signal **D** based on the same or other one or more detected and converted signals **B**, whereby the background level (70) of these latter signals is shifted to a new level (71) that allows for a clearer and more efficient distinction between the good products (2) from the bad products (3) in this signal **D**.

CLAIMS

1. A method for sorting a stream of products (2,3) in products to be accepted (2) and products to be rejected (3) comprising the steps of:

- moving through a scanning zone (28) the products to be sorted, supplied in a product stream extending over a certain width (W) and having a thickness of substantially a single layer of products,
- in this scanning zone (28), linear scanning across the width (W) of this product stream by one or more concentrated light beams (45), which illuminate, in the absence of products (2,3), a background element (5) positioned behind this product stream and extending over the width (W) of it, whereby this light beam (45) produces light signals (46,47,48) at these scanned products (2,3) and at this scanned background element (5),
- detecting these light signals (B:46,47,48) whereby these light signals are converted into electric signals,
- generating one or more control signals based on these converted signals (B:46,47,48) whereby these control signals allow making a selection between the scanned products to be accepted (2) on the one hand and the scanned products to be rejected (3) on the other hand, and
- sorting the product stream (2,3) by means of these one or more control signals,

characterized in that this method further comprises;

- choosing this background element (5) such that the corresponding detected light signal (47) differs in

at least one parameter from the light signals (46,48) of the products to be sorted (2,3) and

- wherein generating one or more control signals further comprises shifting the background level (70) of the converted signals (46,47,48) to a new signal level (71) chosen such that, in the thus obtained signal (D), the level of the signal (46) of a scanned product to be accepted differs from the signal level of the signal (48) of a scanned product to be rejected.

2. Method according to claim 1, wherein after shifting the background level (70) of the converted signals (46,47,48), the thus obtained signal (D) is compared to one or more threshold values (g1,g2), in this way generating the one or more control signals.

3. Method according to claim 2, wherein moving the background level (70) further comprises:

- generating a signal (C) which is indicative of the location (20,21) of the scanned products (2,3) in the detected and converted signals (B:46,47,48), and
- shifting the level (70) of the converted signals (B:46,47,48) at locations (22) other than these of the scanned products (2,3) as indicated by this location signal (C).

4. Method according to claim 3, wherein generating the location signal (C) further comprises:

- detecting and converting the light signals (B:46,47,48) originating from the scanned background element (5) and from the scanned products (2,3),
- in these converted signals (B:46,47,48) separating the signal (47) originating from the scanned

background element (5) from the signals (46,48) originating from the scanned products (2,3) thus obtaining a signal (C) indicative of the location of the scanned products (2,3).

5. Method according to claim 4, wherein distinguishing the signal (47) originating from the scanned background element (5) further comprises comparing the converted signals (B:46,47,48) to one or more threshold values ($g3/t_{min}$, t_{max}).

6. Method according to claim 3, wherein generating the location signal (C) further comprises detecting and converting that part (34) of the concentrated scanning light beam (45), which is passed by the products (2,3), thus obtaining a signal that is indicative of the location of the scanned products (2,3).

7. Method according to any one of claims 3, 4, 5 or 6, wherein the location signal (C) is a Boolean signal.

8. Method according to claim 7, wherein shifting the signal level (70) to a signal level (71) happens according to the formula: $D = BC + s(C \oplus 1)$, wherein B is the detected and converted light signals (46,47,48), s a real number chosen in function of the desired shift of the signal level, C is the location signal, and $\oplus$ is defined as the modulo-2 addition.

9. Method according to claim 7, wherein shifting the signal level (70) to a signal level (71) happens according to the following formula:

D = B when C = 1

D = 0 when C = 0

wherein B is the detected light signals (46,47,48), and C is the location signal (C).

10. Method according to claim 7, wherein comparing the thus obtained signal (D) to one or more threshold values

(g1,g2) only occurs at the location (20,21) of the scanned products (2,3) as indicated by the location signal (C).

11. Method according to any one of claims 1 to 10, wherein the background level (70) of the converted signals (46,47,48) is shifted towards a new signal level (71) corresponding to that of a product to be accepted (2).

12. Method according to any one of claims 1 to 11, wherein the location signal (C) is generated on the basis of one or more first detected signals (B) and wherein this location signal (C) is used for indicating the location of the products in one or more second detected signals (B').

13. Method according to claim 4, wherein the background element (5) consists of a surface that extends over the width (W) of the product stream, wherein said surface at least partially reflects the incident light (34).

14. Method according to claim 13, wherein the background element (5) has the shape of a cylindrical roller.

15. Method according to claim 6, wherein the background element (5) consists of means (57) to capture the incident light (34) and redirect it towards an opto-electrical convertor (40).

16. Method according to claim 15, wherein the background element (5) is an optical fiber with a grooved surface for capturing the incoming light (34).

17. Method according to claim 16, wherein the optical fiber consists of segments and wherein for each segment the orientation of these grooves with respect to the longitudinal direction of the optical fiber is chosen in function of the position of this segment along the width (W) of the product stream.

18. Method according to any one of claims 1 to 17, wherein the thus obtained signal (D) is priorly filtered such that the high-frequency transitions near the product zones (20,21) are flattened, thus generating a new filtered signal (E).

19. Method according to claim 18, wherein this filtering is achieved by means of an adaptive filter which is specifically tuned to flatten the transitions going from a product zone (20,21) to a background zone (22) and vice versa.

20. Method according to any one of claims 1 to 19, wherein the linear scanning of the product stream happens by means of a moving mirror, preferably a rapidly rotating polygonal mirror (30).

21. Method according to any one of claims 1 to 20, wherein the concentrated light beam (45) is a laser beam.

22. Method according to claim 21, wherein the product stream is scanned by several concentrated light beams (45), and wherin each light beam (45) has a separate frequency.

23. Method according to any one of claims 1 to 22, wherein the supply of the product stream can happen by means of a vibrating table (1), a conveyor belt or suchlike.

24. Method according to claim 23, wherein the products (2,3) are further supplied via a free-fall plate which guides these products(2,3) during their free fall towards the scanning zone (28).

25. Method according to any one of claims 1 to 24, wherein sorting the product stream (2,3) by means of these one or more control signals is achieved by controlling, by means of these one or more control

signals, a manifold of air valves (11) positioned across the width (W) of the product stream.

26. Method according to any one of claims 1 to 25, wherein the products (2,3) to be sorted are scanned starting from both edges (9,10) of the product stream.

27. Method according to any one of claims 1 to 26, wherein sorting the product stream (2,3) by means of these one or more control signals is combined with sorting based on color.

28. Method according to any one of claims 1 to 27, wherein generating one or more control signals by means of shifting the background level (70) of the converted signals (46,47,48) to a new signal level (71) is chosen such that, in the thus obtained signal (D), the signal level of the signal (46) of a scanned product to be accepted (2) distinguishes itself from the signal level of the signal (48) of a scanned product to be rejected (3), further comprising:

combining two detected and converted signals (A,A') in a two dimensional graph, wherein each point in that graph corresponds to a particular intensity level according to the path of the first signal (A) combined with a particular intensity level according to the path of the second signal (A'); the points which correspond with product to be accepted (2) are grouped in a first zone (51); the points corresponding to product to be rejected (3) are grouped in a second zone (52); the points corresponding to the background element (5) are outlined by a third zone (50); shifting the level (70) of the background signal (22,47) is effectively achieved by moving the third zone to a new location (n,n').

29. Method according to claim 28, wherein moving said third zone (50) happens by visualizing this zone in a graph displayed in a graphical user interface and subsequently dragging this zone to a new location.

30. Method according to claim 28 or 29, wherein this said new location (n,n') is chosen such that a separation can be made, by means of a separation plane (g'), between the first (51) and third zone (50') on the one hand and the second zone (52) on the other hand.

31. Method according to any one of claims 28, 29 or 30, wherein this two dimensional graph has an additional dimension showing the histogram of said signal combinations.

32. Method according to any one of claims 28, 29, 30 or 31, wherein more than two signals are combined with each other in a more dimensional graph.

33. Method according to any one of claims 28, 29, 30, 31 or 32, wherein all or at least one of said first, second and third zones can be determined by means of automatic clustering algorithms.

34. An apparatus (14) for sorting products according to the method of any of the preceding claims, characterized in that

- it at least consists of a supply system (1,4) transporting the products to be sorted in the form of a product stream extending over a width (W) consisting of a single layer of products, in a certain direction (27);
- means (9,10) to scan the products to be sorted (2,3) across the width (W) of the product stream, wherein these scanning means further comprise;

- means (29) to generate a concentrated light beam (45) and direct it towards the products (2,3) via optical means (30);
- means (40) to detect the returning light (46,47,48) and convert it to an electric signal;

- means (41) for generating control signals enabling the carrying out of a selection between the scanned products (2,3) based on said detected light (46,47,48); and
- means (11) for sorting the product stream (2,3) in function of said selection by means of said one or more control signals,

characterized in that the sorting apparatus (14) further comprises;

- a background element (5) chosen such that the corresponding detected light signal (47) differs in at least 1 parameter from the light signals (46,48) of the products to be sorted (2,3) and
- wherein the selection means (41) comprise means (60,61,62) for generating one or more control signals by shifting the background level (70) of the light signals (46,47,48) towards a new signal level (71) chosen such that, in the thus obtained signal (D), the signal level of the signal (46) of a scanned product to be accepted (2) distinguishes itself from the signal level of a signal (48) of a scanned product to be rejected (3).

35. A sorting apparatus according to claim 34, wherein the selection means (41) further comprise:

- means (60,62) for generating a location signal (C) based on one or more captured signals (46,47,48),

- means (61) to obtain a signal (D) based on this location signal (C) and based on these or other one or more captured signals (B), shifting the background level (70) in these last signals to a new level (71), which allows distinguishing between products to be accepted (2) and products to be rejected (3) in said obtained signal (D).

36. A sorting apparatus according to claim 34 or 35, wherein the selection means (41) further comprise means for comparing the obtained signal (D) to one or more threshold values (g1,g2), in this way generating the one or more control signals.

37. A sorting apparatus according to any one of claims 34, 35 or 36, wherein these selection means (41) further comprise filters to priorly filter the thus obtained signal (D) so that the high-frequency transitions near the product zones (20,21) are flattened, thus creating a new filtered signal (E).

38. A sorting apparatus according to claim 37, wherein this filtering operation is achieved by means of an adaptive filter specifically tuned for flattening the transitions from a product zone (20,21) to a background zone (22) and vice versa.

39. A sorting apparatus according to any one of claims 34 to 38, wherein the background element (5) consists of a surface that extends over the width (W) of the product stream, said surface reflecting the incident light (34) at least partially.

40. A sorting apparatus according to claim 39, wherein this background element (5) has the form of a cylindrical roller.

41. A sorting apparatus according to any one of claims 34 to 38, wherein this background element (5) consists

of means (57) for capturing the incident light (34) and redirecting it towards an opto-electrical convertor (40).

42. A sorting apparatus according to claim 41, wherein this background element (5) is an optical fiber with a grooved surface for capturing the incoming light (34).

43. A sorting apparatus according to claim 42, wherein this optical fiber consists of segments and wherein, for each segment, the orientation of these grooves with respect to the longitudinal direction of the optical fiber is chosen in function of the location of this segment along the width (W) of the product stream.

44. A sorting apparatus according to any one of claims 34 to 43, wherein the means (29) to generate the concentrated light beam (45) consist of a laser.

45. A sorting apparatus according to claim 44, wherein the means (30) to direct the concentrated light beam (45) towards the products (2,3) consist of optical means, more specifically a rotating polygonal mirror, for moving the concentrated light over the width (W) of the product stream.

46. A sorting apparatus according to any one of claims 34 to 45, wherein the means (41) to make a selection between the scanned products (2,3) in function of the observed light (46,47,48) consist of a signal processing platform based on digital electronic components, more specifically Field Programmable Gate Arrays and micro processors, or based on analogue electronic circuits, such as op-amp circuits, or a combination of analogue and digital processing units.

47. A sorting apparatus according to claim 34, wherein the means (11) for sorting the product stream (2,3) in function of said selection by means of these one or more

control signals, consist of a manifold of air valves, positioned transversely across the product stream.

48. A sorting apparatus according to any one of claims 34 to 47, wherein the means (40) for capturing the light (46,47,48) consist of an optical filter (36) rendering the detector device (40) sensitive to a particular light spectrum; in operational communication with a spatial filter (37) rendering the detector device (40) sensitive to a particular area of the returning light; in operational communication with both said filters (36,37) an opto-electrical convertor (38) converting the light into a corresponding electric signal (39).



Figure 1



Figure 2



Figure 3a



Figure 3b



Figure 4



Figure 5

Figure 6a



Figure 6b

Figure 6c

Figure 6d

Figure 6e

Figure 6



Figure 7a



Figure 7b

Figure 7



Figure 8

Figure 9a



Figure 9b



Figure 9c



Figure 9d



Figure 9e



Figure 9f



Figure 10a



Figure 10b



Figure 10c



Figure 10d



Figure 11a



Figure 11b



Figure 11c



Figure 11d



Figure 12a



Figure 12b



Figure 12c



Figure 12d



Figure 13a



Figure 13b



Figure 13c



Figure 14



Figure 15a



Figure 15b



D

Figure 15c



a



b



c



d

e