




US 20170099891A1

(19) **United States**(12) **Patent Application Publication**  
**Hull**(10) **Pub. No.: US 2017/0099891 A1**(43) **Pub. Date: Apr. 13, 2017**(54) **PROTECTIVE DEVICE FOR USE WITH A  
GLOVE****Publication Classification**(71) Applicant: **Summit Glove Inc.**, Minerva, OH (US)(72) Inventor: **James L. Hull**, Malvern, OH (US)(73) Assignee: **Summit Glove Inc.**(21) Appl. No.: **15/384,499**(22) Filed: **Dec. 20, 2016**(51) **Int. Cl.**  
**A41D 19/015** (2006.01)(52) **U.S. Cl.**  
**CPC . A41D 19/01505** (2013.01); **A41D 19/01529**  
(2013.01); **A41D 2600/20** (2013.01)(57) **ABSTRACT**

A protective device for use in a high temperature and liquid environment provides a glove integrally formed with a protective member in the thumb webbing region. The protective member is not readily detectable when viewing the outside of the glove. The protective member is cut resistant and constructed to protect a workman's hand as a sharp and hot object passes over the protective member contacting the outer surface of the glove.

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 14/624,047, filed on Feb. 17, 2015, which is a continuation-in-part of application No. 13/947,423, filed on Jul. 22, 2013.






FIG. 1




FIG.2








FIG.3









**FIG.6**









## PROTECTIVE DEVICE FOR USE WITH A GLOVE

### CLAIM OF PRIORITY

**[0001]** The present application is a continuation in part application of co-pending prior U.S. patent application Ser. No. 14/624,047, filed on Feb. 17, 2015, which is a continuation in part application of prior pending U.S. patent application Ser. No. 13/947,423, filed on Jul. 22, 2013, and claims priority thereto, the entirety of which is incorporated herein as if fully rewritten.

### BACKGROUND OF THE INVENTION

**[0002]** Technical Field

**[0003]** The present invention relates generally to protective coverings. More particularly, the present invention relates to protective coverings used as a glove for a hand. Specifically, the present invention provides a protective device to cover the webbing region located between a thumb and index finger (i.e., the thumb crotch) on a liquid proof heat resistant glove or mitten.

**[0004]** Background Information

**[0005]** Humans have enjoyed roasting chickens on a rotisserie since at least the middle ages. Modern rotisserie devices are provided in the form of ovens, often at supermarkets or grocery stores. The chickens cook on a rotisserie spit that rotates in the oven. The spit is extremely sharp as it has to pierce the chicken so the chicken may be affixed to the spit while it rotates in the oven. The rotisserie oven heats up to high temperatures, often in excess of 500 degrees, and cooks the chicken.

**[0006]** Liquid proof heat resistant gloves are often used in commercial settings, such as delicatessens, that cook their own rotisserie chickens. These gloves are designed to protect a worker's hands from the high heat and hot liquids (e.g., grease) that are associated with the rotisserie roasting of chicken. A deli worker dons these gloves prior to removing the chickens from the spit. To remove a chicken from a spit, a worker wearing the liquid proof heat resistant gloves removes the spit from the rotating oven. The worker then grasps the spit at one end. Ordinarily, a right handed person grasps the right end of the spit with his right hand and grasps adjacent the right end of the spit with his left hand in the glove. The user then pulls the spit using his right hand in a motion similar to drawing a sword, all while continuing to grasp the spit with his left hand. As the spit travels through the user's grasped hand, the chickens are released from the spit and fall into a desired container. A problem often arises when the worker removes the chickens because drawing the spit through the grasped glove has a tendency to cut the glove surface. The liquid proof heat resistant gloves often cost around one hundred dollars a pair and currently some delicatessens are replacing cut or damaged gloves every three days.

**[0007]** A search for prior art revealed a protector for a ski glove. One exemplary ski glove protector is manufactured by Kombi, Ltd. of Essex Junction, Vt., USA and sold commercially under the name of "Glove Protector" available at [www.skis.com](http://www.skis.com). This Kombi glove protector is constructed of natural leather and is for use with ski gloves to protect a cold weather ski glove from being torn by ski tow ropes while a wearer grasps the tow rope. This Kombi glove protector is for cold weather outdoor gear and would not

function in a protective manner at the high temperatures required for protecting a liquid proof heat resistant glove donned by a deli worker. The leather constructed Kombi glove would melt at the high temperature ranges in which the present invention operates.

**[0008]** Additionally, other protective devices used on gloves have been shown in the prior art. For example, U.S. Pat. No. 7,089,600 (the '600 patent) discloses a work glove including a fiber-made base glove with two reinforcement coats. A first reinforcement coat of compound rubber latex (essentially neoprene) extends over the crotch between the thumb and forefinger. A second reinforcement coat of compound rubber latex covers the fiber-made base glove except a back thereof includes the first reinforcement coat. Essentially, the first reinforcement coat is not covered by the second reinforcement coat on the back portion (i.e., dorsal portion or volar portion) of the glove. The first reinforcement coat and the second reinforcement coat extend along the length of the forefinger and cover the distal tip thereof. Thumb implementations of compound rubber latex may increase the stiffness of the base glove thereby reducing finger flexion or increasing finger strain and muscle strength to effectuate a similar flexion of a base glove free of the first and second reinforcement layers. Thus, while the crotch region may be covered with the first and second reinforcement layers, other drawbacks may continue to exist.

**[0009]** An additional attempt at protecting a portion of the hand is detailed in U.S. Pat. No. 4,873,998 (the '998 patent). The '998 patent provides a hardened plastic band formed from a thermos-plastic material that allows enough flexibility to move the hand, but also has a substantial density to protect the same. One drawback associated with the protective device of the '998 patent is that it likely could not be used in high-heat environments inasmuch as portions of the hand are exposed through the protective band.

**[0010]** An additional attempt at protecting the thumb-crotch region of the hand is detailed in U.S. P.G. Publication 2003/0140396 (the '396 publication). The '396 publication details a unilayer flexible textile performance fabric comprising a base fabric having at least one dissimilar high performance fiber interwoven into said base fabric. The '396 publication details that the weaving of the two distinct fibers together creates a single layer of material. The high performance fiber may be cut-resistant.

### SUMMARY

**[0011]** Thus, while the liquid proof heat resistant gloves exist for protecting the deli worker from the hot spit and hot liquids, a need exists to protect the expensive glove from the slicing motion of the spit as it pulled through the grasped hand of the deli worker.

**[0012]** In one aspect, an embodiment of the present disclosure may provide a protective device for use in a high temperature and liquid environment provides a glove integrally formed with a protective member in the thumb webbing region. The protective member is not readily detectable when viewing the outside of the glove. The protective member is cut resistant and constructed to protect a worker's hand as a sharp and hot object passes over the protective member contacting the outer surface of the glove

**[0013]** In another aspect, an embodiment of the present disclosure may provide a protective member for a thumb-crotch region of the glove that, prior to installing on a glove, is laid flat and the protective member comprises: a generally

rounded trapezoidal-shaped edge bounding a first surface opposite a second surface; a major axis associated with the generally rounded trapezoidal-shaped edge; a minor axis associated with the generally rounded trapezoidal-shaped edge; at least two opposing slits interrupting the generally rounded trapezoidal -shaped edge, wherein the at least two slits extend parallel to the minor axis and each terminates prior to the major axis, wherein the two slits are enable the protective member to bend around a thumb region of the glove and a forefinger region of the glove such that the major axis extends over thumb-crotch region of the glove.

**[0014]** In yet another aspect, an embodiment of the present disclosure may provide a protective member for a thumb-crotch region of a glove comprising: a first surface facing towards a hand when donning the glove; a second surface opposite the first surface facing away from the hand when donning the glove; an edge bounding the first surface and the second surface; a major axis and a minor axis associated with the first surface, wherein the first surface is longer along the major axis than along the minor axis; and at least one slit interrupting the edge and the first surface, the at least one slit extending generally parallel the to the minor axis; wherein the at least one slit enables the protective member to bend around one of (a) a thumb and (b) a forefinger such that the protective member extends over and protects the thumb-crotch region.

**[0015]** In yet another aspect, an embodiment of the present disclosure may provide a system for protecting an operator from a sharp object moving above a thumb-crotch region comprising: a hand from an operator including at least the following bones: a first metacarpal bone, a second carpal bone, and a third metacarpal bone; a glove donned by the hand; a protective member attached to the glove spanning the thumb-crotch region; and a first edge of the protective member crossing over the second metacarpal bone at an angle in a range from 15° to 75°. This system may further comprises a second edge of the protective member crossing over the second metacarpal bone at an angle generally orthogonal to the first edge of the protective member. The system may further comprise a third edge of the protective member generally parallel with the second edge such that the protective member is generally shaped like a trapezoid when laid flat. The system may further comprise a terminal corner of the first edge positioned approximately directly above the third metacarpal bone. The system may further provide that the protective member defines two slits to enable the protective member to bend around a thumb region of the glove and around a forefinger region of the glove such that the major axis extends over the thumb-crotch region defined between the thumb region and the forefinger region.

#### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

**[0016]** A sample embodiment of the invention is set forth in the following description, is shown in the drawings and is particularly and distinctly pointed out and set forth in the appended claims.

**[0017]** FIG. 1 is an exploded top view of components that define a protective member for use with a liquid proof and heat resistant glove;

**[0018]** FIG. 2 is an assembled perspective view of the protective member;

**[0019]** FIG. 3 is a perspective view of an alternative embodiment of the protective member;

**[0020]** FIG. 4 is an exploded environmental view of the assembled protective member and a liner for a glove detailing the location where the protective member is attached to the liner;

**[0021]** FIG. 5A is a palmar-side view of the protective member attached to the liner;

**[0022]** FIG. 5B is a dorsal-side view of the protective member attached to the liner;

**[0023]** FIG. 6 is an operational view of the liner carrying the protective member being dipped into a bath of liquefied material which cures to form the outer layer of the glove;

**[0024]** FIG. 7A is a palmar-side view of the assembled liquid proof and heat resistant glove having a protective member extend over and around the thumb crotch of the glove in order to protect the same; and

**[0025]** FIG. 7B is a dorsal-side view of the assembled liquid proof and heat resistant glove having a protective member extend over and around the thumb crotch of the glove in order to protect the same.

**[0026]** Similar numbers refer to similar parts throughout the drawings.

#### DETAILED DESCRIPTION

**[0027]** Initially, the Inventors note that the present disclosure is a continuation-in-part application of U.S. patent application Ser. No. 14/624,047 (the '047 Disclosure) filed on Feb. 17, 2015, the entirety of which is incorporated herein as if fully re-written. The present disclosure touches upon additional subject matter to the aforementioned '047 Disclosure, namely, liquid proof and heat resistant gloves that include integrally formed protective members in, on, along, or extending over the thumb crotch or thumb webbing region of the glove. Since this is a continuation-in-part application of the '047 Disclosure, some similar structural nomenclature is used herein when referencing some portions of the glove. However, there may be some instances where structural nomenclature differs between similar elements and there may be other instances where nomenclature is similar between distinct elements relative to this application and the '047 Disclosure.

**[0028]** A protective member for protecting the thumb crotch region of a liquid proof and heat resistant glove is shown generally throughout FIG. 1 through FIG. 7B at 10. Protective member 10 may include a first portion 12, a second portion 14, and a third portion 16. As will be described in greater detail below, first portion 12, second portion 14, and third portion 16 are connected together to define a unique shape of protective member 10 to cover the thumb crotch region of a liquid proof and heat resistant glove. However, it is to be understood that protective member 10 may be formed as a unibody monolithic member and the regions described herein are to be understood as descriptive of locations relative to other portions of the protective device and are not necessarily independent structures.

**[0029]** FIG. 1 depicts an exploded top view of the first portion 12, the second portion 14, and the third portion 16 laid flat and separated from each other. When laid flat, the first portion 12 is generally trapezoidal in shape having rounded corners. In this embodiment, the first portion 12 may include a first edge 18 spaced apart and generally parallel to a second edge 20. First portion 12 may further include a third edge 22 extending between first edge 18 and second edge 20. First portion 12 may further include a fourth

edge 24 that is opposite and spaced apart from third edge 22 and extends between first edge 18 and second edge 20. The third edge 22 meets the first edge 18 at a rounded first corner 26. Additionally, third edge 22 meets the second edge 20 at a rounded second corner 28. The fourth edge 24 meets the first edge 18 at a rounded third corner 30. Additionally, the fourth edge 24 meets the second edge 20 at a rounded fourth corner 32. The aforementioned edges and corners bound an upwardly facing top surface 34 and a downwardly facing bottom surface 36.

[0030] FIG. 1 further depicts an imaginary longitudinal axis 38 (i.e., the major axis) perpendicularly intersecting an imaginary transverse axis 40 (i.e., the minor axis). The center 42 of first portion 12 is located where the longitudinal axis 38 intersects the transverse axis 40.

[0031] The first portion 12 defines an arcuate cutout region 44 by an arcuately concave edge 46 interrupting first edge 18. In one particular embodiment, the arcuately extending concave edge 46 intersects the imaginary longitudinal axis 38. However, in other embodiments, edge 46 may be located at other portions of first edge 18 to define a cutout region 44. Moreover, in another embodiment, the base, or lowermost portion of concave edge 46, which is closest to transverse axis 40, may intersect longitudinal axis 38.

[0032] First portion 12 may further define a first slit 48 and a second slit 50. The first slit 48 extends towards the longitudinal axis 38 from the third edge 22. The first slit 48 interrupts third edge 22 and is arranged generally parallel with transverse axis 40 when the first portion 12 is laid flat. In one embodiment, first slit 48 may be offset from transverse axis 40. In yet another embodiment, the first slit 48 is offset towards the first edge 18 relative to transverse axis 40. The second slit 50 extends towards the longitudinal axis 38 from the fourth edge 24 and interrupts the same. The second slit 50 is offset generally parallel to the transverse axis 40 and in one embodiment, the first slit 48 and the second slit 50 are coplanar and offset towards the first edge 18 from the transverse axis 40. In some implementations, the first portion 12 may be entirely continuous and uninterrupted for all regions of the first portion 12 offset towards the second edge 20 from the transverse axis 40.

[0033] The length of the first slit 48 and the second slit 50 is oriented generally parallel with the transverse axis 40. In one implementation, the length of the first slit 48 is equal to the length of the second slit 50. In this case, the length of the first slit 48 and the second slit 50 may be in a range from about 0.5 inches to about three inches. Moreover, in other implementations, the length of the first slit 48 is close to about 1.5 inches.

[0034] The first slit 48 is bound by a first slit first edge 52 and a first slit second edge 54. The first slit first and second edges 52, 54 are spaced apart and extend generally parallel to each other and are oriented generally parallel to the transverse axis 40 when protective member 10 is laid flat. First edge 52 meets edge 22 at a corner 56 that is positioned outwardly relative to the inner terminal end of first slit 48. Similarly, second edge 54 meets edge 22 outwardly from the terminal end of first slit 48 relative to the longitudinal axis 38 at a corner 58.

[0035] Second slit 50 is bound by a second slit first edge 60 and second slit second edge 62. The second slit first and second edges 60, 62 extend generally parallel and offset from each other and are also parallel to transverse axis 40. First edge 60 extends transversely from a corner 64 towards

the inner terminal end of second slit 50. Corner 64 is located where first edge 60 meets fourth edge 24 of the first portion 12. Second edge 62 extends transversely from a corner 67 inwardly towards an inner terminal end of second slit 50. Corner 67 is located where second edge 62 meets edge 24 of the first portion 12.

[0036] Reference is now made to the second portion 14 and the third portion 16 inasmuch as they are similarly shaped. Similar reference numerals are utilized for brevity. Each of the second portion 14 and third portion 16 are shaped generally similar to that of an isosceles triangle when laid flat. A first edge 66 is formed generally at a right angle to edge 68 defining a rounded corner 70. An arcuate edge 72 represents a hypotenuse between edge 66 and edge 68 relative to the rounded corner 70. Edge 66 and edge 68 are generally the same length. The arcuate edge 72 meets edge 66 at a corner 74. The arcuate edge 72 meets edge 68 at corner 76. The collective edges of second portion 14 and third portion 16 bound a first surface 78 which faces an opposite second surface 80. First surface 78 of second portion 14 and third portion 16 faces the same direction as top surface 34 of first portion 12. Second surface 80 of second portion 14 and third portion 16 faces the same direction as the bottom surface 36 of first portion 12. Generally, the second portion 14 may be considered as a first quarter-round shaped member having an arcuate edge, and two perpendicular edges meeting at a point, wherein the first quarter-round shaped member is adapted to be disposed within one slit formed by the first portion 12. Similarly, the third portion 16 may be considered a second quarter-round shaped member having an arcuate edge, and two perpendicular edges meeting at a point, wherein the second quarter-round shaped member is adapted to be disposed within an opposing slit on the first portion 12.

[0037] FIG. 2 depicts an assembled perspective view of the protective member 10. When assembled, the second portion 14 occupies the space between first slit first edge 52 and first slit second edge 54. The second portion 14 is oriented such that the rounded corner 70 is positioned closely adjacent the inner terminal end of first slit 48. The corners 56, 58 are spread from each other such that corner 56 is aligned proximate corner 74 on second portion 14. Corner 58 is aligned proximate corner 76 on second portion 14. The arcuate edge 72 flexes upwardly and defines an uppermost apex 82. Edge 66 is aligned such that it runs approximately collinearly with edge 52. Edge 68 is aligned such that it runs approximately collinearly with edge 54. The second portion 14 may be joined to the first portion 12 in any manner of known chemical, or mechanical, or non-chemical, and non-mechanical joining methods. Some exemplary mechanical manners of joining the first portion 12 with the second portion 14 include stitching or other sewing techniques. Exemplary chemical manners in which the first portion 12 may be joined to the second portion 14 include adhesive glues or thermal welding.

[0038] The third portion 16 is positioned in a similar manner such that it occupies space between second slit first edge 60 and second slit second edge 62. Rounded corner 70 of third portion 16 is positioned proximate the innermost terminal end of second slit 50. Edge 66 is closely aligned with edge 60 and edge 68 is closely aligned with edge 62. Moreover, corner 64 is aligned with corner 74 of third portion 16, and corner 67 is generally proximate corner 76 of third portion 16. Arcuate edge 72 is flexed upwardly to

define apex **82** which is at a height similar to that of apex **82** on second portion **14**. Inasmuch as the inner terminal ends of the first slit **48** and the second slit **50** are spaced apart, a region **84** is defined on the first portion **12** between second portion **14** and third portion **16**. First portion **12** may be folded such that the region **84** is positioned above edge **18** and edge **20** on first portion **12**. As will be described in greater detail below, region **84** will extend over the thumb crotch region of a person donning the glove such that the region of first portion **12** offset to one side of region **84** extends over the palmar area of a hand and the opposite region of the first portion **12** and opposite region **84** extends over the dorsal side of a hand.

**[0039]** FIG. 3 depicts an alternative embodiment of a protective member for use with a liquid proof and heat resistant glove and is shown generally at **10A**. Protective member **10A** is similar to protective member **10** inasmuch as it fits over the thumb crotch region to protect the person wearing the glove, however it is formed from a monolithic unibody material. Protective member **10A** may be molded in a manner such that its shape is similar to the assembled protective member **10** depicted in FIG. 2. Protective member **10A** includes a first region **85A** that is configured to fit over the palmar region of the wearer's hand when worn. A second region **87A** of protective member **10A** is configured to lie above the dorsal (or volar) region of a user's hand when donning the glove. In this scenario, the protective region **84A** is positioned over the thumb crotch **104** region of the user's hand.

**[0040]** The protective member **10**, **10A** of the present disclosure can be formed from a variety of materials configured to withstand a sharp object passing over top surface **34** thereof. Protective member **10** or **10A** may be formed from a hardened plastic or polymer, however other materials may be utilized. Two alternative materials that may be used to form protective member **10** or **10A** are an aramid or a para-aramid synthetic fiber. One exemplary para-aramid material is sold under the name Kevlar® manufactured by the E. I. du Pont de Nemours and Company of Wilmington, Del. A further contemplated alternate material that may be used to form the protective member **10**, **10A** is chainmail. Protective member **10**, **10A** is adapted to withstand melting, ignition, and combustion in air at standard reference conditions, at temperatures of at least 500 degrees Fahrenheit, and perhaps able to withstand higher temperatures up to 1000 degrees Fahrenheit.

**[0041]** In accordance with the present disclosure, the protective member **10**, **10A** is configured to be formed within a glove, as will be described in greater detail below, in order to protect the user who has donned the glove from a hot, sharp, elongated member such as a blade passing over the thumb crotch region of the glove. While it is to be understood that this protective member **10**, **10A** is integrally molded within the glove such that it is positioned between a liner and an outer surface of liquid proof and heat resistance material (i.e., sandwiched between the inner liner and the outer surface), it is entirely possible for the protective member to be attached externally to the glove as previously described in the parent disclosures from which this disclosure is a continuation in part.

**[0042]** FIG. 4 is an exploded view of the palmar side of a right handed glove liner **90**. The liner **90** defines a thumb sleeve **92**, an index finger or forefinger sleeve **94**, and three other finger sleeves **96**, **98**, and **100**. The liner **90** may be

formed of liner material described in the parent disclosures or from another material as one having ordinary skill in the art would understand. One non-limiting exemplary material includes cotton twill, which provides for easy donning and doffing.

**[0043]** The liner **90** defines a region to be protected by the protective member **10**, **10A** and is shown generally by stippling/shading and identified generally at **102**. The region to be protected **102** includes the thumb crotch **104**. Region to be protected **102** includes a forefinger boundary edge **105** that extends along a portion of the forefinger sleeve **94** and covers the knuckle joint where the forefinger proximal phalange bone meets the metacarpal bone of the forefinger of the wearer's hand. The forefinger boundary edge **105** extends approximately 180° around the longitudinal axis associated with the forefinger. Additionally, the forefinger boundary edge **105** is disposed between the knuckle joint and the forefinger intermediate phalange bone. Stated otherwise, forefinger boundary edge **105** is positioned proximally relative to the distal tip of the forefinger sleeve **94**.

**[0044]** The region to be protected **102** further includes a thumb boundary edge **107** that extends along a portion of the thumb sleeve **92** and covers a portion of the knuckle joint where the proximal thumb phalange bone meets the metacarpal bone of the thumb. The thumb boundary edge **107** extends approximately 180° around the longitudinal axis associated with the thumb. Additionally, the thumb boundary edge **107** is disposed between the knuckle joint and the thumb distal phalange bone. Stated otherwise, thumb boundary edge **107** is positioned proximally relative to the distal tip of the thumb sleeve **92**.

**[0045]** The region to be protected **102** extends around and over the thumb crotch **104** such that the region to be protected **102** partially covers a palmar portion and partially covers a dorsal portion of the wearer's hand. With respect to the palmar side, the region to be protect **102** includes a palmar first edge boundary **106**, a palmar second edge boundary **108**, and a palmar third edge boundary **110**.

**[0046]** For the following discussion, some anatomical terms are utilized to identify locations of components of the present disclosure relative to anatomical positions. Components of the present disclosure that are closer to the radius bone of the forearm are referred to herein as "radial" or "radially" relative to other components. Components of the present disclosure that are closer to the ulna bone of the forearm are referred to herein as "ulnar" or "ulnarly" relative to other components.

**[0047]** The palmar first edge boundary **106** extends ulnarly from an angled orientation with the forefinger boundary edge **105**. The ulnar-directed extension of the palmar first edge boundary **106** is positioned above the third metacarpal bone (related to the middle finger). The palmar first edge boundary **106** crosses over the third metacarpal bone at an angle between 15° and 75°. In one particular implementation, the palmar first edge boundary **106** crosses over the third metacarpal bone at an angle of about 60° relative to horizontal. The ulnar-directed extension of the palmar first edge boundary **106** terminates proximally above the fourth metacarpal bone (related to the ring finger).

**[0048]** The palmar second edge boundary **108** extends radially from the terminal end of the palmar first edge boundary **106**. In one implementation, the palmar second edge boundary **108** meets the palmar first edge boundary **106** at a rounded approximate 90° angle. The radial-directed

extension of the palmar second edge boundary **108** is positioned above the third metacarpal bone proximal from the palmar first edge boundary **106**. The radial-directed extension of the palmar second edge boundary **108** terminates proximally above the proximal base of the first metacarpal bone (related to the thumb).

**[0049]** The palmar third edge boundary **110** meets the terminal end of the palmar second edge boundary **108** at a rounded approximate 90° angle. The palmar third edge boundary **110** extends distally above the longitudinal axis of the first metacarpal bone. The palmar third edge boundary **110** meets thumb boundary edge **107** above the proximal thumb phalange and proximal relative to the distal thumb phalange.

**[0050]** The aforementioned region to be protected **102** has been described by the respective edge boundaries with respect to the palmar side of the hand, however the region to be protected **102** is to be understood as being similarly shaped on the dorsal side of the hand, and the generally mirrored shape on the dorsal side is not repeated herein for brevity.

**[0051]** As depicted in FIG. 5A, the protective member **10** connects with the liner **90** such that the protective member **10** is positioned directly above the region to be protected **102**. More particularly, a first protecting region **85** of protective member **10** is positioned to protect at least a portion of the palmar side of the wearer's hand. As such, when the protective member **10** is attached to the liner, certain components are positioned relative to the wearer's hand.

**[0052]** In one implementation, the protective member **10** is connected with the liner in any known chemical manner, mechanical manner, or non-chemical and non-mechanical manner. For example, the protective member **10** may be chemically adhered or bonded with the liner **90**, or the protective member **10** may be mechanically fastened with the liner **90**.

**[0053]** With the protective member **10** attached to the liner **90**, the third edge **22** lies directly above the palmar first edge boundary **106** such that the third edge **22** extends ulnarly above the third metacarpal bone at an angle between 15° and 75°. The corner **28** is positioned closely adjacent to directly above the center of the third metacarpal bone. The second edge **20** extends over the second metacarpal bone aligned with palmar second edge boundary **108**. The fourth edge **24** is aligned with palmar third edge boundary **110** such that the fourth edge **24** extends distally above the longitudinal axis of the first metacarpal bone. The edge **72** on the third portion **16** is aligned with the thumb boundary edge **107** above the proximal thumb phalange and proximal relative to the distal thumb phalange and extends 180° around the ulnar-facing side of the longitudinal axis of the thumb sleeve **92**. On the other side of the protective member **10**, the edge **72** of the second portion **14** is aligned with forefinger boundary edge **105** to extend 180° around the radius-facing side of the forefinger. This alignment positions the protecting region **84** directly above and over the thumb crotch **104** of liner **90**.

**[0054]** As depicted in FIG. 5B, a second protecting region **87** of protective member **10** is positioned to protect at least a portion of the dorsal side of the wearer's hand. Namely, the third edge **22** extends ulnarly at an angle between 15° and 75° crossing over the third metacarpal bone. The first edge **18** extends radially at an angle generally orthogonal to that of the third edge **22**. As such, the first edge **18** crosses over the second metacarpal bone at an angle equal to 90° less the

angle of the third edge **22**. Thus, if the third edge **22** crosses the third metacarpal at about 60° relative to horizontal, then the first edge **18** crosses the second metacarpal at about 30° relative to horizontal.

**[0055]** With respect to the dorsal side, the arcuate edge **46** defining cutout region **44** assists with the flexibility and bending of protective member **10** during its use. As indicated previously in the parent references (from which this is a CIP), the liquid proof and heat resistant glove carrying protective member **10** is preferably used in a delicatessen for removing rotisserie chickens from a rotisserie spit. A deli worker dons these gloves prior to removing the chickens from the spit. To remove a chicken from a spit, a worker wearing the liquid proof heat resistant gloves removes the spit from the rotating oven. The worker then grasps the spit at one end. Ordinarily, a right handed person grasps the right end with his right hand and grasps adjacent the right end of the spit with his left hand in the glove. This spit is then positioned above the thumb-crotch region of the left-hand glove. The user then pulls the spit using his right hand in a motion similar to drawing a sword, all while continuing to grasp the spit with his left hand. As the spit travels over the left-hand thumb crotch region through the user's grasped hand, the chickens are released from the spit and fall into a desired container. The protective member **10** protects the user's hand during this motion.

**[0056]** FIG. 6 depicts one exemplary method of manufacture for the glove carrying protective member **10**. After the protective member **10** has been connected to the liner **90**, as described above, the liner may be dipped into a liquefied bath of glove material. This effectively seals the protective member **10** between the liner **90** and an outer surface material layer **112**. The outer surface material layer **112** is liquid proof and heat resistant as one having skill in the art would understand, and when cured defines an assembled glove **114**.

**[0057]** FIG. 7A and FIG. 7B represent an assembled liquid proof and heat resistant glove **114** in accordance with the present disclosure. The protective member **10** is shown in dashed-lines representing that it is secured and sealed below the outer surface material layer **112** and protects the thumb crotch of the same. However, while protective member **10** is sealed within the glove between the inner liner and the outer surface material **112**, it may be visually undetectable.

**[0058]** In the foregoing description, certain terms have been used for brevity, clearness, and understanding. No unnecessary limitations are to be implied therefrom beyond the requirement of the prior art because such terms are used for descriptive purposes and are intended to be broadly construed.

**[0059]** Moreover, the description and illustration set out herein are an example and the invention is not limited to the exact details shown or described.

What is claimed is:

1. A system for protecting an operator from a sharp object moving above a thumb-crotch region comprising:
  - a glove donned by a hand including at least the following bones: a first metacarpal bone, a second metacarpal bone, and a third metacarpal bone;
  - a protective member attached to the glove spanning the thumb-crotch region; and
  - a first edge of the protective member crossing over the second metacarpal bone at an angle in a range from 15° to 75°.

2. The system of claim 1, further comprising:  
a second edge of the protective member crossing over the second metacarpal bone at an angle generally orthogonal to the first edge of the protective member.
3. The system of claim 2, further comprising:  
a third edge of the protective member generally parallel with the first edge such that the protective member is generally shaped like a trapezoid when laid flat.
4. The system of claim 1, further comprising a second edge of the protective member positioned ulnarly from the first edge.
5. The system of claim 1, further comprising a first region on the protective member positioned within a palmar region on the glove, and a second region on the protective member positioned within a dorsal region on the glove.
6. The system of claim 1, further comprising:  
a terminal corner of the first edge positioned approximately directly above the third metacarpal bone.
7. The system of claim 1, wherein the protective member defines two slits to enable the protective member to bend around a thumb region of the glove and around a forefinger region of the glove such that a major axis associated with the protective member extends over the thumb-crotch region defined between the thumb region and the forefinger region.
8. The system of claim 1, further comprising an outer layer and an inner liner of the glove, wherein the protective member is positioned intermediate the outer layer and inner liner.
9. A protective member for a thumb-crotch region of a glove comprising:  
a first surface facing towards a hand when donning the glove;  
a second surface opposite the first surface facing away from the hand when donning the glove;  
an edge bounding the first surface and the second surface;  
a major axis and a minor axis associated with the first surface, wherein the first surface is longer along the major axis than along the minor axis; and  
at least one slit interrupting the edge and the first surface, the at least one slit extending generally parallel to the minor axis; wherein the at least one slit enables the protective member to bend around one of (a) a thumb and (b) a forefinger such that the protective member extends over and protects the thumb-crotch region.
10. The protective member of claim 9, further comprising a terminal end of the at least one slit terminating prior to the major axis.
11. The protective member of claim 10, further comprising:  
a first quarter-round shaped member having an arcuate edge, and two perpendicular edges meeting at a point.
12. The protective member of claim 11, wherein the first quarter-round shaped member is disposed within the at least one slit such that the point is closely adjacent the terminal end of the at least one slit.
13. The protective member of claim 12, further comprising a union of one of the two perpendicular edges of the quarter-round shaped member with a portion of a first slit edge defining a portion of the at least one slit.
14. The protective member of claim 9, further comprising:  
a second slit diametrically opposite the at least one slit relative to the major axis, and a terminal end of the second slit terminating prior to major axis.
15. The protective member of claim 14, further comprising:  
a first quarter-round shaped member having an arcuate edge, and two perpendicular edges meeting at a point, wherein the first quarter-round shaped member is disposed within the at least one slit; and  
a second quarter-round shaped member having an arcuate edge, and two perpendicular edges meeting at a point, wherein the second quarter-round shaped member is disposed within the second slit.
16. The protective member of claim 9, in combination with a liquid proof heat resistant glove, wherein the combination comprises:  
a fixedly attached relationship of the protective member to the glove such that the protective member extends around the thumb-crotch region of the glove.
17. The combination of claim 16, further comprising:  
an outer layer of the glove and an inner layer of the glove, wherein the protective member is fixedly attached intermediate the outer layer and the inner layer of the glove.
18. A protective member for a thumb-crotch region of a glove, wherein when prior to installing the protective member on the glove, the protective member when laid flat comprises:  
a generally trapezoidal-shaped edge bounding a first surface adapted to face a hand of an operator which is opposite from a second surface adapted to face away from the operator;  
a major axis associated with the generally trapezoidal-shaped edge;  
a minor axis associated with the generally trapezoidal-shaped edge;  
wherein the protective member is formed from a material that is harder than that of the glove to which the protective member will be installed.
19. The protective member of claim 18, further comprising:  
at least two opposing slits interrupting the generally trapezoidal-shaped edge, wherein the at least two slits extend parallel to the minor axis and each terminates prior to the major axis, wherein the two slits enable the protective member to bend around a thumb region of the glove and around a forefinger region of the glove such that the major axis extends over a thumb-crotch region defined between the thumb region and the forefinger region.
20. The protective member of claim 18, further comprising:  
a first portion of the generally trapezoidal-shaped edge offset to a first side of the minor axis;  
a second portion of the generally trapezoidal-shaped edge offset to a second side of the minor axis opposite the first side;  
wherein the first arcuate portion, when fixedly attached to the glove's dorsal side, extends to at least a middle metacarpal region of the glove, and wherein the second arcuate portion, when fixedly attached to the glove's palmar side, extends to at least the middle metacarpal region of the glove.