

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 May 2008 (02.05.2008)


PCT

(10) International Publication Number
WO 2008/051683 A1

- (51) International Patent Classification:
B01L 3/02 (2006.01)
- (21) International Application Number:
PCT/US2007/080064
- (22) International Filing Date: 1 October 2007 (01.10.2007)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
11/552,384 24 October 2006 (24.10.2006) US
- (71) Applicant (for all designated States except US): **VIAFLO CORPORATION** [US/US]; 2 Wentworth Drive, Hudson, NH 03051 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **MATHUS, Gregory** [US/US]; 49 Deer Grass Lane, Concord, MA 01742 (US). **KELLY, Terrence** [US/US]; 165 Seventh Avenue, Lowell, MA 01854 (US). **COTE, Richard** [US/US]; 24 Rocky Dundee Road, Bolton, MA 01740 (US).
- (74) Agents: **SOLVESON, George, H.** et al.; Andrus, Scales, Starke & Sawall, LLP, 100 East Wisconsin Avenue, Suite 1100, Milwaukee, WI 53202-4178 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL,

[Continued on next page]

(54) Title: LOCKING PIPETTE TIP AND MOUNTING SHAFT



(57) Abstract: In one aspect, the invention relates to a pipette tip mounting shaft configuration and a disposable pipette tip having a matching configuration. The mounting shaft (12) includes a locking section (30) located above a lower sealing section (32). The locking section (30) has outwardly extending locking lobes located above a stop member (34) and a lower sealing section (32) located below the stop member (34). When the mounting shaft (12) is fully inserted into the collar (36) of the mating disposable pipette tip (14), the tip locks onto the mounting shaft (12). The bore of the pipette tip includes a circumferential shelf or shoulder separating its upper collar from the tip sealing area which is located below the circumferential shelf. The tip collar preferably includes a locking ring located at or near the upper opening for the mounting shaft (12). The dimensions of the collar, and in particular the distance between its circumferential shelf and the locking ring, are selected to match the dimensions of the mounting shaft (12) between the stop member (34) and the upper end of the locking lobes, thus locking the pipette tip (14) in a secure, reliable position and orientation while using ergonomic insertion and ejection forces. The locking lobes preferably include a ramp portion that gently flexes and distorts the pipette tip collar (36) out of round as the mounting shaft (12) is inserted in the pipette tip (14), rather than stretching the tip collar (36). The circumferential shelf on the pipette tip (14) between the tip collar (36) and the barrel (38) isolates the sealing area at the upper end of the barrel (38) from distortion, thus facilitating reliable sealing engagement between the lower sealing section (32) of the mounting shaft (12) and the sealing ring in the upper end of the barrel (38) of the pipette tip (14).

WO 2008/051683 A1



PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*

LOCKING PIPETTE TIP AND MOUNTING SHAFT

FIELD OF THE INVENTION

[0001] The invention relates to improvements in pipettes and automated liquid handling systems. More specifically, the invention relates to a configuration for pipette tip mounting shafts and disposable pipette tips that provides robust sealing engagement with low insertion and ejection forces as well as enhanced resistance to unintentional removal, and maintains the mounted tip in optimum position and orientation when the tip is mounted on the pipette tip mounting shaft.

BACKGROUND OF THE INVENTION

[0002] The use of disposable pipette tips with handheld pipettes and automated liquid handling systems is well known. Disposable pipette tips enable repeated use of such pipetting systems to transfer different fluids or different fluid samples without carryover contamination. Disposable pipette tips are normally formed of a plastic material, such as polypropylene, and have a hollow, elongated, generally conical shape. The upper end of the pipette tip typically includes a collar that is mounted to the tip mounting shaft on the pipette device. The mounting shaft includes an internal bore through which air is displaced in order to aspirate liquid sample into and dispense liquid sample from the pipette tip. The far end of the pipette tip has a small opening through which liquid sample is received into and dispensed from the barrel of the pipette tip.

[0003] Disposable pipette tips have historically relied on tapered fits between the mounting shaft and the pipette tip collar, as well as sealing rings on the inside circumference of the pipette tip collar, to secure and seal the pipette tips to the mounting shaft. In most cases, the fit between the mounting shaft and the disposable tip is achieved by pushing the tapered mounting shaft into the tapered pipette tip collar until it wedges into the tip. At this point, a seal is achieved between the tip collar and the mounting shaft as a result of crushing the sealing ring

and/or stretching the diameter of the collar. In addition to achieving a proper seal, it is also important that position and orientation of the mounted tip also be stable in the face of lateral momentum or slight knocking forces that are typical during normal use such as during touch-off on the sidewall of a vessel. In order to assure tip stability, users tend to jam the pipette mounting shaft into the tip with excessive force.

[0004] Various systems have been devised to provide proper sealing and stability without requiring excessive mounting and ejection forces. For example, the use of cylindrical mounting shafts and cylindrical tip collars lessens mounting and ejection forces. Also, it is well known to use a step within the pipette tip collar as a depth limiting means for the pipette mounting shaft. Even so, such systems typically require the force of an interference fit or stretching of the pipette tip collar to maintain stable engagement of the pipette tip and ensure a reliable seal of the collar against the mounting shaft.

[0005] A further approach is described in U.S. Patent Application Publication No. US 2005/0175511 A1 in which the pipette tip collar has inwardly projecting, cantilevered fingers that latch over a circumferential rim on the mounting shaft. In this approach, sealing is achieved by an O-ring on the mounting shaft that is located below the location of the latching engagement. Ejection of the tip is achieved by modifying the ejection mechanism on the pipette so that it can release the inwardly projecting fingers on the pipette tip before asserting pressure to eject the tip from the mounting shaft.

SUMMARY OF THE INVENTION

[0006] In one aspect, the invention relates to a pipette tip mounting shaft configuration and a disposable pipette tip having a matching configuration. In its preferred form, the pipette tip mounting shaft includes a locking section located above a lower sealing section. The locking section includes a lower stop member and two or more outwardly extending locking lobes located above the stop

member. The pipette tip collar locks onto the mounting shaft when mounting shaft is fully inserted into the collar of a mating pipette tip. The bore of the pipette tip includes a circumferential shelf or shoulder separating its upper collar from the sealing area of the tip located in the upper region of the tip barrel. The collar preferably includes a locking ring located at or near the upper opening of the collar. The dimensions of the collar, and in particular the distance between the circumferential shelf and the locking ring, are selected to match the dimensions on the mounting shaft between the stop member and the upper end of the locking lobes. The locking lobes preferably include a ramp portion that gently flexes and distorts the pipette tip collar out of round as the mounting shaft is inserted into the pipette tip collar. Due to relieved portions of the mounting shaft between the lobes, the tip collar flexes to distort out of round rather than stretch in order to accommodate the interference fit over the locking lobes. This configuration results in an ergonomic, over-center locking engagement. The feel of the engagement provides tactile feedback to the user of a hand-held pipette, in part, as a result of the flexing of the upper collar as the locking ring passes over the lobes on the mounting shaft into locking engagement. At the same time, the stop member on the mounting shaft limits penetration of the mounting shaft into the tip as the stop member engages the shelf in the tip, thus providing a clear indication that the tip is fully mounted

[0007] The lower sealing area on the mounting shaft extends below the stop member. The lower sealing section is preferably tapered in a frustoconical shape, but can be cylindrical, depending on the geometry of the matching pipette tip. Similarly, the pipette tip preferably includes a sealing ring in a sealing area located below the circumferential shelf at the upper end of the pipette tip barrel. The shape of the tip sealing area should match the shape of the lower sealing section of the mounting shaft. The circumferential shelf on a pipette tip isolates the distortion of the collar from the sealing area when the tip is mounted on the mounting shaft, thus maintaining the roundness of the sealing area (i.e. a circular circumference for the

inside surface of the pipette tip barrel) in which the sealing ring is located. This is important in order to facilitate reliable engagement of the sealing ring around the lower sealing section of the mounting shaft.

[0008] As the mounting shaft is pushed into the tip collar, the first point of contact is where the leading edge of the mounting shaft, i.e. the lower sealing section, enters through the circumferential shelf in the pipette tip and contacts the sealing ring. As the mounting shaft is further depressed into the pipette tip bore, sealing ring interference increases simultaneously as the ramp area of the lobes of the mounting shaft engages the locking ring on the tip collar to distort the upper portion of the collar out of round. As mentioned, while the overall insertion force is relatively light and ergonomic, the force increases noticeably and provides tactile feedback to the user that the tip is almost fully mounted. This increase in insertion force continues until the stop member on the mounting shaft engages the circumferential shelf on the pipette tip to abruptly stop further movement of the mounting shaft into the tip, at which point the lobes also snap engage under the locking ring in the collar bore. Thus alerting the user not to use additional, excessive force to mount the tip. These interrelated mounting conditions result in a secure stable mount with consistent sealing at the sealing ring. Alternatively, the initial engagement of the sealing ring can be staggered with respect to the engagement of the locking ring in order to lessen insertion force.

[0009] Moreover, the tip requires relatively low ejection force. When the pipette stripper sleeve pushes against the upper end of the tip collar, a relatively small ejection force is required to release the locking ring on the collar from the locking lobes on the mounting shaft. The flexing of the collar in its distorted shape when it is locked over the mounting shaft lobes stores energy. When the tip is released from the lobes, the combination of the pressure from the stripper and the release of the stored energy throw the tip from the mounting shaft, thereby facilitating convenient ejection of the tips from the mounting shaft after use.

[0010] In another aspect, the invention relates to the configuration of a disposable pipette tip in which a sealing area with a sealing ring is located below a circumferential shelf that separates and isolates the sealing area from the upper mounting collar. By moving the sealing function away from the collar or shelf area into the upper area of the barrel, the design limitations for the mounting configuration of the pipette tip collar is less restrictive. For example, in the cases of the preferred embodiment of the invention, the collar is flexed and distorted out of round when mounted on the mounting shaft. Locating the sealing area on the pipette tip below the circumferential shelf to isolate the sealing area from distortion facilitates this mounting arrangement.

[0011] These and other aspects, features and advantages of the invention are now described in greater detail with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] Fig. 1 is a perspective view of a handheld, electronic air displacement pipette incorporating the concepts of the present invention.

[0013] Fig. 2 is a perspective view showing a disposable pipette tip and a pipette tip mounting shaft in accordance with a preferred embodiment of the invention.

[0014] Fig. 3 is a side elevational view of the mounting shaft and pipette tip shown in Fig. 2.

[0015] Fig. 4 is a longitudinal cross-section taken along line 4-4 in Fig. 3.

[0016] Fig. 5 is a detailed view of the area encircled by line 5-5 in Fig. 4 showing an upper locking collar, sealing area and circumferential shelf of the disposable pipette tip illustrated in Fig. 2.

[0017] Fig. 6 is a detailed view of the area encircled by line 6-6 in Fig. 4 showing a locking section, sealing section and stop member of the mounting shaft shown in Fig. 2.

[0018] Fig. 7 is a side elevational view showing the mounting shaft being inserted into the disposable pipette tip.

[0019] Fig. 8 is a longitudinal cross-section taken along line 8-8 in Fig. 7.

[0020] Fig. 9 is a detailed view over the area encircled by line 9-9 in Fig. 8 showing insertion of the mounting shaft into the pipette tip just prior to final engagement.

[0021] Fig. 10 is a detailed view similar to Fig. 9 showing full insertion of the mounting shaft into the pipette tip.

[0022] Fig. 11 is a view taken along line 11-11 in Fig. 10 illustrating the pipette tip collar and locking ring being distorted out of round when the pipette tip is fully mounted onto the mounting shaft.

[0023] Fig. 12 is a view similar to Fig. 10 illustrating the pipette tip being stripped off the mounting shaft.

DETAILED DESCRIPTION OF THE INVENTION

[0024] Fig. 1 illustrates a handheld, electronic air displacement pipette 10 that incorporates a pipette mounting shaft 12 and a disposable pipette tip 14 constructed in accordance with the preferred embodiment of invention. The pipette 10 includes a housing 16 designed to be held in the palm of the user. Internal components of the pipette (not shown) drive a piston that extends through a seal assembly to displace air within an aspiration and dispensing cylinder. The pipette mounting shaft 12 is threaded or otherwise attached to the lower end of the pipette such that it is in fluid communication with the aspiration and dispensing chamber. The attachment of the mounting shaft to the pipette is not particularly relevant to the concepts of the invention, and is well known in the art. Button 18 is provided for the user to instruct the electronic pipette to aspirate and dispense. The pipette 10 also includes a lever 20 that is actuated in the direction of arrow 22 to move an ejection mechanism sleeve 24 downward in order to eject the disposable pipette tip 14 from the mounting shaft 12.

[0025] While the invention is shown and described with respect to its use on a handheld, electronic air displacement pipette 10, the invention is also useful in connection with other types of handheld pipettes, as well as automated liquid handling machines using dispensable pipette tips. For example, the ergonomic features provided by the invention are particularly useful for handheld manual pipettes as well as electronic pipettes. In addition, features of the invention that relate to the security and stability of the engagement of the pipette tip to the mounting shaft are quite useful for automated liquid handling systems as well as handheld pipettes.

[0026] As shown in Fig. 2, the mounting shaft 12 preferably has threads 26 for attaching the mounting shaft 12 to the lower end of the aspiration and dispensing cylinder (not shown). As discussed herein, the dimensions of the mounting shaft 12 match the dimensions of the pipette tip 14 so that only pipette tips 14 with the proper dimensions can fit onto the mounting shaft 12. In order to use pipette tips with different bore dimensions in the collar and sealing region, it is necessary to replace the mounting shaft 12 and/or the tubular stripper shaft 24 with one having appropriate dimensions.

[0027] Referring now to Figs. 2-6, the mounting shaft 12 contains a central bore 28 that provides for air passage between the aspiration and dispensing cylinder in the pipette 10 and the pipette tip 14, as is well known in the art. The mounting shaft 12 includes an upper locking section 30, a lower sealing section 32, and a stop member 34 located between the locking section 30 and the lower sealing section 32. The pipette tip 14 generally consists of a collar 36, a barrel 38 and a circumferential shelf 40 that extends around the inside bore of the tip 14 and connects the lower end of the collar 36 to the upper end of the barrel 38. The upper end of the collar 36 has an opening 42 to receive the pipette mounting shaft 12. The lower end of the barrel 38 has a small opening 44 through which liquid is aspirated into the tip barrel 38 and dispensed from the tip barrel 38 during normal operation of the pipette 10. Support ribs 46 extend downward on the outside

surface of the pipette tip 14 from the collar 36. The support ribs 46 function to hold the tip 14 or an array of tips 14 in a tray or the like for subsequent use, as is known in the art.

[0028] The internal surface of the pipette tip 14 is now described in more detail, referring in particular to Fig. 5. The inside surface of the collar 36 preferably includes a circumferential locking ring 48, although aspects of the invention can be accomplished without the locking ring 48. The locking ring 48 is preferably located at or slightly below the opening 42 for the collar 36. The locking ring 48 extends inward from the inside wall of the collar 36 a slight amount, preferably in the range of .001 inches to .010 inches, in order to provide a locking fit over the lobes 50 on the mounting shaft 12. It is important, however, that the locking ring 48 not extend so far inward to interfere with efficient and effective ejection of the disposable tip 14 from the mounting shaft 12 after use. The locking ring 48 can optionally include one or more air bleeds 52. The air bleed can optionally be incorporated on the mounting shaft 12 instead of, or in addition to), the locking ring 48 of the pipette tip. The primary purpose of such air bleeds is to prevent aspiration of liquid in the case that an improperly sized pipette tip is mounted onto the mounting shaft. This is important in order to reduce the chance of contamination of the pipette cylinder, for example, when a large volume of liquid is accidentally aspirated into a tip designed for a small volume of liquid.

[0029] The inside surface of the collar 36 is preferably tapered or slightly frustoconical, but can also be cylindrical in accordance with the invention. Preferably, the taper is between 0° and 10°. In any event, horizontal cross-sections through the main section of the collar 36 are preferably circular.

[0030] The upper portion 39 of the barrel 38 is the sealing area for the pipette tip 14. A circumferential sealing ring 54 preferably extends inward from the inner surface of the upper portion 39 of the barrel 38 in the sealing area. Alternatively, sealing can be accomplished without sealing ring 54. The sealing area 39 in the barrel 38 is preferably frustoconical, but can also be substantially

cylindrical, in accordance with the invention. The preferred taper is between $1/2^\circ$ and 4° . Preferably, the sealing ring 54 extends .003 inches inward from the surface of the barrel 38, and its longitudinal thickness is .010 inches.

[0031] The circumferential shelf 40 of the pipette tip 14 connects the lower portion of the collar 36 to the upper portion 39 of the barrel 38. The shelf 40, as shown in the Figures, is angular and continuous around the inside circumference of the tip 14. The shelf 40 need not be angular, however, and can for example be horizontal. The shelf 40 serves to separate the locking region or collar 36 of the pipette tip 14 from the sealing area 39 of the pipette 14 in the upper portion of the barrel 38. As best illustrated in Fig. 11, the collar 36 is distorted out of round when the mounting shaft 12 is fully inserted into the pipette tip 14. The shelf 40 serves to isolate the sealing area in the upper portion of the barrel 38 from this distortion, thereby facilitating an effective seal of the sealing ring 54 against the sealing section 32 of the mounting shaft 12. It also serves to accurately locate the tip on the mounting shaft. With multiple channel devices, the tip shelf insures the same vertical mounting distance from tip to tip. This allows precise and consistent tip position during pipetting.

[0032] It is contemplated that pipette tips 14 manufactured in accordance with the invention will be typically made of molded plastic, normally polyethylene or polypropylene with or without various additives, as is known in the art. This design embodies a locking ring 48 and sealing ring 54 that help the injection molding process. They serve as a way to keep the molded tip on the core of the mold instead of using a puller ring for this process.

[0033] Referring now in particular to Figs. 2, 3, 4 and 6, the sealing section 32 of the mounting shaft 14 is tapered in an amount corresponding to the sealing area 39 of the pipette tip in the upper portion of the pipette tip barrel 38. The outer surface of the sealing section 32 of the mounting shaft 12 forms an interference fit with the sealing ring 54 on the pipette tip 14 to provide an air-tight seal in order to effectuate accurate aspiration and dispense of liquid into and from the pipette tip

barrel 38. The locking section 30 of the mounting shaft preferably includes a central cylindrical stabilizing section 56, which is located immediately above and adjacent the stop member 34. When the pipette tip 14 is mounted on the mounting shaft 12, the central cylindrical stabilizing section 56 on the mounting shaft 12 helps to support the tip 14 in a stable straight orientation. One of the advantages of the invention is that the mating locking mechanism allows the tips 14 to be securely mounted in a consistently straight orientation. This allows the use of longer pipette tips 14, which can be particularly desirable in certain applications. The diameter of the mounting shaft 12 decreases at the stop member 34 between the central stabilizing section 56 and the upper portion of the sealing section 32 commensurate with the reduction in diameter of the matching pipette tip 14 at its circumferential shelf 40. As mentioned, this reduction is preferably in the range of about .004 to .040 inches. Note that it is not necessary that the cylindrical stabilizing section 56 and the stop member 34 be continuous around the circumference of the mounting shaft 12 inasmuch as the purpose of these components is to provide secure, stable locking engagement of the pipette tip 14 on the mounting shaft 12 and not to provide a seal. Above the cylindrical stabilizing section 56, the diameter of the mounting shaft 12 may or may not reduce slightly in order to provide clearance between the mounting shaft 12 and the collar 36 of the pipette tip 14. The top of the locking section 30 of the mounting shaft 12 preferably includes two or more locking lobes 50 spaced equally around the mounting shaft 12, as well as corresponding recessed areas 58 spanning between the locking lobes 50. The lobes 50 include relatively gently sloping inclined ramps 60. The preferred slope of the ramp 60 incline with respect to the vertical axis of the mounting shaft 12 is between 10° and 20°. The lobes 50 extend outward along the ramp 60 towards the top of the locking section 30 until the lobes 50 turn abruptly inward to form catch surfaces 62. The intersection between the ramp surface 60 and the catch surface 62 at the peak of each lobe 50 is preferably slightly rounded. At its peak, the lobes 50 preferably extend outward beyond the outer surface of the cylindrical stabilizing section 56,

although the exact preferred dimensions will depend on the amount of taper of the collar 36 in the corresponding matching pipette tip 14 as well as the tip wall thickness.

[0034] The mounting shaft 12 is preferably made from machined steel or machined or molded from chemically resistant plastic such as PEEK, and the specific dimensions are selected to correspond to the dimensions of the matching pipette tip 14. For example, the distance between the stop member 34 and the catch surfaces 62 of the lobes 50 of the mounting shaft 12 is selected to correspond to the distance between the circumferential shelf 40 and the locking ring 48 on the collar 36 of the pipette tip 14.

[0035] Referring now to Figs. 7-9, as the mounting shaft 12 is pushed into the tip 14, the first point of contact is when the leading edge of the sealing section 32 on the mounting shaft 12 enters through the circumferential shelf 40 on the pipette tip 14 and contacts the sealing ring 54. As the mounting shaft 12 is further inserted into the tip 14, the sealing ring 54 interference force against the sealing section 32 of the mounting shaft 12 increases. At the same time, the ramp area 60 of the lobes 50 begins to engage the upper portion of the tip collar 36. .

Alternatively, as mentioned above, the initial engagement of the sealing ring 54 can be staggered with respect to the engagement of the upper portion of the tip collar 36 in order to lessen insertion force. As the mounting shaft 12 is further inserted into the tip 14, the ramps 60 on the lobes 50 push against the locking ring 48 on the collar 36 of the tip 14 and gently flex the collar 36 and distort it out of round. The recessed areas 58 on the mounting shaft 12 provide ample clearance for the straightening of the collar 30 that occurs between the lobes 50. The intent is for the lobes 50 to flex the collar 36 out of round rather than stretch the collar 36.

[0036] Referring now to Figs. 10 and 11, as the mounting shaft 12 is fully inserted into the pipette tip collar 36, the stop member 34 on the mounting shaft engages the circumferential shelf 40 on the pipette tip 14, thus preventing further movement of the shaft 12 into the tip 14. At the point of engagement, the locking

ring 48 on the inside surface of the tip collar 36 more or less simultaneously snaps over the lobes 50 on the mounting shaft 12. Thus, the pipette tip 14 is securely locked into place onto the mounting shaft 12 with there being a positive engagement between the stop members 34 on the mounting shaft 12 and the circumferential shelf 40 on the pipette tip 14 on the one hand, and the catch surface 62 of the lobes 50 on the mounting shaft 12 and the underside of the locking ring 48 of the tip collar 36 on the other hand. Fig. 11 shows a cross-sectional view looking down on the tip collar 36 being locked onto the mounting shaft 12 over the lobes 50. The collar 36 is flexed and distorted to an out of round condition. Note that phantom line 70 indicates the outside surface of the collar 36 opening in its preferred round state before being mounted on the mounting shaft 12. Phantom line 72 indicates the position of the inside surface of the locking ring 48 of the collar 36 in its preferred round state before being mounted over the lobes 50 on the mounting shaft 12. While the mounted collar 36 is flexed and distorted out of round, the circumferential shelf 40 below the collar 36 remains circular due to its structural integrity.

[0037] By flexing and distorting the tip collar 36 rather than stretching the collar 36 in order to mount the tip 14, the required insertion force is relatively small as compared to other designs which require tight interference fits or stretching of the tip collar. The user senses that full engagement is near as the mounting shaft 12 is inserted into the tip 14 because of the slightly increasing resistance of the interference with the sealing ring 54 on the tip and the increasing diameter of the ramp lobes 50. Definite feedback of full engagement occurs when the stop member 34 engages the circumferential shelf 40 and the locking ring 48 snaps over the lobes 50. The locking engagement is robust and reduces unintentional dismounting of the tip when a side force is applied to the tip, such as during touching-off procedures.

[0038] In addition, the system enables low ejection forces, which is particularly advantageous for handheld pipettes. As mentioned, the out of round distortion of the collar 36 storing energy in the mounted collar 36 is useful for

throwing off the tips 14 after use. Conventional ejection or stripping mechanisms can be used to push on the top of the collar 36 and push the locking ring 48 over the lobes 50 in order to eject the tips 14. Fig. 12 shows a stripper tube 24 moving downward (arrow 22a) to push on the top of the collar 36 to eject the tip 14. When the locking ring 48 clears the peaks of the lobes 50, the energy stored in the distorted collar 36 is released and facilitates efficient ejection of the tip 14 from the mounting shaft 12.

[0039] A preferred embodiment of the invention has been described in connection with the drawings, however, various aspects and features of the invention can be implemented in other forms. For example, it is not necessary that the mounting shaft 12 have more than two lobes. Moreover, as previously mentioned, while the preferred embodiment of the invention provides for low insertion and ejection forces as well as tactile feedback when the mounting shaft is inserted into the pipette tip, the invention is also quite useful in automated liquid handling systems where these attributes may not be as important.

[0040] Also, although not preferred, it may be desirable to move the sealing area on the pipette tip from below the shelf to above the shelf, and configure the mounting shaft so that it accommodates sealing above the stop, rather than below. Even though this is not a preferred design, such a design preferably, in accordance with the invention, includes a mounting shaft with locking lobes as described above. The sealing area on the tip, however, still has to be sufficiently isolated from distortion. This normally requires that the sealing area be located adjacent the shelf and relatively far from the upper portion of the collar that becomes distorted by the mounting shaft lobes.

CLAIMS

We claim:

1. A pipetting system comprising:

a disposable pipette tip having

a barrel with a lower opening through which liquid is aspirated into the barrel and dispensed from the barrel, the barrel having a sealing area at the upper end of the barrel,

a collar having an upper opening for receiving a pipette tip mounting shaft, the inside surface of the collar including a circumferential locking ring, and the lower end of the collar having a larger inside diameter than the inside diameter at the upper end of the barrel, and

a circumferential shelf that connects the lower end of the collar to the upper end of the barrel; and

a pipette mounting shaft including

a lower sealing section; and

an upper locking section, the locking section of the mounting shaft including a stop that engages the shelf of a pipette tip when the mounting shaft is fully inserted into the collar of the pipette tip, two or more outwardly extending lobes located above the stop on the mounting shaft for engaging the locking ring on the inside surface of the collar, and relief portions between the lobes such that the collar distorts outwardly at the lobes and inwardly at the relief portions when the pipette tip is locked on the mounting shaft over the stop and the lobes.

2. The pipetting system as recited in claim 1 wherein:

the inside surface of the pipette tip barrel includes a circumferential sealing ring below the circumferential shelf; and

5 the lower sealing section on the mounting shaft is located below the locking section and engages the circumferential sealing ring when the mounting shaft is fully inserted into the pipette tip.

3. The pipetting system as recited in claim 1 wherein the system is a handheld, air displacement pipetting system.

4. The system as recited in claim 1 wherein the circumferential shelf on the pipette tip extends continuously around the inside circumferential surface of the pipette tip.

5. The system as recited in claim 1 wherein the locking ring on the pipette tip is located slightly below a rim of the upper opening of the collar of the pipette tip.

6. The system as recited in claim 1 wherein a sealing area of the pipette tip barrel is frustoconical.

7. The system as recited in claim 6 wherein the lower sealing section on the mounting shaft is frustoconical.

8. The system as recited in claim 1 wherein each lobe includes an inclined ramp portion that facilitates distortion of the pipette tip collar as the mounting shaft is inserted into the pipette tip.

9. The system as recited in claim 1 wherein the mounting shaft has at least three lobes.

10. The system as recited in claim 1 wherein the locking engagement of the mounting shaft to the pipette tip includes an air bleed.

11. The pipetting system as recited in claim 1 wherein the circumferential shelf of the pipette tip reduces the bore diameter of the pipette tip by about .004 to .040 inches.

12. A pipetting system as recited in claim 1 wherein the specific dimensional relationship between the locking section of the mounting shaft and the pipette tip are determined such that an incorrectly sized pipette tip will not mount properly to the mounting shaft.
13. A pipetting system as recited in claim 1 wherein the locking section of the mounting shaft includes a sealing section that is substantially cylindrical and the corresponding sealing area of the pipette tip barrel below the shelf of the pipette tip is substantially cylindrical as well.
14. A pipette system as recited in claim 1 wherein the stop on the mounting shaft is an angular step between the locking section and the lower sealing section.
15. A pipette system as recited in claim 1 wherein the stop on the mounting shaft is immediately below and adjacent a cylindrical stabilizing section on the mounting shaft which engages the pipette tip collar above the circumferential shelf of the pipette tip when the mounting shaft is fully inserted into the pipette tip.
16. A pipetting system as recited in claim 1 wherein the system is a hand-held pipette.
17. A pipetting system as recited in claim 1 wherein the system is part of an automated liquid transfer system.
18. A pipetting system as recited in claim 1 wherein the system includes multiple pipette mounting shafts each in accordance with the limitations recited in claim 1 for the pipette mounting shaft.
19. A pipetting system comprising:
 - a disposable pipette tip having
 - a barrel with a lower opening through which liquid is aspirated into the barrel and dispensed from the barrel;

5 a collar having an upper opening that receives a lower end of a pipette mounting shaft, a lower end of the collar having a larger inside diameter than the inside diameter of the upper end of the barrel; and
a circumferential shelf that connects the lower end of the collar to the upper end of the barrel; and
10 a pipette mounting shaft including
an upper locking section, the locking section of the mounting shaft including a stop that engages the circumferential shelf of the pipette tip when the mounting shaft is fully inserted into the collar of the tip, two or more outwardly extending lobes located above the stop on the mounting shaft for
15 engaging the inside surface of the collar, and relief portions between the lobes such that the collar distorts outwardly at the lobes and inwardly at the relief portions when the pipette tip is fully mounted on the mounting shaft.

20. A disposable pipette tip comprising:

a barrel having a lower opening through which liquid is aspirated into the barrel and dispensed from the barrel, the inside surface of the pipette tip barrel including at its upper portion a sealing area encircling the inside surface of the
5 pipette tip;
a collar having an opening for receiving a pipette mounting shaft, the lower end of the collar having an inside diameter that is larger than the inside diameter of the upper end of the barrel; and
a circumferential shelf connecting the lower end of the collar to the upper end
10 of the barrel, the sealing area of the pipette tip barrel being located below the circumferential shelf.

21. A disposable pipette tip as recited in claim 20 wherein the sealing area includes a circumferential sealing ring.

22. A disposable pipette tip as recited in claim 20 wherein the inside surface of the circumferential shelf of the pipette tip extends at a downward angle as

it extends from the collar to the barrel.

23. The disposable pipette tip as recited in claim 21 wherein the sealing
5 area of the pipette tip barrel in which the sealing ring is located is frustoconical.

24. The disposable pipette tip as recited in claim 21 wherein the sealing
area of the pipette tip barrel in which the sealing ring is located is cylindrical.

25. The disposable pipette tip as recited in claim 20 wherein the
circumferential shelf reduces the internal bore diameter of the pipette tip by about
.004 to .040 inches.

26. A disposable pipette tip as recited in claim 20 wherein the inside
surface of the collar includes a circumferential locking ring slightly below a rim of
the upper opening of the collar.

27. A disposable pipette tip as recited in claim 26 wherein the locking ring
includes an air bleed.






FIG. 2






FIG. 3




FIG. 4






FIG. 5



44




FIG. 7




FIG. 8




FIG. 6

FIG. 9




FIG. 10





FIG. 11




FIG. 12

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2007/080064

A. CLASSIFICATION OF SUBJECT MATTER
INV. B01L3/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
B01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
E	EP 1 862 219 A (QIAGEN GMBH [DE]; QIAGEN INSTR AG [CH]) 5 December 2007 (2007-12-05) paragraph [0064] - paragraph [0065]; figure 3	1-17
X	----- US 5 200 151 A (LONG ERNEST W [US]) 6 April 1993 (1993-04-06) column 7, line 33 - column 10, line 29; figures 3-5	1-8, 11-27
X	----- EP 1 319 437 A (ARKRAY INC [JP]) 18 June 2003 (2003-06-18) paragraph [0016] - paragraph [0037]; figures 1,2	1-8, 10-26
	----- -/--	

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

14 January 2008

Date of mailing of the international search report

28/01/2008

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Marti, Pedro

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2007/080064

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2006/233669 A1 (PANZER ARMIN [CH] ET AL) 19 October 2006 (2006-10-19) paragraph [0031] - paragraph [0038]; figures 2-4	1-7, 11-16, 19-26
X	EP 0 494 735 A (LABSYSTEMS OY [FI]) 15 July 1992 (1992-07-15) column 1, line 29 - column 3, line 43; figures 4-6	1-8, 10-26
X	US 2005/069460 A1 (LOHN JURGEN [DE]) 31 March 2005 (2005-03-31) the whole document	20-26
X	DE 102 29 788 A1 (EPPENDORF AG [DE]) 15 January 2004 (2004-01-15) the whole document	20-27
X	WO 00/27530 A (RAININ INSTR CO INC [US]) 18 May 2000 (2000-05-18) page 22, line 8 - page 23, line 19; figure 6	20-26
X	US 2005/175511 A1 (COTE RICHARD A [US] ET AL) 11 August 2005 (2005-08-11)	20-26
A	the whole document	1-19

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2007/080064

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:

2. Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:

3. Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. As all required additional search fees were timely paid by the applicant, this international search report covers allsearchable claims.
2. As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:

4. No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 1-19

Claims 1-18: Pipetting system comprising a disposable pipette tip with a barrel, a collar and a circumferential shelf, and a pipette mounting shaft including a lower sealing section, an upper locking section, wherein the locking section includes a stop, two or more outwardly extending lobes located above the stop and relief portions between the lobes.

Claim 19: Pipetting system comprising a disposable pipette tip with a barrel, a collar and a circumferential shelf, and a pipette mounting shaft including an upper locking section, wherein the locking section includes a stop, two or more outwardly extending lobes located above the stop and relief portions between the lobes.

2. claims: 20-27

Disposable pipette tip comprising a barrel, a collar and a circumferential shell.

.

The common inventive concept linking together both groups is a disposable pipette tip comprising the features of the tip defined in claim 20. Since this concept is not novel, the different subject-matters are not linked as to form a single general inventive concept and therefore the requirements of Rule 13 PCT are not fulfilled.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No PCT/US2007/080064

Patent document cited in search report	Publication date	Publication date	Patent family member(s)	Publication date
EP 1862219	A	05-12-2007	WO 2007137818 A1	06-12-2007
US 5200151	A	06-04-1993	AT 122931 T	15-06-1995
			CA 2039600 A1	22-11-1991
			DE 69109998 D1	29-06-1995
			DE 69109998 T2	21-09-1995
			DK 482149 T3	14-08-1995
			EP 0482149 A1	29-04-1992
			ES 2075445 T3	01-10-1995
			JP 5500025 T	14-01-1993
			WO 9117833 A2	28-11-1991
EP 1319437	A	18-06-2003	CN 1447718 A	08-10-2003
			WO 0216039 A1	28-02-2002
			JP 2002062304 A	28-02-2002
			US 2003177849 A1	25-09-2003
US 2006233669	A1	19-10-2006	AT 244070 T	15-07-2003
			DE 19917375 A1	02-11-2000
			WO 0062933 A1	26-10-2000
			EP 1171240 A1	16-01-2002
			ES 2197094 T3	01-01-2004
			JP 3977597 B2	19-09-2007
			JP 2002542017 T	10-12-2002
			US 7033543 B1	25-04-2006
EP 0494735	A	15-07-1992	AT 130531 T	15-12-1995
			DE 69206158 D1	04-01-1996
			DE 69206158 T2	20-06-1996
			DE 494735 T1	22-07-1993
			ES 2080437 T3	01-02-1996
			FI 910087 A	08-07-1992
			JP 3225367 B2	05-11-2001
			JP 7236829 A	12-09-1995
			US 5355738 A	18-10-1994
US 2005069460	A1	31-03-2005	DE 10345324 B3	19-08-2004
			EP 1520624 A1	06-04-2005
			JP 2005103542 A	21-04-2005
DE 10229788	A1	15-01-2004	NONE	
WO 0027530	A	18-05-2000	US 6197259 B1	06-03-2001
US 2005175511	A1	11-08-2005	AU 2005216853 A1	09-09-2005
			EP 1729885 A1	13-12-2006
			JP 2007521956 T	09-08-2007
			WO 2005082536 A1	09-09-2005