



(86) Date de dépôt PCT/PCT Filing Date: 2003/09/23
(87) Date publication PCT/PCT Publication Date: 2004/04/08
(45) Date de délivrance/Issue Date: 2011/08/16
(85) Entrée phase nationale/National Entry: 2005/03/22
(86) N° demande PCT/PCT Application No.: EP 2003/010709
(87) N° publication PCT/PCT Publication No.: 2004/029012
(30) Priorité/Priority: 2002/09/25 (US60/413,278)

(51) Cl.Int./Int.Cl. *C07C 2/32* (2006.01),
B01J 31/18 (2006.01), *B01J 8/18* (2006.01),
B01J 8/22 (2006.01), *C08F 10/00* (2006.01),
C08F 110/02 (2006.01)


(72) Inventeurs/Inventors:
ARNOLDY, PETER, NL;
DE BOER, ERIC JOHANNES MARIA, NL;
MOENE, ROBERT, NL;
VAN ZON, ARIE, NL;
UNGER, PHILLIP EDWARD, US

(73) Propriétaire/Owner:
SHELL INTERNATIONALE RESEARCH
MAATSCHAPPIJ B.V., NL

(74) Agent: NORTON ROSE OR S.E.N.C.R.L., S.R.L./LLP

(54) Titre : PROCEDE DE FABRICATION D'UN OLIGOMERE D'ALPHA-OLEFINE LINEAIRE AU MOYEN D'UN
ECHANGEUR THERMIQUE

(54) Title: PROCESS FOR MAKING A LINEAR ALPHA-OLEFIN OLIGOMER USING A HEAT EXCHANGER



(57) Abrégé/Abstract:

The invention pertains to a process for making a linear alpha-olefin oligomer in a reactor comprising a liquid and a gas phase, comprising the steps of catalytically oligomerizing ethylene in the presence of an iron complex of ,a 2,6-bis (arylimino)pyridine



(57) **Abrégé(suite)/Abstract(continued):**

derivative, to the alpha-olefin oligomer with an average molecular weight between 50 and 350 under release of heat, and removing the heat with a heat exchanger, which is not in direct contact with the liquid phase, using at least part of the gas phase as a coolant medium. The invention further relates to an apparatus to perform said process.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 April 2004 (08.04.2004)

PCT

(10) International Publication Number
WO 2004/029012 A1

(51) International Patent Classification⁷: **C07C 2/32**,
B01J 8/18

(21) International Application Number:
PCT/EP2003/010709

(22) International Filing Date:
23 September 2003 (23.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/413,278 25 September 2002 (25.09.2002) US

(71) Applicant (for all designated States except US): **SHELL INTERNATIONAL RESEARCH MAATSCHAPPIJ B.V.** [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ARNOLDY, Peter** [NL/NL]; Badhuisweg 3, NL-1031 CM Amsterdam (NL). **DE BOER, Eric, Johannes, Maria** [NL/NL]; Badhuisweg 3, NL-1031 CM Amsterdam (NL). **MOENE,**

Robert [NL/NL]; Badhuisweg 3, NL-1031 CM Amsterdam (NL). **VAN ZON, Arie** [NL/NL]; Badhuisweg 3, NL-1031 CM Amsterdam (NL). **UNGER, Phillip, Edward** [US/US]; 10 Shadow Lane, Houston, TX 77080 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: PROCESS FOR MAKING A LINEAR ALPHA-OLEFIN OLIGOMER USING A HEAT EXCHANGER



(57) Abstract: The invention pertains to a process for making a linear alpha-olefin oligomer in a reactor comprising a liquid and a gas phase, comprising the steps of catalytically oligomerizing ethylene in the presence of an iron complex of a 2,6-bis (arylimino)pyridine derivative, to the alpha-olefin oligomer with an average molecular weight between 50 and 350 under release of heat, and removing the heat with a heat exchanger, which is not in direct contact with the liquid phase, using at least part of the gas phase as a coolant medium. The invention further relates to an apparatus to perform said process.

WO 2004/029012 A1

WO 2004/029012 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

- 1 -

PROCESS FOR MAKING A LINEAR ALPHA-OLEFIN OLIGOMER USING A HEAT EXCHANGER

The invention pertains to a process for making a linear alpha-olefin oligomer in a reactor comprising a liquid and a gas phase, comprising the steps of catalytically oligomerizing ethylene in the presence of an iron complex of a 2,6-bis (arylimino) pyridine derivative, to the alpha-olefin oligomer with an average molecular weight between 50 and 350 under release of heat, and removing the heat with a heat exchanger.

Various processes are known for the production of higher linear alpha olefins (for example D. Vogt, Oligomerisation of ethylene to higher a-olefins in Applied Homogeneous Catalysis with Organometallic Compounds, Ed. B. Cornils, W. A. Herrmann, 2nd Edition, Vol. 1, Ch. 2.3. 1.3, page 240-253, Wiley-VCH 2002). These commercial processes afford either a Poisson or Schulz- Flory oligomer product distribution. In such a process, a wide range of oligomers is typically made.

In WO 02/00339, WO 02/12151, WO 02/06192, WO 02/28805, WO 01/58874, and WO 99/02472 novel Fe-based ethylene oligomerization catalysts are described that show high activity and high selectivity towards linear alpha- olefins. These catalysts are based on iron complexes of a selected 2,6-pyridinedicarboxaldehyde bisimine or a selected 2,6- diacylpyridine bisimine.

In the present invention the term "bis- (arylimino)- pyridine" is used to describe both classes of ligands. Alpha-olefin oligomers are compounds or mixture of

compounds with the general formula $\text{H}_2\text{C}=\text{CH}-(\text{CH}_2\text{CH}_2)_n\text{H}$ wherein n is an integer of 1 or greater. In such oligomers the alpha-olefin oligomer is usually a mixture of alpha-olefin oligomers with a mean number n from 1 to 20, preferably from 2 to 10. Alpha-olefin oligomers prepared according to the process of the present invention preferably have an average molecular weight between 50 and 350, more preferably between 60 and 280, even more preferably between 80 and 210.

The reaction of ethylene in the presence of the above iron complex is usually run in a well-mixed reactor in the liquid phase, typically using an aprotic organic solvent. This reaction generates a large amount of heat, which should be removed. As described in WO 02/06192 it is preferred to install a plurality of small reactors in combination with several heat exchangers to help provide sufficient cooling capacity for the reactor system. The process temperature, which usually is between about 35°C and about 90°C, more preferably between about 35°C and about 75°C, affects the cost of manufacture of the alpha-olefins in several ways. The higher the temperature the smaller the heat exchangers which have to be applied to the reactor(s), which generally lowers cost. The decay of the active oligomerization catalyst increases with increasing temperature. It is found that maximum volumetric production of alpha-olefins coupled with good absolute productivity of the catalyst usually occurs in the range of about 45°C to about 75°C, so this temperature range is preferred. Finally, the temperature also affects the bubble point pressure, the amount of ethylene in the liquid phase, and the catalyst selectivity. The higher the temperature the higher the pressure needed to maintain catalyst selectivity, which

increases capital cost of the manufacturing plant because of, for example, the need for thicker vessels, and larger compressors to attain the higher ethylene pressure. Higher pressure also increases energy costs.

5 The amount of ethylene (ethene) oligomerization catalyst used in the reaction will preferably be the maximum permitted by the cooling capacity of the reactor(s) and the ethylene mass transfer from the gas to the liquid phase. Catalyst may be added to the first
10 reactor only or to one or more subsequent reactors in series. Differing amounts of catalyst may be added to each reactor. The oligomerization is quite exothermic, about 100 kJ/mole of ethylene oligomerized, and as such cooling will usually be applied to the reactor(s) to
15 maintain the desired process temperature while maintaining high volumetric productivity of the reactor(s).

 In the prior art cooling is accomplished by running cooling tubes through the liquid in the interior of one
20 or more of the reactors to cool the contents. Another method of cooling is to have one or more heat exchangers external to the reactors and connected to the reactors by a liquid loop to cool the reactor contents. These external heat exchangers may be typical shell and tube
25 exchangers. The reactors may also be jacketed with a cooling jacket. Some or all of the feeds to some or all of the reactors may be cooled to allow the sensible heat of the ingredients to cool the reactors. All these liquid cooling methods, however, suffer from the disadvantage of
30 wax and polyethylene fouling of the coolers, which necessitates regular shut down of the reactor to allow cleaning of the coolers. Furthermore, wax and

- 4 -

polyethylene fouling may increase the paraffinicity of the solvent.

It is therefore an objective of the present invention to devise a process without the above disadvantages. It has now been found that linear alpha-olefin oligomers can be made in a reactor comprising a liquid and a gas phase, comprising the steps of catalytically oligomerizing ethylene in the presence of an iron complex of a 2,6-bis(arylimino)pyridine derivative, to the alpha-olefin oligomer with an average molecular weight between 50 and 350 under release of heat, and removing the heat with a heat exchanger, which is not in direct contact with the liquid phase, and more especially is positioned in the gas phase in the reactor, using at least part of the gas phase as a coolant medium.

This method provides a cooling system having its cooling elements outside the liquid reaction medium. Since wax and polyethylene have high boiling points, deposit of wax and polyethylene can no longer occur, and fouling of the heat exchanger is effectively prevented.

The heat exchanger according to this invention is of a conventional type, such as a shell-and-tube-type, and the like. The heat exchanger is internally cooled with conventional cooling fluids, like water, ammonia, Freon®, and the like. The reaction heat causes the solvents, reactants, and/or reaction products, which are present in the reaction medium, to evaporate and subsequently to be cooled by the heat exchanger, after which it works as a coolant medium for the reactor. The heat exchanger can be placed inside or outside the reactor. When the heat exchanger is placed inside the reactor it is preferred that some condensation occurs on the heat exchanger surface. When the heat exchanger is placed outside the reactor, it is preferred to apply a forced circulation of


the reactor coolant medium from the gas phase of the reactor through heat exchanger(s) compressor(s)/pump(s) and optionally a gas-liquid separator back to the liquid phase of the reactor. This will additionally improve the mixing in the reactor. After cooling this reactor coolant medium in this loop, some condensation can occur. This allows application of a separate gas and liquid return to the reactor using a gas-liquid separator. Furthermore, it is possible to deliberately remove (part of) this liquid phase from this gas-liquid separator and route this directly to the product work-up section. Finally, if full condensation occurs, return of this liquid to the reactor can be achieved by a pump instead of a compressor, which lowers costs. This reactor coolant medium is selected from an alkane, alkene, and aromatic compound, and mixtures thereof, preferably propane, n-pentane, isopentane, ethylene, 1-butene, o-, m-, and p-xylene, and toluene, and mixtures thereof.

An additional advantage of the present process is the possibility to apply only one reactor, because the efficiency and the lack of fouling no longer necessitates the use of a plurality of small reactors. This adds considerably to the lowering of costs of the oligomerization process.

The iron complexes of the 2,6-bis(arylimino)pyridine type that can be used in the above process are known in the art, and are described in WO 02/00339, WO 02/12151, WO 02/06192, WO 02/28805, WO 01/58874, and WO 99/02472. Any of these complexes can be used. Best results, however, are obtained with such iron complexes wherein one of the aryl moieties of the 2,6-bis(arylimino)pyridine derivative is 2,6-disubstituted with the group CH_2R or $\text{C}_2\text{H}_5\text{R}$, wherein R is selected from

H, F, and substituted or unsubstituted aryl, preferably selected from H and F, and the other aryl moiety is 2,6-unsubstituted, or wherein both aryl moieties of the 2,6-bis(arylimino)pyridine derivative are 2,6-disubstituted with F or Cl.

Particularly useful are the 2,6-bis(arylimino)pyridine derivatives with the formula:




wherein

R1 is H or CH₃;

R2 is H, tert-butyl or phenyl; and

R3 is H, tert-butyl or OR' wherein R' stands for CH₃, Si(CH₃)₃ or eicosyl (C₂₀H₄₁); and



The term "aryl" means an aromatic group, such as phenyl, naphthyl, thienyl, pyridyl, pyrrolyl, and the like. Phenyl is the preferred aryl group. Preferred phenyl groups are substituted with CH₃, tert-butyl, F, or OR' wherein R' stands for CH₃ or Si(CH₃)₃.

In a preferred embodiment an aluminum-based co-catalyst, preferably a methylaluminoxane, is added to the liquid phase. Where a co-catalyst such as an alkylaluminum compound is required or preferred for the active catalyst species, an iron complex of a 2,6-bis(arylimino)pyridine derivative, such as a complex of the 2,6-bis(arylimino)pyridine derivative with FeCl_2 , may be reacted with an alkylaluminum compound, preferably an aluminoxane, to form an active ethylene oligomerization species. Specific alkylaluminum compounds include methylaluminoxane (which is an oligomer with the general formula $(\text{MeAlO})_n$), $(\text{C}_2\text{H}_5)_2\text{AlCl}$, $\text{C}_2\text{H}_5\text{AlCl}_2$, $(\text{C}_2\text{H}_5)_3\text{Al}$ and $((\text{CH}_3)_2\text{CHCH}_2)_3\text{Al}$. A particularly preferred aluminoxane is methyl aluminoxane. The ratio of aluminum (as alkylaluminum compound) to iron (as a complex) in the oligomerization may be about 10 to about 10,000.

Another preferred component of the catalyst systems herein is a second co-catalyst compound selected from formula ZnR'_2 wherein each R' , which may be the same or different, is selected from hydrogen, optionally substituted C_1 - C_{20} hydrocarbyl, phenyl, Cl, Br, I, SR'' , NR''_2 , OH, OR'' , CN, NC wherein R'' , which within the same molecule may be the same or different, is C_1 - C_{20} hydrocarbyl.

In preferred catalyst systems herein, the second co-catalyst compound is ZnR'_2 wherein R' is C_1 - C_{20} hydrocarbyl, more preferably C_1 - C_{20} alkyl, even more preferably C_1 - C_6 alkyl. Suitable alkyl groups include methyl, ethyl, propyl, butyl, and the like. It is especially preferred that the R' group is a C_1 - C_3 alkyl, especially ethyl.

The second co-catalyst is particularly valuable in combination with the aluminium-based co-catalyst for increasing the selectivity of linear alpha olefins in ethylene oligomerization reactions, and decreasing the amount of unwanted by-products such as branched olefins, internal olefins, 2,2-disubstituted olefins, and dienes.

It has been noted that particularly high selectivity of linear alpha olefins is achieved when the molar ratio of the metal of the aluminium-based co-catalyst to the metal of the second co-catalyst is in the range of from 5:1 to 1:5, preferably from 3:1 to 1:3, more preferably from 2:1 to 1:2 and especially 1:1.

It is possible to add further optional components to the catalyst systems herein, for example, Lewis acids and bases such as those disclosed in WO02/28805.

The active catalyst system may be formed by mixing together the iron complex of a 2,6-bis(arylimino)pyridine derivative or a mixture of the iron acetylacetonate complex and the appropriate 2,6-bis(arylimino)pyridine derivative (ligand), first co-catalyst compound, second co-catalyst compound and any optional additional compounds, preferably in a solvent.

An important item in the capital cost of this manufacturing plant and in its cost of operation is the amount of reactor coolant medium that must be recycled in the process. Recycling of a gaseous reactor coolant medium often involves recompression to feed one or more of the reactors. Compressors and associated equipment add greatly to capital and operational costs. In the present method the coolant medium is preferably selected to completely dissolve ethylene. In this case the coolant medium only requires a single reactor and a condenser, whereas a simple recycle pump is sufficient. Thus

expensive recycling, such as the use of an expensive recycle blower, is no longer required, which adds further to the advantages of the present method.

The invention is illustrated by the following Figures, which are not meant to limit the invention in any way, showing a scheme of an apparatus that can be used for performing the process of the invention.

Fig. 1 is a scheme of an apparatus for performing the method according to the invention with the heat exchanger positioned outside the reactor.

Fig. 2 is a scheme of an apparatus for performing the method according to the invention with the heat exchanger positioned inside the reactor.

Fig. 1 shows a reactor 2 with a liquid phase 3 and a gas phase 4 being in equilibrium through gas/liquid interface 12. The liquid phase comprises ethylene, the iron complex of a 2,6-bis (arylimino) pyridine derivative, alpha-olefin oligomer, and optionally solvents and auxiliaries such as a co-catalyst. The optional solvents are selected as to dissolve ethylene. The reactor contains an inlet 10 through which the reactor feed 1 is transported, a gas outlet 11, and a reactor bottom outlet 9. In the embodiment of Figure 1, outlet 11 is connected through a conduit 14 to heat exchanger 5a, which is connected through conduit 15 to gas-liquid separator 6. If necessary, conduit 15 may contain a compressor 7a. Gas-liquid separator 6 has an outlet conduit 17 for transporting the liquid, optionally through a pump 8, to obtain a pressurized liquid stream that is recycled via conduit 19 to reactor 2. The gas leaves the gas-liquid separator 6 through conduit 16, which may optionally comprise compressor 7b and/or, heat exchanger 5b, to obtain a cooled gas stream 18 that is recycled to reactor 2. If no condensation occurs in conduit 15, gas-liquid separator 6, and pump 8 are redundant and may be deleted. In that case conduit 15 can directly be connected to compressor 7b and/or heat exchanger 5b, if present, or to conduit 19. Reactor 2 may contain an optional entrainment separator 13.


Fig. 2 shows another embodiment according to the invention. In this embodiment the reactor feed 1 is introduced into the reactor 2 through inlet 10. The liquid phase 3 in the reactor is in equilibrium with the gas phase 4 through gas/liquid interface 12. In the section of the reactor containing the gas phase 4, a heat exchanger 20 is placed, which is not in contact with the liquid phase 3. The section of the gas phase 4 may optionally contain an entrainment separator 13. The heat exchanger 20 cools the gas, after which at least part of the gas condenses and the cooled condensate falls down from the surface of the heat exchanger 20 into the liquid phase 3, thereby cooling the liquid medium. The reaction product may then be discharged from the reactor through the reactor bottom outlet 9.

Hence according to a further aspect of the present invention there is provided an apparatus for performing the process of making linear alpha-olefin oligomer described above, comprising a reactor (2), which can accommodate a liquid (3) and a gas (4) phase, an inlet (10) through which the reactor feed (1) can be transported, a reactor bottom outlet (9), and at least one heat exchanger (5a, b; 20), which is positioned as to prevent direct contact with the liquid phase (3), and further optionally a gas outlet (11), pumps (8), compressors (7a, b), an entrainment separator (13), and/or a gas-liquid separator (6).

CLAIMS:

1. A process for making a linear alpha-olefin oligomer in a reactor comprising a liquid and a gas phase, comprising the steps of catalytically oligomerizing ethylene in the presence of an iron complex of a 2,6-bis(arylimino)pyridine derivative, to the alpha-olefin oligomer with an average molecular weight between 50 and 350 under release of heat, and removing the heat with a heat exchanger which is positioned in the gas phase in the reactor but not in direct contact with the liquid phase, using at least part of the gas phase as a coolant medium.
2. The process according to claim 1 wherein an aluminum-based co-catalyst is added to the liquid phase.
3. The process according to claim 1 or 2 wherein the average molecular weight is between 60 and 280.
4. The process according to any one of claims 1 to 3 wherein one of the aryl moieties of the 2,6-bis(arylimino)pyridine derivative is 2,6-disubstituted with the group CH_2R or $\text{C}_2\text{H}_5\text{R}$, wherein R is selected from H and F, and the other aryl moiety is 2,6-unsubstituted, or wherein both aryl moieties of the 2,6-bis(arylimino)pyridine derivative are 2,6-disubstituted with F or Cl.
5. The process according to any one of claims 1 to 4 wherein the 2,6-bis(arylimino)pyridine derivative has the formula:

- 12 -




wherein

R1 is H or CH₃;

5 R2 is H, tert-butyl or phenyl and

R3 is H, tert-butyl or OR' wherein R' stands for CH₃, Si(CH₃)₃ or eicosyl
(C₂₀H₄₁); or




6. The process according to any one of claims 1 to 5 wherein the coolant medium
is selected from an alkane, alkene, and aromatic compound, and mixtures
thereof.

7. The process according to any one of claims 1 to 6 wherein the coolant medium
is selected from propane, n-pentane, isopentane, ethylene, 1-butene, o-, m-, and
p-xylene, and toluene, and mixtures thereof.

1/2

Fig.1.



2/2

Fig.2.

