Nov. 16, 1965 E. E. CRILE ETAL 3,217,906

PALLET HANDLING MACHINE

Original Filed July 18, 1962 12 Sheets-Sheet 1




Fig. 1

EUGENE E. CRILE INVENTORS.
PAUL M. THOMAS AND
LAWRENCE W. WRIGHT
BY
Wm. H. Dean
AGENT

Nov. 16, 1965 E. E. CRILE ETAL 3,217,906

PALLET HANDLING MACHINE

Original Filed July 18, 1962 12 Sheets-Sheet 2




Fig. 2

EUGENE E. CRILE INVENTORS.
PAUL M. THOMAS -AND-
LAWRENCE W. WRIGHT
BY
Wm. H. Dean
AGENT

Nov. 16, 1965 E. E. CRILE ETAL 3,217,906

PALLET HANDLING MACHINE

Original Filed July 18, 1962 12 Sheets-Sheet 3




Fig. 3




Fig. 4

EUGENE E. CRILE INVENTORS.
PAUL M. THOMAS -AND-
LAWRENCE W. WRIGHT
BY
Wm. H. Dean
AGENT

Nov. 16, 1965 E. E. CRILE ETAL 3,217,906

PALLET HANDLING MACHINE

Original Filed July 18, 1962 12 Sheets-Sheet 4




Fig. 5




Fig. 6




Fig. 7

EUGENE E. CRILE INVENTORS.
PAUL M. THOMAS AND
LAWRENCE W. WRIGHT
BY
Wm. H. Dean
AGENT

Nov. 16, 1965 E. E. CRILE ETAL 3,217,906

PALLET HANDLING MACHINE

Original Filed July 18, 1962 12 Sheets-Sheet 5

Fig. 8




Fig. 9a.





Fig. 9

Fig. 10






Fig. 11

EUGENE E. CRILE INVENTORS.
PAUL M. THOMAS AND
LAWRENCE W. WRIGHT
BY
Wm. H. Dean
AGENT

Nov. 16, 1965 E. E. CRILE ETAL 3,217,906

PALLET HANDLING MACHINE

Original Filed July 18, 1962 12 Sheets-Sheet 6




Fig. 12




Fig. 14




Fig 13

EUGENE E. CRILE INVENTORS.
PAUL M. THOMAS -AND-
LAWRENCE W. WRIGHT
BY
Wm. H. Dean
AGENT

Nov. 16, 1965 E. E. CRILE ETAL 3,217,906

PALLET HANDLING MACHINE

Original Filed July 18, 1962 12 Sheets-Sheet 7




Fig. 15

Fig. 16






Fig. 17





EUGENE E. CRILE INVENTORS.
PAUL M. THOMAS -AND-
LAWRENCE W. WRIGHT
BY

Fig. 18

Wm. H. Dean
AGENT

Nov. 16, 1965 E. E. CRILE ETAL 3,217,906

PALLET HANDLING MACHINE

Original Filed July 18, 1962 12 Sheets-Sheet 8




Fig. 21




Fig. 22




Fig. 23




Fig. 19





Fig. 20

EUGENE E. CRILE INVENTORS.
PAUL M. THOMAS AND
LAWRENCE W. WRIGHT
BY
Wm. H. Dean
AGENT

Nov. 16, 1965 E. E. CRILE ETAL 3,217,906

PALLET HANDLING MACHINE

Original Filed July 18, 1962 12 Sheets-Sheet 9






Fig. 24




Fig. 25

EUGENE E. CRILE INVENTORS.
PAUL M. THOMAS AND
LAWRENCE W. WRIGHT
BY
Wm. H. Dean
AGENT

Nov. 16, 1965 E. E. CRILE ETAL 3,217,906

PALLET HANDLING MACHINE

Original Filed July 18, 1962 12 Sheets-Sheet 10




Fig. 26

EUGENE E. CRILE INVENTORS.
PAUL M. THOMAS -AND-
LAWRENCE W. WRIGHT
BY
Wm. H. Dean
AGENT

PALLET HANDLING MACHINE

Original Filed July 18, 1962 12 Sheets-Sheet 11




Fig. 27

EUGENE E. CRILE INVENTORS.
PAUL M. THOMAS AND
LAWRENCE W. WRIGHT
BY
Wm. H. Dean
AGENT

Nov. 16, 1965 E. E. CRILE ETAL 3,217,906

PALLET HANDLING MACHINE

Original Filed July 18, 1962 12 Sheets-Sheet 12




Fig. 28

EUGENE E. CRILE INVENTORS.
PAUL M. THOMAS -AND-
LAWRENCE W. WRIGHT
BY
Wm. H. Dean
AGENT

United States Patent Office 3,217,906 Patented Nov. 16, 1965

3,217,906

PALLET HANDLING MACHINE

Eugene E. Crile, 1619 W. Marlette Ave.; Paul M. Thomas, 5630 E. Edgewood; and Lawrence W. Wright, 6501 E. Monte Rosa, all of Phoenix, Ariz.

Original application July 18, 1962, Ser. No. 211,477. Divided and this application Dec. 18, 1964, Ser. No. 425,656

5 Claims. (Cl. 214—16.4)

This application is a division of application Ser. No. 211,477 (now abandoned), filed July 18, 1962, which is a continuation-in-part of application Ser. No. 28,929 (now abandoned), filed May 13, 1960.

This invention relates to a pallet handling machine and more particularly to a pallet handling machine adapted to receive laden pallets from a concrete block producing machine and to transfer such laden pallets to vertically spaced superimposed locations in pallet supporting racks adjacent to the concrete block producing machine.

In the production of concrete blocks, conventional block producing machines eject laden pallets which support one or more concrete blocks thereon. These pallets are always ejected from the block producing machine at a particular level and conventional pallet racks into which the pallets are loaded, generally comprise a plurality of vertically spaced superimposed sheves, some of which are below the delivery level of the concrete block producing machine and some of which are above the delivery level of the machine.

The relationship of the delivery level of the machine and the superimposed spaced shelves above and below said delivery level has created many difficult problems in the operation of automatic pallet handling machines which will accurately and properly fill all of the shelves of the racks with laden pallets.

It will be understood by those skilled in the art that such a pallet handling machine must always return to the concrete block producing machine at precisely its delivery level and then must move up or down properly to index with a respective unladen shelf of a rack adjacent to the block producing machine.

The high production rate of modern concrete block producing machines imposes problems in the handling of laden pallets delivered by such machines. Consequently, the rates at which pallet handling machines must operate are quite great when numerous movements, horizontally and vertically, are required properly to deliver laden pallets from the block producing machine to the racks and empty pallets from the racks to such a machine.

In addition to the high rates of operation required of a pallet handling machine, in accordance with the production rates of a concrete block producing machine, various precise locating operations must be carried out by the pallet handling machine in order to locate positions laterally with respect to pallet racks when positioning laden pallets therein. Such operations of laterally locating the laden pallets in position to be inserted in the racks must be accomplished quickly and precisely in order to prevent tipping of the racks or damage of the concrete blocks on the pallets.

Accordingly, it is an object of the invention to provide a shelf height locating mechanism which precisely locates the vertical disposition of the pallet carriage of the machine above or below the delivery level of a concrete block producing machine so that laden pallets may accurately be placed at a proper vertical level with respect to the existing pallet rack shelves regardless of their mechanical condition or even though some shelves may be missing.

Another object of the invention is to provide a pallet handling machine having all of its operating mechanism swingable on a fixed vertical axis and which also comprises mechanism for moving a pallet carriage vertically and horizontally whereby such combined movements may be accomplished simultaneously in order to accommodate a high production rate of a concrete block producing machine and accurately to place laden pallets in pallet racks and to deliver unladen pallets back to the producing machine.

Other objects and advantages of the invention may be apparent from the following specification, appended claims, and accompanying drawings, in which:

FIG. 1 is a side elevational view of a pallet handling machine in accordance with the present invention;

FIG. 2 is a top or plan view thereof showing pallet receiving rack means and motorized mechanism for advancing the racks relative to the pallet handling machine and also illustrating by broken lines a varying position of mechanism of the pallet handling machine. FIG. 2 further discloses the disposition of the concrete block producing machine relative to the pallet handling machine and the receiving rack means;

FIG. 3 is a plan sectional view of the pallet handling machine of the invention taken from the line **3—3** of FIG. 1;

FIG. 4 is a fragmentary sectional view of the pallet handling machine of the present invention taken from the line **4—4** of FIG. 3;

FIG. 5 is a fragmentary side elevational view of the pallet handling machine of the present invention shown in an enlarged scale to illustrate various mechanical details;

FIG. 6 is an enlarged fragmentary top or plan view of the pallet handling machine of the present invention showing means for pivoting the machine about a vertical axis;

FIG. 7 is a fragmentary sectional view taken from the line **7—7** of FIG. 6;

FIG. 8 is a fragmentary sectional view taken from the line **8—8** of FIG. 1;

FIG. 9 is a fragmentary sectional view taken from the line **9—9** of FIG. 8; FIG. 9*a* shows a modification of hook shown in FIG. 9;

FIG. 10 is a fragmentary sectional view taken from the line **10—10** of FIG. 8;

FIG. 11 is a fragmentary sectional view taken from the line **11—11** of FIG. 8;

FIG. 12 is a fragmentary sectional view taken from the line **12—12** of FIG. 1 showing structure thereof on an enlarged scale;

FIG. 13 is a fragmentary elevational view taken from the line **13—13** of FIG. 12;

FIG. 14 is a fragmentary elevational view taken from the line **14—14** of FIG. 12;

FIG. 15 is an enlarged fragmentary plan sectional view of the pallet handling machine of the present invention, showing portions broken away and in section to amplify the illustration and illustrating means for locating laden pallets laterally with respect to the pallet carriage of the machine;

FIG. 16 is a transverse sectional view taken from the line **16—16** of FIG. 15;

FIG. 17 is an enlarged side elevational view of mechanism for locating the pallet carriage laterally with respect to the pallet rack;

FIG. 18 is a top or plan view of the mechanism shown in FIG. 17 and illustrating by broken lines elements of a pallet rack engaged by mechanism for locating the pallet carriage laterally with respect to the rack;

FIG. 19 is a view similar to FIG. 18 but showing a modification of the mechanism illustrated thereby;

FIG. 20 is a view similar to FIG. 17 but showing the modification illustrated in FIG. 19 and further illustrating by broken lines, elements of a pallet rack;

FIG. 21 is a fragmentary side elevational view of the pallet carriage of the present invention shown indexed with a pallet rack for the delivery of a laden pallet to the uppermost shelf of the rack and in position to eject an unladen pallet from said top shelf;

FIG. 22 is a view similar to FIG. 21 but showing a rack supporting the empty pallet ejected from the uppermost shelf of the rack and showing the placement of laden pallets on said upper shelf;

FIG. 23 discloses the pallet carriage of the machine approaching a position to pick up unladen pallets ejected from the top and third shelves of the rack, as illustrated in FIGS. 21 and 22;

FIG. 24 is a fragmentary sectional view taken from the line 24—24 of FIG. 3 and showing the mechanism of a pallet carriage on an enlarged scale and illustrating by broken lines a varying position thereof;

FIG. 25 is a view similar to FIG. 24 showing the manner in which the carriage of the present invention rakes unladen pallets from a rack so that such pallets may be carried back to the concrete block producing machine;

FIG. 26 is a diagrammatic illustration of the hydraulic system of the pallet handling machine, in accordance with the present invention; and

FIGS. 27 and 28 are combined figures but on separate sheets of drawing illustrating diagrammatically the electrical equipment of the pallet handling machine, in accordance with the present invention.

As shown in FIG. 1 of the drawings, the pallet handling machine of the present invention is provided with a base frame **50** having a thrust bearing **52** therein. Supported on this thrust bearing **52** and rotatable on a substantially vertical axis is a column **54** having an upper end portion **56**, as shown in FIG. 5 of the drawings, which is supported in a bearing **58** having a vertical axis. This bearing **58** is supported by an upstanding frame member **60** which comprises a horizontal cantilever section **62** carried by downwardly diverging legs **64** which are adjustably supported on the base frame **50** by means of bolts **66**.

A shown in FIG. 3 of the drawings, the column **54** is composed of a pair of spaced vertical track rails **68** on which a vertically movable frame **70** is mounted. This vertically movable frame **70**, as shown in FIGS. 3 and 4 of the drawings, is provided with a pair of side plates **72**. These side plates **72** are adjacent the track rail members **68**.

Rotatably mounted on each of the side plates **72** are spaced rollers **74** and **76** which are located near the upper portion of the vertically movable frame **72**. These rollers **74** and **76** engage respective edges **78** and **80** of one of the track rail members **68**. It will be seen that the edges **78** and **80** form tracks for these rollers **74** and **76**.

Each side plate **72** is also provided with a pair of rollers **82** and **84** mounted near the lower portion of the vertically movable frame **72**. These rollers **82** and **84** also engage respective track edge portions **78** and **80** of the respective track rails **68**.

Fixed to the side plates **72** of the vertically movable frame are cross members **86** and **88** which extend laterally into fixed connection with horizontal side bars **90** and **92** of the vertically movable frame **70**. This vertically movable frame **70** is provided with a bar **94** which interconnects cross members **96** and **98** which are fixed to the plates **72**. Secured to the cross member **94** is a chain **100** which extends upwardly through a bearing boss **101** fixed on the upper end of the column **56**. The chain **100** extends upwardly and passes over a sprocket **102** which is rotatably mounted on a frame member **104** carried by the cantilever portion **62** of the upper frame member **60**. The chain **100** passes over another sprocket **106** and is coupled to a plunger **108** of a hydraulic cylinder **110** which is anchored by means of a pin **112** to a member **114** of the frame. This hydraulic cylinder **110**, when actuated, as will be hereinafter described, pulls the chain **100** over the sprockets **102** and **106** to elevate the vertically movable frame **70** which travels upwardly on the track rail **68** by means of the rollers **74**, **76**, **82** and **84**, rotatably mounted on the side plates **68** of the vertically movable frame **70**.

The vertically movable frame **70** and the column **54** are pivotal about a vertical axis extending through bearings **52** and **58** by means of hydraulic cylinders **116** and **118** which are carried between the cantilever portions **62** of the upper frame member **60**, as shown best in FIG. 6 of the drawings.

These cylinders **116** and **118** are pivotally mounted on pins **120** and **122** and are provided with respective plungers **124** and **126** carrying sprockets **128** and **130** which engage a chain **132**.

This chain **132** passes over a sprocket **134** which is fixed to the bearing boss **101** which is secured to the upper end of the column **54**, as hereinbefore described. Opposite ends of the chain **132** are fixed by bolts **136** and **138** to the upper frame **60** whereby the hydraulic cylinders **116** and **118** may alternately be energized to cause rotation of the column **54** and the vertically movable frame **70** connected therewith.

It will be understood that the column **54** as hereinbefore described, moves about a vertical axis aligned with the bearings **52** and **58** thereby pivoting the vertically movable frame **70** about said vertical axis.

Horizontally movably mounted on the vertically movable frame **70** is a pallet carriage **140**. The pallet carriage is telescopically mounted on the frame **70** to move in a substantially horizontal disposition thereon. This pallet carriage **140** is provided with a pair of flat bars **142** which are substantially parallel and provide a horizontal upper surface **144** for the support of pallets to be carried thereon. As shown best in FIGS. 3 and 4 of the drawings, the pallet carriage **140** is provided with track bars **146** and **148** which are fixed to the flat bars **142** by cross members **150** and **152**. Fixed to the track bars **146** and **148** are respective trunnions **153** and **154** which carry rollers **156** and **158**. These rollers **156** and **158** bear on the upper edges of the horizontal members **90** and **92** respectively, of the vertically movable frame **70**.

Adjacent to the cross member **88** of the vertically movable frame **70** are bearing supports **160** and **162** carried by the side members **90** and **92**, respectively, of the vertically movable frame **70**. Mounted on each of these bearing supports **160** and **162** is a pair of spaced rollers **164** and **168** which engage upper and lower edges **170** and **172**, respectively, of the carriage track bars **146** and **148**.

Thus, the pallet handling carriage **140** is horizontally reciprocally mounted on the vertically movable frame **70** and is freely operable on the rollers **156**, **158**, **164**, and **168**, as hereinbefore described.

Coupled to the cross member **152** is a lug **174** through which a pin **176** extends. This pin **176** provides a coupling for a plunger shaft **178** of a hydraulic cylinder **180** which is pivotally mounted on a cross member **182**, interconnecting the side bars **90** and **92** of the vertically movable frame **70**. This hydraulic cylinder **180** provides actuating force to move the pallet handling carriage **140** horizontally on the vertically movable frame **70**.

The vertically movable frame **70** is provided with means for centering pallets laterally thereof when the pallet carriage **140** is retracted to the vertically movable frame. Attention is directed to FIGS. 3, 15, and 16, wherein the means for centering pallets laterally of the vertically movable frame is shown.

Interconnecting the side bars **90** and **92** of the vertically movable frame are spaced parallel rods **184** and **186** which extend through openings in the bars **90** and **92** and are fixed longitudinally by means of nuts screw-threaded on the ends of said rods **184** and **186**.

Fixed on the rods **184** and **186** are bars **188** and **190** having respective upper edges **192** and **194** on which pallets may be carried as will be hereinafter described in detail.

Slidably mounted on the rods **184** and **186**, adjacent the frame bar **90**, are slide bearings **196** and **198** which carry a plate **200**. Secured to this plate **200** is a lug **202** through which a pin **204** extends. This pin **204** also extends through a clevis **206** of a plunger **208** reciprocally mounted on a hydraulic cylinder **210**. This hydraulic cylinder **210** is mounted by means of a pin **212** to a lug **214** fixed to a movable plate **216** located adjacent the side bar **92** of the vertically movable frame **72**. The plate **216** is fixed to slide bearings **218** and **220** which are slidably mounted on the rods **184** and **186**, respectively.

The inner ends **222** and **224** of the slide bearings **218** and **220** are arranged to abut stops **226** and **228** on the bar **188** when moved inwardly by the cylinder **210** and the inner ends **230** and **232** of the slide bearings **196** and **198** are arranged to abut stops **234** and **236** of the bar **190** when moved inwardly by the plunger **208** of the cylinder **210**.

These stops precisely locate the inward movement of the plates **200** and **216** so that pallets may be centered therebetween and laterally with respect to the frame bars **90** and **92** of the vertically movable frame **70**.

Referring to FIG. 16 it will be seen that a pallet, as shown by broken lines A, may be engaged at its opposite edges by the plates **200** and **216** when the hydraulic cylinder **210** is energized. The pallet, as shown by broken lines A, is on the same plane as it will be when the pallet handling carriage is retracted relative to the vertically movable frame as will be hereinafter described.

Reference is made to FIGS. 24 and 25 wherein an extended position of the pallet handling carriage is shown by broken lines and wherein pallets laden with concrete blocks B are disclosed on the pallet handling carriage. These concrete blocks B are shown by solid lines C in a retracted position relative to the vertically movable frame of the machine and the pallets are disclosed by solid lines D in such retracted position. These solid line positions D correspond vertically to the broken line position A in FIG. 16 of the drawings, as hereinbefore described. It will be seen from FIGS. 16 and 24 that the laden pallets may be retracted to the solid line positions as shown in FIG. 24 wherein they coincide with the broken lines position A of such pallets laterally of the vertically movable frame bars **90** and **92**.

In order to center these pallets, the plates **200** and **216** are moved inwardly to engage opposite edges of the pallets when the hydraulic cylinder **210** is actuated. Thus, the pallets are centered relative to the vertically movable frame bars **90** and **92**. This lateral centering is necessary since the pallets are received from a concrete block producing machine when the pallet handling carriage **140** is extended in the broken line position as shown in FIG. 24 of the drawings. Sometimes these pallets are not precisely centered relative to the pallet handling carriage **140** and therefore it is necessary to center them relative thereto before they are ejected into a rack which holds them after the laden pallets have been delivered from the concrete block producing machine.

Cooperative with the plates **200** and **216** for locating the pallets precisely in a lateral position with respect to the bars **90** and **92**, is a further means for laterally locating the vertically movable frame and pallet carriage with respect to the shelves in stationary racks wherein laden pallets are placed by the pallet handling machine of the present invention.

This further means comprises an actuator cylinder **240** carried on the horizontal bar **90** of the vertically movable frame **70**. This hydraulic cylinder **40** is secured to the bar **90** by means of a clamp **242** so that the axial alignment of the cylinder **40** is fixed relative to the longitudinal axis of the frame bar **90**. The cylinder **240** is provided with a plunger **244**, having a clevis **246** supporting a roller **248**. This roller **248** is engageable in a vertical channel member **250** of a stationary rack which receives laden pallets from the pallet handling carriage of the present invention. The roller **248**, when forced outwardly into engagement with the channel **250** of the rack, causes precise location and alignment of the vertically movable frame about the vertical axis common to the bearings **52** and **58** as hereinbefore described which support the vertical column **54**.

As will be hereinafter described, limit switch mechanism is provided to stop the swinging movement of the vertically movable frame about its vertical axis to attain approximate lateral alignment of the frame bars **90** and **92** with a shelf of the pallet rack whereupon actuation of the cylinder **240** forces the roller **248** to engage the channel **250** and thereby finalize the exact pivotal alignment of the vertically movable frame and pallet carriage relative to the shelves of the pallet racks.

Attention is directed to FIGS. 19 and 20, wherein the cylinder **240** is provided with a plunger **244** carrying a head having diverging surfaces **252** and **254** which engage opposite edges of the channel member **250** of the pallet rack as hereinbefore described. It will be obvious to those skilled in the art that, either a roller which engages between flanges of a channel member or other structure such as diverging surfaces which engage the outside opposite edges of a structure, will perform the final aligning function. This final aligning function is necessary so that exact placement of the laden pallets in the pallet rack shelves may be accomplished following the lateral centering of such pallets with respect to the pallet handling carriage by means of the plates **200** and **216** hereinbefore described.

Located near the rear ends of the pallet carriage bars **142** is a limit switch operating cross bar **256** which is supported by plungers **258** and **259**, reciprocally mounted in tubes **260** and **261**. The ends of the rods **258** and **259** are provided with heads **262** and **264** engaged by springs **266** and **268** tending to hold the bar **256** forwardly in the direction of the arrow B shown in FIG. 10 of the drawings. The cross bar **256** is provided with a rearwardly extending tab **270**, disposed to engage an arm **272** of a limit switch **4** when a pallet, as indicated by broken lines A in FIG. 10 of the drawings, is delivered by the block producing machine and engage the cross bar **256** thereby forcing it backwardly together with the plunger rods **258** and **259**. The pallet is forced into the dash line position A by the concrete block producing machine which slides it onto the bars **142** of the pallet handling carriage **140**. The movement of the pallet into the dash line position A and rearwardly thereof, forces the tab **270** into engagement with the arm **272** of limit switch **4** and initiates operation of the pallet handling machine of the present invention. The cycle of operation, including this function, will be hereinafter described in detail.

When a laden pallet is received on the bars **142** of the pallet handling carriage and actuates limit switch **4**, as hereinbefore described, a cycle of the pallet handling machine of the present invention is initiated.

As shown in FIG. 9, the hook **358** is provided with trunnions **359**, which mount the hook pivotally between the bars **142**. A spring **361** permits resilient deflection of the hook downwardly, as indicated by broken lines L, when the hook is carried upward under a laden pallet M, delivered by a concrete block producing machine. It will be understood that the pallet M is moved to the position, as shown in FIG. 9, before the carriage bars **142** move upwardly to clear the concrete block producing machine.

Also shown in FIG. 9*a* is a modified hook 363 which is withdrawn in the direction of the arrow P by power cylinder 365 so that the hook 363 will be out of interference with the pallet M when the carriage 140 raises to clear the concrete block producing machine.

Reference is made to FIG. 27 of the drawings, wherein limit switch 4 is disclosed in circuit with contact No. 1 of disc 271 of a stepper switch 273 which comprises discs 275, 277, and 279, coupled therewith on a common axis. All of these discs are shown in FIGS. 27 and 28 of the drawings. The discs 271, 275, 277, and 279, inclusive, of the stepper switch 273 are operated by an actuator 284 which is a common solenoid actuated ratchet mechanism energized by various functional elements of the machine during various stages of operation.

Attention is directed to FIG. 27, wherein a line conductor 274 is coupled to wiper arms 276, 278, and 282 of discs 271, 275, 277, and 279, respectively, of the stepper switch 273.

When limit switch 4 is closed, it completes a circuit to the solenoid actuator 284 of the stepper switch which is coupled by a conductor 286 to a conductor 288.

Thus, when limit switch 4 is closed, as hereinbefore described, the actuator 284 is energized to move the arms 276, 278, 280 and 282 to the contacts No. 2 on the discs 271, 275, 277, and 279, respectively. With the arms coupled to contacts 2, a solenoid valve 290 is energized through contact No. 2 on disc 275 and this solenoid valve 290 conducts hydraulic pressure fluid to the hydraulic cylinder 110 causing its plunger 108 to actuate the chain 100 and raise the carriage 140 upwardly until a limit switch 5, as shown in FIG. 13, is actuated.

This switch 5 is supported on the carriage frame 70 and is provided with a pivotally mounted actuating arm 292, which engages a stationary clip 294 held by a bar 296 adjacent to the carriage frame 70. Thus, actuation of the limit switch 5 closes a circuit between contact 2 of disc 271 and the stepper switch actuate 284 to move the stepper switch to position No. 3, wherein the arms 276, 278, 280 and 282 conduct to contacts No. 3 on discs 271, 275, 277, and 279, respectively. When the stepping switch is moved to position 3, a solenoid valve 298 is energized through contact 3 of disc 277. A solenoid valve 300 may also be energized, depending upon the position of contacts in a relay 302, as will be hereinafter described in detail.

Energization of the solenoid valve 298 supplies hydraulic fluid under pressure to the hydraulic cylinder 118, shown in FIG. 6, which acts to rotate the pallet handling carriage about a vertical axis in a direction F toward a broken line position D, shown in FIG. 2 of the drawings. While the stepping switch contact arms are in conductive relation with the contacts 3 thereof, a solenoid valve 304 is energized through discs 279 and this solenoid valve conducts fluid under pressure to the hydraulic cylinder 180 to retract pallet handling bars 142 of the pallet handling carriage so that the bars 142 will clear pallet racks 306, shown in FIG. 2 of the drawings. It will be understood that the pallet carrying bars 142 are retracted during their pivotal movement around a vertical axis to the broken line position D, shown in FIG. 2 of the drawings. As the pallet carrying bars 142 move inwardly with laden pallets thereon, a limit switch 8, carried on the side bar 90 of the carriage frame, is actuated by a projecting arm 308 carried by the trunnion 153 of the pallet carriage. When limit switch 8 is engaged by the arm 308, it closes a circuit to the stepper switch actuator 284 which is then energized to move the arms of the stepper switch to conductive relation with the contacts 4 of the discs 271, 275, 277, and 279.

Contact 4 of disc 275 is then coupled to limit switch 15 in series with limit switch 1 which is provided with an arm 310 which may alternately contact with a pair of contacts 311 or 312, coupled respectively to solenoid valves 290 and 314. In the respective position of operation, the arm 310 engages the contact 312 to energize the solenoid valve 314 to supply hydraulic fluid to the cylinder 110 in a reverse direction as supplied by the solenoid 290, whereby the carriage is permitted to move downwardly by extension of the hydraulic cylinder plunger 108 and downward movement of the chain 100 which is coupled to the carriage frame 70. The actuation of limit switch 1 by vertical movements of the mechanism of the present pallet handling machine will be hereinafter described in detail. However, in the position shown in FIG. 14 of the drawings and in FIG. 27, the contact 312 is now in position to energize the solenoid 314 and the carriage moves down while it is still swinging about a vertical axis, as hereinbefore described.

At the same time, a solenoid valve 316 is energized through contact 4 of disc 279 and this solenoid 316 conducts fluid under pressure to the cylinder 210 to actuate the plate 200 and 216 inwardly in order to center the pallets relative to the side bars 90 and 92 of the pallet handling carriage. Thus, the laden pallets are centered on the pallet handling bars 142, as hereinbefore described. As the carriage continues its downward movement, limit switch 15, mounted on the carriage frame 70, contacts an arm 318, supported by a magnetic shelf height locator 320 which is vertically movable on a slide bar 322.

The magnetic shelf height locator is arranged to hold itself magnetically on the bar 322, as will be hereinafter described in detail. The limit switch 15 is provided with an arm 15*a*, which contacts the extending arm 318 of the magnetic shelf height locator 320. It will be noted that limit switch 15 is provided with a pair of contacts, one of which is coupled to contact 4 of disc 275 and the other of which is coupled to contact 4 of disc 271. These are alternately open and closed so that the contact of limit switch 15, coupled with contact 4 of disc 275, is now open and the contact arm, coupled with contact 4 of disc 271, is now closed and is in series with limit switch 7 also coupled to contact 4 of disc 271.

Limit switch 7 is closed by swinging movement of the carriage about a vertical axis. Attention is directed to FIG. 1, wherein limit switch 7 is disclosed. This limit switch 7 is provided with a contact arm 319 which is engageable by a clip 321 on an arm 324 carried by the column 54. Thus, as the arm 324 swings through approximately a 90 degree travel, as shown in FIG. 2 of the drawings, limit switch 7 is closed and when it is closed in series with the closed contact of limit switch 15, the solenoid actuator 284 is energized and the stepping switch is automatically advanced to position 5.

It will be understood that limit switch 7, on one side of the machine, is equivalent to a similar switch on the opposite side which limits the swinging movement of the carrage to substantially 90 degrees in the opposite direction. As for example, in FIG. 2 of the drawings, limit switch 7 limits the swinging movement of the carriage in the direction of the arrow F while a similar limit switch 7*a* limits swinging movement in the direction of the arrow G, in FIG. 2 of the drawings, all as will be hereinafter described in detail. It will be seen that limit switch 7 energizes the stepping switch to position 5 on discs 271, 275, 277, and 279, at a time when the carriage is aligned with the respective shelf of one of the racks 306.

Accordingly, position 5 on disc 277 causes energization of a solenoid valve 326 which conducts fluid under pressure to the hydraulic cylinder 240 to extend its plunger 244 and to carry the roller 248 into engagement with a channel member 250 of one of the pallet racks 306 to thereby attain precise alignment of the carriage bars 142 with pallet supporting shelf members 328 and 330 which support opposite edges of the laden pallet when delivered by the pallet carriage of the present machine.

Contact 5, on plate 279 of the stepper switch, is coupled to a solenoid valve 332 which conducts fluid under pressure to the hydraulic cylinder 180 to extend the plunger 178 whereby the bars 142 of the pallet carriage

are projected outwardly between the shelf members 328 and 330 of a pallet rack 306 in order to deposit the laden pallets on these shelves. As the carriage is extended, the arm 308 contacts a pivoted arm 309 of limit switch 141 which energizes the actuation 284 of the stepping switch to a position wherein the arms 276, 278, 280, and 282, contact respective contacts 6 of discs 271, 275, 277, and 279, respectively.

When the arm 278 of the stepping switch 273 is coupled to contact 6 of disc 275, the solenoid valve 314 is energized to conduct fluid under pressure to the hydraulic cylinder 110 in a direction to extend the plunger 108 thereof and lower the frame 70 together with the carriage bars 142, thereby permitting the edges of the laden pallets to come to rest upon the shelf members 328 and 330 of the rack 306.

As the carriage moves downward, the lower surface of the bars 142 approach the next lower shelf in the pallet rack 306 and move downward toward empty pallets resting on the next lower shelf rails 328 and 330. The carriage continues to move downwardly until a switch bar 334 engages the upper surface of the next lower unladen pallet. This switch bar 334 is pivotally mounted on one of the bars 142 by a bolt 336, as shown best in FIG. 11 of the drawings. The rearward end of the bar 334 is provided with an upwardly extending portion 338, which contacts a pivoted arm 340 of a limit switch 29. When this arm 340 is moved upwardly, it opens the contacts of limit switch 29 and thus opens a circuit and de-energizes the magnetic shelf height locator 320 and a latch bar solenoid 352.

It will be understood that previous to de-energization the magnetic shelf height locator 320 held itself fixed on the vertical bar 322 and while the bars 142 of the carriage move down to actuate limit switch 29, a latch bar 346 carried by the frame 70 moves down a distance correspondingly below the magnetic shelf height locator 320, as shown in FIG. 14. Thus, when the magnetic shelf height locator 320 is de-energized and slides down the bar 322, an arm 342 is disposed to engage an arm 344 of the latch bar 346 which is pivoted on the carriage frame 70 by a pin 348. Thus, the magnetic shelf height locator 320 drops to a position limited by the arm 344 in correspondence with the vertical disposition of an unladen pallet previously located by the bar 334 which actuates limit switch 29 to de-energize the electromagnet of the magnetic shelf height locator 320.

The latch bar 346 is normally held in the solid line position, as shown in FIG. 14, by a spring 350 and this latch bar 346 may be pivotally actuated by a solenoid 352 in order to pivot the arm portion 344 out of interference with the arm 342 of the magnetic shelf height locator, as will be hereinafter described in detail.

It will be noted here that the solenoid 352 and the magnetic shelf height locator 320 are in circuit with each other, whereby they are concurrently energized and de-energized. Thus, when the magnetic shelf height locator is energized and fixed on the bar 322, the solenoid 352 is also energized to hold the arm 344 out of interference with the arm 342, whereby the arm 344, carried by the frame, may pass the arm 342 without disturbing the position of the shelf height locator.

When the switch 29 is actuated, as hereinbefore described, it also energizes the stepping switch actuator 284 and energizes the stepping switch to a position in which the arms close with the contacts 7 of discs 271, 275, 277, and 279. It will be seen from FIG. 27 of the drawings, that the limit switch 29, when actuated by the arm portion 338, shown in FIG. 11, opens a switch 354 and closes a switch 356 whereby the magnetic shelf height locator 320 and the solenoid 352 are de-energized and the stepping switch actuator 284 is energized.

With the arms of stepping switch engaging contacts 7 of the discs 271, 275, 277, and 279, it will be seen that contact 7 on disc 279 is coupled with a solenoid valve 304 which supplies fluid under pressure to a hydraulic cylinder 180 in a direction to retract the plunger 178 and to cause retraction of the carriage bars 142 from a position between the vertical members of the pallet rack 306. During this retraction of the pallet carriage bars 142, a pallet hook 358, as shown in FIG. 9 of the drawings, rakes empty pallets from the shelf of the rack immediately below the laden pallets deposited on the shelf above. The hook 358 extends downwardly so that it engages the edge of the pallets and when the bars 142 of the pallet carriage are retracted, this hook 358 rakes the pallets backwardly onto the upper edges 192 and 194 of the bars 188 and 190, hereinbefore described in connection with FIG. 16 of the drawings. As the carriage is retracted, the bar 308, shown in FIG. 4 of the drawings, contacts limit switch 8, shown in FIG. 3 of the drawings, and this limit switch energizes the stepper switch 273 to a position wherein the arms thereof are coupled to the contacts 8 of the discs 271, 275, 277, and 279, inclusive.

Contact 8 on disc 275 then provided closed circuit to the solenoid valve 290 due to the fact that an arm 359 of the limit switch 2, shown in FIGS. 13 and 27 of the drawings, is in a position wherein it closes a circuit to the solenoid valve 290 which conducts fluid under pressure to the hydraulic cylinder 110 in a direction to retract the plunger 108 thereof and to raise the carriage upwardly toward a level at which the concrete block producing machine delivers laden pallets. Concurrently, energy through contact of disc 277 energizes the solenoid valve 298 which conducts hydraulic fluid under pressure to the hydraulic cylinder 116 in a direction to retract its plunger 124 and to rotate the column 54 and carriage 70 in a clockwise direction, as shown in FIG. 2, to thereby swing the carriage of the present machine around toward a delivery axis H of the concrete block producing machine.

The operation of the reversing switch contacts 302 and 303, is simultaneously accomplished by a relay 364 controlled by a disc 366 of a stepper switch 368 having additional discs 370 and 372, as will be hereinafter described.

It will be seen that the stepper switch 368 is energized by means of a conductor 374 coupled to conductor 274.

The relay 364 is a conventional spring loaded solenoid which spring loads the contacts 302 and 303 in one position with respect to the solenoid valves 298 and 300 while energization of the relay 364 causes magnetic shifting of the contacts 302 and 303 to a reverse position. These solenoid valves control the operation of hydraulic cylinders 116 and 118, respectively, which actuate the carriage to swing about a vertical axis. Reversal of the contacts 302 and 303 by the stepper switch 368 is accomplished each time four bays of a rack are filled whereby the solenoids 298 and 300 are properly energized to operate the carriage to and from the concrete block producing machine from either side of the delivery axis H, as shown in FIG. 2 of the drawings.

During the movement of the carriage around to the delivery axis H of the concrete block producing machine, the solenoid 316 is energized to supply fluid under pressure to the hydraulic cylinder 210 in order to force the plates 200 and 216 together so that the empty pallets carried on the edges 192 and 194 of the bars 188 and 190 will be centered relative to the delivery axis H of the concrete block producing machine so that the unladen pallets may be properly delivered to the machine, as will be hereinafter described.

As the carriage frame 70 moves upwardly during its swinging action into alignment with the axis H, hereinbefore described, the limit switch 12 approaches a stationary clip 295 on the bar 296, as shown in FIG. 13 of the drawings. A contact arm 378 of limit switch 12 contacts said clip 295 and this stops the upward travel of the carriage and positions it at a proper vertical level to align with the concrete block producing machine to dis-

charge empty pallets thereinto and subsequently to pick up loaded pallets.

Limit switch 13, as shown in FIG. 1 of the drawings, is carried by the upper member 104 of the frame and is operable by an arm 324, as hereinbefore described, so that as the carriage swings around in the direction of the arrow G, shown in FIG. 2 of the drawings, limit switch 13 is actuated to de-energize the solenoid valve 298 and to stop the actuation of the hydraulic cylinder plunger 124, shown in FIG. 6 of the drawings, in order to bring the carriage into alignment with the delivery axis H of the concrete block producing machine, as shown in FIG. 3 of the drawings. When limit switches 12 and 13 are closed in series with each other, as shown in FIG. 27, they energize the stepper switch actuator 284 so that the arms of this stepper switch move to contacts 9 of discs 271, 275, 277, and 279, inclusive. In this position, the stepper switch energizes the solenoid valve 322 by means of the contact 9 on disc 279, whereupon fluid under pressure is supplied to the hydraulic cylinder 180 to extend the plunger 178 thereof, and to extend the bars 142 to a position relative to the concrete block producing machine, wherein the unladen pallets are moved, by a downwardly depending member 191, from the bars 188 and 190 into the concrete block producing machine and wherein these bars 142 are disposed to receive laden pallets from the machine. The downwardly depending member 191 is carried at the lower portions of the bars 142 and 144, all as shown in FIGS. 10, 24 and 25. At the outward limit of carriage travel, during the extension of the bars 142, limit switch 141 is actuated by the bar 308 on the pallet carriage, whereby the solenoid valve 332 is operated to stop the flow of hydraulic fluid to the cylinder 180. It will be seen that the solenoid valve 332 is concurrently de-energized with the energization of the actuator 284 of the stepper switch when it is then actuated to a position in which the arms 276, 278, 280 and 282 are moved to the contacts 9 of the discs 271, 275, 277, and 279, inclusive. At this time, the stepper switch is automatically energized through positions corresponding to contacts 10, 11, 12, and 13, of discs 1 to 4, inclusive, which returns the stepper switch arms to contacts 1 on the respective discs.

The pallet handling machine of the present invention, then proceeds through subsequent cycles corresponding to the hereinbefore described cycle, until the shelves of the racks 306, below the machine level are filled with laden pallets, whereupon the carriage finally moves to a position below the normal level of the lowermost pallet shelf, whereupon an arm 382 of limit switch 17 engages a clip 384 on the bar 296 to de-energize solenoid valve 314 and stop it from supplying fluid under pressure to the plunger 108 and the lowering of the carriage frame 70. It will be seen that the limit switch 17 is provided with a contact arm 382 which closes to energize the stepper switch actuator 284 which thereby moves the arm 278 from contact 6 to contact 7 on disc 275 of the stepper switch which results in de-energization of the solenoid valve 314.

When limit switch 17 is actuated, as hereinbefore described, its contact arm 388, shown in FIG. 27, closes a circuit to relays 390 and 392.

When limit switch 17 is operated, it also energizes an actuator 426 of the stepper switch 368, as will be hereinafter described.

When relay 390 is energized, it opens contacts 394, de-energizing the electromagnet 352 and the magnetic shelf height locator 320 so that it may be slidably moved upwardly on the bar 322 by engagement of the lever arm 344 with the arm 342 projecting from the shelf height locator 320, all as shown best in FIG. 14 of the drawings.

With the de-energization of contact 7 on disc 271 of the stopper switch 273, the pallet handling carriage is retracted, as hereinbefore described, and the carriage then moves upwardly to a level coinciding with the concrete block producing machine so that it may return to the machine in alignment with the axis H, thereof, as hereinbefore described. As the carriage moves upwardly and while the shelf height locator 320 is de-energized, it is carried up the bar 322 by the lever 344 along with the carriage 70. During the movement of the shelf height locator 320, upwardly on the bar 322, a projecting arm 398, carried by the shelf height locator 320, contacts a roller 400 on a pivoted arm 402 of limit switch 2, thereby pivoting this arm and contact arm 359 into the broken line position, as shown in FIGS. 14 and 27 of the drawings. This action moves the contact arm 358 of limit switch 2, as shown in FIG. 27 of the drawings, to the broken line position while the carriage 70 continues upward to a delivery level of the machine so that it may subsequently swing into alignment with the delivery axis H of the machine, as hereinbefore described, in connection with FIG. 2 of the drawings.

When the carriage of the present invention returns to the machine, as hereinbefore described, and receives laden pallets, the carriage is automatically energized to move upwardly to clear the machine, as hereinbefore described.

While the lowermost rack shelf has just been previously filled, it is now necessary that the machine carriage move upwardly to start filling the uppermost shelves of the next succeeding bay of pallet racks. Thus, as the carriage moves upwardly to clear the machine, as hereinbefore described, the arm 398, as shown in FIG. 14 of the drawings, moves beyond a position of limit switch 2 and contacts a roller 404 on a pivoted arm 406 of limit switch 1, thereby moving it to the broken line position, shown in FIG. 14 of the drawings. This moves the contact arm 310 of limit switch 1 into the broken line position shown in FIGS. 14 and 27.

From the foregoing it will be appreciated that LS1 and LS2 control vertical movement of the carriage with respect to a delivery level of the concrete block producing machine and with respect to pallet rack shelves above said delivery level and below said delivery level. As for example, as shown in FIGS. 14 and 27, when LS1 and LS2 are in the solid line positions, that in position 4 of each operating cycle of the machine, the solenoid valve 314 will be energized when the carriage is moving away from the machine so that the carriage will go down to a rack shelf below the delivery level of the machine.

In position 8 on disc 275, when the carriage is proceeding from the rack to the machine, it will be seen that LS2 at its arm 358 is closed with contact 363 so that the solenoid 290 will be energized and that the carriage will then be energized upwardly in its movement back to the delivery level of the concrete block producing machine.

When the arms 310 and 358 of LS1 and LS2, respectively, are in the broken line position, shown in FIGS. 14 and 27 of the drawings, a reverse situation will occur with respect to the vertical movement of the carriage and the delivery level of the concrete block producing machine. As for example, when contact 4 of an operating cycle is made on disc 275, the arm 310 will couple with contact 311 and thus, energize the solenoid 290 to energize the carriage upwardly as it moves away from the concrete block machine and subsequently when contact 8 on disc 275 is reached, contact arm 359 is engaged with contact 361, thus, energizing the solenoid valve 314 to energize the carriage downward in its return to the level of the concrete block producing machine. Thus, the switches LS1 and LS2 operated by arm 342, shown in FIG. 14, automatically prearrange the electrical circuit of the invention so that the carriage is properly energized in an upward direction or in a downward direction depending upon the preceeding cycles of operation of the machine. For example, when the carriage has filled pallet rack shelves and has progressively moved down from one cycle to the next, the switches LS1 and LS2 are tripped by the arm 398, shown in FIG. 14, and the carriage is thus automatically returned to the block producing machine at its delivery level, in accordance with

the disposition of the carriage as it fills its last successive rack shelf before returning to the concrete block producing machine.

As the pallet rack shelves are filled from the top toward the bottom, LS1 is first tripped from a broken line position to a solid line position, shown in FIG. 14, whereupon arm 310 engages contact 312 which in position 4 of an operating cycle with respect to disc 275, causes the carriage to move downwardly from the machine toward the rack and subsequently, as the arm 398 trips the arm 400 of LS2 from the broken line position to a solid line position, arm 358 engages contact 363 whereupon the carriage of the machine will move up from a rack shelf in its travel back to the delivery level of the machine.

At this time, the stopper switch arm 278 is coupled to contact 2 of disc 275 and the solenoid valve 290, as hereinbefore described, is energized which conducts fluid under pressure to the cylinder 110 so that it retracts its plunger and continues to move the carriage 70 upward.

During the time that the carriage continues to move upward, relay 5, which is a locking type relay provided with time delay circuitry, permits a time delay for the advancement of another rack of shelves. Attention being directed to FIG. 2 of the drawings, wherein several bays of the racks 306 are carried by a truck 408, having wheels 410 running on tracks 412. The truck 408 is provided with a suitable motor 414 to activate the wheels 410 for traction on the tracks 412 in order to advance the bays of racks 306, relative to the broken line position D of the pallet handling machine carriage, all as will be hereinafter described in detail. It will be seen that the rack carried by the truck 408 is provided with four bays having a plurality of superimposed shelves for receiving laden pallets thereon. The carriage 140 moves to its topmost position, wherein an arm 416 of limit switch 6 contacts a stop 418 on bar 296 which causes limit switch 6 to open and de-energize relay 4 which permits the contact arm 394 to close and energize the shelf height locator 320 so that it holds itself on the bar 322 until an unladen pallet is contacted, as hereinbefore described, whereupon the shelf height locator magnet is de-energized, permitting it to fall and establish an elevation of the unladen pallet by contact of the arm 342 upon the projecting arm 344 of the latch lever 346.

From the foregoing, it will be apparent that each time the lowermost shelf in one bay of the rack 306 is loaded and when the limit switch 17 is actuated, that the truck 408 must move another bay of rack shelves into alignment with the broken line position D of the pallet handling machine carriage. This same mode of operation is common to the opposite side of the pallet handling machine with relation to a truck 409, not shown, but which is similar to the truck 408.

When the contacts of limit switch 16 are closed, the relay 392 is energized, whereupon it locks its contact arms 443, 445, and 447, thereby closing the circuit to energize the motors 414 and 415 through contacts 445 and 447, respectively.

It will be understood that one of the trucks moves toward the concrete block producing machine for successive loading of the bays in the rack carried thereby, while the other truck 409, not shown, will be moving away from the machine after having been fully loaded in all of its bays. Thus, according to FIGS. 27 and 28 of the drawings, the truck 408 is movable by the motor 414 in response to a closing of the relay contact arm 445 and during the delay provided by operation of the thermally responsive element 418 of the relay 392, the motor 414 moves the truck 408 far enough so that the limit switch 22 is closed to permit operation of the motor 414 to continue until another clip 407, as shown in FIG. 2 of the drawings, opens the limit switch 22, whereupon another bay of rack shelves is aligned with the broken line position D of the carriage, as shown in FIG. 2 of the drawings.

It will be understood that a clip 407 is arranged to align with each bay of rack shelves so that each time a motor is energized by closing of the arm 445 of the relay 392, that sufficient time is provided for the motor 414 to move the truck far enough to clear the limit switch 22 from the respective clip 407 so that the motor 414 may continue to operate until another bay of rack shelves is reached whereupon another clip 407 will actuate the limit switch 22 and open the circuit to the motor 414.

As shown in FIG. 2, the clips 407 are mounted on a bar 403 which is slidably mounted on the truck 408 and thus bar 403 is spring loaded in a direction away from the motor 414 by a spring 401. A clip 405 on the bar 403 is engaged by the end of the pallet rack when loaded on the truck 408 whereby the bar 403 is adjusted longitudinally against tension of the spring 401 as that the clips 407 carried by the bar 403 are moved to coincide with the positions of the respective bays of the rack.

It will be understood that after all of the bays of the rack on the truck 408 have been filled, that the truck is in the nearest position forward toward the concrete block producing machine and that it must then be reversed and moved in the opposite direction while the other truck 409, not shown, is advanced bay by bay toward the machine delivering the concrete blocks for successive filling of the bays of rack shelves. During reverse movement of the truck 408, the limit switch 23 acts in a similar manner to the limit switch 22 but permits the motor 414 to operate in the reverse direction so that the rack is moved away from the concrete block producing machine. A clip 411 on the truck 408 contacts an arm 413 of limit switch 23 to stop the truck when moving in the reverse direction.

It will be seen that the limit switch 22 is coupled to contacts 5, 6, 7, and 8, of discs 372, while the limit switch 23 is coupled to contacts 1, 2, 3, and 4 of said discs 372. Thus, there are four contacts operating to energize the motor 414 in reverse while there are four contacts operable to move the truck by energizing the motor 414 in the forward direction.

The truck 409, not shown, is provided with a motor 415, shown in FIG. 27 of the drawings, and this motor 415 is operable through a contact arm 447 and limit switch 20 to operate the motor 415 to move the truck 409 forward while the limit switch 21 is operable to control the reverse operation of the motor 415 to move the truck 409 in the reverse direction. Likewise, the disc 370 of the stepper switch 368 is provided with four contacts for reverse operation of the motor 415 and four contacts for forward operation of the motor 415, all of which is similar to operation of the motor 414, hereinbefore described. It will be seen that the stepping switch 368 is coupled through four of its contacts on disc 366 to the relay 364 which is disposed to reverse the disposition of the contact arms 302 and 303 in order to provide reverse operation of the solenoid valves 298 and 300 so that the cylinders 116 and 118, as shown in FIG. 6 of the drawings, will cause the carriage of the pallet handling machine to move in one direction when leaving the axis H of the concrete block producing machine, toward the truck 408, while the absence of the contacts on the remainder of the disc 366 permits the relay 364 to hold the contact arms 302 and 303 in the opposite direction so that the solenoid valves 298 and 300 will cause the carriage of the machine to be energized in the opposite direction by one of the cylinders 116 or 118 to move in the direction of the arrow G when leaving the axis H of the concrete block producing machine.

Each time the limit switch 17 is actuated, the stepper switch 368, comprising discs 366, 370, and 372, is advanced one position whereby contacts are successively made in a similar manner to that hereinbefore described in connection with the stepper switch 273, which comprised discs 271, 275, 277, and 279, inclusive, and the arms 276, 278, 280, and 282, inclusively.

When the arm 420 traverses the disc 366 of the stepping switch 368 to a position of contact 5 thereon a conven-

tional reset device 425 is energized which automatically moves the arm 420 to a position in contact with contact No. 1 on disc 366.

As shown in FIG. 21, the uppermost shelf of a rack bay, when approached by the carriage of the pallet handling machine, is laden with empty pallets 424. These pallets 424 are shoved to the rear and off the respective upper shelf onto a receiving rack 426 which is stationarily located in line with the broken line position of the pallet handling carriage as illustrated by the reference character D in FIG. 2 of the drawings. When the unladen pallets are shoved off onto the rack 426, they are held at a level which is normally above unladen pallets disposed on the third shelf from the top, as shown in FIG. 22 of the drawings, and when the unladen pallets drop onto the rack 426, they actuate limit switch 24 which energizes a solenoid valve 428 which conducts hydraulic fluid under pressure to a hydraulic cylinder 430 causing its plunger 432 to extend and to force the pallets from the rack 426 and onto the unladen pallets disposed on the third shelf down from the top of the pallet rack shown in FIG. 23 of the drawings. When the pallet handling machine of the present invention places laden pallets on the second shelf from the top of the pallet rack, shown in FIG. 23 of the drawings, the carriage then moves down to a position in which the hook 358 engages all of the pallets on the third shelf from the top and retracts them into a position upon the bars 188 and 190 for return to the machine in a similar manner to that hereinbefore described. It will be understood that when the laden pallets are delivered to the uppermost shelf in the rack, as shown in FIG. 22 of the drawings, that the precise location of the rack is not required from the standpoint of elevation. The shelf height locator 320 is not brought into play for the location of the uppermost shelf. This operation involves the outward movement of the machine carriage at a level K considerably above the upper shelf whereupon the carriage is lowered to a position below the level of the shelf, thereby depositing the laden pallets on the upper shelf of the rack. This is readily feasible since there are no pallets to be disturbed above the upper shelf on the rack. The lateral location of the pallet handling machine carriage, relative to the placement of laden pallets on the uppermost shelf, is accomplished, as hereinbefore described, by means of the hydraulic cylinder 240 and its respective lateral locator which may comprise either the roller 248, shown in FIG. 18 of the drawings, or the converging fork structure 254, shown in FIG. 19 of the drawings.

It will be obvious to those skilled in the art that various modifications of the present invention may be resorted to in a manner limited only by a just interpretation of the following claims.

We claim:

1. In a means for handling building block pallets comprising: a first machine disposed to transfer block laden pallets from a building block producing machine to a rack having a plurality of substantially horizontal vertically spaced rack shelf portions; the invention comprising pallet carrying means of said first machine for carrying block laden pallets thereon; vertically movable means for moving said pallet carrying means up and down; horizontally reciprocating means for reciprocating said pallet carrying means horizontally; pallet engaging electrical switch means connected to said pallet carrying means and engageable with an unladen pallet supported on said rack; a vertical bar of magnetic material stationarily mounted; an electromagnet slidably mounted thereon and normally responsive to gravity and tending, when de-energized, to slide downwardly on said bar of magnetic material, said electromagnet electrically coupled to said pallet engaging switch means, said electromagnet, when energized, holding itself fixed on said bar of magnetic material, said electromagnet de-energized by action of said switch means when it engages said unladen pallet; a solenoid actuated latch member carried by said vertically movable means and mounted to catch said electromagnet when it slides down on said bar to a position corresponding with a vertical position at which said switch means is actuated by contact with said unladen pallet, said latch member movable to a position to avoid catching said electromagnet when said vertically movable means moves upwardly or downwardly to dispose said latch member above or below said electromagnet; a first limit switch actuating means carried by said electromagnet; a second limit switch actuating means carried by said vertically movable means; a limit switch disposed to be operated by said first and second actuating means when said vertically movable means moves down to a position at which said second limit switch actuating means contacts said first limit switch actuating means; and power actuated means coupled with and responsive to operation of said limit switch to stop vertical movement of said vertically movable means.

2. In a means for handling building block pallets comprising: a first machine disposed to transfer block laden pallets from a building block producing machine to a rack having a plurality of substantially horizontal vertically spaced rack shelf portions; the invention comprising pallet carrying means of said first machine for carrying block laden pallets thereon; vertically movable means for moving said pallet carrying means up and down; horizontally reciprocating means for reciprocating said pallet carrying means horizontally; pallet engaging electrical switch means connected to said pallet carrying means and engagable with an unladen pallet supported on said rack; a vertical bar of magnetic material stationarily mounted; an electromagnet slidably mounted thereon and normally responsive to gravity and tending, when de-energized, to slide downwardly on said bar of magnetic material, said electromagnet electrically coupled to said pallet engaging switch means, said electromagnet, when energized, holding itself fixed on said bar of magnetic material, said electromagnet de-energized by action of said switch means when it engages said unladen pallet; a solenoid actuated latch member carried by said vertically movable means and movably mounted to catch said electromagnet when it slides down on said bar to a position corresponding with a vertical position at which said switch means is actuated by contact with said unladen pallet, said latch member movable to a position to avoid catching said electromagnet when said vertically movable means moves upwardly or downwardly to dispose said latch member above or below said electromagnet; a first limit switch actuating means carried by said electromagnet; a second limit switch actuating means carried by said vertically movable means; a limit switch disposed to be operated by said first and second actuating means when said vertically movable means moves down to a position at which said second limit switch actuating means contacts said first limit switch actuating means; and power actuated means coupled with and responsive to operation of said limit switch to stop vertical movement of said vertically movable means; and resilient means for holding said latch member in position to catch said electromagnet when said solenoid actuated latch member is de-energized.

3. In a means for handling building block pallets comprising: a first machine disposed to transfer block laden pallets from a building block producing machine to a rack having a plurality of substantially horizontal vertically spaced rack shelf portions; the invention comprising pallet carrying means of said first machine for carrying block laden pallets thereon; vertically movable means for moving said pallet carrying means up and down; horizontally reciprocating means for reciprocating said pallet carrying means horizontally; pallet engaging electrical switch means connected to said pallet carrying means and engagable with an unladen pallet supported on said rack; a vertical bar of magnetic material stationarily mounted; an electromagnet slidably mounted thereon and normally responsive to gravity and tending, when de-energized, to slide down-

wardly on said bar of magnetic material, said electromagnet electrically coupled to said pallet engaging switch means, said electro magnet, when energized, holding itself fixed on said bar of magnetic material, said electromagnet de-energized by action of said switch means when it engages said unladen pallet; a solenoid actuated latch member carried by said vertically movable means and movably mounted to catch said electromagnet when it slides down on said bar to a position corresponding with a vertical position at which said switch means is actuated by contact with said unladen pallet, said latch member movable to a position to avoid catching said electromagnet when said vertically movable means moves upwardly or downwardly to dispose said latch member above or below said electromagnet; a first limit switch actuating means carried by said electromagnet; a second limit switch actuating means carried by said vertically movable means; a limit switch disposed to be operated by said first and second actuating means when said vertically movable means moves down to a position at which said second limit switch actuating means contacts said first limit switch actuating means; and power actuated means coupled with and responsive to operation of said limit switch to stop vertical movement of said vertically movable means; said solenoid actuated latch member electrically coupled to said switch means and disposed to be de-energized by operation of said switch means concurrently with the de-energization of said electromagnet.

4. In a means for handling building block pallets comprising: a first machine disposed to transfer block laden pallets from a building block producing machine to a rack having a plurality of substantially horizontal vertically spaced rack shelf portions; the invention comprising pallet carrying means of said first machine for carrying block laden pallets thereon; vertically movable means for moving said pallet carrying means up and down; horizontally reciprocating means for reciprocating said pallet carrying means horizontally; pallet engaging means connected to said pallet carrying means and engagable with an unladen pallet supported on said rack; fifth means of said first machine responsive to the engagement of said pallet engaging means with said unladen pallet to establish a vertical level at which said vertically movable means will stop for delivery of the next laden pallet so that the horizontally reciprocating means may place said next laden pallet at the correct vertically spaced rack shelf which was previously occupied by said unladen pallet; first switch means disposed to stop said vertically movable means at a level corresponding to a laden pallet delivery level of a concrete block machine; some of said rack shelf portions disposed above said level and some of said rack shelf portions disposed below said level; second switch means operable by and in response to a vertical movement of said vertically movable means and disposed to control subsequent upward and downward movement of said vertically movable means above and below said delivery level whereby said rack shelf portions above and below said level may be respectively approached by said pallet handling means.

5. In a means for handling building block pallets comprising: a first machine disposed to transfer block laden pallets from a building block producing machine to a rack having a plurality of substantially horizontal vertically spaced rack shelf portions; the invention comprising pallet carrying means of said first machine for carrying block laden pallets thereon; vertically movable means for moving said pallet carrying means up and down; horizontally reciprocating means for reciprocating said pallet carrying means horizontally; pallet engaging means connected to said pallet carrying means and engagable with an unladen pallet supported on said rack; fifth means of said first machine responsive to the engagement of said pallet engaging means with said unladen pallet to establish a vertical level at which said vertically movable means will stop for delivery of the next laden pallet so that the horizontally reciprocating means may place said next laden pallet at the correct vertically spaced rack shelf which was previously occupied by said unladen pallet; first switch means disposed to stop said vertically movable means at a level corresponding to a laden pallet delivery level of a concrete block machine; some of said rack shelf portions disposed above said level and some of said rack shelf portions disposed below said level; second switch means operable by and in response to a vertical movement of said vertically movable means and disposed to control subsequent upward and downward movement of said vertically movable means above and below said delivery level whereby said rack shelf portions above and below said level may be respectively approached by said pallet handling means; said second switch means comprising switch mechanisms vertically disposed in spaced relationship to each other and stationary relative to said vertically movable means; further means carried by said vertically movable means disposed to trip said switch means at predetermined levels with respect to the delivery level of said building block producing machine whereby said pallet carrying means will be energized in a downward direction when returning from uppermost pallet rack shelves toward said delively level of said producing machine and whereby said pallet carrying means when operating below said delivery level will be energized upwardly when returning from pallet rack shelves disposed below said delivery level as the pallet carrying means returns from such lower shelves to the level of the building block producing machine.

References Cited by the Examiner

UNITED STATES PATENTS

3,011,661 12/1961 Thomas et al. ------- 214—16.4

GERALD M. FORLENZA, *Primary Examiner.*