




(86) Date de dépôt PCT/PCT Filing Date: 2012/02/16
(87) Date publication PCT/PCT Publication Date: 2012/08/23
(45) Date de délivrance/Issue Date: 2021/08/31
(85) Entrée phase nationale/National Entry: 2014/08/15
(86) N° demande PCT/PCT Application No.: US 2012/025466
(87) N° publication PCT/PCT Publication No.: 2012/112787
(30) Priorités/Priorities: 2011/02/16 (US61/443,599);
2012/02/15 (US13/397,611)

(51) Cl.Int./Int.Cl. *F17C 11/00* (2006.01),
F17C 5/00 (2006.01), *F17C 6/00* (2006.01)
(72) Inventeur/Inventor:
SMITH, PAUL H., JR., US
(73) Propriétaire/Owner:
SMITH, PAUL H., JR., US
(74) Agent: BORDEN LADNER GERVAIS LLP

(54) Titre : SYSTEMES D'ENERGIE A BASE D'HYDROGENE
(54) Title: HYDROGEN ENERGY SYSTEMS



(57) Abrégé/Abstract:

Hydrogen energy systems for obtaining hydrogen gas from a solid storage medium using controlled laser beams. Also disclosed are systems for charging/recharging magnesium with hydrogen to obtain magnesium hydride. Other relatively safe systems assisting storage, transport and use (as in vehicles) of such solid storage mediums are disclosed.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(10) International Publication Number
WO 2012/112787 A4

(43) International Publication Date
23 August 2012 (23.08.2012)

(51) International Patent Classification:

F17C 11/00 (2006.01) *F17C 6/00* (2006.01)
F17C 5/00 (2006.01)

(21) International Application Number:

PCT/US2012/025466

(22) International Filing Date:

16 February 2012 (16.02.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/443,599 16 February 2011 (16.02.2011) US
13/397,611 15 February 2012 (15.02.2012) US

(71) Applicant (for all designated States except US): **CARE H2 ENERGY SYSTEMS, LLC** [US/US]; 145 S. 79th Street, #1, Chandler, AZ 85226 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SMITH, Paul H., Jr.** [US/US]; 29760 N. 67th Street, Scottsdale, AZ 85266 (US).

(74) Agent: **STONEMAN, Martin, L.**; Stoneman Law Patent Group, P.O. Box 40070, Phoenix, AZ 85067 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: HYDROGEN ENERGY SYSTEMS




FIG. 1

(57) Abstract: Hydrogen energy systems for obtaining hydrogen gas from a solid storage medium using controlled laser beams. Also disclosed are systems for charging/recharging magnesium with hydrogen to obtain magnesium hydride. Other relatively safe systems assisting storage, transport and use (as in vehicles) of such solid storage mediums are disclosed.

WO 2012/112787 A4



Declarations under Rule 4.17:

— *of inventorship (Rule 4.17(iv))*

(88) Date of publication of the international search report:
27 December 2012

Published:

— *with international search report (Art. 21(3))*

— *with amended claims (Art. 19(1))*

Date of publication of the amended claims: 7 February 2013

HYDROGEN ENERGY SYSTEMS

BACKGROUND

This invention relates to providing hydrogen energy systems. More particularly, this invention relates to providing hydrogen energy systems using magnesium hydride for hydrogen storage. Even more particularly, this invention relates to such hydrogen energy systems using laser excitation to assist adsorption of hydrogen gas from the magnesium hydride.

In using hydrogen energy systems, it is difficult to safely store hydrogen gas for use in providing energy for systems, such as vehicles, given the highly combustible nature of hydrogen. While hydrogen has a high energy to weight ratio, storage of hydrogen in a gaseous state (even compressed) yields a low energy to volume ratio making such storage impractical, particularly for mobile use. Thus, it would be useful to provide safe and compact storage of hydrogen energy near a location where hydrogen gas will be used for energy purposes.

OBJECTS AND FEATURES OF THE INVENTION

A primary object and feature of the present invention is to provide a system overcoming the above-mentioned problem.

It is a further object and feature of the present invention to provide such a hydrogen energy system wherein such magnesium hydride may be safely stored.

Another object and feature of the present invention is to provide such magnesium hydride in the form of a "disk" resembling a CD.

Yet another object and feature of the present invention is to provide a laser system to cooperate with the magnesium hydride disk to provide release of hydrogen gas therefrom.

A further object and feature of the present invention is to provide a laser system utilizing an array of lasers to cooperate with the magnesium hydride disk to provide release of hydrogen gas therefrom.

Yet another object and feature of the present invention is to provide controlled coherent light energy to successive portions of a surface of such magnesium hydride disk to provide controlled release of hydrogen gas.

A further object and feature of the present invention is to provide a system for recharging such disks with hydrogen after such controlled release of hydrogen gas.

Another object and feature of the present invention is to provide hydrogen energy for at least one vehicle, preferably an automobile, in the form of hydrogen gas controllably released from such storage in magnesium hydride disks.

Another primary object and feature of the present invention is to provide a system of manufacturing magnesium hydride disks, which disks may releasably store hydrogen within a compact volume.

5 A further object and feature of the present invention is to provide a system of manufacturing magnesium hydride disks, which disks are perforated to expose a large surface area of interaction and may releasably store hydrogen within a compact volume.

A further primary object and feature of the present invention is to provide such hydrogen energy systems that are efficient, inexpensive, and handy. Other objects and features of this invention will become apparent with reference to the following descriptions.

10 SUMMARY OF THE INVENTION

In accordance with a preferred embodiment hereof, this invention provides a hydrogen energy system comprising: at least one hydrogen storer structured and arranged to store at least one substantial amount of hydrogen; wherein such at least one hydrogen storer comprises at least one hydrogen-release permitter structured and arranged to permit photonic-excitation-assisted
15 release of stored hydrogen from such at least one hydrogen storer; and at least one photonic exciter structured and arranged to photonicallly excite such at least one hydrogen storer to assist release of such stored hydrogen from such at least one hydrogen storer; wherein such at least one photonic exciter comprises at least one controller structured and arranged to control such photonic-excitation-assisted release of hydrogen gas so as to assist at least one commercial use.
20 Moreover, it provides such a hydrogen energy system wherein such at least one hydrogen-release permitter comprises at least one plasmonic-effect-capable dielectric structured and arranged to permit creation of surface plasmon polaritons. Additionally, it provides such a hydrogen energy system wherein such at least one plasmonic-effect-capable dielectric comprises at least one super-elastic material layer structured and arranged to permit resilience through multiple
25 absorption-desorption cycles. Also, it provides such a hydrogen energy system wherein such at least one photonic exciter comprises at least one array of lasers. In addition, it provides such a hydrogen energy system wherein such at least one plasmonic-effect-capable dielectric comprises at least Nitinol and magnesium.

In accordance with another preferred embodiment hereof, this invention provides a
30 hydrogen energy system comprising: at least one metal surface portion capable of absorbing hydrogen; at least one supply of hydrogen gas; and at least one electromagnetic field generator structured and arranged to generate at least one electromagnetic field sufficient to form at least one supply of hydrogen plasma; wherein such at least one electromagnetic field generator is located in at least one position such that such at least one supply of hydrogen plasma is located in

at least one second position; and at least one metal surface locator structured and arranged to locate such at least one metal surface portion within such at least one second position; wherein such at least one metal surface portion may absorb hydrogen to form at least one metal hydride surface portion. And, it provides such a hydrogen energy system wherein such at least one
5 metal surface portion comprises at least one plasmonic-effect-capable dielectric structured and arranged to permit creation of surface plasmon polaritons. Further, it provides such a hydrogen energy system wherein such at least one plasmonic-effect-capable dielectric comprises at least one super-elastic material layer structured and arranged to permit resilience through multiple absorption-desorption cycles. Even further, it provides such a hydrogen energy system wherein
10 such at least one plasmonic-effect-capable dielectric comprises at least Nitinol and magnesium. Moreover, it provides such a system wherein such at least one metal surface portion comprises at least one pattern of cavities structured and arranged to provide substantially uniform porosity. Additionally, it provides such a system wherein such at least one pattern of cavities comprises at least one angle, with respect to such at least one metal surface portion, of about
15 45°. Also, it provides such a system wherein each of such cavities comprises a diameter of about 50 μm . In addition, it provides such a system wherein such at least one metal surface portion comprises magnesium hydride.

In accordance with another preferred embodiment hereof, this invention provides a method, relating to manufacturing at least one hydrogen storer, comprising the steps of: vapor
20 depositing at least one hydrogen storer material adapted to store hydrogen onto at least one substrate; wherein such at least one hydrogen storer material and such at least one substrate comprise at least one plasmonic-effect-capable dielectric structured and arranged to permit creation of surface plasmon polaritons; cutting such at least one hydrogen storer material into at least one geometric shape; and perforating such at least one hydrogen storer material; wherein
25 such method produces at least one hydrogen storer. And, it provides such a method wherein such at least one geometric shape comprises at least one disk. Further, it provides such a method wherein the step of perforating comprises the step of drilling at least one hole. Even further, it provides such a method wherein the step drilling comprises at least one laser. Even further, it provides such a method wherein such at least one chemical comprises HCl. Even
30 further, it provides such a method wherein such at least one substrate comprises at least one super-elastic material structured and arranged to permit resilience through multiple absorption-desorption cycles. Even further, it provides such a method wherein such at least one hydrogen storer material comprises magnesium.

In accordance with another preferred embodiment hereof, this invention provides a process, relating to controlled commercial use of hydrogen gas, comprising the steps of: providing at least one supply of hydrogen gas; and providing at least one electromagnetic field sufficient to form at least one supply of hydrogen plasma; wherein such at least one supply of hydrogen plasma is formed adjacent to at least one metal surface portion capable of storing hydrogen; and wherein such at least one metal surface portion absorbs hydrogen from such at least one supply of hydrogen plasma to form at least one metal hydride; and providing at least one hydrogen storer structured and arranged to store, using such at least one metal hydride, at least one substantial amount of hydrogen so as to permit photonic-excitation-assisted release of stored hydrogen; using at least one photonic exciter to photonicallly excite such at least one hydrogen storer to assist release of such stored hydrogen as hydrogen gas; and controlling such photonic-excitation-assisted release of such hydrogen gas so as to assist at least one commercial use.

In accordance with another preferred embodiment hereof, this invention provides a hydrogen energy system comprising: at least one hydrogen storer structured and arranged to store at least one substantial amount of hydrogen; wherein such at least one hydrogen storer comprises at least one hydrogen-release permitter structured and arranged to permit photonic-excitation-assisted release of stored hydrogen from such at least one hydrogen storer; and at least one photonic exciter structured and arranged to photonicallly excite such at least one hydrogen storer to assist release of such stored hydrogen from such at least one hydrogen storer; wherein such at least one photonic exciter comprises at least one controller structured and arranged to control such photonic-excitation-assisted release of hydrogen gas so as to assist at least one commercial use.

In accordance with a preferred embodiment hereof, this invention also provides a hydrogen energy system comprising: at least one hydrogen storer structured and arranged to store at least one substantial amount of hydrogen; wherein such at least one hydrogen storer comprises at least one hydrogen-release permitter structured and arranged to permit photonic-excitation-assisted release of stored hydrogen from such at least one hydrogen storer; and at least one photonic exciter structured and arranged to photonicallly excite such at least one hydrogen storer to assist release of the stored hydrogen from such at least one hydrogen storer; wherein such at least one photonic exciter comprises at least one controller structured and arranged to control photonic-excitation-assisted release of hydrogen; and at least one hydrogen collector structured and arranged to assist collection of released hydrogen; wherein hydrogen may be stored in such at least one hydrogen storer until controllably released to permit use as desired.

Moreover, it provides such a hydrogen energy system wherein such at least one photonic exciter comprises at least one wavelength of light between about 530nm and about 1700nm. Additionally, it provides such a hydrogen energy system wherein such at least one photonic exciter comprises at least one wavelength of light of about 784nm. Also, it provides such a

5 hydrogen energy system wherein such at least one photonic exciter comprises at least one power between about 200mW and about 2000mW. In addition, it provides such a hydrogen energy system wherein such at least one photonic exciter comprises at least one power of about 200mW.

And, it provides such a hydrogen energy system wherein such at least one hydrogen collector comprises at least one negative pressure environment. Further, it provides such a

10 hydrogen energy system wherein such at least one negative pressure environment comprises at least one pressure between about negative one millimeter of mercury and about negative two atmospheres. Even further, it provides such a hydrogen energy system wherein such at least one negative pressure environment comprises at least one pressure of about negative one atmosphere.

Moreover, it provides such a hydrogen energy system wherein such at least one photonic exciter comprises at least one beam of light with at least one radius of between about 10nm and about 2mm. Additionally, it provides such a hydrogen energy system wherein such at least one photonic exciter comprises at least one beam of light with at least one radius of about 15nm. Also, it provides such a hydrogen energy system wherein such at least one photonic exciter is structured and arranged to excite at least one portion of such at least one hydrogen storer to

20 induce at least one temperature between about 280°C and about 390°C in such at least one portion. In addition, it provides such a hydrogen energy system wherein such at least one hydrogen storer comprises at least one hydride.

In accordance with another preferred embodiment hereof, this invention provides a hydrogen energy system comprising: at least one metal surface portion capable of absorbing

25 hydrogen; at least one supply of hydrogen gas; and at least one electromagnetic field generator structured and arranged to generate at least one electromagnetic field sufficient to form at least one supply of hydrogen plasma; wherein such at least one electromagnetic field generator is located in at least one position such that such at least one supply of hydrogen plasma is located in at least one second position; and at least one metal surface locator structured and arranged to

30 locate such at least one metal surface portion within such at least one second position; wherein such at least one metal surface portion may absorb hydrogen to form at least one metal hydride surface portion.

And, it provides such a hydrogen energy system wherein such at least one electromagnetic field generator comprises: at least one microwave field generator; and at least

one radio wave field generator. Further, it provides such a hydrogen energy system wherein such at least one microwave field generator comprises at least two microwave field generators.

5 In accordance with another preferred embodiment hereof, this invention provides a hydrogen energy system comprising: at least one hydrogen storer comprising at least one disk structured and arranged to store at least one substantial amount of hydrogen; wherein such at least one hydrogen storer comprises at least one central spin axis locator structured and arranged to locate at least one central spin axis of such at least one disk; and wherein such at least one disk may rotate about such at least one central spin axis of such at least one disk; and wherein such at least one disk comprises at least one spinner motor gripper capable of being gripped by at least one motor driven spinner; wherein such at least one spinner motor gripper is substantially concentric to such at least one central spin axis; wherein such at least one spinner motor gripper is structured and arranged to assist enabling such at least one disk to be spun about such at least one central spin axis of such at least one disk by such at least one motor driven spinner; and wherein such at least one disk is structured and arranged to spin substantially stably.

15 Even further, it provides such a hydrogen energy system wherein such at least one disk further comprises at least one outer diameter between about 50mm and about 150mm. Moreover, it provides such a hydrogen energy system wherein such at least one disk further comprises at least one outer diameter of about 120mm. Additionally, it provides such a hydrogen energy system wherein such at least one central spin axis locator comprises at least one diameter between about 5mm and about 15mm. Also, it provides such a hydrogen energy system wherein such at least one central spin axis locator comprises at least one diameter of about 15mm.

25 In addition, it provides such a hydrogen energy system wherein such at least one disk comprises at least one hydride disk. And, it provides such a hydrogen energy system wherein such at least one hydride disk further comprises at least one outer diameter between about 50mm and about 150mm. Further, it provides such a hydrogen energy system wherein such at least one hydride disk further comprises at least one outer diameter of about 120mm. Even further, it provides such a hydrogen energy system wherein such at least one central spin axis locator comprises at least one diameter between about 5mm and about 15mm. Moreover, it provides such a hydrogen energy system wherein such at least one central spin axis locator comprises at least one diameter of about 15mm.

30 Additionally, it provides such a hydrogen energy system wherein such at least one hydride disk comprises at least one thickness of about one millimeter. Also, it provides such a hydrogen energy system wherein such at least one hydride disk further comprises at least one

metal hydride. In addition, it provides such a hydrogen energy system wherein such at least one hydride disk substantially comprises magnesium hydride. And, it provides such a hydrogen energy system wherein such at least one hydride disk comprises hydrogenated AZ31B.

Further, it provides such a hydrogen energy system wherein such at least one hydride disk further comprises at least one catalyst structured and arranged to assist hydrogenation of such at least one hydride disk. Even further, it provides such a hydrogen energy system wherein such at least one catalyst comprises nickel. Moreover, it provides such a hydrogen energy system wherein such at least one catalyst comprises palladium. Additionally, it provides such a hydrogen energy system wherein such at least one catalyst comprises titanium. Also, it provides such a hydrogen energy system wherein such at least one hydride disk comprises surface irregularities of less than about two micrometers. In addition, it provides such a hydrogen energy system further comprising at least one disk coating comprising at least one optically clear mineral oil.

And, it provides such a hydrogen energy system further comprising: at least one photonic-exciter structured and arranged to photonicallly excite such at least one hydrogen storer to assist release of the stored hydrogen from such at least one hydrogen storer; and wherein such at least one hydrogen storer comprises at least one hydrogen-release permitter structured and arranged to permit photonic-excitation-assisted release of stored hydrogen from such at least one hydrogen storer; and wherein such at least one photonic-exciter comprises at least one controller structured and arranged to control photonic-excitation-assisted release of hydrogen; and at least one hydrogen collector structured and arranged to assist collection of released hydrogen; and wherein hydrogen may be stored in such at least one hydrogen storer until controllably released permitting use as desired.

Further, it provides such a hydrogen energy system wherein such at least one disk comprises at least one hydride. The hydrogen energy system wherein such at least one disk is stored in at least one optically clear mineral oil. Even further, it provides such a hydrogen energy system wherein such at least one hydrogen collector further comprises at least one mineral oil condenser structured and arranged to assist collection of mineral oil vaporized during such photonic-exciter-assisted release of hydrogen.

Moreover, it provides such a hydrogen energy system further comprising: at least one hydrogen fuel user structured and arranged to use hydrogen as at least one fuel in at least one vehicle; wherein such at least one hydrogen fuel user comprises at least one energy converter structured and arranged to assist conversion of collected hydrogen through at least one energy-conversion process; and wherein such at least one energy-conversion process provides energy to

operate such at least one vehicle. Additionally, it provides such a hydrogen energy system further comprising at least one hydrogen container structured and arranged to contain at least one volume of hydrogen sufficient to supply increased fuel demand from such at least one vehicle during acceleration. Also, it provides such a hydrogen energy system wherein such at least one
5 energy converter comprises at least one combustion engine.

In addition, it provides such a hydrogen energy system further comprising at least one hydrogen container structured and arranged to contain at least one volume of hydrogen sufficient to supply increased fuel demand from such at least one vehicle during acceleration. And, it provides such a hydrogen energy system wherein such at least one energy converter comprises at
10 least one hydrogen fuel cell.

Further, it provides such a hydrogen energy system further comprising: at least one supply of hydrogen gas; and at least one electromagnetic field generator structured and arranged to generate at least one electromagnetic field sufficient to form at least one supply of hydrogen plasma; wherein such at least one electromagnetic field generator is located in at least one
15 position such that the at least one supply of hydrogen plasma is located in at least one second position; and wherein such at least one hydrogen storer further comprises at least one metal surface portion capable of absorbing hydrogen; and at least one metal surface locator structured and arranged to locate such at least one metal surface portion within such at least one second position; wherein such at least one metal surface portion may absorb hydrogen to form at least
20 one metal hydride surface portion.

Even further, it provides such a hydrogen energy system wherein a plurality of such at least one hydrogen storers locate serially through such at least one second position. Moreover, it provides such a hydrogen energy system wherein such at least one hydride disk is stored in at least one optically clear mineral oil. Additionally, it provides such a hydrogen energy system
25 wherein such plurality of such at least one hydrogen storers may remain in such at least one optically clear mineral oil.

In accordance with another preferred embodiment hereof, this invention provides a process, relating to use of hydrogen, comprising the steps of: providing at least one supply of hydrogen gas; and providing at least one electromagnetic field sufficient to form at least one
30 supply of hydrogen plasma; wherein such at least one hydrogen plasma is formed adjacent to at least one metal surface portion capable of storing hydrogen; and wherein such at least one metal surface portion may absorb hydrogen from such at least one supply of hydrogen plasma to form at least one metal hydride.

In accordance with another preferred embodiment hereof, this invention provides a process, relating to use of hydrogen, comprising the steps of: providing at least one hydride disk capable of releasing hydrogen through photonicallly induced heating; removing at least one hydrogen-expanded hydride disk from at least one vehicle; replacing such at least one hydrogen-expanded hydride disk with such at least one hydride disk; and disposing of such at least one hydrogen-expanded hydride disk. Also, it provides such a process wherein such step of disposing comprises recycling of such at least one hydrogen-expanded hydride disk.

In accordance with another preferred embodiment hereof, this invention provides a process, relating to use of hydrogen, comprising the steps of: providing at least one hydrogen-expanded hydride disk capable of being recycled; purging such at least one hydrogen-expanded hydride disk of any unreleased hydrogen; and recharging such purged at least one hydrogen-expanded hydride disk with hydrogen forming at least one hydride disk capable of releasing hydrogen through photonicallly induced heating.

In accordance with another preferred embodiment hereof, this invention provides a hydrogen energy system comprising: at least one hydrogen storer structured and arranged to store at least one substantial amount of hydrogen; wherein such at least one hydrogen storer comprises at least one substantially full state when such at least one hydrogen storer stores such at least one substantial amount of hydrogen; wherein such at least one hydrogen storer comprises at least one substantially empty state when such at least one hydrogen storer stores substantially no amount hydrogen; and wherein such at least one hydrogen storer comprises at least one substantial variation between transparency of such at least one substantially full state and transparency of such at least one substantially empty state; and at least one transparency variation detection device structured and arranged to detect such at least one substantial variation in transparency of such at least one hydrogen storer; at least one transparency variation data collector structured and arranged to collect transparency variation data from such at least one transparency variation detection device; and at least one transparency variation data processor structured and arranged to evaluate collected transparency variation data; wherein such evaluation results in at least one value indicative of hydrogen content of such system.

In accordance with another preferred embodiment hereof, this invention provides a hydrogen energy system comprising: hydrogen storer means for storing at least one substantial amount of hydrogen; wherein such hydrogen storer means comprises hydrogen-release permitter means for permitting photonic-excitation-assisted release of stored hydrogen from such hydrogen storer means; and photonic-exciter means for photonicallly exciting such hydrogen storer means to assist release of the stored hydrogen from such hydrogen storer means; wherein such

photonic-exciter means comprises controller means for controlling photonic-excitation-assisted release of hydrogen; and hydrogen collector means for assisting collecting released hydrogen; wherein hydrogen may be stored in such hydrogen storer means until controllably released to permit use as desired.

5 In accordance with another preferred embodiment hereof, this invention provides a hydrogen energy system comprising: metal surface portion means for providing at least one metal surface portion capable of absorbing hydrogen; hydrogen supply means for providing at least one supply of hydrogen gas; and electromagnetic field generator means for generating at least one electromagnetic field sufficient to form at least one supply of hydrogen plasma;
10 wherein such electromagnetic field generator means is located in at least one position such that the at least one supply of hydrogen plasma is located in at least one second position; and metal surface locator means for locating such metal surface portion means within such at least one second position; wherein such metal surface portion means may absorb hydrogen to form at least one metal hydride surface portion.

15 In accordance with another preferred embodiment hereof, this invention provides a hydrogen energy system comprising: hydrogen storer means, comprising at least one disk, for storing at least one substantial amount of hydrogen; wherein such hydrogen storer means comprises central spin axis locator means for locating at least one central spin axis of such at least one disk; wherein such at least one disk may rotate about such at least one central spin axis
20 of such at least one hydride disk; wherein such hydrogen storer means comprises spinner motor gripper means for being by at least one motor driven spinner; wherein such spinner motor gripper means is substantially concentric to such at least one central spin axis; wherein such spinner motor gripper means enables such at least one disk to be spun about such at least one central spin axis of such at least one disk by such at least one motor driven spinner; and wherein
25 during spinning, such at least one disk spins substantially stably.

In accordance with another preferred embodiment hereof, this invention provides such a system wherein such at least one metal surface portion comprises at least one pattern of cavities structured and arranged to provide substantially uniform porosity. In accordance with another preferred embodiment hereof, this invention provides such a system wherein such at least one
30 pattern of cavities comprises at least one angle, with respect to such at least one metal surface portion, of about 45°. In accordance with another preferred embodiment hereof, this invention provides such a system wherein each of such cavities comprises a diameter of about 50 μm . In accordance with another preferred embodiment hereof, this invention provides a system wherein such at least one metal surface portion comprises precipitated magnesium plate adapted to be cut

into disks and contain such holes. In accordance with another preferred embodiment hereof, this invention provides such a system wherein such at least one metal surface portion comprises magnesium hydride. In accordance with another preferred embodiment hereof, this invention provides such a system wherein such at least one metal surface portion comprises a plurality of
5 non-porous strut portions structured and arranged to add stiffness. In accordance with another preferred embodiment hereof, this invention provides such a system wherein such at least one metal surface portion comprises at least one thin, stiff non-magnesium frame structured and arranged to add stiffness. In accordance with another preferred embodiment hereof, this invention provides such a system wherein such at least one metal surface portion comprises at
10 least one thin surface-coating substantially comprising nickel and Mg_2Ni . And, it provides such a system wherein such at least one photonic exciter comprises at least one array of lasers. In accordance with another preferred embodiment hereof, this invention provides such a system wherein such at least one catalyst comprises nickel. In accordance with another preferred embodiment hereof, this invention provides such a system wherein such at least one catalyst
15 comprises palladium.

In accordance with another preferred embodiment hereof, this invention provides a method, relating to manufacturing at least one hydrogen storer, comprising the steps of: precipitating at least one hydrogen storer material adapted to store hydrogen; cutting such at least one hydrogen storer material into at least one geometric shape; perforating such at least one
20 hydrogen storer material; etching at least one surface of such at least one hydrogen storer material with at least one chemical; washing such at least one surface to remove such at least one chemical; embedding, in such at least one surface, at least one catalyst structured and arranged to assist hydrogenation of such at least one surface; coating such at least one surface with at least one surface reaction preventer; whereby such method produces at least one hydrogen storer.
25 Further, it provides such a method wherein such at least one geometric shape comprises at least one disk. Even further, it provides such a method wherein the step of perforating comprises the step of drilling at least one hole. Even further, it provides such a method wherein the step drilling comprises at least one laser. Even further, it provides such a method wherein such at least one chemical comprises HCl. Even further, it provides such a method wherein such at least
30 one surface reaction preventer comprises nickel and Mg_2Ni . Even further, it provides such a method wherein such at least one hydrogen storer material comprises magnesium. In accordance with preferred embodiments hereof, this invention provides for each and every novel feature, element, combination, step and/or method disclosed or suggested by this patent application.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a partial side view of a preferred hydride disk, illustrating release of hydrogen gas, preferably by laser heating, according to a preferred embodiment of the present invention.

5 FIG. 2 shows a cutaway perspective view, illustrating a preferred disk player, according to the preferred embodiment of FIG. 1.

FIG. 3 shows a top view, illustrating a preferred disk, according to the preferred embodiment of FIG. 1.

10 FIG. 4A shows a side view of a preferred disk, illustrating a preferred surface preparation, according to the preferred embodiment of FIG. 1.

FIG. 4B shows a side view of the preferred disk, illustrating introduction of preferred hydrogenation catalysts, according to the preferred embodiment of FIG. 3.

15 FIG. 5 shows a diagrammatic view of a preferred stainless-steel high-temperature pressure reactor, illustrating hydrogenation of a plurality of the preferred disks on a preferred spindle, according to the preferred embodiment of FIG. 4.

FIG. 6 shows a diagrammatic view, illustrating at least one preferred holding container for a plurality of the preferred hydride disks, according to the preferred embodiment of FIG. 1.

20 FIG. 7A shows a diagrammatic view of at least one preferred mineral oil removal system, illustrating removal of the preferred optically clear mineral oil from the preferred hydride disk, according to the preferred embodiment of FIG. 6.

FIG. 7B shows a diagrammatic view of the mineral oil removal system, illustrating removal of residual mineral oil from the preferred hydride disk, according to the preferred embodiment of FIG. 7A.

25 FIG. 8 shows a diagrammatic view, illustrating at least one preferred hydrogen supply system, according to the preferred embodiment of FIG. 1.

FIG. 9 shows a diagrammatic view of at least one preferred hydrogen recharging system, illustrating preferred re-hydrogenation of a used hydride disk, according to the preferred embodiment of FIG. 1.

30 FIG. 10 shows a diagram illustrating at least one preferred refueling method according to the preferred embodiment of FIG. 1.

FIG. 11 shows a diagram illustrating at least one preferred disk exchange method according to the preferred embodiment of FIG. 1.

FIG. 12A shows a plan view illustrating at least one hydride disk according to a preferred embodiment of the present invention.

FIG. 12B shows a magnified view of such preferred hydride disk according to the preferred embodiment of FIG. 12A.

FIG. 13 shows an enlarged view of section 13-13 of FIG. 12B.

FIG. 14 shows a diagrammatic view, illustrating the atomic order of such preferred
5 hydride disk, according to the preferred embodiment of FIG. 13.

FIG. 15 shows a flow chart, illustrating at least one hydride disk manufacturing process, according to the preferred embodiment of FIG. 14.

FIG. 16 shows a diagrammatic view, illustrating at least one sheet manufacturing process, according to the preferred embodiment of FIG. 15.

10 FIG. 17 shows a diagrammatic view of at least one drilling chamber, illustrating at least one perforating process, according to the preferred embodiment of FIG. 15.

FIG. 18 shows a diagrammatic flow chart, illustrating at least one hydrogenation process, according to the preferred embodiment of FIG. 15.

15 FIG. 19 shows a chart view illustrating temperature staging processes, during hydrogenation processes, according to the preferred embodiment of FIG. 18.

FIG. 20 shows a perspective view, illustrating a preferred spacer, according to the preferred embodiment of FIG. 18

FIG. 21A shows a plan view illustrating at least one hydride disk according to an alternate preferred embodiment of the present invention.

20 FIG. 21B shows a magnified view of such preferred hydride disk according to the preferred embodiment of FIG. 21A.

FIG. 22 shows an enlarged view of section 22-22 of FIG. 21B.

FIG. 23 shows an enlarged view of section 22-22 of FIG. 21B according to an alternately preferred embodiment of the present invention.

25
DETAILED DESCRIPTION OF THE BEST MODES
AND PREFERRED EMBODIMENTS OF THE INVENTION

Hydrogen absorption within reversible metal hydrides (including metal alloys) may be used as hydrogen storage devices. Applicant has found, by testing, that adsorbing hydrogen (as by destabilizing hydrogen bonds) from such metal hydrides at reasonable temperatures and with
30 reasonable energy expenditures may be best accomplished by very finely controlled heating. It has been found that this may provide an economical return of greater than about 5% (by weight) of hydrogen from a storage medium, with minimal energy consumption and system weight.

It is desirable to increase the absorbed hydrogen mass within the metal hydride while simultaneously reducing the energy required to release the hydrogen. Applicant has found that

metallic alloys and metallic capping layers, along with metal-doped chemical and organic carriers, are excellent storage media for hydrogen. However, one primary obstacle to releasing hydrogen, from such storage media, is a need for heat, since decomposition temperatures are typically greater than 200 °C.

5 Applicant has determined that laser heating of magnesium hydride is one preferred method for extracting hydrogen, with available technology and minimal energy cost. Employment of at least one laser diode, using pulsed-power, preferably provides ample heating of magnesium hydride to release hydrogen, as shown in FIG. 1. Applicant has found, including through experimentation, that less than about 80 continuous watts are needed to heat enough
10 magnesium hydride to release about 10 lbs (4.5 kg) of hydrogen at rates of up to about 2 lbs (0.9 kg) per hour. Such rates of hydrogen may theoretically provide internal combustion, hybrid, and hydrogen-fuel-cell vehicles a range in excess of about 200 miles, while adding less than about 330 lbs (150 kg) and about 6.3 cubic feet (0.18 cubic meters) or about 47 gallons (178 liters). Conventional CD (compact disk) motors, along with modified laser circuitry, may preferably
15 expose at least one magnesium hydride disk to at least one laser beam at rotations of up to about 24,000 rpm.

FIG. 1 shows a partial side view of at least one hydride disk **110**, illustrating release of hydrogen gas **150** preferably by laser heating, according to a preferred embodiment of the present invention. Hydrogen energy system **100** preferably comprises embodiment **101**, as
20 shown. Hydride disk **110** preferably comprises at least one metal hydride, preferably substantially magnesium hydride. As discussed herein, concentration of hydrogen, stored in hydride disk **110**, preferably should be greater than about 5% by weight, for economical efficiency. Magnesium hydride theoretically maximally stores about 7.6% hydrogen by weight. Upon reading this specification, those skilled in the art will now appreciate that, under
25 appropriate circumstances, considering such things as then available forms of metal hydride, abilities to place such forms in a rotatable “disk” shape structure for use with controlled laser heating, etc., other “disks” than unitary and/or complete “disks”, such segmented, liquid, or non-unitary “disks”, etc., may suffice.

Heating of hydride disk **110** preferably comprises localized heating by photonic
30 excitation using at least one coherent light source **160**, as shown. Coherent light source **160** preferably comprises at least one semiconductor laser diode **165**, as shown. Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances, considering such things as then available light sources, cost, used hydrogen storage medium, etc., other light sources, such as focused sunlight, phosphorescent light, biochemical light, etc., may

suffice. Semiconductor laser diode **165** preferably produces a beam of coherent light **170**, as shown, preferably between about 530 nm and about 1700 nm in wavelength, preferably about 784 nm in wavelength and with preferably between about 200 mW and about 2000 mW of power, preferably about 200 mW of power. Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances, considering such things as then available lasers, cost, used hydrogen storage medium, etc., other wavelengths of coherent light, such as other infrared wavelengths, visible spectrum, ultraviolet, etc., may suffice. To assist keeping semiconductor laser diode **165** from overheating, power is preferably pulsed instead of continuous.

10 Preferably, as coherent light **170** adsorbs hydrogen gas **150**, size of hydride disk **110** will preferably initially increase due to thermal expansion and then preferably reduce to pre-hydrogenated volumes. Some small amount of hydrogen movement from higher concentration to lower concentration theoretically can be expected in hydride disk **110** after adsorption of a particular track; but applicant has found such movement to be inconsequential in most
15 circumstances.

Preferably, coherent light source **160** further comprises at least one defocusing lens **162**, as shown. Defocusing lens **162** preferably alters focus of coherent light **170** to form at least one defocused laser beam **168**, as shown. Defocused laser beam **168** preferably comprises at least one beam radius **136** at surface **140**, as shown. Beam radius **136** preferably ranges between
20 about 10 nm and about 2 mm, preferably about 15 nm, as shown. Clearance **174** between defocusing lens **162** and surface **140** preferably is about two millimeters, as shown, assisting protecting defocusing lens **162** from impacting surface **140** due to slight deformations that may occur in surface **140**.

Applicant has determined, including by testing, that decomposition of magnesium
25 hydride using at least one surface temperature of about 390 °C, in a vacuum at about -5 bar, is reached within about 10 ns with enough conductivity to release 100% of stored hydrogen (up to about 7.6 wt %) within beam radius **136**, to a depth of about 20 micrometers. At at least one maximum effective decomposition distance **145** comprising about ½ mm, the temperature decreases to about 280 °C, dropping release of stored hydrogen to about 39.5% of maximum (up
30 to about 3 wt %). Since magnesium typically melts at about 650 °C, applicant has found that a surface temperature of about 390 °C (60% of melting temperature) roughly minimizes adiabatic evaporation of magnesium.

Coherent light source **160** preferably rides on at least one rail **175**, preferably moving radially, near at least one surface **140** of hydride disk **110**, as shown. Hydride disk **110**

preferably spins about a central axis **215** (see FIG. 2), preferably positioning surface **140** for defocused laser beam **168** to induce heating, as shown.

Absorptivity to infrared radiation is inversely proportional to thermal conductivity. Applicant has determined that, unlike for magnesium, thermal conductivity of magnesium hydride increases with rising temperature, attributable to radiation and “the Smoluchowski effect” (described in Marian Smoluchowski’s paper ‘Zur kinetischen Theorie der Brownschen molekulare Bewegung und der Suspensionen’ in *Annalen der Physik*, 21, 1906, 756-780). Heat capacity is also greater in magnesium hydride as compared to magnesium. Magnesium has a specific heat capacity of about 1050 J/(kg·K) (at 298 K) and the specific heat capacity of magnesium hydride is about 1440 J/(kg·K) (at 298 K). Further, magnesium’s thermal conductivity is about 156 W/(m·K), while magnesium hydride’s thermal conductivity is about 6 W/(m·K).

One formula, as determined by applicant, for thermal diffusivity (a) (a factor in the depth of thermal penetration), using thermal conductivity (λ), density (ρ), and specific heat (c) is:

$$a = \lambda / \rho c$$

Calculating thermal diffusivity for magnesium hydride gives:

$$a = (6 \text{ W/(m·K)}) / (0.001450 \text{ kg/m}^3 \times 1440 \text{ J/(kg·K)}) = 2.87 \times 10^6 \text{ J/(m}^3 \text{·K)}$$

Using this calculation of thermal diffusivity for magnesium hydride, applicant estimates thermal penetration (Z), based on a pulse time of 115 ns at 4x rotational speeds and 19 ns at 48x rotational speeds, as:

$$Z = \sqrt{4at} = 36334 \text{ nm at 4x (0.036 mm)}$$

$$Z = \sqrt{4at} = 14769 \text{ nm at 48x (0.015 mm)}$$

Estimated thermal penetration is inadequate for release of all stored hydrogen in hydride disk **110** by a factor of about 30, for a 1 mm thickness. Applicant has determined, however, that since magnesium hydride has a refractive index of about 1.96, which provides about 80% transparency, that optical penetration may aid in increasing release of stored hydrogen. Applicant has found that, through modification of power density to find at least one optimal power setting and beam radius **136**, maximum effective decomposition distance **145**, comprising about ½ mm, may be reached, as shown. In order to instigate hydrogen adsorption substantially through thickness **144** of hydride disk **110**, preferably, defocused laser beam **168** may also be incident upon opposing surface **142**.

Power density, mathematically defined as:

$$E=q/\pi r^2$$

where q is beam power and r is beam radius, determines peak temperature, near surface **140**, and thermal interaction at interface **172** of hydride disk **110** and defocused laser beam **168**.

- 5 Applicant has found that a power density capable of adsorbing hydrogen from magnesium hydride need only be concerned with the melting point of magnesium.

For magnesium hydride, coherent light source **160** preferably produces at least one temperature profile **130** in hydride disk **110**, due to thermal interaction at interface **172**, as shown. Temperature profile **130** preferably ranges from about 390 °C, near surface **140**, to about
10 280 °C at maximum effective decomposition distance **145**, as shown.

Applicant has found by testing that, after the course of repeated hydrogen absorption and desorption cycles, the fabricated disks appear lose the ability to absorb hydrogen to the full extent (0.345 wt %) initially noted when the disks were new. Analysis of the disks indicated that contaminants had blocked interstitial spaces and eventually coated areas along the surface of the
15 disks. These contaminants might be considered (theoretically) to be related to the lack of 100% purity and may be to be an inevitable consequence of the hydrogen source.

In testing and analysis of the previously mentioned lower-capacity disks, there was evidence of deuterium in the form of observed Time of Flight (“ToF”) hydrogen deuterium (“HD”) signals which were not evident in new disks. Time of Flight does not provide
20 quantitative analysis, and testing did identify the isotopes of hydrogen. A Secondary Ion Mass Spectrometry (SIMS) study may be necessary to determine evidence of increased concentration with each absorption and desorption cycle.

The evidence of detectable amounts of deuterium in desorbed disks may theoretically be explained by the stable, but larger structure of the HD molecule, along with its permanent dipole
25 moment. These characteristics may explain limited desorption of deuterium from the medium. Reducing the laser pulse length into the tens of femtoseconds would increase photon absorption by this molecule and potentially increase desorption. However, this approach may not reduce the general rise in contamination by other elements.

An explanation of the contamination by deuterium is inconclusive. The predominant
30 theory is that the molecules of HD and D₂ and even MgD₂ are more stable, individually and within the metal lattice, to the particular wavelengths and energy densities selected for desorption of H₂ from Mg₂NiH₄ + MgH₂. Over multiple cycles (using this theory), the concentration of deuterium rises in the material and reduces the recharging capability.

According to a less predominant theory, it may be suspected that a transmutation may occur due to: (1) the high degree of ionization afforded within the beam channels and (2) the fact that the molecular ions entering into the beam channels are subjected to intense vibration and oscillation in the presence of a nano-scale level electrostatic ion trap with increasing potentials.

- 5 Support for this less predominant theory may be found in: (1) occasions of thermal run-away in which unexplained increases in temperature are clearly detected and (2) the failure of the material to return to ambient temperature within the timeframe expected for the power density and EM pulse directed at the material.

FIG. 2 shows a cutaway perspective view, illustrating at least one preferred disk player
10 **210**, according to the preferred embodiment of FIG. 1. As shown, disk player **210** preferably comprises at least one spinning motor **230**, coherent light source **160** and disk changing mechanics. Such disk changing mechanics preferably accept at least one hydride disk **110**, preferably move such at least one hydride disk **110** to spinning motor, and preferably remove such at least one hydride disk **110**, once expended, from disk player **210**. Spinning motor **230**
15 preferably spins hydride disk **110** to achieve at least one linear motion of up to about 63 meters per second, preferably while coherent light source **160** liberates hydrogen gas **150** from hydride disk **110**, as shown. Disk player **210** preferably operates under vacuum between about -1 torr to about -5 torr. Such vacuum preferably serves to evacuate liberated hydrogen gas **150**, as shown in FIG. 1, and preferably maintains a neutral atmosphere around hydride disk **110**.

20 At least one control circuit **220**, as shown, preferably adjusts speed of spinning motor **230**, preferably moves coherent light source **160** on rail **175**, and preferably adjusts power output of coherent light source **160** (at least embodying herein at least one photonic exciter structured and arranged to photonicallly excite such at least one hydrogen storer to assist release of the stored hydrogen from such at least one hydrogen storer) to preferably optimize release of
25 hydrogen gas **150**. Output of hydrogen gas **150** is preferably optimized to demand for hydrogen gas **150** from at least one hydrogen-driven device **830** (see discussion relating to FIG. 8).

Applicant has determined that disk player **210** may preferably be reconfigured from existing compact disc writer (CD-R) technology. Applicant adapted at least one CD writer drive ("Iomega model 52x" CDRW drive) to adsorb stored hydrogen from hydride disk **110**. In order
30 to adapt such at least one CD writer to use hydride disk **110**, at least one control circuit **220**, as shown, preferably bypasses internal feedback controls of such at least one CD writer drive. Rather than relying on feedback information, control circuit **220** preferably uses direct manipulation of controlled components of disk player **210**, preferably allowing precise control.

Further, internal laser of CD writer preferably may be used provided such laser fulfills requirements given for semiconductor laser diode **165**.

Manufacturing Magnesium Hydride Disks

FIG. 3 shows a top view, illustrating at least one disk **315** according to embodiment **101** of FIG. 1. Such at least one disk **315** is preferably formed by cutting from at least one sheet preferably comprising at least one material capable of absorbing hydrogen, preferably metal, preferably made substantially of magnesium, preferably AZ31B (available commercially). Upon reading this specification, those skilled in the art will appreciate that, under appropriate circumstances, considering such things as available materials, economics, stored hydrogen density, etc. other materials capable of absorbing hydrogen, such as other metals, plastics, glass, etc., may suffice. Upon reading this specification, those skilled in the art will appreciate that, under appropriate circumstances, considering such things as safety, economics, materials used, etc. other disk formation methods, such as using injection molds, machining, laser cutting, etc., may suffice.

Disk **315** is preferably cut using at least one water cutter, alternately preferably using at least one stamp cutter. Disk **315** preferably is about one millimeter thick. Diameter **370** of disk **315** is cut preferably to between about 50 mm and about 150 mm, preferably about 120 mm. A center hole **360** is preferably cut in disk **315**, preferably between about five millimeters and about 15 millimeters in diameter, preferably about 15 millimeters. Preferably, center hole **360** allows disk **315** to be centered for stable spinning. Disk **315** preferably comprises at least one ring **365** concentric to center hole **360** (at least embodying herein wherein such at least one hydrogen storer comprises at least one central spin axis locator structured and arranged to locate at least one central spin axis of such at least one disk) preferably providing at least one friction grippable surface preferably to allow application of rotational torque to spin disk **315**, as shown (this arrangement at least embodying herein wherein such at least one disk comprises at least one spinner motor gripper capable of being gripped by at least one motor driven spinner).

FIG. 4A shows a side view of preferred disk **315**, illustrating surface preparation, according to embodiment **101** of FIG. 1. Preferably, after fabrication, oxidization layers, vapor deposits and other physical obstructions to hydrogenation must be removed from disk **315**. Surfaces **346** of disk **315** preferably may be smoothed to a mirror-like finish with irregularities of preferably less than two micrometers while incorporating small amounts of hydrogenation catalysts. Additionally, disk **315** preferably is structurally balanced so, when spun, surfaces **346** have minimal wobbling. Irregularities of surfaces **346** may be distorted, by the addition of hydrogen gas **150**, up to approximately 2-1/2 micrometers as disk **315** expands.

Disk **315** preferably is lightly sanded with titanium oxide to remove surface oxidation. Disk **315** preferably is then washed with 2% HF to remove bulk oxides and then preferably with dilute pepsin/HCL cleaning solution to remove residual sub-oxides. A plurality of such disks **315** are preferably stacked on at least one spindle **345** with at least one stainless steel washer **520**, as shown in Fig. 5, between each disk **315**. Dimensions of stainless steel washer **520** preferably comprise about 15.3 mm in inner diameter, about 18 mm in outer diameter, and about four millimeters in thickness. Spindle **345** preferably comprises steel, preferably stainless steel. Spindle **345** preferably comprises a diameter of about 14.9 mm. Spindle **345** preferably is positioned in vacuum chamber **310**, as shown. At least one vacuum chamber **310** is preferably purged with nitrogen. Vacuum chamber **310** is brought to preferably about 0.7 torr (0.014 psi) (0.001 bar) for preferably about one hour. After about 1 hour, the plurality of such disks **315**, on spindle **345**, preferably is rotated at about 18,000 rpm. At least one spray nozzle **330**, preferably designed for blasting at least one powder **340**, preferably is at a fixed distance from disk **315**, as shown. Powder **340** preferably comprises nickel powder, comprising a particle-size range of preferably about 2.6 micrometers to about 3.3 micrometers, preferably nickel powder commercially available as "Inco Type 287". Powder **340** is preferably blasted onto disk **315**, as shown, at about 50 psi preferably using argon gas. Disk **315** preferably is subsequently sandblasted with progressively smaller 99.9+% nickel particles, preferably from about -325 mesh to about -500 mesh (American Elements CAS no. 7440-02-0) at preferably about 40 psi using preferably nitrogen gas.

FIG. 4B shows a side view of disk **315**, illustrating introduction of preferred hydrogenation catalysts **440**, according to embodiment **101** of FIG. 1. Inside vacuum chamber **310**, disk **315** is preferably further treated with hydrogenation catalysts **440**, as shown. Hydrogenation catalysts **440** preferably comprise at least one submicron powder **445**, as shown. Hydrogenation catalysts **440** preferably are each applied for between about 10 minutes and about 15 minutes at preferably about 35 psi. Each of preferably three submicron powders **445** preferably comprises a purity of greater than about 99.999%. One Submicron powder **445** preferably comprises 99.999+% nickel. Another submicron powder **445** alternately preferably comprises 99.999+% palladium. Yet another submicron powder **445** alternately preferably comprises 99.999+% titanium. Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances, considering such things as then available materials, other catalyst technologies, cost, hydride material used, etc. other catalysts, such as other metals, plastics, resins, slurries, etc., may suffice.

Hydrogenation catalysts **440**, preferably as described, preferably are serially applied such that application of all hydrogenation catalysts **440** comprises between about 30 minutes and about 45 minutes. The amount of hydrogenation catalysts **440** used is insufficient for capping, and instead preferably serves as a “door man” to preferably keep hydrogen moving past outer layer of surfaces **346** where magnesium hydride formation and buildup could prevent further absorption of hydrogen. Surface preparation and treatments with hydrogenation catalysts **440** preferably provides necessary surface smoothness and preferably impregnates, through adhesion, a preferred amount of hydrogenation catalysts **440** without significant ablation of surfaces **346**.

Vacuum chamber **310** preferably is then returned to atmospheric pressure, preferably with nitrogen, and disk **315** preferably is removed to at least one stainless-steel high-temperature pressure reactor **510**, as shown in FIG. 5. Stainless-steel high-temperature pressure reactor **510** preferably is nitrogen-purged with 0.1 torr on the evacuation cycle, preferably through at least two purging cycles to prepare for hydrogenation. Disk **315** preferably is then ready for hydrogenation.

FIG. 5 shows a diagrammatic view of stainless-steel high-temperature pressure reactor **510**, illustrating preferred hydrogenation of disk **315** on spindle **345**, according to embodiment **101** of FIG. 1. At least one heating element **560** preferably heats stainless-steel high-temperature pressure reactor **510**, as shown, from preferably about 20 °C to preferably about 350 °C. The coefficient of thermal expansion (α) of magnesium is about $27 \cdot 10^{-6}/^{\circ}\text{C}$, which provides that disk **315** will expand from a diameter of about 120mm to about 121mm when raised from about 20 °C to about 350 °C. Because being raised from about 20 °C to about 350 °C effects closing of diameter of central hole by as much as about $\frac{1}{2}$ mm, prevention of size reduction of central hole by thermal expansion or hydrogenation is necessary. The plurality of disks **315** are preferably placed on spindle **345**, as shown, in order to prevent central hole closing. The coefficient of thermal expansion of stainless steel is about $17 \times 10^{-6}/^{\circ}\text{C}$. Spindle **345** expands from about 14.9 mm, at about 20 °C, to about 15mm in diameter, at about 350 °C. Since magnesium is less dense than stainless steel, spindle **345** preferably constrains disk **315** to expand vertically and radially outward as disk **315** is heated and hydrogenated.

Thermal and internal strain from forced expansion away from spindle **345** theoretically reduces absorption of hydrogen near center hole **360** of disk **315**, approximately within ring **365**. Such reduction in absorption is inconsequential since central area of hydride disk **110**, including ring **365**, is preferably not lased. Furthermore, heating is preferably incremented slowly to allow enough time for thermal equilibrium and expansion without undue stress. Such slow heating is preferably accompanied by slow increases in pressure. Hydrogenating slowly preferably allows

greater absorption of hydrogen gas **150** because build up of magnesium hydride does not occur near surfaces **346** impeding complete hydrogenation.

Pressure is preferably raised to atmospheric pressure with hydrogen gas **150** and at least one thermocouple **550**, as shown, is preferably set to about 21.1°C to establish initial
5 temperature. Small increments of temperature and pressure preferably are applied preferably over about 6 hours to preferably raise pressure to about 35 bar (500 psi) and temperature to preferably about 350 °C. Final temperature and pressure are preferably maintained for about an additional 2 hours.

At least one step motor **554**, which preferably can rotate disk **315** at about 18,000 rpm,
10 preferably comprises at least one axle **552**, as shown. Axle **552** is preferably passed into stainless-steel high-temperature pressure reactor **510**, as shown. Spindle **345** is preferably attached to axle **552**, as shown, allowing step motor **554** to spin spindle **345** inside stainless-steel high-temperature pressure reactor **510**. Rotation at about 18,000 rpm preferably allows additionally between about 700 psi and about 3000 psi to be exerted radially on disk **315**, once
15 initial hydrogenation is complete, and preferably allows a small amount of hydrogen “over loading”. Step motor **554** is preferably activated to spin spindle **345** and disk **315** at preferably about 18,000 rpm for about 1 hour. Afterwards, disk **315** preferably is slowed to a stop and preferably allowed to remain at full pressure and temperature for about 1 hour more.

Hydride disk **110** preferably is formed as Disk **315** preferably becomes fully
20 hydrogenated to nearly 100% magnesium hydride preferably with a hydrogen content of about 7.6%. Disk **315** theoretically grows dimensionally during hydrogenation by as much as about 17%, but the surface area of hydride disk **110** to be lased preferably remains the same. Hydride disk **110** is highly reactive in air, and great caution should be taken in handling and storage.

Magnesium hydride ignites spontaneously in air to form magnesium oxide and water.
25 Such ignition is a violent reaction, which cannot be stopped by addition of water or carbon dioxide. Therefore, consideration of the practicality of creating, storing, and transporting hydride disks **110**, comprising magnesium hydride, is important. Hydride disk **110** preferably is stored in at least one inert environment.

Before removing hydride disk **110** from stainless-steel high-temperature pressure reactor
30 **510**, pressure should preferably be allowed to return to atmospheric pressure through release of hydrogen gas **150**. Then, optically clear mineral oil **610** (preferably “Sontex LT-100”) is preferably pumped into stainless-steel high-temperature pressure reactor **510**, preferably to displace any remaining hydrogen gas **150**. Stainless-steel high-temperature pressure reactor **510** may be opened preferably only after a volume of optically clear mineral oil **610**, equal to the

interior volume of stainless-steel high-temperature pressure reactor **510** less the volume of hydride disk **110** and spindle **345**, has been pumped.

Alternately, hydride disks **110** are preferably stored in a light (-1 to -2 bar) vacuum. When storing in such light vacuum, optically clear mineral oil **610** need not be applied to hydride disks **110**. By not applying optically clear mineral oil **610**, other special handling to account for optically clear mineral oil **610** may be preferably bypassed. Upon reading this specification, those skilled in the art will now appreciate that, considering such issues as cost, future technologies, etc., other inert environments, such as, for example, inert gasses, other inert fluids, coatings, etc., may suffice.

Optically clear mineral oil **610**, as shown, (preferably C_nH_{2n+2}) preferably comprises a highly purified organic aliphatic hydrocarbon, preferably comprising an index of refraction of about 1.47 and a light transmittance of about 0.99972. Optically clear mineral oil **610** preferably does not interact with hydride disk **110**. Optically clear mineral oil **610** preferably acts as an atmospheric insulator to prevent oxidation and static discharge. Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances, considering such things as wavelength of light source, cost, available materials, etc., other atmospheric insulators, such as resins, other oils, solutions, etc., may suffice.

In addition, flow of hydrogen, due to concentration differences, is minimal due to inherently high hydrogen content of optically clear mineral oil **610**. Preferably, care should be taken to avoid any moisture content in optically clear mineral oil **610**, as well as in manufacturing environment, when stainless-steel high-temperature pressure reactor **510** is opened. Such moisture may cause formation of hydrogen peroxide (H_2O_2) in optically clear mineral oil **610**. In addition, ambient air preferably should be as dry as possible, also to preferably prevent hydrogen peroxide development in optically clear mineral oil **610**. Optically clear mineral oil **610** preferably has a loss of only about 0.028% of light passing through. Preferably, optically clear mineral oil **610** has a molecular weight of about 40.106, a flash point of about 135°C, a specific gravity greater than 0.8, and a boiling point approximately 300 °C. Hydride disk **110** preferably may now be removed from stainless-steel high-temperature pressure reactor **510** and preferably immediately placed in at least one holding container **600** of optically clear mineral oil **610**, as shown. Preferably, optically clear mineral oil **610** remains around hydride disks **110** to prevent contact with air. As mentioned, such contact may result in a violent reaction creating a magnesium fire.

FIG. 6 shows a diagrammatic view, illustrating at least one holding container **600** for a plurality of hydride disks **110**, according to embodiment **101** of FIG. 1. Transfer of hydride disk

110 from stainless-steel high-temperature pressure reactor **510** to optically clear mineral oil **610** in holding container **600** preferably should only be performed with proper safety apparel and adequate fire suppression available. An understanding of proper handling and methods of fire extinguishing of magnesium hydride is paramount. The information provided in this application is not an adequate substitute for proper training. Eye protection should be worn (preferably a welder's mask) because of the brilliance of a magnesium fire. Also, heat and fire resistant clothing should be worn due to the intensity of a magnesium hydride fire. Sand, in plastic bags, should preferably be available to place on a fire should one erupt. Tabletops and flooring should preferably be of soap stone or other inert material, not metal or wood. Carbon dioxide (CO₂) extinguishers or water should never be used on a magnesium fire, since such extinguishers promote the reaction. Alternately, holding container **600** preferably maintains a light vacuum for storage of hydride disk **110**, negating need for optically clear mineral oil **610**.

FIG. 7A shows a diagrammatic view of at least one mineral-oil removal system **700**, illustrating removal of optically clear mineral oil **610** from hydride disk **110**, according to embodiment **101** of FIG. 1. When using optically clear mineral oil **610**, optically clear mineral oil **610** preferably is removed from hydride disk **110**, using mineral-oil removal system **700**. The heat of vaporization of optically clear mineral oil **610**, comprising about 214 kJ/kg, is particularly important. The more optically clear mineral oil **610** left on hydride disk **110**, the more power needed to efficiently adsorb the stored hydrogen, since optically clear mineral oil **610** left on hydride disk **110** will absorb a portion of the heat generated by coherent light **170**.

Mineral-oil removal system **700** preferably comprises at least one disk spinner **710**, as shown. Disk spinner **710** preferably comprises at least one spinner motor **715**, as shown. Disk spinner **710** preferably operates in an area of negative pressure. Disk spinner **710** preferably may be adapted from at least one CD drive. To adapt such at least one CD drive, all electronic components preferably must be shielded from exposure to optically clear mineral oil **610**, preferably by at least one polymer, preferably polyvinyl. Prior to use, hydride disk **110** is preferably moved into disk spinner **710**, as shown, and preferably spun by spinner motor **715** to about 24,000 rpm to recover most of optically clear mineral oil **610**, preferably for reuse.

FIG. 7B shows a diagrammatic view of mineral oil removal system **700**, illustrating removal of residual mineral oil **712** from hydride disk **110**, according to embodiment **101** of FIG. 7A. Mineral oil removal system **700** preferably further comprises at least one residual mineral oil remover **717**, as shown. Residual mineral oil remover **717** preferably comprises at least two opposing suction vacuums **720**, as shown. After spinning, opposing suction vacuums **720** preferably pump off any residual mineral oil **712**, comprising optically clear mineral oil **610**, for

reuse, as shown. Opposing suction vacuums **720** preferably substantially cover diameter of hydride disk **110**, as shown. 100% recovery, of optically clear mineral oil **610**, may not be possible without vaporization during lasing of hydride disk **110**. Minimization of vaporization preferably minimizes energy consumption of the lasing process. Vaporized mineral oil

5 preferably should be collected for ecological and safety reasons. After removing optically clear mineral oil **610**, hydride disk **110** preferably is passed to disk player **210**, as discussed in FIG. 8, for hydrogen adsorption, as discussed herein (See FIGS. 1 & 2).

FIG. 8 shows a diagrammatic view, illustrating at least one hydrogen supply system **800**, according to the preferred embodiment of FIG. 1. Hydrogen supply system **800** preferably

10 comprises holding container **600**, mineral oil removal system **700** and disk player **210**, as shown. Hydride disk **110** is preferably moved from holding container **600** to mineral oil removal system **700**, preferably for optically clear mineral oil **610** removal, as shown. After optically clear mineral oil **610** is substantially removed, hydride disk **110** preferably transfers to disk player **210** for hydrogen adsorption, as shown. After completing at least one adsorption process, used

15 hydride disk **910** preferably is returned to holding container **600**, as shown, for safe storage. Processing of hydride disk **110** is preferably conducted under negative pressure (about -1 torr) preferably to allow for hydrogen collection and preferably preventing exposure of hydride disk **110** to air.

Unlike magnesium hydride, exhibiting 80% transparency, magnesium exhibits mirror like

20 opacity, when manufactured as discussed herein. Transparency variation of hydride disk **110** from used hydride disk **910** therefore preferably indicates hydrogen content. Such transparency variation may preferably be used to distinguish at least one used hydride disk **910** from such at least one hydride disk **110**, and may also preferably be used as at least one “gas” gauge **880**. At least one transparency probe **850** preferably polls stored disks **860**. Transparency information

25 passes to at least one processor **870** where quantities of such at least one hydride disk **110** and such at least one used hydride disk **910** are determined. At least one value is then calculated for available hydrogen stores and may be displayed as such at least one “gas” gauge **880**.

Hydrogen supply system **800** preferably further comprises at least one condensing tank **810**, as shown. Gases released from processing may contain vaporized mineral oil (when using

30 optically clear mineral oil **610**), in addition to hydrogen gas **150**. Such gases are preferably collected and preferably pass into condensing tank **810**. Condensing tank **810** preferably comprises at least one cooling environment at atmospheric pressure. Optically clear mineral oil **610** is not dissociated into its constituent elements by vaporization in an anaerobic atmosphere. Optically clear mineral oil **610** is preferably recaptured within condensing tank **810**, as shown.

After condensation of optically clear mineral oil **610** in condensing tank **810**, hydrogen gas **150** is preferably supplied to hydrogen-driven device **830**. Alternately preferably, hydrogen gas **150** is pressurized in at least one pressure tank **820** to at least one atmosphere of pressure, before being supplied to hydrogen-driven device **830**, as shown. Hydrogen gas **150** supplied by hydrogen supply system **800** preferably maintains supply of hydrogen gas required by hydrogen-driven device **830** to operate steadily. Pressure tank **820** preferably acts as a hydrogen gas reserve, allowing accelerated use of hydrogen gas **150**, for a limited time, beyond the hydrogen adsorption rate of hydrogen supply system **800**. Pressure tank **820** may preferably be sized to provide sufficient quantity according to at least one brief increased supply need of hydrogen-driven device **830**.

Hydrogen-driven device **830** preferably comprises at least one vehicle engine adapted for using hydrogen gas **150**. Such at least one vehicle engine preferably comprises at least one combustion engine, alternately preferably at least one hybrid engine, alternately preferably at least one hydrogen power cell driven engine. Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances, considering such things as then availability, cost, purpose, etc., other hydrogen-driven devices, such as cooking devices, generators, heaters, etc., may suffice. For application to such at least one vehicle engine, pressure tank **820** preferably comprises a size of about two liters which may hold up to about 1/2kg of hydrogen gas **150**. Applicant has determined that, under relevant circumstances, an about-two-liter size of pressure tank **820** allows for about a 30-second burst of increased consumption for acceleration. After such 30-second burst, pressure tank **820** may preferably recharge giving, as similarly determined by applicant, about a 50-second recovery time.

For hydrogen-driven device **830** comprising at least one typical vehicle, hydrogen supply system **800** should deliver a supply rate of about 1.3 kg/hour of hydrogen to maintain better than 50 miles per hour. Thickness **144**, rotation speed of hydride disks **110**, power of semiconductor laser diode **165**, and the number of semiconductor laser diodes **165** should be optimized to reach such at least one supply rate. If semiconductor laser diode **165** is too weak, then rotation speed of hydride disks **110** has to be slowed in order to liberate enough hydrogen. The slowed rotation speed of hydride disks **110** will then require a plurality of semiconductor laser diodes **165** and a plurality of disk players **210** to maintain an adequate supply of fuel.

Applicant has determined, including by experimentation, that using one semiconductor laser diode **165** (at about 760nm) at an operating speed of about 2X (about 2.6 m/s) requires about 33 minutes to release about 1.2 grams of hydrogen. Using this operating speed requires about 148 disk players **210** with about 8 semiconductor laser diodes **165** each to deliver such at

least one supply rate of about 1.3 kg per hour. This would require an additional 10 kg and 2 cubic feet to accommodate. The total laser power comprises about 236 watts (0.32 horsepower) and such about 148 disk players with disk changing mechanisms would require about 300 watts (0.4 horsepower). Preferably, when using a plurality of semiconductor laser diodes **165**, each semiconductor laser diode **165** differs in power proportional to the distance from the center of hydride disk **110**, since actual linear speed is a function of the radius. Multiple semiconductor laser diodes **165** preferably may be replaced with at least one diode laser array, preferably at least one bar laser (this arrangement at least herein embodying wherein such at least one photonic exciter comprises at least one array of lasers).

By comparison, applicant has determined, including by experimentation, that using another semiconductor laser diode **165** (at about 780 nm) at an operating speed of about 48X requires only 3 minutes. At about 48X, about 14 disk players **210** with about 8 semiconductor laser diodes **165** each delivers such at least one supply rate. Under these conditions, operating hydrogen supply system **800** requires about 0.25 horsepower.

Applicant has determined that the percentage of the power produced needed to run hydrogen supply system **800**, based on experimental findings and a fuel cell efficiency of about 50%, comprises about one percent.

FIG. 9 shows a diagrammatic view of at least one hydrogen recharging system **900**, illustrating re-hydrogenation of used hydride disks **910**, according to embodiment **101** of FIG. 1.

At least one used hydride disk **910** preferably recharges by passing into at least one hydrogen plasma stream **930**, as shown. Hydrogen plasma stream **930** preferably comprises highly charged hydrogen ions, as shown. Hydrogen plasma stream **930** is preferably created from hydrogen gas injected preferably with at least one microwave **920** and at least one radio wave **925**, preferably at least two microwaves **920** and such at least one radio wave **925**, as shown.

Microwave **920** is preferably generated from at least one microwave generator **922**, as shown. Radio wave **925** is preferably generated from at least one radio-wave generator **927**, as shown (these generators at least embodying herein at least one electromagnetic field generator structured and arranged to generate at least one electromagnetic field sufficient to form at least one supply of hydrogen plasma). Hydrogen plasma stream **930** preferably comprises a

temperature of about 2000 °C. Hydrogen plasma stream **930**, being highly charged, preferably envelops used hydride disk **910**, as shown. As hydrogen plasma stream **930** envelops used hydride disk **910**, hydrogen plasma stream **930** will cool and is preferably absorbed into used hydride disk **910**, as shown. Hydrogen recharging system **900** preferably exposes used hydride disk **910** to hydrogen plasma stream **930** for about 0.15 seconds, preferably resulting in a

recharged hydride disk **915**, as shown, preferably substantially similar to and about as useable as hydride disk **110**. Preferably, hydrogen recharging system **900** may proceed while used hydride disk **910** is within holding container **600**, preferably reducing risk of combustion of recharged hydride disk **915**.

5 FIG. 10 shows a diagram illustrating at least one refueling method **730** according to embodiment **101** of FIG. 1. Hydrogen gas **150** preferably is stored at and manufactured in at least one factory **732**, as shown, in step Manufacture and Store Hydrogen **735**. Hydrogen gas **150** preferably is transported, in at least one hydrogen transportation vehicle **742**, to at least one refueling center **747**, as shown, in step Transport Hydrogen to Refueling Center **740**. At least
10 one hydrogen-powered vehicle **750** preferably refuels, preferably using hydrogen recharging system **900**, as described in FIG. 9, in step Recharge Magnesium Hydride Disks **745**, as shown. Refueling method **730** preferably allows multiple cycles of refueling and use without replacing hydride disk **110**.

FIG. 11 shows a diagram illustrating at least one disk exchange method **760** according to
15 embodiment **101** of FIG. 1. When such at least one used hydride disks **910** are insufficiently rechargeable, used hydride disks **910** may preferably be swapped out for hydride disks **110**, as shown. A plurality of such at least one hydride disks **110** are preferably manufactured, as described in FIG. 3-6, in at least one factory **767** in step Manufacture Disks **765**, as shown. Additionally, in step Manufacture Disks **765**, materials required to manufacture hydride disks
20 **110** preferably may be recycled from used hydride disks **910**, as shown. A plurality of such at least one hydride disks **110** are preferably transported, in at least one disk transportation vehicle **772**, to at least one service station **777**, as shown, in step Transport Disks to Service Station **770**. Such transported plurality of such at least one hydride disk **110** (at least embodying herein at least one hydrogen storer structured and arranged to store at least one substantial amount of
25 hydrogen) preferably are immersed in optically clear mineral oil **610** during transport, as during storage in holding container **600** (see FIG. 6). At service station **777**, each used hydride disk **910** in hydrogen-powered vehicle **750** is preferably replaced with new hydride disk **110** in step Exchange Disks **775**, as shown. A plurality of used hydride disks **910** are preferably transported back, in disk transportation vehicle **772**, to factory **767** for recycling, as shown, in step Return
30 Disks for Recycling **785**.

FIG. 12A shows a plan view illustrating at least one hydride disk **1210** according to a preferred embodiment of the present invention.

FIG. 12B shows a magnified view of hydride disk **1210** according to the preferred embodiment of FIG. 12A.

Referring to FIG. 12A and 12B, although most features of embodiment **1200** are repeated from preferred embodiment **101**, in embodiment **1200**, as shown, embodiment **1200** preferably comprises hydride disk **1210**, as shown. Hydride disk **1210** preferably comprises primarily magnesium hydride (at least herein embodying wherein such at least one metal surface portion comprises magnesium hydride). Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances considering such issues as future materials, economics, stored hydrogen density, etc. other materials capable of absorbing hydrogen, such as other metals, plastics, glass, etc., may suffice.

Hydride disk **1210** preferably comprises a thickness **1212** of about 1/2 mm. Hydride disk **1210** preferably comprises an outer diameter **1214** of between about 50 mm and about 150 mm, preferably about 120 mm. Hydride disk **1210** preferably comprises an inner diameter of preferably between about 5 mm and about 15 mm, preferably about 15 mm. Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances considering such issues as future technology, cost, future applications, etc. other dimensions may suffice.

Hydride disk **1210** preferably further comprises at least one surface area extender **1220**, preferably perforations **1225** (see FIG. 13). Surface area extender **1220** preferably increases the amount of surface area of hydride disk **1210**, which preferably reduces hydrogenation time and hydrogenation pressures. Each perforation **1225** preferably comprises a diameter of preferably between about 100 nm and about 50 μm , preferably about 50 μm (at least herein embodying wherein each of such cavities comprises a diameter of about 50 μm). Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances considering such issues as material expansion, cost, future perforation methods, etc. other dimensions may suffice.

Multiple perforations **1225** preferably are spaced about 150 μm apart (measured center-to-center). Perforations **1225** preferably comprise a polar array in arrangement, as shown. Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances considering such issues as future technology, cost, materials, etc. other arrangements, such as, for example, linear arrays, hexagonal arrays, etc., may suffice.

Hydride disk **1210** preferably additionally comprises at least one structural integrity maintainer **1230**, as shown. Structural integrity maintainer **1230** preferably comprises at least one non-perforated “strut” or band **1235** (at least herein embodying wherein such at least one metal surface portion comprises a plurality of non-porous strut portions structured and arranged to add stiffness), as shown. Non-perforated band **1235** preferably extends from inner diameter to

outer diameter of hydride disk **1210**, as shown. Non-perforated band **1235** preferably comprises a width **1227** of about 2-3/4 mm, as shown. Structural integrity maintainer **1230** preferably comprises at least one non-perforated inner ring **1240** and at least one non-perforated outer ring **1245**, as shown. Non-perforated inner ring **1240** preferably comprises a radial width **1242**, as
5 shown, of about 2 mm. Non-perforated outer ring **1245** preferably comprises a radial width **1247** of about 1 mm. Non-perforated band **1235**, non-perforated inner ring **1240**, and non-perforated outer ring **1245** preferably comprise no perforations **1225**. Non-perforated inner ring **1240** and non-perforated outer ring **1245** are preferably concentric with the center of hydride disk **1210**.
Upon reading this specification, those skilled in the art will now appreciate that, under
10 appropriate circumstances considering such issues as future technology, cost, materials, etc. other structural integrity geometries, such as, for example, greater than three concentric rings, radially-staggered bands, parallel bands, etc., may suffice.

FIG. 13 shows an enlarged sectional view of section 13-13 of FIG. 12B.

Perforations **1225** preferably penetrate completely through hydride disk **1210**, as shown.
15 Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances considering such issues as future technology, cost, materials, etc. other penetration depths, such as, for example, about half way through, varying depths, etc., may suffice.

Perforations **1225** are preferably angled at about 45° (angle θ , as shown) from
20 perpendicular to surface **1250** of hydride disk **1210**, as shown (this arrangement at least herein embodying wherein such at least one pattern of cavities comprises at least one angle, with respect to such at least one metal surface portion, of about 45°). Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances considering such issues as future technology, cost, laser incidence, etc. other perforation angles may suffice.

25 Perforations **1225** are preferably linear, as shown. Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances considering such issues as future technology, cost, materials, etc. other perforation geometries, such as, for example, helical, spiral, elbowed, etc., may suffice.

Perforations **1225** (at least herein embodying wherein such at least one metal surface
30 portion comprises at least one pattern of cavities structured and arranged to provide substantially uniform porosity) preferably comprise a circular cross-section perpendicular to the central axis. Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances considering such issues as future technology, cost, laser incidence,

etc. other perforation cross-sections, such as, for example, ovular, hexagonal, slit, etc., may suffice.

Hydride disk **1210** preferably further comprises catalyst particles **1255** embedded near surface **1250**, as shown. Catalyst particles **1255** preferably comprise nickel, and preferably
 5 palladium. Catalyst particles **1255** preferably each comprise at least one near-atomic size. Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances considering such issues as future technology, cost, materials, etc. other catalysts, such as, for example, magnesium, carbon, plastics, etc., may suffice.

Hydride disk **1210** additionally preferably comprises at least one coating **1260**, as shown.
 10 Coating **1260** preferably comprises interspersed Ni and stoichiometric Mg_2Ni . Eutectic compounds formed at surface **1250** between coating **1260**, catalyst particles **1255** and magnesium in hydride disk **1210** preferably prevent separation of coating **1260** (at least herein embodying wherein such at least one metal surface portion comprises at least one thin surface-coating comprising substantially nickel and Mg_2Ni) from hydride disk **1210**. Upon reading this
 15 specification, those skilled in the art will now appreciate that, under appropriate circumstances considering such issues as future technology, cost, materials, etc. other coatings, such as, for example, pure Mg_2Ni , pure nickel, plastics, cermets, etc., may suffice.

FIG. 14 shows a diagrammatic view, illustrating the atomic order of hydride disk **1210**, according to embodiment **1200** of FIG. 13. Hydride disk **1210** preferably comprises multiple
 20 layers **1265** of hydrogen-storing material **1270**, preferably magnesium **1272**, as shown. Hydrogen-storing material **1270** preferably comprises at least one crystalline structure **1275**, as shown. Within crystalline structure **1275**, hydrogen-storing material **1270** preferably stores hydrogen **1280**, as shown.

FIG. 15 shows a flow chart, illustrating at least one hydride disk manufacturing process
 25 **1500**, according to the preferred embodiment of FIG. 14. Hydride disk manufacturing process **1500** preferably comprises the steps of: precipitating sheet **1510**; cutting disks **1520**; perforating disks **1530**; etching disks **1540**; washing disks **1550**; embedding catalysts **1560**; and coating disks **1570**. During hydride disk manufacturing process **1500**, materials used and processes conducted are preferably kept in an inert atmosphere, alternately preferably under vacuum.

30 In step precipitating sheet **1510** (at least embodying herein precipitating at least one hydrogen storer material adapted to store hydrogen), at least one sheet **1410** of hydrogen-storing material **1270** is preferably precipitated using precipitation technique **1610**, as shown in FIG. 16. Sheet **1410** preferably comprises about 99% by wt magnesium, preferably with a thickness of about 0.6 mm. Sheet **1410** is preferably fabricated with the addition of metals designed to

provide enhanced strength, reduced reflectivity, and greater amalgamation when hydrated. Sheet **1410** preferably comprises magnesium, nickel, lithium, boron, aluminum, copper, zinc, and iron, in weight ratios as listed in Table 1.

Table 1: Constituents of Specialty Mg Sheet

Constituent	by Wt %
Magnesium	99.95
Nickel	0.020 $\geq$ 0.025
Lithium*	0.005 $\geq$ 0.010
Boron*	0.005 $\geq$ 0.010
Aluminum	$\leq$ 0.005
Copper	$\leq$ 0.005
Zinc	$\leq$ 0.001
Iron	$\leq$ 0.001

In step cutting disks **1520** (at least embodying herein cutting such at least one hydrogen storer material into at least one geometric shape), sheet **1410** (at least herein embodying wherein such at least one metal surface portion comprises precipitated magnesium plate adapted to be cut into disks and contain such holes) is preferably cut into at least one disk **1420**, as shown, comprising a diameter of about 120 mm and a center hole **360** of about 15 mm diameter. Dimensions of disk **1420** are preferably horizontally similar to conventional compact disks which were introduced as removable storage medium (CD-R) in 1988. Upon reading this specification, those skilled in the art will now appreciate that, under appropriate circumstances, considering such issues as future technologies, costs, materials, etc., other disk manufacturing processes, such as, for example, directly precipitating disks, precipitating cylinders, etc., may suffice.

In step perforating disks **1530** (at least embodying herein perforating such at least one hydrogen storer material), disk **1420** is preferably perforated, preferably with greater than 500,000 perforations **1225**, preferably forming at least one perforated disk **1430**. At least one perforating process **1700** is discussed in connection with FIG. 17.

In step etching disks **1540** (at least embodying herein etching at least one surface of such at least one hydrogen storer material with at least one chemical), perforated disk **1430** is preferably briefly exposed to hydrochloric gas **1545**, preferably between about 40% and about 50% concentration, preferably to provide a sub-micron surface texture. Such exposure to hydrochloric gas is preferably conducted at a temperature of about 70 °C, preferably at about 2 psi, preferably for about 15 seconds. Step etching disks **1540** preferably produces at least one etched perforated disk **1440**.

Following step etching disks **1540**, etched perforated disk **1440** is preferably then placed in an inert atmosphere low pressure sandblaster. In step washing disks **1550** (at least embodying herein washing such at least one surface to remove such at least one chemical), etched perforated disk **1440** is preferably spun on a plate preferably placed about 25 mm from a series of circularly placed nitrogen gas nozzles **1553** married to separate vacuum feed and vacuum removal systems. etched perforated disk **1440** is preferably “washed” with <500 mesh about 99.95% atomized magnesium powder **1555** preferably under weak pressure of Nitrogen gas (about 99.999% purity) to preferably ensure no residual chlorine or MgCl_2 is left on etched perforated disk **1440**, and preferably only trace amounts (<100 ppm) of $\text{Mg}(\text{NH}_3)_6\text{Cl}_2$ can be detected. Step washing disks **1550** preferably results in at least one washed disk **1450**.

In step embedding catalysts **1560** (at least embodying herein embedding, in such at least one surface, at least one catalyst structured and arranged to assist hydrogenation of such at least one surface), nitrogen gas is then used to deliver catalyst particles **1255**, preferably precipitated and atomized nickel (99.999+%) and palladium (99.99+%) powders, (at <500 mesh) to washed disk **1450**. Delivery of catalyst particles **1255** is preferably conducted at between about 5 psi and about 15 psi for periods ranging from about 5 seconds to about 10 seconds. Overspray preferably nets a resultant exposure of about 0.05 seconds per square mm to catalyst particles **1255**. Steps washing disks **1550** and embedding catalysts **1560** preferably provide the necessary catalyst particles **1255**, through simple impact adhesion, to act as catalyst elements, preferably without significant ablation of magnesium in resulting catalyzed disk **1460** or reduction of the surface area created in step etching disks **1540**. The impact of magnesium, nickel, and palladium powder preferably creates sub-micron fractures in the surface of catalyzed disk **1460** and preferably provides embedded particles (catalyst particles **1255**) to preferably act as precipitation points for re-nucleation of magnesium when dehydrogenating from MgH_2 .

In step coating disks **1570** (at least herein embodying coating such at least one surface with at least one surface reaction preventer), coating **1260** is preferably applied to catalyzed disk **1460**. Nickel carbonyl and magnesium are preferably decomposed, preferably by sublimation, preferably in separate decomposition reactors **1575** resulting in gaseous nickel **1573** and gaseous magnesium **1577**. Gaseous nickel **1573** and gaseous magnesium **1577** are preferably fed into reactor **1572**. The atoms of gaseous nickel **1573** and gaseous magnesium **1577** preferably mix with each other as they preferably precipitate onto catalyzed disk **1460**, which is preferably cooled. This process is repeated with cycles of heating and cooling of the disk. Coating **1260** is preferably created from the vapors of the impregnated magnesium and the gaseous precipitates. Coating **1260** preferably aids in preventing loss of stored hydrogen in storage. Step coating

disks **1570** utilizes precipitation technique **1610**, similar to step precipitating sheet **1510**, using catalyzed disk **1460** as precipitation stage **1680** (see FIG. 16).

Hydride disk manufacturing process **1500** preferably yields at least one hydrogenation-ready disk **1580**. Hydrogenation-ready disk **1580** preferably comprises about 9.5 grams
 5 preferably with an average pre-hydrogenation density of greater than 5 g/cubic cm for the surface 2 μ m, preferably a density of greater than 1.8 g/cubic cm from a depth of 2 μ m to 20 μ m below the surface in perforated areas, and 1.74-1.78 g/cubic cm from 20 μ m to the center 250 μ m in areas which are not perforated.

FIG. 16 shows a diagrammatic view, illustrating sheet manufacturing process **1600**,
 10 according to the preferred embodiment of FIG. 15. Sheet manufacturing process **1600** preferably comprises precipitation technique **1610**, as shown. In precipitation technique **1610**, at least one constituent component **1620** is preferably decomposed in at least one decomposition reaction chamber **1630**. Decomposition reaction chamber **1630** preferably heats constituent component **1620** while maintaining a vacuum **1640**. Temperature **1650** and vacuum **1640** preferably
 15 comprise at least one condition in which constituent component **1620** preferably sublimates forming at least one gaseous constituent component **1660**.

Gaseous constituent component **1660** is preferably transferred into at least one precipitation chamber **1670**. Precipitation chamber **1670** preferably cools gaseous constituent component **1660**, preferably allowing gaseous constituent component **1660** to precipitate onto at
 20 least one precipitation stage **1680**. Precipitation stage **1680** is preferably chilled to at least one precipitation temperature **1690**. Precipitation technique **1610** preferably allows uniform distribution of multiple constituent components **1660**, preferably molecularly layered, to form sheet **1410** using constituent components **1660** as listed in Table 1.

Upon reading the specification, those skilled in the art will now appreciate that, under
 25 appropriate circumstances, other sheet manufacturing processes, such as, for example, sputter precipitation, electrolytic precipitation, other future molecular layering techniques, etc., may suffice.

FIG. 17 shows a diagrammatic view of at least one drilling chamber **1710**, illustrating at least one perforating process **1700**, according to the preferred embodiment of FIG. 15.

30 In perforating process **1700**, disk **1420** is preferably placed in a cold inert atmosphere and preferably secured flat on at least one stage **1720**, preferably comprising at least one submicron-sensitive 3-dimensional stage. Stage **1720** is preferably cooled; and drilling chamber **1710** preferably is kept under vacuum **1712**. At least one pressure plate **1730** preferably comprises at least one orifice **1740**. Pressure plate **1730** preferably covers disk **1420**, preferably applying

pressure in order to prevent warping during perforating process **1700**. Orifice **1740** preferably exposes a circular surface area of about 0.7 mm in diameter of disk **1420**. Stage **1720** preferably moves to expose different portions of disk **1420** during perforating process **1700**.

At least one laser **1750** preferably perforates disk **1420**, preferably through orifice **1740**.

- 5 Laser **1750** preferably comprises a Niobium-YAG laser. Laser **1750** preferably is collimated with the ability to focus a beam **1752** of about 45 μ m diameter, preferably with a divergence of less than 2 percent. Laser **1750** is preferably incident at an about 45 degree angle to disk **1420**. Upon reading the specification, those skilled in the art will now appreciate that, under appropriate circumstances, other perforating processes, such as, for example, wire drilling,
10 plasma drilling, etc., may suffice.

- At least one drilling sequence places perforations **1225** such that no perforations **1225** are placed within about 1 mm of a previously placed perforation **1225** during any about 1 minute period. At least one vacuum **1760** evacuates vaporized magnesium **1770** during perforating process **1700** for later reuse in step washing disks **1550**. Warping is prevented by pressure plate
15 **1730** and such at least one drilling sequence.

FIG. 18 shows a diagrammatic flow chart, illustrating at least one hydrogenation process **1800**, according to the preferred embodiment of FIG. 15.

- Hydrogenation process **1800** preferably comprises placing hydrogenation-ready disks **1580** on at least one threaded spindle **1812** between at least one spacer **1110**, as shown in step
20 spindle disks **1810**. Spacer **1110** preferably is cleaned and heat treated in a vacuum, to remove impurities, prior to use. Hydrogenation-ready disks **1580** are secured, between spacers **1110**, with at least one nut **1113** on at least one threaded spindle **1812**.

- Hydrogenation process **1800** preferably employs at least one reactor **1120**, preferably capable of temperatures of about 500 °C and preferably pressures in excess of about 65 bar.
25 Hydrogenation process **1800** preferably takes place between about 55°C and about 440°C and preferably between about 2 bar and about 30 bar, preferably over periods ranging from about 2 hours to about 6 hours. Since magnesium approximates a closed packet crystalline structure, twinning is possible, and preferably desirable, in an enabled isometric configuration to improve hydrogen absorption and desorption kinetics. Therefore, hydrogenation process **1800** preferably
30 uses a slow stepped process (temperature staging process **1820**), preferably which avoids annealing as much as possible, and preferably allows equalized distribution of hydrogen in hydride disk **1210**.

Hydrogenation process **1800** preferably uses bottled ultra-pure (99.999%) hydrogen gas, preferably ALPHAGAZ 2, preferably cooled to near liquid state (cooled hydrogen **1835**).

During stage **1823** of temperature staging process **1820**, small amounts of cooled hydrogen **1835** are preferably introduced by high speed, high pressure injection into reactor **1120**. At least one injection valve **1837** preferably creates an about 1 μ s blast of cooled hydrogen **1835** preferably about each second for an about 10 second interval. The about 10 second interval is preferably repeated about 10 times. Repeated introduction of the cold hydrogen preferably creates sonic pressure waves as cooled hydrogen **1835** expands supersonically inside reactor **1120**. The supersonic waves preferably facilitate cracking of coating **1260**, and preferably permit deeper hydrogenation into hydrogenation-ready disks **1580**, and preferably later adsorption from hydride disk **1210**.

FIG. 19 shows a chart view illustrating temperature staging process **1820**, during hydrogenation process **1800**, according to the preferred embodiment of FIG. 18.

The temperature in reactor **1120** is preferably increased from about 20 °C slowly, and preferably allowed to reach equilibrium at about 55 °C, about 150 °C, and about 300 °C preferably over about 1 hour, in stage **1821**. Stage **1821** comprises a constant hydrogen pressure of about 2 bar. In stage **1822**, temperature is preferably then reduced to about 55 °C and pressure is preferably increased to about 30 bar. Temperature is preferably then increased and preferably allowed to reach equilibrium again at about 55 °C, about 150 °C, and about 300 °C preferably over about 1 hour. Stage **1822** also comprises a constant pressure of about 30 bar, preferably utilizing venting as temperature increases. Temperature is preferably then allowed to rise to about 440 °C, preferably moving particularly quickly between about 350 °C and about 430 °C to reduce annealing.

In stage **1823**, reactor **1120** preferably remains at about 440 °C temperature for about 1 additional hour before being cooled. In stage **1824**, preferably while under constant hydrogen pressure of about 30 bar, reactor **1120** is preferably cooled to about 135 °C. Pressure is preferably reduced to about 2 bar of hydrogen and hydride disks **1210** preferably cool further to about 55 °C preferably under a constant pressure of about 2 bar, in stage **1825**. Hydride disks **1210** are preferably then removed to at least one inert gas oven at about 55 °C and about 1-2 bar, to undergo stage **1826**. Hydride disks **1210** are preferably then cooled as the oven temperature reduces and inert gas is preferably added to ensure constant positive atmospheric pressure of about 1-2 bar.

FIG. 20 shows a perspective view, illustrating spacer **1110**, according to the preferred embodiment of FIG. 18. Spacer **1110** preferably comprises a thickness of about 3 mm. Spacer **1110** preferably comprises at least one ventilator **1115**, preferably designed to allow hydrogen flow to as much surface area of hydrogenation-ready disk **1580** as possible. Spacer **1110**

preferably prevents warping of hydrogenation-ready disk **1580** during hydrogenation process **1800**. Spacer **1110** preferably comprises titanium, preferably 99.98% titanium. Spacer **1110** preferably comprises an outer diameter **1112** of about 130 mm, preferably extending beyond outer diameter **1214** of hydrogenation-ready disk **1580** to account for expansion during

5 hydrogenation process **1800**.

Upon reading the teachings of this specification, those skilled in the art will now appreciate that, under appropriate circumstances, considering such issues as cost, future technologies, etc., other hydrogenation methods, such as, for example, laser-induced plasma ionization hydrogenation, thermal heating hydrogenation using chemical, physical or laser
10 cooling of the medium, switched multi-frequency light activation hydrogenation, etc., may suffice.

FIG. 21A shows a plan view illustrating at least one hydride disk **1910** according to a preferred embodiment of the present invention.

FIG. 21B shows a magnified view of hydride disk **1910** according to the preferred
15 embodiment of FIG. 21A.

FIG. 22 shows an enlarged view of section 22-22 of FIG. 21B.

Referring to FIG. 21A, FIG. 21B and FIG. 22, an alternative method of disk fabrication preferably includes precipitation of constituent components **1620** (as in precipitation technique **1610**) onto at least one core disk **1930** preferably comprising a thickness **1932** of about 0.1 mm.
20 Core disk **1930** preferably comprises carbon, preferably carbon fiber. Core disk **1930** (at least herein embodying wherein such at least one metal surface portion comprises at least one thin, stiff non-magnesium frame structured and arranged to add stiffness) preferably provides stability to hydride disk **1910**, to replace non-perforated band **1235** as structural integrity maintainer **1230**.

25 Core disk **1930** preferably comprises hydrogen passages **1920** which are preferably closed at the top. Hydrogen passages **1920** preferably rise from core disk **1930** about 0.2 mm, preferably at an angle θ of about 45°. Hydrogen passage **1920** comprises a diameter of about 0.0001 mm (100 nanometers), and preferably are perforated to allow passage of hydrogen between hydrogen passage **1920** and hydride disk **1910**.

30 Precipitation preferably produces at least one layer **1940** of constituent components **1620** to a thickness **1922** of about 0.2 mm on each side of core disk **1930**. After precipitation hydrogen passages **1920** are preferably sanded opened to reveal holes similar to perforations **1225** and providing the possibility of more than 5 million hydrogen passages **1920** per hydride

disk **1910**, which increases surface area and Hydrogen adsorption, without reducing strength or storage capacity.

FIG. 23 shows an enlarged view of section 22-22 of FIG. 21B according to an alternately preferred embodiment of the present invention.

5 Although most features of embodiment **1300** are repeated from preferred embodiment **1200**, in embodiment **1300**, as shown, embodiment **1300** preferably comprises hydride disk **1310**, as shown. Hydride disk **1310** preferably comprises at least one magnesium layer **1320** and at least one Nitinol (TiNi) layer **1325**. Like in hydride disk **1210**, hydride disk **1310** preferably comprises perforations **1225**, however in hydride disk **1310**, multiple perforations **1225** are
10 preferably spaced about 100 μm apart (measured center-to-center).

Magnesium layer **1320** preferably comprises at least one magnesium and nickel formula, in the form of small-grain, semi-porous, deposited and perforated material, preferably formed and preferably perforated in an anaerobic environment (≤ 50 ppm oxygen) with the 99.99% purity constituents (Table 2) listed below.

15 Table 2 : Constituents of Specialty Mg layer

Element	Min wt%	Max wt%	Moles/100g	Purpose
Magnesium	98.45	98.55	4.0451	H ₂ storage α , β , γ
Nickel	1.45	1.55	0.0256	H ₂ storage/kinetics/elect-opt α , β
Oxygen	0.00	≤ 50 ppm	0.0	contaminant/lowers storage

Nitinol (TiNi) layer **1325** preferably comprises at least one substrate employed for vapor deposition of Magnesium layer **1320**. Nitinol (TiNi) layer **1325** preferably is baked to allow super-elasticity prior to vapor deposition. The vapor deposited (electron beam) magnesium and
20 nickel material grain sizes are preferably similar to those achieved with equal channel angular pressing at temperatures, which preferably permit homogenous and bimodal grain structures preferably with nano-grains and a small volume fraction of micro-grains. Material grain sizes are preferably in the range of about 0.4 μm to about 1.1 μm , preferably with a mean value of the planar grain size of less than about 500 nm, with twins included as grain boundaries. Nitinol
25 (TiNi) layer **1325** preferably provides super-elasticity to the deposited material and allows Hydride disk **1310** to return to the required shape repeatedly after hydrogen absorption and desorption cycles.

Magnesium layer **1320** preferably comprises structures of stacked partial glancing angle vapor deposition solid sheet magnesium and nickel, preferably with a small grain size (<500 nm
30 diameter), preferably with micro-fractures which preferably localizes material of nano-clusters preferably with only about 2500 nm between fractures, and preferably beam channeling microstructures (50 μm diameter perforations **1225**), preferably deposited on Nitinol (TiNi) layer

1325. Preferably, Multi-gun plasma magnetron sputtering, alternately preferably, plasma enhanced magnetron sputtering (PEMS), alternately preferably, ion-beam assisted deposition (IBAD), alternately preferably, e-beam evaporation (EVAP) may be used to create Magnesium layer 1320. Magnesium layer 1320 preferably comprises suitable semi-porosity, preferably
 5 micro-fractures, preferably solidity, and preferably adequate surface area to effect laser-induced desorption. Alternately preferably, hydride chemical vapor deposition (HCVD) may be used with a formula which includes hydrogen and preferably results in mixtures of MgH_2 and Mg_2NiH_4 .

Light beam channeling microstructures (perforations 1225) are preferably placed in the
 10 material with a focused laser beam preferably in a trepanning manner, alternately preferably in a compounding manner. Perforations 1225 are placed about 100 μm on center apart, and are preferably created at about a 45 degree angle to the surface. Perforations 1225 may preferably be drilled blind (not through Nitinol (TiNi) layer 1325) when only a single layer of material (thin foil) is to be used. Note that normally layers will preferably be stacked, as shown, and blind
 15 holes will not be used.

The storage structure of hydride disk 1310 is preferably porous and preferably has channels to allow hydrogen and light into, and out of, the material. The fabrication process preferably provides perforations 1225 at about a 45 degree angle to the surface, with a preferred diameter of about 50 μm prior to hydrogen absorption. Perforations 1225 will shrink due to
 20 expansion during hydrogen absorption. While the overall material volume change is on the order of 8 to 15%, the holes tend to close by more than 20% and have a diameter of about 36 μm after hydrogen absorption. The channels preferably have an average population density between about 300 and about 440 channels per 0.01 cm^2 . The internal porosity preferably contains about 1000 macro and meso-pores (open cell) per inch. Fabrication is preferably conducted in an
 25 anaerobic atmosphere. Initial hydrogen absorption and degassing, with medium vacuum, preferably will rupture any closed cell structures.

Applicant has found through testing that this preferred formula ($Mg + MgNi$) and preferred structure ($NiTi-Mg+MgNi-NiTi$) absorb hydrogen at modest temperature and hydrogen pressure. What Applicant found to be remarkable and novel is the effect that UV (100 nm to 400
 30 nm) and IR laser light (400 nm to 1 mm) have on the sorption kinetics of the material. The dielectric created by the hydrogen material ($MgH_2 + Mg_2NiH_4$) (higher insulation), while stacked between layers of a partially hydrogenated Nitinol (NiTi) metal material (lower insulation) creates multi-layers of surface plasmon polaritons. The interface between the layers gives rise to coupled modes in the metal-insulator-metal heterostructure. The ability to control

wave vectors through these structures can preferably be attained with geometry, including the holes drilled in the material, and also preferably with triangular V-grooves in the surfaces of the Nitinol metal. The localized surface plasmons in the metal nano-particles and near the insulator nano-particles, allows electromagnetic energy to be confined into a volume less than the

5 diffraction limit. This leads to field enhancement and supports emissive processes which further the effect of the UV and laser light in photon-molecular interactions. In addition, the preferred structures selected, and preferred frequencies used, preferably allow coupling of the electromagnetic field to lattice vibrations at infrared frequencies, and preferably give rise to localized and propagating surface phonon polaritons. This preferred arrangement preferably

10 provides that photonics with phonons at infrared frequencies and plasmonics at lower frequencies preferably provide sub-wavelength energy localization, preferably with evanescent waves, and together preferably contribute to the enhanced sorption kinetics observed by Applicant in the magnesium-hydrogen complexes and structures developed with drilled beam-channel holes, as described herein, and also with triangular V-grooves. Upon reading the

15 teachings of this specification, those skilled in the art will now appreciate that, under appropriate circumstances, considering such issues as cost, future technologies, etc., other substrates, such as, for example, silicon substrates, other nickel substrates, gold substrates, iron substrates, etc., may suffice.

Upon reading the teachings of this specification, those skilled in the art will now

20 appreciate that, under appropriate circumstances, considering such issues as cost, future technologies, etc., other light sources, such as, for example, UV LED, deuterium lamp, laser irradiation, IR electromagnetic energy, diode, diode pumped lasers, active gain media fiber lasers including ytterbium at 1080 nm, multi-wavelength (stable single-, dual- and triple-wavelength dissipative soliton) in a dispersion fiber laser passively mode-locked with a semiconductor

25 saturable absorber with active mode locking (SESAM), etc., may suffice.

These preferred nano-optic and plasmonic effects, in combination with the previously disclosed beam channeling, electromagnetic, and electro-optical properties, provides insight into the exceptional excitation energies noted in release of hydrogen, from preferred formulated and structured metal hydrides, by electromagnetic irradiation.

30 Although applicant has described applicant's preferred embodiments of this invention, it will be understood that the broadest scope of this invention includes modifications such as diverse shapes, sizes, and materials. Such scope is limited only by the below claims as read in connection with the above specification. Further, many other advantages of applicant's invention will be apparent to those skilled in the art from the above descriptions and the below claims.

CLAIMS:

1. A hydrogen energy system comprising:
 - a) at least one hydrogen storer structured and arranged to store at least one substantial amount of hydrogen;
 - b) wherein said at least one hydrogen storer comprises at least one hydrogen-release permitter structured and arranged to photonically-excitation-assist release of stored hydrogen from said at least one hydrogen storer; and
 - c) at least one photonic exciter structured and arranged to photonically excite said at least one hydrogen storer to assist release of such stored hydrogen from said at least one hydrogen storer;
 - d) wherein said at least one photonic exciter comprises at least one controller structured and arranged to control such photonic-excitation-assisted release of hydrogen gas so as to assist at least one commercial use; and
 - e) wherein said at least one hydrogen release permitter comprises at least one plasmonic-effect-capable dielectric structured and arranged to create surface plasmon polaritons.
2. The hydrogen energy system according to claim 1, wherein said at least one plasmonic-effect-capable dielectric comprises at least one super-elastic material layer structured and arranged to resiliently expand and contract through multiple absorption-desorption cycles.
3. The hydrogen energy system according to claim 2, wherein said at least one photonic exciter comprises at least one array of lasers.
4. The hydrogen energy system according to claim 2, wherein said at least one plasmonic-effect-capable dielectric comprises at least Nitinol and magnesium.

5. The hydrogen energy system according to claim 3, further comprising:
- f) at least one metal surface portion for absorbing hydrogen;
 - g) at least one supply of hydrogen gas; and
 - h) at least one electromagnetic field generator structured and arranged to generate at least one electromagnetic field sufficient to form at least one supply of hydrogen plasma;
 - i) wherein said at least one electromagnetic field generator is located in at least one position such that said at least one supply of hydrogen plasma is located in at least one second position; and
 - j) at least one metal surface locator structured and arranged to locate said at least one metal surface portion within such at least one second position;
 - k) wherein said at least one metal surface portion may absorb hydrogen to form at least one metal hydride surface portion.




FIG. 1

2/22




FIG. 2

3/22




FIG. 3

4/22




FIG. 4A




FIG. 4B

5/22




FIG. 5

6/22





FIG. 6

7/22



8/22





FIG. 7B



FE³⁺




FIG. 9

11/22




FIG. 10




FIG. 11




FIG. 12A






FIG. 12B

13/22



14/22




FIG. 14

15/22





FIG. 15

16/22






FIG. 17

18/22




FIG. 18

19/22




FIG. 19

20/22




FIG. 20

21/22




FIG. 21A




FIG. 21B

