



US 20040100400A1

(19) **United States**

(12) Patent Application Publication

Perelman et al.

(10) Pub. No.: US 2004/0100400 A1

(43) Pub. Date: May 27, 2004

(54) **POWER-SCALABLE ASYNCHRONOUS ARCHITECTURE FOR A WAVE-PIPELINED ANALOG TO DIGITAL CONVERTER**

(22) Filed: **Nov. 27, 2002**

Publication Classification

(75) Inventors: **Yevgeny Perelman**, Haifa (IL);
Eliyahu Shamsaev, Haifa (IL); **Israel Wagner**, Haifa (IL); **Michael Zelikson**, Haifa (IL)

(51) Int. Cl.⁷ H03M 1/38
(52) U.S. Cl. 341/155; 341/161

(57) **ABSTRACT**


Correspondence Address:

**Stephen C. Kaufman
Intellectual Property Law Dept.
IBM Corporation
P.O. Box 218
Yorktown Heights, NY 10598 (U)**

(73) Assignee: **International Business Machines Corporation, Armonk, NY**

(21) Appl. No.: **10/306,919**

A method for converting a signal from analog-to-digital domain. Upon receipt of an i^{th} triggering signal, where $1 \leq i \leq N$, the method includes initiating at least a partial AD operation. Upon completion of the at least partial operation, the method may include generating and transmitting an $i^{th}+1$ triggering signal. The $i^{th}+1$ triggering signal may be adapted to initiate an $i^{th}+1$ at least partial operation, thereby creating an asynchronous process. The method further includes repeating the above operations until completion of the analog to digital conversion. In some embodiments of the present invention, upon completion of the conversion, $i=N$ and the $i^{th}+1$ operation is a power-down function.






FIG.1A
PRIOR ART




FIG.1B
PRIOR ART





FIG. 2A



POWER-SCALABLE ASYNCHRONOUS ARCHITECTURE FOR A WAVE-PIPELINED ANALOG TO DIGITAL CONVERTER

FIELD OF THE INVENTION

[0001] This invention relates generally to analog-to-digital converters (ADC), and more specifically to wave-pipelined ADCs.

BACKGROUND OF THE INVENTION

[0002] There are many analog-to-digital signal conversion (ADC) methods and apparatus. One of the well known ADC methods and apparatus is an synchronous pipeline ADC with error correction.

[0003] Reference is now made to **FIG. 1A**, a block diagram of prior art error correction synchronous pipeline ADC architecture 1. Reference is made in parallel to **FIG. 1B**, a block diagram of a prior art sample stage 10. ADC 1 may comprise a series of stages 10. Each stage 10 may typically comprise one or more sub-stages, such as a sample/hold (SH) circuit 12, ADC 14, digital to analog converter (DAC) 16, subtractor 17 and amplifier 18. As is commonly known in the art, the signal flow within and between stages 10 is regulated via synchronized strobes or clock signals. In **FIGS. 1A and 1B**, each progressive strobe or clock signal is represented by a “clk”, i.e. clk1, clk2, etc.

[0004] **FIG. 1B** also illustrates an exemplary flow of a analog-to-digital conversion in exemplary stage 10. An analog signal 22 is received by SH 12, which samples and holds a sample analog value 24. Upon clk1, SH 12 transfers sample 24 to ADC 14 and to subtractor 17. ADC 14 converts sample 24 to a digital signal 26 representative of the sample 24. Upon clk2, ADC 14 transfers digital signal 26 to a register or latch (not shown) and to DAC 16. DAC 16 receives digital signal 26 and converts it to a reconstructed analog signal 28, representative of a quantization of sample 24. Upon clk 3, DAC 16 transmits reconstructed signal 28 to subtractor 17. Subtractor 17 first calculates the quantization error between sample 24 and reconstructed signal 28. Subtractor 17 then transmits the result to amplifier 18. Upon clk 4, amplifier 18 transmits multiplied signal 30 to the next stage 10. Upon the next clk (not shown) the present cycle is repeated. Each stage 10, and the elements comprised therein, progress synchronously with each other stage 10.

[0005] It is noted that the above sample is a typical known in the art routine. As an example, ADC 14 is illustrated as 1.5 bit ADC, however, may be a single bit ADC or any other known in the art ADC. Stage 10 may have various alternative elements or may proceed upon alternative paths, however, the basic principle is similar to that presented in such that the entire process is regulated via synchronized clock strobes.

[0006] A disadvantage of the above procedure is that a comparator or stage may not complete its function during the clocked period, and may hence transmit a partial, incomplete or incorrect signal. Other drawbacks are the need for dedicated complex clocking circuits, the vulnerability to clock jitter and process variations, and a non-scalable power budget.

SUMMARY OF THE INVENTION

[0007] In accordance with one aspect of the present invention, there is now provided an apparatus and method of

analog-to-digital conversion, wherein the elements and stages in an analog-to-digital (AD) wave pipeline architecture are not regulated via a synchronized clock. Rather, upon completion of each stage or function, the relevant element or stage transmits a “completed” signal, or an “ACK” signal to the next element/stage. The “ACK” signal then triggers that element/stage. Each stage thus receives the time necessary for proper operation, in a manner that is independent of the sampling frequency. Due to the novel “ACK” triggering method, the present invention is robust to technology scatter, process variations, and jitter problems. This robustness is in contrast to prior art circuits wherein each element and stage is allotted a predefined clocked period, which alternatively may be too much or too little time.

[0008] Another advantage of the present invention may be the elimination of global clocks in or between the stages. Inasmuch as no global clocks are needed, the design complexity may be reduced and the risk may be lowered.

[0009] In some preferred embodiment, each stage may be powered up only when it is required to process its input data. Furthermore, all stages may be powered down upon completion of the analog-to-digital conversion process. Thus, another advantage of the present invention may be scalable power consumption via application of a lower clock frequency, resulting in a reduced average power consumption.

[0010] In accordance with one aspect of the present invention, there is now provided a method for converting a signal from analog-to-digital domain. Upon receipt of an i^{th} triggering signal, where $1 \leq i \leq N$, the method includes initiating at least a partial AD operation. Upon completion of the at least partial operation, the method may includes generating and transmitting an $i^{th}+1$ triggering signal. The $i^{th}+1$ triggering signal may be adapted to initiate an $i^{th}+1$ at least partial operation, thereby creating an asynchronous process. The method further includes repeating the above operations until completion of the analog to digital conversion. In some embodiments of the present invention, upon completion of the conversion, $i=N$ and the $i^{th}+1$ operation is a power-down function.

[0011] In accordance with one aspect of the present invention, there is now provided analog-to-digital (AD) wave pipeline system. The system may include a plurality of AD pipeline stages in series, each of the stages, upon receipt of an i^{th} triggering signal where $1 \leq i \leq N$, may initiate an AD operation. Upon completion of the operation, each stage may generate and transmit an $i^{th}+1$ triggering signal adapted to initiate an $i^{th}+1$ operation, thereby creating an asynchronous process.

[0012] In accordance with one aspect of the present invention, there is now provided an analog-to-digital (AD) stage. The stage may include a plurality of sub-stages, each sub-stage, upon receipt of an i^{th} triggering signal where $1 \leq i \leq N$, may initiate a partial AD operation. Upon completion of the partial AD operation, each sub-stage may generate and transmit an $i^{th}+1$ triggering signal adapted to initiate an $i^{th}+1$ partial AD operation, thereby creating an asynchronous process. Each sub-stage may include a shut down mechanism adapted to shut down the sub-stage when $i=N$ and upon receipt of the $i^{th}+1$ triggering signal.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] For a better understanding of these and other objects of the present invention, reference is made to the

detailed description of the invention, by way of example, which is to be read in conjunction with the following drawings, wherein:

[0014] **FIG. 1A** is a block diagram of a prior art synchronous pipeline ADC circuit comprising a series of stages;

[0015] **FIG. 1B** is a block diagram of a prior art ADC stage;

[0016] **FIG. 2A** is a block diagram of an asynchronous pipeline ADC circuit operable in accordance with a preferred embodiment of the invention; and

[0017] **FIG. 2B** is a block diagram of an asynchronous ADC stage operable in accordance with a preferred embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0018] Reference is now made to **FIG. 2A**, a block diagram of asynchronous pipeline (APL) ADC architecture **40**, operated and constructed in accordance with a preferred embodiment of the invention. Reference is made in parallel to **FIG. 2B**, a block diagram of an asynchronous stage **50**, operated and constructed in accordance with a preferred embodiment of the invention. APL **40** may comprise a series of asynchronous stages **50**.

[0019] As is seen in both **FIGS. 2A and 2B**, APL **40** and stages **50** are not regulated via a synchronized clock. Rather, upon completion of each stage or function, the relevant element or stage transmits a “completed” signal, or an “ACK” signal to the next element/stage. The “ACK” signal then triggers that element/stage. Each progressive triggering signal is represented by progressive “ACK” signals, i.e. ACK<1>, ACK<2>, etc.

[0020] It is noted that the ability of each element to generate a “completed” signal and transmit such signal is known in the art process. Examples of such are described in “12-bit low-power fully differential switched capacitor noncalibrating successive approximation ADC with 1 MS/s” Promitzer, G. IEEE JSSC, July 2001, Page(s): 1138-1143, and included herein in its entirety, and will not be explained in detail herein.

[0021] It is apparent to one skilled in the art that the analog-to-digital functioning of stages **10** and **50** are similar, and will not be further explained herein. Inconsequential differences in the sub-stages or elements within stages **10** and **50** may exist, however the analog-to-digital conversion process is similar. As an example, in **FIG. 1B** the register/latch which receives the digital signal **26** is not shown, however, in the embodiment presented in **FIG. 2B** a latch **15** is shown.

[0022] Although ADC **14** is illustrated as a 1.5 bit ADC, a preferred embodiment of the present invention may alternatively comprise a current-mode algorithmic ADC implemented with a cascade of 1-bit stages, with no clock control, i.e. comparators are working continuously. It is thus appreciated that various modification to the embodiment described herein will be apparent to a person skilled in the art and still fall within the principles of the present invention.

[0023] One of the novel aspects of the present invention is signal progression within and between stages **50** via “ACK” signal triggering. This novel method is in contrast to the known-in-the-art usage of global clocks.

[0024] In a preferred embodiment of the present invention, because all timing events are derived from the “ACK” signal, no global clocks are needed in or between stages **50**. Since no global clocking is needed, the design complexity may be reduced and the risk may be lowered. Additionally, because only one clock signal may be needed (to initiate the sequence), the present clocking scheme may be much simpler than prior art systems with several different clock signals distributed throughout the ADC system.

[0025] The present invention may provide significant power saving over prior architectures in that:

[0026] 1) no large clock drivers are needed,

[0027] 2) the level of noise may be smaller. In prior art system not all comparators/latches lock synchronously, creating noise. Due to the asynchronous nature of the present invention, the noise level may be smaller, and the analog circuits may be “relaxed” and designed more economically, and

[0028] 3) no digital synchronizers are needed to align the digital outputs from the stages, thus saving $O(N^2)$ latches, for N -bit ADC.

[0029] As an asynchronous system, the APL **40** may be robust to technology scatter, process variations, and jitter problems. These robust advantages are obtained because each stage receives the time necessary for proper operation, in a manner that is independent of the sampling frequency, rather than a rigid pre-specified period.

[0030] An additional advantage of the present invention is that whereas APL **40** completes a code computation within a single clock cycle, the operation time of each analog sub-stage is limited to the period necessary to complete the relevant function. Analog sub-stages may comprise elements **14**, **16**, **18**, stages **50** etc. As an example, DAC **16** may function for the period necessary to perform an D-to-A conversion.

[0031] Additionally, each stage **50** may be powered up only when it is required to process its input data. Furthermore, stages **50** may be powered down upon completion of the analog-to-digital conversion process. This robustness is in contrast to prior art circuits wherein each element and stage is allotted a predefined clocked period. In some instances, the predefined clocked period may alternatively be too much time, or too little. Thus, another advantage of the present invention may be scalable power consumption via application of a lower clock frequency, resulting in a reduced average power consumption.

[0032] As seen from **FIG. 2B**, each element in stage **50** may comprise a shut down mechanism **19**. When the last stage **50** has completed its operation, the “ACK” signal from the last element in stage **50** (i.e. amplifier **18**) may be transferred to the respective shut down mechanisms **19**. Mechanism **19** may then cause the elements to power down. Each element will then resume operation upon receipt of an “ACK” signal, as explained in detail herein above.

[0033] In a preferred embodiment of the present invention, the comparators, such as elements **14** and **16** can work in “precharge-evaluate” cycles, and thus can be made faster and more power-efficient.

[0034] An example of possible power savings may be calculated as follows:

[0035] f —clock repetition rate,

[0036] t —stage delay,

[0037] T —clock cycle time,

[0038] N —number of stages,

[0039] i —specific stage number

[0040] $Pst[i]$ — i^{th} ($0 < i < N$) stage power dissipation,

$$a = \frac{Pst[i]}{Pst[i-1]}$$

[0041] Psh —SH (Sample and Hold) power dissipation,

[0042] Ppl —power dissipation of the ADC without SH,

[0043] $Ptot$ —ADC power dissipation.

[0044] The necessary condition for the ADC functionality is: $T/t > N$.

[0045] Therefore, an approximate estimation of the average power dissipation of the pipeline, ignoring set-up and hold times, is given by:

$$Ppl = Pst[0] * t * f * \sum_{i=1}^{N-1} (n-i)ai$$

[0046] If $t * n * f < 2^{(N+1)}$ there is no need in the SH circuit, i.e. $Ptot = Ppl$.

[0047] Otherwise, $Ptot = Ppl + Psh$.

[0048] It is noted that in common traditional pipeline ADCs, additional power optimization may be obtained by design of non-identical stages, corresponding to $a < 1$ in the above terminology. Unfortunately, use of non-identical stages in prior art ADCs requires redesign of the entire clocking scheme. In contrast, in the present invention, due to the usage of the “ACK” triggers, the use of non-identical stages is transparent and does not require any additional circuit redesign.

[0049] It is noted that in APL architecture 40, since the entire computation may be completed within a single clock cycle, no synchronizing registers are needed and internal SH circuits 12 may be optional. These improvements may provide power consumption savings of $O(N^2)$ latches, as compared to a regular pipeline ADC. Also, there is a power/frequency tradeoff: in some preferred embodiments, k SH cells can be added along the pipeline for a k times faster sampling, and in the cost of about $O(k^2)$ more latches.

[0050] As is apparent to those skilled in the art, power scalability is an important requirement in modern integrated circuit design. Examples of the present invention offer flexible power scalability, such as an exemplary preferred embodiment of a family of pipeline APLs 40 with moderate resolution (up to 10 bit). This embodiment may be a superset design. As such, APLs 40 may be featured by lower resolution and/or lower operation frequency can be directly obtained. Alternatively, an exemplary preferred embodiment may include an APL 40 with higher operation frequencies.

This may be constructed by a series connection of the proposed basic architecture, e.g. stages 50.

[0051] As seen, the novel architectural approach of asynchronous mode of operation, dynamic power up and power down of the circuit, allows for the flexible power scalability without compromising the power efficiency of a design.

[0052] It is noted that while self-timed comparators in the context of a successive-approximation (SAR) ADC are known in the art, the present invention is significantly different in several aspects. Prior art does not include power-scalability, in that it does not provide for turning-off of unused circuits. Additionally, prior art methods are not suitable for a pipeline ADC (only to a successive approximation register (SAR)).

[0053] It is noted that the utilization of the described mode of operation is not a necessary feature of the design. The features dynamic power up/power down and asynchronous operation are equally applicable to traditional, voltage mode approaches and applicable within the principles of the present invention.

[0054] It will be appreciated by persons skilled in the art that the present invention is not limited to what has been particularly shown and described hereinabove. Rather, the scope of the present invention includes both combinations and sub-combinations of the various features described hereinabove, as well as variations and modifications thereof that are not in the prior art, which would occur to persons skilled in the art upon reading the foregoing description.

1. A method for converting a signal from analog-to-digital domain, the method comprising the steps of:

a) upon receipt of an i^{th} triggering signal where $1 < i < N$, initiating at least a partial AD operation; and

b) upon completion of said at least partial operation, generating and transmitting an $i^{\text{th}}+1$ triggering signal adapted to initiate an $i^{\text{th}}+1$ at least partial operation, thereby creating an asynchronous process.

2. The method according to claim 1, and further comprising repeating steps a) and b) until completion of said conversion.

3. The method according to claim 2, wherein upon completion of said conversion, $i=N$ and said $i^{\text{th}}+1$ operation is a power-down operation.

4. An analog-to-digital (AD) stage comprising:

a plurality of sub-stages, each sub-stage, upon receipt of an i^{th} triggering signal where $1 \leq i \leq N$, adapted to initiate a partial AD operation, and upon completion of said partial AD operation, to generate and transmit an $i^{\text{th}}+1$ triggering signal adapted to initiate an $i^{\text{th}}+1$ partial AD operation, thereby creating an asynchronous process.

5. An analog-to-digital (AD) wave pipeline system comprising:

a plurality of AD pipeline stages in series, each of said stages, upon receipt of an i^{th} triggering signal where $1 \leq i \leq N$, adapted to initiate an AD operation, and upon completion of said operation, to generate and transmit an $i^{\text{th}}+1$ triggering signal adapted to initiate an $i^{\text{th}}+1$ operation, thereby creating an asynchronous process.

6. The system of claim 4, wherein each of said stages comprises:

a plurality of sub-stages, each sub-stage, upon receipt of an i^{th} triggering signal where $1 \leq i \leq N$, adapted to initiate a partial AD operation, and upon completion of said partial AD operation, to generate and transmit an $i^{\text{th}}+1$ triggering signal adapted to initiate an $i^{\text{th}}+1$ partial AD operation.

7. The system of claim 6, wherein each sub-stage comprises a shut down mechanism adapted to shut down said sub-stage when $i=N$ and upon receipt of said $i^{\text{th}}+1$ triggering signal.

* * * * *