

(12) PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 200050739 B2**
(10) Patent No. **770544**

(54) Title
Error correction encoding a data stream of information

(51) ⁶ International Patent Classification(s)
G11B 020/12 G11B 027/30
G11B 020/18

(21) Application No: 200050739 (22) Application Date: 2000.05.29

(87) WIPO No: W000/77787

(30) Priority Data

(31) Number	(32) Date	(33) Country
99201840	1999.06.10	EP

(43) Publication Date : 2001.01.02
(43) Publication Journal Date : 2001.03.15
(44) Accepted Journal Date : 2004.02.26

(71) Applicant(s)
Koninklijke Philips Electronics N.V.

(72) Inventor(s)
Gijsbert J. Van Den Enden; Aalbert Stek; Martinus W. Blum

(74) Agent/Attorney
F B Rice and Co,605 Darling Street,BALMAIN NSW 2041

(56) Related Art
EP 820063
US 6175686
US 5854876

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
21 December 2000 (21.12.2000)


PCT

(10) International Publication Number
WO 00/77787 A1

- (51) International Patent Classification: G11B 20/12, 27/30, 20/18 (74) Agent: VAN DER KRUK, Willem, L.; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (21) International Application Number: PCT/EP00/04931
- (22) International Filing Date: 29 May 2000 (29.05.2000) (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 99201840.8 10 June 1999 (10.06.1999) EP
- (71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. (NL/NL); Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors: VAN DEN ENDEN, Gijsbert, J.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). STEK, Aalbert; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). BLUM, Martinus, W.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:
— With international search report.

[Continued on next page]

(54) Title: ERROR CORRECTION ENCODING A DATA STREAM OF INFORMATION



(57) Abstract: An apparatus for error correction encoding a datastream of information into blocks of error correction encoded information is disclosed, comprising an input terminal (20) for receiving the data stream of information. An error correction encoding unit (22) is present for carrying out an error correction encoding step on portions of said datastream of information so as to obtain said blocks of error correction encoded information, a block of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word and a portion of said error correction encoded information, where n is a positive integer larger than 3. An output terminal (24) is present for supplying said blocks of error correction encoded information. In accordance with the invention, the error correction encoding unit (22) is adapted to supply one of m mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that the sequence of two sync words of two subsequent sync blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of error correction encoded information, m being an integer for which holds $2 < m < n$.

WO 00/77787 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Technical Field

The invention relates to an apparatus and method for error correction encoding a data stream of information into blocks of error correction encoded information. The invention further relates to a record carrier having blocks of error correction encoded information recorded on it.

Background Art

An apparatus for error correction encoding a data stream of information into blocks of error correction encoded information is known from WO96/31880.

The known apparatus discloses the generation of different sync words for the sync blocks in a block of error correction encoded information. This enables the identification of the position of a sync block within a block of error correction encoded information. In spite of this, errors occur after receiving the error correction encoded information that cannot be corrected for in the error correction step normally available in the receiver.

Summary of the Invention

In a first aspect, the invention is an apparatus for error correction encoding a data stream of information into blocks of error correction encoded information, the apparatus comprising:

- input means for receiving the data stream of information,
- error correction encoding means for carrying out an error correction encoding step on portions of said data stream of information so as to obtain said blocks of error correction encoded information, a block of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word and a portion of said error correction encoded information, where n is a positive integer larger than 3,
- output means for supplying said blocks of error correction encoded information, characterized in that the error correction encoding means are adapted to supply one of 7 mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information, such that the sequence of two sync words of two subsequent sync blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of error correction encoded information, and such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by one sync block, is unique for each group of two sync blocks in the block of error

correction encoded information, said two sync blocks being separated from each other by one sync block,

characterized in that the error correction encoding means are further adapted to supply sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks.

In a second aspect, the invention is a method for error correction encoding a data stream of information into blocks of error correction encoded information, the method comprising the steps:

- receiving the data stream of information,
- carrying out an error correction encoding step on portions of said data stream of information so as to obtain said blocks of error correction encoded information, a block of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word and a portion of said error correction encoded information, where n is a positive integer larger than 3,
- supplying said blocks of error correction encoded information,

the error correction encoding step is adapted to supply one of 7 mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that the sequence of two sync words of two subsequent sync blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of error correction encoded information, and such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by one sync block is unique for each group of two sync blocks in the block of error correction encoded information, said two sync blocks being separated from each other by one sync block,

characterized in that the error correction encoding step is further adapted to supply sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks.

In a third aspect, the invention is a record carrier having blocks of error correction encoded information recorded on it, a block of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word from one of 7 mutually different sync words, and a portion of said error

correction encoded information, where n is a positive integer larger than 3, wherein, in each of said n sync blocks in said block of error correction encoded information, said sync words are assigned such that the sequence of two sync words of two subsequent sync blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of error correction encoded information, and such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by one sync block is unique for each group of two sync blocks in the block of error correction encoded information, said two sync blocks being separated from each other by one sync block,

characterized in that said sync words are further assigned such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks.

According to at least one embodiment of the invention the error correction capability is improved.

In accordance with one embodiment of the invention, the apparatus is defined as characterized in that the error correction encoding means are adapted to supply a sync word to each of said n sync blocks in said block of error correction encoded information, such that a group of two sync words, one sync block in the block of error correction encoded information and the other in the next block of error correction encoded information and being separated by two sync blocks is unique for each group of two sync blocks in the two blocks of error correction encoded information.

The invention is based on the following recognition. Sync words used for identifying the sync blocks are generally unique bit patterns that do not occur elsewhere in the serial data stream of information. A further aim is to uniquely identify the exact position of a sync block in the array of n sync blocks in the blocks of error correction encoded information. This requires a plurality of mutually different sync words. It should further be noted that the error correction capability increases for increasing size of the blocks of error correction encoded information: that means for an increasing number of sync blocks in a block of error correction encoded information. Identifying each sync block separately would mean as many sync words as there are sync blocks in a block of error correction encoded information. In accordance with the invention, with the requirement that the sequence of two sync words of two sync blocks that are separated from each other by two sync blocks in the block of error correction encoded information is unique for each such two sync blocks in the block of error correction encoded information, less mutually different sync words are needed, so that more

words are available for the information itself, whilst moreover improving the error correction capability.

This enables a reliable determination of the position of the sync block detected, even in the case that the sync word of this sync block and the sync word of the preceding or the next sync block was missed.

Brief Description of the Drawings

These and other aspects of the invention will be apparent from and further elucidated with respect to embodiments described in the following figure description, in which:

Figure 1 shows a block of error correction encoded information, including sync blocks of information,

Figure 2 shows an embodiment of the error correction encoding apparatus; and

Figure 3 shows an embodiment of an error correction apparatus.

Detailed Description of the Drawings

Figure 1 shows a block 10 of error correction encoded information obtained from carrying out an error correction encoding step, generally known in the art, on a portion of the incoming data stream of information. The block 10 comprises n sync blocks, denoted $SB_1, SB_2, \dots, SB_{n-1}, SB_n$. Each sync block comprises a sync word, included in the first part FP1 in each of the sync blocks and the remaining part FP2 of the sync blocks is used for storing portions of the error correction encoded information in. A limited number of m mutually different sync words are used for incorporation into the first parts FP1 of each of the sync blocks.

In an embodiment of the block of error correction encoded information, it is assumed that $n=31$ and that 7 mutually different sync words are used for incorporation in the first parts FP1 of the 31 sync blocks.

In the table given below, the sync words for the 31 sync blocks of the block of error correction encoded information are given for four different embodiments. In all embodiments, 7 mutually different sync words are available sw0 to sw6. As can be seen, in each embodiment, the sync word sw0 is used for the first sync block of the block of error correction encoded information. The other sync words are used to identify the sync blocks numbered 2 to 31 in the block of error correction encoded information.

Table 1: various sequences of sync words

Sync block sequence no.	Sync word 1 st embodiment	Sync word 2 nd embodiment	Sync word 3 rd embodiment	Sync word 4 th embodiment
1	sw0	sw0	sw0	sw0
2	sw1	sw1	sw1	sw1
3	sw1	sw2	sw2	sw2
4	sw2	sw2	sw3	sw3
5	sw3	sw3	sw2	sw3
6	sw2	sw1	sw4	sw1
7	sw4	sw3	sw4	sw4
8	sw5	sw4	sw2	sw1
9	sw5	sw4	sw5	sw5
10	sw4	sw5	sw3	sw5
11	sw3	sw3	sw5	sw4
12	sw4	sw5	sw6	sw3
13	sw6	sw1	sw6	sw4
14	sw2	sw1	sw5	sw6
15	sw2	sw6	sw4	sw6
16	sw6	sw5	sw3	sw3
17	sw3	sw6	sw4	sw5
18	sw6	sw3	sw1	sw3
19	sw1	sw3	sw1	sw2
20	sw4	sw2	sw4	sw2
21	sw4	sw6	sw6	sw5
22	sw1	sw2	sw3	sw6
23	sw3	sw5	sw6	sw5
24	sw1	sw5	sw2	sw1
25	sw5	sw4	sw2	sw1
26	sw6	sw2	sw6	sw6
27	sw6	sw4	sw1	sw2
28	sw5	sw6	sw3	sw6
29	sw3	sw6	sw1	sw4
30	sw5	sw1	sw5	sw4
31	sw2	sw4	sw5	sw2

5 It is submitted that the apparatus of the invention generates the blocks of error correction encoded information in accordance with the array of sync words in one of the columns given below.

From the examples given above, it is clear that the array of sync words satisfy the following rules:

- 10 1. A sequence of two sync words of two subsequent sync blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of

error correction encoded information. An example: in the first embodiment, the sync words of the sync blocks SB_{27} and SB_{28} are sw_6 and sw_5 . This sequence of two sync words occurs only once in the sequence of 31 sync words. Further, preferably, also the sequence of the last sync word in a block of error correction encoded information and the first sync word in the next block of error correction encoded information is unique.

2. Each time two sync words of two sync blocks in the block of error correction encoded information being separated from each other by one sync block is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by one sync block. An example: in the second embodiment, the sync words of the sync blocks SB_{13} and SB_{15} are sw_1 and sw_6 . This sequence of two sync words occurs only once for sync words of sync blocks being separated from each other by one sync block in the block of error correction encoded information. This requirement is preferably also valid across the boundary between two subsequent blocks of error correction encoded information.

3. In accordance with the present invention, each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks. An example: in the third embodiment, the sync words of the sync blocks SB_2 and SB_6 are sw_1 and sw_2 . This sequence of two sync words occurs only once for sync words of sync blocks separated from each other by two sync blocks in the block of error correction encoded information.

This requirement is preferably also valid across the boundary between two subsequent blocks of error correction encoded information.

4. Each time two sync words of two sync blocks in the block of error correction encoded information being separated from each other by three sync blocks is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by three sync blocks. An example: in the fourth embodiment, the sync words of the sync blocks SB_{20} and SB_{24} are sw_2 and sw_1 . This sequence of two sync words occurs only once for sync words of sync blocks separated from each other by three sync blocks in the block of error correction encoded information. This requirement is preferably also valid across the boundary between two subsequent blocks of error correction encoded information.

During reception of a data stream comprising an array of blocks of error correction encoded information, subsequent sync blocks of information are received. Three subsequent sync blocks, defined as SB_{i-2} , SB_{i-1} , SB_i , SB_{i+1} and SB_{i+2} , have sync words defined as sw_a , sw_b , sw_c , sw_d and sw_e , respectively.

Suppose that, upon reception, the sync word of the sync block SB_i is distorted and cannot be identified. Assuming that the sync words sw_b and sw_e equal both sw_2 , and further assuming that the sync words satisfy the array of sync words in accordance with the first embodiment, it can be established that the distorted sync word was sw_3 , and that the sync block of this distorted sync word was the sync block SB_5 . It is now possible to store the data included in this sync block in the correct position in an error correction memory included in a receiver, so that an error correction step can be carried out on the data stored in the memory.

Suppose that, upon reception, the sync words of the sync blocks SB_i and SB_{i+1} are distorted and cannot be identified. Assuming that the sync words sw_b and sw_e equal sw_3 and sw_1 , and further assuming that the sync words satisfy the array of sync words in accordance with the second embodiment, it can be established that the distorted sync words were sw_5 and sw_1 and that the sync blocks of the distorted sync words were the sync blocks SB_{12} and SB_{13} , respectively. It is now possible to store the data included in these sync blocks in the correct position in an error correction memory included in a receiver, so that an error correction step can be carried out on the data stored in the memory.

Suppose that, upon reception, the sync words of the sync blocks SB_{i+1} , SB_i and SB_{i+1} are distorted and cannot be identified. Assuming that the sync words sw_a and sw_e equal sw_1 and sw_5 , and further assuming that the sync words satisfy the array of sync words in accordance with the third embodiment, it can be established that the distorted sync words were sw_3 , sw_1 and sw_5 and that the sync blocks of the distorted sync words were the sync blocks SB_{28} , SB_{29} and SB_{30} , respectively. It is now possible to store the data included in these sync blocks in the correct position in an error correction memory included in a receiver, so that an error correction step can be carried out on the data stored in the memory.

It will be clear that, where necessary, this can be extended in order to correct for more than three distorted sync words.

Figure 2 shows schematically an embodiment of the apparatus in accordance with the invention. The apparatus for error correction encoding a data stream of information into blocks of error correction encoded information, comprises an input terminal 20 for receiving the data stream of information. The input terminal 20 is coupled to an input of a signal processing unit 22. The unit 22 is capable of carrying out an error correction encoding step, well known in the art, on the incoming data stream. Further, the unit 22 may be capable of carrying out a channel encoding step, well known in the art, either prior to, but generally after, the error correction encoding step, on the incoming data stream. An error correction encoded data stream of information is supplied to an output terminal 24. Further, a generator

unit 26 is available for supplying the plurality of m mutually different sync words. The unit 26 could be in the form of a memory in which the m mutually different sync words are stored. Generation of a sync word can be realized by addressing a memory location in the memory by means of an address signal generated by a microprocessor unit 28 and supplied via the line 30.

- 5 The unit 28 further supplies a control signal via the line 32 to the processing unit 22 to control the functioning of the unit 22.

The error correction encoding unit 22 generates blocks of error correction encoded information in response to said error correction encoding step carried out a portions of said data stream of information. As an example, a block of v times w data words of the serial data stream of information is subjected to an error correction encoding step, resulting in the generation of 'horizontal' parity words and 'vertical' parity words. The parity words are arranged such that blocks of error correction encoded data are created comprising n times m data words. The n arrays of m data words each fit in the right hand portion of figure 1, indicated by FP2 for each of the n sync blocks. Each sync block further comprises a sync word. n is a positive integer larger than 3.

The error correction encoding unit 22 is further adapted to supply one of the m mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that the sequence of two sync words of two subsequent sync blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of error correction encoded information, m being an integer for which holds $2 < m < n$.

In another embodiment, the error correction encoding unit 22 is further adapted to supply one of the m mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information being separated one sync block apart from each other is unique for each group of two sync blocks in the block of error correction encoded information being separated one sync block apart, m being an integer for which holds $2 < m < n$.

7a

In another embodiment in accordance with the present invention, the error correction encoding unit 22 is adapted to supply one of m mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated
5 two sync blocks apart from each other is unique for each group of two sync blocks in the block of error correction



encoded information separated two sync blocks apart from each other, m being an integer for which holds $3 < m < n$. n should be larger than 4 in this case.

All above requirements could also be valid across the boundary between two subsequent blocks of error correction encoded information.

5 It should further be noted that the apparatus may be provided with a channel encoding unit 40 for carrying out a channel encoding step on the information prior to eg. recording the error correction encoded data on a record carrier 44, such as a magnetic record carrier, or an optical record carrier 46. The channel encoding step is well known in the art. The step of adding the sync words may be carried out in the channel encoding unit 40, instead
10 of in the error correction encoding unit 22.

It should be noted here that the various requirements described above for the application of the mutually different sync words to the various sync blocks could be combined into one and the same embodiment.

Figure 3 shows an error correction apparatus, provided with an input terminal
15 50 for receiving the blocks of error correction encoded information. Those blocks of error correction encoded information may have been obtained from reading information from a record carrier, such as the magnetic record carrier 44 or the optical record carrier 46, by means of a reading unit and after having carried out a channel decoding step on the information read from the record carrier in a channel decoding unit 52.

20 An error correction unit 56 is available for carrying out an error correction step on blocks of error correction encoded information included in the signal supplied via the terminal 50, so as to obtain blocks of error corrected information. The blocks of error corrected information are supplied to an output terminal 58 as a serial data stream of information. The apparatus is provided with a detection unit 60 for detecting m mutually
25 different sync words, where m is an integer smaller than n . More specifically, the detection unit 60 is adapted to detect two sync words in the blocks of error correction encoded information, said two sync words being the sync words of the i^{th} and j^{th} sync block in a block of error correction encoded information. The sync words detected are stored in a memory 62. This memory has at least three memory locations for storing the sync words detected for three
30 subsequent sync blocks in a block of error correction encoded information. When having detected two subsequent sync words of two subsequent sync blocks i and j in a block of information, the apparatus is capable of identifying the position of the said i^{th} and j^{th} sync block in said block of error correction encoded information. This is realized by means of a converter unit 64, which is capable of converting the sequence of two directly successive sync

words into a position information, indicating the position of the two sync blocks in the block of error correction encoded information.

The memory 62 has p memory locations for storing the sync words of p subsequent sync blocks, where p equals 3 or larger. In the case of $p=3$, the sync word in the second memory location may be erroneous, or could not be detected at all. Again the position of this central sync block of the three successive sync blocks corresponding to the three sync words in the memory 62 can be established in the converter unit 64, using the sync words in the first and third memory location of the memory 62.

In the case of $p=4$, the sync words in the second and/or third memory location of the memory 62 may be erroneous, or could not be detected at all. Again the position of this second and/or third sync block of the four successive sync blocks corresponding to the four sync words in the memory 62 can be established in the converter unit 64, using the sync words in the first and fourth memory location of the memory 62.

In the case of $p=5$, the sync words in the second and/or third and/or fourth memory location of the memory 62 may be erroneous, or could not be detected at all. Again the position of this second and/or third and/or fourth sync block of the five successive sync blocks corresponding to the five sync words in the memory 62 can be established in the converter unit 64, using the sync words in the first and fifth memory location of the memory 62.

Next, a different approach for determining the row number within a block from the sync numbers will be given. Use will be made of the sequence of sync words as listed in embodiment 4 in the previous table 1.

- Suppose two sync numbers S_R and S_{R-d} have been detected, where R is the unknown row number and d is the (known) distance between the syncs.
- It appears to be convenient to remap the sync numbers (see columns 4 and 5 of table 2) and to divide the total block of 31 sync blocks into 6 sub blocks of 5 rows and row 0. Now the sync numbers show a regular structure (as shown in column 6 of table 2). Sync S_0 disturbs the regular structure, which has to be accounted for (dark gray areas in columns 8 to 10 in table 2). Note that all additions in table 2 are done modulo 6.

Next, follows the procedure to determine the row number in the total block from two sync numbers and their distance:

1. Check for special cases: $S_R = 0$ (before remapping)
 $S_R = 2$ and $S_{R-d} = 5$ (after remapping, only when $d = 4$)
2. Calculate the difference $\Delta = S_R - S_{R-d}$ (modulo 6)

3. Determine the relative row number r with the appropriate lookup table (see table 3)
4. Calculate n_b . This is also the sub block number b
5. Calculate the absolute row number: $R = 5*b + r + 1$

5 With a brute force lookup table one would need 8 input bits (2 x 3 bits for the sync numbers and 2 bits for the distance) and 5 output bits. When this table is implemented in a ROM 1280 bits are required.

With the method described above 5 lookup tables (4 shown in table 3 and one to do the remapping of the sync numbers) with 3 input bits and 3 output bits are necessary. This requires

10 135 ROM bits plus some additional logic.

Table 2: Overview

sub block numbe r	Absolute row number	relative row number	Sync numb er	Remapped Sync number		Difference $\Delta = S_R - S_{R-d}$			
						Distance (d)			
b	R	r	S_R		n_b	1	2	3	4
	0		0	5					
0	1	0	1	0	$n_0 = 0$	1			
	2	1	2	5	n_0+5	5	0		
	3	2	3	2	n_0+2	3	2	3	3
	4	3	3	2	n_0+2	0	3	2	3
	5	4	1	0	n_0	4	4	1	0
1	6	0	4	1	$n_1 = 1$	1	5	5	2
	7	1	1	0	n_1+5	5	0	4	4
	8	2	5	3	n_1+2	3	2	3	1
	9	3	5	3	n_1+2	0	3	2	3
	10	4	4	1	n_1	4	4	1	0
2	11	0	3	2	$n_2 = 2$	1	5	5	2
	12	1	4	1	n_2+5	5	0	4	4
	13	2	6	4	n_2+2	3	2	3	1
	14	3	6	4	n_2+2	0	3	2	3
	15	4	3	2	n_2	4	4	1	0
3	16	0	5	3	$n_3 = 3$	1	5	5	2
	17	1	3	2	n_3+5	5	0	4	4
	18	2	2	5	n_3+2	3	2	3	1
	19	3	2	5	n_3+2	0	3	2	3
	20	4	5	3	n_3	4	4	1	0
4	21	0	6	4	$n_4 = 4$	1	5	5	2
	22	1	5	3	n_4+5	5	0	4	4
	23	2	1	0	n_4+2	3	2	3	1
	24	3	1	0	n_4+2	0	3	2	3
	25	4	6	4	n_4	4	4	1	0
5	26	0	2	5	$n_5 = 5$	1	5	5	2
	27	1	6	4	n_5+5	5	0	4	4
	28	2	4	1	n_5+2	3	2	3	1
	29	3	4	1	n_5+2	0	3	2	3
	30	4	2	5	n_5	4	4	1	0

Table 3 : Lookup tables that map the difference Δ to the relative row number r

$d = 1$	
r	Δ
0	1
1	5
2	3
3	0
4	4

(a)

$d = 2$	
r	Δ
0	5, 1
1	0
2	2
3	3
4	4

(b)

$d = 3$	
r	Δ
0	5
1	4, 0
2	3
3	2
4	1

(c)

$d = 4$	
r	Δ
0	2, 5
1	4
2	1
3	3
4	1

(d)

- Whilst the invention has been described with reference to preferred
- 5 embodiments thereof, it is to be understood that these are not limitative examples. Thus, various modifications may become apparent to those skilled in the art, without departing from the scope of the invention, as defined by the claims. Further, any reference signs do not limit the scope of the claims. The invention, as far as incorporated in the error correction encoding apparatus, can be implemented by means of both hardware and software, and several "means"
- 10 may be represented by the same item of hardware. The word 'comprising' does not exclude the presence of other elements or steps than those listed in a claim. Also, the word "a" or "an" preceding an element does not exclude the presence of a plurality of such elements. In addition, the invention lies in each and every novel feature or combination of features.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:-

1. An apparatus for error correction encoding a data stream of information into blocks of error correction encoded information, the apparatus comprising:
 - input means for receiving the data stream of information,
 - 5 - error correction encoding means for carrying out an error correction encoding step on portions of said data stream of information so as to obtain said blocks of error correction encoded information, a block of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word and a portion of said error correction encoded information, where n is a positive integer
 - 10 larger than 3,
 - output means for supplying said blocks of error correction encoded information, characterized in that the error correction encoding means are adapted to supply one of 7 mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks
 - 15 in the block of error correction encoded information, such that the sequence of two sync words of two subsequent sync blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of error correction encoded information, and such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other
 - 20 by one sync block, is unique for each group of two sync blocks in the block of error correction encoded information, said two sync blocks being separated from each other by one sync block,
 - characterized in that the error correction encoding means are further adapted to supply sync words to each of said n sync blocks in said block of error correction
 - 25 encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks.
2. An apparatus as claimed in claim 1, characterized in that the error correction
 - 30 encoding means are further adapted to supply sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by p sync blocks is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by p - 35 sync blocks apart from each other, where p is an integer larger than 2.

3. An apparatus as claimed in claim 1 or 2, characterized in that the error correction encoding means are further adapted to supply a specific one of said 7 sync words only to the first sync block of said n sync blocks in each of said blocks of error correction encoded information.
- 5 4. An apparatus as claimed in claim 1 characterized in that $n = 31$.
5. An apparatus as claimed in claim 4, characterized in that the error correction encoding means are further adapted to generate a block of error correction encoded information having a sequence of sync words in accordance with one of the embodiments given in table 1.
- 10 6. An apparatus as claimed in claim 1 characterized in that the error correction encoding means are further adapted to carry out a channel encoding step on either the data stream of information or on the error correction encoded data stream of information.
7. An apparatus as claimed in claim 1, characterized in that it further comprises
- 15 means for writing said blocks of error correction encoded information on a record carrier.
8. An apparatus as claimed in claim 1 characterized in that the error correction encoding means are adapted to supply a sync word to each of said n sync blocks in said block of error correction encoded information, such that a group of two sync words,
- 20 one sync block in the block of error correction encoded information and the other in the next block of error correction encoded information and being separated by q sync blocks is unique for each group of two sync blocks in the two blocks of error correction encoded information, said two sync blocks being separated from each other by q sync blocks, where q is an integer larger than 1.
- 25 9. A method for error correction encoding a data stream of information into blocks of error correction encoded information, the method comprising the steps:
- receiving the data stream of information,
 - carrying out an error correction encoding step on portions of said data stream of information so as to obtain said blocks of error correction encoded information, a block
 - 30 of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word and a portion of said error correction encoded information, where n is a positive integer larger than 3,
 - supplying said blocks of error correction encoded information,
 - the error correction encoding step is adapted to supply one of 7 mutually
 - 35 different sync words to each of said n sync blocks in said block of error correction encoded information, such that the sequence of two sync words of two subsequent sync



blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of error correction encoded information, and such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by one sync block is unique for each group of two sync blocks in the block of error correction encoded information, said two sync blocks being separated from each other by one sync block,

characterized in that the error correction encoding step is further adapted to supply sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks.

10. A record carrier having blocks of error correction encoded information recorded on it, a block of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word from one of 7 mutually different sync words, and a portion of said error correction encoded information, where n is a positive integer larger than 3, wherein, in each of said n sync blocks in said block of error correction encoded information, said sync words are assigned such that the sequence of two sync words of two subsequent sync blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of error correction encoded information, and such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by one sync block is unique for each group of two sync blocks in the block of error correction encoded information, said two sync blocks being separated from each other by one sync block,

characterized in that said sync words are further assigned such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks.

11. A record carrier as claimed in claim 10, characterized in that a block of error correction encoded information has a sequence of sync words in accordance with one of the embodiments given in table 1.

12. An apparatus for error correcting blocks of error correction encoded information obtained with the method as claimed in claim 9 into a serial data stream of information, the apparatus comprising:

- input means for receiving the blocks of error correction encoded information,
 - error correction means for carrying out an error correction step on said blocks of error correction encoded information so as to obtain blocks of error corrected information,
- 5 - output means for supplying said blocks of error corrected information as a serial data stream of information,
- characterized in that said error correction means is adapted to detect 7 mutually different sync words, the error correction means comprising detection means for detecting first and last sync word of p subsequent sync blocks, where p is larger than 3,
- 10 the error correction means further being adapted to identify the position of the said p subsequent sync blocks in said block of error correction encoded information using the detected first and last sync word of the said p subsequent sync blocks.
13. An apparatus as claimed in claim 12, characterized in that said identifying step for identifying said position makes use of a conversion table.
- 15 14. An apparatus for error correction encoding a data stream of information into blocks of error correction encoded information, substantially as herein described with reference to Figures 2 or 3 of the accompanying drawings and with reference to the accompanying tables.
15. A method for error correction encoding a data stream of information into blocks
- 20 of error correction encoded information, substantially as herein described with reference to Figures 2 or 3 of the accompanying drawings and with reference to the accompanying tables.
16. A record carrier having blocks of error correction encoded information recorded on it, substantially as herein described with reference to Figures 2 or 3 of the
- 25 accompanying drawings and with reference to the accompanying tables.

DATED this sixth day of January 2003

Koninklijke Philips Electronics NV
Patent Attorneys for the Applicant:

F.B. RICE & CO.

1/2




FIG. 1




FIG. 2

2/2




FIG. 3