



- (51) International Patent Classification:
B62D 11/14 (2006.01)
- (21) International Application Number:
PCT/EP2014/058460
- (22) International Filing Date:
25 April 2014 (25.04.2014)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
1311628.0 28 June 2013 (28.06.2013) GB
- (71) Applicant: **QINETIQ LIMITED** [GB/GB]; Cody Technology Park, Ively Road, Farnborough Hampshire GU14 0LX (GB).
- (72) Inventor: **FLAXMAN, Robert, John, Bonner**; QinetiQ Limited, c/o Cody Technology Park, Ively Road, Farnborough Hampshire GU14 0LX (GB).
- (74) Agent: **LOUGHREY, Paul, Francis**; QinetiQ Limited, Malvern Technology Centre, St Andrews Road, Malvern Worcestershire WR14 3PS (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

[Continued on next page]

(54) Title: DRIVE CONFIGURATIONS FOR SKID STEERED VEHICLES




Figure 6

(57) Abstract: A controlled differential adapted to couple two shafts (7a, 7b) and steer input, such as those provided in a drive configuration for a skid steered vehicle, the controlled differential comprising: a pair of planet carriers (14a, 14b) arranged to turn with respective shafts; a pair of ring gears (12) interconnected by a cross-shaft such that the ring gears rotate in common; planet gears (11) and a pair of sun gears (10), the sun gears being coupled to at least one steer motor (9) to enable rotation of the sun gears in mutually opposite senses upon input from the steer motor.



Published:

— *with international search report (Art. 21(3))*

DRIVE CONFIGURATIONS FOR SKID STEERED VEHICLES

Field of the invention

The present inventions relate to novel drive configurations for skid steered vehicles, including tracked or wheeled vehicles, for example but not limited to, a military
5 armoured tank.

Background to the invention

A skid steered tracked vehicle is steered by forcing opposing parallel tracks to run at different speeds (skid steering). Similarly, a skid steered wheeled vehicle is steered by forcing wheels on one side of the vehicle to run at different speeds to the wheels
10 on the other side of the vehicle. For tracked vehicles to steer, large driving force differences are required between the two tracks – large braking forces on the inner track and high driving forces on the outer track. Differential gears and cross-shafts are used to control the relative speeds of the tracks and transfer the braking power from the inner track to the outer track to sustain the turn. A similar arrangement is
15 used for a skid steered wheeled vehicle.

A number of electric track drive arrangements use a separate electric motor (propulsion or traction motor) to drive each track, known as a “two-line” system. The regenerative steering power in such a system is generally handled electrically resulting in the need for oversized motors and power converters to handle this power.
20 An alternative configuration uses the same mechanical regenerative arrangement as in a conventional transmission combined with an electric drive, known as a “cross-shaft electric drive” system. In this arrangement, the steer cross-shaft runs across the vehicle outside the propulsion motor which increases the size of the assembly and requires a number of idler gears. If a gear-change is to be used, the propulsion
25 cross-shaft should be separate from the motor shaft. This can be achieved by making the motor shaft hollow and passing the cross-shaft through the motor shaft. However, this increases the diameter of the motor bearings making a high speed motor difficult to achieve. The propulsion cross-shaft may be mounted outside of the motor, or the motor mounted outside of the propulsion shaft but this increases the
30 package size and adds the needs for idler gears, increasing the complexity of the arrangement and reducing its efficiency.

US Patent No. 4,998,591 discloses a drive configuration which uses a single differential, mounted centrally and driven by a single propulsion motor. The

differential is identical to a single differential in a conventional wheel driven car or truck axle. The torque from the drive motor is divided equally between the two half shafts which can rotate at different speeds relative to one another. On each half shaft is mounted a steer motor. To steer the vehicle, the inside steer motor must act
5 as a brake and the outside steer motor must apply additional driving torque to generate the large track drive force difference across the vehicle to cause it to skid steer. The steer motors are operating at the speed of the half shafts, handling high torque and at high power, one regenerating and one driving and thus require oversized motors.

- 10 The present Applicant, QinetiQ Limited, has developed skid steering arrangements that make use of a controlled differential. A controlled differential has the characteristics that it couples two half shafts and controls their speeds. When the steer motor is stationary the two half shafts are simply coupled by the control differential so that they run at the same speed. When the steer motor is rotated in
15 one direction one half shaft runs faster than the other and when the steer motor is rotated in the other direction, the other half shaft runs faster than the other. Operation of the steer motor thereby causes the vehicle to turn.

WO 02/083482 describes an electric drive configuration for a skid steered vehicle wherein a pair of propulsion motors is each in operable communication with one of a
20 pair of rear track drive sprockets. The steer motor is in drivable communication with a controlled differential steer gear unit positioned centrally of a pair of steering cross-shafts and in drivable communication with each shaft, the opposing end of these shafts being in operable communication with one of a pair of front track drive sprockets. This arrangement enables fitting of the steering cross-shaft and controlled
25 differential at one end of the vehicle and the drives at the other end of the vehicle, simplifying the packaging of the arrangement and reducing the volume taken up in the hull. Both track drives at the rear of the vehicle are able to continue to drive the vehicle forwards during turning unlike the two-line system where inside motors brake and the outside motors apply additional driving power to cause the vehicle to turn.

- 30 WO 02/083483 relates to another drive configuration having a controlled differential configured to cause transmission of regenerative steering powers through the propulsion motor shaft thereby removing the need for cross-shafts. A steer motor is mounted on a cross-shaft which is interconnected via gears with a shaft of the controlled differential which in turn is connected via gears and an output shaft of the
35 controlled differential to each propulsion motor.

WO2006/0121745 describes a central casing for housing the various components of the electric drive transmission. The electric propulsion motors each comprise a stator fixed in the casing and associated with a rotor borne within the casing. A through-shaft passes coaxially through the rotor for delivering torque from each motor to track drive sprockets and a gear change mechanism is located within the casing to transmit torque from the rotor to the through-shaft at selected gear ratios. The through-shaft is rotationally supported by bearings acting between the shaft and the casing and the rotor is rotationally supported by bearings between the rotor and shaft. This enables the motor rotor bearings to be simple, small diameter low speed rated ball bearings. The arrangement also reduces the number of bearing points in the casing and the complexity, mass and cost of the casing and the overall size of the transmission can be reduced.

WO 2008/117025 describes a controlled differential for a skid steered vehicle that has a parallel pair of planetary gear sets but comprising compound (linked) planet gears in a common planet carrier coupling two motor drive shafts. Respective ring gears turn with the shafts and mesh with the compound planet gear in the planet carrier, the ratios of the teeth between each ring gear and the respective gear of the compound planet gear being unequal so that when the planet carrier is stationary the two shafts are coupled through the differential to turn together in the same sense but with a speed difference. Controlled rotation of the planet carrier varies the speed difference between the shafts in accordance with the sense and speed of rotation of the planet carrier.

The controlled differential for known skid steer transmission systems is more efficient for low speed - high torque applications. In order to minimise the control differential torque (and hence the overall weight) the rotational speed is stepped up through multiple gears in order to drive the tracks or wheels. The bearings can be highly loaded during straight-line driving as well as during steering which is not ideal. As the speed of the vehicle increases, the high speed controlled differential causes increased parasitic spin losses due to friction and aerodynamic drag. The high centripetal forces also put high stress on the bearing cages of the planet gears. The bearing stress can be addressed by the use of high strength bearing cages with anti-wear coatings but these are expensive and therefore add to the cost of the system. The heat generated is removed by the provision of cooling oil to regulate the control differential temperatures.

During a skid-steer turn, the regenerated steering power from the inside track (sprocket) is transferred through the inside final drive gear reduction, through the transmission and through the outside final drive gear reduction to the outside track (sprocket). The transmission arrangements of the prior art transfer the regenerative steering power through the transmission through four gear stages (i.e. the (inside) output gear reduction stage, the two gear sets of the steer differential, and the (outside) gear reduction stage). Given that each planetary gear stage introduces a reduction in efficiency of the energy transfer, the use of multiple gear sets leads to a reduction in efficiency of the system. The output gear stages also need to be sized to transfer the same steering power and torque as the final drive and output track sprockets, requiring large output gear stages.

Furthermore, the maximum propulsion or traction motor speed in the prior art designs is currently limited to that of the main shaft. The maximum main shaft speed is limited by the controlled differential speed and the maximum allowable load on the controlled differential planet gear bearings. For the same power output of an electric motor, the faster the motor speed can be, the smaller the size of the traction motor and associated gearing (and hence the lower the overall weight and size).

The propulsion motor speed sensors (resolvers) of the known systems are also susceptible to electro-magnetic interference due to their position around the main shaft inside the motor rotor. Additionally, there is the potential for the motor currents to cause electrical discharge machining of the gear elements, possible incompatibility of the gearbox oil with the electric motor components, and a less than optimal solution for the transmission package in terms of size, weight and efficiency; all these issues require specific remedies that complicate the design.

The present invention aims to provide novel drive configurations and controlled differentials for skid steered vehicles which seek to overcome, or at least alleviate, one or more of the aforementioned problems encountered with the prior art drive configurations.

Summary of the invention

In accordance with a first aspect of the present invention there is provided a controlled differential adapted to couple two shafts and steer input, such as those provided in a drive configuration for a skid steered vehicle, the controlled differential comprising: a pair of planet carriers arranged to turn with respective shafts; a pair of ring gears interconnected by a cross-shaft such that the ring gears rotate in common;

planet gears and a pair of sun gears, the sun gears being coupled to at least one steer motor to enable rotation of the sun gears in mutually opposite senses upon input from the steer motor.

5 According to a second aspect of the present invention there is provided a controlled differential adapted to couple two shafts comprising: first and second outer ring gears arranged to turn with respective shafts; first and second inner ring gears interconnected by a cross-shaft such that the inner ring gears rotate in common; planet gears and planet carriers, the carriers being coupled to at least one steer motor whereby operation of the steer motor enables rotation of the carriers in
10 mutually opposite senses and a corresponding change in rotation of the one or each shaft via the ring and planet gears.

The controlled differential according to the second aspect of the present invention may be incorporated into a standard drive configuration for a skid steered vehicle comprising a respective drive member adapted to be located at each side of the
15 vehicle, each drive member engaging with a track or wheel of the vehicle; at least one propulsion motor in operable communication with said drive members operable to drive the tracks or wheels of the skid steered vehicle; at least one steer motor in driveable communication with the carrier of the controlled differential according to the first aspect of the present invention, the controlled differential being positioned
20 between and connecting two shafts and being in driveable communication with each shaft, the ends of each shaft remote from the controlled differential forming an output of the transmission and being in driveable communication with the drive members. The incorporation of the novel controlled differential of the first aspect of the invention reduces load on bearings supporting the planet gears during straight line driving of a
25 skid steered vehicle.

Preferably, a final drive unit or final drive reduction gear is provided on each shaft positioned between the transmission output and the drive member. At least one gear reduction stage and/or gear change unit associated with said propulsion motor is generally provided between the controlled differential and the drive member. The
30 controlled differential is provided between the two transmission outputs.

It is to be appreciated that the drive configuration should also include at least one brake and that any number of gear reduction stages may be included to give a desired optimum balance of weight, volume, efficiency and reliability.

A third aspect of the present invention provides a novel drive configuration for a skid steered vehicle. The drive configuration may incorporate a controlled differential according to the first aspect of the present invention, incorporate a conventional controlled differential according to the prior art or may incorporate novel controlled
5 differentials according to later aspects of the invention. The novel drive configuration re-positions the shafts to be in direct contact with the drive members. Rather than the output of the controlled differential connecting to the input of an output gear reduction, the output of the controlled differential connects directly to the output of the transmission. Generally, the output from the propulsion motor and the gear reduction
10 stage(s) will be connected in parallel to the transmission output.

To this end, a third aspect of the present invention provides a novel drive configuration comprising: a respective drive member adapted to be located at each side of the vehicle, each drive member engaging with a track or wheel of the vehicle; at least one propulsion motor in operable communication with said drive members
15 operable to drive the tracks or wheels of the skid steered vehicle; at least one steer motor in driveable communication with the controlled differential, the controlled differential being positioned between and connecting two shafts and being in driveable communication with each shaft, the ends of each shaft remote from the controlled differential forming the transmission output and being in driveable
20 communication with the drive members, wherein at least part of the output of the controlled differential connects directly to the transmission output.

In the context of this disclosure, the term "connects directly to" means that the controlled differential output attaches solidly to and turns at the same speed without any gear mesh loss or coupling that would introduce a power transfer loss. The
25 controlled differential output preferably does not pass through any range change gears. Preferably, a spline coupling connects a part of the controlled differential directly to the, or each, shaft. One or both output sides of the controlled differential may connect directly to the transmission output.

Preferably, the drive configuration includes a gear reduction unit and/or gear change
30 unit which may be indirectly connected to the transmission output. Preferably, the transmission output is connected to a final drive input. It is preferable for the propulsion motor and/or gear reduction/change units to be connected in parallel to the transmission output.

It is to be appreciated that bearings should be provided to rotationally support the
35 shafts and gears.

The aforesaid arrangement enables the speed of the propulsion motor to be independent of the main drive shaft and controlled differential. The centripetal load on the planet bearings is still present but since the speeds are much less, the bearings do not experience the current level of parasitic loss at high speeds and standard bearing cages may be used. The controlled differential and drive configuration according to the first and second aspects of the invention reduce wear on the bearings enabling standard bearings to be used.

As mentioned above, the third aspect of the present invention may be provided with a conventional controlled differential adapted to couple two shafts and steer input comprising: a pair of planetary gear sets, each comprising a sun gear, planet gears carried by a planet carrier and a ring gear, the sun gears being coupled to at least one steer motor whereby operation of the steer motor enables rotation of the sun gears in mutually opposite senses, the planet carriers being interconnected by a cross-shaft such that the carriers rotate in common, the shafts of the drive configuration being coupled to respective ring gears.

Alternatively, a modified controlled differential according to a fourth aspect of the present invention may be used. The fourth aspect of the present invention provides a controlled differential adapted to couple two shafts and a steer input, such as those provided in a drive configuration for a skid steered vehicle, the controlled differential comprising: a planet carrier arranged to turn with one of said shafts and being in direct communication with an output carrier of a first output gear reduction stage; a first controlled differential sun gear arranged to turn with the other of said shafts and being in direct operable communication with a second sun gear of a second output gear reduction stage; a ring gear being coupled to at least one steer motor through a series of gear reduction stages to enable a differential torque to be applied at the first sun gear and planet carrier.

A second planet carrier may be coupled to a second set of planet gears, the second planet carrier to be in direct operable communication with the output drive. The gear reduction stages between the ring gear and the steer motor may consist of a planetary gear set.

The aforesaid arrangement enables the torque from the controlled differential carrier to go directly into the transmission output whereas the torque from the controlled differential sun gear goes into an output gear reduction sun gear and another gear reduction. Thus, the controlled differential output is connected directly to the

transmission output on only one side of the drive transmission. The speed of the propulsion motor and controlled differential may be set the same but the sizing of the differential would be no different than the sizing of the output gear reduction therefore alleviating specific issues with the controlled differential of the prior art.

5 The present invention also provides for alternative embodiments of the second aspect of the present invention having novel drive configurations with a modified layout of the component parts. Again, the controlled differential is coupled directly to the transmission output, preferably without passing through any range change gears.

10 This drive configuration may be provided with a conventional controlled differential to couple the shafts and steer input or be provided with a controlled differential according to the first, third or fourth aspects of the present invention.

To this end, a fifth aspect of the present invention provides a drive configuration for a
15 skid steered vehicle comprising a respective drive member adapted to be located at each side of the vehicle, each drive member engaging with a track or wheel of the vehicle; at least one propulsion motor in operable communication with said drive members operable to drive the tracks or wheels of the skid steered vehicle; at least one steer motor in driveable communication with a controlled differential positioned
20 between and connecting a pair of primary shafts and in driveable communication with each primary shaft, the ends of each primary shaft remote from the controlled differential forming an output of the transmission and being in driveable communication with the drive members; wherein the at least one propulsion motor is provided on a secondary shaft remote from the primary shafts.

25 A final drive unit or final drive reduction gear is preferably provided on each primary shaft positioned between the drive member and the output of the transmission.

More preferably, at least one gear reduction stage and/or gear change unit associated with said propulsion motor is provided remote from the primary shaft,
30 more preferably both the gear reduction and gear change units are provided remote from the primary shaft with the propulsion motor on the secondary or lay shaft. Preferably the gear reduction and gear change units are provided in series whereby the controlled differential connects to the shaft in parallel with the output gear reduction from the propulsion motor.

35

The at least one gear change unit associated with said propulsion motor provided remote from the primary shaft may be coupled directly to the secondary shaft or through a tertiary shaft through which the selectable gears may be attached.

5 The drive configuration according to the fifth aspect of the present invention may include at least one resolver to monitor the speed of the motor, preferably being positioned on the unattached end on at least one propulsion motor mounted on the secondary (or tertiary) shaft.

10 The aforesaid arrangement enables the speed of the propulsion motor to be independent of the primary shaft and controlled differential. The repositioning of one or more gear sets from the primary shaft to the secondary shaft is also desirable and the lay out provides greater versatility for the positioning of the various components of a drive transmission system.

15 A sixth aspect of the present invention provides a novel controlled differential adapted to couple two shafts and steer input, such as those provided in a drive configuration for a skid steered vehicle, the controlled differential comprising a pair of planetary gear sets comprising at least a pair of planet carriers, planet gears and ring gears, at least one of the pairs being arranged to turn with respective shafts, at least one of the other pairs being interconnected by a cross-shaft such that these gears rotate in common and the gears of at least one of another pair being coupled to at least one steer motor to enable rotation of these gears in mutually opposite senses upon input from the steer motor, the controlled differential further comprising a releasable locking mechanism for temporary locking of the cross-shaft whereby at least one steer motor provides torque and power through the controlled differential.

25 The provision of a locking mechanism to lock the differential cross shaft requires the steer motors to be de-coupled from one another and the speed and direction of the steer motors can be independently controlled.

30 Preferably, the locking mechanism comprises a clutch mechanism. The controlled differential according to the sixth aspect of the present invention may be incorporated into a drive configuration for a skid steered vehicle comprising: a pair respective drive members adapted to be located at each side of the vehicle, each drive member engaging with a track or wheel of the vehicle; at least one propulsion motor in operable communication with said drive members operable to drive the tracks or wheels of the skid steered vehicle; at least one steer motor in driveable communication with a controlled differential according to the sixth aspect of the

35

present invention, the controlled differential being positioned between and connecting two shafts and being in driveable communication with each shaft, the ends of each shaft remote from the controlled differential forming an output of the transmission and being in driveable communication with the drive members.

5

Preferably, the locking clutch mechanism enables locking of the cross-shaft to a housing surrounding the components of the drive configuration.

10 It is to be appreciated that the sixth aspect of the present invention may be provided in any of configurations according to the first, second, third, fifth and sixth aspects of the present invention wherein a locking mechanism may be applied to lock the cross shaft to allow use of the steer motors for low speed propulsion.

The present invention also provides a vehicle equipped with a drive configuration and/or controlled differential according to any of the aspects of the invention.

15 **Brief Description of the Drawings**

For a better understanding of the present invention and to show more clearly how it may be carried into effect, embodiments of the invention will now be described, by way of example only, with reference to the following Figures in which:

Figure 1 is a diagrammatic illustration of a prior art drive configuration;

20 **Figure 2** illustrates schematically an example of a mechanism for the controlled differential of Figure 1;

Figure 3 shows one embodiment of a controlled differential according to a second aspect of the present invention;

25 **Figure 4** illustrates the controlled differential of Figure 3 installed into the prior art drive configuration of Figure 1;

Figure 5 shows one embodiment of a drive transmission system according to a third aspect of the present invention, fitted with the controlled differential shown in Figure 3;

30 **Figure 6** shows the drive transmission system of the first aspect of the present invention provided with a novel controlled differential according to a third aspect of the present invention;

Figure 7 is an alternative embodiment of a drive transmission system according to the present invention, incorporating the third aspect of the present invention on one side of the system only and being provided with a novel controlled differential according to a fourth aspect of the present invention;

Figure 8 is an embodiment of a drive transmission system according to a fifth aspect of the present invention fitted with the controlled differential shown in Figure 3;

Figure 9 is an embodiment of a drive transmission system according to a fifth aspect of the present invention fitted with the controlled differential of Figure 6; and

Figure 10 is an embodiment of a drive transmission system according to a sixth aspect of the present invention, fitted with the controlled differential of Figure 6.

Detailed Description

Figures 1 and 2 of the accompanying drawings illustrates diagrammatically one drive transmission arrangement for a skid steer vehicle according to the prior art. The traverse drive arrangement comprises two propulsion motors, also known as traction motors 1a, 1b. Outboard of each motor there is a planetary gear range change unit 2a, 2b, planetary gear reduction stage 3a, 3b and final drive gear reduction 5a, 5b leading to respective track drive sprockets 6a, 6b at opposite sides of the vehicle. Inboard, the motor drive shafts 7a, 7b are coupled to opposite sides of a controlled differential 8 which can be driven by a coupled pair of electric steer motors 9a, 9b. All of the aforesaid components except the final drive gear reduction 5a, 5b and drive members 6a, 6b form the transmission.

A more detailed representation of the controlled differential 8 is shown schematically in Figure 2. It comprises a pair of planetary gear sets or epicyclic gear trains joined back-to-back, each comprising a sun gear 10a, 10b, planet gear 11a, 11b, a planet carrier 14a, 14b and a ring gear 12a, 12b. The ring gears 12a, 12b connect to the main output drive shafts 7a, 7b and the sun gears 10a, 10b connect to the steer motors 9a, 9b via wheels 15a, 15b that mesh with a pinions 17a, 17b via idlers 18a, 18b, 18c on the end of a steer motor shaft 19. The carriers 14a, 14b connect to a cross-shaft 13. For straight-line driving, the steer motors 9a, 9b pinion 17a, 17b, idlers

18a,18b,18c, wheels 15a, 15b and sun gears 10a, 10b are stationary whilst the ring gears 12a, 12b and carriers 14a, 14b can spin continuously. In this respect, energising the propulsion motors 1a, 1b to drive the sprockets 6a, 6b also rotates the annuli or ring gears 12a, 12b and causes the planet gears 11a, 11b to rotate about the sun gears 10a, 10b. The planet carriers 14a, 14b also rotate at the same speed due to being connected through the cross shaft 13, equalising the speeds of the two annuli 12a, 12b and the two connected transmission drives 1a, 1b causing the tracks to operate at the same speed and therefore move in a straight line. However, the continuously rotating carrier 14 results in the bearings of the planet gears 11a, 11b being subjected to g-forces due to the centripetal forces from the planet mass itself which load the bearings continuously. The bearing cages which hold the rolling elements of the bearing in place are also subjected to the same g-forces. The loads get higher as the main shaft increases in speed. This can lead to parasitic losses and stressed bearing cages being experienced with straight-line driving alone which increases with the speed.

The vehicle is turned in one sense by operation of the steer motors 9a, 9b. The steer motor is energised to rotate the pinion 17a,17b in the same sense as the steer motor, thus causing the wheels 15a, 15b via idlers 18a,18b,18c and their respective sun gears 10a or 10b to rotate in mutually opposite senses. The two planet carriers 14a, 14b must always turn together resulting in an increase in the rate of rotation of the planet gears 11a or 11b in that set for which the sun gear 10a or 10b is turning in the opposite sense to the respective annulus 12a or 12b and a decrease in the rate of rotation of the planet gears 11a or 11b in that set for which the sun gear 10a or 10b is turning in the same sense as the respective annulus 12a or 12b. This causes the annuli and their respective connected transmission drives to the sprockets 6a, 6b to run at different speeds thus turning the vehicle in the required sense, while power from the slower running transmission drive is regenerated to the faster running transmission drive through the controlled differential 8.

In this arrangement one end of the main shaft is connected to the controlled differential 8 ring gears 12a, 12b and the other end of the main shaft is connected to the input (i.e. sun) of the gear reduction stage 3a, 3b. Therefore, steering power flows into the transmission on one side and must pass through the output gear reduction stage gear meshes on the other side before exiting the transmission. Power passes through four sets of epicyclic gear meshes.

The aforementioned controlled differential is fit for purpose but it is desirable to reduce the current level of spin losses during high speed straight-line driving and reduce the dependency on specialised bearing cages.

5 The various aspects of the present invention provide changes to the architecture and/or controlled differential gear arrangements to provide more efficient and reliable drive transmission systems.

10 Figures 3 and 4 of the accompanying drawings illustrate one embodiment of a novel controlled differential arrangement according to a second aspect of the present invention which aims to address the current level of spin losses during straight-line driving and the need for specialised bearing cages. Identical features to those present in Figures 1 and 2 are given the same reference numerals for simplicity. Note that the figures only show the transmission part of the system with the brakes, final drive units 5a, 5b and drive members 6a, 6b, which are common to all designs, being omitted.

15 Figure 3 provides a detailed representation of the new controlled differential and Figure 4 illustrates the controlled differential installed in the prior art drive transmission layout of Figure 1. The controlled differential comprises a pair of gear sets joined back-to-back, each comprising compound planet gears 11a, 11b, 11c, 11d, planet carriers 14a, 14b and a ring gears 12a, 12b, 12c, 12d. There are no sun
20 gears. The ring gears 12a, 12b connect to the main output drive shafts 7a, 7b and the planet carriers 14a, 14b connect to the steer motors 9a, 9b via idlers 18a, 18b, 18c that mesh with a pinions 17a, 17b on the end of a steer motor shaft 19. The compound planet gears 11a, 11b connect to the outer ring gears 12a, 12b and planet gears 11c, 11d connect to inner ring gears 12c, 12d. The inner ring gears 12c, 12d
25 connect to a cross-shaft 13. Again, one end of the main shaft 7a, 7b is connected to the ring gears 12a, 12b and the other end of the shaft connected to the input (i.e. sun) of the gear reduction stage 3a, 3b (see Figure 4).

30 For straight-line driving, the steer motor 9a, 9b pinion 17a, 17b idlers 18a, 18b, 18c, and carriers 14a, 14b are stationary whilst the ring gears 12a, 12b, 12c, 12d will spin continuously. In this respect, energising the propulsion motors 1a, 1b to drive the sprockets 6a, 6b also rotates the outer annuli or ring gears 12a, 12b and causes the compound planet gears 11a, 11b, 11c, 11d to rotate about their pin axis. The inner annuli or ring gears 12c, 12d will rotate at the same speed due to being connected through the cross shaft 13. The speeds of the two outer annuli 12a, 12b and the two

connected transmission drives 1a, 1b cause the tracks to operate at the same speed and therefore move in a straight line.

The planet gears 11a,11b,11c,11d rotate only about their pin axis for straight-line driving and their respective bearings are not subjected to any centripetal forces until
5 the vehicle turns thus reducing the parasitic losses associated with the centripetal forces and forces on the bearings cages.

The vehicle is turned in one sense by operation of the steer motor 9a, 9b. The steer motor is energised to rotate the pinion 17a, 17b in the same sense as the steer motor, thus causing carriers 14a, 14b via idlers 18a, 18b, and 18c to rotate in
10 mutually opposite senses. Rotating the carriers 14a and 14b in mutually opposite directions will also rotate the compound planets 11a,11c and 11b,11d in mutually opposite directions. One side will increase the speed of the outer ring gear 12a or 12b and the other side the other side will decrease the speed of the outer ring 12b or 12a causing their respective connected transmission drives to the sprockets 6a, 6b to
15 run at different speeds thus turning the vehicle in the required sense, while power from the slower running transmission output drive is regenerated to the faster running transmission output drive through the controlled differential 8.

Figures 5 to 7 of the accompanying drawings illustrate embodiments of a third aspect of the present invention. The system architecture is altered to improve further the
20 efficiency and reliability of the drive transmission system. These figures again show only the transmission part of the layout, with the brakes, final drive units and drive members being omitted for simplicity. In certain embodiments, the controlled differential is also changed as the re-arrangement of the system architecture may lend itself to a more optimal arrangement of gears within the controlled differential.

Referring to the first embodiment shown in Figure 5, the main shafts 7a, 7b are no longer connected to the transmission output through output gear reductions 3a, 3b but directly become the output of the transmission. The propulsion motors 1a, 1b are no longer directly connected to the main shaft 7a, 7b via the gear change 2a, 2b but go through the output gear reduction stages 3a, 3b. The controlled differential 8 is
25 still connected directly to the main shafts 7a, 7b. In this manner, the power transfer from one side of the transmission needs only to travel through the controlled differential and the losses associated with the output gear reduction stages is no longer present thus making the system more efficient.
30

In more detail, the controlled differential ring gear 12a, 12b is connected directly to the main shaft 7a, 7b. In the context of the present disclosure, the phrase “connected directly to” means attached solidly to and turns at the same speed as the shaft without any gear mesh loss or with any type of coupling that would introduce a power transfer loss. For example, the ring gears may be connected to the shaft via a spline coupling. The output carrier of the gear reduction stage 3a, 3b is connected directly to the main shaft 7a, 7b along the middle of the shaft via a spline coupling, with the other end of the shaft being the transmission output. In this arrangement, the output shaft has two parallel power sources; one from the propulsion or traction motor 1a, 1b via the range change 2a, 2b and the output gear reduction stages 3a, 3b and the other from the controlled differential 8. The main shaft 7a, 7b connects directly to the controlled differential 8 on one end and to the transmission output on the other end. The output (i.e. carrier) of the gear reduction stage 3a, 3b connects directly to the shafts 7a, 7b in parallel (i.e. shafts 7a, 7b, 3a output carrier, 3b output carrier, 12a, 12b all rotate at the same speed). The steering power flows into the transmission on one side and only need pass through the controlled differential gear meshes and out the other side. Power does not need to flow through any of the output gear reduction stage gear meshes and therefore power only flows through two sets of epicyclic gear meshes.

The controlled differential will operate in straight line driving and steering as described in relation to Figures 1 and 2 although it will be rotating at a slower rate since it no longer has to go through the output gear reduction; therefore, the associated spin losses will be less and there will be an overall improvement in efficiency. The controlled differential and main shafts will have to be bigger due to the fact that they will have to take more torque but this may be offset by the reduction in weight of the output gear stages 3a, 3b.

Figure 6 shows an alternative embodiment of the third aspect of the present invention. The overall transmission layout is similar to the first embodiment as described for Figure 5 with the controlled differential connected directly to the transmission output enabling the controlled differential to rotate at a much slower speed and thus the losses associated with the centripetal forces will be considerably less. This enables an alternative controlled differential according to a first aspect of the present invention to be used which may be lighter and less costly than the one required to minimise the spin losses and bearing stresses for the transmission layout described in Figure 3 and 4.

The controlled differential layout according to an embodiment of the second aspect of the present invention comprises a pair of planetary gear sets or epicyclic gear trains joined back-to-back, each comprising a sun gear 10a, 10b, planet gear 11a, 11b, a planet carrier 14a, 14b and a ring gear 12a, 12b. The carrier 14a, 14b connect to the main output drive shafts 7a, 7b and the sun gears 10a, 10b connect to the steer motors 9a,9b via wheels 15a, 15b that mesh with a pinions 17a,17b via idlers 18a, 18b,18c on the end of a steer motor shaft 19. The ring gears 12a, 12b connect to a cross-shaft 13. For straight-line driving, the steer motors 9a,9b pinion 17a,17b idlers 18a,18b,18c, wheels 15a, 15b and sun gears 10a, 10b are stationary whilst the ring gears 12a, 12b and carriers 14a, 14b can spin continuously. In this respect, energising the propulsion motors 1a, 1b to drive the sprockets 6a, 6b also rotates the planet carriers 14a, 14b and causes the planet gears 11a, 11b to rotate about the sun gears 10a, 10b. The annuli or ring gears 12a, 12b also rotate at the same speed due to being connected through the cross shaft 13, equalising the speeds of the two planet carriers 14a, 14b and the two connected transmission drives 1a, 1b causing the tracks to operate at the same speed and therefore move in a straight line.

The controlled differential will be rotating at a slower rate since it no longer has to go through the output gear reduction; therefore, the associated spin losses will be less and there will be an overall improvement in efficiency.

The vehicle is turned in one sense by operation of the steer motors 9a, 9b. The steer motor is energised to rotate the pinion 17a,17b in the same sense as the steer motor, thus causing the wheels 15a, 15b via idlers 18a,18b,18c and their respective sun gears 10a or 10b to rotate in mutually opposite senses. The two ring gears 12a, 12b must always turn together resulting in an increase in the rate of rotation of the planet gears 11a or 11b in that set for which the sun gear 10a or 10b is turning in the opposite sense to the respective annulus 12a or 12b and a decrease in the rate of rotation of the planet gears 11a or 11b in that set for which the sun gear 10a or 10b is turning in the same sense as the respective carriers 14a or 14b. This causes the carriers and their respective connected transmission drives to the sprockets 6a, 6b to run at different speeds thus turning the vehicle in the required sense, while power from the slower running transmission output drive is regenerated to the faster running transmission output drive through the controlled differential 8.

Figure 7 shows another embodiment of the third aspect of the present invention having an alternative configuration for the controlled differential with an improved

layout of the transmission. This embodiment has only one side of the controlled differential connected directly to the transmission output (left hand side in figure).

This side of the transmission has one end of the main shaft 7a connected directly to carrier 14 of the controlled differential and the other end of shaft 7a to the

5 transmission output. The torque and power from propulsion motor 1a passes through a gear range change unit 2a and output gear reduction stage 3a before connecting in parallel to the main shaft 7a. The other side of the transmission (right hand side in figure) has one end of the shaft 7b connected directly to the sun 10 of the controlled differential and the end of the shaft 7b connected to the input of the
10 reduction stage 3b. The torque and power from the other propulsion motor 1b goes through a range change unit 2b before connecting in parallel to the shaft 7b. The combined torque and power from the propulsion motor 1b (via range change unit 2b) and controlled differential sun gear 10 go into the sun of gear reduction stage 3b. The transmission output on this side thus connects directly to the carrier of the gear
15 reduction stage 3b. A final drive or final drive reduction gear (not shown in Figure 7) may sit between the drive member and the controlled differential on one side and the gear reduction stage and drive member on the opposing side.

Thus in this embodiment the controlled differential is combined with one of the output gear reduction stages and combines two planetary gear sets or epicyclic gear
20 trains. As shown in Figure 7, the right output gear reduction stage 3b is used with the centre controlled differential gear stage 8 to steer the vehicle. The sun gear 10 of the controlled differential connects directly to the sun gear of the right output gear reduction stage 3b. The controlled differential carrier 14 connects directly to the carrier of the left output gear reduction stage 3a. The steering torque through the
25 controlled differential is through the ring gear 12. A second planetary gear set is used only as part of the gear reduction stages between the controlled differential 8 and the steer motors 9a, 9b. The controlled differential ring gear is attached to the planetary gear reduction stage 21 and connects steer motor via wheel gear 15, idler 18, pinion 17 and steer motor shaft 19.

30 In this arrangement, the left output gear reduction stage 3a will only need to be sized for the maximum power and torque of the propulsion motor 1a whereas the right output gear reduction 3b stage will be sized for the maximum power and torque from the right propulsion motor 1b plus the steering power and torque from the controlled differential 8.

During straight line driving, the controlled differential sun gear 10 will rotate at the same speed as the right output stage 3b sun gear and the controlled differential carrier 14 will rotate at the same speed as the left output stage 3a carrier. The controlled differential ring gear 12 and the steer motor reduction gears 21, 15, 17, 19 and the steer motors 9a, 9b will be stationary. Since the rotational speed is the same as the output gear reduction stages 3a, 3b, the spin losses associated with controlled differential will be similar to the losses in the output gear reduction stages 3a, 3b and the centripetal forces on the planet gear 11 bearings will be considerably less, thereby improving efficiency and reducing heat loss. Also, the need for bearings to take high g-forces is no longer necessary.

To steer the vehicle, torque is applied at steer motors 9a, 9b which apply torque to the controlled differential ring gear 12 via the gear reduction stages, 17, 18, and 21. This will result in a differential torque at the sun gear 10 and the carrier 14 which will impose a torque difference between the main shafts. The torque from the controlled differential carrier 14 will go directly into the left transmission output and the torque from the controlled differential sun gear 10 will go into the right output gear reduction sun gear 3b and then goes through the right gear reduction 3b.

This layout results in an asymmetry between the left and right sides which is different from the other symmetrical system layouts herein described. Note that the controlled differential 8 gear ratio will need to be the same as the right output gear reduction stage 3b and the left output gear reduction 3a. During straight line driving, this will allow the propulsion motors to be the same size and rotate at the same speed and the output from the transmission to be the same on the left and right sides. However, the power transfer from left side to right side only goes through two gear stages (i.e. the controlled differential 8 and the right gear reduction 3a) which will improve the efficiency during steering.

A fifth aspect of the present invention relates to a significant change in the architecture of the drive transmission system to optimise the design for weight, volume, efficiency, reliability and cost. This is achieved by locating the propulsion motors on a secondary, parallel lay-shaft to the main shaft, along with multiple gear change stages. Any one of the controlled differentials discussed hereinbefore in relation to the prior art, first, second, third or fourth aspects of the present invention may be incorporated into the drive transmission systems of the fifth aspect of the invention. Again the arrangement is such that the controlled differential may connect

directly to the transmission output with the range gear reduction stage 2a, 2b and the output reduction stage 3a, 3b being in series.

Figure 8 shows one embodiment according to a fifth aspect of the present invention having an alternative drive transmission layout but with the controlled differential according to an embodiment of the second aspect of the invention shown in Figures 3 and 4. The propulsion motors 1a and 1b are no longer in line with the main shaft 7a, 7b but instead are located on secondary lay shafts 20a, 20b. The associated range change gears 2a, 2b are also located on this lay-shaft and the gear reduction stage 3a, 3b is between the lay-shaft and the main shaft, thereby reducing the number of gears that are present on the main shafts between the left and right sides. Additionally, the controlled differential 8 has been adapted to reduce the loading on the planet gear bearings whilst straight-line driving, thereby reducing overheating and wear on the bearings and allowing standard bearings to be used. More specifically, the controlled differential 8 now has outer ring gears 12a, 12b attached to the main shafts 7a, 7b and inner ring gears 12c, 12d attached to a cross-shaft 13. The steer motors 9a, 9b connect to the carriers 14a, 14b of the planetary gear assembly via pinions 17a, 17b and idler 18 and there are no sun gears. This arrangement results in there being no load on the planet bearings until steer motor torque is applied or steering of the vehicle occurs. During straight-line driving, all of the ring gears 12a-12d rotate, causing the compound planet gears to rotate but the carriers 14a, 14b is stationary. The planet gears spin only about their pin axis and therefore are not subjected to any centripetal forces which result from the carrier spinning until steering occurs, thereby creating a more efficient controlled differential with parasitic losses at maximum vehicle speed reduced by around 60%, possibly even 80%, without the need for high-strength bearing cages with anti-wear coatings. Operation of the steer motor causes movement of the carrier and a corresponding change in rotation of the main shaft via the gears to effect steering of the vehicle.

Figure 9 shows an alternative embodiment of the fifth aspect of the present invention having the novel drive transmission layout of Figure 8 but with a controlled differential 8 according to the first aspect of the invention, described hereinbefore in relation to Figure 6. The propulsion motors 1a and 1b are again no longer in line with the main shaft 7a, 7b but instead are located on secondary lay shafts 20a, 20b. The associated range change gears 2a, 2b are also located on this lay-shaft and gear reduction stage 3a, 3b is between the lay-shaft and the main shaft, thereby reducing the number of gears that are present on the main shafts between the left and right sides. Additionally, as described in relation to Figure 6, the controlled differential 8

has been adapted to reduce the loading on the planet gear bearings whilst straight-line driving, thereby reducing overheating and wear on the bearings and allowing standard bearings to be used. More specifically, the controlled differential 8 now has outer planet carriers 14a, 14b attached to the main shafts 7a, 7b and ring gears 12a, 12b attached to a cross-shaft 13. The steer motors 9a, 9b connect to the sun gears 10a, 10b of the planetary gear via the wheel gear 15a, 15b, idler 18, and pinions 17a, 17b.

During straight-line driving, all the planet carriers 14a, 14b, and ring gears 12a, 12b rotate and sun gears 10a, 10b, wheel gears 15a, 15b, idler 18, pinions 17a, 17b and steer motors 9a, 9b are stationary. There are centripetal forces which result from the carrier spinning but the speeds are much slower thereby creating a more efficient controlled differential with parasitic losses at maximum vehicle speed reduced without the need for high-strength bearing cages with anti-wear coatings. Operation of the steer motors 9a, 9b causes movement of the pinion 17a, 17b, idler 18, wheel gears 15a, 15b and sun gears 10a, 10b and a corresponding change in rotation of the main shaft via the gears to effect steering of the vehicle.

The lay-shaft arrangement shown in Figures 8 and 9 provides a number of benefits over the prior art. Placement of the selectable gears and gear reduction stages between the propulsion motors and the main shaft enables the differential to run at the same speed as the transmission output whilst the propulsion motors are not limited to this speed. Furthermore, the presence of fewer gear stages between the controlled differential and the final output to the tracks or wheels reduces the loss during steer power transfer between the inside and outside sprocket. The ability of the planet gears to rotate only about their pin axis during straight line driving as in the arrangement shown in Figure 8 also assists in addressing this issue. This increases the efficiency of the arrangement.

The drive transmission according to the present invention also enables the output reduction gears associated with the propulsion motor to be reduced in size as they no longer have to take the full steering power and torque (i.e. full cross-shaft regenerative power and the propulsion power) but instead take only the power of the propulsion motor. In this respect, steering powers can be typically 200% to 300% higher than the propulsion motor power and steering torque about 80% higher. Locating the propulsion motor away from the middle of the configuration also makes these motors more accessible aiding in assembly and maintenance of the propulsion motors.

The motor speed sensing resolver can be fitted to the end of the propulsion motor (similar to the steer motors in prior art) which would allow a smaller standard size resolver to be fitted rather than a large custom designed resolver which needs to fit around the main shaft in the in-line configuration. This arrangement also will minimise the amount of sensor interference from any induced currents within the main shaft allowing a more stable resolver signal to the electric motor inverter drives.

This arrangement also isolates the electric motors from the gearbox, reducing concerns about gearbox oil compatibility with the motors and electric machining damage from the electric motors to the gears.

The lay-shaft arrangement can also be more compact and versatile. In particular, optimum design, in terms of motor size and shape, is more easily achievable since maximum length of the motor is less of a constraint. Gear size and ratio can also be optimised for face width and diameter since the need to have very narrow gears with a large diameter to fit in-line with the propulsion motors has been alleviated in this embodiment of the invention.

Referring to Figure 10 of the accompanying drawings, one embodiment of a sixth aspect of the present invention is illustrated. The embodiment shown has a drive transmission arrangement similar to that shown in Figure 9, having the propulsion motors 1a, 1b, range change gears 2a, 2b and output gear reduction 3a, 3b located on a separate lay-shaft 20a, 20b to reduce the number of gear stages on the main shaft and to enable the controlled differential to run at the same speed as the final drive output. The controlled differential 8 is again symmetrical with carriers 14a, 14b as the output and ring gears 12a, 12b connecting the cross-shaft 13, with steering power provided from the planet suns 10a, 10b.

Additionally, the arrangement includes a locking clutch mechanism 22 coupled to the cross shaft 13 to enable locking of the cross shaft to the case 30 to allow the steer motors 9a, 9b to drive the vehicle at low speed as in a two-line system of the prior art. This enables the steering motor to switch between a normal configuration (wherein the steer motors provide steering power and the propulsion motors are used for propulsion) and a configuration where the steer motors can be used to drive the vehicle. The steer motors could be used to drive the vehicle to provide extra torque and power to the propulsion motors or could be used in the event of a failure of a propulsion motor. Since the gear ratio to steer motors is generally high, using the steer motors for driving the vehicle will most likely be used at low speed up to the speed, torque and power limit of the steer motor.

Once the vehicle is required to travel at high speeds, the clutch mechanism is used to unlock the centre shaft, enabling the steering motor to be used for steering and the propulsion motors to be used for propulsion. Note the steer motors are no longer connected together on a common shaft, as described in the earlier embodiments of the invention.

In detail, during normal operation both control differential carriers 14a, 14b, planet gears 11a, 11b, and both ring gears 12a, 12b rotate while both sun gears 10a, 10b steer motors 9a, 9b and associated gear reduction stages are stationary. Driving the steer motors 9a, 9b in opposite directions applies steering torque and power through the controlled differential 8 and the drive transmission operates in the standard manner with the steer motors providing steering power and the propulsion motors providing traction power.

Prior to application of the locking mechanism 22, it is necessary to drive the steer motors 9a, 9b together in the same direction to spin up the sun gears 10a, 10b of the controlled differential and slow down the controlled differential cross shaft 13. Once the cross shaft rotation speed reaches zero, the locking mechanism 22 may be applied to lock the cross shaft to the case 30. From this point, the steer motors are able to apply torque and power through the controlled differential 8. Each steer motor can be controlled independently and can apply torque and speed at each output to either drive the vehicle directly or as a supplement to the respective propulsion motors.

It is to be appreciated that the ability to lock the centre shaft by way of a clutch mechanism 22 may be provided for other types of drive transmission systems in addition to the type shown in Figure 10 and to systems using other types of controlled differentials to enable the steer motors to drive the vehicle at low-speed and high torque.

The present inventions concern improvements to various aspects of drive transmission systems for skid steered vehicles, including the provision of an additional lay-shaft or twin shaft arrangement for mounting of the propulsion motor(s) and/or gear shifts and modifications to the controlled differential. Any one transmission system may include one, some or all of the changes discussed herein. The optimal embodiment chosen for a given vehicle will depend upon the operating environment and other factors, such as cost, efficiency, reliability, power and weight.

Claims

1. A controlled differential adapted to couple two shafts and steer input, such as those provided in a drive configuration for a skid steered vehicle, the controlled differential comprising: a pair of planet carriers arranged to turn with respective shafts; a pair of ring gears interconnected by a cross-shaft such that the ring gears rotate in common; planet gears and a pair of sun gears, the sun gears being coupled to at least one steer motor to enable rotation of the sun gears in mutually opposite senses upon input from the steer motor.
2. A controlled differential adapted to couple two shafts comprising: first and second outer ring gears arranged to turn with respective shafts; first and second inner ring gears interconnected by a cross-shaft such that the inner ring gears rotate in common; planet gears and planet carriers, the carriers being coupled to at least one steer motor whereby operation of the steer motor enables rotation of the carriers in mutually opposite senses and a corresponding change in rotation of the one or each shaft via the ring and planet gears.
3. A drive configuration for a skid steered vehicle comprising a respective drive member adapted to be located at each side of the vehicle, each drive member engaging with a track or wheel of the vehicle; at least one propulsion motor in operable communication with said drive members operable to drive the tracks or wheels of the skid steered vehicle; at least one steer motor in driveable communication with the carrier of a controlled differential as claimed in claim 2, the controlled differential being positioned between and connecting two shafts and being in driveable communication with each shaft, the ends of each shaft remote from the controlled differential forming an output of the transmission and being in driveable communication with the drive members.
4. A drive configuration as claimed in claim 3 further comprising at least one gear reduction stage and/or gear change unit associated with said propulsion motor provided between the controlled differential and the drive member.

5. A drive configuration for a skid steered vehicle comprising: a respective drive member adapted to be located at each side of the vehicle, each drive member engaging with a track or wheel of the vehicle; at least one propulsion motor in operable communication with said drive members operable to drive the tracks or wheels of the skid steered vehicle; at least one steer motor in driveable communication with the controlled differential, a controlled differential being positioned between and connecting two shafts and being in driveable communication with each shaft, the ends of each shaft remote from the controlled differential forming an output from the transmission and being in driveable communication with the drive members, wherein at least part of the output of the controlled differential connects directly to the transmission output.
6. A drive configuration as claimed in claim 5 wherein a spline coupling connects a part of the controlled differential directly to the or each shaft.
7. A drive configuration as claimed in claim 5 or claim 6 further comprising a gear reduction unit and/or gear change unit indirectly connected to the transmission output.
8. A drive configuration as claimed in claim 7 wherein the propulsion motor and/or gear reduction unit and/or gear change units are connected in parallel to the transmission output.
9. A drive configuration as claimed in any one of claims 5 to 8 having a controlled differential comprising a pair of planetary gear sets, each comprising a sun gear, planet gears carried by a planet carrier and a ring gear, the sun gears being coupled to at least one steer motor whereby operation of the steer motor enables rotation of the sun gears in mutually opposite senses, the planet carriers being interconnected by a cross-shaft such that the carriers rotate in common, the shafts of the drive configuration being coupled to respective ring gears.
10. A drive configuration as claimed in any one of claims 5 to 8 incorporating a controlled differential according to claim 1.

11. A controlled differential adapted to couple two shafts and a steer input, such as those provided in a drive configuration for a skid steered vehicle, the controlled differential comprising: a planet carrier arranged to turn with one of said shafts and being in direct communication with an output carrier of a first output gear reduction stage; a first controlled differential sun gear arranged to turn with the other of said shafts and being in direct operable communication with a second sun gear of a second output gear reduction stage; a ring gear being coupled to at least one steer motor through a series of gear reduction stages to enable a differential torque to be applied at the first sun gear and planet carrier.
12. A controlled differential as claimed in claim 11 wherein a second planet carrier is coupled to a second set of planet gears, the second planet carrier being in direct operable communication with the transmission output.
13. A controlled differential as claimed in claim 11 or claim 12 wherein the gear reduction stages between the ring gear and the steer motor consist of a planetary gear set.
14. A drive configuration according to any one of claims 5 to 8 incorporating a controlled differential of any of claims 11 to 13.
15. A drive configuration for a skid steered vehicle comprising a respective drive member adapted to be located at each side of the vehicle, each drive member engaging with a track or wheel of the vehicle; at least one propulsion motor in operable communication with said drive members operable to drive the tracks or wheels of the skid steered vehicle; at least one steer motor in driveable communication with a controlled differential positioned between and connecting a pair of primary shafts and in driveable communication with each primary shaft, the ends of each primary shaft remote from the controlled differential forming an output of the transmission and being in driveable communication with the drive members; wherein the at least one propulsion motor is provided on a secondary shaft remote from the primary shafts.
16. A drive configuration as claimed in claim 15 wherein a final drive unit is provided on each primary shaft positioned between the transmission output and the drive member.

17. A drive configuration as claimed in claim 15 or claim 16 wherein at least one gear reduction stage and/or gear change unit associated with said propulsion motor is provided remote from the primary shaft.

5

18. A drive configuration as claimed in claim 17 wherein both the gear reduction and gear change units are provided remote from the primary shaft with the propulsion motor on the secondary shaft.

10 19. A drive configuration as claimed in claim 18 wherein the at least one gear change unit associated with said propulsion motor provided remote from the primary shaft is provided on a tertiary shaft.

15 20. A drive configuration as claimed in any one of claims 15 to 19 further comprising at least one resolver to monitor the speed of the motor.

21. A drive configuration as claimed in claim 20 wherein the resolver is positioned on the at least one propulsion motor mounted on the secondary shaft.

20 22. A controlled differential adapted to couple two shafts and steer input, such as those provided in a drive configuration for a skid steered vehicle, the controlled differential comprising a pair of planetary gear sets comprising at least a pair of planet carriers, planet gears and ring gears, at least one of the pairs being arranged to turn with respective shafts, at least one of the other
25 pairs being interconnected by a cross-shaft such that these gears rotate in common and the gears of at least one of another pair being coupled to at least one steer motor to enable rotation of these gears in mutually opposite senses upon input from the steer motor, the controlled differential further comprising a releasable locking mechanism for temporary locking of the
30 cross-shaft whereby the at least one steer motor provides torque and power through the controlled differential.

23. A controlled differential as claimed in claim 22 wherein the locking mechanism comprises a clutch mechanism.

35

24. A drive configuration for a skid steered vehicle comprising: a pair of respective drive members adapted to be located at each side of the vehicle,

each drive member engaging with a track or wheel of the vehicle; at least one propulsion motor in operable communication with said drive members operable to drive the tracks or wheels of the skid steered vehicle; at least one steer motor in driveable communication with a controlled differential as claimed in claim 22 or claim 23, the controlled differential being positioned between and connecting two shafts and being in driveable communication with each shaft, the ends of each shaft remote from the controlled differential forming an output of the transmission and being in driveable communication with the drive members.

25. A vehicle equipped with a drive configuration and/or controlled differential according to any one of the preceding claims.




Figure 1
PRIOR ART




Figure 2
PRIOR ART




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10

INTERNATIONAL SEARCH REPORT

International application No.
PCT/EP2014/058460

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:
1-10, 25

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2014/058460

A. CLASSIFICATION OF SUBJECT MATTER
INV. B62D11/14
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
B62D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2007/213160 A1 (LYONS ARTHUR P [US] ET AL) 13 September 2007 (2007-09-13)	1,5-10
A	paragraph [0038]; figures 4,4a	2
X	US 2003/106725 A1 (IRIKURA KOJI [JP]) 12 June 2003 (2003-06-12)	1,5
	figure 1	
A	US 4 998 591 A (ZAUNBERGER FRANZ-XAVER [DE]) 12 March 1991 (1991-03-12)	1
	cited in the application	
	abstract	
A	WO 02/083482 A1 (QINETIQ LTD [GB]; THOMPSON ROBERT WILLIAM [GB]) 24 October 2002 (2002-10-24)	1
	cited in the application	
	abstract	
	-/--	



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

24 June 2014

Date of mailing of the international search report

09/10/2014

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Van Prooijen, Tom

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2014/058460

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 02/083483 A1 (QINETIQ LTD [GB]; THOMPSON ROBERT WILLIAM [GB]) 24 October 2002 (2002-10-24) cited in the application abstract	1
A	----- WO 2006/021745 A1 (QINETIQ LTD [GB]; THOMPSON ROBERT WILLIAM [GB]) 2 March 2006 (2006-03-02) cited in the application abstract	1
A	----- WO 2008/117025 A1 (QINETIQ LTD [GB]; THOMPSON ROBERT WILLIAM [GB]) 2 October 2008 (2008-10-02) cited in the application abstract	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2014/058460

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2007213160 A1	13-09-2007	US 2007213160 A1	13-09-2007
		WO 2007106480 A2	20-09-2007
US 2003106725 A1	12-06-2003	US 2003106725 A1	12-06-2003
		US 2006048975 A1	09-03-2006
		US 2006191725 A1	31-08-2006
		US 2007284173 A1	13-12-2007
		US 2009194360 A1	06-08-2009
US 4998591 A	12-03-1991	NONE	
WO 02083482 A1	24-10-2002	AT 305871 T	15-10-2005
		DE 60206481 D1	10-11-2005
		DE 60206481 T2	22-06-2006
		EP 1381534 A1	21-01-2004
		GB 2390069 A	31-12-2003
		US 2004121871 A1	24-06-2004
		WO 02083482 A1	24-10-2002
WO 02083483 A1	24-10-2002	AT 316030 T	15-02-2006
		AT 334860 T	15-08-2006
		AU 2002249414 B2	17-02-2005
		CA 2444240 A1	24-10-2002
		CN 1511096 A	07-07-2004
		CN 101041362 A	26-09-2007
		DE 60208779 T2	02-11-2006
		DE 60213673 T2	02-08-2007
		EP 1379424 A1	14-01-2004
		EP 1506905 A1	16-02-2005
		ES 2254665 T3	16-06-2006
		ES 2266974 T3	01-03-2007
		GB 2389829 A	24-12-2003
		RU 2252888 C1	27-05-2005
		US 2004116228 A1	17-06-2004
		WO 02083483 A1	24-10-2002
		ZA 200307760 A	04-10-2004
		ZA 200407380 A	25-05-2005
WO 2006021745 A1	02-03-2006	AT 462637 T	15-04-2010
		AU 2005276267 A1	02-03-2006
		CA 2574074 A1	02-03-2006
		EP 1781525 A1	09-05-2007
		ES 2340186 T3	31-05-2010
		KR 20070049640 A	11-05-2007
		US 2008300084 A1	04-12-2008
		WO 2006021745 A1	02-03-2006
		ZA 200700646 A	25-09-2008
WO 2008117025 A1	02-10-2008	AT 529317 T	15-11-2011
		EP 2125492 A1	02-12-2009
		ES 2375677 T3	05-03-2012
		US 2010105511 A1	29-04-2010
		WO 2008117025 A1	02-10-2008

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 1-10, 25

A drive configuration for a skid steered vehicle with at least one propulsion motor and one steer motor having two pairs of ring wheels, the ring wheels of one pair being connected to drive shafts and those of the other pair being interconnected, and carriers coupled to the at least one steer motor

2. claims: 11-14

A controlled differential adapted to couple two shafts and a steer input, such as those provided in a drive configuration for a skid steered vehicle, with a planet carrier connected to one shaft, the sun gear to the other shaft, and the ring gear to the steer motor

3. claims: 15-21

A drive configuration for a skid steered vehicle wherein the at least one propulsion motor is provided on a secondary shaft remote from the primary shafts

4. claims: 22-24

A controlled differential adapted to couple two shafts and steer input involves a releasable locking mechanism for temporary locking of the cross-shaft whereby the at least one steer motor provides torque and power through the controlled differential
