




(86) Date de dépôt PCT/PCT Filing Date: 2003/10/17
(87) Date publication PCT/PCT Publication Date: 2005/05/26
(45) Date de délivrance/Issue Date: 2013/11/26
(85) Entrée phase nationale/National Entry: 2006/03/16
(86) N° demande PCT/PCT Application No.: EP 2003/011568
(87) N° publication PCT/PCT Publication No.: 2005/047995

(51) Cl.Int./Int.Cl. *G05B 19/18* (2006.01)
(72) Inventeurs/Inventors:
BLUMBERG, MANFRED, DE;
DIRRICHS, STEFAN, DE;
LONDON, WOLFGANG, DE;
TOEPFER, GARY, DE
(73) Propriétaire/Owner:
TRINARY ANLAGENBAU GMBH, DE
(74) Agent: BERESKIN & PARR LLP/S.E.N.C.R.L.,S.R.L.

(54) Titre : SYSTEME DE COMMANDE INFORMATIQUE DE DONNEES NEUTRES POUR UNE MACHINE-OUTIL
SERVANT A LA FABRICATION DE PIECES USINEES COMPORTANT UNE SURFACE D'ENVELOPPE FILETEE
ET MACHINE-OUTIL ASSOCIEE

(54) Title: NEUTRAL DATA COMPUTER CONTROL SYSTEM FOR A MACHINE TOOL USED TO PRODUCE
WORKPIECES WITH A THREADED SURFACE AND ASSOCIATED MACHINE TOOL



(57) **Abrégé/Abstract:**

Neutral data computer control system for a multiaxis machine tool for producing workpieces having a helicoidal generated surface with an optional computer system (1) for generating machine control parameters for a multiaxis machine tool (2, 2a) in which there is provided at least one virtual axis, which can be parameterized as a guiding axis for other axes and then serves only for the synchronization of these other axes, and with at least one data processing unit and at least one memory, the data processing unit being set up in programming terms in such a way that it generates at least one data carrier or an electronic carrier signal (3) with machine control parameters for the machine (2, 2a), or an optional computer program or a computer program product for this and at least one such multiaxis machine tool (2, 2a).



Abstract

Neutral data computer control system for a multiaxis machine tool for producing workpieces having a helicoidal generated surface with an optional computer system (1) for generating machine control parameters for a multiaxis machine tool (2, 2a) in which there is provided at least one virtual axis, which can be parameterized as a guiding axis for other axes and then serves only for the synchronization of these other axes, and with at least one data processing unit and at least one memory, the data processing unit being set up in programming terms in such a way that it generates at least one data carrier or an electronic carrier signal (3) with machine control parameters for the machine (2, 2a), or an optional computer program or a computer program product for this and at least one such multiaxis machine tool (2, 2a).

- 1 -

NEUTRAL DATA COMPUTER CONTROL SYSTEM FOR A MACHINE TOOL
USED TO PRODUCE WORKPIECES WITH A THREADED SURFACE AND
ASSOCIATED MACHINE TOOL

5

The present invention relates to a neutral data computer control system for a machine tool with a computer system, a computer program and computer program products, and also an associated machine tool.

10

Against the background of increasingly interlinked production processes and their standardization in the industry, the problem that is nowadays the prime concern in the production of machine tools is that of also
15 incorporating in this process the computer systems that are necessary for activating the machine tools. In this respect, one aim is to provide, to the extent technically possible, standardized machine control systems, offering the user greatest possible uniformity of the machine control
20 parameters for the products from his range of workpieces - for instance when changing an actual machine type or else for improved data storage and archiving.

25

Such initiatives have already been pursued for some time for various types of machine tool, including for instance for bevel gear cutting machines, which are the focus of attention here.

30

For bevel gear cutting machines there are for instance solutions to this in which the relevant machine control parameters of an entire machine family are combined in a standardized data model with all the axes to be activated that come into consideration in the machine family, which then, in individual cases, is replicated on the respective
35 machine actually concerned - to the extent to which this is possible - that is to say the axes activated by the machine control parameters are also actually present.

40

For gear cutting machines for the form milling or grinding of workpieces having a helicoidal generated surface, that is to say in particular spur gears, worms and rotors, such a system does not exist as yet -

- 2 -

although it would of course also be desirable here for the reasons stated above.

The reason for this lies in a particular technical difficulty that has to be overcome in the form grinding of these workpieces: multiaxis positioning systems, as are also required by machine tools, need synchronization of the individual movements with one another, so that a defined curve is followed in three-dimensional space. This is achieved by one of the axes serving not only for its own positioning but also as a guiding axis for the synchronization of the other axes to be positioned.

Such a method according to the prior art can be found for instance in EP 0 784 525, which relates to a method of producing tooth flank modifications on bevel gears. The relevant axes are activated preferably by means of a polynomial function of the form

20

$$f(\Theta) = a_0 + \frac{a_1}{1!} \cdot \Delta\Theta + \frac{a_2}{2!} \cdot \Delta\Theta^2 + \frac{a_3}{3!} \cdot \Delta\Theta^3 + \frac{a_4}{4!} \cdot \Delta\Theta^4$$

where $f(\Theta)$ is the positioning function for the respective axis to be activated in dependence on the movement of the guiding axis Θ . The coefficients a_0 , a_1 , a_2 , a_3 and a_4 serve in this case as further parameters of the position control of the respective axis activated by the function $f(\Theta)$.

According to the prior art, one of the mechanical axes of the machine tool to be activated always serves in this case as the guiding axis. In the case of bevel gear cutting machines, which operate by the generating method and therefore have a cradle, as also in the case of EP 0 784 525, usually this cradle, which is always necessary, is used as the guiding axis; consequently, its generating movement is used as a guiding movement for the synchronization of the movements of the other

- 3 -

axes. In this way there always exists - even
irrespective of the further actual configuration of the
respective machine type - a machine axis which, as a
result of the generating process, can be used in a
5 standard way as a guiding axis.

For form grinding machines on the other hand, which
have no cradle or comparable axis, the problem of
suitably choosing such a standardized guiding axis, or
10 the question of possibly doing without it, immediately
arises when attempting to standardize the machine
control parameters for different machine types.

It is of course also possible here in principle to do
15 without such a standard guiding axis and instead to
specify the axis respectively used in the individual
case as the guiding axis in the machine control
parameters. Creating such a possibility can already
lead to a certain standardization of the machine
20 control parameters. Nevertheless, this is
unsatisfactory, since, when changing a machine type to
a machine which does not have the selected guiding
axis, there is not only the problem of creating new
machine control parameters for the guiding axis but
25 also, on account of the dependencies described above of
the other axes on the guiding axis, always the
immediate requirement of generating new machine control
parameters for all the other axes that are dependent on
the guiding axis. If, on the other hand, there is no
30 other axis present as the guiding axis, it can be
attempted to achieve its positioning result on the
workpiece by other further axes that are instead
present on the new machine type being activated by
machine control parameters in a corresponding way, the
35 other axes with their respective machine control
parameters remaining unaffected.

Thus, for instance, an absent positionable pivoting
axis for the pivoting of the workpiece and tool with

- 4 -

respect to each other by means of a rotation of the tool axis in the vertical can be replaced by a pivoting axis for the pivoting of the workpiece and the tool with respect to each other by means of a rotation of the workpiece axis in the horizontal, without the machine control parameters for instance of a radial infeed axis or a positionable rotating axis of a clamping head for the rotation of the workpiece in the workpiece holder being affected.

10

A precondition for this, however, is that a guiding axis that is standard for the entire control concept of all machine types coming into consideration can be specified. This condition is not met in the case of form grinding machines, as already stated above, if only because here - by contrast with machines which operate on the basis of a generating method - there is no generating movement that is always necessary and always able to serve as a guiding movement.

20

It is therefore the object of the present invention to provide a computer control system for a machine tool for producing workpieces having a helicoidal generated surface which allows the use of the respective machine control parameters for different machine types with different activatable axes in such a way that, when changing the machine to be activated, as few machine control parameters as possible - within the limits of geometrical possibility - have to be newly formed for activating the axes.

30

This is achieved by a multiaxis machine tool for producing workpieces with a helicoidal generated surface which has a workpiece holder for receiving a workpiece, a tool, activatable mechanical axes for machining the workpiece or for positioning the workpiece and the tool in relation to each other, and also an open-loop and/or closed-loop control device for activating axes, and which is characterized according

35

- 5 -

to the invention in that there is provided at least one virtual axis, which can be parameterized as a guiding axis for other axes and then serves only for the synchronization of these other axes.

5

In this way there is created an additional virtual axis, which itself does not activate any mechanical axis of the machine tool, but nevertheless is able to synchronize other axes. This can take place for instance by an only time-dependent polynomial, as follows

$$L_{virt}(t) = a_{virt,0} + a_{virt,1} \cdot t + a_{virt,2} \cdot t^2 + a_{virt,3} \cdot t^3$$

to be precise without the thereby determined value $L_{virt}(t)$ being used for the direct activation of a mechanical axis of the machine tool. Rather, this is included somewhat as follows

$$\begin{aligned} Achspos_1(L_{virt}(t)) &= a_{1,0} + a_{1,1} \cdot L_{virt}(t) + a_{1,2} \cdot L_{virt}(t)^2 + a_{1,3} \cdot L_{virt}(t)^3 \\ Achspos_2(L_{virt}(t)) &= a_{2,0} + a_{2,1} \cdot L_{virt}(t) + a_{2,2} \cdot L_{virt}(t)^2 + a_{2,3} \cdot L_{virt}(t)^3 \\ Achspos_3(L_{virt}(t)) &= a_{3,0} + a_{3,1} \cdot L_{virt}(t) + a_{3,2} \cdot L_{virt}(t)^2 + a_{3,3} \cdot L_{virt}(t)^3 \end{aligned}$$

with a synchronizing effect in the formation of the position values actually used for the activation of the mechanical axes, $Achspos_i$ (here 3 axes, that is to say $i = 1$ to 3).

The provision of such a virtual axis consequently allows the formation of the axial positions for the activation of the mechanical axes to be kept completely independent of any actual movement of each axis of the machine tool, whereby it is therefore possible when changing the machine to be activated - within the limits of geometrical possibility - newly to form only the machine control parameters which serve for the activation of axes that are additionally present in the new machine. On the other hand, the machine control parameters for axes that are to be encountered before and after the change of the machine are retained. In

- 6 -

the case of the aforementioned polynomials, this means for instance that the coefficients $a_{i,j}$ defining the path curve do not have to be newly formed for these axes.

5

With respect to the term used here, the virtual axis, it should be noted with regard to the use of this term in the prior art that this is standard terminology to the extent that it concerns an axis formed only in the
10 respective open-loop and/or closed-loop control device that is used, having no direct equivalent in the mechanical axes of the respective machine tool that are actually present. Differences from the prior art, for instance according to DE 42 91 619 C1, exist here
15 however to the extent that the virtual axis there (sometimes also referred to there as the soft axis) serves for the direct activation of actual mechanical axes, from which the virtual axis there is combined to a certain extent on a software basis. By contrast, the
20 virtual axis in the sense of the present invention here does not serve for any actual activation of mechanical axes, in particular not for any software synthesis of additional axes finding an equivalent in the mechanical reality of the machine tool to be activated, but only
25 for the synchronization of the activation of other axes.

Accordingly, the success according to the invention is also achieved by a method of activating a multiaxis
30 machine tool according to the invention, a virtual axis initially being parameterized as a guiding axis for other axes, and then, during the operation of the machine for machining the workpiece, the other axes merely being synchronized in their positioning with the
35 aid of this virtual guiding axis.

The multiaxis machine tool according to the invention preferably has at least five activatable mechanical axes for the positioning of the workpiece and the tool

- 7 -

in relation to each other, which permits the fabrication of rotationally symmetrical workpieces. If it is also desired to fabricate non-rotationally symmetrical workpieces, such as worms for instance, at least one additional axis is needed, provided for the pivoting of the workpiece and the grinding wheel with respect to each other in the horizontal, as still to be explained.

10 In a particularly preferred way, the multiaxis machine tool according to the present invention is characterized in that a grinding wheel is provided as the tool and, as mechanical axes, at least one

15 - positionable radial infeed axis, also designated by χ , is provided for the grinding wheel,

20 - a grinding slide which can be positioned horizontally and orthogonally in relation to the radial infeed axis, also designated by ζ , is provided for the positioning of the grinding wheel in the direction of displacement of the grinding slide,

25 - a positionable rotating axis, also designated by β , of a clamping head is provided for the rotation of the workpiece in the workpiece holder,

30 - a positionable pivoting axis, also designated by τ , is provided for the pivoting of the workpiece and the grinding wheel with respect to each other by means of a rotation of the grinding wheel axis or its parallel projection in the vertical plane, also designated by B, and

35 - a rotating axis, also designated by ω , is provided for the driving of the grinding wheel.

- 8 -

A positionable displacing axis, also designated by δ , for the monitoring of a displacing position of the grinding wheel along the grinding wheel axis, may also be provided as a mechanical axis.

5

The multiaxis machine tool according to the invention preferably also has a pivoting axis, also designated by σ , as a mechanical axis for the pivoting of the workpiece and the grinding wheel with respect to each other by means of a rotation of the grinding wheel axis or its parallel projection in the horizontal plane, also designated by A, which also allows the already mentioned fabrication of non-rotationally symmetrical workpieces.

15

As an alternative or in addition, this may also be achieved by a mechanical pivoting axis, also designated by , for the pivoting of the workpiece and the grinding wheel with respect to each other by means of a rotation of the workpiece axis or its parallel projection in the horizontal plane, also designated by A.

20

Furthermore, a displacing axis, also designated by , may be provided as a mechanical axis, serving for the vertical displacement of the workpiece and the grinding wheel with respect to each other.

25

The virtual axis itself is formed particularly preferably by the open-loop and/or closed-loop control device by means of a freely selectable function or relation, which is dependent in a particularly preferred way on time and in one embodiment of the present invention only on time. However, it is equally possible to make the virtual axis not dependent on time but on other events or values - possibly also external events or values - for instance positions reached by external machines, such as robots.

35

- 9 -

The embodiment of the present invention which forms the virtual axis by means of a freely selectable function or relation also has some special advantages:

5 During the grinding of workpieces having a helicoidal generated surface, such as for instance spur gears (of a helicoidal surface which sometimes also has a zero pitch of the thread, namely in the case of straight teeth), worms or rotors, it is frequently the case that
10 a single non-virtual guiding axis is often not adequate here for the entire workpiece fabrication process, since its guiding movement often becomes too minimal, in view of the limited numerical accuracy in reality, to allow activating functions (or relations) with
15 sufficient movement still to be calculated for the other axes in dependence on it. This becomes particularly clear for instance for the case where a grinding slide which can be positioned horizontally and orthogonally in relation to a radial infeed axis is
20 used for instance as a guiding axis for the positioning of the grinding wheel in the displacing direction of the grinding slide, and then an edge running orthogonally in relation to the workpiece rotating axis is to be milled on the workpiece, for instance as a
25 termination of a helicoidal generated surface, as occurs for instance in the case of workpieces which have a number of helicoidal surfaces that are separated from one another, for instance by round axial portions, or are at least different in terms of their geometry.
30 (In this connection it should be stated that workpieces with such partial or portional helicoidal surfaces are regarded as workpieces having a helicoidal generated surface in the sense of the present invention.) In the aforementioned case this is so because the movement of
35 the grinding slide comes completely to a standstill at the point of the perpendicular to the workpiece axis, and consequently can no longer serve as a guiding movement even without limited numerical resolution; the grinding slide is consequently unusable as a guiding

- 10 -

axis at this point. It is therefore necessary to carry out a change of the guiding axis at such points, which makes standardized machine control parameters for different machine models all the more
5 difficult, since then, in the case of a change of machine type, the difficulties already mentioned at the beginning of adaptation to the new machine sometimes occur for each guiding axis used. Moreover, it should be noted that such a change of axis also always leads
10 to undesired fabrication marks on the workpiece to be created at the point of the workpiece where the change is performed, on account of the associated discontinuity of the activation of the axes.

15 While the virtual axis according to the present invention can be formed by means of a freely selectable function or relation, this can take place in such a way that this virtual guiding axis meets requirements throughout the entire fabrication process without
20 changing the guiding axis, since in this way any dependence of the guiding axis caused by the fabrication process can be avoided on account of the complete freedom in its choice. In this way, the present invention is advantageously also suitable for
25 the case of operating only a single machine type that comes into consideration, since in this case no problems of the type described at the beginning in respect of changing the guiding axis occur any longer when the freely selectable virtual axis according to
30 the invention is used, and consequently no resultant defects occur any longer on the workpieces. If, on the other hand, the virtual guiding axis is chosen to be unchanging, process-related dependencies possibly cannot be ruled out, which may then lead to the already
35 mentioned numerically unfavourably conditioned systems.

As already explained in the example given above, a polynomial function comes into consideration in particular as the freely selectable function, but so

- 11 -

too does for example a circular relation. A freely selectable relation may also similarly be defined by a table of values.

- 5 The activation of the respective mechanical axis by the open-loop and/or closed-loop control device may also take place by means of a freely selectable function or relation, the respective mechanical axis preferably being dependent, as also already explained above, on
10 the value of a virtually formed axis acting as a guiding axis, in order in this way to achieve the synchronization of the axial positions with respect to one another.
- 15 Of course, the respective axis may in this case also be made dependent on the value of further parameters, for instance for the activation of the desired positional values. As already explained, a polynomial function, which is also dependent on the value of one of the
20 virtual axes and polynomial coefficients, may serve in this case as the freely selectable function.

However, similarly suitable as the freely selectable relation for the respective mechanical axis is a
25 circular relation, which is dependent on the value of one of the virtual axes and circle constants, preferably a circle radius and a centre point, given by a pair of coordinates, and also a direction of rotation.

30

The same applies to the activation of the respective mechanical axis, which takes place by the open-loop and/or closed-loop control device by means of a freely selectable relation which is given by a table of
35 coordinates, and similarly for all other functions and/or relations that appear to be suitable for achieving the desired workpiece geometry.

- 12 -

In the case of use of a relation formed by a table of coordinates, this is preferably formed by an X coordinate, a Y coordinate and a normal angle, preferably as viewed in end-on section.

5

In a further preferred embodiment according to the present invention, the multiaxis machine tool is characterized in that a memory is also provided, stored in which are machine control parameters which are
10 accessed by the open-loop and/or closed-loop control device, which permits flexible realization of the present invention by a computer control system.

This is so because a data structure which allows the
15 parameterization of the virtual axis as a guiding axis for other axes can be provided in this memory, it also being possible that here there is a data structure which also allows the parameterization of any mechanical axis as a guiding axis for other axes, for
20 instance to allow older machine control parameters that are not yet adjusted to the computer control system according to the invention to be used.

The definition of the function or relation for the
25 formation of the virtual axis and also the definition of the function or relation for the activation of the respective mechanical axis by the open-loop and/or closed-loop control device can also be flexibly stored in the memory.

30

In this case, data fields may serve for the identification of predefined types of function or types of relation, used for the definition of a function or relation of the respective mechanical axis. Such a
35 predefinition of frequently used types of function and/or relation makes it easier here for the definition to be stored in the memory. Preferably coming into consideration as types of function predefined in such a way are for instance a polynomial function, for

- 13 -

instance of the sixth degree, with polynomial coefficients as parameters, or else once again a circular relation with a circle radius and a centre point, given by a pair of coordinates, and a direction of rotation as parameters. Similarly, however, a table of coordinates with coordinates as parameters may be predefined as a type of relation, an X coordinate, a Y coordinate and a normal angle, preferably as viewed in end-on section, preferably being used in each case as coordinates.

In a further preferred embodiment of a multiaxis machine tool according to the present invention, in the memory in which the machine control parameters accessed by the open-loop and/or closed-loop control device are stored there is a data structure which is intended for receiving an identification of the workpiece flank being machined by the activation of the respective mechanical axis by the open-loop and/or closed-loop control device, preferably an identification for a flank on the right or on the left. This parameter is required by the machine in the case of non-symmetrically formed grinding wheels, such as for instance for the fabrication of worms, in order to move to the respective flank with the correct side of the tool. This control parameter also permits open-loop or closed-loop control of the force in a way corresponding to the respective flank.

In the memory in which machine control parameters accessed by the open-loop and/or closed-loop control device are stored there is also a data structure which combines at least one group of machine control parameters corresponding to a partial region of the workpiece, as a segment under a common segment identification, preferably a segment number, it being preferred that such a group of machine control parameters for which the same axis is parameterized as the guiding axis are always combined as a segment.

- 14 -

The structuring of the machine control parameters into segments makes it possible to replicate a segmentation of the workpiece that exists in reality also in the structuring of the machine control parameters, which improves their overall clarity and consequently also the possibility of their assignment to the first cuts made on workpieces.

10 The embodiments described above of a multiaxis machine tool according to the invention with a memory consequently serve for the replication in this memory of machine control parameters which initiate during the operation of the machine machine functions for
15 workpiece fabrication. However, this can take place not only by storage in the memory of the machine, but also by reading in a data carrier provided with corresponding machine control parameters, such as for instance a floppy disc, a CD or else a DVD, or else by
20 reading an electronic carrier signal with these machine control parameters into the multiaxis machine tool according to the invention, for instance via a data line, as preferably also used in a data network. Such a data carrier or such a data carrier signal is in this
25 case constructed in a way corresponding to the present invention for reading the data constructed according to the invention as described above into the multiaxis machine tool according to the invention for controlling the latter in a way corresponding to the present
30 invention.

In every case, such a data carrier or such an electronic carrier signal is parameterized according to the invention with machine control parameters for
35 reading into a multiaxis machine tool, the data carrier or the electronic carrier signal having on it at least one data structure which has a data field which allows the parameterization of the virtual axis as a guiding axis for other axes, and the data carrier or the

- 15 -

electronic carrier signal activating the machine tool during the reading-in or after the reading-in by means of this data structure on the basis of the method according to the invention stated above.

5

Also serving for carrying out the present invention is a method of generating machine control parameters for a multiaxis machine tool which is characterized according to the invention in that it generates a data carrier or
10 an electronic carrier signal with machine control parameters as described above. It goes without saying that this method may also be realized on a computer system with at least one data processing unit and at least one memory, usually for instance as a computer
15 program, it having the corresponding instructions set up for carrying out the method. Such a computer program may in this case take any form, but in particular also that of a computer program product on a computer-readable medium, such as for instance a floppy
20 disc, CD or DVD, it having computer program coding means, with which, after loading the computer program, a computer is in each case made by the program to carry out the method according to the invention. It may, however, also be for instance in the form of a computer
25 program product which has a computer program on an electronic carrier signal, with which, after loading the computer program, a computer is in each case made by the program to carry out the method according to the invention.

30

The different individual elements of the present invention described above, seen in their entirety, can provide a neutral data computer control system for a multiaxis machine tool for producing workpieces having
35 a helicoidal generated surface with

- a computer system according to the invention for generating machine control parameters for a multiaxis machine tool with at least one data

- 16 -

processing unit and at least one memory,
the data processing unit being set up in
programming terms in such a way that it generates
at least one data carrier or an electronic carrier
5 signal with machine control parameters according to
the present invention, or

- such a computer program or computer program
product,
- 10 - and at least one multiaxis machine tool according
to the invention.

Further details of such a system according to the
15 present invention can be taken from the exemplary
embodiments.

Exemplary embodiments of the present invention, which
are to be understood as non-restrictive, are discussed
20 below on the basis of the drawing, in which:

Figure 1 shows a neutral data computer control system
according to the invention for a multiaxis
machine tool for producing workpieces having
25 a helicoidal generated surface,

Figure 2 shows an abstract model of a multiaxis
machine tool according to the invention for
producing workpieces having a helicoidal
30 generated surface with diverse mechanical
axes, and

Figure 3 shows a workpiece having a helicoidal
generated surface for being produced on a
multiaxis machine tool according to the
35 invention.

Figure 1 shows a neutral data computer control system
according to the invention for a multiaxis machine tool

- 17 -

for producing workpieces having a helicoidal generated surface, to be precise

with

5

- a computer system 1 according to the invention for generating machine control parameters for a multiaxis machine tool 2, 2a with at least one data processing unit and at least one memory, the data processing unit being set up in programming terms in such a way that it generates here in a data network an electronic carrier signal 3 with machine control parameters according to the present invention,

15

- and a first multiaxis machine tool 2 according to the invention and a second such machine tool 2a.

In the present case, the situation is therefore such that the first machine 2 has (along with other axes) a mechanical pivoting axis σ for the pivoting of the workpiece and the grinding wheel with respect to each other by means of a rotation of the grinding wheel axis or its parallel projection in the horizontal plane A; a possibility which the second machine 2a does not have. However, the latter does have a pivoting axis γ for the pivoting of the workpiece and the grinding wheel with respect to each other by means of a rotation of the workpiece axis or its parallel projection in the horizontal plane A. In the present neutral data computer system, it is thus easily possible to use machine control parameters generated by the computer system 1 for the first machine 2 according to the invention also for the second machine tool 2a according to the invention if the generated machine control parameters make use of a virtual guiding axis according to the present invention. Both machines 2, 2a have a virtual guiding axis, so that, when there is a change of machine from the first machine 2 to the second

- 18 -

machine 2a, only the machine control parameters for the pivoting axis γ instead of the pivoting axis σ have to be formed. All the other machine control parameters, on the other hand, can be
5 retained, since they are coupled by the virtual guiding axis.

Figure 2 shows an abstract model (covering various actual configurational possibilities) of a multiaxis
10 machine tool according to the invention for producing workpieces having a helicoidal generated surface with diverse mechanical axes, to be precise with

- 15 - a positionable radial infeed axis χ for the grinding wheel,
- a grinding slide ξ which can be positioned horizontally and orthogonally in relation to the radial infeed axis, for the positioning of the
20 grinding wheel in the direction of displacement of the grinding slide,
- a positionable rotating axis β of a clamping head for the rotation of the workpiece in the workpiece
25 holder,
- a positionable pivoting axis τ for the pivoting of the workpiece and the grinding wheel with respect to each other by means of a rotation of the
30 grinding wheel axis or its parallel projection in the vertical plane B,
- a rotating axis ω for the driving of the grinding wheel,
- 35 - a positionable displacing axis δ for the monitoring of a displacing position of the grinding wheel along the grinding wheel axis,

- 19 -

5 - a pivoting axis σ for the pivoting of the workpiece and the grinding wheel with respect to each other by means of a rotation of the grinding wheel axis or its parallel projection in the horizontal plane A,

10 - a displacing axis η for the vertical displacement of the workpiece and the grinding wheel with respect to each other, and

15 - a pivoting axis γ for the pivoting of the workpiece and the grinding wheel with respect to each other by means of a rotation of the workpiece axis or its parallel projection in the horizontal plane A

for better illustration of the geometrical relationships taken as a reference.

20 Figure 3 shows a workpiece having a helicoidal generated surface for being produced on a multiaxis machine tool according to the invention, with 9 different segments. With reference to the abstract model illustrated in Figure 2, the machine control parameters are to be specified below in a way
25 corresponding to the present invention by way of example for the segment 8, a conical kneading element Seg. 8, the virtual guiding axis being designated here by κ :

Guiding axis: κ			X_{Start}	X_{End}	A	B	C	D	E	F	G
κ	[]	008=PB	0	1	0	1	0	0	0	0	0
η	[mm]	008=PB	0	1	0	0	0	0	0	0	0
γ	[rad]	008=PB	0	1	0	0	0	0	0	0	0
ω	[m/s]	008=PB	0	1	40.0	0	0	0	0	0	0
τ	[rad]	008=PB	0	1	0.00706	0.000027	0	0	0	0	0
δ	[mm]	008=PB	0	1	0.0	0	0	0	0	0	0
σ	[rad]	008=PB	0	1	0	0	0	0	0	0	0
ξ	[mm]	008=PB	0	1	0	0.3183	0	0	0	0	0
β	[rad]	008=PB	0	1	0	0.00395	0	0	0	0	0

- 20 -

χ	[mm]	008=PB	0	1	90.17	-0.0797	0	0	0	0	0
--------	------	--------	---	---	-------	---------	---	---	---	---	---

Table 1: Segment 008: 2nd conical kneading element
Process: roughing

To explain such a table (not all the options are used
above in Table 1), which reproduces an embodiment of
the functional data structures according to the present
invention:

Column 1: Designation of axis
Column 2: Unit
Column 3: Segment number = code letter for the
type of neutral data (to be precise C
for circle, P for polynomial [of the 6th
degree], K for coordinates [points] of a
table of coordinates) and code letter
for which flank (R for right flank; L
for left flank; B for both flanks)

Other columns: Table values with X_{Start} and X_{End} as range
limits and the values for parameters A,
B, C, D, E, F and G (in the case of a
polynomial), R, A, B, C (in the case of
a circle) and A, B, C (in the case of a
table of coordinates) with respect to
the relations and/or functions on the
basis of the following:

$$R = \sqrt{(x-A)^2 + (y-B)^2}$$

Circle [C as code letter]:

with the value in column R as radius, C as direction of
rotation, with -1 indicating the clockwise direction of
rotation (cw) and the value +1 indicating the
counterclockwise direction of rotation (ccw)



polynomial [P as code letter]: $Y = A + B \cdot x + C \cdot x^2 + D \cdot x^3 +$
 $E \cdot x^4 + F \cdot x^5 + G \cdot x^6$

- 21 -

coordinates (points) of a table of coordinates
[K as code letter]:

value in column A: X coordinate, value in column B: Y
5 coordinate, value in column C: normal angle, always
stored in end-on section

Examples:



- 22 -

Patent claims

1. A multiaxis tooling machine (2) for producing workpieces having a helicoidal generated surface, the tooling machine comprising:
- 5
- a) a workpiece holder for receiving a workpiece,
 - b) a tool,
 - c) a plurality of activatable mechanical axes,
 - d) a control device for activating the mechanical axes,

10

 - e) wherein the control device is configured to:
 - i. use a time dependent relation to generate at least one virtual axis;
 - ii. parameterize the at least one virtual axis as a guiding axis for at least one of the activatable mechanical axes;

15

 - iii. use a virtual axis dependent relation to activate at least one of the mechanical axes;
- 20
- A. wherein the virtual axis dependent relation is dependent on the at least one virtual axis, and
 - B. wherein the virtual axis dependent relation is further dependent on at least one additional parameter.

25
2. The tooling machine (2) of Claim 1, wherein the control device is of a type selected from the group comprising: (i) an open-loop device, (ii) a closed-loop device, and (iii) an open-loop and closed-loop device.
- 30

- 23 -

3. The tooling machine (2) of Claim 1 or 2, wherein the time dependent relation corresponds to a polynomial function.
- 5 4. The tooling machine (2) of Claim 1 or 2, wherein the time dependent relation corresponds to a circular relation.
5. The tooling machine (2) of Claim 1 or 2, wherein the time dependent relation corresponds to a table of values.
- 10 6. The tooling machine (2) of any of Claims 1 to 5, wherein the virtual axis dependent relation corresponds to a polynomial function, and wherein the polynomial function depends on at least one polynomial coefficient.
- 15 7. The tooling machine (2) of any of Claims 1 to 5, wherein the virtual axis dependent relation corresponds to a circular relation, and wherein the circular relation depends on circle constants comprising: (i) a circle radius, (ii)
20 a centre point, and (iii) a direction of rotation.
8. The tooling machine (2) of any of Claims 1 to 5, wherein the virtual axis dependent relation corresponds to a table of coordinates.
- 25 9. The tooling machine (2) of Claim 8, wherein the table of coordinates comprises: (i) an X coordinate, (ii) a Y coordinate, and (iii) a normal angle.
- 30 10. The tooling machine (2) of Claim 9, wherein the coordinates correspond to an end-on section view.

- 24 -

11. The tooling machine (2) of any of Claims 1 to 10, wherein the mechanical axes are configured for machining the workpiece.
- 5 12. The tooling machine (2) of any of Claims 1 to 11, wherein the mechanical axes are configured for positioning the workpiece and the tool in relation to each other.
- 10 13. The tooling machine (2) of any of Claims 1 to 12, wherein the plurality of activatable axes comprise at least five of the mechanical axes.
14. The tooling machine (2) of any of Claims 1 to 12, wherein the tool comprises a grinding wheel, and wherein the plurality of activatable mechanical axes comprises:
- 15 a) at least one positionable radial infeed axis (χ) for the grinding wheel;
- 20 b) at least one grinding slide axis (ζ) that can be positioned horizontally and orthogonally relative to the radial infeed axis for positioning the grinding wheel in the direction of displacement of the grinding slide;
- 25 c) at least one positionable rotating axis (β) of a clamping head for rotating the workpiece in the workpiece holder;
- 30 d) at least one positionable pivoting axis (τ) for pivoting the workpiece and the grinding wheel relative to each other by rotating the grinding wheel axis or its parallel projection in the vertical plane (B); and
- e) at least one rotating axis (ω) for driving the grinding wheel.

- 25 -

15. The tooling machine (2) of Claim 14, wherein the plurality of activatable mechanical axes also comprises at least one positionable displacing axis (δ) for displacing the grinding wheel along the grinding wheel axis.
- 5
16. The tooling machine (2) of Claim 14 or 15, wherein the plurality of activatable mechanical axes also comprises at least one pivoting axis (σ) for pivoting the workpiece and the grinding wheel relative to each other by rotating the grinding wheel axis or its parallel projection in the horizontal plane (A).
- 10
17. The tooling machine (2) of any of Claims 14 to 16, wherein the plurality of activatable mechanical axes also comprises at least one displacing axis (η) for vertically displacing the workpiece and the grinding wheel relative to each other.
- 15
18. The tooling machine (2) of any of Claims 14 to 17, wherein the plurality of activatable mechanical axes also comprises at least one pivoting axis (γ) for pivoting the workpiece and the grinding wheel relative to each other by rotating the workpiece axis or its parallel projection in the horizontal plane (A).
- 20
- 25
19. The tooling machine (2) of any of Claims 1 to 18, comprising a memory that is operationally coupled to the control device, and wherein the memory stores machine control parameters.
20. The tooling machine (2) of Claim 19, wherein the tooling machine is configured to read machine control parameters carried on a carrier.
- 30
21. The tooling machine (2) of Claim 20, wherein the tooling machine is configured to store the read machine control parameters in the memory.
- 35

- 26 -

22. The tooling machine (2) of Claim 20 or 21, wherein the carrier is of a type selected from the group comprising: (i) a data carrier, and (ii) an electronic carrier signal.
- 5 23. The tooling machine (2) of any of Claims 19 to 22, wherein the memory stores at least one data structure configured to allow for parameterization of the at least one virtual axis.
- 10 24. The tooling machine (2) of any of Claims 19 to 23, wherein the memory stores at least one data structure configured to allow for parameterization of at least one of the mechanical axes as a guiding axis.
- 15 25. The tooling machine (2) of any of Claims 19 to 24, wherein the memory stores at least one data structure configured to receive a definition of the time dependent relation.
- 20 26. The tooling machine (2) of any of Claims 19 to 25, wherein the memory stores at least one data structure configured to receive a definition of the virtual axis dependent relation.
27. The tooling machine (2) of Claim 26, further comprising:
- 25 a) at least one predefined type of relation,
- b) wherein the data structure comprises at least one data field for identifying the at least one predefined type of relation, and
- 30 c) wherein the at least one predefined type of relation defines a relation of at least one of the mechanical axes.
28. The tooling machine (2) of Claim 27, wherein at least one of the at least one predefined type of

- 27 -

relation corresponds to a polynomial function, and wherein the polynomial function comprises polynomial coefficients as parameters.

- 5 29. The tooling machine (2) of Claim 28, wherein the polynomial function is of the sixth degree.
- 10 30. The tooling machine (2) of any of Claims 27 to 29, wherein at least one of the at least one predefined type of relation corresponds to a circular relation, and wherein the circular relation depends on circle constants comprising: (i) a circle radius, (ii) a centre point, and (iii) a direction of rotation.
- 15 31. The tooling machine (2) of any of Claims 27 to 30, wherein at least one of the at least one predefined type of relation corresponds to a table of coordinates, wherein the table of coordinates comprises coordinates as parameters.
- 20 32. The tooling machine (2) of Claim 31, wherein the coordinates comprise: (i) an X coordinate, (ii) a Y coordinate, and (iii) a normal angle.
33. The tooling machine (2) of Claim 32, wherein the coordinates correspond to an end-on section view.
- 25 34. The tooling machine (2) of any of Claims 19 to 33, wherein the memory stores a data structure configured to receive at least one parameter identifying at least one workpiece flank to be machined by the tooling machine (2).
- 30 35. The tooling machine (2) of Claim 34, wherein the at least one parameter identifies whether the at least one workpiece flank is of a type selected from the group comprising: (i) a right workpiece flank, (ii) a left workpiece flank, and (iii) a

- 28 -

right workpiece flank and a left workpiece flank.

- 5 36. The tooling machine (2) of any of Claims 19 to 35, wherein the memory stores a data structure that combines at least one group of machine control parameters as a segment under a common segment identification, and wherein the group of machine control parameters correspond to a partial region of the workpiece.
- 10 37. The tooling machine (2) of Claim 36, wherein the common segment identification is a segment number.
- 15 38. The tooling machine (2) of Claim 36 or 37, wherein for at least one segment all of the machine control parameters correspond to the same guiding axis.
39. A method of activating the tooling machine (2) of any one of Claims 1 to 22,
- the method comprising the steps of:
- 20 a) providing a time dependent relation;
- b) generating at least one virtual axis corresponding to the time dependent relation;
- 25 c) parameterizing the at least one virtual axis as a guiding axis for at least one of the mechanical axes;
- d) providing a virtual axis dependent relation corresponding to the activation of at least one of the mechanical axes;
- 30 A. wherein the virtual axis dependent relation is dependent on the at least one virtual axis, and

- 29 -

B. wherein the virtual axis dependent relation is further dependent on at least one additional parameter.

- 5 40. The method of Claim 39, further comprising the step of generating a carrier comprising machine control parameters.
41. The method of Claim 40, wherein the carrier comprises:
- 10 a) at least one data structure having a data field that allows for the parameterization of a virtual axis as a guiding axis;
- b) at least one data structure configured to receive a definition of a time dependent relation; and
- 15 c) at least one data structure configured to receive a definition of a virtual axis dependent relation.
- 20 42. The method of Claim 40, wherein the carrier comprises at least one data structure comprising at least one data field configured to receive the identification of at least one predefined type of relation.
- 25 43. The method of Claim 42, wherein the predefined type of relation corresponds to a type selected from the group comprising: (i) a polynomial function, (ii) a circular relation, and (iii) a table of coordinates.
- 30 44. The method of Claim 40, wherein the carrier comprises at least one data structure configured to receive at least one parameter identifying at least one workpiece flank to be machined by the tooling machine.


- 30 -

45. The method of Claim 44, wherein the at least one parameter identifies whether the at least one workpiece flank is of a type selected from the group comprising: (i) a right workpiece flank,
5 (ii) a left workpiece flank, and (iii) a right workpiece flank and a left workpiece flank.
46. The method of Claim 40, wherein the carrier comprises at least one data structure configured to combine at least one group of machine control
10 parameters as a segment under a common segment identification, and wherein the machine control parameters correspond to a partial region of the workpiece.
47. The method of Claim 46, wherein the common
15 segment identification is a segment number.
48. The method of Claim 46 or 47, further comprising the step of combining into a segment at least one group of machine control parameters that correspond to the same guiding axis.
- 20 49. The method of any of Claims 40, wherein the carrier comprises at least one data structure configured to allow the parameterization of at least one of the mechanical axes as a guiding axis.
- 25 50. A computer system (1) comprising:
- a) at least one data processing unit;
 - b) at least one memory storing a computer program, and
 - c) wherein the computer program is configured
30 to make the at least one data processing unit carry out the method of any of Claims 40 to 49.

- 31 -


51. A computer readable medium comprising a computer
program for execution on a computer and
configured to cause the computer to carry out
the method of any of Claims 40 to 49 when the
program is executed.
- 5

FIG. 1



2/3

FIG. 2



2

3/3

FIG. 3

