



US 20020094161A1

(19) **United States**

(12) **Patent Application Publication**

Maitland

(10) **Pub. No.: US 2002/0094161 A1**

(43) **Pub. Date: Jul. 18, 2002**

(54) **LIGHT DIFFUSING FIBER OPTIC CHAMBER**

(22) Filed: **Jan. 16, 2001**

Publication Classification

(75) Inventor: **Duncan J. Maitland**, Lafayette, CA (US)

(51) **Int. Cl.⁷ G02B 6/26**

(52) **U.S. Cl. 385/31; 385/901**

Correspondence Address:

Eddie E. Scott

Patent Attorney

Lawrence Livermore National Laboratory

P.O. Box 808 - L-703


Livermore, CA 94551 (US)

(57) **ABSTRACT**

A light diffusion system for transmitting light to a target area. The light is transmitted in a direction from a proximal end to a distal end by an optical fiber. A diffusing chamber is operatively connected to the optical fiber for transmitting the light from the proximal end to the distal end and transmitting said light to said target area. A plug is operatively connected to the diffusing chamber for increasing the light that is transmitted to the target area.

(73) Assignee: **The Regents of the University of California**

(21) Appl. No.: **09/761,024**






FIG. 1




FIG. 2




FIG.3




FIG.4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16

LIGHT DIFFUSING FIBER OPTIC CHAMBER

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] Some subject matter is disclosed and claimed in the following commonly owned, copending, U.S. Patent Application, "SHAPE MEMORY POLYMER ACTUATOR AND CATHETER," by Duncan J. Maitland, Abraham P. Lee, Daniel L. Schumann, Dennis L. Matthews, Derek Decker, and Charles A. Jungreis, patent application number _____, filed _____, 2001, which is hereby incorporated by reference in its entirety.

[0002] The United States Government has rights in this invention pursuant to Contract No. W-7405-ENG-48 between the United States Department of Energy and the University of California for the operation of Lawrence Livermore National Laboratory.

BACKGROUND OF THE INVENTION

[0003] 1. Field of the Invention

[0004] The present invention relates to light diffusing systems.

[0005] 2. State of Technology

[0006] U.S. Pat. No. 5,754,717 for a light-diffusing device for an optical fiber, methods of producing and using same, and apparatus for diffusing light from an optical fiber, by Victor C. Esch, patented May 19, 1998, provides the following description: "A diffusing tip is provided for diffusing light from a light-emitting end of an optical fiber in a radial distribution pattern relative to the axis of the tip and along a length of the tip. The tip has an inner core and an outer covering which define a light guide. The outer covering is modified on its interior surface adjacent to the core such that light transmitted down the light guide is removed from the core upon encountering a surface modification on the interior surface. The light so removed is transmitted to the outer surface along the length of the tip, where it can be used to irradiate a selected object or material. The diffusing tip preferably provides light in a substantially uniform intensity distribution for the substantially uniform irradiation of a selected object or material."

[0007] U.S. Pat. No. 6,102,917 for a shape memory polymer (SMP) gripper with a release sensing system, by Maitland et al, patented Aug. 15, 2000, provides the following description: "A system for releasing a target material, such as an embolic coil from an SMP located at the end of a catheter utilizing an optical arrangement for releasing the material. The system includes a laser, laser driver, display panel, photodetector, fiber optics coupler, fiber optics and connectors, a catheter, and an SMP-based gripper, and includes a release sensing and feedback arrangement. The SMP-based gripper is heated via laser light through an optic fiber causing the gripper to release a target material (e.g., embolic coil for therapeutic treatment of aneurysms). Various embodiments are provided for coupling the laser light into the SMP, which includes specific positioning of the coils, removal of the fiber cladding adjacent the coil, a metal coating on the SMP, doping the SMP with a gradient absorbing dye, tapering the fiber optic end, coating the SMP with low refractive index material, and locating an insert between the fiber optic and the coil."

[0008] U.S. Pat. No. 5,207,669 for an optical fiber diffusion tip for uniform illumination, by Baker et al, patented May 4, 1993, provides the following description: "A diffusion tip coupled to the end of an optical fiber for directing laser energy outwardly in a cylindrical or other desired radiation pattern. The diffusion tip includes a core, a cladding around the core and a jacket around the cladding. The cladding has an index of refraction that is lower than that of the core and has a thickness selected to transmit a portion of the laser radiation that is carried through the optical fiber so that laser radiation penetrates through the cladding and the jacket over the length of the diffusion tip. The thickness of the cladding is about the same as or slightly less than the penetration depth of the evanescent field in the cladding. The cladding can be tapered along the length of the diffusion tip to provide a uniform radiation pattern. The diffusion tip is particularly useful in a laser balloon catheter utilized in coronary angioplasty."

[0009] U.S. Pat. No. 5,337,381 for a fiber optic cylindrical diffuser, by Biswas et al, patented Aug. 9, 1994, provides the following description: "A fiber optic, cylindrical, light diffuser for medical use includes an unclad distal fiber end where the exposed core end has a conical shape. The core end is enclosed by a sleeve which contacts the clad portion of the fiber only and defines a closed chamber with the distal end of the fiber. The chamber is filled with light diffusing material. The diffuser exhibits highly uniform output light distribution and is capable of carrying relatively high power densities safely."

SUMMARY OF THE INVENTION

[0010] The present invention provides a light diffusion system for transmitting light to a target area. The light is transmitted in a direction from a proximal end to a distal end by an optical fiber. A diffusing chamber is operatively connected to the optical fiber for transmitting the light from the proximal end to the distal end and transmitting said light to said target area. A plug is operatively connected to the diffusing chamber for increasing the light that is transmitted to the target area. Additional aspects, advantages, and features of the invention are set forth in part in the following description. Various aspects, advantages, and features of the invention will become apparent to those skilled in the art upon examination of the description and by practice of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] The accompanying drawings, which are incorporated into and form a part of the disclosure, illustrate embodiments of the invention, and, together with the description, serve to explain the principles of the invention.

[0012] FIG. 1 illustrates a basic light diffusion system constructed in accordance with the present invention.

[0013] FIG. 2 illustrates another version of a basic light diffusion system constructed in accordance with the present invention.

[0014] FIG. 3 illustrates basic modes and systems of operating a light diffusion system constructed in accordance with the present invention.

[0015] FIG. 4 illustrates the basic system multiplexed with a reflection based sensor.

[0016] FIG. 5 illustrates an embodiment wherein the proximal end of the plug is reflective (specular or diffusive) such that the diffusive source is increased.

[0017] FIG. 6 illustrates an embodiment wherein the proximal end of the plug is convex in shape.

[0018] FIG. 7 illustrates an embodiment wherein the proximal end of the plug is concave in shape.

[0019] FIG. 8 illustrates an embodiment wherein the distal surface of the plug may be modified for transparent or near-transparent plugs.

[0020] FIG. 9 illustrates an embodiment wherein the proximal surface of the transparent or near transparent plug may be modified in shape so as to enhance the transmission of light from the optical fiber to the plug or its distal surface and back into the optical fiber.

[0021] FIG. 10 illustrates an embodiment wherein the plug is an optical fiber.

[0022] FIG. 11 illustrates an embodiment with modifications to the external tube that encases the diffusion device.

[0023] FIG. 12 illustrates an embodiment wherein the inner and/or outer surface of the tube are diffusely scattering.

[0024] FIG. 13 illustrates an embodiment wherein the tube has an embedded or coated transducer on or about its external surface.

[0025] FIG. 14 illustrates an embodiment wherein the tubing is doped with absorbing, transducing or scattering materials.

[0026] FIG. 15 illustrates an embodiment wherein a full angle (360°) radial radiation pattern is included.

[0027] FIG. 16 illustrates an embodiment wherein the total angle and directions of the diffuse source may be controlled.

DETAILED DESCRIPTION OF THE INVENTION

[0028] Referring to the drawings, and in particular to FIG. 1, an embodiment of a light diffusion system constructed in accordance with the present invention is illustrated. Fiber optics provide the opportunity to guide light to a desired target and distribute the light at or in the target. When the target, as a whole or in part, circumferentially surrounds the fiber, methods of extracting the light from the fiber and distributing the light at or on the target are required. These systems are often classified as light diffusing devices. The present invention also provides general sensing locations and methods that enhance the performance of a diffusing chamber.

[0029] The present invention provides a light diffusing device and method, sensing systems that are complementary to the diffusing device, and optical systems that employ the diffusing device and/or sensors. In addition to the primary objective of bringing light to a target, optical systems provide the opportunity to either detect, via a transducer, the status of environmental parameter or parameters and/or detect how the exposure of light to the target changes the target or environment.

[0030] The light diffusion system of the present invention can be used with light activated actuator and catheter systems for removing blockages from luminal structures. The systems are similar to a guide wire that is commonly pushed through a blockage such as a blood clot, fed through the clot, and then actuated to open like an umbrella. The catheter uses an expanding opto-mechanical actuator system. The expanded opto-mechanical device is retracted and the blockage is removed. The blockage could be a blood clot, plaque, other emboli, or other blockage. The system uses energy in the form of light guided by an optical fiber to a light diffusing device that radiates the light into the shape memory polymer (SMP). Actuation is achieved by converting optical energy into thermal energy that allows the stored energy in the SMP to be released. The optical energy is absorbed by the SMP and converted into thermal energy that heats the SMP above its transition temperature and the SMP moves to its primary shape, resulting in opto-mechanical actuation. The SMP actuator is drawn backward resulting in the removal of the blockage from the vessel.

[0031] Light diffusion systems have other medical uses. "Photodynamic Therapy" (PDT) is a term for a common method for the treatment of cancer and in humans and in animals. In one class of diagnosis and treatment with photosensitizing drugs, tumors are detected and treated by irradiating the tumors with light after the drug accumulates in the tumor. The drugs are photosensitizing and some of the drugs in this class are derivatives of hemoglobin. The photosensitive characteristic of tumor-selective porphyrin compounds also make them useful in the treatment of tumors.

[0032] Referring again to FIG. 1 of the drawings, an embodiment of a light diffusion system constructed in accordance with the present invention is shown. The system is generally designated by the reference numeral 10. The optical fiber 11 is typically sheathed in a buffer jacket 12. The figure shows an optical fiber 11 made of glass or plastic, a buffer jacket 12 made of polyimide, silicone, acrylate, or polymers, a transparent tubing 13 made of Teflon, silicone, polymer, or other material, a diffusing chamber 19 made of a transparent material, air, plastic, glass, or diffusing material with embedded scatterers, and an end plug 14 made of plastic, glass, or metal. Typical dimensions for these components are fiber diameter 25-2000 μm , buffer jacket thickness 5-500 μm , tubing thickness 1-500 μm , tubing diameter generally the same as the fiber but it may be necked down to a smaller diameter, chamber length 0-5000 μm for microscopic applications and 0.1-10 cm for macroscopic devices. The distal end 15 of the fiber 11 delivers light to the diffusing chamber 19.

[0033] The light source comes from the proximal end 16 and is directed toward the distal end 15. The configuration takes advantage of a standard fiber terminating technique of polishing the buffer jacket flush or near flush with the fiber end. An optical source provides light energy 17 through the optical fiber 11. The light energy provides the diffuse light source 18.

[0034] The optical source can be an optical source such as that as described in U.S. Pat. No. 6,102,917, by Maitland et al, patented Aug. 15, 2000, as follows: "The catheter section, extension section, and control unit are interconnected by optic fiber connectors. Control unit includes a laser, laser

control or driving electronics and display panel assembly generally indicated, and connected as indicated to laser. Laser is connected by optic fibers via an optic fiber connector to a fiber optic coupler, such as a conventional 90/10 optical coupler, which is connected via an optic fiber to optic fiber connector. Coupler, wherein 90 percent of the light passes through and 10 percent is Coupler, wherein 90 percent of the light passes through and 10 percent is bypassed, is also connected by an optic fiber to a sensing photodetector, which is connected to the display panel section of assembly as indicated. Coupler is also connected by an optic fiber to a source photodetector, which is connected to the driving electronics or control section of assembly, as indicated. Laser light (pulsed or continuous) from laser is transmitted, as indicated by pulses and arrows, through optic fiber, connector, optic fiber, coupler, optic fiber, connector, an optic fiber in extension section, connector, and an optic fiber in catheter section onto an end section of SMP microgripper, which retains the coil, causing heating of the material of microgripper located around the coil" The disclosure of U.S. Pat. No. 6,102,917 is incorporated herein by reference. Also, some subject matter is disclosed and claimed in the following commonly owned, copending, U.S. patent application, "SHAPE MEMORY POLYMER ACTUATOR AND CATHETER," by Duncan J. Maitland, Abraham P. Lee, Daniel L. Schumann, Dennis L. Matthews, Derek Decker, and Charles A. Jungreis, patent application Ser. No. _____, filed _____, 2001, incorporated herein by reference.

[0035] FIG. 2 illustrates another version of the basic diffusing chamber system of the present invention. This version of the basic diffusing chamber system is generally designated by the reference numeral 20. A fiber core 21, stripped of its cladding 22, and coated with a mechanically roughened polymer 30, such as $n_{\text{polymer}} > n_{\text{core}}$ is shown. The proximal end of the plug 27, a piece of fiber optic glass, is a bright surface.

[0036] The optical fiber 21 is typically sheathed in a buffer jacket 22. The figure shows an optical fiber 21 made of glass or plastic, a buffer jacket 22 made of polyimide, silicone, acrylate, or polymers, a transparent tubing 24 made of Teflon, silicone, polymer, or other material, a diffusing chamber 23 made of a scatterers, and an end plug 25 made of plastic, glass, or metal. Typical dimensions for these components are fiber diameter 25-2000 μm , buffer jacket thickness 5-500 μm , tubing thickness 1-500 μm , tubing diameter generally the same as the fiber but it may be necked down to a smaller diameter, chamber length 0-5000 μm for microscopic applications and 0.1-10 cm for macroscopic devices. The distal end 26 of the fiber 21 delivers light to the diffusing chamber 23.

[0037] The light source comes from the proximal end 27 and is directed toward the distal end 26. The configuration takes advantage of a standard fiber terminating technique of polishing the buffer jacket flush or near flush with the fiber end. An optical source provides light energy 28 through the optical fiber 21. The light energy provides the diffuse light source 29.

[0038] The optical source can be an optical source such as that as described in U.S. Pat. No. 6,102,917, by Maitland et al, patented Aug. 15, 2000, as follows: "The catheter section, extension section, and control unit are interconnected by

optic fiber connectors. Control unit includes a laser, laser control or driving electronics and display panel assembly generally indicated, and connected as indicated to laser. Laser is connected by optic fibers via an optic fiber connector to a fiber optic coupler, such as a conventional 90/10 optical coupler, which is connected via an optic fiber to optic fiber connector. Coupler, wherein 90 percent of the light passes through and 10 percent is bypassed, is also connected by an optic fiber to a sensing photodetector, which is connected to the display panel section of assembly as indicated. Coupler is also connected by an optic fiber to a source photodetector, which is connected to the driving electronics or control section of assembly, as indicated. Laser light (pulsed or continuous) from laser is transmitted, as indicated by pulses and arrows, through optic fiber, connector, optic fiber, coupler, optic fiber, connector, an optic fiber in extension section, connector, indicated by pulses and arrows, through optic fiber, connector, optic fiber, coupler, optic fiber, connector, an optic fiber in extension section, connector, and an optic fiber in catheter section onto an end section of SMP microgripper, which retains the coil, causing heating of the material of microgripper located around the coil" The disclosure of U.S. Pat. No. 6,102,917 is incorporated herein by reference.

[0039] Referring now to FIGS. 3, and 4, modes and systems of operating the light diffusing device are illustrated. FIG. 3 illustrates the basic operation of a light source coupled into an optical fiber, delivered to a light to a diffusion chamber, and delivered to the desired target by the light diffusion chamber and an end plug. A sensor operatively connected to the distal end of the optical fiber may be used to transmit information from the target area.

[0040] As shown by FIG. 3 light is radiated from the light source 31. The light source 31 provides light energy through the optical fiber 15. The light source 31 can be any one of various systems. For example, the light source 31 can as described in U.S. Pat. No. 6,102,917, by Maitland et al, patented Aug. 15, 2000. The light source can include a laser and laser control and driving electronics. The light is transmitted into the optical fiber 32. The optical fiber 32 is typically sheathed in a buffer jacket with additional material layers. The optical fiber 32 can be multimode with typical core dimensions between 50-1000 μm . The distal end of the optical fiber 32 delivers light to a diffusing chamber 33. The diffusing chamber 33 distributes the light evenly around the circumference of the chamber and along the chamber length. The light can be used for heating or otherwise treating a target. The distal end of the chamber 33 is terminated with a reflective plug that maximizes the amount of light released from the chamber 33. Typical lengths of the diffusing chamber are 100-5000 μm . A sensor operatively connected to the distal end of the optical fiber may be used to transmit information from the target area.

[0041] Referring now to FIG. 4, the basic system, previously described, is multiplexed with a reflection based sensor. In this case the light source includes a laser 44. A light diffusing device/sensor 41 is operatively connected to the distal end of the optical fiber and can be used to transmit information from the target area. The source power is monitored, via the fiber coupler (shown as 90/10 coupler but it could be any fiber or open air coupling system), by an optional photodetector. The inverted pulses show the reflected signal that will transmit the transduced signal from

the sensor in the diffusing device. The system, generally indicated at **40**, comprises a light diffusing device with sensor section **41** and an optic fiber **42**. Control unit **43** includes a laser **44**, laser control or driving electronics and display panel assembly generally indicated at **45**, and connected as indicated to laser **44**. Laser **44** is connected by optic fibers **46** and **47** via an optic fiber connector **48** to a fiber optic coupler **49**, such as a conventional 90/10 optical coupler, which is connected via an optic fiber **50** to optic fiber connector **51**. Coupler **49**, wherein 90 percent of the light passes through and 10 percent is bypassed, is also connected by an optic fiber **52** to a sensing photodetector **53**, which is connected to the display panel section of assembly **45**. Coupler **49** is also connected by an optic fiber **54** to a source photodetector **55**, which is connected to the driving electronics or control section of assembly **45**. Laser light (pulsed or continuous) from laser **44** is transmitted, as indicated by pulses and arrows, through optic fiber **46**, connector **48**, optic fiber **47**, coupler **49**, optic fiber **50**, connector **51**, an optic fiber **42** onto an diffusing device/sensor **41**.

[0042] A test was conducted wherein the light diffusing system of the present invention was compared to a diffusing device that requires the fiber cladding to be removed. The diffusing system of the present invention was clearly brighter. In this test two exercises in creating diffuse light with an optical fiber were compared on the same brightness scale. In the first exercise a fiber core, stripped of its cladding, and coated with a mechanically roughened polymer ($n_{\text{polymer}} > n_{\text{core}}$) was tested. The second exercise the diffusing system of the present invention was tested. The distal end of the fiber optic could not be seen. The proximal end of the plug, a piece of fiber optic glass, was the bright surface to the right of the image. The diffusing chamber was filled with air. The tube was the original plastic buffer jacket that was originally stripped. The results of the test were that the diffusing system of the present invention was brighter.

[0043] Additional enhancements include modifications to the diffusion chamber. The diffusion chamber can be any material with a lower refractive index than the tubing. The material in the diffusing chamber is preferably transparent or scattering in nature. Air, plastics and glass are likely materials in the diffusing chamber. Additionally, instead of the inner surface of the tubing being modified with reflective materials, etched or abraded, transducers or absorbing materials, the outer surface of the diffusing chamber material, if not air, may likewise be modified. The present invention provides a system that is easy to manufacture. The fiber, tubing, and plug materials are off-the-shelf components. Their modification by etching, coating and attaching transducers lend themselves to common manufacturing techniques.

[0044] Other embodiments of the basic system describe above, are shown in FIGS. 5, 6, 7, 8, 9, and 10. In FIG. 5 the system is generally designated by the reference numeral **60**. The optical fiber **61** is typically sheathed in a buffer jacket **62**. The figure shows an optical fiber **61** made of glass or plastic, a buffer jacket **62** made of polyimide, silicone, acrylate, or polymers, a transparent tubing **63** made of Teflon, silicone, polymer, or other material, a diffusing chamber **64** made of a transparent material, air, plastic, glass, or diffusing material with embedded scatterers, and an

end plug **65** made of plastic, glass, or metal. The distal end **67** of the optical fiber **61** delivers light to the diffusing chamber **64**.

[0045] The light from the light source comes from the proximal end **66** and is directed toward the distal end **67**. The configuration takes advantage of a fiber terminating technique of polishing the buffer jacket flush or near flush with the fiber end. An optical source provides light energy **68** and **68A** through the optical fiber **61**. The light energy provides the diffuse light source. The optical source can be an optical source such as that as described in U.S. Pat. No. 6,102,917, by Maitland et al, patented Aug. 15, 2000, incorporated herein by reference. The proximal end **69** of the plug **65** is reflective (specular or diffusive) such that the diffusive source is increased.

[0046] In FIG. 6 the system is generally designated by the reference numeral **70**. The optical fiber **71** is typically sheathed in a buffer jacket **72**. The figure shows an optical fiber **71** made of glass or plastic, a buffer jacket **72** made of polyimide, silicone, acrylate, or polymers, a transparent tubing **73** made of Teflon, silicone, polymer, or other material, a diffusing chamber **74** made of a transparent material, air, plastic, glass, or diffusing material with embedded scatterers, and an end plug **75** made of plastic, glass, or metal. The distal end **77** of the fiber **71** delivers light to the diffusing chamber **74**.

[0047] The light from the light source comes from the proximal end **76** and is directed toward the distal end **77**. The configuration takes advantage of a fiber terminating technique of polishing the buffer jacket flush or near flush with the fiber end. An optical source provides light energy **78** and **78A** through the optical fiber **71**. The light energy provides the diffuse light source. The optical source can be an optical source such as that as described in U.S. Pat. No. 6,102,917, by Maitland et al, patented Aug. 15, 2000, incorporated herein by reference. The proximal end **79** of the plug **75** is convex in shape. This includes all surfaces of revolution associated with cuts through a cone or multi-faceted flat surfaces that approximate a smooth surface of curvature. The surface may or may not be reflective. The convex shape acts to enhance the diffusive light source.

[0048] In FIG. 7 the system is generally designated by the reference numeral **80**. The optical fiber **81** is typically sheathed in a buffer jacket **82**. The figure shows an optical fiber **81** made of glass or plastic, a buffer jacket **82** made of polyimide, silicone, acrylate, or polymers, a transparent tubing **83** made of Teflon, silicone, polymer, or other material, a diffusing chamber **84** made of a transparent material, air, plastic, glass, or diffusing material with embedded scatterers, and an end plug **85** made of plastic, glass, or metal. The distal end of the fiber delivers light to the diffusing chamber.

[0049] The light from light source comes from the proximal end **86** and is directed toward the distal end **87**. The configuration takes advantage of a fiber terminating technique of polishing the buffer jacket flush or near flush with the fiber end. An optical source provides light energy **88** and **88A** through the optical fiber **81**. The light energy provides the diffuse light source. The optical source can be an optical source such as that as described in U.S. Pat. No. 6,102,917, by Maitland et al, patented Aug. 15, 2000, incorporated herein by reference. The proximal end **89** of the plug **88** is

concave is shape. This includes all surfaces of revolution associated with cuts through a cone or multi-faceted flat surfaces that approximate the a smooth surface of curvature. The surface may or may not be reflective. The concave shape **89** acts to enhance the diffusive light source.

[0050] In FIG. 8 the system is generally designated by the reference numeral **90**. The optical fiber **91** is typically sheathed in a buffer jacket **92**. The figure shows an optical fiber **91** made of glass or plastic, a buffer jacket **92** made of polyimide, silicone, acrylate, or polymers, a transparent tubing **93** made of Teflon, silicone, polymer, or other material, and a diffusing chamber **94** made of a transparent material, air, plastic, glass, or diffusing material with embedded scatterer. The distal end **97** of the fiber **91** delivers light to the diffusing chamber **94**. The light from the light source comes from the proximal end **96** and is directed toward the distal end **97**. An optical source provides light energy through the optical fiber **91**. The optical source can be an optical source such as that as described in U.S. Pat. No. 6,102,917, by Maitland et al, patented Aug. 15, 2000, incorporated herein by reference. The light energy **98** is diffused to the target area by the light diffusing chamber **94**. A transparent or near-transparent plug **95** is connected to the distal end of light diffusing chamber **94**. The distal end surface **95A** of the plug **95** can include, but is not limited to, a reflective surface, attachment of an optical transducer, material coating(s), and doping the plug with a material that acts as an optical transducer. This allows for an optical sensor to be built into the diffusive device. The light energy **98A** is returned through the optical fiber **91** carrying a signal form the transducer.

[0051] In FIG. 9 the system is generally designated by the reference numeral **100**. The optical fiber **101** is typically sheathed in a buffer jacket **102**. The figure shows an optical fiber **101** made of glass or plastic, a buffer jacket **102** made of polyimide, silicone, acrylate, or polymers, a transparent tubing **103** made of Teflon, silicone, polymer, or other material, a diffusing chamber **104** made of a transparent material, air, plastic, glass, or diffusing material with embedded scatterers, and an end plug **105**. The distal end **107** of the fiber **101** delivers light to the diffusing chamber. The light from the light source comes from the proximal end **106** and is directed toward the distal end **107**. An optical source provides light energy **108** through the optical fiber **101**. The light energy provides the diffuse light source. The optical source can be an optical source such as that as described in U.S. Pat. No. 6,102,917, by Maitland et al, patented Aug. 15, 2000, incorporated herein by reference. A transparent or near-transparent plug **105** is connected to the distal end of light diffusing chamber **104**. The distal end surface **105A** of the plug **105** can be, but is not limited to, a reflective surface, attachment of an optical transducer, material coating(s), and doping the plug with a material that acts as an optical transducer. This allows for an optical sensor to be built into the diffusive device. The light energy **108A** is returned through the optical fiber **101** carrying a signal form the transducer.

[0052] In FIG. 10 the system is generally designated by the reference numeral **110**. The optical fiber **111** is typically sheathed in a buffer jacket **112**. The figure shows an optical fiber **111** made of glass or plastic, a buffer jacket **112** made of polyimide, silicone, acrylate, or polymers, a transparent tubing **113** made of Teflon, silicone, polymer, or other

material, a diffusing chamber **114** made of a transparent material, air, plastic, glass, or diffusing material with embedded scatterers, and a second optical fiber **105** made of glass or plastic. The distal end of the fiber delivers light to the diffusing chamber. The light from the light source comes from the proximal end **116** and is directed toward the distal end **117**. An optical source provides light energy **118** through the optical fiber **111**. The light energy provides the diffuse light source. The optical source can be an optical source such as that as described in U.S. Pat. No. 6,102,917, by Maitland et al, patented Aug. 15, 2000, incorporated herein by reference. Attached to the distal end of the diffusing chamber **114** is an optical fiber **105**. This allows multiple diffusing devices and sensors to be used serially and/or allows for a fiber-based sensor to be directly used in conjunction with the diffusing device **114**. The optical fiber **105** may be connected to a transducer that interacts with the light **118A** from the diffusing chamber **114** to sense desired parameters. The light energy **118A** is returned through the optical fiber **111** carrying a signal form the transducer.

[0053] Other embodiments of the basic system describe above, are shown in are shown in FIGS. 11, 12, 13, 14, 15, and 16. FIG. 11 illustrates an embodiment with a tube enhancement. This embodiment, generally designated by the reference numeral **120**, shows modifications to the external tube **123** that encases the diffusion device **124**. In the embodiment of FIG. 11, the optical fiber **121** is typically sheathed in a buffer jacket **122**. The figure shows an optical fiber **121** made of glass or plastic, a buffer jacket **122** made of polyimide, silicone, acrylate, or polymers, a diffusing chamber **124** made of a transparent material, air, plastic, glass, or diffusing material with embedded scatterers, an end plug **125** made of plastic, glass, or metal. The distal end **127** of the optical fiber **121** delivers light to the diffusing chamber **124**. The light from the light source comes from the proximal end **126** and is directed toward the distal end **127** of the optical fiber **121**. The light energy **128** and **128A** is directed from the optical fiber **121** through the diffusing chamber **124** to the target area. The proximal end **129** of the plug **125** is reflective (specular or diffusive) such that the diffusive source is increased. As shown, the foregoing structure is contained in the external tube **123**. The tube **123** is be constructed of multiple materials and/or layers. The tube multiple layers are selected to enhance the device **120** by changing its mechanical properties and/or facilitate a means of introducing multiple materials to the diffuse light.

[0054] The embodiment of FIG. 12 illustrates an embodiment, generally designated by the reference numeral **130**. The optical fiber **131** is typically sheathed in a buffer jacket **132**. The figure shows an optical fiber **131** made of glass or plastic, a buffer jacket **132** made of polyimide, silicone, acrylate, or polymers, a diffusing chamber **134** made of a transparent material, air, plastic, glass, or diffusing material with embedded scatterers, an end plug **135** made of plastic, glass, or metal. The distal end **137** of the optical fiber **131** delivers light to the diffusing chamber **134**. The light from the light source comes from the proximal end **136** and is directed toward the distal end **137** of the optical fiber **131**. The light energy **138** and **138A** is directed from the optical fiber **131** through the diffusing chamber **134** to the target area. The proximal end **139** of the plug **135** is reflective (specular or diffusive) such that the diffusive source is increased. As shown, the foregoing structure is contained in the external tube **133**. The inner surface **133B** and/or outer

surface **133A** of the tube **135** are diffusely scattering. This is achieved by abrading or etching the inner surface **133B** and/or outer surface **133A** of the tube **135** with mechanical or chemical means. The scattering properties of the surface may be a function of axial and/or radial position. The scattering surfaces enhance the basic design by modifying the diffuse nature of the light source.

[0055] The embodiment of **FIG. 13** illustrates an embodiment, generally designated by the reference numeral **140**. The optical fiber **141** is typically sheathed in a buffer jacket **142**. The figure shows an optical fiber **141** made of glass or plastic, a buffer jacket **142** made of polyimide, silicone, acrylate, or polymers, a diffusing chamber **144** made of a transparent material, air, plastic, glass, or diffusing material with embedded scatterers, an end plug **145** made of plastic, glass, or metal. The distal end **147** of the optical fiber **141** delivers light to the diffusing chamber **144**. The light from the light source comes from the proximal end **146** and is directed toward the distal end **147** of the optical fiber **141**. The light energy **148** is directed from the optical fiber **141** through the diffusing chamber **144** to the target area. The proximal end **149** of the plug **145** is reflective (specular or diffusive) such that the diffusive source is increased. As shown, the foregoing structure is contained in the external tube **143**. The tube **143** has an embedded or coated transducer **143A** on or about its external surface. The transducer **143A** may be partially or totally absorbing of light **148A**. The transducer **143A** may also act to alter the wavelength of the incident light **148A**. The transducer **143** may span all or part of the radial or axial area. This transducer **143A** placement enhances the device's ability to act as a sensor.

[0056] The embodiment of **FIG. 14** illustrates an embodiment, generally designated by the reference numeral **150**. The optical fiber **151** is typically sheathed in a buffer jacket **152**. The figure shows an optical fiber **151** made of glass or plastic, a buffer jacket **152** made of polyimide, silicone, acrylate, or polymers, a diffusing chamber **154** made of a transparent material, air, plastic, glass, or diffusing material with embedded scatterers, an end plug **155** made of plastic, glass, or metal. The distal end **157** of the optical fiber **151** delivers light to the diffusing chamber **154**. The light from the light source comes from the proximal end **156** and is directed toward the distal end **157** of the optical fiber **151**. The light energy **158** and **158A** is directed from the optical fiber **151** through the diffusing chamber **154** to the target area. The proximal end **159** of the plug **155** is reflective (specular or diffusive) such that the diffusive source is increased. As shown, the foregoing structure is contained in the external tube **153**. The tubing may be doped with absorbing, transducing or scattering materials. This material **153A** may be used to control the axial distribution of diffuse light. Also, the doped material **153A** may be used to enhance the diffuse nature of the light source. Finally, the tube **153** may be made into a transducer if the proper material **153A**, such as a fluorophore, is embedded in the tubing **153**.

[0057] In **FIG. 15** a full angle (360°) radial radiation pattern is illustrated in connection with **FIG. 6**. As shown in **FIGS. 5 and 15** the system is generally designated by the reference numeral **60**. The optical fiber **61** is typically sheathed in a buffer jacket **62** made of polyimide, silicone, acrylate, or polymers. The optical fiber **61** is contained in a transparent tubing **63** made of Teflon, silicone, polymer, or other material. A diffusing chamber **64** made of a transparent

material, air, plastic, glass, or diffusing material with embedded scatterers is connected to the distal end **67** of the optical fiber **61**. An end plug **65** made of plastic, glass, or metal scatterers is connected to the distal end **67** of the diffusing chamber **64**. An optical source provides light energy **68** and **68A** that is transmitted from the diffusing chamber **64**, as best shown in **FIG. 15**.

[0058] In the embodiment of **FIG. 16**, the total angle and directions of the diffuse source may be controlled by combinations of other embodiments. As shown in **FIG. 16**, the system is generally designated by the reference numeral **160**. The optical fiber is contained in a transparent tubing **163** made of Teflon, silicone, polymer, or other material. A diffusing chamber **162** made of a transparent material, air, plastic, glass, or diffusing material with embedded scatterers is connected to the distal end of the optical fiber. An end plug made of plastic, glass, or metal scatterers is connected to the distal end of the diffusing chamber. The diffusing chamber **162** transmits the light energy **165** in a radial direction outward. The diffusing chamber **162** has modified surface **164** that provides a window **166** for the light. Multiple windows provided by openings in the modified surface **164** may be used to transmit the diffuse light in more than one direction.

The invention claimed is:

1. A light diffusion system for transmitting light to a target area, said light transmitted in a direction from a proximal end to a distal end by an optical fiber, comprising:

a diffusing chamber operatively connected to said optical fiber for transmitting said light from said proximal end to said distal end and transmitting said light to said target area, and

a plug operatively connected to said diffusing chamber for increasing the light that is transmitted to said target area.

2. The light diffusion system of claim 1, wherein said plug has a convex surface for increasing the light that is transmitted to said target area.

3. The light diffusion system of claim 1, wherein said plug has a concave surface for increasing the light that is transmitted to said target area.

4. The light diffusion system of claim 1, wherein said diffusing chamber transmits some of the light to said target area, wherein said plug is relatively transparent to said light, and wherein said plug has a reflective end surface for returning the light to said optical fiber.

5. The light diffusion system of claim 1, wherein said diffusing chamber transmits some of the light to said target area, wherein said plug is relatively transparent to said light, and including a second optical fiber for receiving some of the light.

6. The light diffusion system of claim 1, wherein said diffusing chamber has a window that transmits the light to a specific portion of said target area

7. The light diffusion system of claim 1, including a tube surrounding said optical fiber and said diffusing chamber.

8. The light diffusion system of claim 7, wherein said tube surrounding said optical fiber and said diffusing chamber has multiple layers selected to enhance said light diffusion system by changing the mechanical properties of said tube.

9. The light diffusion system of claim 7, wherein said tube surrounding said optical fiber and said diffusing chamber has

multiple layers selected to enhance said light diffusion system by introducing multiple materials to the light.

10. The light diffusion system of claim 7, wherein said tube surrounding said optical fiber and said diffusing chamber is diffusely scattering.

11. The light diffusion system of claim 10, wherein said tube surrounding said optical fiber and said diffusing chamber is diffusely scattering resulting from abrading or etching the inner surface and/or outer surface of the said tube with mechanical or chemical means.

12. The light diffusion system of claim 1, wherein said diffusing chamber is operatively connected to said optical fiber toward said proximal end and said plug is operatively connected to said diffusing chamber toward said proximal end.

13. A method of manufacturing a light diffusing system, comprising the steps of:

operatively connecting a diffusing chamber to an optical fiber for transmitting light from the proximal end of said optical fiber to the distal end of said optical fiber and to a target area, and

operatively connecting a plug to said diffusing chamber for increasing the light that is transmitted to said target area.

14. The method of manufacturing a light diffusing system of claim 13, including providing a convex surface on said plug for increasing the light that is transmitted to said target area.

15. The method of manufacturing a light diffusing system of claim 13, including providing a concave surface on said plug for increasing the light that is transmitted to said target area.

16. The method of manufacturing a light diffusing system of claim 13, wherein said plug is relatively transparent to said light, and wherein said plug has a reflective end surface for returning the light to said optical fiber.

17. The method of manufacturing a light diffusing system of claim 13, wherein diffusing chamber is constructed to transmit some of the light to said target area, wherein said plug is relatively transparent to said light, and including a second optical fiber for receiving some of the light.

18. The method of manufacturing a light diffusing system of claim 13, wherein said diffusing chamber has a window that transmits the light to a specific portion of said target area

19. The method of manufacturing a light diffusing system of claim 13, including a tube surrounding said optical fiber and said diffusing chamber.

20. The method of manufacturing a light diffusing system of claim 19, wherein said tube surrounding said optical fiber and said diffusing chamber has multiple layers selected to enhance said light diffusion system by changing the mechanical properties of said tube.

21. The method of manufacturing a light diffusing system of claim 19, wherein said tube surrounding said optical fiber and said diffusing chamber has multiple layers selected to enhance said light diffusion system by introducing multiple materials to the light.

22. The method of manufacturing a light diffusing system of claim 19, wherein said tube surrounding said optical fiber and said diffusing chamber is diffusely scattering.

23. The method of manufacturing a light diffusing system of claim 19, wherein said tube surrounding said optical fiber and said diffusing chamber is diffusely scattering resulting from abrading or etching the inner surface and/or outer surface of the said tube with mechanical or chemical means.

24. The method of manufacturing a light diffusing system of claim 13, wherein said diffusing chamber is operatively connected to said optical fiber toward said proximal end and said plug is operatively connected to said diffusing chamber toward said proximal end.

* * * * *