



US009186442B2

(12) **United States Patent**
Olson

(10) **Patent No.:** **US 9,186,442 B2**

(45) **Date of Patent:** **Nov. 17, 2015**

(54) **DYNAMIC, REDUCED-PRESSURE TREATMENT SYSTEMS AND METHODS**

(71) Applicant: **KCI Licensing, Inc.**, San Antonio, TX (US)

(72) Inventor: **Jonathan Scott Olson**, Houston, TX (US)

(73) Assignee: **KCI Licensing, Inc.**, San Antonio, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 239 days.

(21) Appl. No.: **13/896,779**

(22) Filed: **May 17, 2013**

(65) **Prior Publication Data**

US 2013/0253453 A1 Sep. 26, 2013

Related U.S. Application Data

(62) Division of application No. 12/621,340, filed on Nov. 18, 2009, now Pat. No. 8,465,465.

(60) Provisional application No. 61/116,121, filed on Nov. 19, 2008.

(51) **Int. Cl.**
A61M 1/00 (2006.01)

(52) **U.S. Cl.**
CPC **A61M 1/0023** (2013.01); **A61M 1/009** (2014.02); **A61M 1/0037** (2013.01); **A61M 1/0088** (2013.01); **Y10T 29/49236** (2015.01)

(58) **Field of Classification Search**
CPC A61F 13/02; A61M 1/00; A61M 1/34; A61M 27/00; B01D 69/02; B01D 69/04; B01D 69/08; B01D 69/12; B01D 69/14; B01D 71/00; B01D 71/30; B01D 71/36; B01D 71/82

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,355,846 A 10/1920 Rannells
2,159,164 A 5/1939 Karlström

(Continued)

FOREIGN PATENT DOCUMENTS

AU 550575 A1 3/1986
AU 745271 4/1999

(Continued)

OTHER PUBLICATIONS

N.A. Bagautdinov, "Variant of External Vacuum Aspiration in the Treatment of Purulent Diseases of the Soft Tissues," Current Problems in Modern Clinical Surgery: Interdepartmental Collection, edited by V. Ye Volkov et al. (Chuvashia State University, Cheboksary, U.S.S.R. 1986);pp. 94-96 (certified translation).


(Continued)

Primary Examiner — Melanie Hand

(57) **ABSTRACT**

A dynamic, reduced-pressure treatment system generates reduced pressure and a wave experienced at a tissue site where the wave may have a frequency in the range of from 0.5 Hertz to 20 Hertz. The system includes a manifold for delivering reduced pressure to the tissue site, a sealing member forming a fluid seal over the tissue site, a reduced-pressure source for providing reduced pressure, a reduced-pressure delivery member for delivering reduced pressure from the reduced-pressure source to the manifold, and a wave generator associated with the reduced-pressure delivery member for imparting a wave to the reduced pressure developed by the reduced-pressure source. A reduced-pressure delivery member with liquid-impermeable-and-gas-permeable element may be applied to help reduce blockages and to facilitate ease of treatment. Other systems, apparatuses, and methods are disclosed.

20 Claims, 5 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,547,758 A 4/1951 Keeling
 2,632,443 A 3/1953 Leshner
 2,682,873 A 7/1954 Evans et al.
 2,893,382 A 7/1959 Demeny
 2,910,763 A 11/1959 Lauterbach
 2,969,057 A 1/1961 Simmons
 3,066,672 A 12/1962 Crosby, Jr. et al.
 3,367,332 A 2/1968 Groves
 3,520,300 A 7/1970 Flower Jr.
 3,568,675 A 3/1971 Harvey
 3,648,692 A 3/1972 Wheeler
 3,682,180 A 8/1972 McFarlane
 3,826,254 A 7/1974 Mellor
 4,080,970 A 3/1978 Miller
 4,096,853 A 6/1978 Weigand
 4,139,004 A 2/1979 Gonzalez, Jr.
 4,165,748 A 8/1979 Johnson
 4,184,510 A 1/1980 Murry et al.
 4,233,969 A 11/1980 Lock et al.
 4,245,630 A 1/1981 Lloyd et al.
 4,256,109 A 3/1981 Nichols
 4,261,363 A 4/1981 Russo
 4,275,721 A 6/1981 Olson
 4,284,079 A 8/1981 Adair
 4,297,995 A 11/1981 Golub
 4,333,468 A 6/1982 Geist
 4,373,519 A 2/1983 Errede et al.
 4,382,441 A 5/1983 Svedman
 4,392,853 A 7/1983 Muto
 4,392,858 A 7/1983 George et al.
 4,419,097 A 12/1983 Rowland
 4,465,485 A 8/1984 Kashmer et al.
 4,475,909 A 10/1984 Eisenberg
 4,480,638 A 11/1984 Schmid
 4,525,166 A 6/1985 Leclerc
 4,525,374 A 6/1985 Vaillancourt
 4,540,412 A 9/1985 Van Overloop
 4,543,100 A 9/1985 Brodsky
 4,548,202 A 10/1985 Duncan
 4,551,139 A 11/1985 Plaas et al.
 4,569,348 A 2/1986 Hasslinger
 4,605,399 A 8/1986 Weston et al.
 4,608,041 A 8/1986 Nielsen
 4,640,688 A 2/1987 Hauser
 4,655,754 A 4/1987 Richmond et al.
 4,664,662 A 5/1987 Webster
 4,710,165 A 12/1987 McNeil et al.
 4,733,659 A 3/1988 Edenbaum et al.
 4,743,232 A 5/1988 Kruger
 4,748,973 A 6/1988 Cho
 4,758,220 A 7/1988 Sundblom et al.
 4,787,888 A 11/1988 Fox
 4,826,494 A 5/1989 Richmond et al.
 4,838,883 A 6/1989 Matsuura
 4,840,187 A 6/1989 Brazier
 4,863,449 A 9/1989 Therriault et al.
 4,872,450 A 10/1989 Austad
 4,878,901 A 11/1989 Sachse
 4,897,081 A 1/1990 Poirier et al.
 4,906,233 A 3/1990 Moriuchi et al.
 4,906,240 A 3/1990 Reed et al.
 4,919,654 A 4/1990 Kalt et al.
 4,941,882 A 7/1990 Ward et al.
 4,953,565 A 9/1990 Tachibana et al.
 4,969,880 A 11/1990 Zamierowski
 4,985,019 A 1/1991 Michelson
 4,985,055 A 1/1991 Thorne et al.
 5,037,397 A 8/1991 Kalt et al.
 5,086,170 A 2/1992 Luheshi et al.
 5,092,858 A 3/1992 Benson et al.
 5,100,396 A 3/1992 Zamierowski
 5,134,994 A 8/1992 Say
 5,149,331 A 9/1992 Ferdman et al.
 5,167,613 A 12/1992 Karami et al.
 5,176,663 A 1/1993 Svedman et al.

5,215,522 A 6/1993 Page et al.
 5,232,453 A 8/1993 Plass et al.
 5,261,893 A 11/1993 Zamierowski
 5,278,100 A 1/1994 Doan et al.
 5,279,550 A 1/1994 Habib et al.
 5,298,015 A 3/1994 Komatsuzaki et al.
 5,342,376 A 8/1994 Ruff
 5,344,415 A 9/1994 DeBusk et al.
 5,358,494 A 10/1994 Svedman
 5,437,622 A 8/1995 Carion
 5,437,651 A 8/1995 Todd et al.
 5,527,293 A 6/1996 Zamierowski
 5,549,584 A 8/1996 Gross
 5,556,375 A 9/1996 Ewall
 5,607,388 A 3/1997 Ewall
 5,636,643 A 6/1997 Argenta et al.
 5,645,081 A 7/1997 Argenta et al.
 5,738,656 A 4/1998 Wagner
 6,071,267 A 6/2000 Zamierowski
 6,135,116 A 10/2000 Vogel et al.
 6,241,747 B1 6/2001 Ruff
 6,287,316 B1 9/2001 Agarwal et al.
 6,345,623 B1 2/2002 Heaton et al.
 6,488,643 B1 12/2002 Tumey et al.
 6,493,568 B1 12/2002 Bell et al.
 6,553,998 B2 4/2003 Heaton et al.
 6,814,079 B2 11/2004 Heaton et al.
 2002/0077661 A1 6/2002 Saadat
 2002/0115951 A1 8/2002 Norstrem et al.
 2002/0120185 A1 8/2002 Johnson
 2002/0143286 A1 10/2002 Tumey
 2007/0239078 A1 10/2007 Jaeb
 2008/0208147 A1 8/2008 Argenta et al.

FOREIGN PATENT DOCUMENTS

AU 755496 2/2002
 CA 2005436 6/1990
 DE 26 40 413 A1 3/1978
 DE 43 06 478 A1 9/1994
 DE 295 04 378 U1 10/1995
 EP 0100148 A1 2/1984
 EP 0117632 A2 9/1984
 EP 0161865 A2 11/1985
 EP 0358302 A2 3/1990
 EP 1018967 B1 8/2004
 FR 14151 9/1911
 GB 692578 6/1953
 GB 2 195 255 A 4/1988
 GB 2 197 789 A 6/1988
 GB 2 220 357 A 1/1990
 GB 2 235 877 A 3/1991
 GB 2 329 127 B 3/1999
 GB 2 333 965 A 8/1999
 JP 4129536 4/1992
 SG 71559 4/2002
 WO 80/02182 10/1980
 WO 87/04626 8/1987
 WO 90/010424 9/1990
 WO 93/09727 5/1993
 WO 94/020041 9/1994
 WO 96/05873 2/1996
 WO 97/18007 5/1997
 WO 99/13793 3/1999
 WO WO 2005105175 A1 * 11/2005 A61M 1/00
 WO WO2008086397A2 A2 7/2008
 WO 2008100446 A2 8/2008

OTHER PUBLICATIONS

Louis C. Argenta, MD and Michael J. Morykwias, PhD; "Vacuum-Assisted Closure: A New Method for Wound Control and Treatment: Animal Studies & Basic Foundation"; *Annals of Plastic Surgery*, vol. 38, No. 6, Jun. 1997; pp. 553-562.
 Susan Mendez-Eastman, RN; "When Wounds Won't Heal" *RN* Jan. 1998, vol. 61 (1); Medical Economics Company, Inc., Montvale, NJ, USA; pp. 20-24.

(56)

References Cited

OTHER PUBLICATIONS

James H. Blackburn, II, MD, et al; "Negative-Pressure Dressings as a Bolster for Skin Grafts"; *Annals of Plastic Surgery*, vol. 40, No. 5, May 1998, pp. 453-457.

John Masters; "Reliable, Inexpensive and Simple Suction Dressings"; *Letters to the Editor, British Journal of Plastic Surgery*, 1998, vol. 51 (3), p. 267; Elsevier Science/The British Association of Plastic Surgeons, UK.

S.E. Greer, et al "The Use of Subatmospheric Pressure Dressing Therapy to Close Lymphocutaneous Fistulas of the Groin" *British Journal of Plastic Surgery* (2000), vol. 53, pp. 484-487.

George V. Letsou, MD., et al; "Stimulation of Adenylate Cyclase Activity in Cultured Endothelial Cells Subjected to Cyclic Stretch"; *Journal of Cardiovascular Surgery*, vol. 31, 1990, pp. 634-639.

Orringer, Jay, et al; "Management of Wounds in Patients with Complex Enterocutaneous Fistulas"; *Surgery, Gynecology & Obstetrics*, Jul. 1987, vol. 165, pp. 79-80.

International Search Report for PCT International Application PCT/GB95/01983; Nov. 23, 1995.

PCT International Search Report for PCT International Application PCT/GB98/02713; Jan. 8, 1999.

PCT Written Opinion; PCT International Application PCT/GB98/02713; Jun. 8, 1999.

PCT International Examination and Search Report, PCT International Application PCT/GB96/02802; Jan. 15, 1998 & Apr. 29, 1997. PCT Written Opinion, PCT International Application PCT/GB96/02802; Sep. 3, 1997.

Dattilo, Philip P., Jr., et al; "Medical Textiles: Application of an Absorbable Barbed Bi-directional Surgical Suture"; *Journal of Textile and Apparel, Technology and Management*, vol. 2, Issue 2, Spring 2002, pp. 1-5.

Kostyuchenok, B.M., et al; "Vacuum Treatment in the Surgical Management of Purulent Wounds"; *Vestnik Khirurgi*, Sep. 1986, pp. 18-21 and 6 p. English translation thereof.

Davydov, Yu. A., et al; "Vacuum Therapy in the Treatment of Purulent Lactation Mastitis"; *Vestnik Khirurgi*, May 14, 1986, pp. 66-70, and 9 page English translation thereof.

Yusupov, Yu. N., et al; "Active Wound Drainage"; *Vestnik Khirurgi*, vol. 138, Issue 4, 1987, and 7 page English translation thereof.

Davydov, Yu. A., et al; "Bacteriological and Cytological Assessment of Vacuum Therapy for Purulent Wounds"; *Vestnik Khirurgi*, Oct. 1988, pp. 48-52, and 8 page English translation thereof.

Davydov, Yu. A., et al; "Concepts for the Clinical-Biological Management of the Wound Process in the Treatment of Purulent Wounds by Means of Vacuum Therapy"; *Vestnik Khirurgi*, Jul. 7, 1980, pp. 132-136, and 8 page English translation thereof.

Chariker, Mark E., M.D., et al; "Effective Management of incisional and cutaneous fistulae with closed suction wound drainage"; *Contemporary Surgery*, vol. 34, Jun. 1989, pp. 59-63.

Egnell Minor, Instruction Book, First Edition, 300 7502, Feb. 1975, pp. 24.

Egnell Minor: Addition to the Users Manual Concerning Overflow Protection—Concerns all Egnell Pumps, Feb. 3, 1983, p. 1.

Svedman, P.: "Irrigation Treatment of Leg Ulcers", *The Lancet*, Sep. 3, 1983, pp. 532-534.

Chinn, Steven D. et al.: "Closed Wound Suction Drainage", *The Journal of Foot Surgery*, vol. 24, No. 1, 1985, pp. 76-81.

Arnljots, Bjorn et al.: "Irrigation Treatment in Split-Thickness Skin Grafting of Intractable Leg Ulcers", *Scand J. Plast Reconstr. Surg.*, vol. 19, 1985, pp. 211-213.

Svedman, P.: "A Dressing Allowing Continuous Treatment of a Biosurface", *IRCS Medical Science: Biomedical Technology, Clinical Medicine, Surgery and Transplantation*, vol. 7, 1979, p. 221.

Svedman, P. et al.: "A Dressing System Providing Fluid Supply and Suction Drainage Used for Continuous or Intermittent Irrigation", *Annals of Plastic Surgery*, vol. 17, No. 2, Aug. 1986, pp. 125-133.

K.F. Jeter, T.E. Tittle, and M. Chariker, "Managing Draining Wounds and Fistulae: New and Established Methods," *Chronic Wound Care*, edited by D. Krasner (Health Management Publications, Inc., King of Prussia, PA 1990), pp. 240-246.

G. Živadinovic, V. Đukić, Ž. Maksimović, Đ. Radak, and P. Peška, "Vacuum Therapy in the Treatment of Peripheral Blood Vessels," *Timok Medical Journal* 11 (1986), pp. 161-164 (certified translation). F.E. Johnson, "An Improved Technique for Skin Graft Placement Using a Suction Drain," *Surgery, Gynecology, and Obstetrics* 159 (1984), pp. 584-585.

A.A. Safronov, Dissertation Abstract, Vacuum Therapy of Trophic Ulcers of the Lower Leg with Simultaneous Autoplasty of the Skin (Central Scientific Research Institute of Traumatology and Orthopedics, Moscow, U.S.S.R. 1967) (certified translation).

M. Schein, R. Saadia, J.R. Jamieson, and G.A.G. Decker, "The 'Sandwich Technique' in the Management of the Open Abdomen," *British Journal of Surgery* 73 (1986), pp. 369-370.

D.E. Tribble, "An Improved Sump Drain-Irrigation Device of Simple Construction," *Archives of Surgery* 105 (1972) pp. 511-513.

C.E. Tennant, "The Use of Hypermia in the Postoperative Treatment of Lesions of the Extremities and Thorax," *Journal of the American Medical Association* 64 (1915), pp. 1548-1549.

Selections from W. Meyer and V. Schmieden, Bier's Hyperemic Treatment in Surgery, Medicine, and the Specialties: A Manual of Its Practical Application, (W.B. Saunders Co., Philadelphia, PA 1909), pp. 17-25, 44-64, 90-96, 167-170, and 210-211.

V.A. Solovev et al., Guidelines, The Method of Treatment of Immature External Fistulas in the Upper Gastrointestinal Tract, editor-in-chief Prov. V.I. Parahonyak (S.M. Kirov Gorky State Medical Institute, Gorky, U.S.S.R. 1987) ("Solovev Guidelines").

V.A. Kuznetsov & N.A. Bagautdinov, "Vacuum and Vacuum-Sorption Treatment of Open Septic Wounds," in II All-Union Conference on Wounds and Wound Infections: Presentation Abstracts, edited by B.M. Kostyuchenok et al. (Moscow, U.S.S.R. Oct. 28-29, 1986) pp. 91-92 ("Bagautdinov II").

V.A. Solovev, Dissertation Abstract, Treatment and Prevention of Suture Failures after Gastric Resection (S.M. Kirov Gorky State Medical Institute, Gorky, U.S.S.R. 1988) ("Solovev Abstract").

V.A.C. ® Therapy Clinical Guidelines: A Reference Source for Clinicians (Jul. 2007).

* cited by examiner




FIG. 1




FIG. 2




FIG. 3








FIG. 4





**DYNAMIC, REDUCED-PRESSURE
TREATMENT SYSTEMS AND METHODS**

RELATED APPLICATION

This Application is a Divisional of U.S. patent application Ser. No. 12/621,340, entitled "Dynamic, Reduced-Pressure Treatment Systems and Methods," filed 18 Nov. 2009, which claims the benefit, under 35 U.S.C. §119(e), of the filing of U.S. Provisional Patent Application Ser. No. 61/116,121, entitled "Dynamic, Reduced-Pressure Treatment System and Method," filed 19 Nov. 2008, both of which are incorporated herein by reference for all purposes.

BACKGROUND

The present disclosure relates generally to medical treatment systems and, more particularly, but without limitation to dynamic, reduced-pressure systems and methods.

Clinical studies and practice have shown that providing a reduced pressure in proximity to a tissue site augments and accelerates the growth of new tissue at the tissue site. The applications of this phenomenon are numerous, but application of reduced pressure has been particularly successful in treating wounds. This treatment (frequently referred to in the medical community as "negative pressure wound therapy," "NPWT," "reduced pressure therapy," or "vacuum therapy") provides a number of benefits, which may include faster healing and increased formulation of granulation tissue. Typically, reduced pressure is applied to tissue through a porous pad or other manifold device. The porous pad contains cells or pores that are capable of distributing reduced pressure to the tissue site and channeling fluids that are drawn from the tissue site. The possible benefits of treating a tissue site with reduced pressure include reduction in edema, enhanced blood flow, promotion of granulation of tissue, decreasing of bacterial colonization, removing of inhibiting agents, promotion of a moist healing environment, and enhanced epithelial migration.

SUMMARY

Problems with existing reduced-pressure treatment systems and methods are addressed by the systems and methods of the illustrative, non-limiting embodiments described herein. According to an illustrative, non-limiting embodiment, a dynamic, reduced-pressure treatment system for treating a tissue site on a patient includes a manifold for placing adjacent to the tissue site, a sealing member for coupling to the patient's epidermis to form a fluid seal over the tissue site, a reduced-pressure source for producing reduced pressure, a reduced-pressure delivery member for delivering reduced pressure from the reduced-pressure source to the manifold, and a wave generator associated with the reduced-pressure delivery member. The wave generator imparts a wave to the reduced pressure developed by the reduced-pressure source.

According to another illustrative, non-limiting embodiment, a method for manufacturing a dynamic, reduced-pressure treatment system for treating a tissue site on a patient includes the steps of: providing a manifold for placing adjacent to the tissue site, providing a sealing member for coupling to the patient's epidermis and operable to form a fluid seal over the tissue site, providing a reduced-pressure source for developing a reduced pressure, and providing a reduced-pressure delivery member for delivering reduced pressure from the reduced-pressure source to the manifold. The

method further includes the steps of providing a wave generator and associating the wave generator with the reduced-pressure delivery member. The wave generator imparts a wave to the reduced pressure developed by the reduced-pressure source.

According to another illustrative, non-limiting embodiment, a method for treating a tissue site on a patient includes the steps of: disposing a manifold adjacent to the tissue site, placing a sealing member on the patient's epidermis to form a fluid seal over the tissue site, fluidly coupling a reduced-pressure delivery member to the manifold, and fluidly coupling the reduced-pressure delivery member to a reduced-pressure source for providing reduced pressure to the manifold. The method further includes associating a wave generator with the reduced-pressure delivery member. The wave generator imparts a wave to the reduced pressure developed by the reduced-pressure source.

According to another illustrative, non-limiting embodiment, a reduced-pressure delivery member includes a first lumen for transmitting a liquid and a second lumen for transmitting a gas. The first lumen has a first interior space and the second lumen has a second interior space. A first liquid-impermeable-and-gas-permeable member is coupled to the second lumen in at least a portion of the second interior space.

According to another illustrative, non-limiting embodiment, a reduced-pressure delivery member includes a first lumen for transmitting a gas and a second lumen for transmitting a liquid. The first lumen has a first interior space and the second lumen has a second interior space. The first lumen is formed at least in part from a fluid impermeable material. The second lumen is formed from a gas-permeable-and-liquid-impermeable material and is disposed within the first interior space.

Other features and advantages of the illustrative embodiments will become apparent with reference to the drawings and detailed description that follow.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram with a portion shown in cross section of an illustrative, non-limiting embodiment of a dynamic, reduced-pressure treatment system;

FIG. 2 is a schematic diagram with a portion shown in cross section of an illustrative, non-limiting embodiment of a wave generator for use with an embodiment of a dynamic, reduced-pressure treatment system;

FIG. 3 is a schematic diagram with a portion shown in cross section of another illustrative, non-limiting embodiment of a wave generator for use with an embodiment of a dynamic, reduced-pressure treatment system;

FIG. 4 is a schematic diagram of another illustrative, non-limiting embodiment of a wave generator for use with an embodiment of a dynamic, reduced-pressure treatment system;

FIG. 5 is a schematic, perspective view of an illustrative, non-limiting embodiment of a reduced-pressure delivery member for use with an embodiment of a reduced-pressure treatment system;

FIG. 6 is a schematic, perspective view of an illustrative, non-limiting embodiment of a reduced-pressure delivery member for use with an embodiment of a reduced-pressure treatment system;

FIG. 7 is a schematic, perspective view of an illustrative, non-limiting embodiment of a reduced-pressure delivery member for use with an embodiment of a reduced pressure treatment system; and

FIG. 8 is a schematic cross section of the reduced-pressure delivery member of FIG. 7 taken along line 8-8.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

In the following detailed description of the illustrative embodiments, reference is made to the accompanying drawings that form a part hereof. These embodiments are described in sufficient detail to enable those skilled in the art to practice the subject matter disclosed herein. Other embodiments may be utilized and logical, structural, mechanical, electrical, and chemical changes may be made without departing from the scope of this disclosure. To avoid detail not necessary to enable those skilled in the art to practice the embodiments described herein, the description may omit certain information known to those skilled in the art. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the illustrative embodiments are defined only by the appended claims.

Referring now primarily to FIG. 1, an illustrative embodiment of a dynamic, reduced-pressure treatment system **100** for treating a tissue site **104**, e.g., a wound **102**, a damaged area of tissue, is presented. The tissue site **104**, such as the wound **102**, may involve epidermis **103**, dermis **105**, and subcutaneous tissue **107**. The dynamic, reduced-pressure treatment system **100** may also be used at other tissue sites. The tissue site **104** may be the bodily tissue of any human, animal, or other organism, including bone tissue, adipose tissue, muscle tissue, dermal tissue, vascular tissue, connective tissue, cartilage, tendons, ligaments, or any other tissue. The dynamic, reduced-pressure treatment system **100** may include a manifold **112**, a sealing member **111**, a reduced-pressure delivery member **144**, a reduced-pressure subsystem **113**, and a wave generator **110**.

The manifold **112** distributes reduced pressure and may be formed from any manifold material suitable for distributing reduced pressure. In one illustrative embodiment, the manifold **112** is made from a porous and permeable foam material and, more particularly, a reticulated, open-cell polyurethane or polyether foam that allows good permeability of wound fluids while under a reduced pressure. One such foam material that has been used is the VAC GranuFoam® Dressing available from Kinetic Concepts, Inc. (KCI) of San Antonio, Tex. Any material or combination of materials may be used for the manifold material provided that the manifold material is operable to distribute the reduced pressure. Unless otherwise indicated, as used herein, “or” does not require mutual exclusivity.

The term “manifold” as used herein generally refers to a substance or structure that is provided to assist in applying reduced pressure to, delivering fluids to, or removing fluids from a tissue site. A manifold typically includes a plurality of flow channels or pathways. The plurality of flow channels may be interconnected to improve distribution of fluids provided to and removed from the area of tissue around the manifold. Examples of manifolds may include, without limitation, devices that have structural elements arranged to form flow channels, cellular foam, such as open-cell foam, porous tissue collections, and liquids, gels, and foams that include, or cure to include, flow channels. The manifold material may also be a combination or layering of materials. For example, a first manifold layer of hydrophilic foam may be disposed adjacent to a second manifold layer of hydrophobic foam to form the manifold **112**.

The reticulated pores of the GranuFoam® material are helpful in carrying out the manifold function, but again other

materials may be used. A material with a higher or lower density (smaller pore size) than GranuFoam® material may be desirable in some situations. Among the many possible materials, the following may be used: GranuFoam® material or a Foamex® technical foam (www.foamex.com). In some instances it may be desirable to add ionic silver to the foam in a microbonding process or to add other substances to the material, such as antimicrobial agents. The manifold **112** may be a bio-absorbable material or an anisotropic material.

The sealing member **111** covers the manifold **112** and extends past a peripheral edge **114** of the manifold **112** to form an extension **116** on an intact portion of the epidermis **103**. The extension **116** has a first side **118** and a second, patient-facing side **120**. The extension **116** may form a fluid seal against the epidermis **103** or against a gasket (e.g., another drape portion near wound edge **109**) by a sealing apparatus **124**, and any references to forming a seal with the epidermis **103** should be regarded as also including a seal formed against such a gasket. The sealing apparatus **124** may take numerous forms, such as an adhesive sealing tape; a drape tape or strip; a double-sided drape tape; an adhesive **126**; a paste; a hydrocolloid; a hydrogel; or other sealing device. If a tape is used, the tape may be formed of the same material as the sealing member **111** with a pre-applied, pressure-sensitive adhesive. The adhesive **126** may be applied on a second, patient-facing side **120** of the extension **116**. The adhesive **126** provides a fluid seal between the sealing member **111** and the epidermis **103**. “Fluid seal,” or “seal,” means a seal adequate to maintain reduced pressure at a desired site given the particular reduced-pressure source or subsystem involved.

The sealing member **111** may be an elastomeric material. “Elastomeric” means having the properties of an elastomer and generally refers to a polymeric material that has rubber-like properties. More specifically, most elastomers have elongation rates greater than 100% and a significant amount of resilience. The resilience of a material refers to the material’s ability to recover from an elastic deformation. Examples of elastomers may include, but are not limited to, natural rubbers, polyisoprene, styrene butadiene rubber, chloroprene rubber, polybutadiene, nitrile rubber, butyl rubber, ethylene propylene rubber, ethylene propylene diene monomer, chlorosulfonated polyethylene, polysulfide rubber, polyurethane, EVA film, co-polyester, and silicones. Further still, other non-limiting examples of sealing member materials may include a silicone drape material, such as a 3M Tegaderm® drape material, an acrylic drape material, such as one available from Avery Dennison, or an incise drape material.

The reduced-pressure subsystem **113** includes a reduced-pressure source **140**, which can take many different forms, and may include a reduced-pressure interface **150** or other components to provide reduced pressure to the manifold **112**. The reduced-pressure source **140** provides reduced pressure as part of the dynamic, reduced-pressure treatment system **100**. As used herein, “reduced pressure” generally refers to a pressure less than the ambient pressure at a tissue site that is being subjected to treatment. In most cases, this reduced pressure will be less than the atmospheric pressure at which the patient is located. Alternatively, the reduced pressure may be less than a hydrostatic pressure at the tissue site **104**. Unless otherwise indicated, values of pressure stated herein are gauge pressures.

The reduced pressure delivered may be constant or varied (patterned or random) and may be delivered continuously or intermittently. Although the terms “vacuum” and “negative pressure” may be used to describe the pressure applied to the tissue site, the actual pressure applied to the tissue site may be

more than the pressure normally associated with a complete vacuum. Consistent with the use herein, an increase in reduced pressure or vacuum pressure typically refers to a relative reduction in absolute pressure.

The reduced-pressure source **140** may be any device for supplying a reduced pressure, such as a vacuum pump, wall suction, or other source. While the amount and nature of reduced pressure applied to a tissue site will typically vary according to the application, the reduced pressure will typically be between -5 mm Hg and -500 mm Hg and more typically between -100 mm Hg and -300 mm Hg.

In the illustrative embodiment of FIG. 1, the reduced-pressure source **140** is shown having a reservoir region **142**, or canister region. An interposed membrane filter, such as a hydrophobic or an oleophobic filter, may be interspersed between the reduced-pressure delivery member **144** and the reduced-pressure source **140**. A first portion **146** of the reduced-pressure delivery member **144** may have one or more devices, such as device **148**. For example, the device **148** may be another fluid reservoir, or collection member to hold exudates and other fluids removed. Other non-limiting examples of the device **148** that may be included on the portion **146** of the reduced-pressure delivery member **144**, or otherwise fluidly coupled to the reduced-pressure delivery member **144**, include: a pressure-feedback device, a volume detection system, a blood detection system, an infection detection system, a flow monitoring system, a temperature monitoring system, etc. Some of these devices may be formed integrally with the reduced-pressure source **140**. For example, a reduced-pressure port **141** on the reduced-pressure source **140** may include a filter member that includes one or more filters, e.g., an odor filter.

The reduced pressure developed by the reduced-pressure subsystem **113** is delivered through the reduced-pressure delivery member **144** to the reduced-pressure interface **150**, which may be an elbow port **152**. In one illustrative embodiment, the elbow port **152** is a TRAC® pad available from Kinetic Concepts, Inc. of San Antonio, Tex. The reduced-pressure interface **150** allows the reduced pressure to be delivered through the sealing member **111** to the manifold **112**, as well as to a sealed space **154** in which the manifold **112** is located. The sealed space **154** is formed by the sealing member **111** over the tissue site **104**. In this illustrative embodiment, the reduced-pressure interface **150** extends through the sealing member **111** and into the manifold **112**. Reduced pressure is supplied by the reduced-pressure delivery member **144** to the manifold **112**. The supply of reduced pressure may be direct or in conjunction with reduced-pressure interface **150**.

The wave generator **110** is typically associated with the reduced-pressure delivery member **144**. For example, the wave generator **110** may be fluidly coupled to the reduced-pressure delivery member **144** on a second portion **138** or with a tributary conduit (see, e.g., tributary conduit **302** in FIG. 3). The wave generator **110** imposes a wave form on the reduced pressure supplied by the reduced-pressure subsystem **113**; that is, the wave generator **110** develops a wave. The wave typically causes the pressure to vary at the tissue site **104**. Preferably, the wave generator **110** allows for a wide frequency range with respect to the absolute value of the pressure experienced at the tissue site **104**. The frequency range of the wave may be about 0.5 Hz to about 20 Hz and greater. The wave generator **110** may also control the amplitude of the wave. The wave generator **110** may take many forms, such as a piezoelectric transducer, a diaphragm member, a valve arrangement, etc.

The wave generator **110** creates a wave, or change in the pressure or energy in the reduced pressure in the reduced-pressure delivery member **144**. The change could be accomplished with a sonic wave or a pressure wave, and so the term “wave generator” has been used. The wave generator **110** may function to develop a sonic wave or a pressure wave by electrical means or mechanical means. The wave generator **110** may utilize a reduced-pressure source, gear set using kinetic motion, piezoelectric transducer, a diaphragm member, a valve arrangement, etc. With respect to mechanical options, anything that produces a mechanical variation may be used, such as a displacement device. The wave generator **110** may also be an electrically-powered membrane. Other non-limiting examples of devices and arrangements that may be used as the wave generator **110** will be presented further below in connection with FIGS. 2-4.

In operation, according to one illustrative embodiment, of the dynamic, reduced-pressure treatment system **100**, the manifold **112** is placed adjacent to the tissue site **104**, and the sealing member **111** is placed over the tissue site **104**, the manifold **112**, and a portion of the epidermis **103** to form a fluid seal seal. The fluid seal creates the sealed space **154**. If not already installed, the reduced-pressure interface **150** is fluidly coupled to the sealed space **154**. The reduced-pressure delivery member **144** is fluidly coupled to the reduced-pressure source **140** and the reduced-pressure interface **150**. In this embodiment, the wave generator **110** is associated with the reduced-pressure delivery member **144**. When the reduced-pressure source **140** is activated, reduced pressure may be provided to the manifold **112** and ultimately to tissue site **104**. When the wave generator **110** is activated, the wave generator **110** imparts a wave and provides dynamic pressure or energy variation at the wound site **104**.

As previously noted, the wave generator **110** may take many forms, such as a piezoelectric transducer, a diaphragm member, or an arrangement of valves, such as solenoid-operated valves. A number of different, non-limiting, illustrative embodiments of wave generators will now be presented.

Referring now primarily to FIG. 2, an illustrative embodiment of a wave generator **200** for use as part of a dynamic, reduced-pressure treatment system is presented. For example, the wave generator **200** may be used as the wave generator **110** in the dynamic, reduced-pressure treatment system of FIG. 1. In forming the wave generator **200**, a piezoelectric transducer **202** is fluidly coupled, i.e., is placed in fluid communication with, a reduced-pressure delivery member **204**. The reduced-pressure delivery member **204** receives reduced pressure from a reduced pressure subsystem **206**, which includes a reduced-pressure source **208**. The reduced-pressure subsystem **206** introduces reduced pressure into the reduced-pressure delivery member **204**. The reduced-pressure subsystem **206** also receives fluids through the reduced-pressure delivery member **204** as suggested by arrows **210**. In this illustrative embodiment, the wave generator **200** has been fluidly coupled to the reduced-pressure delivery member **204**.

The wave generator **200** has a movable face member **212** that extends into an interior portion of the reduced-pressure delivery member **204**, or is otherwise fluidly coupled to fluid within the reduced-pressure delivery member **204**. The movable face member **212** moves relative to the reduced-pressure delivery member **204** at a frequency that may be controlled by a power-and-control connection **214**. The power-and-control connection **214** may be a separate power cord and a device for setting and controlling the frequency of the movable face member **212** or the amplitude of the movement of the movable face member **212**. The movable face member **212**

imparts a wave onto the fluid already present in the reduced-pressure delivery member **204**. The wave causes the absolute pressure or energy delivered to vary with a frequency in the range of 0.5 Hz to 20 Hz or greater.

In yet another illustrative, non-limiting embodiment, the wave generator **200** may be a piezoelectric transducer with a piezoelectric member comprising the movable face member **212**. In this embodiment, the movable face member **212** is electrically driven. In response to receiving a desired wave form or frequency information, the wave generator **200** may develop a wave form in the fluid of the reduced-pressure delivery member **204** with the desired frequency or wave form using physical displacement of the movable face member **212**. The possible frequency range, or spectrum, for the wave developed within the reduced-pressure delivery member **204** with this approach is large from 0.5 Hertz to 20 Hertz and higher. The frequency may include any subset of the previously stated range, e.g., 5-20 Hz, 10-20 Hz, 5-15 Hz, etc.

Again, the wave generator may take numerous other forms. The wave generator may be a mechanically or electrically actuated wave generator, or the wave generator may utilize a diaphragm or a system of valves that turn on and off to achieve the desired effect. A device could be added to a reduced-pressure delivery conduit to press and close, i.e., pinch, the conduit or delivery member, e.g., the reduced-pressure delivery member **144** in FIG. 1, in a pattern that causes a pressure wave.

Referring now primarily to FIG. 3, another illustrative, non-limiting embodiment of a wave generator **300** is presented. The wave generator **300** includes a tributary conduit (or lumen) **302** that is fluidly coupled to a reduced-pressure delivery member **304**. The reduced-pressure delivery member **304** is fluidly coupled to a reduced-pressure subsystem **306**. The reduced-pressure subsystem **306** includes a reduced-pressure source **308**. The reduced-pressure subsystem **306** delivers reduced pressure to the reduced-pressure delivery member **304**. At the same time, the reduced-pressure subsystem **306** pulls and receives fluid as suggested by arrow **310**.

The wave generator **300** includes a wave-imparting member **312**, which may be a diaphragm pump, a piston, a piezoelectric member, or any device that is operable to produce a pressure or energy wave on the fluid within the reduced-pressure delivery member **304**. One or more power-and-control connection members **314** may be coupled to the wave generator **300** to provide electrical power and to control the amplitude or frequency of the energy or pressure wave imparted.

Referring now primarily to FIG. 4, another illustrative, non-limiting embodiment of a wave generator **400** is presented. The wave generator **400** is fluidly coupled to a reduced-pressure delivery member **404**. The wave generator **400** includes a plurality of valves, e.g., a first valve **416**, a second valve **418**, and a third valve **420**. The wave generator **400** may further include a plurality of chambers, e.g., a first chamber **422**, second chamber **424**, and third chamber **426**. A plurality of regulators, e.g., a first regulator **428**, a second regulator **430**, and a third regulator **432**, is associated with the plurality of chambers. The first pressure regulator **428** is fluidly coupled to the first chamber **422**. The second pressure regulator **430** is fluidly coupled to the second chamber **424**. Similarly, the third pressure regulator **432** is fluidly coupled to the third chamber **426**. Each pressure regulator **428**, **430**, **432** is operable to regulate pressure, e.g., operable to step down the pressure to a desired level.

A manifold chamber **434** is fluidly coupled to the pressure regulators **428**, **430**, **432** and provides reduced pressure

thereto. The reduced pressure is supplied by a reduced-pressure subsystem **406** through a reduced-pressure supply conduit **405** to the manifold chamber **434**. The reduced-pressure subsystem **406** may include a reduced-pressure source **408**. The pressure can be controlled in each of the chambers **422**, **424**, and **426** to establish the desired pressure level. In this regard, the pressure regulators **428**, **430**, and **432** may reduce or increase the pressure as needed. Typically, the pressure regulators, e.g., regulators **428**, **430**, and **432**, increase the absolute value of the pressure in the chambers, e.g., chambers **422**, **424**, and **426**.

As a non-limiting example, the pressure in the first chamber **422** may be P_1 , the pressure in the second chamber **424** may be P_2 , the pressure in the third chamber **426** may be P_3 , and $P_1 > P_2 > P_3$. Thus, opening and closing of the valves **416**, **418**, **420** may be sequenced to expose the fluid in the reduced-pressure delivery member **404** to different pressures (P_1 , P_2 , and P_3), and thereby creates a wave. A controller may be associated with the valves **416**, **418**, **420**, which may be solenoid valves, to coordinate the opening and closing of the valves **416**, **418**, **420**. The opening and closing of the valves **416**, **418**, and **420** may allow for a wave to be generated with a frequency in the range of 0.5 Hz to 20 Hz and greater. The frequency range may be any subset of the previously stated range.

The dynamic variation of pressure or energy by the wave generator, e.g., **110**, **200**, **300**, **400** at the tissue site, e.g., tissue site **104**, may help with the healing process. The wave generator may help to debride or clean the wound in a continuous fashion. The wave generator may generally help keep the wound cleaner by removing dead tissue. In addition, the wave generator may de-sensitize nerves and thereby help reduce the patient's pain. The wave generator may also help provide a dynamic motion to the tissue that causes tissue to form with a certain orientation.

The wave generator, e.g., wave generator **110**, **200**, **300**, **400**, may be located at various locations. Depending on how rigid aspects of the dynamic, reduced-pressure treatment system are, the wave generator may need to be close to the tissue site or may be positioned further from the tissue site. Thus, if the maximum amplitude of the wave generator is not adequate for a given location, the wave generator may need to be moved closer, and if the maximum amplitude of the wave generator is more than adequate, the wave generator could be positioned further away from the tissue site. The compressibility of the fluid in the reduced-pressure delivery member will also be a factor in determining the position of the wave generator with respect to the tissue site.

It should be appreciated that the more incompressible the fluid in the reduced-pressure delivery member, e.g., the delivery member **144** in FIG. 1, the less energy required to deliver a certain amplitude for a wave, or alternatively, the further the wave generator **110** may be located from the tissue site **104** without expending any additional energy. To help make the fluid more incompressible for purposes of transmitting amplitude or for other reasons, the reduced-pressure delivery member **144** may be formed in such a way as to provide a segregated portion for the liquid and another portion for any gases. By segregating the fluid from any gases, a substantially incompressible fluid, or more incompressible fluid than would otherwise exist, may result and be utilized with the wave generator **110**. Moreover, segregating the more incompressible fluid portion may facilitate flow of fluids from the tissue site **104** toward the reduced-pressure subsystem **113** with a minimal risk of blockage. The reduced-pressure delivery conduit **144** may be formed in a number of ways to

achieve this desired performance, and illustrative, non-limiting embodiments are described below in connection with FIGS. 5-8.

Referring now primarily to FIG. 5, a reduced-pressure delivery member 500 may be formed as a conduit 502 that includes at least one lumen, e.g., first lumen 504, for transmitting a liquid (a substantially incompressible fluid), and at least one lumen, e.g., second lumen 506, for transmitting a gas. The first lumen 504 has a first interior space 508. The second lumen 506 has a second interior space 510 that is covered proximate a distal end 512 by a first liquid-impermeable-and-gas-permeable member 514. The liquid-impermeable-and-gas-permeable member 514 is operable to substantially restrict liquid while substantially allowing gas to enter. In addition to the first liquid-impermeable-and-gas-permeable member 514, which is located proximate the distal end 512, one or more additional liquid-impermeable-and-gas-permeable members 514 may be located at discrete locations on the interior of the second lumen 506 or disposed continuously throughout the second interior space 510 of the second lumen 506.

The first liquid-impermeable-and-gas-permeable member 514 may be made from any material that is liquid impermeable but gas permeable. The first liquid-impermeable-and-gas-permeable member 514 may be formed, as one non-limiting example, from a synthetic fluoropolymer such as a poly-tetrafluoroethylene material (PTFE). For the illustrative embodiment of FIG. 5, a third lumen 516 and a fourth lumen 518, which are both analogous to first lumen 504, are provided and are available to transmit a fluid. The lumens 504, 506, 516, 518 may be made of any fluid impermeable, flexible material, such as high-density polyethylene (HDPE), high impact polystyrene (HIPS), low-density polyethylene (LDPE), nylon, polycarbonate, polypropylene, polyethylene, polyvinyl chloride (PVC), urethanes, etc.

The first liquid-impermeable-and-gas-permeable member 514 substantially restricts entry of liquid while permitting entry of gas into the second lumen 506. Liquids may enter the first lumen 504 (and lumens 516 and 518). The liquid in the first lumen 504 (or lumens 516 and 518) may be used with a wave generator to transmit a wave or may be used to efficiently remove fluids. The wave generator, e.g., wave generator 110 in FIG. 1, may be fluidly coupled to the first interior space 508 of the first lumen 504 and may also be fluidly coupled to the third lumen 516 and the fourth lumen 518. Thus, the wave generated by the wave generator is delivered through the liquid, or incompressible fluid, in the first lumen 504 or other lumens.

Referring now primarily to FIG. 6, another illustrative, non-limiting embodiment of a reduced-pressure delivery member 600 is presented. The reduced-pressure delivery member 600 may be formed as a conduit 602 that includes at a first lumen 604 for transmitting a liquid and a second lumen 606 for transmitting gases. The first lumen 604 has a first interior space 608. The second lumen 606 has a second interior space 610 that is covered proximate a distal end 612 by a first liquid-impermeable-and-gas-permeable member 614, which is operable to substantially restrict liquid while substantially allowing gas to enter. In addition to the first liquid-impermeable-and-gas-permeable member 614, additional liquid-impermeable-and-gas-permeable members may be distributed at discrete locations or continuously throughout the second interior space 610 of the second lumen 606. The first liquid-impermeable-and-gas-permeable member 614 may be made from the same material as the first liquid-impermeable-and-gas-permeable member 514 in FIG. 5. The lumens 604 and 606 may be made of any fluid impermeable, flexible material. A wave generator, e.g., wave generator 110 in FIG. 1, may be fluidly coupled to the first lumen 604 for imparting a wave.

Referring now primarily to FIG. 7, another illustrative, non-limiting embodiment of a reduced-pressure delivery member 700 is presented. The reduced-pressure delivery member 700 may be formed as a conduit 702 that includes a first lumen 704 for transmitting gases (substantially compressible fluid), e.g., air, and a second lumen 706 for transmitting a liquid (substantially incompressible fluid). The first lumen 704 has a first interior space 708. In this illustrative embodiment, a third lumen 710 and a fourth lumen 712 are provided for transmitting a gas.

The first lumen 704, third lumen 710, and fourth lumen 712 are spaced and concentrically disposed about the second lumen 706. The second lumen 706 is disposed within an interior space of the other lumens 704, 710, 712 and defines an interior conduit therein. An exterior wall 714 of the conduit 702, which makes up the exterior walls of the first lumen 704, third lumen 710, and fourth lumen 712, is made from a fluid impermeable, flexible material, such as the materials previously mentioned. The exterior wall 716 of the second lumen 706 is made from a liquid-impermeable-gas-permeable material, such as a synthetic fluoropolymer, e.g., a poly-tetrafluoroethylene material (PTFE). The exterior wall 716 of the second lumen 706 is also an interior wall of the first lumen 704, third lumen 710, and fourth lumen 712. In one illustrative embodiment, the first lumen 704 may be a 360 degree conduit with a first interior space into which the second lumen 706 is inserted.

As fluid is pulled through the second lumen 706 of the reduced-pressure delivery member 700, gases are free to pass through the exterior wall 716 of the second lumen 706 as suggested by arrows 717 and into the first lumen 704, third lumen 710, or fourth lumen 712. As such, the fluid remaining within the second lumen 706 contains less gas and is therefore more incompressible. As previously noted, a wave generator may more easily or efficiently impart a wave on the fluid when the fluid is more incompressible, and a wave generator, e.g., wave generator 110 in FIG. 1, may be fluidly coupled to the first lumen 704 or lumens 710 and 712 for imparting a wave thereto.

The systems and methods herein may allow reduced-pressure treatment of a tissue site with dynamic pressure or energy that preferably allows high frequency variation and controls the pressure or energy wave amplitude. Moreover, it does so with reliability and with minimal energy requirements.

Although the subject matter of the present disclosure has been described in the context of certain illustrative, non-limiting embodiments, various changes, substitutions, permutations, and alterations can be made without departing from the scope of this disclosure as defined by the appended claims. Any feature described in a connection to any one embodiment may also be applicable to any other embodiment.

What is claimed is:

1. A reduced-pressure treatment system for treating a tissue site comprising:
 - a reduced-pressure delivery member for delivering reduced pressure to the tissue site, the reduced-pressure delivery member adapted to transmit liquid and gas from the tissue site;
 - a liquid-impermeable-and-gas-permeable member adapted to substantially segregate the liquid into a separate liquid flow and the gas into a separate gas flow; and
 - a wave generator in fluid communication with the separate liquid flow, wherein the wave generator imparts a wave to the liquid.
2. The reduced-pressure treatment system of claim 1, wherein the wave generator is coupled to the reduced-pressure delivery member in fluid communication between a reduced-pressure source adapted to provide the reduced pres-

11

sure and a sealing member, the sealing member adapted to provide a fluid seal between the sealing member and the tissue site.

3. The reduced-pressure treatment system of claim 1, wherein the wave generator comprises a piezoelectric transducer in fluid communication with the reduced-pressure delivery member.

4. The reduced-pressure treatment system of claim 1, wherein the wave generator comprises a diaphragm member in fluid communication with the reduced-pressure delivery member.

5. The reduced-pressure treatment system of claim 1, wherein the wave generator comprises a plurality of chambers with valves, and wherein each of the chambers is selectively in fluid communication with the reduced-pressure delivery member.

6. The reduced-pressure treatment system of claim 1, wherein the reduced-pressure delivery member comprises a conduit, and wherein the conduit comprises:

a first lumen for transmitting the liquid, the first lumen having a first interior space;

a second lumen for transmitting the gas, the second lumen having a second interior space;

wherein the liquid-impermeable-and-gas-permeable member is coupled to the second lumen in at least a portion of the second interior space; and

wherein the wave generator is in fluid communication with the first lumen.

7. The reduced-pressure treatment system of claim 1, wherein the reduced-pressure delivery member comprises:

a first lumen for transmitting the gas, the first lumen having a first interior space;

a second lumen for transmitting the liquid, the second lumen having a second interior space;

the first lumen comprising a fluid impermeable material; and

the second lumen formed from the liquid-impermeable-and-gas-permeable member and disposed within the first interior space.

8. The reduced-pressure treatment system of claim 1, wherein the reduced-pressure delivery member comprises:

an outer lumen having a first interior space and formed from a fluid impermeable material, wherein the first interior space comprises a liquid flow path;

an inner flow member comprising a lumen formed from the liquid-impermeable-and-gas-permeable member and disposed within the first interior space; and

wherein the wave generator is in fluid communication with the liquid flow path.

9. A method of manufacturing a reduced-pressure treatment system for treating a tissue site, comprising:

providing a reduced-pressure delivery member for delivering reduced pressure to the tissue site, the reduced-pressure delivery member comprising a first lumen and a second lumen;

segregating the first lumen from the second lumen with a liquid-impermeable-and-gas-permeable member, the liquid-impermeable-and-gas-permeable member adapted to substantially preclude liquid from entering the second lumen to provide a liquid flow in the first lumen and a gas flow in the second lumen; and

coupling a wave generator in fluid communication with the first lumen, the wave generator for imparting a wave to the liquid flow in the first lumen.

12

10. The method of manufacturing of claim 9, wherein coupling the wave generator with the first lumen comprises coupling the wave generator to the reduced-pressure delivery member in fluid communication between a reduced-pressure source for developing the reduced pressure and a sealing member operable to form a fluid seal over the tissue site.

11. The method of manufacturing of claim 9, wherein the wave generator comprises a piezoelectric transducer fluidly coupled to the reduced-pressure delivery member.

12. The method of manufacturing of claim 9, wherein the wave generator comprises a diaphragm member fluidly coupled to the reduced-pressure delivery member.

13. The method of manufacturing of claim 9, wherein the wave generator comprises:

a plurality of valves in fluid communication with the reduced-pressure delivery member;

a plurality of chambers associated with the plurality of valves; and

wherein the plurality of valves are operable to selectively open and close to generate a wave in the reduced-pressure delivery member.

14. The method of manufacturing of claim 9, wherein the liquid-impermeable-and-gas-permeable member is coupled to the second lumen in at least a portion of an interior space within the second lumen;

wherein the liquid-impermeable-and-gas-permeable member comprises a synthetic fluoropolymer; and wherein the synthetic fluoropolymer comprises a polytetrafluoroethylene material (PTFE).

15. The method of manufacturing of claim 9, wherein the second lumen comprises a gas-and-liquid-impermeable material;

wherein the first lumen comprises the liquid-impermeable-and-gas-permeable member disposed within an interior space within the second lumen;

wherein the liquid-impermeable-and-gas-permeable member comprises a synthetic fluoropolymer; and wherein the synthetic fluoropolymer comprises a polytetrafluoroethylene material (PTFE).

16. A method for treating a tissue site, comprising: providing reduced pressure to the tissue site;

substantially segregating liquid and gas carried by the reduced pressure from the tissue site into a separate liquid flow and a separate gas flow; and

coupling a wave generator in fluid communication with the separate liquid flow for imparting a wave to the liquid flow.

17. The method of claim 16, wherein coupling a wave generator comprises fluidly coupling the wave generator to a reduced-pressure delivery member in fluid communication between a reduced-pressure source for providing the reduced pressure and a sealing member adapted to form a fluid seal over the tissue site.

18. The method of claim 16, wherein the wave generator comprises a piezoelectric transducer in fluid communication with the reduced-pressure delivery member.

19. The method of claim 16, wherein the wave generator comprises a diaphragm member in fluid communication with the reduced-pressure delivery member.

20. The method of claim 16, wherein the wave generator comprises a plurality of chambers with valves and wherein each of the chambers selectively in fluid communication with the reduced-pressure delivery member.

* * * * *