



US010105862B1

(12) **United States Patent**
Koch et al.

(10) **Patent No.:** **US 10,105,862 B1**
(45) **Date of Patent:** **Oct. 23, 2018**

(54) **FENESTRATED GRAFT PRESS CUTTING DIE ASSEMBLY**

(71) Applicant: **BioCut, LLC**, Milwaukee, WI (US)

(72) Inventors: **Jared Koch**, Milwaukee, WI (US);
John Reimer, Wauwatosa, WI (US);
Eric Schmitt, Sussex, WI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 105 days.

(21) Appl. No.: **15/475,530**

(22) Filed: **Mar. 31, 2017**

(51) **Int. Cl.**
B26D 1/06 (2006.01)
A61F 2/10 (2006.01)

(52) **U.S. Cl.**
CPC **B26D 1/065** (2013.01); **A61F 2/105** (2013.01)

(58) **Field of Classification Search**
CPC **B26D 1/065**; **A61F 2/105**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,313,801 A	3/1943	Carl	
2,495,221 A	1/1950	Berlin	
2,703,023 A	3/1955	Sarno	
2,821,871 A	2/1958	Sarno	
2,939,347 A	6/1960	Tobey	
3,020,785 A	2/1962	Leavesley et al.	
3,048,069 A	8/1962	Berlin et al.	
3,120,601 A	2/1964	Berlin et al.	
3,152,492 A *	10/1964	Whitecotton B21D 37/205 76/107.8
3,182,530 A *	5/1965	Scott B26F 1/00 493/338

3,194,090 A	7/1965	Becker	
3,228,263 A	1/1966	Bien	
3,292,461 A	12/1966	Bien	
3,383,969 A	5/1968	Saunders	
3,396,620 A *	8/1968	Raphael B21D 37/205 76/107.8
3,587,377 A *	6/1971	Olson B26D 7/10 219/601
3,737,365 A	6/1973	Smith	
3,786,732 A *	1/1974	Forbes, Jr. B26F 1/44 493/354
3,835,746 A	9/1974	Young, Jr. et al.	
3,941,038 A *	3/1976	Bishop B26D 7/2614 493/371
4,052,886 A *	10/1977	Buick B26F 1/44 493/468
4,226,143 A	10/1980	Whitecotton et al.	
4,249,432 A *	2/1981	Graboyes B23P 15/406 76/107.8
4,598,206 A *	7/1986	Nelson G01J 5/522 250/494.1


(Continued)

Primary Examiner — Sean Michalski

(57) **ABSTRACT**

An assembly and method of forming a press cutting die assembly that is configured to perforate a tissue graft blank during cutting of the blank from a bulk graft material. The press cutting die assembly includes a frame, a perimeter blade, and a plurality of fenestration blades that extend between respective portions of the perimeter blade. In a preferred embodiment, the plurality of fenestration blades are provided in at least two groups to form a repeating pattern of preferably uniformly spaced perforations within the perimeter of the blank. Such a press cutting die assembly is particularly applicable for cutting biologically compatible materials having a desired shape and uniform fenestration pattern from a bulk source of the biologically compatible material.

20 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,140,872	A	8/1992	Holliday et al.	
5,211,084	A *	5/1993	Holliday	B26F 1/44
				219/121.67
5,943,935	A *	8/1999	Brayton	B26F 1/44
				493/354
6,189,414	B1 *	2/2001	Yoshizawa	B23P 15/406
				76/107.8
6,626,965	B2	9/2003	Workman et al.	
6,889,588	B1	5/2005	Jenkins	
2005/0197699	A1 *	9/2005	Jacobs	A61F 2/0811
				623/13.14
2007/0183974	A1 *	8/2007	Pearlman	A61B 17/322
				424/9.1
2011/0251602	A1 *	10/2011	Anderson	A61B 17/32093
				606/13
2013/0085570	A1 *	4/2013	Rose	B26F 1/24
				623/15.12
2015/0059544	A1 *	3/2015	Ohnishi	B26D 1/0006
				83/168
2015/0140058	A1 *	5/2015	Tumey	A61L 27/56
				424/423
2015/0151531	A1 *	6/2015	Ohno	B32B 43/006
				156/755
2015/0327699	A1 *	11/2015	Habib	B65D 81/2015
				206/234
2016/0221206	A1 *	8/2016	Jeske	B26F 1/40
2017/0165859	A1 *	6/2017	Kropf	B26D 1/065

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 7




FIG. 8

FENESTRATED GRAFT PRESS CUTTING DIE ASSEMBLY

FIELD OF THE INVENTION

The present invention relates generally to press cutting dies and, more particularly, to a press cutting die assembly that is constructed of medical grade materials and which fenestrates a graft tissue blank during cutting of the tissue graft blanks from bulk graft material.

BACKGROUND OF THE INVENTION

As commonly understood, skin or other tissue grafting processes commonly involve the transplanting of a section of tissue to an injury or other anatomical abnormality associated with damage to or a loss of tissue. Some grafting processes involve the transplantation of a section of tissue from one area of a patient to another area of a patient. Other grafting processes, such as allogeneic grafts (where donors and recipients are the same species), xenogeneic grafts (where donors and recipients are different species, such as porcine grafts), and prosthetic grafts (which include synthetic graft materials); can commonly be effectuated by cutting a graft from a sheet of graft material and subsequently applying the cut graft to the intended graft location. Various considerations must be addressed when forming grafts in such a manner.

One consideration to graft preparation relates to providing a sanitary condition associated with the entire process of forming each discrete tissue graft. Failure to properly attend to the sanitation of the process can result in contamination between the various devices associated with the cutting process, the blank materials, as well as already cut graft materials. Still further, inadequate attention to sanitary conditions can result in cross-contamination between already cut grafts, subsequent blank materials, and even subsequent material lots. Accordingly, devices associated with such tissue cutting processes must commonly be disposable and/or constructed to withstand periodic exposure to a suitable sanitation process to mitigate contamination between respective grafts.

Whether provided in a disposable or reusable configuration, another consideration that must be addressed during die formation is the suitability of the materials associated with forming or defining the die as being suitable for exposure to materials or tissues which are ultimately intended to be associated with and supported by a host body. That is, the die assembly and generation of the grafts preferably does not transfer materials that are ill-suited and/or dangerous for biological applications to the grafts.

Another consideration of the press cut generation of tissue grafts relates to providing a graft product that can satisfy generally uniform or repeatable size parameters. In order to press cut graft materials, a cutting edge defined by a press die must be maintained in a generally planar arrangement such, that the cutting edge can pass through the graft material in a substantially orthogonal direction relative to the exposed surface plane of the material to generate grafts that are of substantially the same size and which maintain a robust graft edge for subsequent cooperation adjacent tissue of an underlying patient. Movement of the cutting edge relative to an underlying blade support or deviation of the blade during die formation and/or sterilization process can result in a die configuration that is susceptible to incomplete cut operations or undesirable cut profiles. Such shortcom-

ings can detract from a repeatable generation of a uniform graft product and/or decrease the efficiency with which grafts can be created.

Still further considerations associated with graft production relate to improving the acceptance or integration of the graft during healing. Commonly, graft tissue blanks are prepared, during or immediately prior to use, by meshing, also called fenestration. During fenestration, small perforations, slits, or cuts are formed in the donor tissue. These fenestrations allow the donor graft to be stretched thereby increasing the surface area of the donor graft and reducing the amount of graft material needed to reconstruct damaged dermis. In autograft processes, such considerations reduce the trauma and scarring associated with the donor area and allows the donor area to heal more quickly than it would if more graft tissue were harvested.

Fenestration of graft material also improves healing of the wound area. The perforations, and openings associated therewith due to stretching of the donor graft material, increases the amount of graft perimeter available for capillary pass-through and connection with other vessels. The openings associated with the fenestrations also allows fluids produced by the wound during healing to drain thereby mitigating capture of the fluid which may lead to infection between the graft and the wound.

Donor graft material is commonly fenestrated manually through the use of either a scalpel or by passing the donor graft tissue through a mechanical mesher. Such approaches have various drawbacks. Manually meshing the graft tissue with a scalpel can be tedious and requires the time and skill of highly qualified technicians. Even with the most skilled technicians, such processing often produces a less than uniform fenestration pattern which can result in undesired tearing and/or non-uniform presentation of the openings associated with the fenestrations when the graft tissue is stretched during use. Although mechanical meshers tend to mitigate some of the concerns associated with uniform fenestration production, use of such machines present their own complications associated with production of the desired fenestrated graft tissue.

Mechanical meshes commonly rely on using opposing rollers that flatten and perforate the graft tissue as it is passed therethrough. Such treatment of the donor graft tissue is unduly aggressive and can result in blemishes such as pock marks or the like in healed tissue. Such blemishes, depending on the severity and patient location, commonly require additional cosmetic surgery to resolve. Still further, donor graft tissue can commonly become torn or entangled when passed through such mechanical meshes. The severity of the damage to the tissue can render the graft tissue unusable for its intended purpose and effectively wasting the same. Such considerations are particularly problematic during autograft processes. Still further, during mechanical meshing, small particles of biological material may separate from the graft and remain adhered to the mesher thereby complicating the ability to maintain the desired level of sanitation associated with the same. Still further, both manual fenestration and utilization of mechanical meshers require clean room levels of sterilization yet further increasing costs associated with production of the same.

Accordingly, it would be desirable to have an assembly and method for generating fenestrated graft tissue blanks in a more uniform, sanitary, and conveniently implemental manner. The present invention discloses a press cut die

3

assembly and method of forming a die assembly for generating fenestrated graft tissue blanks.

BRIEF DESCRIPTION OF THE INVENTION

The present invention provides a press cutting die assembly and method of forming a press cutting die assembly that overcomes one or more of the drawbacks mentioned above. One aspect of the application discloses a press cutting die assembly that is configured to perforate a blank during cutting of the blank from a bulk material. The press cutting die assembly includes a frame, a perimeter blade assembly, and a plurality of graft field perforation blades that extend between respective portions of the perimeter blade assembly. In a preferred aspect, the plurality of perforation blades are provided in at least two groups to form a repeating pattern of preferably uniformly spaced perforations within the perimeter of the graft blank.

Another aspect of the application discloses a press cutting die assembly that includes a frame that is configured to support a blade stack. The blade stack includes a perimeter blade assembly that is configured to circumscribe a cut area and defines a cutting edge that extends beyond the frame in a cutting direction. A plurality of fenestration blades are oriented to extend across the cut area circumscribed by the perimeter blade. A plurality of cutouts are formed in a cutting edge of at least a plurality of, and preferably each of, the plurality of fenestration blades.

A further aspect of the application discloses a fenestrated tissue graft press cutting die assembly that includes a first edge blade and a second edge blade that each include a continuous cutting edge configured to sever a material, being cut. A plurality of field blades are disposed between the first edge blade and the second edge blade. Each field blade has a discontinuous cutting edge formed along at least a portion of a longitudinal edge of the respective field blade such that the field blades perforate an area of the material being cut which is circumscribed by the continuous cutting edge.

Yet another aspect of the application discloses a method of forming a press cutting die assembly. The method includes providing a perimeter blade assembly that is configured to circumscribe a cut area. A plurality of fenestration blades are provided that extend between the perimeter blade assembly. Each of the fenestration blades includes a discontinuous cutting edge that generates a generally uniform perforation pattern within the cut area bounded by the perimeter blade.

It is appreciated that the aspects and features of the application summarized above are not limited to any one particular embodiment of the invention. That is, many or all of the aspects above may be achieved with any particular embodiment of the invention. Those skilled in the art will appreciate that the invention may be embodied in a manner preferential to one aspect or group of aspects and advantages as taught herein. These and various other aspects, features, and advantages of the, present invention will be made apparent from the following detailed description and the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings illustrate a preferred embodiment presently contemplated for carrying out the invention. In the drawings:

FIG. 1 is an cutting side perspective view of a press cutting die assembly according to the present invention;

4

FIG. 2 is an edge side elevation view of the press cutting die assembly shown in FIG. 1;

FIG. 3 is an end side elevation view of the press cutting die assembly shown in FIG. 1;

FIG. 4 is an exploded perspective view of the press cutting die assembly shown in FIG. 1;

FIG. 5 is a perspective view of a portion of a blade stack of the press cutting die assembly shown in FIG. 1;

FIG. 6 is a cross section view of the, press cutting die assembly shown in FIG. 1 taken along line 6-6 shown in FIGS. 2 and 3;

FIG. 7 is a perspective view of a graphical representation of the press cutting die assembly shown in FIG. 1 associated with a section of graft tissue; and

FIG. 8 is a top plan view of a portion of a press cut graft tissue blank formed by the press cutting die shown in FIG. 1 when subjected to radially outward directed tension forces.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIG. 1 shows a press cutting die assembly 10 according to the present invention. Referring to FIGS. 1-3, die assembly 10 includes a base or frame 12 that is constructed to support a blade assembly 14 relative thereto. Frame 12 is defined by a body 16 that defines a cavity, recess, or blade window 18 associated with supporting blade assembly 14 relative thereto. Body 16 includes end portions 20, 22 and edge portions 24, 26 that are continuous or constructed to cooperate with one another to generally surround blade window 18.

A first side 28 of frame 12 is associated with a cutting side 30 of die assembly 10 and blade assembly 14. As commonly understood, the cutting side 30 of die assembly 10 is associated with the lateral side of die assembly 10 that is constructed to be introduced to a cutting material and effectuate the cutting operation as a cutting edge side of blade assembly 14 is passed therethrough. An opposing side 32 of frame 12 faces in a generally opposite lateral direction. As disclosed further below with respect to FIG. 4, cutting die assembly 10 includes one or more fasteners 34, 36, 38, 40 that cooperate with edge portions 24, 26 of frame 12 and pass through blade window 18 and cooperate with blade assembly 14 positioned therein.

One or more adjusters 42, 44, 46 cooperate with respective end portions 20, 22 of frame 12 and cooperate with a spacer or crowder 48, 50 disposed proximate the respective end portion 20, 22 of frame 12. As explained further below with respect, to FIGS. 4-6, fasteners 34, 36, 38, 40; adjusters 42, 44, 46; and crowdiers 48, 50 cooperate with frame 12 and blade assembly 14 to maintain a generally orthogonal and contacting or compressing orientation of respective portions of blade assembly 14 relative to one another and frame 12 as described further below.

Still referring to FIGS. 1-3, blade assembly 14 includes a pair of edge blades 54, 56 that extend along the generally opposite longitudinal edges of blade assembly 14 and a pair of end blades 58, 60 that extend along the generally opposite lateral edges or ends of blade assembly 14. Each of edge blades 54, 56 and end blades 58, 60 include a cutting edge 64 defined by the respective blade 54, 56, 58, 60. Although shown as discrete edge and end blade portions, it is appreciated that the edge and end blade portions could be formed by a generally continuous blade member wherein discrete sections of the blade member are bent relative to one another so as to extend in generally crossing directions relative to one another. Regardless of the formation methodology

5

employed, the cutting edges **64** defined by blades **54, 56, 58, 60** circumscribe an area to be cut from a graft material is described further below with respect to FIG. 7. As shown in FIGS. 2 and 3, a plane, indicated by line **70**, is defined by cutting edge **64** and is oriented to be offset, as indicated by dimension arrows **72**, from the surface associated with cutting side **28** of frame **12**. Such a consideration allows blades **54, 56, 58, 60** to be pressed through a material to be cut without interference and/or contact of frame **12** with the cut material.

Referring to FIG. 4, press die assembly **10** includes a blade stack **76** that is constructed to be disposed between end blades **58, 60**. It should be appreciated that the orientation of press die assembly **10** shown in FIG. 4 is from the opposite or non-cutting side **32** of frame **12** of assembly **10** as compared to the cutting side shown in FIG. 1. It should be further appreciated that blade stack **76** has been expanded merely for illustration purposes. When assembled, the respective components of blade stack **76**, as described further below with respect to FIG. 5, are configured to be oriented in adjacent or touching proximity relative to one another and such that blade stack **76** can be oriented substantially between end blades **58, 60** with the respective longitudinal ends of each discrete portion of the blade stack **76** in close if not touching proximity relative to the adjacent respective end blade **58, 60**.

Still referring to FIG. 4, an interior of blade window **18** facing surface **78, 80** of portions **20, 22** of frame **12** includes opposing channels **84, 86** that are shaped to generally match a contour **88** associated with a frame facing side **90** of an adjacent spacer or crowder **48, 50**. When fully assembled, crowders **48, 50** are oriented in close or overlapping proximity to the respective portions **20, 22** of frame **12**. Adjusters **42, 44, 46** cooperate with respective threaded cavities **94** defined by frame **12**. Adjusters **42, 44, 46** cooperate with respective threaded cavities **94** such that crowders **48, 50** can be oriented in a generally orthogonal or perpendicular orientation relative to edge portions **24, 26** defined by frame **12** and the blade stack **76** associated therewith. Crowdres **48, 50** further effectuate a desired longitudinal alignment between each of edge blades **54, 56** and the respective components of blade stack **76** as disclosed further below.

Each of fasteners **34, 36, 38, 40** includes an elongated body **100** having a threaded portion **102** disposed at one end thereof and a head portion **104** associated with the opposite end thereof. Elongated body **100** of each fastener is constructed to slidably cooperate with a respective opening **106** associated with frame **12**, traverse blade window **18**, slidably cooperate with a respective sleeve **108**, and engage a nut **110** via threaded portion **102**. Fasteners **34, 36, 38, 40**; respective sleeves **108**; respective nuts **110**; and frame **12** are constructed to allow fasteners to maintain a contact engagement between the adjacent structures associated with blade stack **76** when die assembly **10** is assembled as disclosed further below with respect to FIG. 6.

As shown in FIG. 5, blade stack **76** includes edge blades **54, 56** that are disposed along the opposite longitudinal edges thereof. Between edge blades **54, 56**, blade stack **76** includes a plurality of perforation, field, or fenestration blades **116**. Each fenestration blade **116** defines a discontinuous cutting edge **118** that extends along the longitudinal edges thereof. The discontinuous cutting edge **118** associated with each fenestration blade **116** includes a gap or cutout **120** that is disposed between adjacent cutting portions **122** along the longitudinal length of the respective discontinuous cutting edge **118**. When assembled, cutting portions **122** of each cutting edge **118** associated with each fenestra-

6

tion blade lies in plane **70** associated with the continuous cutting edge defined by edge and end blades **54, 56, 58, 60**.

In a preferred embodiment, the length associated with each discrete cutting portion **122** and discrete cutout **120** of each fenestration blade **116** extend a generally similar distance relative to one another along the respective fenestration blade **116**. It is appreciated that the geometry associated with the cutting portions **122** and cutouts **120** associated with fenestration blades **116** could be provided in various geometries. Fenestration blades **116** are further segregated into a first group or set of blades **124** and a second group or set of blades **126**. Referring to FIGS. 1 and 5 and comparing the respective cutting edge **118** of a first group fenestration blade **124** relative to the cutting edge **118** of a second group fenestration blade **126**, it should be appreciated that the cutting portion **122** of a first group fenestration blade **124** is generally aligned with a cutout **120** associated with a second group fenestration blade **126** when considered in the stacked direction. It should further be appreciated that the cutting portions **122** and cutouts **120** of the first group of fenestration blades **124** are aligned with one another in the stack direction and the cutting portion **122** and the cutouts **120** of the second group of fenestration blades **126** are aligned with one another in the stack direction. Although the discrete cutting portions and cutouts associated with the discrete groups of fenestration blades are aligned with the other blades in the same group in the stack direction, discrete cutting portions **122** and cutouts **120** associated with the first group fenestration blades **124** are offset in the longitudinal directions, indicated by arrow **128**, relative to the respective to the discrete cutting portions **122** and cutouts **120** associated with each second group fenestration blade **126**. Such a consideration produces a repeating and substantially uniform staggered pattern of each discrete fenestration within the boundary of the edge and end blades **54, 56, 58, 60** of die assembly **10**.

Still referring to FIG. 5, a spacer **130** is disposed between adjacent fenestration blades **116** as well as respective edge blades **54, 56** and an adjacent fenestration blade **116**. Preferably, each spacer **130** is provided to have a uniform thickness in the stack direction and a depth such that no portion of a respective spacer **130** extends beyond a bottom **132** associated with each discrete cutout **120** of an adjacent fenestration blade **116**. Each of edge blades **54, 56**, fenestration blades **116**, and spacers **130** associated with blade stack **76** includes a plurality of openings **136** configured to accommodate the slidable passage of the elongate body **100** of a respective fasteners **34, 36, 38, 40** therethrough as disclosed further below with respect to FIG. 6. As mentioned above, when fully assembled, the cutting portions **122** of each fenestration blade **116** is oriented to lie in plane **70** associated with the cutting edge **64** of edge blades **54, 56** and end blades **58, 60**. Such considerations ensure that the cutting portion **122** associated with each fenestration blade **116** forms a cut, hole, or perforation in the graft tissue and that all but those perforations formed by the cutting portions **122** of the fenestration blades that lie adjacent the end blades **58, 60** are circumferentially bounded by the graft tissue. Such a consideration ensures generally uniform propagation of the fenestration pattern across the entirety of the graft blank as disclosed further below with respect to FIGS. 7 and 8.

As shown in FIG. 6, when assembled, blade stack **76** is bounded or circumscribed by edge blades **54, 56** and end blades **58, 60**. Fenestration blades **116** extend in a longitudinal direction between end blades **58, 60**. When considered in the stack direction, fenestration blades **116** are oriented in

a generally repeating pattern inboard of a respective edge blade **54**, **56** wherein the pattern propagates in a pattern of a respective spacer **130**, a respective one of first or second group fenestration blades **124**, **126**, another spacer **130**, and a respective one of the other of first or second group fenestration blades **124**, **126**. Such a pattern repeats in the lateral or stack direction relative to blade stack **76** to the opposing edge blade **56** and the respective spacer **130** that is disposed adjacent to the opposing edge blade **56**. Although disclosed as repeating in a pattern associated with two respective first and second group of fenestration blades **124**, **126** as designated by their respective cutting edges, it is appreciated that the fenestrations could be provided in virtually any pattern via manipulation of the number of sets of fenestration blade groups and/or the pattern associated with the cutouts **120** and cutting edges **122** associated therewith.

Referring to FIGS. **7** and **8**, die assembly **10** is constructed to cut and fenestrate a graft tissue blank **140** each time blade assembly **14** is pressed into a bulk graft material sheet **144**. FIG. **7** shows an exemplary press cutting process associated with use of die assembly **10**. As shown in FIG. **7**, during press cutting operations, a blank material, such as a graft material **144**, is associated with a platen or other support structure **146**. Each introduction of blade assembly **14** of die assembly **10** to the graft material **144**, and downward translation of the same, indicated by arrow **148**, cuts and fenestrates a respective graft or graft blank **140** from the sheet material **144** and leaves a cutout **150** associated with each graft blank **140** that is removed from material **144**. It should be appreciated that the shape of die assembly **10**, and particularly the cutting edge associated therewith, will commonly dictate the most efficient consumption or usage of the blank material **144** to generate the desired fenestrated graft blanks **140** therefrom. Although suitable for cutting fenestrated grafts **140**, it is further appreciated that die assembly **10** can be utilized to cut various other materials such as bandages, human or other animal organs, as well as other materials used in medical environments such as wet bandages, wet gauzes, placentas, etc. where fenestration of the underlying material is desired.

It is appreciated that fenestrated grafts **140** can be removed manually from die assembly **10** or extracted in other manners, such as via a blower or vacuum extraction, to remove the cut and fenestrated grafts **140** from die assembly **10**. Preferably, each of end and edge blades **54**, **56**, **58**, **60** and fenestration blades **116** are oriented orthogonally parallel or perpendicular to frame **12** and the respective cutting edges associated with each of the perimeter and fenestration or field blades is preferably maintained in a plane that is parallel to frame **12** such that each graft cutting operation results in a circumferential severing of the fenestrated graft **140** cut from bulk material **144**. Such a consideration reduces the potential that a supplemental cut operation will be required to effectuate fall separation between the respective grafts from the bulk graft material.

Die assembly **10** and the plurality of perimeter and field or fenestration blades associated therewith provide a press cutting die assembly that can be economically produced, is robust, does not adversely affect the sanitation of the materials to which it is applied, and produces fenestrated graft blanks that are ready for use without supplemental fenestration. As shown in FIG. **8**, when subjected to radially outward directed tension forces in the plane associated with the fenestrated graft blanks **140**, as indicated by arrows **154**, the uniformity of the formation of the fenestrations allows each graft to be stretched without failure of the boundary

associated with any discrete fenestration opening **156** thereby improving healing associated with the same. It has been shown that fenestrated graft blanks produced with die assembly **10** can be stretched 3-4 times per unit of donor tissue. Die assembly **10** is sufficiently robust to tolerate subsequent sanitation and disinfectant processes and economically producible so as to tolerate periodic disposable and replacement of the die assembly. Die assembly **10** further mitigates the shortcomings of current graft fenestration processes as disclosed above.

Therefore, one embodiment of the invention includes a press cutting die assembly that includes a frame that is configured to support a blade stack. The blade stack includes a perimeter blade assembly that is configured to circumscribe a cut area and defines a cutting edge that extends beyond the frame in a cutting direction. A plurality of fenestration blades are oriented to extend across the cut area circumscribed by the perimeter blade. A plurality of cutouts are formed in a cutting edge of at least a plurality of, and preferably each of, the plurality of fenestration blades portions.

A further embodiment of the invention that is useable or combinable with one or more of the features or aspects of the other embodiments of the invention includes a fenestrated tissue graft press cutting die assembly. The press cutting die assembly includes a first edge blade and a second edge blade that each include a continuous cutting edge that is configured to sever a material being cut. A plurality of field blades are disposed between the first edge blade and the second edge blade. Each field blade has a discontinuous cutting edge formed along at least a portion of longitudinal edge of the respective field blade such that the field blades perforate an area of the material being cut that is circumscribed by the continuous cutting edge.

Yet another embodiment of the invention that is combinable or usable with one or more of the features or aspects of the above embodiments includes a method of forming a press cutting die assembly. The method includes providing a perimeter blade assembly that is configured to circumscribe a cut area. A plurality of fenestration blades are provided that extend between the perimeter blade assembly. Each of the fenestration blades includes a discontinuous cutting edge that generates a generally uniform perforation pattern within the cut area bounded by the perimeter blade. The present invention has been described in terms of the preferred embodiments, and it is recognized that equivalents, alternatives, and modifications, aside from those expressly stated, are possible and within the scope of the appending claims. It is further appreciated that the respective features of any one of the embodiments discussed above is not necessarily solely exclusive thereto.

What is claimed is:

1. A press cutting die assembly, the assembly comprising: a frame configured to support a blade stack; and the blade stack comprising:

a perimeter blade configured to circumscribe a cut area and having a cutting edge that extends beyond the frame in a cutting direction;

a plurality of fenestration blades oriented to extend across the cut area circumscribed by the perimeter blade; and

a plurality of cutouts formed in a cutting edge of a plurality of the plurality of fenestration blades portions.

2. The assembly of claim **1** wherein the plurality of fenestration blades include a first set of fenestration blades and a second set of fenestration blades and the plurality of

9

cutouts associated with the cutting edge of the first set of fenestration blades is offset from the plurality of cutouts associated with the cutting edge of the second set of fenestration blades relative to adjacent respective fenestration blades.

3. The assembly of claim 1 further comprising a spacer disposed between adjacent blades of the plurality of fenestration blades.

4. The assembly of claim 1 further comprising an end plate supported by the frame and disposed at an end of the blade stack.

5. The assembly of claim 4 further comprising another end plate supported by the frame and disposed at an opposite end of the blade stack.

6. The assembly of claim 5 wherein at least one of the end plate and another end plate are adjustable relative to the frame.

7. The assembly of claim 1 further comprising at least one fastener that passes through the blade stack in a lateral direction and traverses the cut area such that opposing ends of the at least one fastener cooperate with the frame.

8. The assembly of claim 7 further comprising a plurality of fasteners that pass through the blade stack in the lateral direction wherein opposing ends of each fastener cooperate with the frame.

9. A fenestrated tissue graft press cutting die assembly, the assembly comprising:

a first edge blade and a second edge blade that each include a continuous cutting edge configured to sever a material being cut; and

a plurality of field blades disposed between the first edge blade and the second edge blade, each field blade having a discontinuous cutting edge formed along at least a portion of longitudinal edge of the respective field blade such that each field blade perforate an area of the material being cut circumscribed by the continuous cutting edge.

10. The assembly of claim 9 further comprising a frame configured to support the first edge blade, the second edge blade, and the plurality of field blades relative to one another.

11. The assembly of claim 10 further comprising at least one fastener that passes through the plurality of field blades at a location offset from the discontinuous cutting edge.

10

12. The assembly of claim 10 further comprising an end plate disposed between the frame and a respective longitudinal end of each of the first edge blade, the second edge blade, and the plurality of field blades.

13. The assembly of claim 12 further comprising another end plate associated with an opposite respective longitudinal end of each of the first edge blade, the second edge blade, and the plurality of field blades.

14. The assembly of claim 13 further comprising at least one adjuster engaged with the frame and a respective one of the end plate and the another end plate.

15. The assembly of claim 9 wherein the plurality of field blades include a first group of field blades and a second group of field blades wherein the discontinuous cutting edge of each of the first group of field blades are aligned with one another and are staggered relative to the discontinuous cutting edge of each of the second group of field blades.

16. The assembly of claim 9 further comprising a spacer disposed between adjacent blades of the plurality of field blades.

17. The assembly of claim 9 further comprising a first end blade and a second end blade that are each oriented at crossing directions relative to the first edge blade and the second edge blade and each include a continuous cutting edge disposed in a common plane with the continuous cutting edge defined by the first edge blade and the second edge blade.

18. A method, of forming a press cutting die assembly, the method comprising:

providing a perimeter blade assembly configured to circumscribe a cut area; and

providing a plurality of fenestration blades that extend between the perimeter blade assembly and each include a discontinuous cutting edge that generates a perforation pattern within the cut area bounded by the perimeter blade.

19. The method of claim 18 further comprising a frame configured to maintain an orientation of the perimeter blade assembly and the plurality of fenestration blades relative to one another.

20. The method of claim 18 further comprising orienting the plurality of fenestration blades so that the perforation pattern is provided in at least two repeating patterns of perforations.

* * * * *