

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
26 May 2006 (26.05.2006)

PCT

(10) International Publication Number
WO 2006/054058 A1

(51) International Patent Classification:
C09K 8/02 (2006.01) C09K 8/52 (2006.01)

(21) International Application Number:
PCT/GB2005/004389

(22) International Filing Date:
14 November 2005 (14.11.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/991,228 17 November 2004 (17.11.2004) US

(71) Applicant (for all designated States except US): **HAL-LIBURTON ENERGY SERVICES, INC.** [US/US]; P.O. Box 1431, Duncan, OK 73533 (US).

(71) Applicant (for MW only): **WAIN, Christopher, Paul** [GB/GB]; A A Thornton & Co, 235 High Holborn, London WC1V 7LE (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **MUNOZ, Trinidad, Jr.** [US/US]; 701 Drexal Place, Duncan, OK 73533 (US).

(74) Agents: **WAIN, Christopher, Paul** et al.; A A Thornton & Co, 235 High Holborn, London WC1V 7LE (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHODS OF DEGRADING FILTER CAKES IN SUBTERRANEAN FORMATIONS

(57) Abstract: Methods of degrading filter cakes in subterranean formations are provided. An example of a method is a method of drilling a well bore in a subterranean formation. Another example of a method is a method of degrading a filter cake in a subterranean formation, the filter cake comprising an inorganic portion and an organic portion, and having been established in the formation by a well drill-in and servicing fluid that comprises a delayed-release acid component. An example of a composition is a well drill-in and servicing fluid.



WO 2006/054058 A1

METHODS OF DEGRADING FILTER CAKES IN SUBTERRANEAN FORMATIONS

BACKGROUND

The present invention relates to subterranean treatment operations, and more particularly, to methods of degrading filter cakes in subterranean formations.

Often, once drilling of a well bore in a subterranean formation has been initiated, a fluid referred to as a "well drill-in and servicing fluid" may be employed. As referred to herein, the term "well drill-in and servicing fluid" will be understood to mean a fluid placed in a subterranean formation, such as those from which production has been, is being, or may be cultivated. For example, an operator may begin drilling a subterranean borehole using a drilling fluid, cease drilling at a depth just above that of a productive formation, circulate a sufficient quantity of a well drill-in and servicing fluid through the bore hole to completely flush out the drilling fluid, then proceed to drill into the desired formation using the well drill-in and servicing fluid. Well drill-in and servicing fluids often may be utilized, *inter alia*, to minimize damage to the permeability of such formations.

Well drill-in and servicing fluids may include "fluid-loss-control fluids." As referred to herein, the term "fluid-loss-control fluid" will be understood to mean a fluid designed to form a filter cake onto a screen or gravel pack, or in some cases, directly onto the formation. For example, a fluid-loss-control fluid may comprise a comparatively small volume of fluid designed to form a filter cake so as to plug off a "thief zone" (*e.g.*, a formation, most commonly encountered during drilling operations, into which the drilling fluid may be lost). Generally, well drill-in and servicing fluids are designed to form a fast and efficient filter cake on the walls of a well bore within a producing formation to minimize leak-off and damage. The filter cake often comprises an inorganic portion (*e.g.*, calcium carbonate), and an organic portion (*e.g.*, starch and xanthan). The filter cake generally is removed before hydrocarbons from the formation are produced. Conventional methods of removal have involved contacting the filter cake with one or more subsequent fluids.

Other conventional methods of removing the filter cake include formulating the well drill-in and servicing fluid so as to include an acid-soluble particulate solid bridging agent. The resultant filter cake formed by such well drill-in and servicing fluid then is contacted with a strong acid to ultimately dissolve the bridging agent. This method is problematic,

however, because the strong acid often corrodes metallic surfaces of completion equipment (e.g., sand control screens), thereby causing such equipment to prematurely fail. Further, the strong acid may damage the producing formation. Additionally, the strong acid may cause the bridging agent to dissolve prematurely, resulting in the loss of the strong acid into the formation, before it can completely cover the filter cake.

Another method of filter cake removal has involved the use of a water-soluble particulate solid bridging agent in the well drill-in and servicing fluid, which bridging agent subsequently is contacted with an aqueous salt solution that is undersaturated with respect to such bridging agent. This method is problematic, however, because such bridging agents may require a relatively long period of time to dissolve in the aqueous salt solution, due to, *inter alia*, the presence of various gelling agents in the well drill-in and servicing fluids. Such gelling agents may prevent the aqueous salt solution from contacting the water-soluble bridging agents.

Operators also have attempted to remove the filter cake by contacting it with a combination of an acid and an oxidizer. The acid may be used to degrade the inorganic portion of the filter cake, while the oxidizer may be employed to degrade the organic portion. However, this may be unnecessarily expensive, as it involves placement of additional components into the formation, at additional cost. For example, operators have attempted to remove the filter cake by flowing a solution comprising hydrogen peroxide into the well bore and permitting it to contact the filter cake. This may be problematic, however, as the transportation, storage, and handling of hydrogen peroxide may present safety concerns.

SUMMARY

The present invention relates to subterranean treatment operations, and more particularly, to methods of degrading filter cakes in subterranean formations.

An example of a method of the present invention is a method of drilling a well bore in a subterranean formation, comprising: using a well drill-in and servicing fluid to drill a well bore in a subterranean formation, the well drill-in and servicing fluid comprising a base fluid, a viscosifier, a fluid loss control additive, a bridging agent, and a delayed-release acid component; permitting the well drill-in and servicing fluid to establish a filter cake in at least a portion of the well bore; contacting the filter cake with an initiator component; and permitting the filter cake to degrade at a desired time. In certain embodiments of the present

invention, the filter cake may be formed upon the face of the formation itself, upon a sand screen, or upon a gravel pack. *Inter alia*, the well drill-in and servicing fluid may be circulated through a drill pipe and drill bit in contact with the subterranean formation, in certain embodiments of the present invention.

Another example of a method of the present invention is a method of degrading a filter cake in a subterranean formation, the filter cake comprising an inorganic portion and an organic portion, and having been established in the formation by a well drill-in and servicing fluid that comprises a delayed-release acid component, the method comprising: permitting the delayed-release acid component to release an acid; contacting the filter cake with an initiator component; permitting the initiator component to interact with the released acid to produce an oxidizer; allowing the released acid to degrade at least a portion of the inorganic portion of the filter cake; and allowing the oxidizer to degrade at least a portion of the organic portion of the filter cake.

An example of a composition of the present invention is a well drill-in and servicing fluid comprising: a base fluid; a viscosifier; a fluid loss control additive; a bridging agent; and a delayed-release acid component.

The features and advantages of the present invention will be readily apparent to those skilled in the art upon a reading of the description of the embodiments which follows.

DETAILED DESCRIPTION

The present invention relates to subterranean treatment operations, and more particularly, to methods of degrading filter cakes in subterranean formations.

Certain embodiments of the methods of the present invention comprise degrading a filter cake in a subterranean formation by reacting an initiator component with a delayed-release acid component that may be present in the filter cake. In certain embodiments of the present invention, the filter cake has been established in the subterranean formation by a well drill-in and servicing fluid of the present invention generally comprising a base fluid, a viscosifier, a fluid loss control additive, a bridging agent, and a delayed-release acid component.

The base fluid utilized in the well drill-in and servicing fluids of the present invention may be aqueous-based, non-aqueous-based, or mixtures thereof. Where the base fluid is aqueous-based, the base fluid may comprise fresh water, salt water (*e.g.*, water containing

one or more salts dissolved therein), brine (*e.g.*, saturated salt water), or seawater. Generally, the water can be from any source provided that it does not contain an excess of compounds that may adversely affect other components in the well drill-in and servicing fluid. Where the base fluid is non-aqueous-based, the base fluid may comprise any number of organic fluids. Examples of suitable organic fluids include, but are not limited to, mineral oils, synthetic oils, esters, and the like, and derivatives thereof. Generally, these organic fluids may be referred to generically as "oils." Generally, any oil in which a water solution of salts can be emulsified may be suitable for use as a non-aqueous-based base fluid in the well drill-in and servicing fluids of the present invention. Generally, the base fluid may be present in an amount sufficient to form a pumpable well drill-in and servicing fluid. More particularly, the base fluid typically is present in the well drill-in and servicing fluids of the present invention in an amount in the range of from about 20% to about 99.99% by volume of the well drill-in and servicing fluid.


The well drill-in and servicing fluids of the present invention further comprise a viscosifier. Examples of suitable viscosifiers include, *inter alia*, biopolymers (*e.g.*, xanthan and succinoglycan), cellulose, cellulose derivatives (*e.g.*, hydroxyethylcellulose), guar, and guar derivatives (*e.g.*, hydroxypropyl guar). In certain embodiments of the present invention, the viscosifier is guar. Commercially available examples of suitable viscosifiers include, but are not limited to, those that are available from Halliburton Energy Services, Inc., of Duncan, Oklahoma, under the trade name "N-VIS." Generally, the viscosifier is present in the well drill-in and servicing fluids of the present invention in an amount sufficient to provide a desired degree of solids suspension. More particularly, the viscosifier may be present in the well drill-in and servicing fluids of the present invention in an amount in the range of from about 0.01% to about 1.0% by weight. In certain embodiments, the viscosifier is present in the well drill-in and servicing fluids of the present invention in an amount in the range of from about 0.2% to about 0.6% by weight.

The well drill-in and servicing fluids of the present invention further comprise a fluid loss control additive. A variety of fluid loss control additives can be included in the well drill-in and servicing fluids of the present invention, including, *inter alia*, polysaccharides and derivatives thereof. Examples of suitable fluid loss control additives include, *inter alia*, starch, starch ether derivatives, hydroxyethylcellulose, cross-linked hydroxyethylcellulose, and mixtures thereof. In certain embodiments, the fluid loss control additive is starch.

Commercially available examples of suitable fluid loss control additives include, but are not limited to, those that are available from Halliburton Energy Services, Inc., of Duncan, Oklahoma, under the trade name "N-Dril HT PLUS." The fluid loss control additive generally is present in the well drill-in and servicing fluids of the present invention in an amount sufficient to provide a desired degree of fluid loss control. More particularly, the fluid loss control additive may be present in the well drill-in and servicing fluids of the present invention in an amount in the range of from about 0.01% to about 3% by weight. In certain embodiments, the fluid loss control additive is present in the well drill-in and servicing fluids of the present invention in an amount in the range of from about 1% to about 2% by weight.

The well drill-in and servicing fluids of the present invention further comprise a bridging agent. The well drill-in and servicing fluids of the present invention suspend the bridging agent and, as the well drill-in and servicing fluids begin to form a filter cake within the subterranean formation, the bridging agent becomes distributed throughout the resulting filter cake, most preferably uniformly. In certain embodiments of the present invention, the filter cake may form upon the face of the formation itself, upon a sand screen, or upon a gravel pack. In certain embodiments of the present invention, the bridging agent comprises, *inter alia*, calcium carbonate, a magnesium compound (*e.g.*, magnesium oxide), or a chemically bonded ceramic bridging agent, or derivatives thereof. Generally, the bridging agent is present in the well drill-in and servicing fluids of the present invention in an amount sufficient to create an efficient filter cake. As referred to herein, the term "efficient filter cake" will be understood to mean a filter cake comprising no material beyond that required to provide a desired level of fluid loss control. In certain embodiments of the present invention, the bridging agent is present in the well drill-in and servicing fluids of the present invention in an amount ranging from about 0.1% to about 32% by weight. In certain embodiments of the present invention, the bridging agent is present in the well drill-in and servicing fluids of the present invention in the range of from about 3% and about 10% by weight. In certain embodiments of the present invention, the bridging agent is present in the well drill-in and servicing fluids of the present invention in an amount sufficient to provide a fluid loss of less than about 15 mL in tests conducted according to the procedures set forth by API Recommended Practice (RP) 13.

The well drill-in and servicing fluids of the present invention further comprise a delayed-release acid component. When the well drill-in and servicing fluids of the present invention have been formulated and placed within the subterranean formation, the delayed-release acid component releases an acid (*e.g.*, lactic acid), as illustrated in **Equation 1** below:

EQUATION 1:


The optional catalyst may be present within the well drill-in and servicing fluids of the present invention, or may be placed in the well bore separately. The optional catalyst may comprise an acid, or a base. One of ordinary skill in the art, with the benefit of this disclosure, will recognize when the use of an optional catalyst may be appropriate for a particular application, and whether such optional catalyst should comprise an acid or a base.

The released acid reacts with the initiator component to produce an oxidizer, as illustrated in **Equation 2** below:

EQUATION 2:

In certain embodiments of the present invention, the oxidizer produced may be, *inter alia*, hydrogen peroxide. In certain embodiments of the present invention, one or more byproducts may be produced by the reaction between the released acid and the initiator component. For example, when the released acid comprises lactic acid, and the initiator component comprises lactate oxidase, the reaction between lactic acid and lactate oxidase may produce an oxidizer (*e.g.*, hydrogen peroxide) and a byproduct (*e.g.*, pyruvic acid). Accordingly, the compositions and methods of the present invention are capable of producing an oxidizer while within the subterranean formation, thereby eliminating or reducing certain safety concerns that may be present in conventional operations, *e.g.*, safety concerns that accompany the storage, transportation, and handling of oxidizers that are injected into the formation from the surface.

In addition to reacting with the initiator component, the released acid also may react with the inorganic portion of the filter cake, as illustrated in **Equation 3** below:

EQUATION 3:

For example, where the inorganic portion of the filter cake comprises calcium carbonate, and where the released acid comprises lactic acid, the reaction product may comprise calcium lactate. As another example, where the inorganic portion of the filter cake comprises magnesium oxide, and where the released acid comprises lactic acid, the reaction product may comprise magnesium lactate.

The rate at which the released acid is released by the delayed-release acid component, "k1," *inter alia*, may largely determine the total degradation time of the inorganic portion of the filter cake (though, as will be described further with reference to "k2," the total degradation time of the inorganic portion of the filter cake may be delayed, *inter alia*, by the presence and amount of an initiator component). Generally, k1 depends on factors such as, *inter alia*, the time during which water and the delayed release acid component are permitted to contact each other, the amount of water that is available to react with the delayed release acid component, temperature, and the presence or absence of the optional catalyst. Generally, both acid catalysts and base catalysts may be used to increase k1. In certain embodiments of the present invention, the reaction depicted in Equation 1 may be base-catalyzed, and caustic may be used as the optional catalyst.

The reaction rate between the initiator component and the released acid, "k2," *inter alia*, determines the extent to which the reaction between the released acid and the inorganic portion of the filter cake may be delayed. Furthermore, the oxidizer produced by the reaction of the released acid with the initiator component may degrade the organic portions of a filter cake that has been established in a subterranean formation by the well drill-in and servicing fluid. In certain embodiments of the present invention, k2 may be increased by permitting the reaction to occur in the presence of an oxygen source (*e.g.*, by bubbling oxygen into the region of the subterranean formation where the reaction is occurring). In certain embodiments of the present invention, k2 may be decreased by the placement of a temporary physical barrier between the initiator component and the released acid, *e.g.*, by encapsulating the initiator component in a suitable encapsulant, which encapsulant may be selected to degrade within the subterranean formation at a desired time. Examples of suitable encapsulants for the initiator component may include, *inter alia*, fatty acids, and the like.

The delayed-release acid components generally comprise an acid derivative. Examples of suitable acid derivatives include, but are not limited to: esters, such as ortho esters; poly(ortho esters); aliphatic polyesters; lactides, poly(lactides); glycolides;

poly(glycolides); lactones; poly(ϵ -caprolactones); poly(hydroxybutyrates); anhydrides; poly(anhydrides); and poly(amino acids). The delayed-release acid components also may comprise an esterase enzyme (*e.g.*, proteinase-K), if desired. In certain embodiments of the present invention, the esterase enzyme may be encapsulated by means known in the art. Blends of certain acid-releasing degradable materials also may be suitable. One example of a suitable blend of materials includes a blend of a poly(lactic acid) and an ortho ester. It is within the ability of one skilled in the art, with the benefit of this disclosure, to select a suitable acid-releasing degradable material. When used in the present invention, a desirable result may be achieved if the acid-releasing degradable material degrades slowly over time, as opposed to instantaneously.

In certain embodiments of the present invention, the delayed-release acid components may comprise a mixture of an acid derivative and a hydrated organic or inorganic solid compound. For example, in circumstances wherein an insufficient amount of water is present in the subterranean formation to facilitate the degradation of the acid derivative, a desirable choice for a delayed-release acid component may comprise a mixture of an acid derivative and a hydrated organic or inorganic solid compound. In an embodiment of the present invention, the acid derivative may degrade in the water provided by the hydrated organic or inorganic compound, which dehydrates over time when heated in the subterranean zone. Examples of such hydrated organic or inorganic compounds may include, but are not limited to: sodium acetate trihydrate; L-tartaric acid disodium salt dihydrate; sodium citrate dihydrate; sodium tetraborate decahydrate; sodium hydrogen phosphate heptahydrate; sodium phosphate dodecahydrate; amylose; starch-based hydrophilic polymers; or cellulose-based hydrophilic polymers.

The delayed-release acid components generally may be present in the well drill-in and servicing fluids of the present invention in an amount sufficient to release a desired amount of acid. In certain embodiments of the present invention, the desired amount of acid that will be released is an amount that will: (1) react with an initiator component to produce a desired amount of an oxidizer; and (2) degrade at least a portion of the inorganic component of the filter cake. The oxidizer produced by the reaction between the initiator component and the released acid may degrade the organic portions of a filter cake that has been established in a subterranean formation by, *inter alia*, a well drill-in and servicing fluid. In certain embodiments of the present invention, the delayed-release acid component may be present in

the well drill-in and servicing fluids of the present invention in an amount in the range of from about 1% to about 40% by weight. In certain embodiments of the present invention, the delayed-release acid component may be present in the well drill-in and servicing fluids of the present invention in an amount in the range of from about 5% to about 20% by weight.

In accordance with certain embodiments of the methods of the present invention, an initiator component may be placed in the subterranean formation at a desired time, so as to contact, and react with, an acid released by the delayed-release acid component (that may be present in a well drill-in and servicing fluid of the present invention), to thereby produce an oxidizer. Examples of suitable initiator components include, *inter alia*, enzymes such as lactate oxidase, and the like. Generally, the amount of initiator component required is an amount sufficient to: (1) delay, for a desired period of time, the interaction between the inorganic portion of the filter cake and the acid released by the delayed-release acid component; and (2) produce a sufficient amount of an oxidizer (*e.g.*, a peroxide such as hydrogen peroxide) when reacting with the released acid to ultimately degrade at least a portion of the organic portion of the filter cake. In certain embodiments of the present invention, the amount of the initiator component that may be placed in the subterranean formation may be an amount in the range of from about 0.0005% to about 0.01% by weight of the delayed-release acid component. In certain embodiments of the present invention, the amount of the initiator component that may be placed in the subterranean formation may be an amount in the range of from about 0.001% to about 0.002% by weight of the delayed-release acid component. For example, where the delayed-release acid component is poly(lactic acid) and the initiator component is lactate oxidase, the initiator component may be added in a ratio of 2 milligrams of lactate oxidase per 1 gram of poly(lactic acid). In certain embodiments of the present invention where an operator desires a long delay of the interaction between the released acid and the inorganic portion of the filter cake, the operator may elect to increase the amount of the initiator component. However, the particular acid-derivative component of the delayed-release acid composition, the particular components of the filter cake, and any other components present in the well bore (*e.g.*, other acids) may dictate the appropriate amount to include. Also, the desired delay period for degrading the filter cake should be considered in deciding upon the appropriate relative concentrations of the delayed-release acid component and the initiator component. One of ordinary skill in the

art, with the benefit of this disclosure, will recognize the appropriate amount of each component to include for a desired application.

Generally, the initiator component interacts with acids present in the well bore (*e.g.*, the acid released by the delayed-release acid component) in such a way as to delay the interaction between at least a portion of the acids and at least a portion of the inorganic portion of the filter cake for a period of time, thereby delaying degradation of the inorganic portion of the filter cake by the acid. Thus, the integrity of the filter cake may not be jeopardized for a given desired delay period. Degradation of only a very small percentage of the inorganic portion of the filter cake (*e.g.*, less than about 2%) may compromise the integrity of the filter cake. The reaction between the initiator component and the released acid also generates an oxidizer (*e.g.*, a peroxide) that ultimately may degrade the organic portion of the filter cake. In certain embodiments, the oxidizer may be, *inter alia*, hydrogen peroxide and/or pyruvate. The oxidizer then may interact with the organic portion of the filter cake to ultimately degrade at least a portion of the organic portion of the filter cake.

An example of a composition of the present invention is a well drill-in and servicing fluid comprising 78.5% water by weight, 7.9% sodium chloride by weight, 0.2% N-VIS by weight, 1.7% N Dril HT PLUS by weight, 7.0% poly(lactic acid) by weight, and 4.7% calcium carbonate by weight.

An example of a method of the present invention is a method of drilling a well bore in a subterranean formation, comprising: using a well drill-in and servicing fluid to drill a well bore in a subterranean formation, the well drill-in and servicing fluid comprising a base fluid, a viscosifier, a fluid loss control additive, a bridging agent, and a delayed-release acid component; permitting the well drill-in and servicing fluid to establish a filter cake in at least a portion of the well bore; contacting the filter cake with an initiator component; and permitting the filter cake to degrade at a desired time. In certain embodiments of the present invention, the filter cake may be formed upon the face of the formation itself, upon a sand screen, or upon a gravel pack. *Inter alia*, the well drill-in and servicing fluid may be circulated through a drill pipe and drill bit in contact with the subterranean formation, in certain embodiments of the present invention.

Another example of a method of the present invention is a method of degrading a filter cake in a subterranean formation, the filter cake comprising an inorganic portion and an organic portion, and having been established in the formation by a well drill-in and servicing

fluid that comprises a delayed-release acid component, the method comprising: permitting the delayed-release acid component to release an acid; contacting the filter cake with an initiator component; permitting the initiator component to interact with the released acid to produce an oxidizer; allowing the released acid to degrade at least a portion of the inorganic portion of the filter cake; and allowing the oxidizer to degrade at least a portion of the organic portion of the filter cake.

An example of a composition of the present invention is a well drill-in and servicing fluid comprising: a base fluid; a viscosifier; a fluid loss control additive; a bridging agent; and a delayed-release acid component.

Therefore, the present invention is well adapted to carry out the objects and attain the ends and advantages mentioned as well as those that are inherent therein. While the invention has been described with reference to embodiments of the invention, such a reference does not imply a limitation on the invention, and no such limitation is to be inferred. The invention is capable of considerable modification, alternation, and equivalents in form and function, as will occur to those ordinarily skilled in the pertinent arts and having the benefit of this disclosure. The described embodiments of the invention are exemplary only, and are not exhaustive of the scope of the invention. Consequently, the invention is intended to be limited only by the spirit and scope of the appended claims, giving full cognizance to equivalents in all respects.

What is claimed is:

1. A method of drilling a well bore in a subterranean formation, comprising:
using a well drill-in and servicing fluid to drill a well bore in a subterranean formation, the well drill-in and servicing fluid comprising a base fluid, a viscosifier, a fluid loss control additive, a bridging agent, and a delayed-release acid component;
permitting the well drill-in and servicing fluid to establish a filter cake in at least a portion of the well bore;
contacting the filter cake with an initiator component; and
permitting the filter cake to degrade at a desired time.
2. The method of claim 1 wherein the step of forming a filter cake upon a surface within the formation comprises forming the filter cake upon the face of the formation itself, upon a sand screen, or upon a gravel pack.
3. The method of claim 1 wherein the base fluid is aqueous-based, nonaqueous-based, or a mixture thereof.
4. The method of claim 3 wherein the nonaqueous-based base fluid comprises at least one of the following: mineral oil, a synthetic oil, an ester, or a derivative thereof.
5. The method of claim 1 wherein the base fluid is present in the well drill-in and servicing fluid in an amount in the range of from about 20% to about 99.99% by volume.
6. The method of claim 1 wherein the viscosifier comprises at least one of the following: a biopolymer, cellulose, a cellulose derivative, guar, or a guar derivative.
7. The method of claim 6 wherein the biopolymer is xanthan or succinoglycan.
8. The method of claim 6 wherein the cellulose derivative is hydroxyethylcellulose.
9. The method of claim 6 wherein the guar derivative is hydroxypropyl guar
10. The method of claim 1 wherein the viscosifier is present in the well drill-in and servicing fluid in an amount sufficient to provide a desired degree of solids suspension.
11. The method of claim 1 wherein the viscosifier is present in the well drill-in and servicing fluid in an amount in the range of from about 0.2% to about 0.6% by weight.
12. The method of claim 1 wherein the fluid loss control additive is present in the well drill-in and servicing fluid in an amount sufficient to provide a desired degree of fluid loss control.

13. The method of claim 1 wherein the fluid loss control additive is present in the well drill-in and servicing fluid in an amount in the range of from about 0.01% to about 3% by weight.
14. The method of claim 1 wherein the bridging agent comprises at least one of the following: calcium carbonate, a magnesium compound, a chemically bonded ceramic bridging agent, or a derivative thereof.
15. The method of claim 1 wherein the bridging agent is present in the well drill-in and servicing fluid in an amount sufficient to create an efficient filter cake.
16. The method of claim 1 wherein the bridging agent is present in the well drill-in and servicing fluid in an amount in the range of from about 0.1% to about 32% by weight.
17. The method of claim 1 wherein the delayed-release acid component comprises an acid derivative.
18. The method of claim 17 wherein the acid derivative comprises at least one of the following: an ester; a poly(ortho ester); an aliphatic polyester; a lactide; a poly(lactide); a glycolide; a poly(glycolide); a lactone; a poly(ϵ -caprolactone); a poly(hydroxybutyrate); an anhydride; a poly(anhydride); a poly(amino acid); an esterase enzyme, and a derivative thereof.
19. The method of claim 17 wherein the acid derivative comprises a blend of poly(lactic acid) and an ortho ester.
20. The method of claim 1 wherein the initiator component comprises lactate oxidase, or a derivative thereof.
21. The method of claim 1 wherein the delayed-release acid component is present in the well drill-in and servicing fluid in an amount in the range of from about 1% to about 40% by weight.
22. The method of claim 1 wherein using a well drill-in and servicing fluid to drill a well bore in a subterranean formation comprises circulating the well drill-in and servicing fluid through a drill pipe and drill bit in contact with the formation.
23. The method of claim 1 wherein permitting the filter cake to degrade at a desired time comprises:
- allowing the delayed-release acid component to release an acid;
 - allowing the initiator component to interact with the released acid to produce hydrogen peroxide;

allowing the released acid to degrade at least a portion of the inorganic portion of the filter cake after a desired delay; and

allowing the hydrogen peroxide to degrade at least a portion of the organic portion of the filter cake.

24. A method of degrading a filter cake in a subterranean formation, the filter cake comprising an inorganic portion and an organic portion, and having been established in the formation by a well drill-in and servicing fluid that comprises a delayed-release acid component, the method comprising:

permitting the delayed-release acid component to release an acid;

contacting the filter cake with an initiator component;

permitting the initiator component to interact with the released acid to produce an oxidizer;

allowing the released acid to degrade at least a portion of the inorganic portion of the filter cake; and

allowing the oxidizer to degrade at least a portion of the organic portion of the filter cake.

25. The method of claim 24 wherein the initiator component comprises lactate oxidase.

26. The method of claim 24 wherein the oxidizer comprises hydrogen peroxide.

27. The method of claim 24 wherein the delayed-release acid component comprises at least one of the following: an ester; a poly(ortho ester); an aliphatic polyester; a lactide; a poly(lactide); a glycolide; a poly(glycolide); a lactone; a poly(ϵ -caprolactone); a poly(hydroxybutyrate); an anhydride; a poly(anhydride); a poly(amino acid); an esterase enzyme, and a derivative thereof.

28. The method of claim 24 wherein the delayed-release acid component comprises a blend of poly(lactic acid) and an ortho ester.

29. A well drill-in and servicing fluid comprising:

a base fluid;

a viscosifier;

a fluid loss control additive;

a bridging agent; and

a delayed-release acid component.

30. The well drill-in and servicing fluid of claim 29 wherein the base fluid is aqueous-based, nonaqueous-based, or a mixture thereof.
31. The well drill-in and servicing fluid of claim 30 wherein the nonaqueous-based base fluid comprises at least one of the following: a mineral oil, a synthetic oil, or an ester, or a derivative thereof.
32. The well drill-in and servicing fluid of claim 29 wherein the base fluid is present in the well drill-in and servicing fluid in an amount in the range of from about 20% to about 99.99% by volume.
33. The well drill-in and servicing fluid of claim 29 wherein the viscosifier comprises at least one of the following: a biopolymer, cellulose, a cellulose derivative, guar, or a guar derivative.
34. The well drill-in and servicing fluid of claim 29 wherein the viscosifier is xanthan or succinoglycan.
35. The well drill-in and servicing fluid of claim 29 wherein the viscosifier is hydroxyethylcellulose.
36. The well drill-in and servicing fluid of claim 29 wherein the viscosifier is hydroxypropyl guar.
37. The well drill-in and servicing fluid of claim 29 wherein the viscosifier is present in the well drill-in and servicing fluid in an amount sufficient to provide a desired degree of solids suspension.
38. The well drill-in and servicing fluid of claim 29 wherein the viscosifier is present in the well drill-in and servicing fluid in an amount in the range of from about 0.2% to about 0.6% by weight.
39. The well drill-in and servicing fluid of claim 29 wherein the fluid loss control additive is present in the well drill-in and servicing fluid in an amount sufficient to provide a desired degree of fluid loss control.
40. The well drill-in and servicing fluid of claim 29 wherein the fluid loss control additive is present in the well drill-in and servicing fluid in an amount in the range of from about 0.01% to about 3% by weight.
41. The well drill-in and servicing fluid of claim 29 wherein the bridging agent comprises at least one of the following: calcium carbonate, a magnesium compound, a chemically bonded ceramic bridging agent, or a derivative thereof.

42. The well drill-in and servicing fluid of claim 29 wherein the bridging agent is present in the well drill-in and servicing fluid in an amount sufficient to create an efficient filter cake.

43. The well drill-in and servicing fluid of claim 29 wherein the bridging agent is present in the well drill-in and servicing fluid in an amount in the range of from about 0.1% to about 32% by weight.

44. The well drill-in and servicing fluid of claim 29 wherein the delayed-release acid component comprises an acid derivative.

45. The well drill-in and servicing fluid of claim 44 wherein the acid derivative comprises an ester; a poly(ortho ester); an aliphatic polyester; a lactide; a poly(lactide); a glycolide; a poly(glycolide); a lactone; a poly(ϵ -caprolactone); a poly(hydroxybutyrate); an anhydride; a poly(anhydride); a poly(amino acid); and an esterase enzyme.

46. The well drill-in and servicing fluid of claim 44 wherein the acid derivative comprises a blend of poly(lactic acid) and an ortho ester.

INTERNATIONAL SEARCH REPORT

ational application No
/GB2005/004389

A. CLASSIFICATION OF SUBJECT MATTER
C09K8/02 C09K8/52

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
C09K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 672 740 A (TEXAS UNITED CHEMICAL COMPANY, LLC) 20 September 1995 (1995-09-20) page 2, line 15 - line 18 page 3, line 6 - line 20 page 4, line 6 - page 5, line 56	1-46
X	WO 01/02698 A (CLEANSORB LIMITED; HARRIS, RALPH, EDMUND; MCKAY, IAN, DONALD) 11 January 2001 (2001-01-11) page 2, line 28 - page 4, line 10 page 8, line 25 - page 11, line 12	24-28

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

15 March 2006

Date of mailing of the international search report

24/03/2006

Name and mailing address of the ISA/
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Zimpfer, E

INTERNATIONAL SEARCH REPORT

International application No

/GB2005/004389

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 00/57022 A (CLEANSORB LIMITED; HARRIS, RALPH, EDMUND; MCKAY, IAN, DONALD) 28 September 2000 (2000-09-28) page 3, line 5 - page 5, line 5 page 7, line 14 - page 8, line 24 page 12, line 5 - line 22 -----	24-28
A	US 2004/106525 A1 (WILLBERG DEAN ET AL) 3 June 2004 (2004-06-03) the whole document -----	1-46
A,P	US 2005/059557 A1 (TODD BRADLEY L ET AL) 17 March 2005 (2005-03-17) the whole document -----	1-46

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

/GB2005/004389

Patent document cited in search report	A	Publication date	Patent family member(s)	Publication date
EP 0672740	A	20-09-1995	AU 689842 B2	09-04-1998
			AU 1472295 A	21-09-1995
			CA 2140845 A1	16-09-1995
			DE 69517223 D1	06-07-2000
			DE 69517223 T2	22-02-2001
			DK 672740 T3	07-08-2000
			NO 950946 A	18-09-1995
			US 5607905 A	04-03-1997
			US 5783527 A	21-07-1998
			<hr style="border-top: 1px dashed black;"/>	
WO 0102698	A	11-01-2001	AU 5696200 A	22-01-2001
			CA 2378073 A1	11-01-2001
			US 6702023 B1	09-03-2004
<hr style="border-top: 1px dashed black;"/>				
WO 0057022	A	28-09-2000	AU 3308300 A	09-10-2000
			CA 2366350 A1	28-09-2000
			GB 2364725 A	06-02-2002
			MX PA01009400 A	20-08-2002
			US 6763888 B1	20-07-2004
<hr style="border-top: 1px dashed black;"/>				
US 2004106525	A1	03-06-2004	NONE	
<hr style="border-top: 1px dashed black;"/>				
US 2005059557	A1	17-03-2005	WO 2005028587 A2	31-03-2005
			US 2005059556 A1	17-03-2005
<hr style="border-top: 1px dashed black;"/>				