




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ :	A1	(11) International Publication Number: WO 00/57633
H04N 3/14, 5/335		(43) International Publication Date: 28 September 2000 (28.09.00)

(21) International Application Number: PCT/US00/07523	(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 21 March 2000 (21.03.00)	
(30) Priority Data:	
60/125,670 22 March 1999 (22.03.99) US	
09/528,818 20 March 2000 (20.03.00) US	
(71) Applicant: SARNOFF CORPORATION [US/US]; 201 Washington Street, CN 5300, Princeton, NJ 08543-5300 (US).	
(72) Inventors: LEVINE, Peter, Alan; 38 Dunbar Drive, West Windsor, NJ 08550 (US). MCCAFFREY, Nathaniel, Joseph; 412 Lambertville-Hopewell Road, Lambertville, NJ 08530 (US). HUGHES, Gary, William; 1794 Kirsten Lee Drive, Westlakes Village, CA 91361 (US). PATEL, Vipulkumar, Kantilal; 607 Falcongate Drive, South Brunswick, NJ 08852 (US).	
(74) Agents: NEY, Andrew, L.; Ratner & Prestia, 301 One Westlakes (Berwyn), P.O. Box 980, Valley Forge, PA 19482-0980 (US) et al.	

(54) Title: METHOD AND APPARATUS TO EXTEND DYNAMIC RANGE OF TIME DELAY AND INTEGRATE CHARGE COUPLED DEVICES



(57) Abstract

A novel method and apparatus capable of extending the intra-scene dynamic range of Time Delay and Integrate Charge-Coupled Device imagers. Charge which is collected and accumulated over a plurality of photosensitive devices is limited by adjusting the barriers levels of stages 101-105, 106-107, or 108 at which collected accumulated charge is removed from the photosensitive devices (Fig. 4). By limiting the amount of accumulated charge that is collected, images of high intensity are prevented from overflowing or saturating the photosensitive devices. Thus, information that is included in the brighter levels of the image is not lost because of clipping the photosensitive device to prevent saturation. Blooming barrier levels can be adjusted in a step-wise linear manner to retain a known amount of charge during the initial collection phase while retaining progressively greater amounts of charge as the collection phase proceeds.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

METHOD AND APPARATUS TO EXTEND DYNAMIC RANGE OF TIME DELAY AND INTEGRATE CHARGE COUPLED DEVICES

CROSS REFERENCE TO RELATED APPLICATIONS

5 This application relates to Provisional Application Serial Number 60/125,670, entitled, "TIME DELAY AND INTEGRATE CCD WITH EXTENDED DYNAMIC RANGE" filed on March 22, 1999, which is assigned to the same assignee and is incorporated by reference herein. Applicant claims the benefit of the priority filing date of March 22, 1999 pursuant 35 U.S.C. § 119(e)(1).

10

FIELD OF THE INVENTION

The present invention is related to the field of imaging devices. More specifically, to extending the dynamic range of Time Delay and Integrate (TDI) imagers.

15 **BACKGROUND OF THE INVENTION**

Typical single line imagers, for example, Charge Coupled Device (CCD) imagers, incorporate a single row of photosensitive electrical devices, such as photo-detectors, to collect photonic charge. A photo-detector converts the collected photonic charge into an electrical charge that is related to the amount of photonic charge collected. In moving 20 target imaging the detector integration time is limited by the allowable time the target image moves past the imaging device or scanner. Consequently, as the target image velocity across the imager increases, the allowable time to collect photonic charge

decreases. A Time Delay & Integration (TDI) method of operating CCD imagers incorporates multiple single row CCD scanners in an imaging array. Each row in the array collects image data for a finite period of time as the target image and the imager move relative to each other. Typically, the collected charge moves from one row to the 5 next at the same speed as the target image moves across the imager to prevent blurring. TCI-CCD scanners offer an advantage over single line scanners in that TDI-CCD devices provide for longer times to collect and integrate photonic charge from the target image. The longer collection time also increases the sensitivity of the imager.

However, when TDI-CCD devices are used to collect highly intense images, the 10 longer integration time may cause the accumulated charge to exceed the capability of the photosensitive devices. To prevent the excess charge from influencing adjacent photosensitive devices, the excess charge is generally drained away. This draining causes details of an image to be lost. One method of avoiding this loss of detail is to increase the level that is deemed excessive charge – i.e., increase the threshold beyond which charge 15 drainage begins. This method, however, has the disadvantage that the maximum threshold drainage level is set by the saturation level of the photosensitive device. In this case, information is lost not because of draining of the excessive charge, but rather from the inability of the cells to collect any additional charge. Another method to avoid excess charge-accumulation problems is to reduce the amount of time that is used in collecting 20 an image. This method, however, has the disadvantage of reducing sensitivity of the imaging device. Thus, dark images remain relatively dark. Hence, there is a need to

extend the dynamic range of TDI-CCD devices that allows for the collection of sufficient image data to view dark images while not losing data from relatively bright images.

SUMMARY OF THE INVENTION

5 In accordance with the principles of the invention, a method is disclosed that increases the intra-scene dynamic range of a TDI-CCD device by selectively limiting the amount of charge collected in each stage by selectively setting blooming barrier levels. By selectively setting barrier levels, the maximum accumulated charge collected in each cell is incrementally increased as the charge is passed from one cell to a subsequent cell.

10 In one embodiment, the level of the barrier is set in a step-wise increasing manner that limits the amount of charge collected in each stage while allowing for the accumulation of progressively greater amounts of collected charge in subsequent cells. In this embodiment, a step-wise increase in the barrier levels changes the reference level at which charge is accumulated in a cell. These changes in the reference level shift the

15 imaging device response characteristic to cause a compression of the accumulated photonic charge for highly intense images while the response to lower intensity images is not substantially affected.

BRIEF DESCRIPTION OF THE DRAWINGS

The advantages, nature and various additional features of the invention will appear more fully upon consideration of the illustrative embodiments to be described in detail in connection with the accompanying drawings. In the drawings:

- 5 Figure 1 illustrates a schematic diagram of an exemplary TDI-CCD device;
- Figure 2 depicts a cross-sectional view of a pixel cell and barrier of a CCD structure;
- Figure 3 illustrates typical response characteristic of a TDI-CCD device;
- Figure 4 illustrates a schematic diagram of a TDI-CCD device in accordance with 10 the principles of the invention;
- Figure 5 illustrates a response characteristic of a TDI-CCD device illustrated in Figure 4 in accordance with the principles of the invention;
- Figure 6a illustrates one exemplary embodiment of limiting charge capacity in accordance with the principles of the invention;
- 15 Figure 6b illustrates a second exemplary embodiment of limiting charge capacity in accordance with the principles of the invention;
- Figure 7a illustrates a third exemplary embodiment of limiting charge capacity in accordance with the principles of the invention;
- Figure 7b illustrates a fourth exemplary embodiment of limiting charge capacity 20 in accordance with the principles of the invention;

Figure 8 illustrates an exemplary response characteristic of a TDI-CCD device in accordance with a second embodiment of the invention;

Figure 9 illustrates an exemplary response characteristic of a TDI-CCD device in accordance with another embodiment of the invention;

5 Figure 10a illustrates a cross-sectional view of an exemplary embodiment of a back-illuminated TDI-CCD device having a response characteristic as illustrated in Figure 8;

Figure 10b illustrates a cross-sectional view of a second exemplary embodiment of a back-illuminated TDI-CCD device having a response characteristic as illustrated in 10 Figure 8; and

Figure 10c illustrates a cross-sectional view of an exemplary embodiment of a top-illuminated TDI-CCD device having a response characteristic as illustrated in Figure 8.

It is to be understood that these drawings are for purposes of illustrating the 15 inventive concepts of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

As would be understood the principles of the invention disclosed are related to TDI-CCD array imagers. However, the principles of the invention may also be applied to 20 other solid-state TDI imaging devices, for example, CMOS TDI-APS devices.

Figure 1 illustrates an exemplary schematic diagram of an 8-stage TDI-CCD device **100**. Only four photosensitive devices (pixel cells) **115**, among a plurality of cells in each stage are shown to describe the operation of the TDI-CCD device. In operation, the photonic charge from a target image is collected beginning in pixel cells **115** associated with the first stage -- *i.e.*, stage **101**. As the target image or imager moves, the image moves past the pixel cells in a next stage (**102**). The cells in this stage then collect photonic charge from the target image. In addition, the charge collected in previous cells is added to the charge collected in the currently-imaging cell. Thus, the charge collected in pixel cell **115** associated with stage **101**, for example, is added or transferred to pixel cell **115** associated with stage **102**, as the image moves past stage **102**. Similarly, the accumulated charge in pixel cell **115** associated with stage **102** is added to the charge collected in pixel cell **115** associated with stage **103**, as the image moves past stage **103**. This transferring of accumulated photonic charge from a cell in one stage to a cell in a subsequent stage continues, one stage at a time, until an end stage is reached -- in this case, stage **108**. The photonic charge collected for the image is accumulated and integrated over the depth of the TDI-CCD device, -- *i.e.*, stages **101-108**. At stage **110** the accumulated charge is read out from the TDI-CCD device.

In transferring the collected charge for each pixel cell **115** to a subsequent pixel cell **115**, the charge is transferred along a channel of pixel cells **115**, known as a transfer channel, illustrated for one channel of pixel cells as **120**. When the energy collected in one cell **115** exceeds the maximum capability of the cell, the excess energy would

normally overflow the cell and “spread” into an adjacent cell. To prevent the accumulated charge in the cells of one transfer channel from influencing the accumulated charge in cells in an adjacent channel, such as transfer channel 121, channels are isolated from one another by blooming drains 125 and barriers 130. The level at which 5 accumulated charge is deemed excessive is determined by barrier 130 that exists between, for example, transfer channel 120 and drain 125. The greater the level, or potential, of barrier 130, the greater the amount of accumulated charge that may be collected in each cell 115. Generally, the levels of barrier 130 are set to achieve the maximum accumulation of charge – i.e., saturation level -- in a pixel cell. As illustrated, 10 barrier 130 is positioned horizontally adjacent to channel 120 and 121. As would be known in the art, barrier 130 may also be positioned vertically adjacent to channels 120 and 121 to limit the charge capacity of pixel cell 115.

Figure 2 illustrates the operation of barrier 130 in controlling excessive charge. As shown, pixel cell 115 fills to a value that is set by barrier 130. When the accumulated 15 charge exceeds the level of barrier 130, the excess, as represented by charge 140, is directed into drain 125. In this illustrative example, when the maximum charge is achieved, any further charge that may be collected is simply discarded. The maximum level of barrier 130 thus limits the accumulated charge.

Figure 3 illustrates an exemplary performance characteristic of TDI-CCD device 20 of Figure 1 for three images of different brightness levels. In the first example, the charge collected by the imager is represented by response characteristic 400. In this

example, each pixel cell **115** in a stage adds a substantially similar amount of charge to pixel cell **115** in the next subsequent stage as the imager and target image move past each other. The accumulated charge collected increases proportionally to the number of stages in the imager. For this first exemplary image, the total amount of charge collected after 5 the eight stages remains below the barrier level **465** set by barrier **130**. In a second example, wherein the image is brighter than the first image, the charge collected is represented by response characteristic **420**. In this example, more charge is collected in each pixel cell **115** (relative to that collected for response characteristic **400**) as the target image and imager move past one another. The accumulated energy collected would 10 normally continue along dashed line portion **425** of response characteristic **420** until the accumulated charge is read out at stage **110**. However, when the collected charge exceeds barrier level **465** (as happens in this example near the end of the sixth CCD stage), the excess charge is drained into drain **125**. The accumulated charge thus remains limited, or clipped, at the barrier level **465**, as represented by response characteristic **430**. 15 Any image detail that may be captured in the dashed line portion of response characteristic **420** is not processed and is therefore lost.

As a third example, the charge of an even brighter image is collected. The response to this brighter image is represented by response characteristic **440**. In this example the brightness of the image causes the accumulated charge to exceed the 20 maximum level set by barrier **130** (at level **465**) after scanning of the image by only about two of the CCD stages. Were the accumulated charge permitted to accumulate through

continuing CCD stages, that charge would be represented by the dashed line portion 445 of response characteristic 440, but the charge is limited by barrier level 465. Barrier level 465 thus limits the response characteristic of the imager. Charge above barrier level 465 is simply discarded into drain 125 and the accumulated charge for this third exemplary 5 image thus remains limited at level 465 as represented by response characteristic 460.

Figure 4 illustrates an 8-stage TDI-CCD in accordance with the principles of the invention. As is illustrated, barrier 130 is selectively set in accordance with the capacity charge curve 510. Accordingly, the amount of charge accumulated and retained in each stage is incremental increased. In the exemplary embodiment, barrier 130 is set to limit 10 the accumulated charge to twenty-five per cent (0.25) of maximum barrier level 465 in stages 101-105 of the imager, and fifty percent of that level for stages 106 and 107. At stage 108, the level of barrier 130 is set to the maximum barrier level 465. The maximum barrier level may be set independently of the maximum capacity of pixel cell 115, but is typically set substantially equal to the maximum capacity of the pixel cell. 15

In this illustrated example, barrier 130 is selectively set in an step-wise pattern that limits the amount of data collected in the early stages of collection while allowing for incrementally greater amounts of charge in latter stages. Thus, stages 101-105 accumulate 25 percent of the charge that could be collected. Stages 106 and 107 accumulate 50 percent of the charge that could be collected, and stage 108 allows for the 20 accumulation of a maximum amount of charge. With the illustrated configuration, the

maximum amount of charge may be collected without causing a saturation of pixel cell
115.

Figure 5 illustrates the response characteristics of a TDI-CCD device having barrier characteristics selectively set in accordance with the exemplary characteristics 5 illustrated in Figure 4 for the three exemplary images discussed in regard to Figure 3. With regard to the first exemplary image (least bright), the charge collected is represented by response characteristic 600. Response characteristic 600 is similar to the response characteristic 400 of Figure 3, as the accumulated charge does not exceed the selectively set barrier levels of stages 101-105, 106-107 or 108. Accordingly, the response 10 characteristic is not altered and the accumulated charge is not limited.

With regard to the second exemplary image, the accumulated charge, as represented by response characteristic 610, is shown to exceed the first barrier level while charge is collected in stage 102. That is, the accumulation of the charge collected in stage 101 and the charge being collected in stage 102 exceeds the barrier level selectively set for stages 101 through 105. Any additional charge collected in stages 103 through 15 105 would, accordingly, cause the accumulated charge to exceed the level of barrier 130 and is thus drained off. The accumulated charge in stages 103 through 105 remains limited to 25 percent of the charge that may be collected, as represented by response characteristic 620. At stage 106, the level of barrier 130 is increased to 50 percent of the 20 maximum barrier level to allow an incremental increase in the charge collected. As stage 106 moves past the target image, charge is accumulated in pixel cells 115 associated with

stage 106. The increase in accumulated charge is represented by response characteristic 630. As shown, the accumulated charge exceeds the level of barrier 130 during the charge collection of stage 107 and the excess charge is drained off. The accumulated charge remains limited to the 50 percent level, as represented by response characteristic 640. At stage 108, the level of barrier 130 is increased to allow an incremental increase in the charge collected. As stage 108 moves past the target image, charge is accumulated, as represented by response characteristic 650. The charge level continues to accumulate until the collected charge is read out in stage 110.

In this exemplary case, the accumulated charge level is substantially less than the maximum level; hence, the brightest image data is not lost because the image data is compressed. As is illustrated, an imager incorporating a step-wise increase in the level of barrier 130 causes alterations or shifts in reference points that are used by subsequent cells to accumulate charge. These alterations in the reference points allow for the collection of more data from brighter images.

In a third exemplary image, similar to the brightest image discussed in regard to Figure 4, the brightness of the image causes the charge collected to exceed the first level of barrier 130 during the collection phase of stage 101. Any charge collected as the target image moves past stages 101 through 105 is thus drained off. The level of the accumulated charge remains fixed at the barrier level as represented by response characteristic 620. Beginning at stage 106, the level of barrier 130 is increased. As stage 106 moves past the target image, charge is again accumulated in pixel cell 115 associated

with stage 106, as represented by response characteristic 670. As shown, the brightness of the image causes the accumulated charge to quickly exceed the increased barrier level. Thus, any charge collected after this increased barrier level is exceeded is drained off. Accordingly, the accumulated charge level remains limited during stage 106 and 5 continuing through stage 107, as represented by response characteristic 640. At stage 108, the level of barrier 130 is incrementally increased and charge is again accumulated, as represented by the response characteristic 680. In this embodiment, the brightest portions of the image are collected and the brightest portions of the image are not lost. The altered reference points compress the image data to allow pixel cells to accumulate 10 charge that would otherwise be greater than their maximum capability. These alterations in the reference points allow for the collection of image data from brighter images that would otherwise be lost without affecting low light level performance.

In accordance with the principles of the invention, the dynamic range of a TDI-CCD device is extended by selectively setting levels of barriers that limit the charge 15 collection capability. The selectively set barrier levels shift the reference point of accumulated charge. The altered, or shifted, reference point causes the imager to compress brighter portions of an image while not influencing the lower intensity portions of the same image.

As should be understood, the scope of the invention is not limited to the step-wise 20 increase in charge capacity in the exemplary 8-stage TDI-CCD device illustrated. Rather the method of setting progressive barrier levels, and thereby progressively accumulating

charge in a TDI-CCD device, may also be determined using, for example, exponential, logarithmic, inverse logarithmic, geometric or polynomial functions. Furtherstill, the number of barrier levels also may be increased commensurate with the number of stages in a TDI-CCD device. Thus, the number of different barrier levels may be set 5 substantially equal to the number of stages.

Figure 6a illustrates one embodiment for fabricating a TDI-CCD imager having a charge capacity illustrated in Figure 4. In this illustrative embodiment, the barrier level 130 is set to limit the amount of charge collected. For example, barrier levels are set to limit pixel cell 115 associated with stages 101 through 105 to collect only twenty-five 10 (25) percent of full capacity of pixel cell 115 -- *i.e.*, maximum level 465. For stages 106 and 107, barrier levels are set to limit pixel cell 115 associated with stages 106 and 107 to collect and retain an accumulated charge that corresponds to fifty (50) percent of full capacity. At stage 108, the barrier levels are set to the full width of pixel cell 115 to collect and retain an accumulated charge that is substantially equal to full capacity. 15 Figure 6b illustrates a second embodiment for fabricating a TDI-CCD imager having a charge capacity illustrated in Figure 4. In this embodiment, the barrier levels, or potentials, are constant but are positioned to adjust the width of pixel cells 115 to limit the charge collected. In this case, the amount of charge collected is limited by the size of the pixel cells. Further, the width of barrier level 130 remains substantially constant.

20 Figure 7a illustrates a second embodiment of fabricating a TDI-CCD device to achieve the exemplary step-wise accumulated charge characteristics illustrated in Figure

4. In this embodiment, the pixel cell charge capacity is set in designated stages to limit the accumulated charge. As illustrated, the width of pixel 115 in stages 101 through 104 is set at a maximum level 465 -- *i.e.*, full collection capacity. At stage 105, the width of pixel 115 is reduced to twenty-five (25) percent of maximum level 465. At stage 106, the 5 width of pixel 115 is again increased to maximum level 465, and at stage 107, the width of pixel 115 is reduced to fifty (50) percent of maximum level 465. Finally, at stage 108, the width of pixel 115 is again increased to maximum level 465. The narrow channel regions at stages 105 and 107 act as charge clippers. Figure 7b illustrates another embodiment, similar to that described in regard to Figure 7a, wherein the width of barrier 10 130 remains substantially constant. This embodiment is advantageous as the width of drain 125 is correspondingly increased when the size of pixel 115 is decreased. This increase in drain 125 allows for the draining of excessive accumulated charge.

In another embodiment, which is not illustrated, the depth of the pixel cell 115, as illustrated in Figure 2, may also be used to control pixel charge capacity. For 8-stage 15 TDI-CCD device discussed herein, the depth of pixel cells 115 associated with stages 101-105 may be set to collect twenty-five percent of full charge capacity. Similarly, the depth of pixel cells 115 associated with stages 106-107 may be set to collect fifty percent of full charge capacity and the depth of pixel cell 115 associated with stage 108 may be set to accumulate a full charge.

Figure 8 illustrates the response characteristics of this embodiment of the invention to the three exemplary images discussed in regard to Figure 3 and Figure 5. The response characteristic to the first exemplary image is represented by the response characteristic **800**. As discussed previously, the accumulated charge in stages **101** through **108** remains lower than the associated barrier levels. Thus, the selectively set levels do not influence the response characteristic of the TDI-CCD device to this first exemplary image. With regard to the second exemplary image as discussed in regard to Figure 3, the charge accumulated in stages **101** through **104**, as represented by response **810**, rises to maximum level **465**. At stage **105**, however, the charge capacity of pixel cell **115** is set to twenty-five percent of maximum level **465**. Accordingly, as the target image passes stage **105**, the accumulated charge above this twenty-five percent level is drained off, as represented by response **820**. Furthermore, any additional charge collected during stage **105** is also drained off. Thus, the accumulated charge remains limited, as represented by response characteristic **830**. At stage **106**, the charge capacity of pixel cell **115** is again increased to maximum level **465** and charge is again accumulated, as represented by response characteristic **840**. At stage **107**, the charge capacity of the associated pixel cell **115** is reduced to fifty percent. Any charge collected above this fifty-percent level is, accordingly, drained off and the accumulated charge remains at a fixed level, as is represented by response characteristic **850**. At the beginning of stage **108**, the charge capacity of the associated pixel cell **115** increased to maximum level **465** and charge again is accumulated, as represented by response

characteristic 860. Accordingly, the brighter portions of the imager are again captured in the imaging device similar to that illustrated in Figure 5.

With regard to the third exemplary image as discussed in regard to Figure 3, the accumulated charge quickly rises to maximum level 465, as illustrated by response 5 characteristic 865. Any additional charge that may be collected in stages 102 - 104 is drained off, as represented by response characteristic 870. At stage 105, the charge capacity of the associated pixel cell 115 is set at twenty five percent and any accumulated charge above this level is drained off, as represented by response characteristic 875. Further, any additional charge collected is similarly drained off and the accumulated 10 charge level remains constant, as represented by response characteristic 830. At stage 106 the charge capacity of the associated pixel cell 115 is again increased to maximum level 465. The charge is again accumulated, as represented by response characteristic 880. At the beginning of stage 107, the charge capacity of the associated pixel cell 115 is again reduced to fifty percent, and the accumulated charge above this reduced level is 15 again drained off, as represented by response characteristic 885. The accumulated charge remains fixed at this level as any additional charge collected is drained off, as represented by response characteristic 850. At stage 108, the charge capacity of the associated pixel cell 115 is again increased and the accumulated charge again increases, as represented by response 20 890. The brightest portions of this third exemplary image are thus captured in a manner similar to that illustrated in Figure 5.

It should be understood, the representation of the transfer channel having varying size is intended merely to illustrate different methods of achieving the exemplary model of varying barrier levels. Other methods may also be used to achieve similar increases in accumulated charge.

5 A further means of increasing dynamic range is achieved by placing a filtering element over at least one stage of a TDI-CCD device. Filter elements are used to further extend dynamic range by reducing the intensity of an image as the image moves with respect to the collection stages. Figure 4 illustrates the placement of filter **500** over stage **108**. In this embodiment, in addition to selectively setting of barrier levels, filter **500** is
10 used to reduce the image intensity as the image passes stage **108**. Filter **500** may be, for example, a neutral-density filter, or a slotted metal filter. Filtering is well known in the art and need not be discussed in detail herein.

Figure 9 illustrates the response characteristic of the TDI-CCD imager illustrated in Figure 4 with filter **500** positioned over stage **108**. In this case, the response to the
15 three exemplary images is similar to the responses illustrated in Figure 5, except for the response in the filtered stage. That is, the response of this embodiment to the first exemplary image is similar to response characteristic **600** of Figure 5. However, the imposed filter **500** causes the image intensity to decrease during charge collection at stage **108**. The amount of charge collected is thus reduced and this reduction in the
20 accumulated charge is represented by response characteristic **910**. Similarly, the responses of the second and third exemplary images, as illustrated in Figure 9 are

equivalent to corresponding responses illustrated in Figure 5, except for the response during stage **108**. With the imposed filter **500** placed over stage **108** the charge collection is reduced as represented by response characteristics **960** and **990**, respectively. Thus, in accordance with the principles of the present invention, dynamic range of TDI-CCD is 5 further extended by selectively using filters over at least one collection stage to collect highly intense images.

Figure 10a illustrates a cross-sectional view of an exemplary embodiment of an 8-stage back-illuminated TDI-CCD imager incorporating filtering over one stage (stage **108**). Figure 10b illustrates a cross-sectional view of a second exemplary embodiment of 10 an 8-stage back-illuminated TDI-CCD imager incorporating filtering over one stage (stage **108**). As would be understood the principles of the invention are equally applicable to top-illuminated TDI-CCD imagers. Figure 10c illustrates a cross-sectional view of an exemplary embodiment of an 8-stage top-illuminated TDI-CCD imager incorporating filtering over one stage (stage **108**).

15 Using Figure 10a as an illustrative example of TDI-CCD device constructed in accordance with the principles of the invention, light energy **1040** from a target image is sequentially collected in each of the collection stage as imager **1010** moves past the target image in the direction **1050**. As illustrated, TDI-CCD imager **1010** is composed of eight (8) stages, -- *i.e.*, stages **101-108**. Stages **101-108** are formed in wafer **1000**, which is 20 typically made of a semi-conductor material, such as silicon or GaAs.

Attached to wafer 1000 is block 1020. Block 1020 provides support and protection for wafer 1010. Typically block 1020 is an optically transparent material. For example, for imagers used in the visible light range, block 1020 may be constructed of materials such as glass, plastic, acrylic or polymer, that allows light 1040 to pass without significant degradation or loss. For imagers operating in the IR region, block 1020 may be constructed of materials such as silicon. For imagers operating in the UV region, block 1020 may be materials such as quartz and calcium chloride.

5 Filter 1030 is positioned on surface 1070 between block 1020 and wafer 1010. Filter 1030, similar to filter 500 discussed previously, is positioned over stage 108 to reduce the charge collected in this stage. As should be understood, the placement of filter 1030 is not limited to surface 1070, as illustrated. Rather, filter 1030 may be placed, for example, on surface 1060, or may even be incorporated within block 1020 to achieve a reduction in the intensity of the image. For example, a filter may be included within block 1020, by altering the index of reflective of the material of block 1020. The altered 10 index of reflective reduces the intensity of light that traverses block 1020 and is collected in stages 101-108 in wafer 1000. Further still, filter 1030 may be incorporated onto wafer 1010. However, placing filter 1030 on wafer 1010 has the disadvantage that when a change of filtering is necessary wafer 1010 is affected. Accordingly, incorporating filter 1030 onto block 1020 allows for filter changes without affecting wafer 1010.

15 Filters may be used over a plurality of stages and each of these filters need not cause the same reduction in image intensity. For example, filters may be graduated along

the depth of a TDI-CCD such that no filtering occurs in the earlier collection stages while significant reductions of intensity occurs in the latter collection stages. Graduated filtering, thus, does not affect the low intensity portions of any image but will affect the brighter portions, as illustrated in Figure 9.

5 The examples given herein are presented to enable those skilled in the art to more clearly understand and practice the instant invention. The examples should not be considered as limitations upon the scope of the invention, but as merely being illustrative and representative of the invention. Numerous modifications and alternative 10 embodiments of the invention will be apparent to those skilled in the art in view of the foregoing description. Accordingly, this description is to be construed as illustrative only and is for the purpose of teaching those skilled in the art the best mode of carrying out the invention and is not intended to illustrate all possible forms thereof. It is also understood that the words used are words of description, rather than limitation, and that details of the structure may be varied substantially without departing from the spirit of the invention 15 and the exclusive use of all modifications which come within the scope of the appended claims is reserved.

WHAT IS CLAIMED IS



1. An imaging apparatus having a plurality of photosensitive cells arranged in a plurality of rows, said cells providing an output representing a measure of accumulated charge, comprising
 - at least one channel of photosensitive cells, said channel having at least one photosensitive device from each of said rows wherein said accumulated charge in one of said cells is available to a subsequent one of said cells within said channel;
 - at least one barrier level adjacent to each of said at least one channel, said barrier limiting the amount of said accumulated charge collected in said photosensitive cells, wherein said barrier causes alterations in charge capacity of said photosensitive cells to incremental increase said accumulated charge; and means for removing excessive accumulated charge.
- 10 2. The imaging apparatus as recited in Claim 1 further comprising at least one filter, said at least one filter reducing said charge collected in said cell corresponding to said filter.



3. The imaging apparatus as recited in Claim 2 further comprising an optically transparent block, wherein said filter is attached to said block.
4. The imaging apparatus as recited in Claim 1 wherein said photosensitive cells are charged-coupled devices.
5. The imaging apparatus as recited in Claim 1 wherein said barrier level is set as a potential.
6. The imaging apparatus as recited in Claim 1 wherein said barrier level is set by positioning said barrier in said channel.
7. The imaging apparatus as recited in Claim 1 wherein said barrier level is set to allow a step-wise linear increase in said accumulated charge.
8. The imaging apparatus as recited in Claim 1 wherein said barrier level is set to reduce said accumulated charge in designated ones of said plurality of rows.
9. The imaging apparatus as recited in Claim 1 wherein said barrier level in each of said rows is set in accordance with a known relation to cause an incremental increase in a response characteristic of said imaging apparatus.




10. A method of operating an image sensing device which includes a plurality of photosensitive cells arranged in a plurality of rows, said cells further arranged in channels wherein charge collected within one of said cells is transferable to a subsequent one of said cells within said channel, comprising the steps of:
 - 5 creating at least one barrier adjacent to said channels;
 - setting each of said at least one barrier levels to allow said charge to accumulate in said cells, wherein the amount of charge transferred from one of said cells to a subsequent one of said cells is incrementally increased.
11. The method as recited in Claim 10 further comprising the step of:
 - applying filtering selectively to said image sensing device to reduce the image sensing capability.
12. The method as recited in Claim 10 wherein said step of setting said barrier levels includes setting said barriers levels to allow a step-wise increase in accumulated charge.

13. The method as recited in Claim 10 wherein said step of setting said barrier levels includes setting said barriers levels to reduce said accumulated charge in designated ones of said plurality of rows.
14. The method as recited in Claim 10 wherein said step of setting said barriers includes setting each of said barriers levels in each of said rows in accordance with a known relation causing an incremental increase in a response characteristic of said image sensing device.
15. The method as recited in Claim 10 wherein said barrier level is set as a potential.
16. The method as recited in Claim 10 wherein said barrier level is set by positioning said barrier in said channel.



1/6

**FIG. 1****FIG. 2**

**FIG. 3****FIG. 4**

**FIG. 5****FIG. 6a****FIG. 6b**

4/6

**FIG. 7a****FIG. 7b**




FIG. 8






FIG. 9



INTERNATIONAL SEARCH REPORT

International application No.

PCT/US00/07523

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) :H04N 3/14, 5/335

US CL :348/294, 295

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 348/294, 295

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EAST, WEST

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,114,237 A (CAZAUXT) 19 May 1992, col. 7, lines 1-63.	1-16
Y	US 5,418,563 A (DISCHERT et al.) 23 May 1995, col. 5, lines 1-63.	2-4, 11
Y	US 4,695,889 A (PORTMANN) 22 SEPTEMBER 1987, col. 2, lines 29-65.	1,4-10, 12-16
Y	US 4,627,084 A (MCIVER) 02 DECEMBER 1986, col. 3, lines (6-65).	1-16
A	US 5,113,263 A (AUDAIRE et al.) 12 May 1992	1-16

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents.	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	"X"	document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	"Y"	document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"X"	document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	"X"	
P document published prior to the international filing date but later than the priority date claimed	"X"	

Date of the actual completion of the international search
22 MAY 2000

Date of mailing of the international search report

18 AUG 2000¹Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231
Facsimile No. (703) 305-3230

Authorized officer

WENDY GARBET

Telephone No. (703) 305-3230

