



(12) **United States Patent**
Hattori et al.

(10) **Patent No.:** **US 11,059,390 B2**
(45) **Date of Patent:** **Jul. 13, 2021**

(54) **SLIDING DEVICE**

(56) **References Cited**

(71) Applicant: **TOYOTA BOSHOKU KABUSHIKI KAISHA**, Aichi (JP)

U.S. PATENT DOCUMENTS

(72) Inventors: **Takashi Hattori**, Aichi (JP); **Motohisa Nakamura**, Gifu (JP); **Takuya Mizuno**, Aichi (JP); **Tsutomu Oya**, Aichi (JP)

5,746,409 A	5/1998	Rees	
10,059,230 B2 *	8/2018	Kume	A47C 1/12
2013/0020459 A1 *	1/2013	Moriyama	B60N 2/01
			248/636
2014/0110554 A1 *	4/2014	Oya	B60N 2/0722
			248/430
2018/0001791 A1 *	1/2018	Kume	B60N 2/0705
2018/0086230 A1 *	3/2018	Kume	B60N 2/0705
2018/0086232 A1 *	3/2018	Kume	B60N 2/0707
2020/0001745 A1 *	1/2020	Shimizu	B60N 2/0818

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

JP 3110003 11/2000

* cited by examiner

(21) Appl. No.: **16/745,780**

Primary Examiner — Steven M Marsh

(22) Filed: **Jan. 17, 2020**

(74) *Attorney, Agent, or Firm* — Greenblum & Bernstein, P.L.C.

(65) **Prior Publication Data**

US 2020/0238858 A1 Jul. 30, 2020

(30) **Foreign Application Priority Data**

Jan. 25, 2019 (JP) JP2019-011285

(57) **ABSTRACT**


Disclosed is one example of a sliding device in which a movable rail can be inhibited from being largely deformed even when a load such as a compressed load acts on the movable rail. The sliding device includes a fixed rail, a movable rail, and a load receiving portion. The fixed rail is configured to be fixed to a vehicle. To the movable rail, the seat body is attachable. The movable rail is slidable with respect to the fixed rail. The load receiving portion extends from a fixed rail side toward a movable rail side. The load receiving portion is configured to receive a load directed from the movable rail toward the fixed rail in conjunction with the movable rail when the load acts on the movable rail.

(51) **Int. Cl.**
B60N 2/00 (2006.01)
B60N 2/07 (2006.01)

(52) **U.S. Cl.**
CPC **B60N 2/0722** (2013.01)

(58) **Field of Classification Search**
CPC B60N 2/0715; B60N 2/06; B60N 2/067; B60N 2/07; B60N 2/0702
USPC 248/424, 429, 430
See application file for complete search history.

8 Claims, 3 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3

1

SLIDING DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application claims the benefit of Japanese Patent Application No. 2019-0011285 filed on Jan. 25, 2019 with the Japan Patent Office, the entire of which is incorporated herein by reference.

BACKGROUND

The present disclosure relates to a sliding device that supports a seat body of a vehicle seat in a slidable manner.

As disclosed in, for example, the official gazette of Japanese Patent No. 3110003, a sliding device includes a fixed rail, such as a lower rail, and a movable rail, such as an upper rail. A compressed load that acts on the upper rail is transmitted to the lower rail through the upper rail.

SUMMARY

In the invention disclosed in the aforementioned gazette, when a load such as the compressed load, directed from the movable rail to the fixed rail acts on the movable rail, the movable rail may be deformed.

It is desirable that the present disclosure provides a sliding device in which the movable rail can be inhibited from being deformed to a large extent even when a load such as the compressed load acts on the movable rail.

One aspect of the present disclosure relates to a sliding device configured to support a seat body of a vehicle seat in a slidable manner. The sliding device comprises a fixed rail, a movable rail, and a load receiving portion. The fixed rail is configured to be fixed to a vehicle. To the movable rail, the seat body is attachable. The movable rail is slidable with respect to the fixed rail. The load receiving portion extends from a fixed rail side toward a movable rail side. The load receiving portion is configured to receive a load directed from the movable rail toward the fixed rail in conjunction with the movable rail when the load acts on the movable rail.

In the sliding device, the movable rail is thus inhibited from being deformed to a large extent, even when a load such as a compressed load acts on the movable rail.

According to one aspect of the present disclosure, the load receiving portion may be configured to slide with respect to the fixed rail in an integrated manner with the movable rail. Thus, a load such as the compressed load can be received by the load receiving portion in the sliding device, irrespective of the position of the movable rail. Accordingly, large deformation of the movable rail can be more reliably inhibited in the sliding device.

According to one aspect of the present disclosure, the movable rail may comprise a clamp configured to fasten and secure the seat body. A distal end of the load receiving portion in an extending direction may be located directly below the clamp. Thus, a load such as the compressed load applied from the clamp can be more reliably transmitted to the load receiving portion in the sliding device. Accordingly, the large deformation of the movable rail can be inhibited in the sliding device.

According to one aspect of the present disclosure, the sliding device may further comprise at least one roller that makes the movable rail slidable with respect to the fixed rail. The movable rail may comprise at least one roller bracket supporting the at least one roller. The load receiving portion may be integrated with the at least one roller bracket. Such

2

a structure can facilitate production of the sliding device in which the large deformation of the movable rail can be inhibited.

According to the present disclosure, the load receiving portion may be fixed to the at least one roller bracket by swaging. Thus, dimensional accuracy of the at least one roller bracket can be maintained.

Specifically, if the load receiving portion is fixed to the roller bracket by welding, the roller bracket may be thermally deformed due to the heat of the welding. In the sliding device, however, the load receiving portion is fixed to the roller bracket by swaging, which is less likely to cause thermal deformation, and thus the dimensional accuracy of the roller bracket can be maintained.

According to one aspect of the present disclosure, the load receiving portion may be located at a front end of the movable rail in a sliding direction. Thus, the portion of the movable rail where a load such as the compressed load is highly likely to be applied can be more reliably reinforced.

BRIEF DESCRIPTION OF THE DRAWINGS

Some embodiments of the present disclosure will be described hereinafter by way of example with reference to the accompanying drawings, in which:

FIG. 1 is a diagram showing a vehicle seat according to a first embodiment;

FIG. 2 is a diagram showing a front end portion of a movable rail in a sliding direction according to a first embodiment; and

FIG. 3 is an exploded view showing the front end portion of the movable rail in the sliding direction according to the first embodiment.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

Embodiments below describe examples of embodiments within the technical scope of the present disclosure. In other words, matters specifying the invention recited in the appended claims are not limited to specific configurations and structures to be described below.

The embodiments below relate to a seat to be installed in a vehicle such as an automobile (hereinafter referred to as a vehicle seat). Arrows indicating the directions, hatched lines, and so on in the drawings are made for easy understanding of the relations between the drawings, the shapes of constituent members or portions, and so on.

Accordingly, the sliding device is not limited by the directions shown in the drawings. The directions shown in the figures are based on a state in which the vehicle seat according to the embodiments below is installed in the automobile.

In regard at least to a member or a portion provided with a reference numeral and explained below, there is at least one such member or portion unless it is specified, for example, that there is only one such member or portion. In other words, two or more of such members or portions may be provided if the number is not specified to be only one. The sliding device according to the present disclosure comprises at least components, such as the members or portions, provided with reference numerals and to be explained below.

First Embodiment

1. Overview of Vehicle Seat (see FIG. 1)

A vehicle seat **1** according to the present embodiment at least comprises two sliding devices **10** and a seat body **2**. The seat body **2** at least includes a seat cushion **3** and a seatback **5**.

The seat cushion **3** supports the buttocks of an occupant. The seatback **5** supports the back of the occupant. The two sliding devices **10** support the seat body **2** of the vehicle seat **1** in a slidable manner.

The seat body **2** is slidably supported by the two sliding devices **10**.

Specifically, among the two sliding devices **10**, a first sliding device **10** supports a first end of the seat body **2** in a seat width direction, and a second sliding device **10** supports a second end of the seat body **2** in the seat width direction.

2. Structure of Sliding Devices

<Overview of Sliding Devices>

In the present embodiment, the two sliding devices **10** have identical structures. The following description is directed to the sliding device **10** disposed on the left side in the seat width direction. As shown in FIGS. **1** to **3**, the sliding device **10** at least comprises a fixed rail **11**, a movable rail **12**, and a load receiving portion **14**.

<Fixed Rail and Movable Rail>

As shown in FIG. **1**, the fixed rail **11** is fixed to the vehicle. The fixed rail **11** extends in a front-rear direction of the vehicle seat **1**. In the present embodiment, an extending direction of the fixed rail **11** corresponds to a front-rear direction of the vehicle.

The movable rail **12** is slidable with respect to the fixed rail **11**. The seat body **2** is attached to the movable rail **12**. Accordingly, the seat body **2** is slidable together with the movable rail **12** in the front-rear direction of the vehicle seat **1** (in the front-rear direction of the vehicle in the present embodiment).

As shown in FIG. **2**, at least one roller **16A** (two rollers **16A** in the present embodiment) and a roller bracket **16** are provided at least at the front end of the movable rail **12** in a sliding direction.

The two rollers **16A** are one example of rolling elements and make roll contact with the fixed rail **11** enabling the movable rail **12** to be slidable. The roller bracket **16** is fixed to the movable rail **12** while supporting the two rollers **16A**. The roller bracket **16** is fixed to the movable rail **12** by mechanical fasteners, such as screws or rivets, or by welding, for example.

<Load Receiving Portion>

The load receiving portion **14** can receive a load directed from the movable rail **12** to the fixed rail **11** (hereinafter referred to as a compressed load) in conjunction with the movable rail **12** when the compressed load acts on the movable rail **12**. The direction of the compressed load according to the present embodiment is from top to bottom.

As shown in FIG. **3**, the load receiving portion **14** is formed by a metal plate extending from the fixed rail side toward the movable rail side. The load receiving portion **14** is integrated with the movable rail **12** and is slidable with respect to the fixed rail **11**.

Specifically, the load receiving portion **14** is integrated with the roller bracket **16**. The load receiving portion **14** according to the present embodiment is fixed to the roller bracket **16** by swaging.

In other words, at the lower end of the load receiving portion **14**, at least one protrusion **14A** for swaging is

provided (in the present embodiment, two protrusions **14A** for swaging are provided). The roller bracket **16** is provided with at least one through hole **16B** for swaging (two through holes **16B** for swaging in the present embodiment) where the protrusions **14A** can penetrate.

While the two protrusions **14A** respectively penetrate the through holes **16B**, the tips of the protrusions **14A** are swaged and plastically deformed. The load receiving portion **14** is thus fixed to the roller bracket **16** by swaging.

Accordingly, while being located at the front end of the movable rail **12** in the sliding direction, the load receiving portion **14** of the present embodiment is displaced in a sliding manner together with the movable rail **12**. As shown in FIG. **2**, the load receiving portion **14** is located directly below the clamp **15**.

In other words, the distal end of the load receiving portion **14** in an extending direction, that is, the upper end of the load receiving portion **14** is located directly below the clamp **15**. Specifically, the upper end of the load receiving portion **14** faces the clamp **15** while contacting the clamp **15** or while having a gap therebetween.

The clamp **15** is a portion of the movable rail **12** and is a portion where the seat body **2** can be fastened and secured. The clamp **15** according to the present embodiment is formed by a nut member into which a bolt for fastening (not shown) can be inserted.

3. Features of Vehicle Seat (Particularly, Sliding Device) According to Present Embodiment

The sliding device **10** comprises the load receiving portion **14** that can receive the compressed load in conjunction with the movable rail **12**. In the sliding device **10**, the movable rail **12** is thus inhibited from being deformed to a large extent even when the compressed load acts on the movable rail **12**.

The load receiving portion **14** is integrated with the movable rail **12** and is slidable together with the movable rail **12** with respect to the fixed rail **11**. In the sliding device **10**, the compressed load thus can be received by the load receiving portion **14** irrespective of the position of the movable rail **12**. Accordingly, the large deformation of the movable rail **12** can be more reliably inhibited in the sliding device **10**.

The distal end of the load receiving portion **14** in the extending direction is located directly below the clamp **15**. In the sliding device **10**, a load such as the compressed load applied from the clamp **15** is thus more reliably transmitted to the load receiving portion **14**. Accordingly, the large deformation of the movable rail **12** can be more reliably inhibited in the sliding device **10**.

The load receiving portion **14** is integrated with the roller bracket **16**. This can facilitate production of the sliding device **10** in which the large deformation of the movable rail **12** can be inhibited.

The load receiving portion **14** is fixed to the roller bracket **16** by swaging. Accordingly, dimensional accuracy of the roller bracket **16** can be maintained.

Specifically, if the load receiving portion **14** is fixed to the roller bracket **16** by welding, the roller bracket **16** may be thermally deformed due to the heat of the welding. In the sliding device **10**, however, the load receiving portion **14** is fixed to the roller bracket **16** by swaging, which is less likely to cause thermal deformation, and thus the dimensional accuracy of the roller bracket **16** can be maintained.

The load receiving portion **14** is located at the front end of the movable rail **12** in the sliding direction. Thus, the

5

portion of the movable rail 12 where a load such as the compressed load is highly likely to be applied can be more reliably reinforced.

Other Embodiments

For example, the load receiving portion 14 does not have to be integrated with the movable rail 12.

For example, the distal end of the load receiving portion 14 in the extending direction may be located at a position displaced from the clamp 15 in the sliding direction.

For example, the load receiving portion 14 may be provided to the main body portion 12A of the movable rail 12 (see FIG. 3).

For example, the load receiving portion 14 may be welded to the roller bracket 16 or the movable rail 12.

For example, the load receiving portion 14 may be located at a position other than at the front end of the movable rail 12 in the sliding direction.

The present disclosure can be applied to seats used in other vehicles such as railroad vehicles, ships, boats, and aircrafts, and to stationary seats used in theaters and at homes, and other places.

Furthermore, the present disclosure is only required to conform to the gist of the invention described in the above-described embodiments, and thus is not limited to the aforementioned embodiments. Accordingly, the present disclosure may be configured in combination of at least two of the aforementioned embodiments, or may be configured without some of the components illustrated in the drawings or described with reference numerals in the aforementioned embodiments.

What is claimed is:

1. A sliding device configured to support a seat body of a vehicle seat in a slidable manner, the sliding device comprising:

- a fixed rail configured to be fixed to a vehicle;
- a movable rail to which the seat body is attachable, the movable rail being slidable with respect to the fixed rail; and
- a load receiving portion extending from a fixed rail side toward a movable rail side, the load receiving portion being configured to receive a load directed from the movable rail toward the fixed rail in conjunction with the movable rail when the load acts on the movable rail, wherein the load receiving portion is disposed on the inner side of opposing sidewalls of the movable rail.

6

2. The sliding device according to claim 1, wherein the load receiving portion is configured to slide with respect to the fixed rail in an integrated manner with the movable rail.

3. The sliding device according to claim 2, wherein the movable rail comprises a clamp configured to fasten and secure the seat body, and wherein a distal end of the load receiving portion in an extending direction is located directly below the clamp.

4. The sliding device according to claim 2 further comprising at least one roller that makes the movable rail slidable with respect to the fixed rail, wherein the movable rail comprises at least one roller bracket supporting the at least one roller, and wherein the load receiving portion is integrated with the at least one roller bracket.

5. The sliding device according to claim 4, wherein the load receiving portion is fixed to the at least one roller bracket by swaging.

6. The sliding device according to claim 2, wherein the load receiving portion is located at a front end of the movable rail in a sliding direction.

7. A sliding device configured to support a seat body of a vehicle seat in a slidable manner, the sliding device comprising:

- a fixed rail configured to be fixed to a vehicle;
- a movable rail to which the seat body is attachable, the movable rail being slidable with respect to the fixed rail; and
- a load receiving portion extending from a fixed rail side toward a movable rail side, the load receiving portion being configured to receive a load directed from the movable rail toward the fixed rail in conjunction with the movable rail when the load acts on the movable rail, wherein a distal end of the load receiving portion in an extending direction is located above the fixed rail.

8. A sliding device configured to support a seat body of a vehicle seat in a slidable manner, the sliding device comprising:

- a fixed rail configured to be fixed to a vehicle;
- a movable rail to which the seat body is attachable, the movable rail being slidable with respect to the fixed rail; and
- a load receiving portion extending from a fixed rail side toward a movable rail side, the load receiving portion being configured to receive a load directed from the movable rail toward the fixed rail in conjunction with the movable rail when the load acts on the movable rail, wherein the load receiving portion is configured to transmit the received load to the fixed rail.

* * * * *