



Office de la Propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2531699 A1 2006/06/30

(21) **2 531 699**

(12) **DEMANDE DE BREVET CANADIEN
CANADIAN PATENT APPLICATION**

(13) **A1**

(22) Date de dépôt/Filing Date: 2005/12/29

(41) Mise à la disp. pub./Open to Public Insp.: 2006/06/30

(30) Priorité/Priority: 2004/12/31 (ES200403174)

(51) Cl.Int./Int.Cl. *B64D 33/02* (2006.01)

(71) Demandeur/Applicant:
AIRBUS ESPANA, S.L., ES

(72) Inventeur/Inventor:
HERNANZ MANRIQUE, JOSE ANGEL, ES

(74) Agent: MARKS & CLERK

(54) Titre : CANAL D'ENTREE D'AIR DE GROUPE AUXILIAIRE DE PUISSANCE A AUBES DIRECTRICES
AEROACOUSTIQUES

(54) Title: AUXILIARY POWER UNIT INTAKE DUCT WITH AERO-ACOUSTIC GUIDE VANES

(57) **Abrégé/Abstract:**

An auxiliary power unit intake duct for an aircraft, comprising an internal straight portion 1a, an internal first bend portion 1b and an internal second bend portion 1c, extending between an air inlet 2 and a plenum entry 3 of the auxiliary power unit, a plurality of acoustic guide vanes 4,5 located in the straight portion 1a of the intake duct 1, extending horizontally between opposite side portions of the straight portion 1a; and a plurality of curved aerodynamic guide vanes 6,7 located in the second bend portion 1c proximate to said plenum inlet 3, extending vertically between a top portion and a bottom portion of the second bend portion 1c, each of the curved aerodynamic guide vanes 6,7 being concentric with said bend curvature of the second bend portion 1c.



ABSTRACT

An auxiliary power unit intake duct for an aircraft, comprising
an internal straight portion 1a, an internal first bend
5 portion 1b and an internal second bend portion 1c, extending
between an air inlet 2 and a plenum entry 3 of the auxiliary
power unit,

a plurality of acoustic guides vanes 4,5 located in the
straight portion 1a of the intake duct 1, extending horizontally
10 between opposite side portions of the straight portion 1a; and
a plurality of curved aerodynamic guide vanes 6,7 located in the
second bend portion 1c proximate to said plenum inlet 3,
extending vertically between a top portion and a bottom portion
of the second bend portion 1c, each of the curved aerodynamic
15 guide vanes 6,7 being concentric with said bend curvature of the
second bend portion 1c.

AUXILIARY POWER UNIT INTAKE DUCT WITH AERO-ACOUSTIC GUIDE VANES

TECHNICAL FIELD OF THE INVENTION

The present invention relates auxiliary power units for aircraft's and, particularly, to intake ducts for such power
5 units.

BACKGROUND ART

As known, modern aircraft's are equipped with a plurality of electrical and electronic devices requiring an input of electrical power to fulfil their functions. Such devices are
10 environmental controls and systems, as well as, especially in passenger aircraft's, outlets for passenger's use and comfort. Whilst electrical power is often provided by power generators driven by the engines of the aircraft, passenger aircraft's are nowadays aircraft's generally equipped with auxiliary power
15 units ('APU') as an alternative, supplementary or additional source of power for electricity needed on the aircraft. APUs are used to supply electrical power to the aircraft's systems and components while the aircraft is parked on the ground, in flight and during taxiing or landing.

20 An APU is a gas turbine engine mounted in the tailcone or in the wheelwell of the aircraft, i.e. inside the aircraft so that an intake duct is needed to feed outside air to the APU, as well as an outlet duct through which exhaust gases are expelled from the APU. Typically, an APU comprises a compressor inlet
25 ('plenum chamber'), a compressor, a combustor having a primary fuel nozzle and a secondary fuel nozzle, a turbine, a gas exhaust, and a shaft on which the compressor and the combustor are mounted for rotation on a shaft connected to a gearbox and the gearbox is connected to a power generator. When the shaft
30 rotates, air is drawn through the intake duct to the compressor inlet, pressurized by the compressor, mixed with fuel in the combustor and ignited so that hot pressurized gas is formed. This gas expands across the turbine and leaves the APU through the gas exhaust. When expanding, the pressurized hot gas causes
35 the turbine, shaft, and compressor to rotate.

The length, width and shape of an intake conduct is generally subject to position of the air intake and the position of the APU, and to the structural elements, components and/or aggregates that may be located between the air intake and the plenum entry of the APU. Thus, the air intake is normally be located in a forward position with respect to the APU so as to allow a stream of air to be guided to the APU in the smoothest possible manner. The duct air inlet is normally in connection with housing with an actuator flap used to close and open the air intake,

The APU plenum entry may be located in a position being lower or higher than the air intake or at the same level as the air intake. Thus, when the air intake is in higher position with respect to the APU, the first bend portion of the intake duct may extend downwards from the straight portion and connect with the second bend portion, whilst the second bend portion of the intake duct may extend leftwards or rightwards from the first bend portion. Also, when the air intake is in a lower position with respect to the APU, the first bend portion of the intake duct may extend upwards from the straight portion and connect with the second bend portion, whilst the second bend portion of the intake duct may extend leftwards or rightwards from the first bend portion.

APUs generate high levels of noise at the outside of the aircraft. This is especially unpleasant and even harmful when the APU is operating to power the aircraft systems prior to take off. An intake duct for the APU therefore must not only be suitable to efficiently provide a uniform flow of air to the APU but should also contribute to reduce noise propagation through the APU intake. For this purpose, it is known to place aeroacoustic guide vanes within an intake duct having a bend in a position following the curvature of the bend. Whilst this has proven to provide a rather efficient air-flow control and reduction of noise propagation, it is not fully satisfactory in respect of intake ducts having two bend portions, as for example

in the case where the air intake is in an upper position with regard to the plenum inlet and where thus two internal bend portions are required on its path to the APU. Taking into account that the presence of the two internal bends leads to
5 high values of flow distortion measured by the distortion coefficient in the plenum entry with the conventional guide vanes definition, conventionally placed guide vanes have proven to be unsatisfactory in intake ducts with two bended portions.

DESCRIPTION OF THE INVENTION

10 The present invention is intended to provide a vane structure for an intake duct with two bends that reduces noise propagation through the APU intake and simultaneously provides an efficient and uniform flow of air to the plenum entry of the APU. This is achieved by an auxiliary power unit intake duct
15 with elongated guide vanes for an aircraft, the intake duct comprising

an internal straight portion, an internal first bend portion, and an internal second bend portion, said portions extending between a duct air inlet and a plenum entry of the
20 auxiliary power unit, the second bend having a first side wall having a first side wall curvature and a second side wall having a second side wall curvature, the second side wall being shorter than the first side wall;

the first bend portion extending between the straight
25 portion and the second bend portion, said second bend portion having a bend curvature,

wherein the intake duct further comprises:
a plurality of acoustic guide vanes located in said straight portion of the intake duct, said acoustic guide vanes extending
30 horizontally between opposite side portions of said straight portion; and

a plurality of curved aerodynamic guide vanes located in said second bend portion proximate to said plenum inlet, said curved aerodynamic guide vanes extending vertically between a
35 top portion and a bottom portion of said second bend portion;

each of said curved aerodynamic guide vanes being concentric with said bend curvature of said second bend portion.

By arranging the guide vanes in two different sets, i.e. one set comprised of the plurality of acoustic guide vanes in the straight part of the duct, and another set comprised of the plurality of aerodynamic guide vanes following the curvature of the second bend of the duct, a uniform flow velocities distribution in the APU plenum inlet is achieved in intake ducts for APUs comprising two bend portions, whereby the APU performances are improved and noise propagation through the duct air inlet is reduced. The guide vanes are in the shape of deflectors.

The plurality of acoustic guide vanes may comprise an upper acoustic guide vane and a lower acoustic guide vane being positioned such that the straight portion is divided into paths having the same heights. The upper acoustic guide vane may be longer than the lower acoustic guide vane and extend into the first bend portion when the first bend portion is bent downwards, whilst, when the first bend portion is bent upwards, lower acoustic guide vane may be longer than the upper acoustic guide vane.

The plurality of curved aerodynamic guide vanes may comprise

a curved first aerodynamic guide vane located in a radial position in the middle between at least a first external radius given by the first side wall curvature of said second bend portion and at least a first internal radius given by the second side wall curvature of said second bend portion

a curved second aerodynamic guide vane located between said first aerodynamic guide vane and said second sidewall. In this embodiment, the second aerodynamic guide vane is preferably shorter than the first aerodynamic guide vane.

The intake duct of the present invention preferably has a substantially quadrangular horizontal cross section such that the cross sections of its top and the bottom walls are longer

than the cross sections of its sidewalls.

The curvatures of the side walls of the second bend portion of the intake duct do not need to be uniform but may be composed of a plurality differing arched sections, but is its
5 important that the curvature of the guide vanes follows the curvature of the second bend portion. Thus, when any or both of the side wall curvatures comprises such a plurality of differing arched sections, the first aerodynamic guide vane may be comprised of an equal number of curved sections located in
10 radial positions in the middle between a plurality of external radius given each by one of the differing arched sections of the first side wall curvature of said second bend portion, and at least said first internal radius given each by second differing arched sections of the second side wall curvature of said second
15 bend portion or a plurality of internal radius given each by second differing arched sections of the second side wall curvature of said second bend portion.

In an embodiment of the invention where one or both of the side wall curvatures is composed of such a plurality of
20 differing arched sections, a first curved section of the first aerodynamic guide vane is located in a radial position in the middle between the first external radius given by a first arched section of the first side wall curvature, and at least one internal radius given by a first arched section of the second
25 side wall curvature of said second bend portion, whilst a second curved section of the curved first aerodynamic guide vane is located in a radial position in the middle between a second external radius given by a second arched section of the first side wall curvature and at least a second internal radius given
30 by a second arched section of the second side wall curvature.

BRIEF DESCRIPTION OF THE DRAWINGS

Features relating to embodiments of the inventions will be explained hereinafter on the grounds of hereto attached drawings in which

35 figure 1 is a schematic perspective top view of an

embodiment of the intake duct according to the present invention showing the inside of the duct;

figure 2 is a schematic partial side view showing the straight portion from the duct air inlet side of the intake
5 duct;

figure 3 is a schematic partial side view showing the straight portion towards the duct air inlet side of the intake duct;

figure 4 is a schematic bottom perspective view of an
10 embodiment of the curved aerodynamic guide vanes shown in figure 1.

In these figures there are reference signs having the following meanings:

	1	intake duct
15	1a	straight portion of the intake duct
	1b	first bend portion of the intake duct
	1c	second bend portion of the intake duct
	2	duct air inlet
	2a, 2b, 2c	flow paths
20	3	plenum entry of the APU
	4	first acoustic guide vane
	5	second acoustic guide vane
	6	first curved aerodynamic guide vane
	6a	first curved section of the first aerodynamic guide
25		vane
	6b	second curved section of the curved first aerodynamic
		guide vane
	7	second curved aerodynamic guide vane
	7a	first curved section of the second aerodynamic guide
30		vane
	7b	second curved section of the second aerodynamic guide
		vane
	8	first sidewall of the second bend portion
	9	second sidewall of the second bend portion
35	a1	first side wall curvature

	a1a	first arched section of the first side wall curvature
	a1b	second arched section of the first side wall curvature
	a2	second side wall curvature
5	a2a	first arched section of the second side wall curvature
	a2b	second arched section of the second side wall curvature
	Rext	first external radius of the first arched section of
10		the first side wall curvature
	Rext'	second external radius of the second arched section of the first side wall curvature
	Rint	first internal radius of the first arched section of the second side wall curvature
15	Rint'	second internal radius of the second arched section of the second side wall curvature
	R1	radius defining the radial position of the first curved section of the first aerodynamic guide vane
	R1'	radius defining the radial position of the second curved section of the first aerodynamic guide vane
20		
	R2	radius defining the radial position of the first curved section of the second aerodynamic guide vane
	R2'	radius defining the radial position of the radial position second curved section of the second
25		aerodynamic guide vane

EMBODIMENTS OF THE INVENTION

Figures 1 to 4 schematically show an embodiment of the intake duct of the present invention.

As shown in figure 1, the intake duct 1 has a substantially quadrangular cross section and comprises an internal straight portion 1a, an internal first bend portion 1b and an internal second bend portion 1c which extend between a duct air inlet 2 and a plenum entry 3 of a per se conventional auxiliary power unit (not shown in the drawings). The straight portion 1a connects with the first bend portion 1b that extends

downwards and connects with the second bend portion 1c that bends leftwards.

An upper acoustic guide vane 4 and a lower acoustic guide vane 5 are placed horizontally between the sidewalls of the straight portion 1a of the duct 1. As the first bend portion 1b of the intake duct 1 bends downwards, the upper acoustic guide vane 4 is slightly longer than the lower acoustic guide vane 5 and extends into the first bend portion 1b.

The second bend portion 1c has a first side wall 8 with a first sidewall curvature a1 and a second side wall 9 with a second sidewall curvature a2. The second side wall 9 is shorter than the first side wall 8. Two curved aerodynamic guide vanes 6,7 are located in the second bend portion 1c proximate to the plenum inlet 3. The aerodynamic guide vanes 6,7 extend vertically between the top wall and the bottom wall of the second bend portion 1c. One, i.e. the first curved aerodynamic guide vane 6 is located in a radial position in the middle between the first side wall 8 and the second side wall 9, approximately in the middle of the second bend portion 1c, whilst the second curved aerodynamic guide vane 7 is located between the first aerodynamic guide vane 6 and the second side wall 9 of the second bend portion 1c.. The second aerodynamic guide vane 7 is shorter than the first aerodynamic guide vane 6. Both aerodynamic guide vanes 6,7 have a shape that follows the curvature of the second bend portion.

As apparent from the combination of figures 1 and 4, the first aerodynamic guide vane 6 comprised a first curved section 6a and a second curved section 6b. The first curved section 6a of the first aerodynamic guide vane 6 is located in a radial position R1 in the middle between the first external radius Rext given by a first arched section a1a of the first side wall curvature a1, and a first internal radius Rint given by a first arched section a2a of the second side wall curvature a2 of the second bend portion 1c. The second curved section 6b of the curved first aerodynamic guide vane 6 is located in a radial

position $R1'$ in the middle between a second external radius R_{ext}' given by a second arched section $a1b$ of the first side wall curvature $a1$ and a second internal radius R_{int}' given by a second arched section $a2b$ of the second side wall curvature $a2$.

5 Figure 4 shows a possible relationship between the geometries of the curvatures of the second bend portion $1c$ and of the two aerodynamic guide vanes $6,7$ in the embodiment of the intake duct shown in figure 1.

In the embodiment shown in figure 4,

10 $R1$ i.e. the radius of the first curved section $6a$ of the first aerodynamic guide vane 6 is of approx. 59cm ,

$R1'$ i.e. the radius of the second curved section $6b$ of the first aerodynamic guide vane 6 is of approx. 150cm ,

15 $R2$ i.e. the radius of the first curved section $7a$ of the second aerodynamic guide vane 7 is of approx. 45cm ,

$R2'$ i.e. the radius of the second curved section $7b$ of the second aerodynamic guide vane 7 is of approx. 115cm ,

$a1a$ i.e. the first arched section of the first side wall curvature is an arched section of approx. 26.8° ,

20 $a1b$ i.e. the second arched section of the first side wall curvature is an arched section of approx. 10.5° ,

$a2a$ i.e. the first arched section of the second side wall curvature is an arched section of approx. 26.3° ,

25 $a2b$ i.e. the second arched section of the second side wall curvature is an arched section of approx. 10.1° .

As shown in figures 2 and 3, the upper acoustic guide vane 4 and the lower acoustic guide vane 5 are positioned such that the straight portion $1a$ is horizontally divided into flow paths $2a, 2b, 2c$. So as to avoid propagation of soundwaves through the duct air inlet 2 , the longitudinal axes of the acoustic vanes $4, 5$ are slightly divergent in the direction of the free ends of the acoustic guide vanes $4, 5$ i.e. the flowpaths have a narrower cross section at the duct air inlet 2 than at the free ends of the acoustic guide vanes $4, 5$. Thus, the longitudinal axis of the upper acoustic guide vane 4 may deviate from the longitudinal

30
35

axis of the top wall of the straight portion 1a of the intake duct by approx. 1.7° . The deviation between the longitudinal axis of the upper acoustic guide vane 4 and the longitudinal axis of the lower acoustic guide vane 5 may be approx. 2.6° . The
5 deviation between the lower acoustic guide vane 5 and the longitudinal axis of the bottom wall of the straight portion 1a of the intake duct by approx. 2.7° .

CLAIMS

1. An auxiliary power unit intake duct with aero-acoustic guide vanes for an aircraft, the intake duct (1) comprising
an internal straight portion (1a), an internal first bend
5 portion (1b) and an internal second bend portion (1c), said internal portions (1a,1b,1c) extending between a duct air inlet (2) and a plenum entry (3) of the auxiliary power unit, the second bend (1c) having a first side wall (8) having a first side wall curvature (a1) and a second side wall (9) having a
10 second side wall curvature (a2), the second side wall (9) being shorter than the first side wall (8), the first bend portion (1b) extending between the straight portion (1a) and the second bend portion (1c), said second bend portion (1c) having a bend curvature; and
15 elongated guide vanes (4,5,6,7) placed within the intake duct,
wherein the intake duct further comprises
a plurality of acoustic guide vanes (4,5) located in said straight portion (1a) of the intake duct (1), said acoustic
20 guide vanes (4,5) extending horizontally between opposite side portions of said straight portion (1a); and
a plurality of curved aerodynamic guide vanes (6,7) located in said second bend portion (1c) proximate to said plenum inlet (3), said curved aerodynamic guide vanes (6,7)
25 extending vertically between a top portion and a bottom portion of said second bend portion (1c); each of said curved aerodynamic guide vanes (6,7) being concentric with said bend curvature of said second bend portion (1c).
- 30 2. An auxiliary power unit intake duct according to claim 1, wherein said plurality of acoustic guide vanes (4,5) comprises an upper acoustic guide vane (4) and a lower acoustic guide vane (5) being positioned such that the straight portion (1a) is horizontally divided into flow paths (2a,2b,2c).

3. An auxiliary power unit intake duct according to claim 2, wherein the first bend portion (1b) of the intake duct (1) bends downwards, and the upper acoustic guide vane (4) is longer than the lower acoustic guide vane (5) and extends into the first
5 bend portion (1b).

4. An auxiliary power unit intake duct according to claim 1, wherein the first bend portion (1b) of the intake duct (1) bends upwards and the lower acoustic guide vane (5) is longer than the
10 upper acoustic guide vane (4) and extends into the first bend portion (1b).

5. An auxiliary power unit intake duct according to claim 1, wherein the plurality of curved aerodynamic guide vanes (6,7)
15 comprises

a curved first aerodynamic guide vane (6) located in a radial position R1 in the middle between at least a first external radius (Rext) given by the first side wall curvature (a1) of said second bend portion (1c) and at least a first
20 internal radius (Rint) given by the second side wall curvature (a2) of said second bend portion (1c), and
a curved second aerodynamic guide vane (7) located in a radial position R2 in the middle between said first aerodynamic guide vane (6) and said second sidewall (9).

25

6. An auxiliary power unit intake duct according to claim 5, wherein

the first side wall curvature (a1) is comprised of a plurality of differing first arched sections (a1a; a1b);

30 the first aerodynamic guide vane (6) is comprised of a plurality of curved sections (6a,6b) being equal in number to said first arched sections (a1a,a1b);

said curved sections are located in radial positions in the middle between a plurality of external radius' (Rext,Rext')
35 given each by one of said first arched sections (a1a; a1b) of

the first side wall curvature (a1) of said second bend portion (1c) and at least said first internal radius (Rint) given by said second side wall curvature (a2) of said second bend portion (1c).

5

7. An auxiliary power unit intake duct according to claim 5, wherein

a first curved section (6a) of the first aerodynamic guide vane (6) is located in a radial position R1 in the middle
10 between the first external radius (Rext) given by a first arched section (a1a) of the first side wall curvature (a1), and a first internal radius (Rint) given by a first arched section (a2a) of the second side wall curvature (a2) of said second bend portion (1c), and

15 a second curved section (6b) of the curved first aerodynamic guide vane (6) is located in a radial position R1' in the middle between a second external radius (Rext') given by a second arched section (a1b) of the first side wall curvature (a1) and a second internal radius (Rint') given by a second
20 arched section (a2b) of the second side wall curvature (a2).

8. An auxiliary power unit intake duct according to claim 5, wherein

a first curved section (7a) of the second aerodynamic guide
25 vane (7) is located in a radial position R2 in the middle between the first guide vane radius (R1) given by a first arched section (a1a) of the first side wall curvature (a1), and a first internal radius (Rint) given by a first arched section (a2a) of the second side wall curvature (a2) of said second bend portion
30 (1c), and

a second curved section (7b) of the curved second aerodynamic guide vane (7) is located in a radial position R2' in the middle between the first guide vane radius (R1') given by a second arched section (a1b) of the first side wall curvature
35 (a1) and a second internal radius (Rint') given by a second

arched section (a2b) of the second side wall curvature (a2).

9. An auxiliary power unit intake duct according to any of claims 5 to 7, wherein the second aerodynamic guide vane (7) is shorter than the first aerodynamic guide vane (6).

5

10. An auxiliary power unit intake duct according to any of the preceding claims, wherein the intake duct (1) has a substantially quadrangular horizontal cross section.

10

Application number/numéro de demande: 2531699

Figures: 1-2

Pages: _____

DRW-TP

Unscannable items
received with this application
(Request original documents in File Prep. Section on the 10th Floor)

Documents reçus avec cette demande ne pouvant être balayés
(Commander les documents originaux dans la section de préparation des dossiers au
10ième étage)




Fig. 3




Fig. 4