



- (51) International Patent Classification:
B29C 70/38 (2006.01) *B29D 99/00* (2010.01)
B29C 70/54 (2006.01)
- (21) International Application Number:
PCT/US2013/071124
- (22) International Filing Date:
21 November 2013 (21.11.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/749,881 7 January 2013 (07.01.2013) US
13/901,813 24 May 2013 (24.05.2013) US
- (71) Applicant: THE BOEING COMPANY [US/US]; 100 North Riverside Plaza, Chicago, Illinois 60606-2016 (US).
- (72) Inventors: BUTTRICK, James N.; 100 North Riverside Plaza, Chicago, Illinois 60606 (US). BANKS, David P.; 100 North Riverside Plaza, Chicago, Illinois 60606 (US). STEWART, Dennis W.; 100 North Riverside Plaza, Chicago, Illinois 60606 (US). SANCHEZ, Jesus; 100 North Riverside Plaza, Chicago, Illinois 60606 (US). MODIN, Andrew E.; 100 North Riverside Plaza, Chicago, Illinois 60606 (US). DEPASE, Edoardo P.; 100 North Riverside Plaza, Chicago, Illinois 60606 (US).


(74) Agents: SOUCY, Kathryn A. et al.; THE BOEING COMPANY, P.O. Box 2515, MC 110-SD54, Seal Beach, California 90740-1515 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR FABRICATING CONTOURED LAMINATE STRUCTURES



(57) Abstract: A plurality of identical fabrication modules are linked together and configurable to fabricate any of a plurality of differing laminate structures in a family of structures having common features. Each of the fabrication modules is locally adapted to fabricate a section of the laminate structure on a corresponding tool. A controller controls and coordinates automated operation of the fabrication modules.

WO 2014/107243 A1



Published:

— *with international search report (Art. 21(3))*

METHOD AND APPARATUS FOR FABRICATING CONTOURED LAMINATE STRUCTURES

BACKGROUND INFORMATION

5 1. Field:

The present disclosure generally relates to fabrication of laminates, especially those that are contoured, and deals more particularly with a method and apparatus for automated layup and forming of different laminate structures within a family of
10 structures having common features.

2. Background

Composite structures, especially those having contours, sometimes have features that require that the structure be
15 formed of multiple parts. For example, in the aircraft industry, contoured composite fuselage barrel frame sections may be formed using a two-piece assembly comprising a channel section frame and a shear tie, mechanically fastened together. More recently, one-piece composite frame sections have been proposed that
20 employ braided composites, however this fabrication approach is time consuming and labor intensive, and may result in a frame that is heavier than desired. The problem of fabricating one-piece frame sections is more difficult in high production rate environments where production flow times may be important to
25 achieve manufacturing efficiencies.

Accordingly, there is a need for a method and apparatus for producing one-piece laminate structures, especially those that are contoured, which reduce labor and assembly time through automation. There is also a need for a method and apparatus for
30 producing different laminate structures within a family of structures having common features in order to reduce material and labor costs while increasing production rates. Furthermore, there is a need for a method and apparatus for fabricating laminate structures using certain material forms such as

unidirectional prepreg tape, that may not be producible using conventional, manual fabrication methods.

SUMMARY

5 The disclosed embodiments provide a method and apparatus for producing different composite laminate structures within a family of structures having common features. The apparatus comprises an automated, reconfigurable composite forming system especially designed to form unidirectional prepreg tape in the
10 production of structural members, such as aircraft fuselage frames. The apparatus comprises a plurality of substantially identical forming modules linked together to form a single former that may be reconfigured to conform to a wide range of tools defining corresponding structural shapes. Each of the
15 forming modules possesses the ability to locally adapt or transform to the unique design, shape or features of the tool. In one aircraft application, the apparatus may be employed to fabricate multi-ply composite frame sections having a Z cross-sectional shape, by laying up, forming and compacting each ply
20 of the frame section. The plies are formed from an inner chord outwardly to an outer chord, sometimes referred to as a shear tie. Each of the forming modules adapts to the local shape of the tool. The modules are linked together in a manner to form a single former that adjusts to the entire tool. Different tool
25 arc lengths can be accommodated by adding or removing forming modules. It is not necessary that the forming modules exactly match the total arc length of a tool in those cases where the structure is contoured. The apparatus employs an adaptive control system based on a generic structural shape profile of
30 structures within a family of structures. The adaptive control system forms each ply of the structure based on a combination of force feedback and positional control. Each forming module has two servo axes and employs force feedback on one of these two axes at a time. The use of force feedback is dependent upon the

area of the structure being formed. During the forming process, the feedback switches back and forth between the two axes. Switching between the two axes is controlled by the adaptive system and is determined by generic shape parameters of the structure being formed. Reliance on a generic motion profile allows the apparatus to form any of a multiplicity of unique structures, ply-by-ply without the need for NC (numerical control) programming. The apparatus is easily scalable to fabricate structures of different sizes within a family of structures by adding or removing forming modules, and arranging the modules to substantially match corresponding tool shapes.

According to one disclosed embodiment, a system is provided for fabricating a plurality of unique parts. The system comprises a plurality of unique layup tools respectively corresponding to the plurality of parts to be fabricated and, a plurality of former modules configured to be combined together to define a plurality of unique formers respectively corresponding to the plurality of parts and the plurality of layup tools. Each of the formers is adapted for laying down material on a corresponding one of the layup tools to form a corresponding one of the parts. The former modules are substantially identical, and each of the plurality of unique formers is configured by coupling each of the substantially identical former modules to the corresponding unique layup tool. The former modules are linked together and are mounted on bases allowing the former modules to move in multiple directions. Each of the former modules includes a forming head adapted to form the material on a corresponding one of the layup tools. Each of the forming heads includes compliance. The part may be a laminated structure, and the laminated structure may be a carbon fiber reinforced plastic.

According to another disclosed embodiment, apparatus is provided for fabricating each of a plurality of differing laminate structures in a family of structures having common features. The apparatus comprises a plurality of separate
5 fabrication modules each locally adapted to fabricate a section of the laminate structure on a corresponding tool. The fabrication modules are reconfigurable to fabricate each of the laminate structures in the family thereof. The apparatus also includes a controller for controlling and coordinating automated
10 operation of the fabrication modules. The apparatus may further comprise a forming member adapted for forming laminate plies over the tool. The forming member extends along a length of the fabrication modules, and is mounted on each of the fabrication modules for movement over the tool along at least two axes. The
15 forming member is continuous along the length of the fabrication modules. The forming member is controlled along two axes, but has a shape that adapts to changes between different areas of the structure being formed, such as, in the case of a one-piece aircraft fuselage frame, between an inner chord radius and a
20 shear tie radius of the frame. Each of the fabrication modules includes a track in which a portion of the forming member is locally mounted. A single forming member may be used to fabricate a particular structure, however the forming member is removably mounted in the track to allow interchangeability of a
25 plurality of forming members respectively having different shapes to fabricate differently shaped structures. The track allows for lateral (or tangential) slip of the forming member relative to each module as the arc length of the structure changes as the forming member moves over the structure. The
30 forming member is adapted to sweep laminate plies over the tool, and includes compliance. Each of the fabrication modules includes a clamp adapted for clamping a portion of a laminate ply against a portion of the tool. Each of the fabrication modules includes a powered drive coupled with the forming member

for sweeping the forming member over the laminate plies and compacting laminate plies on the tool. The apparatus may further comprise a flexible ply carrier adapted to hold at least one laminate ply thereon, wherein each of the fabrication modules includes a pair of spaced apart tracks adapted to releasably hold the ply carrier, and a ply carrier control assembly for holding the ply carrier in tension as the forming member forms the ply over the tool. The forming member is engageable with the ply carrier to sweep the ply carrier along with the ply thereon over the tool, and the ply carrier control assembly includes drives for adjusting the position ply carrier along two axes. Each of the fabrication modules further includes a force sensor for sensing a level of force applied to the laminate plies by the forming member, and a position sensor for sensing the position of the forming member. Each of the fabrication modules further includes a clamp for clamping the fabrication module to the tool. The apparatus may also comprise linkage between the fabrication modules for coupling the fabrication modules together and for aligning the fabrication modules relative to the tool. The linkage is configured to allow the forming modules to rotate along an arc that is substantially the same as the retracted arc of the continuously extending forming member. The fabrication modules are substantially identical and interchangeable with each other. The apparatus also includes a central controller for controlling and coordinating the operation of the fabrication modules to collectively fabricate the laminate structure.

According to still another embodiment, a method is provided of fabricating a plurality of differing parts in a family of parts having common features, wherein each of the parts is fabricated using a unique tool. The method comprises arranging a plurality of separate, substantially identical fabrication modules to substantially match a tool on which one of the parts

is to be fabricated, and adapting each of the fabrication modules to a local section of the tool. The method further comprises controlling and coordinating operation of the fabrication modules to fabricate portions of the part over a corresponding section of the tool. Arranging the fabrication modules includes moving each of the fabrication modules into proximity to the tool, and linking the fabrication modules together. The method may further comprise clamping each of the fabrication modules to the tool. Adapting each of the fabrication modules includes learning, by each of the fabrication modules, the location of surfaces on the tool on which the part is to be fabricated. The method may also comprise sweeping materials across the surfaces of the tool using a forming member, and using the forming member to learn the location of the surfaces on the tool. Learning the location of the surfaces includes sensing the position of the forming member as the forming member sweeps materials across the surfaces of the tool, and recording the sensed position of the forming member. Adapting each of the fabrication modules includes adjusting the elevation of the fabrication modules to a common waterline. The method may further comprise forming a continuous spline along all of the fabrication modules. Forming the continuous spline includes mounting a continuous forming member along substantially the entire length of the fabrication modules. Each of the fabrication modules may be a laminate ply former module for forming a local section of a ply. Arranging the fabrication modules includes linking the fabrication modules together to form a single laminate ply former.

According to another disclosed embodiment, a method is provided of fabricating a composite laminate structure. The method comprises arranging a plurality of substantially identical forming modules to generally match a tool on which composite plies are to be formed to fabricate the laminate

structure, and linking the forming modules together to form a single former for forming an entire composite laminate structure. The method further comprises mounting a continuous forming member on the forming modules, the continuous forming member defining a spline extending substantially the entire length of the former, and using the forming member to form and compact the composite plies on the tool. The method may also include placing the composite plies on a ply carrier. The forming member is used to engage and sweep the ply carrier along with the plies over the tool.

According to still another disclosed embodiment, a forming module is provided for forming a composite laminate part over a tool. The forming module comprises a base and a ply carrier control assembly adapted for controlling the position of a flexible ply carrier on which composite resin plies are mounted. The forming module further comprises a head section mounted on the base and adapted for automatically forming the composite resin plies from the ply carrier onto the tool. The base is adapted to move over a supporting surface, and the head section includes adaptive control for learning a profile of the tool. The forming module may further include a clamp for clamping the head section to the tool, and an automatically controlled forming member for forming the plies over the tool.

According to an aspect of the present disclosure there is provided a system for fabricating a plurality of unique parts, comprising: a plurality of unique layup tools respectively corresponding to the plurality of parts to be fabricated, and, a plurality of former modules configured to be combined together to define a plurality of unique formers respectively corresponding to the plurality of parts and the plurality of layup tools, each of the formers being adapted for laying down material on a corresponding one of the layup tools to form a

corresponding one of the parts. Advantageously the system wherein the former modules are substantially identical, and each of the plurality of unique formers is configured by coupling each of the substantially identical former modules to the corresponding unique layup tool. Advantageously the system wherein the former modules are mounted on bases allowing the former modules to move in multiple directions. Advantageously the system wherein former modules are rigidly linked together. Advantageously the system wherein each of the former modules includes a forming head section adapted to form the material on a corresponding one of the layup tools. Advantageously the system wherein each of the forming head sections includes compliance. Advantageously the system wherein the compliance is removed when the former modules are coupled to the layup tool. Advantageously the system wherein the part is a laminated structure. Advantageously the system wherein the part is a carbon fiber reinforced plastic.

According to a further aspect of the present disclosure there is provided an apparatus for fabricating each of a plurality of differing laminate structures in a family of structures having common features, comprising: a plurality of separate fabrication modules each locally adapted to fabricate a section of the laminate structure on a corresponding tool, the fabrication modules being reconfigurable to fabricate each of the laminate structures in the family thereof, and a controller for controlling and coordinating automated operation of the fabrication modules. Advantageously the apparatus further comprises a forming member adapted for forming laminate plies over the tool, the forming member extending along a length of the fabrication modules, the forming member being mounted on each of the fabrication modules for movement over the tool along at least two axes. Advantageously the apparatus wherein the forming member is continuous along the length of the fabrication

modules...Advantageously the apparatus wherein each of the fabrication modules includes a track in which a portion of the forming member is local mounted. Advantageously the apparatus wherein the forming member is removably mounted in the tracks to
5 allow interchangeability of a plurality of forming members respectively having different shapes. Advantageously the apparatus wherein the forming member is adapted to sweep laminate plies over the tool, and includes compliance. Advantageously the apparatus wherein each of the fabrication
10 modules includes a clamp adapted for clamping a portion of a laminate ply against a portion of the tool. Advantageously the apparatus wherein each of the fabrication modules includes a powered drive coupled with the forming member for sweeping the forming member over the laminate plies and compacting laminate
15 plies on the tool. Advantageously the apparatus further comprises: a flexible ply carrier adapted to hold at least one laminate ply thereon, and wherein each of the fabrication modules includes a pair of spaced apart tracks adapted to releasably hold the ply carrier, and a ply carrier control
20 assembly for holding the ply carrier in tension as the forming member forms the ply over the tool. Advantageously the apparatus wherein: the forming member is engageable with the ply carrier to sweep the ply carrier along with the ply thereon over the tool, and the ply carrier control assembly includes drives
25 for adjusting a position of the ply carrier along two axes. Advantageously the apparatus wherein each of the fabrication modules further includes: a force sensor for sensing a level of force applied to the laminate plies by the forming member, and a position sensor for sensing the position of the forming member.
30 Advantageously the apparatus wherein each of the fabrication modules includes a clamp for clamping the fabrication module to the tool. Advantageously the apparatus further comprises linkage between the fabrication modules for rigidly coupling the fabrication modules together and for aligning the fabrication

modules relative to the tool. Advantageously the apparatus wherein the fabrication modules are substantially identical and interchangeable with each other. Advantageously the apparatus further comprises a central controller for controlling and
5 coordinating the operation of the fabrication modules to collectively fabricate the laminate structure.

According to yet a further aspect of the present disclosure there is provided a method of fabricating each of a plurality of
10 differing parts in a family of parts having common features, wherein each of the parts is fabricated using a unique tool, comprising: arranging a plurality of separate, substantially identical fabrication modules to substantially match a tool on which one of the parts is to be fabricated, adapting each of the
15 fabrication modules to a local section of the tool, and, controlling and coordinating operation of the fabrication modules to fabricate portions of the part over a corresponding section of the tool. Advantageously the method wherein arranging the fabrication modules includes: moving each of the
20 fabrication modules into proximity to the tool, and rigidly linking the fabrication modules together. Advantageously the method further comprises: clamping each of the fabrication modules to the tool. Advantageously the method wherein adapting the each of the fabrication modules includes learning, by each
25 of the fabrication modules, the location of surfaces on the tool on which the part is to be fabricated. Advantageously the method further comprises: sweeping materials across the surfaces of the tool using a forming member, and using the forming member to learn the location of the surfaces on the tool.
30 Advantageously the method wherein learning the location of the surfaces includes: sensing a position of the forming member as the forming member sweeps materials across the surfaces of the tool, and recording the sensed position of the forming member. Advantageously the method wherein adapting each of the

fabrication modules includes adjusting the elevation of the fabrication modules to a common waterline. Advantageously the method further comprises: forming a continuous spline along all of the fabrication modules. Advantageously the method wherein
5 forming the continuous spline includes mounting a continuous forming member along substantially the entire length of the fabrication modules. Advantageously the method wherein: each of the fabrication modules is a laminate ply former module for forming a local section of a ply, and arranging the fabrication
10 modules includes linking the fabrication modules together to form a single laminate ply former.

According to yet a further aspect of the present disclosure there is provided a method of fabricating a composite laminate
15 structure, comprising: arranging a plurality of substantially identical forming modules to generally match a tool on which composite plies are to be formed to fabricate the laminate structure, linking the forming modules together to form a single former for forming an entire composite laminate structure,
20 mounting a continuous forming member on the forming modules, the continuous forming member defining a spline extending substantially the entire length of the former, and using the forming member to form and compact the composite plies on the tool. Advantageously the method further comprises: placing the
25 composite plies on a ply carrier, and wherein using the forming member includes engaging and sweeping the ply carrier along with the plies over the tool.

According to yet a further aspect of the present disclosure
30 there is provided a forming module for forming a composite laminate part over a tool, comprising: a base, a ply carrier control assembly adapted for controlling the position of a flexible ply carrier on which composite resin plies are mounted, and a head section mounted on the base and adapted for

automatically forming the composite resin plies from the ply carrier onto the tool. Advantageously the forming module wherein the base is adapted to move over a supporting surface. Advantageously the forming module further comprises a clamp for
5 clamping the head section to the tool. Advantageously the forming module wherein the head section includes an adaptive control for learning a profile of the tool. Advantageously the forming module further comprises a nosepiece for engaging the ply carrier and forming the plies onto the tool, the nosepiece
10 being mounted for movement on the head section along first and second axes. Advantageously the forming module wherein the head section includes a load cell for sensing the magnitude of a force applied by the nosepiece to the ply carrier and the tool. Advantageously the forming module wherein the base includes a
15 powered slide assembly for moving the head section along a third axis substantially orthogonal to the first and second axes. Advantageously the forming module wherein the head section includes at least one position sensor for sensing the position of the nosepiece. Advantageously the forming module wherein the
20 nosepiece has compliance allowing the nosepiece to conform to features of the tool. Advantageously the forming module wherein the ply carrier control assembly includes a device for controlling tension on the flexible ply carrier. Advantageously the forming module wherein the ply carrier control assembly is
25 mounted on the head section. Advantageously the forming module wherein the ply carrier control assembly includes an automatically controlled, motorized arm for supporting and displacing the ply carrier as the plies are being formed from the ply carrier onto the tool. Advantageously the forming
30 module wherein the head section includes a datum locator for locating a datum on the tool.

The features, functions, and advantages can be achieved independently in various embodiments of the present disclosure

or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

5

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode of use, further objectives and advantages thereof, will
10 best be understood by reference to the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

15 Figure 1 is an illustration of a block diagram of a system for fabricating any of a plurality of parts within a family having common features using corresponding tools and fabrication modules according to the disclosed embodiments.

20 Figure 2 is an illustration of a diagrammatic plan view of apparatus for fabricating contoured composite laminate structures.

Figure 3 is an illustration of a perspective view of a
25 composite laminate frame section having a Z-shaped cross-section.

Figure 4 is an illustration of a cross-sectional view of the frame section shown in Figure 3.

30

Figure 5 is an illustration of an end view of a tool having the frame section shown in Figures 3 and 4 laid up and compacted thereon.

Figure 6 is an illustration of a functional block diagram of the apparatus of Figure 2, shown clamped to the tool illustrated in Figure 5.

5 Figure 7 is an illustration of a perspective view of the apparatus, prior to being moved into proximity to and clamped to a tool, a ply carrier not shown for clarity.

10 Figure 8 is an illustration of a front perspective view of three adjacent fabrication modules forming part of the apparatus shown in Figure 7.

15 Figure 9 is an illustration of a front perspective view of one of the fabrication modules shown in Figure 8, depicting additional details of the module.

Figure 10 is an illustration of a plan view of a ply carrier having a ply mounted thereon.

20 Figure 11 is an illustration of a front view of a nosepiece track forming part of each of the fabrication modules shown in Figures 7-9.

25 Figure 12 is an illustration of a perspective view of a portion of the length of a nosepiece adapted to be mounted on the nosepiece track shown in Figure 11.

30 Figure 13 is an illustration of a flow diagram of a method of fabricating each of a plurality of different parts in a family of parts having common features.

Figure 14 is an illustration of a flow diagram of a method of fabricating a composite laminate structure.

Figure 15 is an illustration of a flow diagram of the method used to set up and teach each of the fabrication modules.

Figure 16 is an end view of the tool shown in Figure 5, illustrating the progressive movement of the nosepiece during the set up and teaching phase shown in Figure 15.

Figure 17 is illustration of a flow diagram of an adaptive control method employed by each of the fabrication modules

Figure 18 is an illustration of a flow diagram of aircraft production and service methodology.

Figure 19 is illustration of a block diagram of an aircraft.

DETAILED DESCRIPTION

Referring first to Figure 1, a system 38 is provided for fabricating any of a plurality of unique parts 54 within a family 56 of parts 54 having common features or characteristics. The unique parts 54 may be fabricated using corresponding, unique tools 48, which may be layup tools, and a combination 43 of fabrication modules 42 arranged and configured to form a fabricator 40, sometimes hereinafter also referred to as a former 40. As will be discussed below in more detail, the fabrication modules 42 may be identical and interchangeable. The number and arrangement of the fabrication modules 42 is matched to the particular tool 48 required to fabricate a particular part 54. The fabricator 40 fabricates the part 54 by placing and forming material 46 on the particular tool 48. In one application, the part 54 may be a multi-ply composite laminate, and the material 46 may be a carbon fiber reinforced plastic (CFRP).

Attention is now directed to Figure 2 which illustrates one embodiment of the system 38 shown in Figure 1. In this example, a plurality of former modules 42 are arranged in a configuration generally matching the shape of a layup tool 48 on which a particular part (not shown in Figure 2) is to be formed. In the illustrated example, the former modules 42 are arranged in an arc shape that substantially matches the arc shaped layup tool 48, however, a variety of other shapes are possible. The former 40 forms and laminates composite plies 46 on the tool 48. The former modules 42 are rigidly connected with each other by linkage 44 to form a former 40. The former 40 self-adapts and aligns itself to each particular tool 48 required to make a particular part 54 (Figure 1). The former modules 42 may be substantially identical to each other and are thus interchangeable 50 with modules 42a purposes of repair, replacement or reconfiguration of the former 40 to form unique parts within a family of parts having common features or characteristics. Each of the former modules 42 is coupled with a central controller 52 which may comprise a special or general purpose computer, or a PLC (programmable logic controller). The central controller 52 controls and coordinates the automated operation of the former modules 42.

As previously mentioned, the former 40 may be used to form a variety of composite parts within a family of parts having common features or characteristics. For example, referring to Figures 3 and 4, the former 40 may be used to form and laminate a composite frame section 58 used in an aircraft fuselage (not shown). The frame section 58 is curved or contoured along its length and has a radius "R". The former 40 may be used to form any of a range of frame sections 58 having different arc lengths, radii or other common features within a family of frame sections 58. These features, including contours or radii, may be continuous or non-continuous along the length of the frame

section 58 or other parts being formed. The frame section 58 is generally Z-shaped in cross section, and comprises an inner chord flange 62 and an outer chord flange 64 (sometimes also referred to as a shear tie 64). The inner and outer chord flanges 62, 64 respectively are connected by a central web 60. The shear tie 64 is connected to the web 60 by a shear tie radius 68, and the inner chord flange 62 is connected to the web 60 by an inner chord radius 70. While a Z-shaped frame section 58 has been illustrated in the exemplary embodiment, it should be noted that the disclosed method and apparatus may be employed to fabricate composite laminate parts having a variety of other cross-sectional shapes, including but not limited to L, I and C cross-sectional shapes.

Referring now to Figure 5, the former 40 forms and laminates composite prepreg plies 46 on a tool 48. The tool 48 has tool features matching the frame section 58. In this example, the tool 48 includes an inner chord tool flange 72, an inner chord tool radius 74, a tool web 76, shear tie tool radius 78 and an outer chord tool flange 80. The tool 48 also includes a clamping flange 82 extending around its entire inner chord. Other types of layup tools 48 may be used in connection with the disclosed method and apparatus to form other types and sizes composite laminate parts, having cross-sectional shapes other than Z cross-sections. Moreover, the illustrated tool 48 may be employed to layup a curved composite laminate frame section or other part having an L-shaped cross-section.

Attention is now directed to Figures 6-9 which illustrate one embodiment of the former 40. Figure 6 is a functional block diagram showing one of the former modules 42, in the process of laying up a single prepreg ply 46 on the tool 48. The ply 46 is supported in a desired, or indexed position on a ply carrier 84 discussed below in more detail. The ply carrier 84 is held along

its upper edge on a carrier track 120 at the end of a support arm 95 forming part of the former module 42. The former module 42 broadly comprises a ply carrier control assembly 86 mounted on a head section 92 which is supported on a movable base 106.

5 The base 106 may include an on-board controller 110 that is coupled with the central controller 52 (Figure 2) previously discussed. Wheels or casters 112 on the base 106 allow the former module 42 to be moved along a supporting surface such as a factory floor (not shown) in any direction in order to allow
10 the former module 42 to be positioned in a desired configuration with other former modules 42, such that the collective geometry of the former modules 42 substantially matches that of the tool 48. The base 106 includes a Z-axis slide assembly 108 which moves the head section 92 and the ply carrier control assembly
15 86 in the vertical direction, or Z-axis within a machine coordinate system 124.

The ply carrier control assembly 86 controls the attitude of, and tension on the ply carrier 84 in order to support and
20 continuously reposition position the ply 46 as it is being formed onto the tool 48. The ply carrier control assembly 86 may include a motorized drive system which moves the support arm 95 and thus the carrier support track 120 along both the Y and Z axes. For example, the motorized drive system may comprise a
25 servo-motor 88 for driving the carrier support track 120 along the Y axis, and an air cylinder 90 for driving the support arm 95 and the carrier support track 120 along the Z axis. Other drive arrangements are possible.

30 The head section 92 includes a ply forming member, referred to hereinafter as a nosepiece 116, which engages the ply carrier 84 and follows the shape of the tool 48 to form and compact the ply 46 onto the tool 48. The nosepiece 116 is removably mounted in a nosepiece track 118 discussed later in more detail. The

nosepiece 116 extends continuously along the entire arc length of the tool 48, and effectively forms a spline between the forming modules 42. Both the nosepiece 116 and the track 118 may be flexible along their length to conform to the curvature and other features of the tool 48. The nosepiece track 118 is coupled with a motorized drive system which may comprise, for example and without limitation, a plurality of air cylinders 102 which move the nosepiece 116 in the Y direction.

Movement of the nosepiece 116 in the Z direction may be effected through movement of the head section 92 by the Z-axis slide assembly 108 on the base 106. The head section 92 further includes an inner chord clamp 122 driven in the Y direction by air cylinders 104 or similar motor drives. The inner chord clamp 122 clamps the lower edge of the ply carrier 84 and the ply 46 against the inner chord tool flange 72 (Figure 5) while the ply 46 is being formed over other surfaces of the tool 48. The head section 92 may include a datum locator 98 which may comprise, for example and without limitation, a proximity sensor, as well as servo-motors 94 and encoders 96. The servo-motors 94 and the encoders 96 may be used to determine the position of the nosepiece 116, and thus the location of surfaces on the tool 48, during an adaptive tool learning process discussed below. One or more load cells 100 on the head section 92 may be used to sense the amount of force being applied by the nosepiece 116 during both the learning and ply forming processes.

As can be appreciated from the foregoing description, the former 40 provides 2-axis (Y-Z) controlled sweeping of prepreg plies with 2-axis coordinated motion. However, motion is not limited to 2 axes. For example, the required motion may be accomplished using multiple robots (not shown) operating in unison. The adaptive control employed by former 40 allows the former 42 to adapt to each particular tool 48 used to make any

of a number of parts within a family of parts, by using a generic profile of the parts in the family, and force feedback to learn and follow the specific tool and part geometry. The adaptive control used by the former 40 also automatically adapts or adjusts to the shape of the part 54 as the thickness of the part 54 increases with layup of each successive ply 46. The use of a combination of position control and motor torque feedback allow constant pressure to be applied by the nosepiece 116 to the part 54 during the forming process.

As shown in Figure 7, the tool 48 may be supported on a wheeled cart 126 for movement into proximity with a former 40 comprising a plurality of former modules 42 that have been configured to substantially match the geometry of the tool 48. The former modules 42 are rigidly connected together by mechanical linkages 44 (see Figure 8) between bases 106 of adjacent former modules 42. Referring particularly to Figure 9, the ply carrier control assembly 86 (Figure 6) includes a Z-axis slide support allowing movement of the support arm 95 (see Figures 6-8) along the Z axis, and a slide 130 providing movement of the support arm 95 along the Y-axis. Tool clamps 114 driven by air cylinders 136 function to clamp the flange 82 (Figure 5) of the tool 48 against an index plate 132 which establishes a common "waterline" or reference datum, for all of the former modules 42, automatically aligning all of the former modules 42 relative to the tool 48. Each of the former modules 42 includes a slight amount of "float" that allows each of the head sections 92 to align to the tool waterline and then lock into position. As a result of this feature, the tool 48 does not have to be located on a precise platform, and the forming process can be carried out on standard factory floors that may be uneven. Although not shown in the drawings, the tool 48 and/or the plies 46 may be heated during a layup process in order to soften the resin and facilitate forming. Heating may be

achieved using any suitable technique, including but not limited to infrared radiation using IR heat lamps.

Referring to Figure 10, the ply carrier 84 may be formed of a flexible, durable material that may be stretchable in one or more directions, for example along its width "W". One or more plies 46 may be placed in preselected, indexed positions on the ply carrier 84 prior to the ply carrier 84 being loaded onto the former 40. The ply carrier 84 may include upper and lower carrier guides 140, 142 that are used to removably mount the ply carrier on the former 40. For example, the upper carrier guide 140 may include individual guide members (not shown) on the back of the ply carrier 84 which are received within a groove (not shown) in the carrier support track 120. Similarly, the lower carrier guide 142 may comprise a continuous guide strip (not shown) on the back of the ply carrier 84 which is received within a groove (not shown) extending along the inner chord clamp 122.

Figure 11 illustrates further details of one embodiment of the nosepiece track 120. In this example, the nosepiece track 120 comprises a plurality of spaced apart segments 144 which allow the track 120 to flex as required to permit the nosepiece 116 to conform to features of the tool 48. As shown in Figure 12, the nosepiece 116 includes an outer forming tip 146 that has a profile suited for the particular application and features of the tool 48. The nosepiece 116 is mounted on the nosepiece track 120 by a T-shaped guide 148 that is slidably received within a groove 145 in the nosepiece track 120. The nosepiece 116 may be removably installed in the nosepiece track 120 by sliding it lengthwise through the groove 145. Thus, nosepieces 116 having different sizes and shapes are interchangeable, allowing selection of a nosepiece 116 that is suitable for the application and tool shape. The nosepiece 116 may be compliant

in order to better conform it to features of the tool 48 during the forming process.

Figure 13 broadly illustrates the steps of a method of fabricating each of the plurality of differing parts 54 in a family 56 of parts 54 having common features, wherein each of the parts 54 is fabricated using a unique tool 48. Beginning at 154, identical fabrication modules 42 are arranged to match a tool 48 in which the part 54 to be fabricated. At 156, each of the fabrication modules 42 is adapted to a local section of the tool 48. At 158, operation of the fabrication modules 42 is controlled and coordinated to fabricate portions of the part 54 over a corresponding section of the tool 48.

Figure 14 broadly illustrates the steps of a method of fabricating a composite laminate structure 54. Beginning at 160, a plurality of forming modules 42 are arranged to match a tool 48 on which the structure 54 is to be formed. At 162, the modules 42 are linked together to form a single former 40 for forming the entire composite laminate structure 54. At 164, a continuous forming member 116 is mounted on the forming modules 42. The forming member 116 defines a spline extending substantially the entire length of the former 40. At 166, the forming member 116 is used to form and compact composite plies 46 on the tool 48.

Attention is now directed to Figure 15 which broadly illustrates the steps that may be carried out to set up and teach each of the forming modules 42 in preparation for a forming process using a particular tool 48. At 168, former 40 is set up by arranging and linking former modules 42 together using linkages 44, and initializing settings of each of the modules 42. Then, at 170, the linked former modules 42 are moved to engage and lock onto the tool 48. The tool clamps 114 (Figure 9)

clamp the flange 82 (Figure 5) of the tool 48 against the tool waterline index plate 132. The former modules 42 are aligned to match the curvature of the tool 48, and the linkage 44 maintains the shape and alignment of the former modules 42. At 172, the former module 42 is taught the position of the inner chord clamp relative to the tool 48, and at 174 the position of the nosepiece relative to the tool 48 is learned. At 176, the servo-motors 94 (Figure 6) and the encoders 96 are used to initially learn the shape of the tool, and then to relearn the surface of the laminated plies 46 as each of the plies 46 is laid up.

Attention is now directed to Figures 16 and 17 which illustrate additional details of the disclosed forming method. Beginning at 178 (Figure 17), the tool 48 is moved into proximity to the former 40, and at 180, the tool 48 is clamped to the former 40. At 182, one or more plies 46 are mounted on the ply carrier 84. At 184, the ply carrier 84 having the ply 46 mounted thereon is loaded onto the former 40. This loading process is performed by inserting the bottom carrier guide 142 into the former at 186, and at step 188, inserting the top guide 140 into the upper guide rail track 120 on the former 40. At 190, the position of the nosepiece 116 along the Y-axis is determined by driving the nosepiece 116 forward along the Y-axis into contact with the inner chord flange 72 using a predetermined motor torque. An encoder 96 coupled with the servo-motor 94 is read to indicate the position of the nosepiece 116. At 192, the nosepiece 116 is pressed against the inner chord flange with a predetermined amount of force. At 194, the nosepiece 116 is moved upwardly along the Z-axis at a predetermined rate. The ply 46 is swept and compacted against the inner chord tool surface 72, at step 194.

At 196, the transition of the nosepiece 116 from the inner chord tool surface 72 to the web tool surface 76 is sensed by

monitoring a Y-axis encoder 96 for a change. At 198 control of the nosepiece 116 along the Y-axis is switched from a torque mode to a position mode, and along the Z-axis from a position mode to a torque mode. The nosepiece 116 maintains compaction pressure against the ply 46 during the transition over the inside corner 74 of the inner chord to web radius. At 200, the nosepiece 116 sweeps and compacts the ply against the web tool surface 76 on the tool 48. At 202, movement of the nosepiece 116 is terminated when the nosepiece 116 is a short distance from the shear tie radius 78. At 204, the nosepiece 116 is used to "discover" the shape of the shear tie radius 78. This is accomplished by advancing the nosepiece 116 along the Y-axis until a preselected torque limit is reached. At step 206, control of the nosepiece 116 is switched to the torque mode along the Y-axis and along the Z-axis. At 208, the nosepiece 116 sweeps and compacts apply against the shear tie tool surface 80. During this step, the nosepiece 116 applies force along the Y-axis in the torque mode, while being driven upwardly along the Z-axis in the position mode. At step 210 the ply forming process is complete and steps 182-208 may be repeated to layup, form and compact additional plies.

Embodiments of the disclosure may find use in a variety of potential applications, particularly in the transportation industry, including for example, aerospace, marine, automotive applications and other application requiring automated fabrication of a variety of parts within a family of parts having common features or characteristics. Thus, referring now to Figures 19 and 20, embodiments of the disclosure may be used in the context of an aircraft manufacturing and service method 212 as shown in Figure 19 and an aircraft 214 as shown in Figure 20. Aircraft applications of the disclosed embodiments may include, for example, without limitation, fuselage frame sections, spars, stringers and other structural members, to name

only a few. During pre-production, exemplary method 212 may include specification and design 216 of the aircraft 214 and material procurement 218. During production, component and subassembly manufacturing 220 and system integration 222 of the aircraft 214 takes place. Thereafter, the aircraft 214 may go through certification and delivery 224 in order to be placed in service 226. While in service by a customer, the aircraft 214 is scheduled for routine maintenance and service 228, which may also include modification, reconfiguration, refurbishment, and so on.

Each of the processes of method 212 may be performed or carried out by a system integrator, a third party, and/or an operator (e.g., a customer). For the purposes of this description, a system integrator may include without limitation any number of aircraft manufacturers and major-system subcontractors; a third party may include without limitation any number of vendors, subcontractors, and suppliers; and an operator may be an airline, leasing company, military entity, service organization, and so on.

As shown in Figure 20, the aircraft 214 produced by exemplary method 212 may include an airframe 230 with a plurality of systems 232 and an interior 234. Examples of high-level systems 232 include one or more of a propulsion system 236, an electrical system 238, a hydraulic system 240, and an environmental system 242. Any number of other systems may be included. Although an aerospace example is shown, the principles of the disclosure may be applied to other industries, such as the marine and automotive industries.

Systems and methods embodied herein may be employed during any one or more of the stages of the production and service method 212. For example, components or subassemblies

corresponding to production process 220 may be fabricated or manufactured in a manner similar to components or subassemblies produced while the aircraft 214 is in service. Also, one or more apparatus embodiments, method embodiments, or a combination thereof may be utilized during the production stages 220 and 222, for example, by substantially expediting assembly of or reducing the cost of an aircraft 214. Similarly, one or more of apparatus embodiments, method embodiments, or a combination thereof may be utilized while the aircraft 242 is in service, for example and without limitation, to maintenance and service 228.

The description of the different illustrative embodiments has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different illustrative embodiments may provide different advantages as compared to other illustrative embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

CLAIMS:

What is claimed is:

1. A system for fabricating a plurality of unique parts,
5 comprising:

a plurality of unique layup tools respectively
corresponding to the plurality of parts to be fabricated; and,

a plurality of former modules configured to be combined
together to define a plurality of unique formers respectively
10 corresponding to the plurality of parts and the plurality of
layup tools,

each of the formers being adapted for laying down material
on a corresponding one of the layup tools to form a
corresponding one of the parts.

15 2. The system of claim 1, wherein:

the former modules are substantially identical, and

each of the plurality of unique formers is configured by
coupling each of the substantially identical former modules to
20 the corresponding unique layup tool.

3. The system of claim 1, wherein the former modules are
mounted on bases allowing the former modules to move in multiple
directions.

25 4. The system of claim 1, wherein former modules are rigidly
linked together.

5. The system of claim 1, wherein each of the former modules
30 includes a forming head section adapted to form the material on
a corresponding one of the layup tools.

6. The system of claim 5, wherein each of the forming head
sections includes compliance.

7. The system of claim 6, wherein the compliance is removed when the former modules are coupled to the layup tool.

5 8. The system of claim 1, wherein the part is a laminated structure.

9. The system of claim 1, wherein the part is a carbon fiber reinforced plastic.

10 10. Apparatus for fabricating each of a plurality of differing laminate structures in a family of structures having common features, comprising:

a plurality of separate fabrication modules each locally adapted to fabricate a section of the laminate structure on a corresponding tool, the fabrication modules being reconfigurable to fabricate each of the laminate structures in the family thereof; and

20 a controller for controlling and coordinating automated operation of the fabrication modules.

11. The apparatus of claim 10, further comprising:

25 a forming member adapted for forming laminate plies over the tool, the forming member extending along a length of the fabrication modules, the forming member being mounted on each of the fabrication modules for movement over the tool along at least two axes.

12. The apparatus of claim 11, wherein the forming member is continuous along the length of the fabrication modules.

13. The apparatus of claim 11, wherein each of the fabrication modules includes a track in which a portion of the forming member is local mounted.

14. The apparatus of claim 13, wherein the forming member is removably mounted in the tracks to allow interchangeability of a plurality of forming members respectively having different shapes.

15. The apparatus of claim 11, wherein the forming member is adapted to sweep laminate plies over the tool, and includes compliance.

16. The apparatus of claim 10, wherein each of the fabrication modules includes a clamp adapted for clamping a portion of a laminate ply against a portion of the tool.

17. The apparatus of claim 11, wherein each of the fabrication modules includes a powered drive coupled with the forming member for sweeping the forming member over the laminate plies and compacting laminate plies on the tool.

18. The apparatus of claim 11, further comprising:
a flexible ply carrier adapted to hold at least one laminate ply thereon, and

wherein each of the fabrication modules includes a pair of spaced apart tracks adapted to releasably hold the ply carrier, and a ply carrier control assembly for holding the ply carrier in tension as the forming member forms the ply over the tool.

19. The apparatus of claim 18, wherein:

the forming member is engageable with the ply carrier to sweep the ply carrier along with the ply thereon over the tool, and

the ply carrier control assembly includes drives for adjusting a position of the ply carrier along two axes.

20. The apparatus of claim 11, wherein each of the fabrication modules further includes:

a force sensor for sensing a level of force applied to the laminate plies by the forming member, and

5 a position sensor for sensing the position of the forming member.

21. The apparatus of claim 10, wherein each of the fabrication modules includes a clamp for clamping the fabrication module to
10 the tool.

22. The apparatus of claim 10, further comprising:

linkage between the fabrication modules for rigidly coupling the fabrication modules together and for aligning the
15 fabrication modules relative to the tool.

23. The apparatus of claim 10, wherein the fabrication modules are substantially identical and interchangeable with each other.

20 24. The apparatus of claim 10, further comprising a central controller for controlling and coordinating the operation of the fabrication modules to collectively fabricate the laminate structure.

25 25. A method of fabricating each of a plurality of differing parts in a family of parts having common features, wherein each of the parts is fabricated using a unique tool, comprising:

arranging a plurality of separate, substantially identical fabrication modules to substantially match a tool on which one
30 of the parts is to be fabricated;

adapting each of the fabrication modules to a local section of the tool; and,

controlling and coordinating operation of the fabrication modules to fabricate portions of the part over a corresponding section of the tool.

5 26. The method of claim 25, wherein arranging the fabrication modules includes:

moving each of the fabrication modules into proximity to the tool, and

rigidly linking the fabrication modules together.

10

27. The method of claim 25, further comprising:

clamping each of the fabrication modules to the tool.

15 28. The method of claim 25, wherein adapting the each of the fabrication modules includes learning, by each of the fabrication modules, the location of surfaces on the tool on which the part is to be fabricated.

29. The method of claim 28, further comprising:

20 sweeping materials across the surfaces of the tool using a forming member, and

using the forming member to learn the location of the surfaces on the tool.

25 30. The method of claim 29, wherein learning the location of the surfaces includes:

sensing a position of the forming member as the forming member sweeps materials across the surfaces of the tool, and

recording the sensed position of the forming member.

30

31. The method of claim 25, wherein adapting each of the fabrication modules includes adjusting the elevation of the fabrication modules to a common waterline.

32. The method of claim 25, further comprising:
forming a continuous spline along all of the fabrication modules.

5 33. The method of claim 32, wherein forming the continuous spline includes mounting a continuous forming member along substantially the entire length of the fabrication modules.

34. The method of claim 25, wherein:
10 each of the fabrication modules is a laminate ply former module for forming a local section of a ply, and
arranging the fabrication modules includes linking the fabrication modules together to form a single laminate ply former.

15 35. A method of fabricating a composite laminate structure, comprising:
arranging a plurality of substantially identical forming modules to generally match a tool on which composite plies are
20 to be formed to fabricate the laminate structure;
linking the forming modules together to form a single former for forming an entire composite laminate structure;
mounting a continuous forming member on the forming modules, the continuous forming member defining a spline
25 extending substantially the entire length of the former; and
using the forming member to form and compact the composite plies on the tool.

36. The method of claim 35, further comprising:
30 placing the composite plies on a ply carrier, and
wherein using the forming member includes engaging and sweeping the ply carrier along with the plies over the tool.

37. A forming module for forming a composite laminate part over a tool, comprising:

a base;

a ply carrier control assembly adapted for controlling the position of a flexible ply carrier on which composite resin plies are mounted; and

a head section mounted on the base and adapted for automatically forming the composite resin plies from the ply carrier onto the tool.

38. The forming module of claim 37, wherein the base is adapted to move over a supporting surface.

39. The forming module of claim 37, further comprising a clamp for clamping the head section to the tool.

40. The forming module of claim 37, wherein the head section includes an adaptive control for learning a profile of the tool.

41. The forming module of claim 37, further comprising a nosepiece for engaging the ply carrier and forming the plies onto the tool, the nosepiece being mounted for movement on the head section along first and second axes.

42. The forming module of claim 41, wherein the head section includes a load cell for sensing the magnitude of a force applied by the nosepiece to the ply carrier and the tool.

43. The forming module of claim 41, wherein the base includes a powered slide assembly for moving the head section along a third axis substantially orthogonal to the first and second axes.

44. The forming module of claim 41, wherein the head section includes at least one position sensor for sensing the position of the nosepiece.

5 45. The forming module of claim 41, wherein the nosepiece has compliance allowing the nosepiece to conform to features of the tool.

10 46. The forming module of claim 37, wherein the ply carrier control assembly includes a device for controlling tension on the flexible ply carrier.

15 47. The forming module of claim 37, wherein the ply carrier control assembly is mounted on the head section.

48. The forming module of claim 37, wherein the ply carrier control assembly includes an automatically controlled, motorized arm for supporting and displacing the ply carrier as the plies are being formed from the ply carrier onto the tool.

20 49. The forming module of claim 37, wherein the head section includes a datum locator for locating a datum on the tool.

1/10




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

3/10





FIG. 6






FIG. 8






FIG. 9



7/10




FIG. 12




FIG. 13




FIG. 14

8/10




FIG. 15




FIG. 16

9/10






FIG. 17

10/10

212
FIG. 18214
FIG. 19

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2013/071124

A. CLASSIFICATION OF SUBJECT MATTER

INV. B29C70/38 B29C70/54 B29D99/00
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

B29C B29D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EP0-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2010/024971 A1 (BENSON VERNON M [US] ET AL) 4 February 2010 (2010-02-04) abstract figure 6 paragraph [0040] paragraph [0060] - paragraph [0062] -----	1-9
X	US 2012/006475 A1 (COLOMBO DENIS [FR] ET AL) 12 January 2012 (2012-01-12) abstract figures 1,6A-6E,7 paragraph [0045] - paragraph [0059] paragraph [0065] paragraph [0075] - paragraph [0081] ----- -/--	10-34



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

14 February 2014

Date of mailing of the international search report

21/02/2014

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Lozza, Monica

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2013/071124

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 352 306 A (GRIMSHAW MICHAEL N [US] ET AL) 4 October 1994 (1994-10-04) abstract figures 5-7 column 3, line 44 - column 4, line 5 column 8, line 13 - column 10, line 17 -----	35, 36
X	US 2007/229805 A1 (ENGELBART ROGER W [US] ET AL) 4 October 2007 (2007-10-04) abstract figures 1-3 paragraph [0020] - paragraph [0027] -----	37-49

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2013/071124

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2010024971 A1	04-02-2010	CA 2711929 A1 EP 2240315 A1 US 2010024971 A1 WO 2009097514 A1	06-08-2009 20-10-2010 04-02-2010 06-08-2009
US 2012006475 A1	12-01-2012	CA 2752032 A1 DK 2408609 T3 EP 2408609 A2 ES 2421084 T3 FR 2942741 A1 MA 33099 B1 PT 2408609 E US 2012006475 A1 WO 2010100386 A2	10-09-2010 13-05-2013 25-01-2012 28-08-2013 10-09-2010 01-03-2012 23-05-2013 12-01-2012 10-09-2010
US 5352306 A	04-10-1994	EP 0626251 A1 US 5352306 A	30-11-1994 04-10-1994
US 2007229805 A1	04-10-2007	CA 2646818 A1 EP 2002245 A1 ES 2424320 T3 JP 2009531715 A JP 2013178257 A KR 20080106316 A US 2007229805 A1 WO 2007126891 A1	08-11-2007 17-12-2008 01-10-2013 03-09-2009 09-09-2013 04-12-2008 04-10-2007 08-11-2007