




US 20070256492A1

(19) **United States**(12) **Patent Application Publication**
Trogdon(10) **Pub. No.: US 2007/0256492 A1**(43) **Pub. Date: Nov. 8, 2007**(54) **NAUTICAL INSTRUMENT HAVING
SLIDABLE MOUNTING AND LOCKING**(76) Inventor: **Peter Trogdon**, Arnold, MD (US)Correspondence Address:
CHERNOW KATZ, LLC
721 DRESHER RD, SUITE 1100
HORSHAM, PA 19044 (US)(21) Appl. No.: **11/429,388**(22) Filed: **May 5, 2006****Publication Classification**(51) **Int. Cl.**
G01D 11/24 (2006.01)
G01C 21/00 (2006.01)(52) **U.S. Cl.** **73/178 R**(57) **ABSTRACT**

A nautical instrument that can be repetitively mounted to and removed from a surface within a ship without the use of tools or other instruments. The nautical instrument incorporates a mounting system that achieves slidable locking

engagement of the nautical instrument to a bulkhead plate that is permanently secured to the surface of the ship. In one embodiment, the invention comprises: a housing containing a gauge; a back plate connected to the housing and having a rear surface; a bracket assembly protruding from the rear surface of the back plate, the bracket assembly comprising a downwardly extending overhang section that forms first and second channels between the overhang section and the rear surface of the back plate, the channels opposing one another in an angled orientation that diverges from the top to the bottom of the nautical instrument; a bulkhead plate comprising means for securing the bulkhead plate to a surface of a boat; a mounting plate assembly connected to a front surface of the bulkhead plate in spaced relation, the mounting plate assembly having first and second angled edges that substantially corresponds to the angled orientation of the channels; and wherein the mounting plate assembly is adapted so that the first and second edges slidably insert into the first and second channels of the bracket assembly respectively when the rear surface of the back plate is positioned adjacent to and above the front surface of the bulkhead plate and the back plate is lowered, thereby effectuating mating engagement of the mounting plate assembly and the bracket assembly.








FIG. 1








FIG. 4











FIG. 5










FIG. 10A




FIG. 10C




FIG. 10B




FIG. 10D




FIG. 11A




FIG. 11B




FIG. 12A









FIG. 12B



NAUTICAL INSTRUMENT HAVING SLIDABLE MOUNTING AND LOCKING

FIELD OF THE INVENTION

[0001] The present invention relates generally to the field of nautical instruments and, specifically to nautical instruments having a mounting system that facilitates repetitive removal and re-mounting of the nautical instrument to a surface within a ship without the use of tools.

BACKGROUND OF THE INVENTION

[0002] A host of equipment, electronic devices, instruments, and gauges are used on ships, such as clocks, barometers, radio control clocks, comfort meters, tide clocks, temperature gauges, etc. It is often desirable for many of these nautical instruments to be mounted to a surface within the ship, such as a control deck, bulkhead, or other surface, during use.

[0003] In existing instruments, mounting is typically achieved by extending screws or bolts through holes in the casing of nautical instrument and into the desired surface. Such nautical instruments are undesirable in that the mounting requires the use of a tool, such as a screwdriver or wrench. Moreover, the screws or bolts are visible from the front face of the instruments, resulting in a less pleasing aesthetic appearance. Furthermore, securing the rear surface of the nautical instrument's housing directly against a surface of ship results in moisture and other possible contaminants getting trapped between the two. Trapped moisture and/or contaminants can negatively effect the accuracy and functioning of a nautical instrument. Finally, repetitive mounting and removal of such a nautical instrument damages the surface within the ship because the screws/bolts repetitively penetrate and make new holes in the ship's surface.

[0004] In other existing nautical instruments, mounting is achieved through the use of a bulky box-like casing in which the nautical instrument is inserted and locked into place. These box-like mounting systems, however, are less than optimal in that they occupy a lot of precious room in a ship's cabin. Moreover, such box-like mounting systems are not compatible with many instruments.

[0005] Some nautical instruments are designed to be mounted to the surface of a ship by utilizing a number of relatively inaccessible components that make removal of the instrument relatively burdensome. In still other instances, some nautical instruments are mounted on a lift bracket (or pedestal) located externally from the dashboard or desired mounting surface within the ship. Mounting on these brackets does not firmly secure the instrument to the ship. Further, the positioning of the device outside of flush alignment with a surface of the ship leaves the instrument exposed to damage by outside sources.

[0006] The above-noted deficiencies are compounded by the fact that it is oftentimes desirable to remove certain nautical instruments from the ship each and every time the user leaves his/her ship. For instance, some electronic nautical instruments allow the user to exchange information between the instrument and a personal computer. Generally, it is less burdensome to remove the instrument from the ship rather than move the computer onto the ship. Furthermore,

in some cases, it may be desired to use a single nautical instrument with a number of different ships by transferring the instrument from one ship to another.

[0007] Most commonly, however, nautical instruments are removed from the ship to prevent theft of the device. Theft is of particular concern with unguarded boats docked in public marinas. Thus, a nautical instruments is required that facilitates easy removal and mounting of the nautical instrument in a ship.

[0008] An additional problem is that existing nautical instruments do not stand up well against the harsh conditions experienced on a ship. For example, existing brass nautical instruments tend to tarnish very easily, thereby reducing their aesthetic appeal considerably. Most brass cased nautical instruments are laquered for tarnish protection. However, most laquers that permit maximum brass luster offer minimal life protection and partially wear away or easily scratch and chip, thereby rendering the exposed brass vulnerable to oxidation. While polishing the instrument with certain chemicals provides short term restoration and further erosion of the brass, such a temporary fix is unsatisfactory.

[0009] Finally, many nautical instruments tend to lose their water-tight attributes over time, which for obvious reasons, is undesirable.

SUMMARY OF THE INVENTION

[0010] It is therefore an object of the present invention to provide a nautical instrument that can be repetitively removed and mounted to a ship's surface without the use of tools and/or without damaging the mounting surface.

[0011] Another object of the present invention is to provide a nautical instrument that comprise a universal mounting system.

[0012] A further object of the present invention is to provide a nautical instrument that can be repetitively removed and mounted to a ship's surface in a secure manner that will not rotate with respect to and/or otherwise disengage from the ship's surface.

[0013] A still further object of the present invention is to provide a nautical instrument that can be slidably mounted to and disengaged from a ship's surface.

[0014] A yet further object of the present invention is to provide a nautical instrument that has increased watertight capabilities when mounted.

[0015] Still another object of the present invention is to provide a nautical instrument that provides a ventilation space between the instrument's back surface and the surface to which it is mounted.

[0016] Yet another object of the present invention is to provide a nautical instrument that minimizes and/or eliminates tarnishing.

[0017] Another object of the present invention is to provide a nautical instrument that can be mounted to a surface of a ship without any fasteners visible on the front face of the instrument.

[0018] These and other object are met by the present invention, which in one aspect, is a nautical instrument having a top and a bottom comprising: a housing containing

a gauge; a back plate connected to the housing and having a rear surface; a bracket assembly protruding from the rear surface of the back plate, the bracket assembly comprising a downwardly extending overhang section that forms first and second channels between the overhang section and the rear surface of the back plate, the channels opposing one another in an angled orientation that diverges from the top to the bottom of the nautical instrument; a bulkhead plate comprising means for securing the bulkhead plate to a surface of a boat; a mounting plate assembly connected to a front surface of the bulkhead plate in spaced relation, the mounting plate assembly having first and second angled edges that substantially corresponds to the angled orientation of the channels; and wherein the mounting plate assembly is adapted so that the first and second angled edges slidably insert into the first and second channels of the bracket assembly respectively when the rear surface of the back plate is positioned adjacent to and above the front surface of the bulkhead plate and the back plate is lowered, thereby effectuating mating engagement of the mounting plate assembly and the bracket assembly.

[0019] In one preferred embodiment, the bracket assembly comprises a first bracket comprising the first channel and a second bracket comprising the second channel. The first and second channels will preferably form an upside-down truncated V-shaped configuration. In such an embodiment, it is further preferred that the mounting plate assembly comprise a first mounting plate comprising the first angled edge and a second mounting plate comprising the second angled edge.

[0020] In order to provide stable mounting, the nautical instrument preferably comprises a means for pressing the overhang section of the bracket assembly against the mounting plate assembly during the mating engagement. In other words, it is desired that the overhang section be maintained under force against the mounting plate assembly during the mating engagement. In one embodiment, one or more protrusions extending from the rear surface of the back plate and pressing against the front surface of the bulkhead plate can be utilized to achieve this goal. The protrusion can be generally conical or semi-ellipsoid in shape.

[0021] In order to prohibit rotational movement of the backplate (and the housing) with respect to the bulkhead plate, a horizontal ridge and a guide channel can be provided on the front surface of the bulkhead plate. In this embodiment, at least three protrusions can be provided on the rear surface of the back plate. The three protrusions are preferably arranged on the back plate in a triangular arrangement. During mating engagement, one of the protrusions will extend into the guide channel and the other two protrusions will slide over the horizontal ridge and snap-lock to the underside of the horizontal ridge. This arrangement also prohibits the back plate from becoming easily dislodged from the bulkhead plate in the upward direction.

[0022] In another embodiment, the locking of the backplate to the bulkhead plate with a pressing force can be achieved by providing first and second locking plates that are connected to the rear surface of the back plate. Preferably, the locking plates are spaced from one another and the bracket assembly is located between them. One or more protrusions can extend from each of first and second locking plates. In this embodiment, when the bulkhead plate is secured to a planar surface of a ship and the backplate is

matingly engaged to the bulkhead plate (as described above), the protrusions on the locking plates contact and press against the planar surface of the ship, thereby providing a pressing force and maintaining the overhang section of the bracket assembly under force against the mounting plate assembly. As discussed below, this force can also be used to compress a gasket seal to hermetically seal the front face of the instrument.

[0023] In a preferred embodiment, first and second compression plates are positioned between the first and second locking plates and the back plate. The compression plates are preferably made of a rubber or plastic material. As with the protrusions on the backplate, the protrusions on the locking plates can be generally conical or semi-ellipsoid in shape.

[0024] Preferably, the nautical instrument further comprises a substantially transparent lens located within the housing. The lens preferably covers an opening in a front face of the housing. A gasket seal is preferably provided between the lens and the housing. The gasket seal, which can be an O-ring, is preferably located in a groove located on an inside surface of the front face of the housing. The front surface of the lens preferably has a beveled perimeter region against which the gasket seal is compressed.

[0025] In this embodiment of the nautical instrument, the compression plates that are located between the locking plates and back plate are preferably made of a material which is harder than the gasket seal. This ensures that the gasket seal is further compressed during the mounting of the nautical instrument by the force exerted by the protrusions on the locking plates.

[0026] In order to prohibit tarnishing, the housing is preferably constructed of zirconium plated brass. Finally, when the mounting plate assembly and the bracket assembly are matingly engaged, a ventilation space preferably exists between the rear surface of the back plate and the front surface of the bulkhead plate. The ventilation space allows air to circulate behind the nautical instrument, thereby preventing moisture and heat build-up.

[0027] In another aspect, the invention is a nautical instrument comprising: a housing containing a gauge; a back plate connected to the housing and having a top, a bottom and rear surface; a bracket assembly protruding from the rear surface of the back plate, the bracket assembly comprising a channel that is accessible from below the bracket assembly; a bulkhead plate comprising means for securing the bulkhead plate to a surface of a boat; a mounting plate assembly connected to a front surface of the bulkhead plate in a spaced relation, the mounting plate assembly having an edge that corresponds to the roof of the channel of the bracket assembly; and wherein when the rear surface of the back plate is positioned adjacent to and above the front surface of the bulk head plate and the back plate is lowered, the edge of the mounting plate assembly slidably inserts into the channel of the bracket assembly until the edge of the mounting plate assembly contacts the roof of the bracket assembly.

[0028] In yet another aspect, a nautical instrument comprising: a housing containing a gauge; a back plate connected to the housing and having a rear surface, a bottom, a top and vertical centerline; a first bracket protruding from

the rear surface of the back plate on one side of the centerline and a second bracket protruding from the rear surface of the back plate on the opposite side of the centerline; each of the brackets forming an elongated channel that angles inwardly toward the centerline from the bottom toward the top of the back plate, the channels being accessible from below the brackets and have a roof; a bulkhead plate having a top, a bottom and a front surface and comprising means for securing the bulkhead plate to a surface; first and second mounting plates connected to a front surface of the bulkhead plate in a spaced relation, the first mounting plate having a lateral edge that angularly corresponds to the channel of the first bracket and the second mounting plate having a lateral edge that angularly corresponds to the channel of the second bracket; and the lateral edges being spaced from one another so that when the rear surface of the back plate is positioned adjacent to and above the front surface of the bulk head plate and lowered, the lateral edges of the first and second plates slidably insert into the channels of the first and second brackets respectively until the lateral edges of the first and second plates come into contact with the roofs of the channels of the first and second brackets.

[0029] It should be noted that the inventive nautical instrument can take on a variety of embodiments, incorporating any single one or any combination of the features described in the detailed description below. For example, in a further aspect, the invention can be a nautical instrument comprising a housing constructed of zirconium-plated brass. In a still further aspect, the invention can be nautical instrument comprising a lens having a beveled perimeter region and gasket seal compressed against the beveled region. In a yet further aspect, the invention can be a nautical instrument comprising a universal dial plate.

BRIEF DESCRIPTION OF THE DRAWINGS

[0030] FIG. 1 is a bottom perspective of a nautical instrument according to an embodiment of the present invention.

[0031] FIG. 2 is an exploded view of the nautical instrument of FIG. 1.

[0032] FIG. 3A is a combined temperature and humidity indicia plate that can be incorporated into the nautical instrument of FIG. 1.

[0033] FIG. 3B is a barometric pressure indicia plate that can be incorporated into the nautical instrument of FIG. 1.

[0034] FIG. 3C is a clock indicia plate that can be incorporated into the nautical instrument of FIG. 1.

[0035] FIG. 4 is a right side view of the nautical instrument of FIG. 1.

[0036] FIG. 5 is a rear view of the nautical instrument of FIG. 1.

[0037] FIG. 6A is a rear view of the dial plate of the nautical instrument of FIG. 1 adapted for combined temperature and humidity measurement.

[0038] FIG. 6B is a rear view the dial plate of the nautical instrument of FIG. 1 adapted for barometric pressure measurement.

[0039] FIG. 6C is a rear view the dial plate of the nautical instrument of FIG. 1 adapted for time measurement.

[0040] FIG. 7 is a cross-sectional side view of the nautical instrument of FIG. 1 viewed along its vertical centerline.

[0041] FIG. 8 is a rear view of the housing of the nautical instrument of FIG. 1.

[0042] FIG. 9A is a front view of the lens of the nautical instrument of FIG. 1.

[0043] FIG. 9B is a side view of the lens of the nautical instrument of FIG. 1.

[0044] FIG. 10A is a rear view of the back plate of the nautical instrument of FIG. 1.

[0045] FIG. 10B is a top view of the back plate of the nautical instrument of FIG. 1.

[0046] FIG. 10C is a right side view of the back plate of the nautical instrument of FIG. 1.

[0047] FIG. 10D is a bottom view of the back plate of the nautical instrument of FIG. 1.

[0048] FIG. 11A is a rear view of the compression plates of the nautical instrument of FIG. 1.

[0049] FIG. 11B is a cross-sectional right side view of the compression plates of FIG. 11A.

[0050] FIG. 12A is a rear view of the locking plates of the nautical instrument of FIG. 1.

[0051] FIG. 12B is a cross-sectional right side view of the locking plates of FIG. 12A.

[0052] FIG. 13A is a front view of the bulkhead plate of the nautical instrument of FIG. 1.

[0053] FIG. 13B is a top view of the bulkhead plate of the nautical instrument of FIG. 1.

[0054] FIG. 13C is a right side view of the bulkhead plate of the nautical instrument of FIG. 1.

[0055] FIG. 13D is a bottom view of the bulkhead plate of the nautical instrument of FIG. 1.

[0056] FIG. 13E is a rear view of the bulkhead plate of the nautical instrument of FIG. 1.

DETAILED DESCRIPTION OF THE DRAWINGS

[0057] An embodiment of the inventive nautical instrument **100** will now be described in relation to FIGS. 1-13E. Throughout the description of the figures, like numbers are used to refer to like elements. While an embodiment of the invention will be described, the embodiment is in no way limiting of the present invention and various modifications and embodiments of the invention exist. The true scope of the invention is to be determined by the claims.

[0058] FIG. 1 is a bottom perspective view a nautical instrument **100** according to an embodiment of the present invention. While the nautical instrument **100** is a barometer, the invention is not limited to any specific type of nautical instrument. For example, the inventive nautical instrument **100** can take on a variety of functions, including without limitation radio control clocks, comfort meters, tide clocks, hygrometers, and any combination thereof. As will be discussed in greater detail below, the functioning of the inven-

tive nautical instrument can be altered by merely changing the interior measuring components, the indicia plate, and the dials.

[0059] The nautical instrument 100 is illustrated as being circular in shape but can take on any shape desired. Similarly, the nautical instrument 100 can take on any desired size. The nautical instrument 100, as illustrated in FIG. 1, is fully assembled. The nautical instrument 100 has a top 1, a bottom 2, a left side 3, a right side 4, a front 5 and a rear 6. As the various components of the nautical instrument 100 are described below, reference to the top, bottom, front and rear of any component will correspond to the top 1, bottom 2, front 5 and rear 6 of the nautical instrument 100 in general orientation.

[0060] Referring now to FIG. 2, the nautical instrument 100 is shown in an exploded fashion so that its major components are visible. The components of the nautical instrument 100 are assembled in the order in which they are arranged. The nautical instrument 100 comprises a housing 10, an O-ring 20, a transparent lens 21, dials 22, a knob 23, a gauge mechanism 24, an indicia plate 30, a dial plate 40, a back plate 50, compression plates 60, locking plates 70, and a bulkhead plate 80. Each of these components will first be described in detail with a discussion of their assembly and interaction to follow.

[0061] Referring to FIGS. 2 and 8 concurrently, the housing 10 is a casing comprising a wall portion 11 and a flange 12. The flange 12 surrounds the wall portion 11 at the rear of the housing 10. At its front face, the wall portion 11 of the housing terminates in a curved edge 15. As will be discussed below, the curved edge 15 forms a groove 14 (FIG. 7) on the inner surface of the housing 10 for receiving the O-ring 20. The front face of the housing 10 also comprises an opening 13. The opening 13 acts as the viewing area of the nautical instrument 100 so that the dials 22 can be read.

[0062] The housing 10 can be made of any material, however, it is preferred that the housing 10 be constructed of brass. It has been discovered that coating the brass housing 10 with zirconium is effective to prevent tarnishing, discoloration and/or any type of corrosion. The brass can be plated with zirconium via an electro-plating procedure. Zirconium plating has been discovered to be extremely resistant to wear and does not require the application of lacquer. Restorative polishing of the zirconium plating restores the entire surface of the housing as opposed to the patchwork of lacquering the surface.

[0063] The O-ring 20 is designed to fit in the housing 10 and is sized to fit in the groove 14 formed by the curved edge 15 (this will be discussed in greater detail below with respect to the assembly of the nautical instrument 100 in FIG. 7). Proper compression of the O-ring 20 within the groove results in the front face of the nautical instrument 100 being watertight and weatherproof. While an O-ring 20 is illustrated, other types of seals may be used. The O-ring 20 may be made of a silicone rubber material.

[0064] Referring now to FIGS. 2, 9A and 9B concurrently, the lens 21 is constructed of a transparent material such as glass, crystal, plastic, etc. Preferably, a mineral glass is used. The lens 21 comprises a beveled perimeter region 25 and a center hole 26. The lens 21 is sized to fit within the wall portion 11 of the housing 10 so that the beveled perimeter

region 25 contacts and compresses the O-ring 21 within the groove 14 formed by the curved edge 15 of the housing 10. The center hole 26 acts as a passageway for the knob 23 which is to be connected to one of the dials 22. Proper rubber rings/seals can be used to make the center hole 26 watertight. In some embodiments of the inventive nautical instrument 100, it is not necessary to include the center hole 26. Whether or not to include the center hole 26 is dictated by the type of nautical instrument being created. For example, the center hole is not necessary for a clock.

[0065] The indicia plate 30 comprises the markings necessary to read the standard being measured by the nautical instrument 100. As mentioned above, the indicia plate 30 can take on a wide variety of embodiments. For example, in FIGS. 3A-3C, the indicia plates 30A-30C are illustrated for combined temperature and humidity, barometric pressure and time measurements respectively. The exact location and indicia added to the front surface 31 of the indicia plate 30 will be dictated by the desired functionality of the nautical instrument 100 into which it is to be incorporated.

[0066] Referring again to FIG. 2, the front surface 31 of the indicia plate 30 (which includes the indicia) faces the lens 21 so that it is visible through the opening 13 of the housing 10 when the nautical instrument 100 is assembled. The indicia plate 30 comprises the necessary holes 32 (one illustrated) for connection of the dials 22 to the gauge mechanism 24. The number and positioning of the holes 32 is dictated by the type of nautical instrument 100 designed. The indicia plate 30 is sized so that it fits within the cavity 41 of the dial plate 40. The indicia plate 30 can be adhered or otherwise connected to the floor 42 of the cavity 41 of the dial plate 40 if desired. In another embodiment, the indicia plate can be pressed into position within the cavity 41.

[0067] The indicia plate 30 is preferably formed of an opaque material, such as rigid PVC or polystyrene. The indicia plate can be die cut or pierced from a blank. The indicia plate 30, however, can be made from a wide variety of materials.

[0068] Referring still to FIG. 2, the dial plate 40 will now be described. The dial plate 40 comprises a wall portion 43 that terminates in a ring-like edge 44. The ring-like edge 44 forms the perimeter of the cavity 41. The cavity 41 comprises a floor 42 upon which the indicia plate 30 can rest. The wall portion 43 of the dial plate 40 is sized and shaped to fit within the housing 10. It is accurately matched to the taper of the brass housing 10 with the proper clearance for thermal cycling.

[0069] The dial plate 40 is also sized and shaped so that the lens 21 will rest atop the ring-like edge 44 when assembled, thereby substantially enclosing the cavity 41. In order to facilitate proper placement of the lens 21 on the dial plate 40, the ring-like edge 44 comprise a raised edge 46 about its perimeter thereby forming an internal ledge 47 upon which the lens 21 can rest (illustrated in FIG. 7). The raised edge 46 acts as a self-guiding wall during assembly of the lens 21 to the dial plate 40 and restricts the lens 21 from sliding off the edge 44. If desired, the lens 21 can be sealed to the dial plate 40 by applying a wet adhesive on the ledge 47 and positioning the lens 21 thereon. Using an adhesive also provides additional moisture sealing for the internal components of the nautical instrument 100.

[0070] The dial plate 40 is designed so that it is a multi-purpose and universal component that can be used in any

nautical instrument **100** of the present invention, irrespective of the instrument's ultimate end functioning as a barometer, temperature gauge, comfort meter, tide clock, etc. To this extent, the dial plate comprises a plurality of holes **45** that extend through the floor **42** of the cavity **41**. The holes **45** provide passageways from the rear of the dial plate **40** to the cavity **41** so that the appropriate dials **22** can be operably coupled to the appropriate gauge mechanism **24** (or mechanisms) which are nested in the rear of the dial plate **40** behind the floor **42**. Depending on the desired end functioning of the nautical instrument **100**, one or more of the holes **45** may not be used. Unused holes **45** may simply be covered up by the indicia plate **30**.

[0071] Referring now to FIGS. 6A-6C, the rear of the dial plate **40** is illustrated having three different gauge mechanism arrangements. In FIG. 6A, the dial plate **40** is fitted with a temperature gauge mechanism **32** and humidity gauge mechanism **33**. In FIG. 6B, the dial plate **40** is fitted with a barometric pressure gauge mechanism **24**. In FIG. 6C, the dial plate **40** is outfitted with a clock gauge mechanism **34**. Thus, as can be seen, the dial plate **40** enables visual presentation of a multitude of accurately pre-printed indicia plates **30** in a wide range of suitable materials.

[0072] The universal nature of the dial plate **40** is facilitated by the specially designed internal walls **46** that extend from the rear surface of the floor **42** of the dial plate **40**. The internal walls **46** are sized and shaped to: (1) accommodate the various gauge mechanisms **24** and **32-34**; (2) hold the various gauge mechanisms **24** and **32-34** in place and maintain their proper orientation; and (3) properly align the various gauge mechanisms **24** and **32-34** with the desired holes **45** so that the dials **22** can be operably connected thereto.

[0073] As illustrated, the internal walls **46** of the dial plate **40** form three nesting areas **47-49**. The nesting area **47** is a central nesting area designed to accommodate centrally located gauge mechanisms, such as a clock or barometer. The central nesting area **47** can accommodate larger gauge mechanisms. The lower nesting areas **48, 49** are formed by two semi-spherical portions of the internal wall **46** and are located so that two gauge mechanisms can be accommodated by the dial plate **40** simultaneously. The internal walls **46** provide quick and accurate fixation of the gauge mechanisms to the dial plate **40**.

[0074] Therefore, the dial plate **40** is a universal component that facilitates the mounting of a multiplicity of different gauge mechanisms for measuring various standards. The dial plate **40** allows different nautical instruments to be constructed from a common case system, thereby economically extending the application of the invention.

[0075] The dial plate **40** further comprises threaded bores **35** for receiving and engaging screws that penetrate the back plate **50**, the compression plates **60** and the locking plates **70**. The threaded bores **35** are formed into the internal walls **46** of the dial plate **40** near the wall portion **43** at about 180 degrees apart. As such, the dial plate **40** locates and centers the back plate **50** to ensure correct alignment with the internal mechanisms and dial legend on the indicia plate **30**.

[0076] The dial plate **40** is preferably a single-piece structure constructed of ABS plastic. The dial plate **40** can be formed by injection molding or other techniques. The inven-

tion, however, is not limited to any specific material and/or technique of construction. All of the holes in the dial plate **40** can be formed by lathing, boring, trepanning, or press piercing after molding. Rubber washers can be used to seal any of the holes in the dial plate **40** if desired.

[0077] Referring back to FIG. 2, the nautical instrument also comprises a gauge mechanism **24** for measuring a desired standard, such as time, humidity, temperature, etc. The gauge mechanism **24** comprises a needle **36** (or other extension) that protrudes through the dial plate **40** so that one or more of the dials **22** can be connected thereto. The mounting of the gauge mechanism **24** in the dial plate **40** is discussed above and, thus, will not be further described in order to avoid redundancy. It should be noted that the invention is not limited by the structure and/or functioning of the gauge mechanism **24**. The inventive nautical instrument **100** can incorporate any and all types of gauge mechanisms.

[0078] Referring now to FIGS. 2 and 12A-12B concurrently, the nautical instrument **100** further comprises two D-shaped locking plates **70**. Each of the locking plates **70** comprises a hole **71** extending therethrough and two protrusions **72** protruding from the rear surface **73** of the locking plates **70**. The holes **71** provide a means by which the locking plates **70** can be secured the back surface of the back plate **50** by a screw or other fastener. The protrusions **72** are similar to those discussed below with respect to the back plate **50**.

[0079] The locking plates **70** are preferably made of stainless steel or another suitably hard material. The protrusions **72** on the locking plates **70** can be formed by performing a punching-to-dimple technique to the front surface **74** of the locking plates **70** while the holes **71** are formed by a punching-to-pierce technique.

[0080] Referring now to FIGS. 2 and 11A-11B concurrently, the nautical instrument **100** further comprises two D-shaped compression plates **60**. Each of the compression plates **60** comprises a hole **61** extending therethrough. The holes **61** provide a means by which the compression plates **60** can be secured the rear surface **52** of the back plate **50** by a screw or other fastener.

[0081] The compression plates **60** are preferably formed of a material having a thickness and shore hardness that ensures appropriate rear assembly compression and security of the internal parts of the nautical instrument **100**. Most preferably, the compression plates **60** are formed of a material that has the same or higher hardness rating than the material of the O-Ring **20**. As will be discussed below, this achieves maximum compression of the O-Ring **20** between the lens **21** and the housing **10** during mounting.

[0082] In one embodiment, the compression plates **60** are formed from a rubber, a plastic or a synthetic flexible polymer. The compression plates **60** can be die cut with a knife tool, molded or pierced from a blank of material.

[0083] Referring still to FIG. 2, the nautical instrument **100** further comprises a back plate **50**. While the back plate **50** is illustrated as being a separate structure than that of the housing **10**, in some embodiments of the invention, the back plate **50** will be integrally formed as part of the housing **10**. The back plate **50** connects to the rear of the housing **10** so as to substantially enclose the back side of the housing **10**.

The back plate **50** is preferably constructed of galvanized steel and powder coated and formed by a die cutting or piercing technique.

[0084] As will be discussed in greater detail below, the back plate **50** (in combination with the bulkhead plate **80**) is specially designed to facilitate a novel mounting technique for the nautical instrument **100**.

[0085] Referring now to FIGS. **10A-10D**, the back plate **50** comprises a front surface **51**, a rear surface **52**, a top **53** and a bottom **54**. The top **53** and bottom **54** of the back plate **50** correspond to the top **1** and bottom **b** of the nautical instrument **100**. The back plate **50** comprises a rectangular cutout **57** near the center of the back plate **50**. The cutout **57** provides a passageway through the back plate **50** so that the internal components of the nautical instrument **100** are accessible to a user.

[0086] The back plate further comprises a plurality of holes **58** extending through the back plate **50**. The holes **58** provide a means by which the back plate **50** can be secured to the dial plate **40** via screws **95**, etc. Two of the holes **58** are positioned so as to be aligned with the bores **35** of the dial plate **40**. During assembly, screws **95** pass through these two holes **58** and into the bores **35** of the dial plate **40**, thereby securing/connecting the back plate **50** to the dial plate **40** (and the housing **10**).

[0087] The back plate **50** further comprises three generally conical-shaped protrusions **59** extending from the rear surface **52** of the back plate **50**. The protrusions **59**, however, are not limited to any specific shape. The protrusions **59** are formed by punching the front surface **51** of the back plate **50** so as to form dimples therein. The dimples of the front surface **51** of the back plate **50** appear as protrusions on the rear surface **52** of the back plate **50**.

[0088] The protrusions **59** are located in a generally triangular pattern. One protrusion **59** is located near the top **53** of the back plate **50** along the vertical centerline of the back plate **50** while the other two protrusions **59** are located below the cutout **57** in a horizontally aligned and spaced relation. All of the protrusions **59** are located closer to the vertical centerline of the back plate **50** than are the first and second brackets **55**, **56**. Most preferably, the protrusion **59** near the top **53** of the back plate **50** is slightly larger than the two lower protrusions **59**. As a result, the protrusion **59** near the top **53** protrudes further from the rear surface **52** of the back plate than do the two lower protrusion **59** (i.e., it has a greater height).

[0089] The back plate **50** further comprises a bracket assembly which comprises a first bracket **55** and a second bracket **56**. It should be noted that while the bracket assembly is illustrated as a two-piece structure, in some embodiments of the invention the bracket assembly will be a single structure. The brackets **55**, **56** can be formed by punching the blank material of the back plate **30** on three sides, bending the material outward and then angling the material to form the overhang portions **165**, **166**. Each of the first and second brackets **55**, **56** have a substantially L-shaped cross-sectional configuration. The invention, however, is not so limited and the brackets **55**, **56** can take on an almost endless variety of shapes and configurations.

[0090] The first and second brackets **55**, **56** extend from the rear surface of the back plate **50**. The first bracket **55** is

located on one side of the vertical centerline of the back plate **50** while the second bracket **56** is located on the opposite side of the vertical centerline. The first and second brackets **55**, **56** are oriented in an angled fashion so as to diverge from one another going from the top **53** to the bottom of the **54** of the base plate **50**. In one embodiment, the first and second brackets **55**, **56** are at a 10 degree offset angle from the vertical centerline of the back plate **50**. In this manner, the first and second brackets **55**, **56** form an upside-down truncated V-shaped assembly.

[0091] The first bracket **55** forms a first channel **155**. Similarly, the second bracket **56** forms a second channel **156**. The first channel **155** is formed between the overhang portion **165** of the first bracket **55** and the rear surface **52** of the base plate **50**. The second channel **156** is formed between the overhang portion **166** of the second bracket **56** and the rear surface **52** of the base plate **50**. As a result, the first channel **155** and the second channel **156** oppose one another in a spaced and angled relation (identical to that of the brackets **55**, **56** themselves).

[0092] The channels **155**, **156** are accessible from the bottom **54** of the back plate **50** (i.e., from below the bracket assembly). Each of the channels **155**, **156** comprises a roof **175**, **176**. In the aggregate, the first and second channels brackets **55**, **56** form an upside-down truncated V-shaped channel. In alternate embodiments, the bracket assembly can form a single or segmented channel that has an upside-down substantially U-shaped or semi-elliptical configuration.

[0093] Referring solely to FIG. **2**, the nautical instrument **100** further comprises a bulkhead plate **80**. The bulkhead plate **80** cooperates with the back plate **50** to effectuate the novel mounting and locking of the nautical instrument **100** to a wall or other surface of a ship. Generally, the bulkhead plate **80** is secured to the desired surface of the ship and the remaining components of the nautical instrument **100** are slidably mounted to the bulkhead plate **80**.

[0094] Referring now to FIGS. **13A-13E**, the bulkhead plate **80** comprises a front surface **81**, a rear surface **82**, a top **83** and a bottom **84**. The top **83** and bottom **84** of the bulkhead plate **80** corresponds to the top **1** and bottom **2** of the nautical instrument **100** (FIG. **1**).

[0095] The bulkhead plate **80** comprises a plurality of mounting holes **85** extending through the back plate **50**. The mounting holes **85** provide a means by which the bulkhead plate **80** can be secured to a wall or other surface of a ship via screws, bolts, etc. The mounting holes **85** are of a counter bored shape (i.e., stepped). By making the mounting holes **85** a counter bored shape, the mounting holes **85** facilitate accurate marking and drilling for mounting the bulkhead plate **80**. As a result, the mounting plate **80** itself acts as its own drill jig/template. The mounting holes **85** enlarge as the mounting screws are inserted. The bulkhead plate **80** also comprises location markers (not illustrated) to enable the bulkhead plate **80** to act as an installation marker.

[0096] A horizontal ridge **86** is provided on the front surface **81** of the bulkhead plate **80**. The horizontal ridge **86** is a raised elongated feature that has a semi-circular cross-sectional profile. The horizontal ridge **86** is located near the bottom **84** of the bulkhead plate **80**. The horizontal ridge **86** acts as a retaining element for the two lower protrusions **59** of the back plate **50** during the novel mounting procedure.

The height and cross-sectional profile of the horizontal ridge **86** is chosen so that the two lower protrusions **59** of the back plate **50** slide over and snap lock against the underside of the horizontal ridge **86** during the sliding mounting procedure (as illustrated in FIG. 7).

[0097] The bulkhead plate **80** further comprises a guide channel **87** in its front surface **81**. The guide channel **86** is a vertically oriented depression that extends downwardly from the top edge of the bulkhead plate **80**. The guide channel **87** does not extend through the entire thickness of the bulkhead plate **80** (i.e., from the front surface **81** to the rear surface **82**). The depth of the guide channel **87** is determined on a design basis. As will be discussed below, the guide channel **87** is provided to receive, guide and laterally restrain the top protrusion **59** of the back plate **50** during mounting.

[0098] The bulkhead plate **80** further comprises a mounting plate assembly which comprises a first mounting plate **88** and a second mounting plate **89**. The mounting plates **88**, **89** utilize a dovetail design. It should be noted that while the mounting plate assembly is illustrated as a two-piece structure, in some embodiments of the invention, the mounting plate assembly will be a single structure. Each of the first and second mounting plates **88**, **89** are connected to the front surface **81** of the bulkhead plate **80** in a spaced relation from each other and the front surface **81**. As a result, spaces **188**, **189** are formed between the mounting plates **88**, **89** and the front surface **81** of the bulkhead plate **80**.

[0099] Each of the first and second mounting plates **88**, **89** are connected to the bulkhead plate **80** along three sides. The first mounting plate **88** comprises a first angled edge **90** and the second mounting plate **89** comprises a second angled edge **91**. The first and second angled edges **90**, **91** are not connected to the bulkhead plate **80**, thereby allowing a passageway into the spaces **188**, **189** that exist between the mounting plates **88**, **89** and the front surface **81** of the bulkhead plate **80**.

[0100] The first and second angled edges **90**, **91** diverge from one another from the top **83** to the bottom **84** of the bulkhead plate **80**. The angled orientation of the first and second angled edges **90**, **91** is designed to correspond to the angled orientation of the first and second channels **155**, **156** of the bracket assembly of the back plate **50**. This facilitates the mating engagement of the mounting plate assembly and the bracket assembly. By angling the edges **90**, **91** of the mounting plates **88**, **89** in a manner that corresponds to the angled orientation of the channels **155**, **156** of the brackets **55**, **56**, the edges **90**, **91** of the mounting plates **88**, **89** can slidably insert into the channels **55**, **56**. Thought of another way, the overhang portions **165**, **166** of the brackets **55**, **56** slide into the spaces **188**, **189** that exist between the mounting plates **88**, **89** and the front surface **81** of the mounting plate **80**. Either way, a mating engagement occurs.

[0101] A floor **92**, **93** exists at the bottom of each angled edge **90**, **91** and prohibits excessive downward movement of the brackets **55**, **56** during the mating engagement. The angled edges **88**, **89** are unobstructed at their tops to allow entry into the channels **155**, **156**. The first and second mounting plates **88**, **89** are spaced from one another so that they fit between the brackets **55**, **56**. The first mounting plate **88** is located on one side of the vertical centerline of the bulkhead plate **80** while the second mounting plate **89** is located on the opposite side of the vertical centerline.

[0102] The bulkhead plate **80** can be formed of a wide variety of materials, including plastic, nylon, metals, or other materials. In one embodiment, the bulkhead is formed by injection molded nylon.

[0103] Referring now to FIGS. **2** and **7** concurrently, the assembly of the nautical instrument **100** and the interaction of its components will be discussed. When the nautical instrument **100** is assembled, the O-ring **20** is first placed in the groove **14** formed by the curved edge **15** of the housing **10**.

[0104] The appropriate indicia plate **30** and dial(s) **22** are positioned within the cavity **41** of the dial plate **40**. The appropriate gauge mechanism(s) **24** are also inserted into the proper nesting area in the rear of the dial plate **40** and operably coupled to the dial(s) **22**.

[0105] The lens **21** is then placed atop the ring-like edge **44** of the dial plate **40**. The lens **21** rests atop the ledge **47** formed by the raised edge **46**. If desired, the lens **21** can be sealed to the dial plate **40** by applying a wet adhesive between the ledge **47** and the lens **21**. This "dial plate and lens assembly" is then inserted into the housing **10** so that the beveled portion **25** of the lens **21** is pressed against the O-ring **20**, thereby creating a hermetic seal. As will be discussed in greater detail below, the bulkhead plate **80**, the back plate **50** and locking plates **70** are designed to apply an additional compression force to the silicon rubber O-ring **20** when the nautical instrument **100** is mounted to the surface of a ship, thereby increasing the watertight characteristics of the front face of the instrument.

[0106] The knob **23** is then inserted into the hole **26** of the lens **21** and coupled to a dial **22** if needed. A rubber seal can be provided between the knob **23** and the lens **21** to maintain the weatherproof integrity of the front face of the nautical instrument **100**.

[0107] The back plate **50** is connected to the dial plate **40** via two screws **95** (FIG. **5**) that penetrate into the threaded bores **35** (FIG. **6A**) of the dial plate **40**. The back plate **50** is connected to the housing **10** by a sized fit into a groove **16** formed by the curved rear edge **17** of the flange **12** of the housing **10**.

[0108] Referring now to FIG. **5**, the locking plates **70** and the compression plates **60** are also connected to the back plate **50** via the screws **95**. The compression plates **60** are located between the locking plates **70** and the back plate **50**. Each screw **95** penetrates the locking plate **70**, the compression plate **60**, the back plate **50** and the bores **35** of the dial plate **40**. The locking plates **70** are connected to the back plate **50** in a spaced relation so that the bracket assembly (which comprises the first and second brackets **55**, **56**) is located therebetween.

[0109] Referring to FIG. **4**, it can be seen that the protrusions **72** of the locking plates **70** extend furthest from the rear of the nautical instrument **100**. As a result, when the bulkhead plate **80** is secured to the surface of a ship and the remaining assembly of the nautical instrument **100** is mounted to bulkhead plate **80** as described below, the protrusions **72** of the locking plates **70** press against the ship's surface. Because the back plate **50** is locked to the bulkhead plate **80** during this mounting, the force exerted on the protrusions **72** is transferred to the locking plates **70** and in turn to the O-ring **20** (via the dial plate **40**). It is in this

way that the dual locking plate system holds the nautical instrument **100** together while simultaneously exerting an additional compression force on the O-ring **20** to effectively seal the front face of the instrument **100**.

[0110] The novel mounting of the nautical instrument **100** to a wall or other surface (i.e., a mounting surface) of a ship will now be described. Reference will be made to the structure identified in FIGS. 1-13E as necessary. First, the bulkhead plate **80** is used as its own drill jig/template. Once properly marked, the bulkhead plate **80** is secured to the mounting surface of the ship via a plurality of screws that pass through the mounting holes **85**. The bulkhead plate **80** is mounted so that its front surface **81** faces away from the mounting surface.

[0111] Once the bulkhead plate **80** is mounted securely in place, the remaining nautical instrument assembly **100** (as shown in FIGS. 4 and 5) is oriented so that the rear surface **51** of the back plate **50** faces the front face **81** of the bulkhead plate **80**. The nautical instrument assembly **100** is positioned adjacent to and above the bulkhead plate **80** so that the first and second brackets **55, 56** of the back plate **50** are vertically aligned with the first and second mounting plates **88, 89** of the bulkhead plate **80** respectively.

[0112] The nautical instrument assembly **100** (as used hereafter the term "nautical instrument assembly" refers to the nautical instrument of FIG. 2 less the bulkhead plate) is then lowered until the angled edges **90, 91** of the mounting plates **88, 89** slidably insert into the first and second channels **155, 156** of the brackets **55, 56**, thereby resulting in a mating engagement of the back plate **50** to the bulkhead plate **80**. During the lowering and slidable insertion, the centered protrusion **59** near the top **53** of the back plate extends into and is guided by the guide channel **83** of the bulkhead plate **80**. Concurrently, the two lower protrusions **59** that are aligned near the bottom **54** of the back plate **50** contact and slide down the front surface **81** of the back plate **80**. As the lowering of the nautical instrument assembly **100** continues, the two lower protrusions **59** of the back plate **50** slide over the horizontal ridge **86** of the bulkhead plate and snap lock into position below and against the underside of the horizontal edge **86**.

[0113] The protrusions **59** of the back plate **50** perform four primary functions in the mounted state. First, the interaction of the protrusions **59** with the guide channel **87** and the horizontal ridge **86** of the bulkhead plate **80** prevents relative rotational movement between the back plate **50** and the bulkhead plate **80**. Second, the interaction of the protrusions **59** with the horizontal ridge **86** snap lock the back plate **50** (and thus the nautical instrument assembly **100**) to the bulkhead plate **80** in a manner that prevents accidental upward dislodgement and vibration. Third, the protrusion **59** are of a sufficient height that maintains the angled edges **90, 91** of the mounting plates **88, 89** (which are located in the channels **155, 156** of the brackets **55, 56** at this time) under pressing force against the overhang portions **165, 166** of the brackets **55, 56**. This pressing force helps increase the integrity of the mounting of the nautical instrument assembly **100** to the bulkhead plate **80**. Fourth, the protrusions **59** maintain a ventilation space between the back plate **50** and the bulkhead plate **80** to prevent moisture and heat build-up.

[0114] During the lowering of the nautical instrument assembly **100** onto the bulkhead plate **80** as described above,

it is important to note that the bulkhead plate **80** fits between the locking plates **70**. This allows the protrusions **72** on the locking plates **70** to come into contact with the mounting surface of the ship during the mounting procedure. The protrusions **72** are designed to have a height that results in the protrusions **72** being under pressure from the ship's mounting surface during the mating engagement of the bracket assembly and the mounting plate assembly. The protrusions **72** transfer this pressure force to the locking plates **70**, which in turn transfer the pressure force to the compression plates **60** and eventually the O-ring **20** (via the dial plate **40**) as a compression force. Both the O-ring **20** and the compression plates **60** compress so as to afford the necessary tolerance for mounting. However, because the compression plates **60** are constructed of a material that is harder than the O-ring **20**, the O-ring **20** is compressed sufficiently to hermetically seal the perimeter of the lens **21** to the housing **10**, thereby making the front face of the nautical instrument **100** watertight. The protrusions **72** also apply additional pressure to the back plate **50** so as to help maintain the angled edges **90, 91** of the mounting plates **88, 89** under pressing force against the overhang portions **165, 166** of the brackets **55, 56**.

[0115] The existence of the protrusions **72** on the locking plates **70** and/or the existence of the protrusions **59** on the back plate **50** also serve the function of maintaining a space between the back plate **50** and the bulkhead plate **80** during the mating engagement. This space allows the back of the nautical instrument assembly **100** with proper ventilation and prevents the undesired build-up of moisture which can affect the functioning of the internal gauge mechanism(s). This space also serves to prevent internal heat build-up within the instrument itself when in prolonged direct sunlight.

[0116] The unique sliding and snap fit mounting system allows the nautical instrument assembly **100** to be lifted off its mounted location without having to remove screws. This allows the nautical instrument **100** to be easily removed for battery replacement, storage and/or instrument calibration. This mounting technique conceals all of the mounting screws used on the bulkhead plate **80** behind the housing **10** of the nautical instrument **100**.

[0117] While the invention has been described and illustrated in sufficient detail that those skilled in this art can readily make and use it, various alternatives, modifications, and improvements should become readily apparent without departing from the spirit and scope of the invention.

What is claimed is:

1. A nautical instrument having a top and a bottom comprising:

- a housing containing a gauge mechanism;
- a back plate connected to the housing and having a rear surface;
- a bracket assembly protruding from the rear surface of the back plate, the bracket assembly comprising a downwardly extending overhang section that forms first and second channels between the overhang section and the rear surface of the back plate, the channels opposing one another in an angled orientation that diverges from the top to the bottom of the nautical instrument;

a bulkhead plate comprising means for securing the bulkhead plate to a surface of a ship;

a mounting plate assembly connected to a front surface of the bulkhead plate in spaced relation, the mounting plate assembly having first and second angled edges that substantially corresponds to the angled orientation of the channels; and

wherein the mounting plate assembly is adapted so that the first and second angled edges slidably insert into the first and second channels of the bracket assembly respectively when the rear surface of the back plate is positioned adjacent to and above the front surface of the bulkhead plate and the back plate is lowered, thereby effectuating mating engagement of the mounting plate assembly and the bracket assembly.

2. The nautical instrument of claim 1 wherein the bracket assembly comprises a first bracket comprising the first channel and a second bracket comprising the second channel.

3. The nautical instrument of claim 2 wherein the first and second channels form an upside-down truncated V-shaped configuration.

4. The nautical instrument of claim 2 wherein the mounting plate assembly comprises a first mounting plate comprising the first angled edge and a second mounting plate comprising the second angled edge.

5. The nautical instrument of claim 1 further comprising:

a substantially transparent lens located within the housing and covering an opening in a front face of the housing;

a gasket seal positioned between the lens and the housing.

a dial plate positioned in the housing and in contact with a rear surface of the lens and a front surface of the back plate;

first and second locking plates connected to the rear surface of the back plate and spaced from one another, the bracket assembly located between the first and second locking plates;

one or more protrusions extending from a rear surface of each locking plate; and

wherein when the bulkhead plate is secured to a surface of a ship and the mounting plate assembly and the bracket assembly are matingly engaged, the protrusions on the locking plates contact and press against the surface of the ship thereby providing a compression force to the gasket seal.

6. The nautical instrument of claim 1 further comprising a dial plate comprising a plurality of nesting areas for slidably receiving one or more gauge mechanisms.

7. The nautical instrument of claim 1 further comprising means for maintaining the overhang section of the bracket assembly under force against the mounting plate assembly when the mounting plate assembly and the bracket assembly are matingly engaged.

8. The nautical instrument of claim 7 wherein the means for maintaining the force comprises one or more protrusions that extend from the rear surface of the back plate and press against the front surface of the bulkhead plate when the mounting plate assembly and the bracket assembly are matingly engaged.

9. The nautical instrument of claim 1 further comprising:

a horizontal ridge protruding from the front surface of the bulkhead plate;

a guide channel in the front surface of the bulkhead plate, the guide channel extending downward from a top edge of the bulkhead plate;

three protrusions extending from the rear surface of the back plate that press against the bulkhead plate when the mounting plate assembly and the bracket assembly are matingly engaged; and

wherein the three protrusion are arranged on the back plate so that when the mounting plate assembly and the bracket assembly are matingly engaged, one of the protrusions extends into the guide channel and the other two protrusions slide over the horizontal ridge and to snap-lock to an underside of the horizontal ridge.

10. The nautical instrument of claim 1 further comprising:

first and second locking plates connected to the rear surface of the back plate and spaced from one another, the bracket assembly located between the first and second locking plates;

one or more protrusions extending from a rear surface of each locking plate;

first and second compression plates positioned between the first and second locking plates, the compression plates made of a rubber or plastic material;

wherein when the bulkhead plate is secured to a surface of a ship and the mounting plate assembly and the bracket assembly are matingly engaged, the protrusions on the locking plates contact the planar surface.

11. The nautical instrument of claim 10 wherein the protrusions on the locking plate have a height that maintains the overhang section of the bracket assembly under force against the mounting plate assembly.

12. The nautical instrument of claim 11 wherein the protrusions are generally conical in shape.

13. The nautical instrument of claim 1 wherein the housing is constructed of brass and plated with zirconium.

14. The nautical instrument of claim 1 further comprising:

a substantially transparent lens located within the housing and covering an opening in a front face of the housing; and

a gasket seal positioned and compressed between the lens and the housing.

15. The nautical instrument of claim 14 further comprising a groove located on an inside surface of the front face of the housing, the gasket seal positioned in the groove.

16. The nautical instrument of claim 14 wherein a front surface of the lens has a beveled perimeter region, the gasket seal being compressed between the beveled perimeter region and the housing.

17. The nautical instrument of claim 14 further comprising:

a dial plate positioned in the housing and in contact with a rear surface of the lens and a front surface of the back plate;

first and second locking plates connected to the rear surface of the back plate and spaced from one another, the bracket assembly located between the first and second locking plates;

one or more protrusions extending from a rear surface of each locking plate;

first and second compression plates positioned between the first and second locking plates, the compression plates made of a material which is harder than the gasket seal;

wherein when the bulkhead plate is secured to a surface of a ship and the mounting plate assembly and the bracket assembly are matingly engaged, the protrusions on the locking plates contact the planar surface and provides a compression force to the gasket seal.

18. The nautical instrument of claim 17 wherein the locking plates are substantially D-shaped.

19. The nautical instrument of claim 17 further comprising:

a horizontal ridge protruding from the front surface of the bulkhead plate;

a guide channel in the front surface of the bulkhead plate, the guide channel extending downward from a top edge of the bulkhead plate; and

three protrusions extending from the rear surface of the back plate, the protrusions on the back plate arranged so that when the mounting plate assembly and the bracket assembly are matingly engaged, one of the protrusions on the back plate extends into the guide channel of bulkhead plate and the other two protrusions on the back plate slide over the horizontal ridge and snap-lock against an underside of the horizontal ridge.

20. The nautical instrument of claim 1 further comprising means for maintaining a ventilation space between the rear surface of the back plate and the front surface of the bulkhead plate when the mounting plate assembly and the bracket assembly are matingly engaged.

21. A nautical instrument comprising:

a housing containing a gauge;

a back plate connected to the housing and having a top, a bottom and rear surface;

a bracket assembly protruding from the rear surface of the back plate, the bracket assembly comprising a channel that is accessible from below the bracket assembly;

a bulkhead plate comprising means for securing the bulkhead plate to a surface of a boat;

a mounting plate assembly connected to a front surface of the bulkhead plate in a spaced relation, the mounting plate assembly having an edge that corresponds to the roof of the channel of the bracket assembly; and

wherein when the rear surface of the back plate is positioned adjacent to and above the front surface of the bulk head plate and the back plate is lowered, the edge of the mounting plate assembly slidably inserts into the channel of the bracket assembly until the edge of the mounting plate assembly contacts the roof of the bracket assembly.

22. A nautical instrument comprising:

a housing containing a gauge;

a back plate connected to the housing and having a rear surface, a bottom, a top and vertical centerline;

a first bracket protruding from the rear surface of the back plate on one side of the centerline and a second bracket protruding from the rear surface of the back plate on the opposite side of the centerline;

each of the brackets forming an elongated channel that angles inwardly toward the centerline from the bottom toward the top of the back plate, the channels being accessible from below the brackets and have a roof;

a bulkhead plate having a top, a bottom and a front surface and comprising means for securing the bulkhead plate to a surface;

first and second mounting plates connected to a front surface of the bulkhead plate in a spaced relation, the first mounting plate having a lateral edge that angularly corresponds to the channel of the first bracket and the second mounting plate having a lateral edge that angularly corresponds to the channel of the second bracket; and

the lateral edges being spaced from one another so that when the rear surface of the back plate is positioned adjacent to and above the front surface of the bulk head plate and lowered, the lateral edges of the first and second plates slidably insert into the channels of the first and second brackets respectively until the lateral edges of the first and second plates come into contact with the roofs of the channels of the first and second brackets.

* * * * *