

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2002302597 B2**

- (54) Title
Process for preparing alkylene oxide (epoxid, oxirane)
- (51) International Patent Classification(s)
C07D 301/19 (2006.01) **C07D 303/04** (2006.01)
- (21) Application No: **2002302597** (22) Date of Filing: **2002.05.03**
- (87) WIPO No: **WO02/090340**
- (30) Priority Data
- (31) Number **01304132.2** (32) Date **2001.05.08** (33) Country **EP**
- (43) Publication Date: **2002.11.18**
(43) Publication Journal Date: **2003.05.01**
(44) Accepted Journal Date: **2007.12.20**
- (71) Applicant(s)
Shell Internationale Research Maatschappij B.V.
- (72) Inventor(s)
Santen, Augustinus;Van Der Linden, Johannes Petrus;Ploemen, Ingmar Hubertus Josephina;Van Der Veen, Alexander Jan
- (74) Agent / Attorney
Davies Collison Cave, 1 Nicholson Street, Melbourne, VIC, 3000

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
14 November 2002 (14.11.2002)

PCT

(10) International Publication Number
WO 02/090340 A1

(51) International Patent Classification⁷: C07D 301/12

VEEN, Alexander, Jan [NL/NL]; Badhuisweg 3,,
NL-1031 CM Amsterdam (NL).

(21) International Application Number: PCT/EP02/04970

(22) International Filing Date: 3 May 2002 (03.05.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
01304132.2 8 May 2001 (08.05.2001) EP

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): SHELL
INTERNATIONALE RESEARCH MAATSCHAPPIJ
B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR
The Hague (NL).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): VAN DER LIN-
DEN, Johannes, Petrus [NL/NL]; Badhuisweg 3,
NL-1031 CM Amsterdam (NL). PLOEMEN, Ingmar,
Hubertus, Josephina [NL/NL]; Bahuisweg 3, NL-1031
CM Amsterdam (NL). SANTEN, Augustinus [NL/NL];
Volmerlaan 8, NL-2288 GD Rijswijk (NL). VAN DER

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 02/090340 A1

(54) Title: PROCESS FOR PREPARING ALKYLENE OXIDE (EPOXID, OXIRANE)

(57) Abstract: Process for the preparation of alkylene oxide, which process comprises passing a feed containing an organic hydroperoxide and alkene through a bank of at least two serially connected reactors containing epoxidation catalyst and withdrawing a product stream comprising alkylene oxide and an alcohol as reaction products, in which bank of reactors the temperature of the feed is controlled such that during operation the outlet temperature of the final reactor is at least 4°C higher than the outlet temperature of the first reactor.

2002302597 07 Dec 2007

- 1 -

PROCESS FOR PREPARING ALKYLENE OXIDE (EPOXID, OXIRANE)

Background of the invention

5 The present invention relates to a process for the preparation of an alkylene oxide.

The epoxidation of an alkene into an alkylene oxide by reacting the alkene with an organic hydroperoxide is known in the art.

10 For instance, in the commonly known method for co-producing propylene oxide and styrene starting from ethylbenzene, the aforementioned epoxidation reaction is applied. In general this co-production process involves the steps of (i) reacting ethylbenzene with oxygen or air to form ethylbenzene hydroperoxide, (ii) reacting the
15 ethylbenzene hydroperoxide thus obtained with propene in the presence of an epoxidation catalyst to yield propylene oxide and 1-phenyl-ethanol and (iii) converting the 1-phenyl-ethanol into styrene by dehydration using a suitable dehydration catalyst.

20 Another method for producing an alkylene oxide is the coproduction of propylene oxide and methyl tert-butyl ether (MTBE) starting from isobutane and propene. This process is well known in the art and involves similar reaction steps as the styrene/propylene oxide production process described in
25 the previous paragraph. In the epoxidation step tert-butyl hydroperoxide is reacted with propene forming propylene oxide and tert-butanol in the presence of a heterogeneous epoxidation catalyst. Tert-butanol is subsequently etherified with methanol into MTBE, which is used as an
30 additive in motor fuels.

US-A-5,849,937 relates to an olefin epoxidation process using a plurality of reactor vessels each containing a fixed

2002302597 07 Dec 2007

- 2 -

bed of a heterogeneous catalyst. When the activity of the catalyst in an individual reactor vessel falls to an undesirably low level, said reactor vessel is taken out of service and a replacement reactor vessel containing fresh or regenerated catalyst is introduced. The temperature of the feedstream is controlled such that the temperature does not exceed 125 °C. In Comparative Example 1, the temperature of the feed to the reactor vessel is about 38 °C at the start of the epoxidation cycle and the heat-exchangers are initially by-passed. The temperature is gradually increased as necessary to maintain the desired level of conversion. At the end of the epoxidation cycle, the feed inlet temperature of the heat exchanger (and therefore the reactor outlet temperature) is 121 °C for each reactor.

As mentioned in US-A-5,849,937, during operation the temperature of a bank of epoxidation reactors generally is increased in time to maintain the desired level of conversion which would otherwise decrease due to catalyst deactivation.

In the process according to the present invention, it has been found that better use can be made of the catalyst if the temperature of the reactors is increased according to a certain temperature profile.

Summary of the Invention

It has now surprisingly been found that a higher selectivity towards an alkylene oxide can be obtained in a process for preparing the alkylene oxide from an organic hydroperoxide and an alkene with the help of a bank of reactors by applying a specific temperature profile over the reactors. According to the present invention, the temperature of the feed should be such that during operation the outlet temperature of the final reactor is at least 4 °C

2002302597 07 Dec 2007

- 3 -

higher than the outlet temperature of the first reactor and the average temperature of the first reactor should be lower than the average temperature of the final reactor.

Therefore, the present invention concerns a process for the preparation of an alkylene oxide, which process comprises:

passing a feed containing an organic hydroperoxide and an alkene through a bank of at least two serially connected reactors containing epoxidation catalyst; and

withdrawing a product stream comprising an alkylene oxide and an alcohol as reaction products;

wherein the temperature of the feed is controlled in the bank of reactors such that during operation the outlet temperature of the final reactor is at least 4 °C higher than the outlet temperature of the first reactor and that the average temperature of the first reactor is lower than the average temperature of the final reactor.

Detailed Description of the Invention

In the present specification, the reactor is considered to be a reactor if it contains at least 5 %wt of the total catalyst used in the process according to the present invention, preferably at least 7 %wt.

The first reactor is the reactor which is first contacted by the feed in the process according to the present invention. It will be clear to someone skilled in the art that the feed can be pretreated in one or more reactors before being subjected to the process according to the present invention.

The final reactor is the reactor before the alkylene oxide is separated off and is in operation. If the conversion in the reactors in operation is sufficient, it is possible that no feed is passed through one or more reactors

- 4 -

at the start of the operation. At the time when one or more reactors are taken into operation, the temperature profile of these reactors will be relatively rapidly brought into accordance with the present invention. In the present
5 description, the reactors are described in the direction of flow of the feed.

The start of the operation is the time at which the catalyst in the first reactor is replaced by fresh catalyst. In many cases, the temperature profile at the start of
10 operation will be different from the temperature profile during operation due to the fresh catalyst present and constrained cooling duties. The rate at which the temperature profile changes from the profile at the start of operation to the profile during operation, will differ per
15 case. However, "during operation" will generally be after at least one fifth of the lifetime of the catalyst has passed, preferably at least one quarter of the lifetime of the catalyst has passed, more specifically when at least one third of the lifetime of the catalyst has passed. The
20 lifetime of the catalyst is the time during which the catalyst is being used in the process. After having been taken out of operation, catalyst will generally be regenerated and used again in the process of the present invention.

25 As stated, the first reactor contains fresh catalyst at the start of operation. Although the catalyst in all reactors can be replaced at the same time, in some instances it can be advantageous if the catalyst at the end of the reactor bank is replaced at a time different from the time
30 when the catalyst is replaced in the reactors at the beginning of the of the reactor bank.

In the process of the present invention, the

2002302597 07 Dec 2007

2002302597 07 Dec 2007

- 5 -

temperature of the feed is controlled such that during operation the outlet temperature of the final reactor is at least 4 °C higher than the outlet temperature of the first reactor. Preferably, the outlet temperature of the final reactor during operation is at least 8 °C higher than the outlet temperature of the first reactor. More preferably, the outlet temperature of the final reactor during operation is at least 10 °C higher than the outlet temperature of the first reactor, more preferably at least 15 °C higher. Most preferably, the outlet temperature of the final reactor during operation is at least 20 °C higher than the outlet temperature of the first reactor.

In the process of the present invention, the temperature of the feed is preferably controlled such that at the start of the operation the average temperature of each reactor is similar. Although there can be temperature differences, the difference in average temperature of the reactor having the highest average temperature and the reactor having the lowest average temperature is preferably at most 20 °C, more preferably at most 15 °C. There can be exceptional circumstances which make acceptable larger differences in average temperature. The average temperature is defined as the sum of the temperature of the feed on entering the reactor and the temperature of the feed on leaving the reactor, divided by 2.

Generally, catalyst deactivates during operation. Therefore, it is customary to increase the temperature of the reactor containing the catalyst. It has now further been found that a bank of reactors gives a higher yield if the temperature of the reactor is increased not only in such way that the outlet temperature of the final reactor is at least 4 °C higher than the outlet temperature of the first

2002302597 07 Dec 2007

- 6 -

reactor, but if additionally the average temperature of the first reactor is increased at a slower rate than the average temperature of the final reactor. Therefore, at the same point in time during operation the average temperature of the first reactor is lower than the average temperature of the final reactor. More preferably, the average temperature of the first and the final reactor is increased over time in such a way that the difference between the average temperature at the start of operation and the average temperature at a point in the time during operation is smaller for the first reactor than for the final reactor at the same point in time during operation.

If the bank of the reactors contains at least 5 reactors, it is preferred that the second reactor upstream of the final reactor is operated at an average temperature which is at least 5 °C higher during operation than the average temperature maintained in the first reactor, preferably at least 10 °C higher, more preferably at least 15 °C higher.

The temperature difference over reactors can differ greatly even if the average temperature are similar. The temperature difference over a reactor will generally be determined by the feed composition, such as the amount of organic hydroperoxide present, the temperature of the feed on entering the reactor, the activity of the catalyst and the amount of catalyst present in the reactor. It will be clear that the latter can be chosen within the technical and economical constraints known to someone skilled in the art. The activity of the catalyst will depend strongly on the previous operation of the catalyst, such as the amount of feed treated, the number of hours in operation, the composition of the feed and the temperature at which the

2002302597 07 Dec 2007

- 6A -

catalyst has been operated and is being operated.
Preferably, the factors determining the temperature difference over a single reactor are maintained such that the temperature difference over the first reactor is smaller
5 than the temperature difference over the final reactor.
Preferably, the operation is carried out such that the temperature difference over the first reactor is at most 9 °C. If the bank of reactors contains at least 3 reactors, it is further preferred that the temperature difference over
10 the first reactor is smaller than the temperature difference over the middle one or two reactors. If the bank of reactors contains at least

5 reactors, it is preferred that operation is carried out such that the temperature difference over the second reactor upstream of the final reactor is larger than the temperature difference over the first reactor. If the bank of reactors contains at least 5 reactors, the temperature difference over the second reactor upstream of the final reactor preferably is at least 10 °C. If the bank of reactors contains at least 5 reactors, the temperature difference over each the first and the second reactor most preferably is at most 9 °C.

Catalyst is generally replaced when the operating temperature can not be increased further because the temperature of the product coming out of the reactor has reached the maximum temperature. The maximum temperature is mainly determined by the separation means to which the product is sent for separating off the alkylene oxide. The separation means will usually be a distillation column. At the same organic hydroperoxide conversion, increased yield has been observed if the outlet temperature of the final reactor is increased. It is preferred to allow the outlet temperature of the final reactor to be 125 °C or higher, more preferably 130 °C or higher, more preferably 135 °C or higher. Such high outlet temperature of the final reactor, allows reduction of the temperature of the preceding reactors. This makes that the catalyst is used to its full potential.

If cooling means are present between the final reactor and the reactor preceding the final reactor, it can be advantageous to operate the reactor preceding the final reactor at a higher average temperature than the final reactor such as shortly before the majority of the catalyst is to be replaced. In view of the temperature constraints due to the separation means behind the final reactor, the reactor before the final reactor is less restricted in its outlet temperature than the final

reactor if cooling means are present between the reactors.

Heterogeneous epoxidation catalysts are known in the art. Such catalysts may comprise as the catalytically active metal one or more transition metals, such as vanadium, molybdenum, tungsten, titanium and zirconium. One particularly suitable class of heterogeneous epoxidation catalysts are the titanium-based catalysts. Examples of such catalysts are for instance described in US-A-4,367,342 and EP-A-0,345,856. US-A-4,367,342 discloses the use of inorganic oxygen compounds of silicon in chemical composition with at least 0.1% by weight of an oxide or hydroxide of titanium, while EP-A-0,345,856 discloses a titania-on-silica heterogeneous catalyst. According to EP-A-0,345,856 this catalyst is obtainable by impregnating a silicon compound with a stream of gaseous titanium tetrachloride followed by calcination and hydrolysis steps and optionally a silylation step.

In commercial operation the average temperature in an epoxidation reactor is typically of from 50 to 150 °C, preferably of from 60 to 135 °C. The pressure in each reactor can be up to 80 bar, preferably of from 10 to 60 bar. Generally, the reaction medium is in the liquid phase.

In order to obtain the required temperature profile over each reactor, the feed is generally cooled with the help of cooling means present between two subsequent epoxidation reactors.

The bank of serially connected reactors, comprises at least 2 serially connected reactors. Preferably, the bank comprises of from 3 to 7 reactors.

In the process according to the present invention, the feed is preferably passed through the reactors of the bank in a fixed order. This makes that the first reactor

2002302597 07 Dec 2007

- 9 -

will remain the first reactor and the final reactor will remain the final reactor independent from the degree to which the catalyst has been deactivated.

Before passing the feed through a bank of reactors according to the present invention which bank is operated in a fixed order, at least part of the feed can have been passed through a series of reactors which is operated cyclically. A preferred series of reactors which can be used as a series of at least two serially connected reactors containing a bed of heterogeneous epoxidation catalyst particles and operated in a cyclic mode, optionally followed by at least one additional epoxidation reactor containing a bed of heterogeneous epoxidation catalyst particles, and continuously withdrawing a product stream from the final epoxidation reactor comprising an alkylene oxide and an alcohol as reaction products, from which product stream the alkylene oxide end-product is recovered, in which process:

- (a) the first reactor of the cyclically operated bank is put in a position further down this bank or in a position directly after any one of the additional reactors, when the activity of the epoxidation catalyst contained therein has decreased to an undesirably low level;
- (b) in this position the catalyst with decreased activity is contacted with the effluent from the reactor in the preceding position at a temperature which is at least 5 °C higher than the final temperature at which the catalyst was in use in the first position of the bank and for sufficient time to restore its activity to the desired level.

This preferred series of reactors has been described in more detail in PCT patent application EP00/08052.

The process according to the present invention is used in the reaction of an alkene with an organic hydroperoxide. Suitable organic hydroperoxides are

secondary and tertiary hydroperoxides derived from a C₄-C₂₀ aliphatic hydrocarbon, a C₇-C₂₀ aralkyl hydrocarbon or mixtures thereof. Examples of suitable organic hydroperoxides include tert-butyl hydroperoxide, tertiary amyl hydroperoxide, tertiary octyl hydroperoxide, ethylbenzene hydroperoxide, cyclohexyl hydroperoxide and diethyl benzyl hydroperoxide. Of these, ethylbenzene hydroperoxide and tert-butyl hydroperoxide are most suitably applied.

The alkene used can be any organic compound having at least one aliphatic carbon-carbon double bond. Such compound will generally contain from 2 to 25 carbon atoms and preferably from 3 to 12 carbon atoms, such as propene, 1-butene, 2-butene, 1-pentene, 1-octene, 1-dodecene, styrene and methylstyrene. Most preferably, however, propene is used as the alkene, thus producing propylene oxide in accordance with the process of the present invention.

The heterogeneous epoxidation catalyst used may be any such catalyst known in the art to be suitable for catalysing the reaction between an alkene and an organic hydroperoxide into the corresponding alkylene oxide and alcohol. However, titanium-containing catalysts are preferred. Accordingly, the catalysts disclosed in the patent specifications US-A-4,367,342 and EP-A-0,345,856 discussed above may, for instance, be applied. It has, however, been found particularly advantageous to use the titania-on-silica catalysts disclosed in EP-A-0,345,856 in all epoxidation reactors for the purpose of the present invention. When these catalysts are used, very good results are achieved by the present process.

A further catalyst which can be used in the process according to the present invention is a titanium-containing silicon oxide catalyst having (1) a mean pore

size of at least 10 Å, (2) 5 to 200 Å pore size fraction constituting at least 90% of total pore volume, (3) specific pore volume of at least 0.2 cm³/g, and (4) which catalyst is obtained by use of a quaternary ammonium salt template, followed by removal of the template, which template is [NR¹R²R³R⁴]⁺ (Within this formula, R¹ is a linear or branched hydrocarbon group having a carbon number of 2 to 36, and R² to R⁴ indicate alkyl groups having carbon numbers of 1 through 6). The catalyst has been described in more detail in WO-A-01/5778.

The product obtained in a process according to the present invention will generally contain at most 4% wt of unconverted organic hydroperoxide, preferably at most 2 %wt, more preferably at most 1 %wt. The amount of hydroperoxide which is converted in the final reactor can be quite small in which case there is sometimes only a small temperature difference over the final reactor.

The composition of the feed to the epoxidation reactor is not critical for the process of the present invention in the sense that it may have any composition which is common in commercial operation. Accordingly, in case of a styrene/propylene oxide co-production process, the feed to the epoxidation unit comprises at least some ethylbenzene hydroperoxide and normally also a substantial amount of ethylbenzene. Propene is either added to the reactor as a separate feed stream or may be added to the ethylbenzene hydroperoxide-containing feed stream prior to entry into the epoxidation reactor(s). The feed may also contain some methyl phenyl ketone and/or 1-phenyl-ethanol formed in the preceding oxidation section or in a preceding epoxidation reactor or contained in a recycle stream. The exact feed composition depends on whether at least part of the feed has already

2002302597 07 Dec 2007

- 12 -

been contacted with a previous series of epoxidation reactors, preferably a series which is operated cyclically, preferably a series as described in patent application PCT/EP00/08052. A typical feed stream to the epoxidation reactor, which is first
5 in line after the preceding oxidation step including oxidation reactor product work-up steps (like washing and distillation), comprises from 15 to 25 wt% ethylbenzene hydroperoxide, from 30 to 50 wt% ethylbenzene, from 30 to 50 wt% propene, from 0 to 5 wt% 1-phenyl-ethanol and from 0 to 5 wt% methyl phenyl ketone,
10 to a total of 100 wt%.

In an MTBE/propylene oxide co-production process the feed to the epoxidation reactor comprises at least some tert-butyl hydroperoxide (TBHP) in a tert-butanol solvent. Similarly to the styrene/propylene oxide co-production process, propene is
15 either added to the reactor as a separate feed stream or may be added to the TBHP-containing feed stream prior to entry into the epoxidation reactor.

The process according to the present invention can further comprise recovering the alkylene oxide from the product stream
20 comprising the alkylene oxide and the alcohol, preferably with the help of distillation.

The process according to the present invention can further comprise recovering the alcohol from the product stream comprising the alkylene oxide and the alcohol and dehydrating
25 the alcohol with the help of a dehydration catalyst to obtain the corresponding alkene.

The process according to the present invention can further comprise recovering the alcohol from the product stream comprising the alkylene oxide and the alcohol and reacting the
30 alcohol with methanol to obtain an ether.

The invention is further illustrated by the following

examples without limiting the scope of the invention to these particular embodiments.

Examples

The epoxidation catalyst was a catalyst containing
5 titanium on silica which was prepared as described in the Example according to the teaching of EP-A-345856.

The organic hydroperoxide used contained between 30 and 40 wt% of ethylbenzene hydroperoxide in ethylbenzene.

There was a molar excess of propene present in the feed,
10 based on the molar amount of organic hydroperoxide.

The feeds were supplied to the first reactor via two high pressure pumps and mixed together before entering the reactor. The reactor was operated liquid full at 50 bar pressure. Before entering the bank of reactors according to the present
15 invention, the feed had been treated with the help of a series of reactors which was operated cyclically as described in patent application PCT/EP00/08052.

The bank of reactors consisted of 7 reactors which had been operated for more than 1 month. Each of these reactors
20 contained at least 7 %wt of the total amount of catalyst applied in the bank of reactors. Cooling means between each of the reactors adjust the temperature of the reaction fluid, with the exception of reactors 6 and 7 between which there is no cooling means.

25 The product of reactor 7 was virtually free of ethylbenzene hydroperoxide both during operation according to the invention and during operation not according to the invention.

The propylene oxide yield was taken to be the molar
30 amount of propylene oxide obtained divided by the molar amount of ethylbenzene hydroperoxide supplied, multiplied by 100.

Example 1

The temperature profile of the reactors was as described in Table 1 (not according to the invention).

2002302597 07 Dec 2007

Table 1

(not according to the invention)

	Average temperature (°C)	Temperature in (°C)	Temperature out (°C)	Increase (°C)
Reactor 1	104	97	112	15
Reactor 2	104	97	110	13
Reactor 3	104	93	114	21
Reactor 4	105	94	117	23
Reactor 5	105	100	110	10
Reactor 6	101	101	102	1
Reactor 7	102	101	103	2

After changing the temperature profile over the reactors with the help of the cooling means, the temperature profile of Table 2 (according to the invention) was attained.

Table 2

(according to the invention)

	Average temperature (°C)	Temperature in (°C)	Temperature out (°C)	Increase (°C)
Reactor 1	77	75	79	3
Reactor 2	74	73	75	2
Reactor 3	72	69	74	5
Reactor 4	77	69	84	15
Reactor 5	95	79	112	34
Reactor 6	111	107	115	8
Reactor 7	118	115	121	6

5

It was found that when operation was carried out according to Table 2 for 10 hours, the average propylene oxide yield during these 10 hours was 0.7 mole% higher than the average yield during the 10 hours before

switching to the temperature profile according to Table 2, i.e. when the operation still had the temperature profile according to Table 1.

Example 2

- 5 After having operated the bank of reactors according to Table 2 for 3 days after having carried out Example 1, the temperature profile was according to Table 3 (according to the invention).

Table 3
(according to the invention)

	Average temperature (°C)	Temperature in (°C)	Temperature out (°C)	Increase (°C)
Reactor 1	86	84	88	5
Reactor 2	82	80	83	3
Reactor 3	77	74	80	6
Reactor 4	80	73	86	13
Reactor 5	98	82	115	33
Reactor 6	115	109	121	13
Reactor 7	124	120	127	7

- 10 With the help of the cooling means, the temperature profile was changed to the temperature profile according to Table 4 (not according to the invention).

Table 4

(not according to the invention)

	Average temperature (°C)	Temperature in (°C)	Temperature out (°C)	Increase (°C)
Reactor 1	105	99	111	12
Reactor 2	103	98	108	10
Reactor 3	103	95	111	17
Reactor 4	103	93	113	20
Reactor 5	101	94	108	13
Reactor 6	109	108	111	4
Reactor 7	112	110	114	4

It was found that when the operation according to Table 4 was carried out for 10 hours, the average propylene oxide yield during these 10 hours was 0.6 mole% less than the average propylene oxide yield during 10 hours before the temperature profile was changed to Table 4, i.e. during operation according to the temperature profile of Table 3.

Example 3

After having operated the bank of reactors not according to the invention for 4 days after having carried out Example 2, the temperature profile was according to Table 5 (not according to the invention).

Table 5

(not according to the invention)

	Average temperature (°C)	Temperature in (°C)	Temperature out (°C)	Increase (°C)
Reactor 1	105	98	111	13
Reactor 2	104	99	110	11
Reactor 3	105	95	114	19
Reactor 4	106	94	118	24
Reactor 5	105	99	111	12
Reactor 6	110	109	111	2
Reactor 7	111	110	113	3

After changing the temperature profile over the reactors with the help of the cooling means, the temperature profile of Table 6 (according to the invention) was attained.

Table 6

(according to the invention)

	Average temperature (°C)	Temperature in (°C)	Temperature out (°C)	Increase (°C)
Reactor 1	87	84	89	5
Reactor 2	85	83	87	4
Reactor 3	80	76	84	8
Reactor 4	82	74	90	16
Reactor 5	101	84	118	34
Reactor 6	114	109	118	9
Reactor 7	120	117	123	6

5

It was found that when operation was carried out according to Table 6 for 10 hours, the average propylene oxide yield during these 10 hours was 1.2 mole% higher than the average propylene oxide yield during 10 hours

before switching to the temperature profile according to Table 6, i.e. when the operation still had the temperature profile according to Table 5.

Example 4

5 After having operated the bank of reactors according to the invention for 4 days, the temperature profile was according to Table 7 (according to the invention).

Table 7
(according to the invention)

	Average temperature (°C)	Temperature in (°C)	Temperature out (°C)	Increase (°C)
Reactor 1	87	84	89	4
Reactor 2	83	81	84	3
Reactor 3	78	76	81	5
Reactor 4	80	74	86	12
Reactor 5	97	81	114	34
Reactor 6	114	106	122	17
Reactor 7	127	122	133	11

10 After changing the temperature profile over the reactors with the help of the cooling means, the temperature profile of Table 8 (according to the invention) was attained.

2002302597 07 Dec 2007

- 19 -

Table 8
(according to the invention)

	Average Temperature (°C)	Temperature in (°C)	Temperature out (°C)	Increase (°C)
Reactor 1	105	99	110	11
Reactor 2	103	98	107	9
Reactor 3	103	95	111	16
Reactor 4	104	92	116	24
Reactor 5	102	93	111	18
Reactor 6	109	106	112	6
Reactor 7	114	111	117	6

It was found that when operation was carried out according to Table 8 for 10 hours, the average propylene oxide yield during these 10 hours was 0.3 mole% less than the average propylene oxide yield during the 10 hours before switching to the temperature profile according to Table 8, i.e. when the operation still had the temperature profile according to Table 7.

Throughout this specification and the claims which follow, unless the context requires otherwise, the word "comprise", and variations such as "comprises" and "comprising", will be understood to imply the inclusion of a stated integer or step or group of integers or steps but not the exclusion of any other integer or step or group of integers or steps.

The reference in this specification to any prior publication (or information derived from it), or to any matter which is known, is not, and should not be taken as an

2002302597 07 Dec 2007

- 19A -

acknowledgment or admission or any form of suggestion that that prior publication (or information derived from it) or known matter forms part of the common general knowledge in the field of endeavour to which this specification relates.

- 20 -

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A process for the preparation of an alkylene oxide,
which process comprises:
 - 5 passing a feed containing an organic hydroperoxide and
an alkene through a bank of at least two serially connected
reactors containing epoxidation catalyst; and
withdrawing a product stream comprising an alkylene
oxide and an alcohol as reaction products;
 - 10 wherein the temperature of the feed is controlled in
the bank of reactors such that during operation the outlet
temperature of the final reactor is at least 4 °C higher
than the outlet temperature of the first reactor and that
the average temperature of the first reactor is lower than
15 the average temperature of the final reactor.
2. A process as claimed in claim 1, wherein the
temperature difference over the first reactor is smaller
than the temperature difference over the final reactor.
- 20 3. A process as claimed in claim 1 or 2, wherein the
average temperature of the first and the final reactor is
increased over time in such a way that the difference
between the average temperature at the start of operation
25 and the average temperature at a point in the time during
operation is smaller for the first reactor than for the
final reactor at the same point in time during operation.
4. A process as claimed in any one of claims 1 to 3,
30 wherein the feed is passed through the reactors of the bank
in a fixed order.

2002302597 07 Dec 2007

2002302597 07 Dec 2007

- 21 -

5. A process according to any one of claims 1 to 3 comprising passing at least part of the feed through a series of reactors which is operated cyclically, before passing the feed obtained through a bank of reactors
5 operated in a fixed order.
6. A process as claimed in any one of claims 1 to 5, which process further comprises:
recovering the alkylene oxide from the product stream
10 comprising the alkylene oxide and the alcohol.
7. A process as claimed in any one of claims 1 to 6, which process further comprises:
recovering the alcohol from the product stream
15 comprising the alkylene oxide and the alcohol; and
dehydrating the alcohol with the help of a dehydration catalyst to obtain the corresponding alkene.
8. A process as claimed in any one of claims 1 to 6, which
20 process further comprises:
recovering the alcohol from the product stream
comprising the alkylene oxide and the alcohol and reacting the alcohol with methanol to obtain an ether.
- 25 9. A process for the preparation of an alkylene oxide according to claim 1, substantially as hereinbefore described with reference to the Examples.
10. An alkylene oxide when prepared by the process
30 according to any one of the preceding claims.
11. An alkene when obtained by the process according to

- 22 -

claim 7.

12. An ether when obtained by the process according to
claim 8.

5

2002302597 07 Dec 2007