

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : C23G 5/028, C11D 7/50	A1	(11) International Publication Number: WO 93/04219 (43) International Publication Date: 4 March 1993 (04.03.93)
(21) International Application Number: PCT/US92/06800 (22) International Filing Date: 13 August 1992 (13.08.92) (30) Priority data: 746,255 15 August 1991 (15.08.91) US 851,447 16 March 1992 (16.03.92) US (71) Applicant: ALLIED-SIGNAL INC. [US/US]; 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US). (72) Inventors: SWAN, Ellen, Louise ; 4584 Dickersonville Road, Ransomville, NY 14131 (US). BASU, Rajat, Subhra ; 167 Shetland Road, Williamsville, NY 14075 (US). VAN DER PUY, Michael ; 32 Joanne Lane, Cheektowaga, NY 14227 (US). HOLLISTER, Richard, Mervil ; 221 Englewood Avenue, Buffalo, NY 14214 (US).		(74) Agent: ROONEY, Gerard, P.; Allied-Signal, Inc., Law Department (C.A. McNally), P.O. Box 2245, Morristown, NJ 07962-2245 (US). (81) Designated States: AU, BB, BG, BR, CA, CS, FI, HU, JP, KP, KR, LK, MG, MN, MW, NO, PL, RO, RU, SD, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: AZEOTROPE-LIKE COMPOSITIONS OF 2-TRIFLUOROMETHYL-1,1,1,2-TETRAFLUOROBUTANE AND METHANOL, ETHANOL OR ISOPROPANOL (57) Abstract Azeotrope-like compositions comprising 2-trifluoromethyl-1,1,1,2-tetrafluorobutane and methanol, ethanol or isopropanol and optionally nitromethane are stable and have utility as degreasing agents and as solvents in a variety of industrial cleaning applications including cold cleaning and defluxing of printed circuit boards and dry cleaning.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FI	Finland	MN	Mongolia
AU	Australia	FR	France	MR	Mauritania
BB	Barbados	GA	Gabon	MW	Malawi
BE	Belgium	GB	United Kingdom	NL	Netherlands
BF	Burkina Faso	GN	Guinea	NO	Norway
BG	Bulgaria	GR	Greece	NZ	New Zealand
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	IE	Ireland	PT	Portugal
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	RU	Russian Federation
CG	Congo	KP	Democratic People's Republic of Korea	SD	Sudan
CH	Switzerland	KR	Republic of Korea	SE	Sweden
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovak Republic
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CS	Czechoslovakia	LU	Luxembourg	SU	Soviet Union
CZ	Czech Republic	MC	Monaco	TD	Chad
DE	Germany	MG	Madagascar	TG	Togo
DK	Denmark	ML	Mali	UA	Ukraine
ES	Spain			US	United States of America

5 AZEOTROPE-LIKE COMPOSITIONS OF
 2-TRIFLUOROMETHYL-1,1,1,2-TETRAFLUOROBUTANE
 AND METHANOL, ETHANOL OR ISOPROPANOL

10 FIELD OF THE INVENTION

10 This invention relates to azeotrope-like mixtures
 of 2-trifluoromethyl-1,1,1,2-tetrafluorobutane. These
 mixtures are useful in a variety of vapor degreasing,
 cold cleaning and solvent cleaning applications
15 including defluxing and dry cleaning.

BACKGROUND OF THE INVENTION

20 Vapor degreasing and solvent cleaning with
 fluorocarbon based solvents have found widespread use
 in industry for the degreasing and otherwise cleaning
 of solid surfaces, especially intricate parts and
 difficult to remove soils.

25 In its simplest form, vapor degreasing or solvent
 cleaning consists of exposing a room temperature object
 to be cleaned to the vapors of a boiling solvent.
 Vapors condensing on the object provide clean distilled
30 solvent to wash away grease or other contamination.
 Final evaporation of solvent from the object leaves
 behind no residue as would be the case where the object
 is simply washed in liquid solvent.

35 For difficult to remove soils where elevated
 temperature is necessary to improve the cleaning action
 of the solvent, or for large volume assembly line

operations where the cleaning of metal parts and assemblies must be done efficiently and quickly, the conventional operation of a vapor degreaser consists of immersing the part to be cleaned in a sump of boiling solvent which removes the bulk of the soil, thereafter immersing the part in a sump containing freshly distilled solvent near room temperature, and finally exposing the part to solvent vapors over the boiling sump which condense on the cleaned part. In addition, the part can also be sprayed with distilled solvent before final rinsing.

Vapor degreasers suitable in the above-described operations are well known in the art. For example, Sherliker et al. in U.S. Patent 3,085,918 disclose such suitable vapor degreasers comprising a boiling sump, a clean sump, a water separator, and other ancillary equipment.

Cold cleaning is another application where a number of solvents are used. In most cold cleaning applications, the soiled part is either immersed in the fluid or wiped with rags or similar objects soaked in solvents and allowed to air dry.

Fluorocarbon solvents, such as trichlorotrifluoroethane, have attained widespread use in recent years as effective, nontoxic, and nonflammable agents useful in degreasing applications and other solvent cleaning applications. Trichlorotrifluoroethane has been found to have satisfactory solvent power for greases, oils, waxes and the like. It has therefore found widespread use for cleaning electric motors, compressors, heavy metal parts, delicate precision metal parts, printed circuit

boards, gyroscopes, guidance systems, aerospace and missile hardware, aluminum parts and the like.

Azeotropic or azeotrope-like compositions are
5 desired because they do not fractionate upon boiling. This behavior is desirable because in the previously described vapor degreasing equipment with which these solvents are employed, redistilled material is generated for final rinse-cleaning. Thus, the vapor
10 degreasing system acts as a still. Unless the solvent composition exhibits a constant boiling point, i.e., is azeotrope-like, fractionation will occur and undesirable solvent distribution may act to upset the cleaning and safety of processing. Preferential
15 evaporation of the more volatile components of the solvent mixtures, which would be the case if they were not azeotrope-like, would result in mixtures with changed compositions which may have less desirable properties, such as lower solvency towards soils, less
20 inertness towards metal, plastic or elastomer components, and increased flammability and toxicity. The art has looked towards azeotrope or azeotrope-like compositions including the desired fluorocarbon components such as trichlorotrifluoroethane which
25 include components which contribute additionally desired characteristics, such as polar functionality, increased solvency power, and stabilizers.

The art is continually seeking new fluorocarbon,
30 hydrofluorocarbon, and hydrochlorofluorocarbon based azeotrope-like mixtures which offer alternatives for new and special applications for vapor degreasing and other cleaning applications. Currently, of particular interest, are fluorocarbon, hydrofluorocarbon, and
35 hydrochlorofluorocarbon based azeotrope-like mixtures

with minimal or no chlorine which are considered to be stratospherically safe substitutes for presently used chlorofluorocarbons (CFCs). The latter are suspected of causing environmental problems in connection with the earth's protective ozone layer. Mathematical models have substantiated that hydrofluorocarbons, such as 2-trifluoromethyl-1,1,1,2-tetrafluorobutane (known in the art as HFC-467), will not adversely affect atmospheric chemistry, being negligible contributors to ozone depletion and to green-house global warming in comparison to chlorofluorocarbons such as 1,1,2-trichloro-1,2,2-trifluoroethane (CFC-113).

European Publication 431,458 published June 12, 1991 teaches a mixture of 1,1,2,3,4,4-hexafluorobutane and ethanol. U.S. Patent 5,023,010 teaches an azeotropic mixture of 1,1,1,2,3,3-hexafluoro-3-methoxypropane and methanol. U.S. Patent 5,035,830 teaches an azeotropic mixture of hexafluoropropylene/ethylene cyclic dimer and methanol or ethanol. U.S. Patent 5,064,559 teaches an azeotropic mixture of 1,1,1,2,3,4,4,5,5,5-decafluoropentane and methanol or ethanol. U.S. Patent 5,073,291 teaches an azeotrope-type mixture of 1,4-dihydroperfluorobutane and methanol.

U.S. Patents 5,073,288 and 5,073,290 teach binary azeotrope-like compositions of 1,1,1,2,2,3,5,5,5-nonafluoro-4-trifluoromethylpentane or 1,1,1,2,2,5,5,5-octafluoro-4-trifluoromethylpentane and methanol or ethanol.

U.S. Patent 4,842,764 discloses azeotrope-like compositions of 1,1-dichloro-1-fluoroethane and methanol. U.S. Patent 4,970,013 discloses azeotropic

mixtures of 2,3-dichloro-1,1,1,3,3-pentafluoropropane and methanol. U.S. Patent 4,986,928 discloses azeotropic mixtures of 1-chloro-1,2,2-trifluorocyclobutane and methanol. Commonly assigned
5 U.S. Patent 4,988,455 discloses azeotrope-like compositions of 1,1-dichloro-1,2,2-trifluoropropane and methanol.

U.S. Patent 5,023,010 discloses azeotropic
10 mixtures of 1,1,1,2,3,3-hexafluoro-3-methoxypropane and methanol. Kokai Patent Publication 98,699 published April 17, 1989 discloses azeotropic compositions of 1,1-dichloro-2,2,2-trifluoroethane and methanol. Kokai Patent Publication 304,194 published December 7, 1989
15 discloses azeotropic mixtures of 1-chloro-2,2,3,3-tetrafluoropropane and methanol.

DETAILED DESCRIPTION OF THE INVENTION

20 Our solution to the need in the art for substitutes for chlorofluorocarbon solvents is mixtures comprising 2-trifluoromethyl-1,1,1,2-tetrafluorobutane and methanol, ethanol or isopropanol and optionally nitromethane. Also, novel azeotrope-like or
25 constant-boiling compositions have been discovered comprising 2-trifluoromethyl-1,1,1,2-tetrafluorobutane and methanol, ethanol or isopropanol and optionally nitromethane.

30 Preferably, the novel azeotrope-like compositions comprise effective amounts of 2-trifluoromethyl-1,1,1,2-tetrafluorobutane and methanol, ethanol or isopropanol and optionally nitromethane. The term
"effective amounts" as used herein means the amount of
35 each component which upon combination with the other

component, results in the formation of the present azeotrope-like compositions.

The azeotrope-like compositions comprise from about 64 to about 99.5 weight percent of 2-trifluoromethyl-1,1,1,2-tetrafluorobutane and from about 0.5 to about 36 of ethanol or isopropanol and from 0 to about 1 weight percent nitromethane. When methanol is present the novel azeotrope-like compositions comprise from about 70 to about 99.5 weight percent of 2-trifluoromethyl-1,1,1,2-tetrafluorobutane and from about 0.5 to about 30 weight percent of methanol.

The present azeotrope-like compositions are advantageous for the following reasons. The 2-trifluoromethyl-1,1,1,2-tetrafluorobutane is a negligible contributor to ozone depletion and has a boiling point of 37°C. The methanol, ethanol and isopropanol components have good solvent properties. Thus, when these components are combined in effective amounts, an efficient azeotrope-like solvent results.

The preferred methanol based azeotrope-like compositions are in Table I below where 2-trifluoromethyl-1,1,1,2-tetrafluorobutane is abbreviated as HFC-467:

TABLE I

COMPONENTS	PREFERRE D RANGE (WT. %)	MORE PREFERRED RANGE (WT. %)	MOST PREFERRE D RANGE (WT. %)	BOILING POINT (°C) (760mmHg)
HFC-467	75-97	80-96	96-94	33.5 ± 1.0
Methanol	3-25	4-20	6-14	
Nitrometha ne	0	0	0	

The preferred ethanol based azeotrope-like compositions are in Table II below where 2-trifluoromethyl-1,1,1,2-tetrafluorobutane is abbreviated as HFC-467:

TABLE II

COMPONENTS	PREFERRED RANGE (WT. %)	MORE PREFERRED RANGE (WT. %)	MOST PREFERRED RANGE (WT. %)	BOILING POINT (°C) (760mmHg)
HFC-467	64-99.5	79.5-99	84.6-98.5	36.5 ± 0.5
Ethanol	0.5-36	1-20.5	1.5-15.4	
Nitromethane	0-1	0-0.5	0-0.4	

The preferred isopropanol based azeotrope-like compositions are in Table III below where 2-trifluoromethyl-1,1,1,2-tetrafluorobutane is abbreviated as HFC-467:

TABLE III

COMPONENTS	PREFERRED RANGE (WT. %)	MORE PREFERRED RANGE (WT. %)	MOST PREFERRED RANGE (WT. %)	BOILING POINT (°C) (760mmHg)
HFC-467	71.5-99.5	78.3-99	82.9-98.6	38.1 ± 0.5
Isopropanol	0.5-28.5	1-21.7	1.4-17.1	
Nitromethane	0-1	0-0.5	0-0.4	

All compositions within the indicated ranges, as well as certain compositions outside the indicated ranges, are azeotrope-like, as defined more particularly below.

The precise azeotrope compositions have not been determined but have been ascertained to be within the above ranges. Regardless of where the true azeotropes lie, all compositions with the indicated ranges, as well as certain compositions outside the indicated ranges, are azeotrope-like, as defined more particularly below.

The term "azeotrope-like composition" as used herein is intended to mean that the composition behaves like an azeotrope, i.e. has constant-boiling characteristics or a tendency not to fractionate upon boiling or evaporation. Thus, in such compositions, the composition of the vapor formed during boiling or evaporation is identical or substantially identical to the original liquid composition. Hence, during boiling or evaporation, the liquid composition, if it changes at all, changes only to a minimal or negligible extent. This is to be contrasted with non-azeotrope-like compositions in which during boiling or evaporation, the liquid composition changes to a substantial degree. As is readily understood by persons skilled in the art, the boiling point of the azeotrope-like composition will vary with the pressure.

25

The azeotrope-like compositions of the invention are useful as solvents in a variety of vapor degreasing, cold cleaning and solvent cleaning applications including defluxing and dry cleaning.

30

In one process embodiment of the invention, the azeotrope-like compositions of the invention may be used to dissolve contaminants or remove contaminants from the surface of a substrate by treating the surfaces with the compositions in any manner well known

35

to the art such as by dipping or spraying or use of conventional degreasing apparatus wherein the contaminants are substantially removed or dissolved.

5 The 2-trifluoromethyl-1,1,1,2-tetrafluorobutane of the present azeotrope-like compositions may be prepared by reacting commercially available 4-iodo-2-trifluoromethyl-1,1,1,2-tetrafluorobutane with zinc and hydrogen chloride. The methanol; ethanol; isopropanol;
10 and nitromethane components of the novel solvent azeotrope-like compositions of the invention are known materials and are commercially available.

 The present invention is more fully illustrated by
15 the following non-limiting Examples.

EXAMPLE 1

 This Example is directed to the preparation of 2-trifluoromethyl-1,1,1,2-tetrafluorobutane.

20

 A 500 milliliter flask fitted with a mechanical stirrer, distillation column, and take-off head was charged with 15 grams (0.046 mole) of commercially available 4-iodo-2-trifluoromethyl-
25 1,1,1,2-tetrafluorobutane, 28.5 grams (0.45 mole) zinc dust, and 230 milliliters of 10% hydrogen chloride. The mixture was stirred and heated to 50°C and 7.4 grams (80% yield) of distillate (boiling point 37°C-39°C) was collected. ¹H NMR (CDCl₃): 2.1 (m,
30 2H), 1.2 (t, 3 H) ppm.

EXAMPLE 2

 A microebulliometer which consisted of a 15 milliliter round bottom double neck flask containing a
35 magnetic stirbar and heated with an electrical heating

mantel was used. Three milliliters of 2-trifluoromethyl-1,1,1,2-tetrafluorobutane was charged into the microebulliometer and methanol was added in small measured increments by an automated syringe capable of a injecting microliters. The temperature was measured using a platinum resistance thermometer and barometric pressure was measured. An approximate correction to the boiling point was done to obtain the boiling point at 760 mm Hg.

10

The following Table IV shows the boiling point measurements, corrected to 760 mm Hg (101kPa), for various mixtures of 2-trifluoromethyl-1,1,1,2-tetrafluorobutane and methanol. From about 6.5 to about 25 weight percent methanol as shown in Table IV, the boiling point of the composition changed by only 1°C. Therefore, the composition behaves as a constant-boiling composition over this range.

<u>TABLE IV</u>			
<u>Liquid Mixture</u>			
	Parts by weight%	Parts by Weight %	Boiling Point
	<u>(CFC) 2CFCH₂CH₃</u>	<u>Methanol</u>	<u>@760mmHg(101kPa)</u>
	100.00	0	37.0
	97.28	2.72	36.3
25	95.72	4.28	35.1
	94.70	5.30	34.6
	93.71	6.29	34.1
	92.00	8.00	33.0
	90.00	10.00	32.8
30	86.70	13.30	32.6
	75.40	24.60	32.8

EXAMPLE 3

This example shows that a minimum in the boiling point versus composition curve occurs in the region of

35

88.7 weight percent 2-trifluoromethyl-1,1,1,2-tetrafluorobutane (hereinafter HFC-467) and 11.3 weight percent ethanol indicating that an azeotrope forms in the neighborhood of this composition.

5

A microebulliometer which consisted of a 15 milliliter round bottom double neck flask containing a magnetic stirbar and heated with an electrical heating mantel was used. Approximately 2.5 milliliters of the lower boiling material, HFC-467, was charged into the microebulliometer and ethanol was added in small measured increments by an automated syringe capable of injecting microliters. The temperature was measured using a platinum resistance thermometer and barometric pressure was measured. An approximate correction to the boiling point was done to obtain the boiling point at 760 mm Hg.

The boiling point was measured and corrected to 760 mm Hg (101 kPa) for various mixtures of HFC-467 and ethanol. Interpolation of the data shows that a minimum boiling point occurs in the region of about 1.5 to about 18 weight percent ethanol. The best estimate of the position of the minimum is 11.3 weight percent ethanol, although the mixtures are constant-boiling, to within 0.3°C, in the region of 0.5 to 35 weight percent ethanol. A minimum boiling azeotrope is thus shown to exist in this composition range.

From the above example, it is readily apparent that additional constant-boiling or essentially constant-boiling mixtures of the same components can readily be identified by anyone of ordinary skill in this art by the method described. No attempt was made to fully characterize and define the outer limits of

the composition ranges which are constant-boiling. Anyone skilled in the art can readily ascertain other constant-boiling or essentially constant-boiling mixtures containing the same components.

5

EXAMPLE 4

Example 3 was repeated except that isopropanol (purity 90%) was used instead of ethanol. Approximately 2.8 milliliters of the lower boiling material, HFC-467, were initially charged into the microebulliometer and isopropanol was added in small measured increments by an automated syringe capable of injecting microliters. The boiling point was measured and corrected to 760 mm Hg (101 kPa), for various mixtures of HFC-467 and isopropanol. Interpolation of these data shows that a minimum boiling point occurs in the region of about 1.4 to about 17.7 weight percent isopropanol. The best estimate of the position of the minimum is 8 weight percent isopropanol, although the mixtures are constant-boiling, to within 0.3°C, in the region of 0.5 to 27.5 weight percent isopropanol. A minimum boiling azeotrope is thus shown to exist in this composition range.

Inhibitors may be added to the present azeotrope-like compositions to inhibit decomposition of the compositions; react with undesirable decomposition products of the compositions; and/or prevent corrosion of metal surfaces. Any or all of the following classes of inhibitors may be employed in the invention:

- alkanols having 4 to 7 carbon atoms, nitroalkanes having 2 to 3 carbon atoms, 1,2-epoxyalkanes having 2 to 7 carbon atoms, phosphite esters having 12 to 30 carbon atoms, ethers having 3 or 4 carbon atoms, unsaturated compounds having 4 to 6 carbon atoms,

acetals having 4 to 7 carbon atoms, ketones having 3 to 5 carbon atoms, and amines having 6 to 8 carbon atoms. Other suitable inhibitors will readily occur to those skilled in the art.

5

The inhibitors may be used alone or in mixtures thereof in any proportions. Typically, up to about 2 percent based on the total weight of the azeotrope-like composition of inhibitor might be used.

10

When the present azeotrope-like compositions are used to clean solid surfaces by spraying the surfaces with the compositions, preferably, the azeotrope-like compositions are sprayed onto the surfaces by using a propellant. Preferably, the propellant is selected from the group consisting of hydrocarbons, chlorofluorocarbons, hydrochlorofluorocarbon, hydrofluorocarbon, dimethyl ether, carbon dioxide, nitrogen, nitrous oxide, methylene oxide, air, and mixtures thereof.

20

Having described the invention in detail and by reference to preferred embodiments thereof, it will be apparent that modifications and variations are possible without departing from the scope of the invention defined in the appended claims.

25

What is claimed is:

1. Azeotrope-like compositions comprising from about 64 to about 99.5 weight percent of 2-trifluoromethyl-1,1,1,2-tetrafluorobutane and from about 0.5 to about 36 of ethanol or isopropanol and from 0 to about 1 weight percent nitromethane.
2. The azeotrope-like compositions of claim 1 wherein said compositions boil at about 36.5°C at 760 mm Hg.
3. The azeotrope-like compositions of claim 1 consisting essentially of from about 79.5 to about 99.5 weight percent said 2-trifluoromethyl-1,1,1,2-tetrafluorobutane and from about 1 to about 20.5 weight percent said ethanol and from about 0 to about 0.5 weight percent said nitromethane wherein said compositions boil at about 36.5°C at 760 mm Hg.
4. The azeotrope-like compositions of claim 1 consisting essentially of from about 71.5 to about 99.5 weight percent said 2-trifluoromethyl-1,1,1,2-tetrafluorobutane and from about 0.5 to about 28.5 weight percent said isopropanol and from about 0 to about 1 weight percent said nitromethane wherein said compositions boil at about 38.1°C at 760 mm Hg.
5. The azeotrope-like compositions of claim 1 consisting essentially of from about 82.9 to about 98.6 weight percent said 2-trifluoromethyl-1,1,1,2-tetrafluorobutane and from about 1.4 to about 17.1 weight percent said isopropanol and from about 0 to about 0.4 weight percent said nitromethane wherein said compositions boil at about 38.1°C at 760 mm Hg.

6. Azeotrope-like compositions comprising from about 70 to about 99.5 weight percent of 2-trifluoromethyl-1,1,1,2-tetrafluorobutane and from about 0.5 to about 30 weight percent of methanol.

7. The azeotrope-like compositions of claim 1 which boil at about 33.5°C \pm about 1.0°C at 760 mm Hg.

8. The azeotrope-like compositions of claim 2 comprising from about 75 to about 97 weight percent said 2-trifluoromethyl-1,1,1,2-tetrafluorobutane and from about 3 to about 25 weight percent said methanol.

9. The azeotrope-like compositions of claim 1 through 8 wherein said compositions additionally contain an inhibitor selected from the group consisting of alkanols having 4 to 7 carbon atoms, nitroalkanes having 2 to 3 carbon atoms, 1,2-epoxyalkanes having 2 to 7 carbon atoms, phosphite esters having 12 to 30 carbon atoms, ethers having 3 or 4 carbon atoms, unsaturated compounds having 4 to 6 carbon atoms, acetals having 4 to 7 carbon atoms, ketones having 3 to 5 carbon atoms, and amines having 6 to 8 carbon atoms.

25

10. A method of dissolving contaminants or removing contaminants from the surface of a substrate which comprises the step of:

using said azeotrope-like composition of claims 1 through 8 as solvent.

INTERNATIONAL SEARCH REPORT

PCT/US 92/06800

International Application No

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC Int.Cl. 5 C23G5/028; C11D7/50		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
Int.Cl. 5	C23G ; C11D	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
	No relevant documents disclosed -----	
<p>¹⁰ Special categories of cited documents :</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search 16 OCTOBER 1992	Date of Mailing of this International Search Report 29. 10. 92	
International Searching Authority EUROPEAN PATENT OFFICE	Signature of Authorized Officer LOISELET-TAISNE S.	