



(43) International Publication Date
31 July 2014 (31.07.2014)

(10) International Publication Number
WO 2014/116281 A1

(51) International Patent Classification:

A61B 17/03 (2006.01) *A61B 17/04* (2006.01)
A61F 13/02 (2006.01)

(21) International Application Number:

PCT/US2013/031502

(22) International Filing Date:

14 March 2013 (14.03.2013)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/756,931 25 January 2013 (25.01.2013) US

(72) Inventor; and

(71) Applicant : PATENAUDE, Bart [US/US]; 15 E. 54th
Street, Kansas City, MO 64112 (US).

(74) Agent: COOK, Crissa, A.; HOVEY WILLIAMS LLP,
10801 Mastin Blvd. Suite 1000, 84 Corporate Woods,
Overland Park, KS 66210 (US).

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,

— with international search report (Art. 21(3))

(54) Title: ATRAUMATIC WOUND CARE AND CLOSURE SYSTEM

(57) Abstract: An article useful for atraumatic care and/or closure of wounds, as well as for repairing torn or ripped fabric is provided. The article comprises a substrate having opposing first and second major surfaces, a plurality of raised anchoring members disposed across the first major surface, and an adhesive adjacent the second major surface. The substrate is a flexible and conformal continuous web that can be cut into pieces to custom fit the wound or fabric opening. Using the anchoring members and a thread, the pieces can be drawn together to correspondingly draw the tissue or fabric on either side(s) of the opening together, thereby closing the opening without piercing or suturing/sewing together the underlying tissue or fabric. Methods for the atraumatic care and/or closure of wounds, as well as for repairing torn or ripped fabric are also provided, including kits to facilitate the same.



WO 2014/116281 A1

ATRAUMATIC WOUND CARE AND CLOSURE SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application claims the priority benefit of U.S. Provisional Patent Application
5 Serial No. 61/756,931, filed January 25, 2013, entitled ATRAUMATIC WOUND CARE AND
CLOSURE SYSTEM, incorporated by reference in its entirety herein.

BACKGROUND

Field of the Invention

10 The present disclosure relates to an article, system, and method for the closure of wounds,
tears, and rips, without piercing the underlying torn tissue or fabric.

Description of Related Art

15 Traditional wound closure techniques involve the use of sutures, commonly known as
stitches, while more modern techniques utilize staples, adhesives, hemostats, and/or sealants. The
primary function of a wound closure device or technique is to close a wound, both internal and
external, and stop the bleeding through hemostasis. And important secondary function that wound
closure techniques are expected to perform is avoiding or minimizing scarring. Scarring is
particularly relevant with respect to facial wounds, as well as in cosmetic surgery procedures.
20 Another problem posed by tissue wounds is the fact that many wounds are not straight cuts on a flat
surface. Rather, living bodies are curved and contoured, and wounds are typically irregular. For
example, stellate lacerations contain several V-shaped openings, wherein the tip of the V has already
been compromised. Using a suture or staple through that tissue will only further compromise the
tissue and the blood supply. Thus, even current wound closure techniques suffer drawbacks and
25 there remains a need in the art for wound closure techniques that avoid further traumatization to the
wound tissue.

SUMMARY

The present disclosure is broadly concerned with an article for the atraumatic closure of a wound, atraumatic securement of medical devices, and/or general atraumatic wound care. The article is also useful for the closure of ripped or torn fabric. The article is particularly useful for the treatment, care, and/or closure of open wounds, such as abrasions, burns, incisions, lacerations/tears, punctures, avulsions, and the like. In general, the article comprises a substrate having opposing first and second major surfaces, a plurality of raised thread-receiving or thread-securing anchoring members disposed across the first major surface, and an adhesive adjacent the second major surface.

A system for atraumatic wound care and/or closure is also provided. The system comprises an article useful for atraumatic closure of a wound, as described herein, and a thread.

A method for the atraumatic closure of a tissue wound of a subject is also disclosed. The wound has wound edges, and the method generally comprises providing an article useful for atraumatic closure of a wound, as described herein, and a thread. The article substrate is adhered to the subject's tissue adjacent the wound edges on a first side of the wound and a second side of the wound opposite the first side. The wound edges are then reapproximated. Wound reapproximation is carried out by realigning the disrupted tissue planes by securing the thread to a first anchoring member on the first side of the wound, passing the thread to the second side of the wound opposite the first side and securing the thread to a second anchoring member. This process is repeated along the edges of the wound keeping the thread under tension to pull the tissue from the first side of the wound towards the tissue on the second side of the wound thereby ultimately closing the wound.

The present disclosure is also concerned with a kit for the atraumatic closure of a wound. The kit comprises an article useful for atraumatic closure of a wound, as described herein, and optionally a thread, along with instructions for using the article and a thread to close a wound.

A method for the atraumatic care of a wound of a subject is also disclosed herein. The wound has wound edges, and the method generally comprises providing an article useful for atraumatic care of a wound, as described herein, and a thread. The article substrate is adhered to the subject's tissue adjacent the wound edges on a first side of the wound and a second side of the wound opposite the first side. The wound (which can optionally be packed and/or covered with a skin graft) is covered with a dressing. The dressing is then secured to the wound by securing the

thread to a first anchoring member on the first side of the wound, passing the thread over the dressing to the second side of the wound opposite the first side and securing the thread to a second anchoring member. This process is repeated along the wound edges keeping the thread under sufficient tension to press the dressing towards the wound and frictionally secure it to the wound.
5 Alternatively, the thread can be passed through the dressing for additional stability and securement.

The present disclosure is also concerned with a method for the atraumatic securement of a medical device to a patient's tissue using the inventive system. The method generally comprises providing an article useful for atraumatic care of a wound, as described herein, and a thread. A medical device is inserted into the patient. The article substrate is adhered to the patient's tissue
10 adjacent where the device has been inserted into the patient on a first side of the device and on a second side of the device opposite the first side. A thread is secured to a first anchoring member on the first side of the device and also to the device itself. A thread (same or different) is also secured to a second anchoring member on the second side of the device and to the device itself. The thread on each side of the device is under opposing forces (tension), which stabilizes the device and
15 prevents dislodgement of the device from the patient.

A method of repairing torn or ripped fabric on a stuffed toy is also disclosed herein. The toy comprises an opening in the fabric corresponding to a tear or rip, and has opening edges. The method comprises providing an article useful for repairing torn or ripped fabric, as described herein, and a thread. The article substrate is adhered to the fabric adjacent the edges on a first side of the
20 tear or rip and a second side of the tear or rip opposite the first side. The opening edges are brought together by securing the thread to a first anchoring member on the first side of the tear or rip, passing the thread to the second side of the tear or rip opposite the first side and securing the thread to a second anchoring member. This process is repeated along the opening edges, keeping the thread under tension to pull the fabric from the first side of the tear or rip towards the fabric on the second
25 side of the tear or rip thereby closing the opening and repairing the torn or ripped fabric.

A kit for repairing torn or ripped fabric on a stuffed toy is also described herein. The kit comprises an article useful for repairing torn or ripped fabric, as described herein, and optionally a thread, along with instructions for using the article and a thread to close the opening and repair the fabric.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure (Fig.) 1 is a perspective view of one embodiment of the atraumatic wound care and/or closure system, including thread;

Fig. 2a is an illustration of a stellate laceration;

5 Fig. 2b is a perspective view of one embodiment of the atraumatic wound care and/or closure substrate article severed into pieces and adhered to tissue adjacent the stellate laceration edges;

Fig. 3 is a further perspective view of one embodiment of the atraumatic wound care and/or closure substrate article severed into pieces and adhered to tissue adjacent the edges of a v-shaped wound;

10 Fig. 4a is a top plan view of one embodiment of the atraumatic wound care and/or closure system and a wound closed by passing the thread back and forth across the wound to reapproximate the wound edges;

Fig. 4b is a top plan view of the system illustrating further threading to reinforce the system;

Fig. 5a is a cross-section illustration of an inverted wound edge;

15 Fig. 5b is a cross-section illustration of the wound edges being everted using the system;

Fig. 6 illustrates a further embodiment of the wound care and/or closure article;

Fig. 7a is a perspective view an IV tube inserted in a subject's arm that is secured to the patient using the system;

20 Fig. 7b is a side elevational view of a patient that has been intubated, wherein the tube is secured to the patient using the system;

Fig. 8a illustrates an open wound filled with sterile packing material, with a portion of the packing external to the wound secured to the wound care substrate;

Fig. 8b illustrates a dressing secured over a wound using the system;

25 Fig. 9 illustrates a process of grafting a burn wound and then securing a bolster dressing over the wound using the system; and

Fig. 10 illustrates use of system to secure a pressure dressing over a wound.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The present disclosure is concerned with a wound care and/or closure system for atraumatic care and/or closure of wounds. The term “atraumatic” is used herein to denote that the wound care and/or closure system involves no penetration or piercing of the subject’s tissue, for example with a needle, staples, or other conventional suturing or wound closure techniques. With reference to Fig. 1, the wound care and/or closure system 10 comprises an article substrate 12 and optionally a thread 14. The substrate 12 comprises first and second opposing major surfaces, referred to herein as a front surface 16 and a back surface 18, respectively. The substrate 12 comprises a continuous web or sheet that is flexible in all directions and conformal to underlying surfaces to which the substrate 12 may be applied, such as for example, conformable topical application to human or animal skin. The substrate 12 can be provided in various shapes and sizes, including an elongated sheet, rectangular, circular, triangular, or other shape. For example, the substrate 14 can have a pair of laterally-spaced longitudinal side edges 12a and a pair of laterally spaced transverse ends 12b, defining a substantially rectangular or square shape, as depicted in Fig. 1. In other embodiments, the substrate 12 can have an annular lateral edge defining a substantially circular shape or three lateral edges forming a triangular shape (not shown).

The substrate 12 may be a woven or nonwoven web (also referred to in the medical tape art as a backing), and may be composed of natural, synthetic, or a combination thereof of fibers. Examples of natural fibers include cotton, silk, hemp, flax, and the like. Examples of synthetic fibers include rayon, polyester, acrylic, acrylate, polyolefin, nylon, polyurethane, polyethylene, polypropylene, polyamide, polytetrafluoroethylene, wire mesh, embedded wire clothe (e.g., butterfly tape), and the like. The substrate 12 may also be a laminated or extruded sheet. Foam substrates 12 may also be used. In some embodiments, the substrate materials are preferably biocompatible. In some embodiments, the substrate comprises a woven or nonwoven breathable material. In one or more embodiments, the substrate is preferably substantially free of metals or other rigid materials. It will be appreciated that materials conventionally useful as backing for medical tapes and dressings are particularly suitable for use as the substrate material. Some exemplary tapes include those available from 3M: Kind Removal Silicon Tape, Medipore Cloth Tape, Transpore White Tape, Micropore, Durapore, Blenderm, and the like. In some embodiments, the web itself may be

comprised of multiple layers (i.e., multilayered). The average thickness of the substrate 12 will generally range from about 1 mil (0.001 inch) to about 10 mil (0.010 inch), preferably from about 1 mil to about 5 mil, and more preferably from about 2 mil to about 5 mil. The thickness of the substrate 12 preferably has little variation across the expanse of the substrate. In other words, the thickness of the substrate is preferably substantially uniform as measured between the first and second major surfaces edge-to-edge. A significant advantage of the inventive substrate is that it is severable 12. As used herein, the term “severable” means that the substrate 12 can be cross-sectionally torn or cut into one or more pieces that conform to the shape of the wound opening to be closed. In other words, the term is directed towards cutting through the substrate 12 along a plane that cuts across (and is preferably generally perpendicular to) the plane defined by the front and back surfaces, and does not encompass separating the substrate along the plane defined by the front and back surfaces (for example, pulling apart layers in a multilayered substrate).

The front surface 16 of the substrate 12 comprises a plurality of raised anchoring members 20. The anchoring members 20 are disposed across the surface 16 and generally project away from the front surface 16 such that they are adapted to receive and secure (i.e., anchor) a thread 14 when the system 10 is in use (i.e., when the thread 14 is looped around or threaded through the anchoring members 20). In general, the anchoring members 20 will have respective heights, as measured from the front surface 16 of from about 1 mm to about 20 mm, preferably from about 2 mm to about 10 mm, and more preferably from about 2 mm to about 5 mm. Exemplary anchoring members include generally upright loops or half-loops, eyelets, raised or pleated mesh, hooks, pegs, prongs, nubs, generally upright strands of fiber (e.g., yarn), prone strands of fiber (e.g., yarn), generally upright pleats, or other protrusions that are comprised either of penetrable materials (e.g., rubber, plastic, composite, etc.) or configured to be looped around. For example, in some embodiments, the protrusions have a head and a throat around which the thread is wrapped whereby the head prevents the thread from disengaging the protrusion. The head may be angled to improve anchoring. In other embodiments, the protrusions are penetrable and adapted for passing the thread 14 through the protrusion itself (in one side and out the other), thereby anchoring the thread 14 to the front surface 16. In yet other embodiments, the anchoring member is an aperture, such as a loop, mesh opening, or eyelet, through which the thread 14 can be guided. Loops or half-loops can be formed by securing

an elongated cord (or individual cord pieces) to the front surface 16 at various intervals across the surface to create a plurality of loops or half-loops as depicted in Fig. 1. The anchoring members 20 are each attached or secured to the substrate as appropriate for the particular anchoring member. For example, the anchoring members 20 can be sewn to or through the substrate, glued, tied, and the like.

5 In some embodiments, the anchoring members 20 are integrally formed with the substrate 12. For example, the front surface 16 of the substrate 12 may be pleated, such that the pleats form anchoring members 20, which are formed of the same material as the substrate 12 itself (instead of being a separate piece that is subsequently attached thereto).

Particularly preferred anchoring member 20 configurations help distribute the pulling forces

10 across the expanse of the substrate, such that the pulling force is not localized to any one area of tissue, as occurs with traditional suturing. In one or more embodiments, the anchoring members 20 will be disposed substantially uniformly across the front surface 16, for example as in a grid or matrix pattern. In other words, the density (number) of anchoring members 20 in a first portion of the front surface 16 will be substantially equivalent to the density of anchoring members 20 in a

15 second, different portion of the front surface 16 having the same surface area. In one or more embodiments, the anchoring members 20 will be disposed in individual, separated groupings across the surface, which have spaces therebetween. In one or more embodiments, the anchoring members 20 will be randomly disposed across the surface 16.

It will be appreciated that the front surface 16 can comprise the same type of anchoring

20 member 20 across the surface. Alternatively, more than one type of the above-described anchoring members 20 can be used across the face of the front surface 16. Combinations of the above described materials can also be used to form the anchoring members 20. For example, a plurality of raised anchoring members (e.g., prone strands of yarn, nubs, etc.) can be covered with a substantially conformal layer of mesh. In use, the thread 14 can be guided through an opening in the

25 mesh as well as through the corresponding raised anchoring member and out the other side through a corresponding opening in the mesh. Such an embodiment is depicted in Fig. 6.

The back surface 18 of the substrate 12 comprises an adhesive, which can be in the form of a layer adjacent (i.e., sharing a common interface with) the back surface 18. In one or more embodiments, the adhesive covers substantially the entire surface area of the back surface 18. In one

or more embodiments, the peripheral margins of the back surface 18 remain substantially free of adhesive. Suitable adhesives include pressure sensitive adhesives, as well as heat- or radiation-activated adhesives. It will be appreciated that the appropriate adhesive will depend upon the ultimate intended use of the system 10. For example, if the substrate 12 will be topically applied to skin, the adhesive should have good initial tack and long-term adhesion, and be able to tolerate the presence of moisture without releasing. Pressure-sensitive adhesives generally comprise elastomers that are inherently tacky or include tackifying resins. Exemplary adhesives for use in the invention include rubber elastomers, acrylics, acrylates (e.g., cyanoacrylates), epoxies, silicones, zinc oxides (or other hot melt adhesives), solvent-based adhesives, solvent-free adhesives, photosensitive adhesives, hydrocolloids, hydrogels, polyurethanes, styrene block co-polymers, and the like. In some embodiments, the adhesive is biocompatible. Numerous types of suitable adhesives are known in the art, and are commercially-available from suppliers such as 3M, Loctite (e.g., Duro-Tak), Adhesives Research, Ashland Chemical (e.g., Aroset), Dow (e.g., Robond), Polymer Science (e.g., Sofsil, Neosil), DuPont, and ITW Formex. Particularly preferred adhesives will have strong tissue adhesion properties, and adhesives suitable for use in medical tapes and dressings are preferred in some embodiments of the invention. For example, zinc oxide is currently considered a preferred adhesive for extreme adhesion needs. Low trauma adhesives can also be used.

The substrate 12 can be provided as one or more sheets or strips, each with a releasable liner adjacent the adhesive layer and covering the adhesive to prevent indiscriminate adherence or sticking of the substrate 12 to an undesired surface and/or preserve the adhesive properties of the adhesive layer and/or protect the adhesive layer from attracting dirt, debris, and the like until use. In some embodiments, the substrate 12 can be an elongated strip wound about a spool or dispensing apparatus. In one or more embodiments, the substrate 12 is provided as a large sheet that can be cut down to the necessary size. For example, dimensions such as 30 cm x 30 cm are envisioned.

The thread (aka string, lace, cord, etc.) 14 can be any suitable type of elongated, woven or extruded threading material, such as cotton, nylon, polyester, polypropylene, silk, wire, stainless steel, plastic, cable (e.g., zip ties), and the like. Conventional suturing threads (2 mm or less, preferably 1 mm or less, more preferably 0.5 mm or less in diameter) are suitable for use with the invention (whether or not specifically provided for use with the system). The thread could be coated

or uncoated. A needle (not shown) can be included for guiding the thread 14. A conventional metal needle may be used; however, since the system does not involve piercing the subject's skin, the needle may also be plastic or other suitably rigid material for guiding the thread 14 that is otherwise not sufficiently sharp or rigid to pierce skin tissue. Alternatively, the thread 14 itself can be provided with a substantially rigid end portion (at one or both ends) to facilitate feeding the thread through the anchoring members. The end portion of the thread can be made rigid by any suitable method, including the use of wax, resin, composite, glue, heat shrink, or melting the end portion of the thread. In some embodiments, the substantially rigid portion is a plastic or metal sheath (i.e., aglet) around the end portion of the thread. In some embodiments, the entire length of the thread is of sufficient rigidity to guide the thread through and/or around the anchoring members, such as in the case of wire or some plastic threads.

The inventive substrate 12 is particularly advantageous for the atraumatic closure of wounds, as mentioned above. In one or more embodiments, a substrate 12 according to the invention is provided for use with a subject having a wound 100. The term wound is used herein to refer to injury or disruption to living tissue caused by a cut, blow, or other impact in which the skin is cut or broken, as well as to incisions (such as surgical incisions) into the skin. Thus, the term encompasses incisions, cuts, lacerations, burns, avulsions, necrosis, and the like of the skin (epidermis). Wounds can follow substantially straight lines, but are generally of irregular shape and contour depending upon the location of the body where the wound occurs. Stellate lacerations, which are illustrated in Figs. 2a-2b, pose a particular problem for traditional suturing techniques. In one or more embodiments, a template can be used to determine the shape of the wound 12. For example, tissue paper or a like absorbent material (e.g., copy paper, cellulosic materials) can be pressed gently against the wound whereby the tissue paper absorbs fluid from the wound and provides an approximate shape for the wound. This shape is then transferred to the substrate 12. A particular advantage of the invention is that the substrate 12 can be cut (e.g., with scissors or a knife) to custom fit the wound 100. As shown in Fig. 2b, the severed pieces of the substrate 12 are then placed on (and adhered to) the skin of the subject, adjacent (i.e., sharing a common border with) the wound edges 102. As noted above, the substrate 12 may first need to be released from the releasable liner to expose the adhesive layer. In some embodiments, to enhance adhesion, the tissue

of the subject can be prepared before applying the substrate 12. Suitable skin preparation techniques include wiping the skin adjacent the wound area with isopropyl alcohol (e.g., Preppies Skin Barrier Wipes; Kendall), betadine, chlorhexidine, and the like.

In some embodiments, the system 10 can further comprise an adhesive underlayment or intermediate layer (not shown) to which the substrate 12 is applied, instead of being applied directly to the tissue adjacent the wound. For example, an adhesive-backed substrate (e.g., medical tape) that includes a sufficiently strong adhesive for skin contact is applied to the subject. The substrate 12 is then applied to the adhesive-backed substrate to bond the substrate to the adhesive underlayment, rather than directly to the tissue of the subject. An example of this type of system is Rigid™ strapping tape, which is typically used for athletic immobilization.

Regardless of the embodiment, once the piece or pieces of the substrate 12' are adhered to tissue adjacent to the wound edges 102, as depicted in Fig. 2b and Fig. 3, the inventive system 10 can be used to close the wound by re-approximating the wounded edges 102 together. More specifically, the thread 14 is secured to a first anchoring member 20 on one side of the wound (e.g., by tying it off on one of the anchoring members 20) and then passed to the other side of the wound where it is secured to/threaded through a second anchoring member 20 on the other side of the wound 100 such that tension is created on the side of the first anchoring member 20 pulling the tissue of the subject towards the second anchoring member 20. The back and forth process is repeated using various anchoring members 20 on either side of the wound edges 102 and thread 14 to keep tension on the tissue surrounding the wound 100, until the edges of the wound 102 are lined up and drawn or brought together, as depicted in Fig. 4a. Those skilled in the art will appreciate that one advantage of the invention is that instead of directly pulling the wound edges 102 together, the system 10 instead pulls the adjacent tissue, which in effect, pushes the wound edges 102 together. Thus, there is little to no additional localized trauma to the wound edges 102 in the present wound closure system 10. Additional lacing of the substrate can be performed as depicted in Fig. 4b to further support the tissue and the substrate, for example, to mitigate shearing forces on the wound 100. Those skilled in the art will recognize that the particular pattern of the sutureless method will depend to a certain extent on the shape and location of the wound. It will also be appreciated that the substrate pieces 12' can be "sutured" or laced together using a single continuous thread 14, or

multiple threads 14 that are tied off at various points in the threading process. It will also be appreciated that the thread 14 can be passed through a single anchoring member 20 multiple times during the lacing process, which unlike a conventional suture, allows that single point to be tethered and stabilized from multiple directions, reducing any single directional force/tension on the tissue at that spot. This is particularly important, for example, in the tip of a v-shaped laceration which must be pulled in several different directions to re-approximate the tissue. With traditional suturing or staples, this small section of tissue is ordinarily fragile and prone to tearing and further trauma. Such trauma is avoided by the present invention.

A particular advantage of the present method and device is that it permits eversion of inverted wound edges 102' before drawing those edges together. With reference to Fig. 5a, many wounds involve at least one inverted wound edge 102'. Those skilled in the art will recognize that inverting suture patterns are often associated with delayed healing. Thus, appositional or everting sutures are preferred for many tissue closure as they provide the best anatomical approximation of the disrupted tissue planes. More recently, there has been a recognition of a benefit for a slight eversion on skin closures, because the scar has a tendency to flatten rather than widen. Therefore, as depicted in Fig. 5b, in one or more embodiments, the thread 14 can be secured to an anchoring member 20 proximate to an inverted wound edge 102', and then drawn away from and secured to an anchoring member 20 distal from the wound edge 102' (on that same side of the wound 100) to evert the edge 102'. This procedure can be repeated as necessary or desired on all edges 102 of the wound 100 before subsequently drawing the edges 102 together. Alternatively, if it is noticed that an edge of the wound 102 has become inverted during the process of lacing together the substrate pieces 12', this same procedure can be used to evert the wound edge 102' from the closed wound 100'.

A further advantage of the system and method is that if the approximation of the tissue during wound closure is not satisfactory, the thread 14 can simply be cut and removed from the anchoring members 20 and the wound closure can be re-done without creating any additional trauma to the subject. This is particularly advantageous in cosmetic incision closure where scars and scarring should be minimized as much as possible. It is not practical to remove and re-suture using traditional suturing or staple gun techniques because of the added trauma caused to the subject and the tissue during such a process. Likewise, most wound closure adhesives simply cannot be

practically removed from the wound once used to close the tissue. A further advantage is that because this technique is sutureless, removable, and “re-doable,” it can be used by unskilled persons to close a wound in emergency or short-term situations and mediate further trauma and/or blood loss until the subject can be attended to by a medical practitioner. As noted above, the medical practitioner can then remove the threads and re-close the wound, if necessary. This would be particularly advantageous for home first aid kits, hikers, as well as for soldiers on the battle field.

The atraumatic wound closure system also reduces or even completely eliminates the need for sedation and/or anesthesia, which can be an important factor in treating pediatric and/or veterinary patients. Moreover, the wound itself remains visible for evaluation of infection allowing for better local wound care and healing. The lack of sutures, staples, or other foreign bodies piercing the skin also reduces the risk of infection as well as promotes blood flow (and accordingly healing). In addition, if the wound does become infected, the present method of wound closure allows for easier egress of purulent fluid and material from the wound.

A kit for the atraumatic closure of wound tissue is also provided herein. The kit comprises one or more substrates as described above, optionally thread for lacing together the substrates, and instructions for using the substrate and thread to close a wound. Template material can also be included in the kit, along with scissors or other devices for cutting the substrate to fit the wound shape. Additional conventional first-aid components, such as disinfectant, antibiotic ointment, alcohol, betadine, chlorhexidine, and the like can also be included in the kit.

It will be appreciated that the wound closure system described herein may be used, in one or more embodiments, in addition to traditional wound closure techniques to further stabilize and support the tissue adjacent to the wound. The system could be used before traditional wound closure to facilitate pushing the disrupted tissue planes together for traditional suturing, etc. Alternatively, the system could be applied after traditional wound closure to relieve pressure or tension on the wound edges due to the conventional sutures, staples, etc. used to close the wound. In other embodiments, the system is used entirely in lieu of conventional wound closure techniques. Thus, the tissue of the subject is not pierced (by suture, staple, etc.) before, during, or after the process of reapproximating the wound edges using the inventive system.

It will also be appreciated that, instead of securing wound edges to close a wound, the present

system could also be used to secure medical devices, packing, dressings, and the like to a patient without piercing the subject's tissue. For example, in one or more embodiments, the invention is also concerned with atraumatic securement of a medical device to a patient. The method comprises inserting a medical device 200 into the patient and securing the device to the patient's tissue using the wound care system 10. In particular, one or more pieces of the substrate 12' are adhered to tissue on either side of the device 200, as depicted in Figs. 7a and b. The device 200 is then secured to the substrate 12' using the thread 14, which is secured between any suitable attachment points 202 on the device 200 and the anchoring members 20. For example, the thread 14 can be secured to a first anchoring member 20 on one side of the device 200 (e.g., by tying it off on one of the anchoring members 20) and then passed to an attachment point 202 on the device before being passed to the other side of the device 200 where it is secured to/threaded through a second anchoring member 20 on the other side of the device 200 such that tension is created on both sides of the device 200 to hold it in place. The back and forth process can be repeated using various anchoring members 20 on either side of the device 200 until sufficiently secured in place to avoid being dislodged. It will be appreciated that the device 200 can be secured using a single continuous thread 14, or multiple threads 14 that are tied off or fastened at various points in the threading process. It will also be appreciated that the thread 14 can be passed through a single anchoring member 20 multiple times during the lacing process, which unlike a conventional suture, allows that single point to be tethered and stabilized from multiple directions, reducing any single directional force/tension on the tissue at that spot. Those skilled in the art will also appreciate that one advantage of the invention is that there is little to no additional localized trauma to the patient to secure the device, which can be easily removed by cutting or removing the thread 14. The method would be suitable for securing various devices to a patient, include tracheal tubes, nasogastric tubes, ventilators, drains, catheters, IVs, central lines, arterial lines, and the like.

In one or more embodiments, the system 10 can be used to secure wound packing and dressings. This is particularly advantageous for packings that need to be removed and replaced daily or multiple times per day, and avoids the repeat trauma to the patient that is encountered by repeated application and removal of dressing tape and other similar coverings. One or more pieces of the substrate 12' can be adhered to tissue adjacent the wound 100 which has been packed with suitable

packing material (e.g., sterile gauze, etc.) 200. Typically, the “tail” of the packing material 200 remains outside of the wound to facilitate removal of the packing. In the present system 10, the tail can advantageously be secured to the substrate 12’ using the thread 14. A dressing 204 is then placed over the packed wound, and the system 10 is used to secure the dressing over the wound using the thread 14 and the anchoring members 20, as depicted in Figs. 8a and 8b. The wound care system 10 can also be used to secure bolster dressings or other like dressings in a similar manner, as depicted in Fig. 9, which are often used with burn wounds and skin grafts, and are typically sutured to the skin, again creating additional trauma on the patient. In one or more embodiments, the system 10 can also be used as part of a pressure dressing to stop bleeding and temporarily stabilize the patient until definitive care can be obtained, as depicted in Fig. 10. Thus, the system is suitable for use with various wound dressings, such as cotton 4x4, and the like. It will be appreciated that in each of the foregoing wound care methods, the system 10 has an additional benefit of significance to patient care. After the applicable dressing, packing, or the like is removed from the patient at the appropriate stage of healing (i.e., by cutting or removing the thread 14 to permit removal of the care device), the substrate can remain in place adjacent the wound. Using thread, the system can then be used to subsequently close the wound for permanent healing. Again, the system provides a significant advantage in that the tissue adjacent the wound does not have to undergo additional trauma from the application and/or removal of tape, adhesives, and the like, to remove the dressings, packing, etc., and does not have to be pierced or punctured using staples or suture to subsequently close the wound. This provides an important advancement in the state of the art of wound care and closure.

The present substrate also finds usefulness as a novelty item. For example, the substrate described above can also be used to repair or close ripped seams or other tears in stuffed animals. It will be appreciated that the substrate 12 will comprise an adhesive layer suitable for bonding to a fabric and/or synthetic “fur” surface. Thus, considerations as noted above with respect to biocompatibility will not be as much of a factor in such an embodiment; however, the method of use remains substantially the same as that described above for wound closure. The substrate could be provided, for instance, as part of a teddy bear repair kit. The thread would be provided generally without a needle, such that the kit would be suitable for use by children to repair their stuffed

animals. The kit would also be suitable for use as part of a children's doctor set for pretend suturing of "patients."

Additional advantages of the various embodiments of the disclosure will be apparent to those skilled in the art upon review of the disclosure herein and the working examples below. It will be appreciated that the various embodiments described herein are not necessarily mutually exclusive unless otherwise indicated herein. For example, a feature described or depicted in one embodiment may also be included in other embodiments, but is not necessarily included. Thus, the present invention encompasses a variety of combinations and/or integrations of the specific embodiments described herein.

In addition, while the drawings illustrate, and the specification describes, certain preferred embodiments, it is to be understood that such disclosure is by way of example only. Embodiments are described herein with reference to illustrations of idealized embodiments of the present invention. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. There is no intent to limit the principles of the present embodiments to the particular disclosed embodiments. For example, in the drawings, the size and relative sizes of components may be exaggerated for clarity. In addition, embodiments should not be construed as limited to the particular shapes of regions illustrated herein but are to include deviations in shapes that result, for example, from manufacturing.

As used herein, the phrase "and/or," when used in a list of two or more items, means that any one of the listed items can be employed by itself or any combination of two or more of the listed items can be employed. For example, if a composition is described as containing or excluding components A, B, and/or C, the composition can contain or exclude A alone; B alone; C alone; A and B in combination; A and C in combination; B and C in combination; or A, B, and C in combination. The term "adjacent" means adjoining, abutting (touching) so as to have a common interface/surface or border. In the case of layers, a layer is considered to be adjacent when it shares a common interface with the adjacent structure. With respect to wound tissue, tissue that is adjacent to the wound refers to tissue proximate to the wound but not involving the wound edges (i.e., tissue spaced slightly from the wound edges themselves).

The present description also uses numerical ranges to quantify certain parameters relating to

various embodiments of the invention. It should be understood that when numerical ranges are provided, such ranges are to be construed as providing literal support for claim limitations that only recite the lower value of the range as well as claim limitations that only recite the upper value of the range. For example, a disclosed numerical range of about 10 to about 100 provides literal support
5 for a claim reciting “greater than about 10” (with no upper bounds) and a claim reciting “less than about 100” (with no lower bounds).

WHAT IS CLAIMED:

1. An article for the atraumatic care and/or closure of a wound or closure of ripped or torn fabric, said article comprising:

5 a substrate having opposing first and second major surfaces;
a plurality of raised anchoring members disposed across said first major surface; and
an adhesive adjacent said second major surface.

2. The article of claim 1, wherein said substrate is a continuous, flexible web.

10 3. The article of claim 1, wherein said substrate comprises a pair of laterally spaced longitudinal side edges and a pair of laterally spaced transverse ends.

15 4. The article of claim 1, wherein said substrate has an average thickness of from about 1 mil to about 10 mils.

5. The article of claim 1, wherein said substrate is severable.

20 6. The article of claim 1, wherein said substrate comprises a woven or nonwoven web of cotton, silk, hemp, flax, rayon, polyester, acrylic, acrylate, polyolefin, nylon, polyurethane, polyethylene, polyester, wire, and/or embedded wire clothe.

25 7. The article of claim 1, wherein said anchoring members are selected from the group consisting of loops, half-loops, eyelets, mesh, hooks, pegs, prongs, nubs, generally upright strands of fiber, prone strands of fiber, pleats, and combinations thereof.

8. The article of claim 1, wherein said anchoring members are disposed substantially uniformly across said first major surface.

9. The article of claim 1, wherein said anchoring members project away from said first major surface.

10. The article of claim 1, wherein said anchoring members have respective heights, as measured from said first major surface, of from about 1 mm to about 20 mm.

11. The article of claim 1, wherein said adhesive is in the form of a layer adjacent said second major surface.

12. The article of claim 1, wherein said adhesive is selected from the group consisting of pressure sensitive adhesives, heat-activated adhesives, and radiation-activated adhesives.

13. The article of claim 1, wherein said adhesive comprises rubber elastomers, acrylics, silicones, zinc oxides, or a combination thereof.

14. The article of claim 1, further comprising a releasable liner adjacent to and covering said adhesive.

15. A system for atraumatic wound care and/or closure comprising:
an article according to any one of claims 1-14; and
a thread.

16. The system of claim 15, wherein said thread comprises nylon, polyester, polypropylene, silk, wire, plastic, cable, or a combination thereof.

17. The system of claim 15, wherein said thread comprises a substantially rigid end portion.

18. The system of claim 15, further comprising a needle configured to guide said thread.

19. A method for the atraumatic closure of a tissue wound of a subject, said wound having wound edges, said method comprising:

providing an article according to any one of claims 1-14 and a thread;

adhering said article substrate to said tissue adjacent said wound edges on a first side of said
5 wound and on a second side of said wound opposite said first side; and

reapproximating said wound edges by:

securing said thread to a first anchoring member on said first side of said wound,

passing said thread to said second side of said wound opposite said first side and

securing said thread to a second anchoring member, and

10 repeating said securing and said passing along the wound edges, said thread being
under tension and pulling said tissue from said first side of said wound
towards said tissue on said second side of said wound thereby closing said
wound.

15 20. The method of claim 19, further comprising:

determining the shape of the edges of said wound; and

severing said substrate into one or more pieces to conform to said shape, prior to adhering
said pieces to tissue adjacent said wound edges.

20 21. The method of claim 20, wherein said determining comprises:

placing a piece of tissue paper over said wound, wherein fluid from said wound is absorbed
by said tissue paper providing a template of said shape.

22. The method of claim 19, further comprising:

25 preparing the tissue of said subject adjacent said wound by cleaning said tissue with
isopropyl alcohol.

23. The method of claim 19, wherein the tissue of said subject is not pierced during said
reapproximating.

24. The method of claim 19, wherein at least one of said wound edges is inverted, further comprising

securing a thread to an anchoring member proximate to said inverted wound edge;

drawing said thread away from said wound edge; and

5 securing said thread to an anchoring member distal from said wound edge thereby lifting said inverted wound edge to yield an everted wound edge.

25. The method of claim 24, wherein said inverted wound edge is everted prior to said reapproximating.

10 26. The method of claim 24, wherein said inverted wound edge is everted after said reapproximating.

15 27. The method of claim 19, wherein said securing comprises tying said thread into a knot around said respective anchoring members.

28. A kit for the atraumatic closure of a wound, said kit comprising:

an article according to any one of claims 1-14;

optionally a thread; and

20 instructions for using said article and a thread to close a wound.

29. The kit of claim 28, further comprising a template for determining the shape of said wound.

25 30. The kit of claim 28, further comprising a device for cutting said article.

31. The kit of claim 28, further comprising a first-aid component selected from the group consisting of disinfectant, isopropyl alcohol, antibiotic ointment, betadine, chlorhexidine, and combinations thereof.

32. A method for the atraumatic care of a wound of a subject, said wound having wound edges, said method comprising:

providing an article according to any one of claims 1-14 and a thread;

adhering said article substrate to said tissue adjacent said wound edges on a first side of said wound and on a second side of said wound opposite said first side;

covering said wound with a dressing; and

securing said dressing to said wound by:

securing said thread to a first anchoring member on said first side of said wound,

passing said thread over said dressing to said second side of said wound opposite

said first side and securing said thread to a second anchoring member, and

repeating said securing and said passing over said dressing along the wound edges,

said thread being under tension and pressing said dressing towards said

wound, thereby securing said dressing to said wound.

33. The method of claim 32, wherein said securing further comprises threading said thread through at least a portion of said dressing during said passing of said thread over said dressing.

34. The method of claim 32, wherein said wound is covered with a skin graft prior to covering said wound with dressing.

35. The method of claim 32, wherein said wound is filled with sterile packing prior to covering said wound with dressing.

36. The method of claim 35, further comprising securing at least a portion of said packing to said article outside of said wound by securing a thread to an anchoring member on said substrate and attaching said thread to said portion of said packing outside of said wound.

37. The method of claim 35, further comprising removing said dressing by cutting said thread; and removing said packing from said wound.

38. The method of claim 37, further comprising:

5 re-packing said wound with a sterile packing;

covering said wound with a dressing; and

securing said dressing to said wound by:

securing a thread to a first anchoring member on said first side of said wound,

passing said thread over said dressing to said second side of said wound opposite

10 said first side and securing said thread to a second anchoring member, and

repeating said securing and said passing over said dressing along the wound edges,

said thread being under tension and pressing said dressing towards said

wound, thereby securing said dressing to said wound.

15 39. The method of claim 37, further comprising closing said wound by reapproximating said wound edges by:

securing a thread to a first anchoring member on said first side of said wound,

passing said thread to said second side of said wound opposite said first side and securing

said thread to a second anchoring member, and

20 repeating said securing and said passing along the wound edges, said thread being under

tension and pulling said tissue from said first side of said wound towards said tissue

on said second side of said wound thereby closing said wound.

40. A method for the atraumatic securement of a medical device to a patient's tissue, said method comprising:

providing an article according to any one of claims 1-14 and a thread;

inserting a medical device into said patient;

5 adhering said article substrate to said tissue adjacent where said device is inserted into said patient on a first side of said device and on a second side of said device opposite said first side;

securing a thread to a first anchoring member on said first side of said device and to said device; and

10 securing a thread to a second anchoring member on said second side of said device and to said device, wherein said thread on each side of said device is under tension to stabilize and prevent dislodgement of said device from said patient.

41. The method of claim 40, wherein said device is selected from the group consisting of tracheal tubes, nasogastric tubes, ventilators, drains, catheters, IVs, central lines, arterial lines, and combinations thereof.

42. A method of repairing torn or ripped fabric on a stuffed toy, said toy comprising an opening in said fabric corresponding to a tear or rip, said opening having opening edges, said method comprising:

providing an article according to any one of claims 1-14 and a thread;

adhering said article substrate to said fabric adjacent said edges on a first side of said tear or rip and a second side of said tear or rip opposite said first side; and

reapproximating said opening edges by:


25 securing said thread to a first anchoring member on said first side of said tear or rip, passing said thread to said second side of said tear or rip opposite said first side and



securing said thread to a second anchoring member, and



repeating said securing and said passing along the opening edges, said thread being under tension and pulling said fabric from said first side of said tear or rip



towards said fabric on said second side of said tear or rip thereby closing said opening and repairing said torn or ripped fabric.



43. A kit for repairing torn or ripped fabric on a stuffed toy, said kit comprising:
an article according to any one of claims 1-14;
optionally a thread; and
instructions for using the article and a thread to close the opening and repair the fabric.



*Fig. 1*



*Fig. 2a**Fig. 2b*


*Fig. 3**Fig. 4a*

*Fig. 4b**Fig. 5a*

*Fig. 5b**Fig. 6*



*Fig. 8a**Fig. 8b*

*Fig. 9*




Fig. 10

A. CLASSIFICATION OF SUBJECT MATTER**A61B 17/03(2006.01)i, A61F 13/02(2006.01)i, A61B 17/04(2006.01)i**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B 17/03; A61B 17/00; A61B 17/04; A61B 17/08; A61F 13/02

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models

Japanese utility models and applications for utility models

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS(KIPO internal) & Keywords: fabric, anchor, sutureless, adhesive, wound closure

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	Instructions for use of ABRA adhesive skin closure set (CANICA) 12 November 2009 See pages 1, 2.	1-18, 28-31, 42, 43
A	US 5176703 A (PETERSON, M. L.) 05 January 1993 See abstract; claims 1-9; Figures 1-4.	1-18, 28-31, 42, 43
A	US 2008-0114396 A1 (CORY, J. M.) 15 May 2008 See the whole document.	1-18, 28-31, 42, 43
A	US 2007-0088339 A1 (LUCETTI, P. C.) 19 April 2007 See the whole document.	1-18, 28-31, 42, 43
A	US 2008-0228220 A1 (WEISER, L. P.) 18 September 2008 See the whole document.	1-18, 28-31, 42, 43



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

07 October 2013 (07.10.2013)

Date of mailing of the international search report

08 October 2013 (08.10.2013)

Name and mailing address of the ISA/KR

Korean Intellectual Property Office
189 Cheongsa-ro, Seo-gu, Daejeon Metropolitan City,
302-701, Republic of Korea

Facsimile No. +82-42-472-7140

Authorized officer

HAN In Ho

Telephone No. +82-42-481-3362



INTERNATIONAL SEARCH REPORTInternational application No.
PCT/US2013/031502**Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)**

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 19-27,32-41
because they relate to subject matter not required to be searched by this Authority, namely:
Claims 19-27,32-41 pertain to a method for treatment of the human body and thus relate to a subject matter which this International Searching Authority is not required, under Article 17(2)(a)(i) of the PCT and Rule 39.1(iv) of the Regulation under the PCT, to search.
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2013/031502

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5176703 A	05/01/1993	GB 2275423 A US 5534010 A WO 93-08748 A1	31/08/1994 09/07/1996 13/05/1993
US 2008-0114396 A1	15/05/2008	EP 2081500 A2 WO 2008-060532 A2 WO 2008-060532 A3	29/07/2009 22/05/2008 17/07/2008
US 2007-0088339 A1	19/04/2007	AR 055498 A1 US 7594914 B2	22/08/2007 29/09/2009
US 2008-0228220 A1	18/09/2008	AU 2008-335146 A1 CA 2499866 A1 CN 101938944 A CN 101938944 B US 2004-0204740 A1 US 2004-0243040 A1 US 2008-0228219 A1 US 7981136 B2 WO 2006-014323 A1 WO 2009-076435 A2 WO 2009-076435 A3	18/06/2009 02/01/2006 05/01/2011 21/11/2012 14/10/2004 02/12/2004 18/09/2008 19/07/2011 09/02/2006 18/06/2009 27/08/2009