



US008424789B2

(12) **United States Patent**  
**Ramun**

(10) **Patent No.:** **US 8,424,789 B2**  
(45) **Date of Patent:** **Apr. 23, 2013**

(54) **DEMOLITION TOOL UNIT AND METHOD OF DESIGNING AND FORMING A DEMOLITION TOOL UNIT**

2,980,409 A 4/1961 Goodrich  
3,148,787 A 9/1964 Clark et al.  
3,211,065 A 10/1965 Hunger et al.  
3,227,297 A 1/1966 Kampert et al.  
3,260,387 A 7/1966 Garrett

(Continued)

(76) Inventor: **John R. Ramun**, Poland, OH (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 204 days.

FOREIGN PATENT DOCUMENTS

DE 4208245 A1 9/1993  
DE 29715490 U1 1/1998

(Continued)

(21) Appl. No.: **12/958,050**

(22) Filed: **Dec. 1, 2010**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2011/0068205 A1 Mar. 24, 2011

Maturana et al., "A Finite Element Based Tool to Automate Optimal Design Process", Proceedings of the 1994 Summer Computer Simulation Conference, 1994, p. 63-66.

(Continued)

**Related U.S. Application Data**

(60) Continuation of application No. 11/520,510, filed on Sep. 13, 2006, now abandoned, which is a division of application No. 11/101,265, filed on Apr. 7, 2005, now Pat. No. 7,108,211, which is a division of application No. 10/089,481, filed as application No. PCT/US00/28367 on Oct. 13, 2000, now Pat. No. 6,994,284.

*Primary Examiner* — Mark Rosenbaum  
(74) *Attorney, Agent, or Firm* — The Webb Law Firm

(60) Provisional application No. 60/159,869, filed on Oct. 15, 1999, provisional application No. 60/195,797, filed on Apr. 10, 2000.

(57) **ABSTRACT**

A multiple tool attachment system is adapted to be attached to demolition equipment. The system includes a universal body attached to the demolition equipment. A series of tools is independently attachable to the universal body. The universal body includes a guide slot extending longitudinally along the universal body. Each tool generally includes a pair of pivotable jaws adapted to be pivotably attached to the universal body with at least one linkage extending from the universal body and attachable to each jaw of the tool. A slide member is received within the guide slot, with each linkage attached to the slide member, and a piston cylinder arrangement is attached to the universal body and coupled to the slide member for moving the slide member and the jaws. The multiple tool attachment system is provided with quick change features and is designed to optimize the cutting characteristics throughout the movement cycle.

(51) **Int. Cl.**  
**B02C 1/06** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **241/101.73**

(58) **Field of Classification Search** ..... 241/101.72,  
241/101.73, 266-269


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,332,561 A 10/1943 Drott  
2,455,474 A 12/1948 Drott et al.  
2,903,803 A 9/1959 Austin

**6 Claims, 33 Drawing Sheets**



U.S. PATENT DOCUMENTS

3,422,975 A 1/1969 Crisp  
 3,485,396 A 12/1969 Lundquist  
 4,023,848 A 5/1977 Bennett  
 4,106,646 A 8/1978 Weisgerber  
 4,196,862 A 4/1980 Tagawa  
 4,283,866 A 8/1981 Ogawa  
 4,403,431 A 9/1983 Ramun et al.  
 4,413,945 A 11/1983 LaBounty  
 4,670,983 A 6/1987 Ramun et al.  
 4,686,767 A 8/1987 Ramun et al.  
 4,761,113 A 8/1988 Smith et al.  
 4,771,540 A 9/1988 LaBounty  
 4,799,852 A 1/1989 Ramun  
 4,838,493 A 6/1989 LaBounty  
 4,890,798 A 1/1990 Tagawa et al.  
 4,893,493 A 1/1990 Jacques et al.  
 4,897,921 A 2/1990 Ramun  
 4,903,408 A 2/1990 Tagawa et al.  
 4,951,886 A 8/1990 Berto  
 5,044,568 A 9/1991 Shigemizu  
 5,044,569 A 9/1991 LaBounty et al.  
 5,060,378 A 10/1991 LaBounty et al.  
 5,062,227 A 11/1991 De Gier et al.  
 5,125,788 A 6/1992 Stenger  
 5,199,658 A 4/1993 Bartels et al.  
 5,243,761 A 9/1993 Sullivan et al.  
 5,359,775 A 11/1994 Morikawa et al.  
 5,361,999 A 11/1994 Sakato et al.  
 5,474,242 A 12/1995 Rafn  
 5,480,100 A 1/1996 Tagawa et al.  
 5,546,683 A 8/1996 Clark  
 RE35,432 E 1/1997 LaBounty et al.

5,626,301 A 5/1997 Morikawa et al.  
 5,628,611 A 5/1997 Ito et al.  
 5,636,802 A 6/1997 Tagawa  
 5,645,236 A 7/1997 Sugiura et al.  
 5,671,892 A 9/1997 Morikawa et al.  
 5,738,289 A 4/1998 Tagawa  
 5,797,461 A 8/1998 Noble  
 5,926,958 A 7/1999 Ramun  
 5,940,971 A 8/1999 Ramun  
 6,061,911 A 5/2000 LaBounty et al.  
 6,092,290 A 7/2000 Vogelsanger  
 6,655,054 B1 12/2003 Ward  
 6,662,610 B1 12/2003 Sekita et al.  
 6,994,284 B1 2/2006 Ramun  
 7,032,335 B2 4/2006 Short  
 7,108,211 B2 9/2006 Ramun  
 7,284,718 B2 10/2007 Christenson  
 7,354,010 B2 4/2008 Ramun et al.

FOREIGN PATENT DOCUMENTS

FR 2822482 A1 9/2002  
 GB 2243358 A 10/1991  
 NL 7904335 12/1980  
 NL 9101437 3/1993  
 WO 03021047 A1 3/2003  
 WO 2010099980 A1 9/2010

OTHER PUBLICATIONS

Hale Idex Corporation, "HP Combo Tool Instruction Manual", 2004, 4 pages.  
 Loeffelholz, "CAD/CAM comes of age", Financial World, Oct. 18, 1988, two pages, vol. 157, No. 22. (Abstract Only).




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11a




FIG. 11b




FIG. 11c




FIG. 11d

VIEW A-A




PLATE SHEAR

FIG. 12





FIG. 13



CONCRETE CRACKER

FIG. 14





FIG. 15



CONCRETE PULVERIZER

FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20





FIG. 21



IRON/RAIL CRACKER

FIG. 22




FIG. 23






FIG. 26




FIG. 27a




FIG. 27b




FIG. 29




FIG. 28




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41

FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48






FIG. 49





**DEMOLITION TOOL UNIT AND METHOD  
OF DESIGNING AND FORMING A  
DEMOLITION TOOL UNIT**

CROSS REFERENCE TO RELATED  
APPLICATIONS

This application is a continuation of U.S. application Ser. No. 11/520,510, which is a division of U.S. application Ser. No. 11/101,265, filed Apr. 7, 2005, now U.S. Pat. No. 7,108,211, issued on Sep. 19, 2006, which is a division of U.S. application Ser. No. 10/089,481, now U.S. Pat. No. 6,994,284, issued on Feb. 7, 2006, which is the national phase of International Application No. PCT/US00/028367, filed Oct. 13, 2000, designating inter cilia, the United States, which claimed the benefit of U.S. Provisional Application Nos. 60/159,869, filed Oct. 15, 1999, and 60/195,797, filed Apr. 10, 2000.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a tool attachment system for construction or demolition equipment which is adapted to be attached to a backhoe for attaching multiple tools, such as a heavy-duty metal cutting shear, a plate shear, a concrete crusher, a grapple or the like. More particularly, the present invention relates to a multiple tool attachment system for attaching tools having plural movable jaws.

2. Description of Related Art

The present application refers to demolition equipment; however, the equipment is also referred to as construction equipment, scrap handling equipment and the like. The description of demolition equipment or construction equipment is not intended to be restrictive of the equipment being referenced. Demolition equipment, such as heavy-duty metal cutting shears, grapples and concrete crushers, has been mounted on backhoes powered by hydraulic cylinders for a variety of jobs in the demolition field. This equipment provides for the efficient cutting and handling of scrap. For example, in the dismantling of an industrial building, metal scrap in the form of various diameter pipes, structural I-beams, channels, angles, sheet metal plates and the like, must be efficiently severed and handled by heavy-duty metal shears. Such shears can also be utilized for reducing automobiles, truck frames, railroad cars and the like. The shears must be able to move and cut the metal scrap pieces regardless of the size or shape of the individual scrap pieces and without any significant damage to the shears. In the demolition of an industrial building, concrete crushing devices, such as a concrete pulverizer or concrete crackers, are also used to reduce the structure to manageable components which can be easily handled and removed from the site. Wood shears and plate shears also represent specialized cutting devices useful in particular demolition or debris removal situations depending on the type of scrap. Also, a grapple is often utilized where handling of debris or work pieces is a primary function of the equipment. Historically, all of these pieces of equipment represent distinct tools having significant independent capital cost. Consequently, the demolition industry has tended to develop one type of tool that can have the greatest possible utility and application.

With regard to metal shears, one type of known shear is a shear having a fixed blade and a movable blade pivoted thereto. The movable blade is pivoted by hydraulic cylinder to provide a shearing action between the blades for severing the work pieces. Examples of this type of shear can be found in

my prior U.S. Pat. Nos. 4,403,431; 4,670,983; 4,897,921; 5,926,958; and 5,940,971 which are incorporated herein by reference.

The prior art has also developed a variety of demolition tools utilizing a plurality of movable jaws. U.S. Reissue Pat. No. 35,432 and U.S. Pat. No. 5,060,378 both disclose heavy-duty metal cutting shears having a body and a pair of movable jaws mounted to the frame for pivoting about a common point. Each jaw includes a plurality of cutting inserts in shearing relation with the inserts on the other jaw, with one jaw forming a slot for maintaining the inserts in shearing relation to each other throughout the cutting movement. Each jaw is operated by an independent hydraulic cylinder. The jaw configuration provides a hook-shaped structure with one of the jaws having a cutting or piercing tip at the end thereof. However, these patents do not optimize the jaw structure for the purpose of cutting. Additionally, the independent cylinders increase the cost and prevent a compact shear design.

U.S. Pat. No. 5,359,775 discloses a metal cutting shear with a pair of movable jaws pivotally mounted to a frame with a pair of jaws operated off of a common piston extending between the jaws.

U.S. Pat. Nos. 4,838,493; 4,890,798; 5,044,569; 5,636,802; and 5,738,289 all disclose a variety of concrete crushers having a plurality of movable jaws operated through hydraulic cylinders. U.S. Pat. Nos. 4,903,408; 5,044,568; 5,199,658; 5,243,761; and 5,626,301 also disclose a variety of demolition equipment having a plurality of movable jaws.

The prior art does not provide a system for easily changing tools or a system which allows complete separate tools to efficiently share a common structure. Further, the prior art fails to optimize the jaw structure utilized in the individual tools, such as metal cutting shears, to maximize power and efficiency. Additionally, the prior art provides a complex arrangement for rotations of the tool and jaws without sufficient protection for any hydraulic cylinder powering the working jaws.

SUMMARY OF THE INVENTION

The object of the present invention is to overcome the aforementioned drawbacks of the prior art. It is a further object of the present invention to provide a multiple tool attachment system which is easily converted between a plurality of distinct tools. A further object of the present invention is to provide a demolition tool having a plurality of movable jaws which optimizes the jaw structure. A further object of the present invention is to provide a demolition tool which optimizes the ratio between the jaw and the jaw power structure to provide optimum power performance throughout the blade movement cycle. A further object of the present invention is to provide a demolition tool system that simplifies the construction of the tool system, including rotating tools. A further object of the present invention is to provide a method for designing a demolition tool and tool system.

The objects of the present invention are achieved by a multiple tool attachment system according to the present invention. The attachment system is adapted to be attached to demolition equipment, also referred to as construction equipment, scrap handling equipment and the like. The system includes a universal body attachable to the demolition equipment, a hydraulic cylinder attached to the universal body, a pair of linkages adapted to be coupled with the hydraulic cylinder, and a plurality of demolition tool units each selectively, removably attachable to the body and the hydraulic cylinder.

Each tool unit includes a pair of pivotable blades or jaws adapted to be pivotally connected to the body and to the pair of linkages. In one embodiment, the tool unit includes a pair of movable blades pivoted together with a common pivot pin connecting the blades together, and a bridge housing coupled to the pivot pin providing a quick release system for attaching the tool set to the body.

In one embodiment of the invention, the universal body includes a guide slot extending longitudinally along the body. A slide member is received within the guide slot, with each linkage attached to the slide member and the piston cylinder arrangement attached to the body and coupled to the slide member for moving the slide member and the blades. The linkages may be attached to the slide member at a common point. Additionally, the linkages may have a common sleeve adapted to hold the linkages together when decoupled from the slide member. The universal body may be provided with pivotable sides and/or with side access panels to assist in repair, maintenance and tool changing.

The demolition equipment is provided with quick change features and is designed to optimize the cutting characteristics throughout the movement cycle. Specifically, the lengths of the linkages and the lengths of the relevant lever arms for each blade of a tool set may be set to be substantially equal or varied. In general, these jaw and link dimensions may be selected for a desired positioning of the power curve of the jaw to optimize the performance throughout the intended operating conditions. The jaw and link dimensions may be selected to shape or regulate the power curve in a desired manner. For example, the relative dimensions of the jaw sets may be selected to provide an increasing power curve throughout the blade closing motion or, alternatively, the relative dimensions of the jaw sets may be selected to have the power curve peak slightly before the end of the blade closing motion. In one shear of the present invention, the jaw depth and maximum jaw opening are also the same as the lever arm and linkage lengths. Additionally, the jaw design of the shear of the present invention is designed to perform the majority of the heavy cutting at the throat of the plural moving jaws. The concepts of the present invention can be incorporated into a guided single moving blade demolition tool.

These and other advantages of the present invention will be clarified in the description of the preferred embodiments wherein like reference numerals represent like elements throughout.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view illustrating a heavy-duty shear according to the present invention incorporated into a universal body for a construction tool system according to the present invention;

FIG. 2 is a side view of a shear similar to the shear of FIG. 1 without a rotator in the body;

FIG. 3 is a side view of the shear in FIG. 1 with an outer side panel of the body removed;

FIG. 4 is a sectional view taken along line A-A of FIG. 3;

FIG. 5 is a plan view of the shear in FIG. 1;

FIG. 6 is an enlarged plan view, partially in section, of a slide member of the universal body according to the present invention;

FIG. 7 is a side view of the slide member illustrated in FIG. 6;

FIG. 8 is a plan view, partially in section, of a main shaft assembly of a tool unit mounted on the universal body of the construction tool system shown in FIG. 1;

FIGS. 9-11a sequentially illustrate the disassembly of a tool unit mounted on the universal body of the construction tool system shown in FIG. 1;

FIG. 11b is a front view of a modified bridge of the quick change system of the present invention;

FIG. 11c is an exploded view of the quick change system used with the modified bridge of FIG. 11b;

FIG. 11d is a side view of a keeper pin used in the quick change system of FIGS. 11b-c;

FIG. 12 is a side view of a plate shear according to the present invention incorporated into the universal body of FIG. 1;

FIG. 13 is a front view of the plate shear illustrated in FIG. 12;

FIG. 14 is a side view of a concrete cracker according to the present invention incorporated into the universal body of FIG. 1;

FIG. 15 is a front view of the concrete cracker illustrated in FIG. 14;

FIG. 16 is a side view of a concrete pulverizer according to the present invention incorporated into the universal body of FIG. 1;

FIG. 17 is a front view of the concrete pulverizer illustrated in FIG. 16;

FIG. 18 is a side view of a wood shear according to the present invention incorporated into the universal body of FIG. 1;

FIG. 19 is a front view of the wood shear illustrated in FIG. 18;

FIG. 20 is a side view of a grapple according to the present invention incorporated into the universal body of FIG. 1;

FIG. 21 is a front view of the grapple illustrated in FIG. 20;

FIG. 22 is a side view of an iron and rail cracker according to the present invention incorporated into the universal body of FIG. 1;

FIG. 23 is a front view of the iron and rail cracker illustrated in FIG. 22;

FIG. 24 is a sectional view of the universal body illustrated in FIG. 1 taken along line A-A of FIG. 5;

FIG. 25 is a sectional view of a hydraulic cylinder for the universal body of the present invention;

FIG. 26 is a side view schematically illustrating a jaw and a linkage arrangement of the shear of FIG. 1;

FIG. 27a is a graph of the power curve and relative jaw position for a shear having the linkage arrangement according to FIG. 26;

FIG. 27b is a graph of the power curve of a shear designed according to the present invention to have the power curve peak near the end of the jaw motion;

FIG. 28 is a side view similar to FIG. 1 illustrating a heavy-duty shear according to another embodiment of the present invention;

FIG. 29 is a top view of the shear illustrated in FIG. 28;

FIG. 30 is a sectional view of the shear illustrated in FIG. 28;

FIGS. 31-34 sequentially illustrate the disassembly of a tool unit mounted on a universal body illustrated in FIG. 28;

FIG. 35 is a side view of the shear according to FIG. 28 incorporated into a modified universal body;

FIG. 36 is a plan view of a modified universal body according to the present invention;

FIG. 37 is a plan view of another modified universal body according to the present invention;

FIG. 38 is a side view of the universal body illustrated in FIG. 37;

FIG. 39 is a side view of the shear according to FIG. 28 incorporated into a modified universal body;

5

FIG. 40 is a plan view of the universal body illustrated in FIG. 39;

FIG. 41 is a schematic side view of a shear according to the present invention incorporated into a further modified universal body;

FIG. 42 is a schematic side view of a jaw portion of a shear according to the present invention;

FIG. 43 is a side view, partially in section, of a shear according to the present invention incorporated into a further modified universal body;

FIG. 44 is a side view of a shear according to the present invention;

FIG. 45 is a side view, with a front side removed for clarity, of the shear illustrated in FIG. 44;

FIG. 46 is a sectional view taken along line A-A of FIG. 45;

FIG. 47 is a schematic side view of a shear according to the present invention;

FIG. 48 is a schematic side view of the shear illustrated in FIG. 47 in the closed position;

FIG. 49 is a side view, partially in section, of a shear according to the present invention incorporated into a further modified universal body;

FIG. 50 is a rear view of a rotary coupling of the shear in FIG. 49;

FIG. 51 is an enlarged view of a connector pin assembly for the rotary coupling in FIG. 50;

FIG. 52 is a side view of an adapter of the shear in FIG. 49;

FIG. 53 is a front view of the adapter of FIG. 52;

FIG. 54 is a side view, partially in section, of a shear similar to the shear of FIG. 49 without a rotary coupling in the body; and

FIG. 55 is a side view, partially in section, of a shear similar to the shear of FIG. 49 and formed as a stick mounted type shear.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 illustrates a multiple tool attachment according to the present invention adapted to be attached to demolition equipment, such as a backhoe (not shown). The multiple tool attachment is adapted to connect one of a series of tools or tool units to the demolition equipment.

FIG. 1 illustrates a shear 10 coupled to the multiple tool attachment. The shear 10 includes a first blade 12 and a second blade 14 pivotally connected at a hub or main pin 16 to a universal body 18. The universal body 18 is referred to as the universal body 18 because it remains common to a series of tools or tool units in the attachment system according to the present invention. The universal body 18 is comprised of sides 19, a bearing housing 20 and a yoke 21. The main pin 16 provides a common pivot for both the first blade 12 and second blade 14.

The bearing housing 20 includes spaced mounting apertures 22 for attaching the universal body 18 to the demolition equipment in a conventional fashion through an adaptor (not shown). The adaptor will pivotally connect the universal body 18 to the demolition equipment and to a controlling piston for pivoting of the universal body 18. The adaptor is intended to conform to the specific demolition equipment such that the shape of the adaptor will differ depending on the specific demolition equipment utilized.

A rotary coupling 23 is between the bearing housing 20 and the yoke 21. The rotary coupling 23 allows for a rotation of the remaining portions of the universal body 18 relative to the bearing housing 20 and the associated demolition equipment. Essentially, the rotary coupling 23 allows for 360 degree

6

rotation for angular orientation of the universal body 18 and associated tool such as shear 10. A motor 25, as shown in FIG. 5, is attached to the bearing housing 20 and geared to the rotary coupling 23 for rotationally positioning the universal body 18.

FIG. 2 illustrates a shear 10' similar to shear 10 illustrated in FIG. 1. The shear 10' has a modified universal body 18' that does not include a rotary coupling attached to the bearing housing 20. A bearing housing 20' and a yoke 21' are of a unitary construction. The universal body 18' is appropriate where no rotation of the tool is desired.

As best shown in FIG. 3, a first linkage 24 is pivotally connected at a removable pivot pin 26 to the first blade 12 and a second linkage 28 is pivotally connected at a removable pivot pin 30 to the second blade 14. The first linkage 24 and second linkage 28 are pivotally connected to a slide member 32 at a common pivot pin 34. The slide member 32 is attached to a piston rod 36, as shown in FIG. 25, which is movable by a double-acting hydraulic cylinder 38 (shown in the universal body 18 in FIG. 30). The hydraulic cylinder 38 is pivotally attached to the universal body 18 through a trunnion 40. The details of the hydraulic cylinder 38 are shown in FIGS. 24 and 25 and are described in detail below.

As shown in FIGS. 3 and 4, sides 19 of the universal body 18 include a longitudinally extending guide slot or groove 44 which receives and guides the slide member 32 as shown in FIG. 4. The pivot pin 34 for connecting the first linkage 24 and second linkage 28 to the slide member 32 is aligned with the piston rod 36 and hydraulic cylinder 38 as illustrated in the figures. Having the linkages 24 and 28 attached to the slide member 32 at a common point in line with the hydraulic cylinder 38 helps maximize the power and efficiencies of the tool, such as shear 10, while minimizing the detrimental forces acting on the hydraulic cylinder 38. Additionally, the guiding of slide member 32 within the slot 44 resists torsional forces which otherwise disrupt the action of the tool and the operation of the hydraulic cylinder 38. The structure of the slide member 32 is shown in detail in FIGS. 4 and 6-7 and will be described in detail below.

A significant feature of the multiple tool attachment of the present invention is the quick change design incorporated into the connection between the jaw set of a specific tool and the universal body 18. This connection and the process of disassembly is shown in FIGS. 9-11a. A bridge housing 48 surrounds the main pin 16 and is utilized for quickly and easily attaching the main pin 16 and the associated jaw set to the universal body 18. Specifically, the sides 19 include receiving members 42 at the ends thereof which are adapted to be received in grooves in the bridge housings 48 for attaching the universal body 18 to the bridge housing 48. Keeper pins 50 are received through apertures 52 in the bridge housing 48 and the receiving members 42. Keeper screws or bolts 54 can be used to secure each keeper pin 50 to one bridge housing 48. In this arrangement, the outer bearing structure surrounding the main pin 16 will remain affixed even when the tool unit is removed from the universal body 18. This provides the advantage that all the bearing or rotating surfaces will be protected from dirt and grit even when the tool unit is disassembled. A modification of the quick connecting system is shown in FIGS. 11b-d. FIGS. 11b and 11c show a modified bridge housing 48' which receives keeper pins 50' in apertures 52 in the bridge housing 48'. The keeper pins 50' are held in place by a keeper 54' as shown in FIG. 11c. Specifically, the shaft of the keeper 54' is received in a locking groove 55 formed in the keeper pins 50' as shown in FIG. 11d. FIGS. 11b-d illustrate that various modifications may be made to the quick change

system within the scope of the present invention. Each keeper 54' is held in place by a retainer 55', such as a threaded plug or the like.

The quick change design of the present invention allows the universal body 18 to accommodate a wide variety of tool units. For example, the shear 10 formed by the first blade 12 and second blade 14 can be replaced with a plate shear 100 illustrated in FIGS. 12 and 13 having distinct blades 102 and 104. The plate shear 100 is similar to shear 10 except that the jaw of blades 102 and 104 is specifically designed for cutting plate. The plate shear 100 is similar to the shear 10 in that it is specifically designed for cutting metal products.

FIGS. 18 and 19 illustrate a wood shear 110 utilized with the universal body 18 of the present invention. Wood shear 110 includes blades 112 and 114 specifically designed for cutting wood products.

FIGS. 14 and 15 illustrate a concrete cracker 120 for use with the universal body 18. The concrete cracker 120 includes jaws 122 and 124 designed specifically for cracking concrete structures. Each jaw 122 and 124 includes concrete crushing inserts 126 at a distal end thereof cooperating with the crushing insert 126 on an opposite jaw 122 or 124 as well as cutting inserts 70 adjacent the main pin 16 which provide a shearing relationship with the cutting inserts 70 of the associated jaw 122 or 124.

FIGS. 16 and 17 illustrate a concrete pulverizer 130 for use with the universal body 18 of the present invention. The concrete pulverizer 130 includes jaws 132 and 134 associated with crushing of concrete. The jaws 132 and 134 include crushing inserts 126 cooperating with inserts 126 on an opposite jaw 132 and 134.

FIGS. 20 and 21 illustrate a grapple 140 for use with the universal body 18 of the present invention. The grapple 140 includes jaws 142 and 144 having hook-shaped tines 146 extending from each jaw 142 and 144. The tines 146 of each jaw 142 and 144 are designed to extend between spaces of the tines 146 on the opposed jaw 142 or 144 such that the tines 146 can overlap in a closed position to completely encircle the work piece.

FIGS. 22 and 23 illustrate an iron and rail cracker 150 for use with the universal body 18 of the present invention. The iron and rail cracker 150 includes jaws 152 and 154 having interposed inserts 156 thereon. The iron and rail cracker 150 is designed to crack rail and cast iron products, such as engine blocks and the like.

The series of tools illustrated in the figures is merely intended to be representative of the tools which can be designed for use with the universal body 18. The quick disconnect feature provided by the bridge housing 48 on each tool facilitates the rapid tool change of the present invention. It will be appreciated that the linkages 24 and 28 must also be disconnected during the change. This is easily accomplished through removal of the respective pivot pins 26 and 30. Consequently the linkages 24 and 28 can be considered part of the universal body 18 since these are likely to be common to multiple tool sets. It is also possible to change out the linkages with the tool sets by either disconnecting the linkages 24 and 28 from the slide member 32 or disconnecting the slide member 32 from the hydraulic cylinder 38. This may be desired where a tool set requires a change in the linkage lengths. Different tools may have different respective linkage lengths.

Due to the rotation of the forward portions of the universal body 18 through the rotary coupling 23, the rotation must be addressed in the hydraulic cylinder 38 and the hydraulic lines leading thereto. The hydraulic cylinder 38 is provided as a combined hydraulic cylinder and rotary joint to accommodate the provision of the rotary coupling 23. As shown in

FIGS. 24 and 25, the hydraulic cylinder 38 includes a cylinder housing 160 which is rotatable with the universal body 18 through the trunnion 40. The cylinder housing 160 includes a cylinder extension 162 attached thereto which includes hydraulic lines 164 and 166 appropriately coupled for driving opposite ends of a piston 168 within the cylinder housing 160. The piston rod 36 is attached to the piston 168. The cylinder extension 162 is received within a stationary housing 170 which is secured to the bearing housing 20. The stationary housing 170 includes hydraulic ports 172 and 174 communicating with respective hydraulic lines 164 and 166. As illustrated in FIG. 25, the hydraulic ports 172 and 174 are channels around the interior of stationary housing 170 which provides constant fluid communication between the hydraulic ports 172 and 174 and the associated hydraulic lines 164 and 166 throughout rotation of the cylinder extension 162 relative to the stationary housing 170. Hydraulic lines 176 and 178 extend from the ends of hydraulic lines 164 and 166 to the appropriate interior portions of the cylinder housing 160 as shown in FIG. 25. This design of the hydraulic cylinder 38 accommodates the provision of a rotary coupling 23 without the need for a separate rotary joint. This design also provides a far more compact arrangement for the universal body 18 than if a separate rotary joint were utilized.

FIG. 26 illustrates the geometric relationships of the shear 10 according to the present invention. As illustrated in FIG. 26, the relevant parameters for the shear 10 include the lengths of each linkage 24 and 28 and lever arms 180 and 182 of the first blade 12 and second blade 14, respectively. The lever arms 180 and 182 for each blade 12 and 14 is the distance between the respective pivot pins 26 and 30 and the main pin 16. Further parameters include the jaw depth defined as the distance between the tip of the jaw and the innermost usable portion of that jaw and the maximum shear opening between the respective ends of the first blade 12 and second blade 14 as illustrated in FIG. 26. The shear 10 of the present invention optimizes the operational characteristics by analyzing and setting these dimensions to properly position the associated power curve. For example, in one embodiment, the power curve shown in FIG. 27a is set to continuously increase throughout the jaw movement by providing the shear opening, the shear jaw depth, the knife lever arm and links having substantially the same dimensional lengths. Maintaining these elements as substantially equal may help maximize the jaw opening as well as jaw depth and available shear tonnage. The present invention provides for the shaping and regulation of the power curve by selecting the relative dimensions accordingly. For example, FIG. 27b shows the power curve for one embodiment of the present invention in which the dimensions are selected so that the power curve peaks near the end of the cutting motion.

The cutting effort for each blade 12 or 14 as a function of the linkage geometry utilized in the shear 10 is calculated according to the following equation:

$$\text{Cutting Effort} = (\text{Lever Arm}) \times (\text{Cylinder Force} / 2) \times \sin(\beta) / \cos(\theta);$$

wherein  $\beta$  is the angle between the lever arm 180 and 182 and the associated linkage 24 or 28 and  $\theta$  is the angle between the longitudinal axis of the cylinder 38 and the respective linkage 24 or 28.

The cutting force produced by the shear 10 at any location along the shear cutting edge can be calculated by dividing the cutting effort by the distance measured from the main pin 16 to the desired location along the blade 12 or 14. In order to optimize the geometric parameters of the shear 10 according to the present invention, the above parameters were varied

and the resulting cutting torques were studied. The cutting torque is defined as the torque applied to the respective blade **12** or **14** about the main pin **16** by the hydraulic cylinder **38** through the piston rod **36**, slide member **32** and associated linkage **24** or **28**. This torque can be converted to a single force along the blade **12** or **14** by dividing the torque by the distance from the center of the main pin **16** to the desired location on the blade **12** or **14**. The numerical value of the cutting torque is at its minimum when the blades **12** and **14** are fully open. The torque continuously increases in value as the blades **12** or **14** move to the fully closed position. FIG. **27a** illustrates the favorable cutting force or power curve achieved with one shear of the present invention. FIG. **27a** illustrates the force generated at the throat and piercing tip for the shear **10** through the various jaw positions which is shown in the lower portion of the graph. It is of particular importance to note that the power curve of this shear continually increases throughout the jaw closing cycle. The jaw position is graphed as the distance between the piercing tip and the lower jaw with the negative values reflecting when the portions of the upper jaw are moving through a slot in the lower jaw. The relative dimensions of the jaw parameters can be selected to vary the power curve as desired. For example, it may be advantageous to have the power curve peak slightly before the end of the jaw cycle when the maximum cutting forces are needed such as shown in FIG. **27b**. Providing the linkage lengths slightly greater than the lever arms may be used to achieve this design.

A review of the effect of changing the relevant parameters will clarify the advantages of the design of the shear **10** of the present invention as well as the tool design method of the present invention. Increasing the length of the lever arm **180** or **182** of the respective blade **12** or **14** results in the increased values of cutting torque for all positions of the blade **12** or **14** from fully open to fully closed. However, the length of the respective lever arm **180** and **182** is, of course, limited by the desired overall dimensions of the shear **10**. Varying the length of the linkages **24** and **28** has various effects on the cutting torque. If the linkages **24** and **28** are longer than the respective lever arms **180** and **182**, the cutting torque curve versus the blade **12** and **14** position will increase in value until reaching a peak and then decreasing until the blades **12** and **14** are closed. One embodiment of the present invention utilizes this concept to position the maximum cutting torque near the end of the jaw moving cycle. If the length of the linkages **24** and **28** is shorter than the respective lever arms **180** and **182**, the torque value will continuously increase from the open to the closed position. As the length of the linkage arms **24** and **28** increases, the value of the cutting torque at the open position increases and the value of the closed position decreases. Having the linkages **24** and **28** substantially the same length as the lever arms **180** and **182** results in one shear design which considers all of the factors to be balanced.

The hydraulic cylinder **38** also has an effect on the power of the associated shear **10**. Increasing the diameter of the hydraulic cylinder **38** results in an increased cutting torque for all the blade positions (**12** and **14**) and also increases the open/closed cycle time for the shear **10**. The size of the hydraulic cylinder **38** is effectively determined by the size of the shear **10** and the operating conditions desired.

In addition to the lengths of the linkages **24** and **28** and the length of the respective lever arms **180** and **182**, the value of the angles  $\theta$  between the respective linkages **24** and **28** and the longitudinal axis of the hydraulic cylinder **38**, and an angle  $\phi$  between the lever arm **180** and **182** and the longitudinal axis of the hydraulic cylinder **38** will depend on the initial distance between the pivot pin **34** and the main pin **16** in the fully open position. To allow for the needed pin diameters, required

bushings and the like, the initial values of these angles should be at least **20** degrees. Due to the nature of the force transmission at pivot pin **34** and slide member **32**, the final value of these angles will be less than **90** degrees and should be approximately **80** degrees.

The initial distance between pivot pin **34** and main pin **16** is limited by two physical limitations. First, the distance must be less than the sum of the lengths of the respective lever arm **180** and **182** and linkage **24** or **28** by enough to allow the angles  $\theta$  and  $\phi$  discussed above to be at least about **20** degrees in the open position. Second, this distance must be large enough so that the pivot pin **34** will not run into the main pin **16** at the closed position. Decreasing the length of this initial distance decreases the cutting torque at all positions.

Another issue to review is the total jaw rotation angle. Increasing the size of the initial jaw opening increases the angular rotation necessary to go from the open position to the closed position. However, increasing this rotational angle also has an effect on the cutting torque curve. Increasing the total rotation angle causes an increase in the cutting torque when the jaws are almost fully open and a decrease in the cutting torque when in the fully closed position. Balancing all of the above considerations in the design of the shear **10** of FIG. **1** results in the shear opening, jaw depth, lever arm and linkage length being all substantially the same dimensional length. This ratio works for shears of all sizes such that the specific value of this dimensional length will depend upon the size of the shear desired. This relationship between the linkage length and the lever arm may also be maintained for the various tools illustrated in FIGS. **12-23**. The other relationships may be altered due to jaw structure changes.

Another important aspect of the present invention is the jaw structure of shear **10**. The cutting edge of the first blade **12** is formed of a plurality of removable cutting inserts **190** removably attached to the first blade **12** by bolts or the like as well-known in the art. These inserts **190** may be indexable, meaning that the inserts **190** may be removed and rotated to provide new cutting edges as one cutting edge is worn. The first blade **12** includes a piercing tip **192** at a distal end of the first blade **12**. The piercing tip **192** is also a removable cutting insert. However, the piercing tip **192** is intended to primarily make a cut transverse to the cut supplied by the cutting inserts **190**. Specifically, the primary cut of the piercing tip **192** would be extending into and out of the illustration in FIG. **1**. Additionally, the cutting inserts **190** along the first blade **12** are positioned in a hook shape to provide a first cutting portion **194** and a longer second cutting portion **196** positioned between the first cutting position **194** and the piercing tip **192**. The shear **10** is designed so that the first cutting portion **194** is significantly less than, and preferably approximately one-half of, the length of the second cutting portion **196**. The second blade **14** includes a plurality of cutting inserts **190** which are positioned in shearing relation with the cutting inserts **190** and piercing tip **192** to provide the shearing action for the shear **10**. The second blade **14** provides a slot for the first blade **12** to extend through during the shearing action with the slot helping to maintain the cutting inserts **190** in shearing relation. The jaw design of the first blade **12** and second blade **14** in the shear **10** is constructed to help move material to be severed to the throat area adjacent the main pin **16** where the cutting forces are the highest. Having the piercing tip **192** sever the work piece in a direction transverse to the cutting of the first cutting portion **194** and second cutting portion **196** will help draw the material back to the throat. Additionally, the hook shape, i.e., the angle, between the first cutting portion **194** and the second cutting portion **196** will also serve to pull the material back to the throat area. Finally, the provision

of the first cutting portion **194** having a dimension significantly less than the second cutting portion **196** will further assure that the material is pulled closer to the throat for cutting. This is believed to provide a significant improvement over the jaw designs of existing shears with plural movable blades and compliments the power curve associated with the shear design to magnify the effective shearing force. It is also within the scope of the present invention that different shapes for the piercing tip **192** may be utilized for different types of material. Specifically, a piercing tip having a sharper or shallower angle when viewed from the side may be more or less appropriate for distinct types of work pieces.

FIG. **5** additionally illustrates that the sides **19** of the universal body **18** are pivoted to the yoke **21** through side pivots **78**. This allows for easy replacement of the first and second blades **12** and **14** with the associated linkages **24** and **28**, if desired. The pivotable sides **19** of the universal body **18** can be secured together by bolts or other fastening members. A rectangular tie bar **79** is positioned between the pivotable sides **19** through which the securing bolts extend. The tie bar **79** helps to maintain structural integrity of the universal body **18**.

FIGS. **28-30** illustrate a shear **10** similar to shear **10** of FIG. **1**, except that the quick change feature is modified to utilize the pivoting sides **19** of the universal body **18**. Specifically, the bridge housing **48** has been omitted and the main pin **16** is used to couple the jaw set directly to the universal body **18**. FIG. **29** illustrates bolts **198** which can be used for holding the sides **19** of the universal body **18** together.

FIGS. **31-34** schematically illustrate the process of disassembling the jaw structure and inserting a new jaw structure at the main pin **16** for the quick change device shown in FIGS. **28-30**. As best shown in these figures, this design essentially keeps the structure generally symmetrical about the center line thereby avoiding inappropriate torquing during use of the shear **10**. It will be appreciated that bearing sleeves **202** may be positioned between appropriate elements and the main pin **16**. Retaining members **204** may be secured for holding the assembly in place.

As illustrated in FIG. **32**, by removing retaining bolts **206**, a retaining cap **208**, retaining clips **210** and an alignment sleeve **212** from attachment with the sides **19** of the universal body **18**, the main pin **16** and associated assembly is ready for removal. As shown in FIG. **33**, once the retaining system has been disassembled, the sides **19** of the universal body **18** rotate outwardly to simplify the removal process.

It will be apparent that before the first and second blades **12** and **14** can be removed, the linkages **24** and **28** must be detached from either the first and second blades **12** and **14** or the slide member **32**. In general, the pivot pins **26** and **30** are removed for disconnecting the linkages **24** and **28** from the respective blades **12** and **14**. However, it is possible for the linkages **24** and **28** to remain with the blades **12** and **14** as a single tool unit. This may be important if different linkage lengths are desired for the next tool set.

Maintaining the first linkage **24** and the second linkage **28** with the first and second blades **12** and **14** requires the decoupling of the linkages **24** and **28** from the slide member **32**, or alternatively, decoupling the slide member **32** from the piston rod **36**. In this latter arrangement, the decoupling of the slide member **32** from the piston rod **36** can be by bolts, a pin type connection or other secure fastening which can be easily disassembled. A continuous sleeve **214**, shown in FIG. **6**, is positioned around pivot pin **34** which couples the linkages **24** and **28** to the slide member **32**. The sleeve **214** provides that the linkages **24** and **28** will be held together in a single assembly around sleeve **214** following the removal of pivot

pin **34**. This structure allows the linkages **24** and **28** to be removed, if needed. The removal of the linkages may be desired so that the linkage lengths can be changed with the next tool set.

Regardless of how the linkages are decoupled, with the linkages **24** and **28** decoupled and the sides **19** of the universal body **18** rotated outward, the entire jaw structure comprising the blades **12** and **14**, and linkages **24** and **28**, if maintained with the blades **12** and **14**, can be removed and a separate tool assembly installed (with new linkages **24** and **28** if these were removed). Following this assembly, the sides of the universal body **18** will be pivoted back together and the retaining system attached around a new main pin **16** such as shown in FIG. **32**. Bolts will reattach the sides **19** of the universal body **18** to complete the reassembly. As shown in FIG. **34**, the new blades **12** and **14** have different retaining members and bearing sleeves associated with this particular tool unit. A particular bearing structure will be designed in accordance with the specific tool unit implemented.

FIG. **35** illustrates a shear **10** which incorporates a side access plate **222** for permitting access to the slide member **32** and the associated pivot pin **34**. Specifically, the universal body **18** includes the access plates **222** secured thereto which can be removed to gain access to the guided slide member **32** within the universal body **18**.

FIG. **36** illustrates a modified universal body **18** in which the bolts for attaching the pivotable sides **19** of the universal body **18** are replaced with a retaining connection **224**.

FIGS. **37** and **38** illustrate a modified universal body **18** in which the sides **19** of the universal body **18** are pivoted about side pivots **78** and are secured by independent retaining connections **224** to the universal body **18**.

FIGS. **39** and **40** illustrate a further modified universal body **18** in which the sides **19** of the universal body **18** are completely separable from the remaining portions of the universal body **18** and secured thereto by the attachment of the trunnion **40** and separate retaining connections **224**.

FIG. **41** illustrates a modification of the shear **10** in which the slot **44** is replaced with a guide rod **230** upon which the slide member **32** slides. This modification also results in changing the attachment of the linkages **24** and **28** from a common position to separate offset positions by independent pins **232** and **234**. This change also results in a change in the geometric relationship discussed above in which the offset created must be accounted for in the resulting shear. This offset provides a less desirable shear in terms of cutting characteristics.

Another aspect of the present invention is the details of the slide member **32** and the coupling to the piston rod **36** as shown in FIGS. **4**, **6** and **7**. A sleeve **214** is specifically formed as a hardened steel member and is keyed to the pivot pin **34** through a key **242** positioned behind a cover plate **244**. Wear plates **246** are on the sides of the slide member **32** to be captured in the slot **44** against wear plates **248** in groove **44**. The slide member **32** is connected through a pin **250** to a rod eye **252** of the piston rod **36**. The pin **250** allows for rotation of the rod **36** about an axis which is 90 degrees from the axis of the trunnion **40**. The sleeve **214** will maintain the linkages **24** and **28** together even following removal of the pin **34**. Additionally, the replaceable sleeve **214** absorbs most of the transmitted shear load such that most of the wear will occur on the sleeve **214** and not the pin **34**. Bushings **260** located at each linkage **24** and **28** will ensure proper alignment and eliminate linkage-to-linkage, or linkage-to-slide member, wear. Keying the pivot pin **34**, sleeve **214** and slide member **32** together by key **242** will prevent rotation of the pin **34** or sleeve **214** and eliminate the likelihood of flat spots develop-

ing on either structure. The pinning of the rod eye **252** to the slide member **32** allows for misalignment in relation to the hydraulic cylinder **38** and the slide member **32** which, in conjunction with the trunnion **40**, will help to prolong the seal life of the hydraulic cylinder **38**. Finally, it is anticipated that the wear plates **246** will be made of high wear brass with impregnated graphite, thus eliminating the need for lubrication of these components. These components will serve two functions. First, they prevent the frictional wear between the slide member **32** and the mating part in the slot **44**. Second, the wear plates **246** serve to keep exact linear motion of the slide member **32** in the event of unperceived side loading, thereby maintaining the highest possible cylinder force in operation.

FIG. **42** is a schematic illustration of a jaw and linkage design also including an offset similar to that shown in FIG. **41**. However, the embodiment illustrated in FIG. **42** is considered a "negative" offset due to the crossing of the respective linkages **24** and **28**. The negative offset represented by the embodiment illustrated in FIG. **42** may have a beneficial effect in the theoretical operation of the shear, however, appropriate design of the crossing or linkage arrangement increases the complexity of the device.

FIG. **43** illustrates an embodiment of the shear **10** in which a rotatable connection **280** is provided between the piston rod **36** and the slide member **32**. The provision of the rotational coupling **280** means that the trunnion **40** can be moved back and utilized for attaching the hydraulic cylinder **38** to the bearing housing **20** rather than attaching it to the yoke **21**. Furthermore, since the hydraulic cylinder **38** will not rotate when the universal body **18** rotates, a simple, more conventional hydraulic cylinder **38** can be utilized in this embodiment.

FIGS. **44-46** illustrate a shear **300** of a distinct type different from the shear **10**. Specifically, the shear **300** includes a first pivotable blade **302** pivotally attached to a fixed blade **304** through a hub **305**. The shear **300** is similar to the shear **10** in that a linkage **306** couples the blade **302** to a slide member **308** which is received in a guiding slot **310**. The shear **300** additionally includes piston rod **36**, hydraulic cylinder **38**, trunnion **40** and the bearing housing **20** similar to shear **10** described above.

FIGS. **47** and **48** illustrate a modification of shear **300** in which the slide member **308** and slot **310** are replaced with a separate linkage **312** to the fixed blade **304** and the rod eye **252** of piston rod **36**. The linkage **306** is also attached to the rod eye **252** and linkage **312**. In this embodiment, the guiding of the piston is non-linear and travels through an arc defined by the linkage **312**. The hydraulic cylinder **38** will also pivot about trunnion **40** throughout the movement of the linkage **312**.

FIGS. **49-53** illustrate a shear **10** which details a universal body **18** incorporating a simple four pin connection between the rotary coupling **23** and an adapter **20a**. The adapter **20a** essentially replaces the bearing housing **20** of earlier embodiments. As shown in FIGS. **50** and **51** the rotary coupling **23** includes parallel connecting plates **320** which receive four connector pin assemblies **330**. The connector pin assemblies **330** provide a simple connection between the rotary coupling **23** and the adapter **20a**. A connector pin assembly **330** is shown in detail in FIG. **51**. Each connector pin assembly **330** includes a connecting pin **332** received in and extending between a pair of adjacent connector plates **320** within bushings **334** and **336**. The bushing **336** and the connecting pin **332** receive a locking bolt **338** secured by a nut **340** to hold the connector pin assembly **330** in position. As shown in FIGS. **52** and **53**, the adapter **20a** includes a pair of parallel side

plates having receiving apertures **342** that are received between pairs of adjacent connecting plates **320** to receive the connecting pin **332** therethrough. This provides a simple, easily released connection between the rotary coupling **23** and the adapter **20a**.

FIG. **54** illustrates a shear **10'** which details a universal body **18'** incorporating a simple four pin connection between the yoke **21'** and the adapter **20a**. The four pin connection is similar to the shear of FIG. **49** except without a rotary coupling in the universal body. The parallel connecting plates extend from the yoke **21'** rather than the rotary coupling.

FIG. **55** illustrates a shear **10** incorporating a simple four pin connection between the rotary coupling **23** and the adapter **20a** as shown in FIG. **49**. The shear **10** of FIG. **55** is designed as a stick mounted type shear, also referred to as a third member mount type adapter. Essentially, the adapter **20a** is configured for this type of arrangement. FIG. **55** further illustrates the versatility of the shears of the present invention.

It will be apparent to those of ordinary skill in the art that various modifications may be made to the present invention without departing from the spirit and scope thereof. The described embodiments are intended merely to be illustrative of the concepts of the present invention and not restrictive thereof.

The invention claimed is:

**1.** A demolition tool unit for mounting to a universal body, wherein the tool unit has:

- a) a pair of movable blades pivotally connected to a main pin forming a jaw structure, wherein the main pivot-pin is fixed to the universal body and does not translate relative to the universal body,
- b) a pair of linkages, wherein each linkage has a linkage blade end and a linkage cylinder end, wherein each linkage blade end is attached to a separate movable blade and each linkage cylinder end is pivotally attached along a common axis to a common pivot pin to define a general jaw structure,
- c) a common hydraulic cylinder attached to each linkage at the common pivot pin for moving the blades over a range, wherein a cylinder has a center line that is aligned with the common main pin and the common pivot pin throughout the range of travel of the cylinder,
- d) a general jaw geometry which defines main geometric parameters of the general jaw structure of the demolition tool unit, wherein the distance between the common main pin and the linkage blade end defining a lever arm length is greater than the distance between the linkage blade end and the common pivot pin defining a linkage length, and wherein the lengths of the pair of lever arms are equal and the pair of linkage lengths are equal, and
- e) wherein, when the hydraulic cylinder is activated, the equal length linkages and the equal length lever arms move together to rotate each movable blade the same amount and to apply to each movable blade the same moment.

**2.** The demolition unit according to claim **1**, wherein the range of rotation of the blades with respect to a longitudinal axis extending along the length of the hydraulic cylinder is between **20** and **90** degrees.

**3.** A demolition tool unit for mounting to a universal body, wherein the tool unit has:

- a) a pair of movable blades pivotally connected to a main pin forming a jaw structure, wherein the main pin is fixed to the universal body and does not translate relative to the universal body,
- b) a pair of linkages, wherein each linkage has a linkage blade end and a linkage cylinder end, wherein each

15

- linkage blade end is attached to one movable blade and each linkage cylinder end is pivotally attached along a common axis to a common pivot pin to define a general jaw structure,
- c) a common hydraulic cylinder attached to each linkage at the common pivot pin for moving the blades over a range, wherein a cylinder has a center line that is aligned with the common main pin and the common pivot pin throughout the range of travel of the cylinder, 5
  - d) a general jaw geometry which defines main geometric parameters of the general jaw structure of the demolition tool unit, wherein the distance between the common main pin and the linkage blade end defining a lever arm length is equal to the distance between the linkage blade end and the common pivot pin defining a linkage length, and wherein the lengths of the pair of lever arms are equal and the pair of linkage lengths are equal, and 10
  - e) wherein, when the hydraulic cylinder is activated, the equal length linkages and the equal length lever arms move to either to rotate each movable blade the same amount and to apply to each movable blade the same moment. 15
4. The demolition unit according to claim 3, wherein the range of motion of the blades with respect to a longitudinal axis extending along the length of the hydraulic cylinder is between 20 and 90 degrees. 20
5. A demolition tool unit for mounting to a universal body, wherein the tool unit has: 25
- a) a pair of movable blades pivotally connected to a main pin forming a jaw structure, wherein the main pin is fixed to the universal body and does not translate relative to the universal body,

16

- b) a pair of linkages, wherein each linkage has a linkage blade end and a linkage cylinder end, wherein each linkage blade end is attached to one movable blade and each linkage cylinder end is pivotally attached along a common axis to a common pivot pin to define a general jaw structure,
  - c) a common hydraulic cylinder attached to each linkage at the common pivot pin for moving the blades over a range, wherein a cylinder has a center line that is aligned with the common main pin and the common pivot pin throughout the range of travel of the cylinder,
  - d) a general jaw geometry which defines main geometric parameters of the general jaw structure of the demolition tool unit, wherein the distance between the common main pin and the linkage blade end defining a lever arm length is less than the distance between the linkage blade end and the common pivot pin defining a linkage length, and wherein the lengths of the pair of lever arms are equal and the pair of linkage lengths are equal, and
  - e) wherein, when the hydraulic cylinder is activated, the equal length linkages and the equal length lever arms move together to rotate each movable blade the same amount and to apply to each movable blade the same moment.
6. The demolition unit according to claim 5, wherein the range of motion of the blades with respect to a longitudinal axis extending along the length of the hydraulic cylinder is between 20 and 90 degrees.

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 8,424,789 B2  
APPLICATION NO. : 12/958050  
DATED : April 23, 2013  
INVENTOR(S) : John R. Ramun

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title Page, Column 1, Item (60) Related U.S. Application Data, Line 6,  
delete "6, 994,284." and insert -- 6,994,284 --

In the Claims:

Column 14, Line 29, Claim 1, delete "pivot-pin" and insert -- pin --

Column 15, Line 19, Claim 3, delete "to ether" and insert -- together --

Signed and Sealed this  
Thirtieth Day of July, 2013



Teresa Stanek Rea  
*Acting Director of the United States Patent and Trademark Office*