



US 20060089637A1

(19) **United States**(12) **Patent Application Publication**  
**Werneth et al.**(10) **Pub. No.: US 2006/0089637 A1**(43) **Pub. Date: Apr. 27, 2006**(54) **ABLATION CATHETER****Related U.S. Application Data**(76) Inventors: **Randell L. Werneth**, San Diego, CA (US); **Marshall L. Sherman**, Cardiff-by-the-Sea, CA (US); **Thomas M. Castellano**, Temecula, CA (US); **J. Christopher Flaherty**, Topsfield, MA (US); **Gary Edward Currie**, Fallbrook, CA (US)


(60) Provisional application No. 60/618,753, filed on Oct. 14, 2004.

**Publication Classification**(51) **Int. Cl.**  
**A61B 18/14** (2006.01)(52) **U.S. Cl.** ..... **606/41**

Correspondence Address:

**MAYER, FORTKORT & WILLIAMS, PC**  
**251 NORTH AVENUE WEST**  
**2ND FLOOR**  
**WESTFIELD, NJ 07090 (US)**(57) **ABSTRACT**

Devices, systems and methods are disclosed for the ablation of tissue. Embodiments include an ablation catheter which has an array of ablation elements attached to a deployable carrier assembly. The carrier assembly can be constrained within the lumen of a catheter, and deployed to take on an expanded condition.

(21) Appl. No.: **11/179,333**(22) Filed: **Jul. 12, 2005**













Figure 1












Fig. 7




Fig. 8a

Fig. 8b




Fig. 9








Fig. 10





## ABLATION CATHETER

### STATEMENT OF RELATED APPLICATION

[0001] This application claims the benefit of priority of U.S. Provisional Patent Application No. 60/618,753, filed Oct. 14, 2004, entitled "Ablation Catheter," which is incorporated by reference herein in its entirety.

### FIELD OF THE INVENTION

[0002] The present invention relates generally to catheters and methods for performing targeted tissue ablation in a subject. In particular, the present invention provides devices comprising catheters having distal ends configured to treat two dimensional regions of target tissue, including deployable distal ends, and methods for treating conditions (e.g., cardiac arrhythmias) with these and similar devices.

### BACKGROUND OF THE INVENTION

[0003] Tissue ablation is used in numerous medical procedures to treat a patient. Ablation can be performed to remove undesired tissue such as cancer cells. Ablation procedures may also involve the modification of the tissue without removal, such as to stop electrical propagation through the tissue in patients with an arrhythmia. Often the ablation is performed by passing energy, such as electrical energy, through one or more electrodes causing the tissue in contact with the electrodes to heat up to an ablative temperature. Ablation procedures can be performed on patients with atrial fibrillation by ablating tissue in the heart.

[0004] Mammalian organ function typically occurs through the transmission of electrical impulses from one tissue to another. A disturbance of such electrical transmission may lead to organ malfunction. One particular area where electrical impulse transmission is critical for proper organ function is in the heart. Normal sinus rhythm of the heart begins with the sinus node generating an electrical impulse that is propagated uniformly across the right and left atria to the atrioventricular node. Atrial contraction leads to the pumping of blood into the ventricles in a manner synchronous with the pulse.

[0005] Atrial fibrillation refers to a type of cardiac arrhythmia where there is disorganized electrical conduction in the atria causing rapid uncoordinated contractions that result in ineffective pumping of blood into the ventricle and a lack of synchrony. During atrial fibrillation, the atrioventricular node receives electrical impulses from numerous locations throughout the atria instead of only from the sinus node. This overwhelms the atrioventricular node into producing an irregular and rapid heartbeat. As a result, blood pools in the atria that increases a risk for blood clot formation. The major risk factors for atrial fibrillation include age, coronary artery disease, rheumatic heart disease, hypertension, diabetes, and thyrotoxicosis. Atrial fibrillation affects 7% of the population over age 65.

[0006] Atrial fibrillation treatment options are limited. Lifestyle change only assists individuals with lifestyle related atrial fibrillation. Medication therapy assists only in the management of atrial fibrillation symptoms, may present side effects more dangerous than atrial fibrillation, and fail to cure atrial fibrillation. Electrical cardioversion attempts to restore sinus rhythm but has a high recurrence rate. In

addition, if there is a blood clot in the atria, cardioversion may cause the clot to leave the heart and travel to the brain or to some other part of the body, which may lead to stroke. What are needed are new methods for treating atrial fibrillation and other conditions involving disorganized electrical conduction.

[0007] Various ablation techniques have been proposed to treat atrial fibrillation, including the Cox-Maze procedure, linear ablation of various regions of the atrium, and circumferential ablation of pulmonary vein ostia. The Cox-Maze procedure and linear ablation procedures are tedious and time-consuming, taking several hours to accomplish. Pulmonary vein ostial ablation is proving to be difficult to do, and has led to rapid stenosis and potential occlusion of the pulmonary veins. There is therefore a need for improved atrial ablation products and techniques.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate various embodiments of the present invention, and, together with the description, serve to explain the principles of the invention. In the drawings:

[0009] **FIG. 1** illustrates the treatment to be accomplished with the devices and methods described below.

[0010] **FIG. 2** illustrates a side view of an ablation catheter consistent with the present invention.

[0011] **FIG. 3** illustrates an end view of the distal portion of the ablation catheter of **FIG. 2**.

[0012] **FIG. 4** illustrates an enlarged sectional view of the distal portion of the ablation catheter of **FIG. 2**.

[0013] **FIG. 5a** and **FIG. 5b** and **FIG. 5c** illustrate a sectional view of the distal portion of the ablation catheter of **FIG. 2** demonstrating a series of deployments of the carrier assembly in a fully deployed, partially constrained and fully constrained condition, respectively.

[0014] **FIG. 6** illustrates a perspective, partial cutaway view of an ablation catheter consistent with the present invention in which the carrier element has three carrier arms, the ablation catheter further including a handle for performing multiple functions.

[0015] **FIG. 6a** illustrates a sectional view of the distal end of the ablation catheter of **FIG. 6**.

[0016] **FIG. 7** illustrates a perspective view of an ablation catheter consistent with the present invention in which the carrier element is in a spiral configuration.

[0017] **FIGS. 8a** and **8b** are sectional views of the distal end of an ablation catheter consistent with the present invention in which the carrier assembly and control shaft are a continuous conduit. **FIG. 8a** illustrating the carrier assembly in a fully deployed condition and **FIG. 8b** illustrating the carrier assembly in a fully constrained condition.

[0018] **FIG. 9** illustrates an ablation element of an ablation catheter consistent with the present invention in which the ablation element includes an ultrasound crystal and a thermocouple.

[0019] **FIG. 10** illustrates an ablation element assembly of an ablation catheter consistent with the present invention in which the assembly is a semiconductor with integrated electronics.

[0020] FIG. 11 is an end view of a carrier assembly of an ablation catheter consistent with the present invention.

[0021] FIG. 11a is a side sectional view of the distal portion of the ablation catheter of FIG. 11 in which the carrier assembly lies in multiple planes when fully expanded.

[0022] FIG. 11b is a side sectional view of the distal portion of the ablation catheter of FIG. 11 in which the carrier assembly lies in a single plane when fully expanded.

[0023] FIG. 12 is an end view of the carrier assembly of an ablation catheter consistent with the present invention in which the carrier assembly consists of multiple wire segments each attached to a coupler.

#### DESCRIPTION OF THE EMBODIMENTS

[0024] Reference will now be made in detail to the present embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

[0025] The present invention provides catheters for performing targeted tissue ablation in a subject. In preferred embodiments, the catheters comprise a tubular body member having a proximal end and distal end and preferably a lumen extending therebetween. The catheter is preferably of the type used for performing intracardiac procedures, typically being introduced from the femoral vein in a patient's leg. The catheter is preferably introducable through a sheath and also preferably has a steerable tip that allows positioning of the distal portion such as when the distal end of the catheter is within a heart chamber. The catheters include ablation elements mounted on a carrier assembly. The carrier assembly is attached to a coupler, which in turn is connected to a control shaft that is coaxially disposed and slidably received within the lumen of the tubular body member. The carrier assembly is deployable from the distal end of the tubular body member by advancing the control shaft, such as to engage one or more ablation elements against cardiac tissue, typically atrial wall tissue or other endocardial tissue. Retraction of the control shaft causes the carrier assembly to be constrained within the lumen of the tubular body member.

[0026] Arrays of ablation elements, preferably electrode arrays, may be configured in a wide variety of ways and patterns. In particular, the present invention provides devices with electrode arrays that provide electrical energy, such as radiofrequency (RF) energy, in monopolar (unipolar), bipolar or combined monopolar-bipolar fashion, as well as methods for treating conditions (e.g., atrial fibrillation, supra ventricular tachycardia, atrial tachycardia, ventricular tachycardia, ventricular fibrillation, and the like) with these devices. Alternative to or in combination with ablation elements that deliver electrical energy to tissue, other forms and types of energy can be delivered including but not limited to: sound energy such as acoustic energy and ultrasound energy; electromagnetic energy such as electrical, magnetic, microwave and radiofrequency energies; thermal energy such as heat and cryogenic energies; chemical energy such as energy generated by delivery of a drug; light energy such as infrared and visible light energies; mechanical and physical energy; radiation; and combinations thereof.

[0027] As described above, the normal functioning of the heart relies on proper electrical impulse generation and

transmission. In certain heart diseases (e.g., atrial fibrillation) proper electrical generation and transmission are disrupted or are otherwise abnormal. In order to prevent improper impulse generation and transmission from causing an undesired condition, the ablation catheters of the present invention may be employed.

[0028] One current method of treating cardiac arrhythmias is with catheter ablation therapy. Physicians make use of catheters to gain access into interior regions of the body. Catheters with attached electrode arrays or other ablating devices are used to create lesions that disrupt electrical pathways in cardiac tissue. In the treatment of cardiac arrhythmias, a specific area of cardiac tissue having aberrant conductive pathways, such as atrial rotors, emitting or conducting erratic electrical impulses, is initially localized. A user (e.g., a physician) directs a catheter through a main vein or artery into the interior region of the heart that is to be treated. The ablating element is next placed near the targeted cardiac tissue that is to be ablated. The physician directs energy, provided by a source external to the patient, from one or more ablation elements to ablate the neighboring tissue and form a lesion. In general, the goal of catheter ablation therapy is to disrupt the electrical pathways in cardiac tissue to stop the emission of and/or prevent the propagation of erratic electric impulses, thereby curing the heart of the disorder. For treatment of atrial fibrillation, currently available methods and devices have shown only limited success and/or employ devices that are extremely difficult to use or otherwise impractical.

[0029] The ablation catheters of the present invention allow the generation of lesions of appropriate size and shape to treat conditions involving disorganized electrical conduction (e.g., atrial fibrillation). The ablation catheters of the present invention are also practical in terms of ease-of-use and limiting risk to the patient, as well as significantly reducing procedure times. The present invention addresses this need with, for example, spiral shaped and radial arm shaped (also called umbrella shaped) carrier assemblies whose ablation elements create spiral, radial, or other simple or complex shaped patterns of lesions in the endocardial surface of the atria by delivery of energy to tissue or other means. The lesions created by the ablation catheters are suitable for inhibiting the propagation of inappropriate electrical impulses in the heart for prevention of reentrant arrhythmias.

[0030] Definitions. To facilitate an understanding of the invention, a number of terms are defined below.

[0031] As used herein, the terms "subject" and "patient" refer to any animal, such as a mammal like livestock, pets, and preferably a human. Specific examples of "subjects" and "patients" include, but are not limited, to individuals requiring medical assistance, and in particular, requiring atrial fibrillation catheter ablation treatment.

[0032] As used herein, the terms "catheter ablation" or "ablation procedures" or "ablation therapy," and like terms, refer to what is generally known as tissue destruction procedures. Ablation is often used in treating several medical conditions, including abnormal heart rhythms. It can be performed both surgically and non-surgically. Non-surgical ablation is typically performed in a special lab called the electrophysiology (EP) laboratory. During this non-surgical procedure a catheter is inserted into the heart using fluoros-

copy for visualization, and then an energy delivery apparatus is used to direct energy to the heart muscle. This energy either “disconnects” or “isolates” the pathway of the abnormal rhythm (depending on the type of ablation). It can also be used to disconnect the conductive pathway between the upper chambers (atria) and the lower chambers (ventricles) of the heart. For individuals requiring heart surgery, ablation can be performed during coronary artery bypass or valve surgery.

[0033] As used herein, the term “ablation element” refers to an energy delivery element, such as an electrode for delivering electrical energy. Ablation elements can be configured to deliver multiple types of energy, such as ultrasound energy and cryogenic energy, either simultaneously or serially. Electrodes can be constructed of a conductive plate, wire coil, or other means of conducting electrical energy through contacting tissue. In monopolar energy delivery, the energy is conducted from the electrode, through the tissue to a ground pad, such as a conductive pad attached to the back of the patient. The high concentration of energy at the electrode site causes localized tissue ablation. In bipolar energy delivery, the energy is conducted from a first electrode to one or more separate electrodes, relatively local to the first electrode, through the tissue between the associated electrodes. Bipolar energy delivery results in more precise, shallow lesions while monopolar delivery results in deeper lesions. Both monopolar and bipolar delivery provide advantages, and the combination of their use is a preferred embodiment of this application. Energy can also be delivered using pulse width modulated drive signals, well known to those of skill in the art. Energy can also be delivered in a closed loop fashion, such as a system with temperature feedback wherein the temperature modifies the type, frequency and or magnitude of the energy delivered.

[0034] As used herein, the term “carrier assembly” refers to a flexible carrier, on which one or more ablation elements are disposed. Carrier assemblies are not limited to any particular size, or shape, and can be configured to be constrained within an appropriately sized lumen.

[0035] As used herein, the term “spiral tip” refers to a carrier assembly configured in its fully expanded state into the shape of a spiral. The spiral tip is not limited in the number of spirals it may contain. Examples include, but are not limited to, a wire tip body with one spiral, two spirals, ten spirals, and a half of a spiral. The spirals can lie in a relatively single plane, or in multiple planes. A spiral tip may be configured for energy delivery during an ablation procedure.

[0036] As used herein the term “umbrella tip” refers to a carrier assembly with a geometric center which lies at a point along the axis of the distal portion of the tubular body member, with one or more bendable or hinged carrier arms extending from the geometric center, in an umbrella configuration. Each carrier arm may include one or more ablation elements. Each carrier arm of an umbrella tip includes a proximal arm segment and a distal arm segment, the distal arm segment more distal than the proximal arm segment when the carrier assembly is in a fully expanded condition. One or more additional carrier arms can be included which include no ablation elements, such as carrier arms used to provide support or cause a particular deflection.

An umbrella tip body is not limited to any particular size. An umbrella tip may be configured for energy delivery during an ablation procedure.

[0037] As used herein, the term “lesion,” or “ablation lesion,” and like terms, refers to tissue that has received ablation therapy. Examples include, but are not limited to, scars, scabs, dead tissue, burned tissue and tissue with conductive pathways that have been made highly resistive or disconnected.

[0038] As used herein, the term “spiral lesion” refers to an ablation lesion delivered through a spiral tip ablation catheter. Examples include, but are not limited to, lesions in the shape of a wide spiral, and a narrow spiral, a continuous spiral and a discontinuous spiral.

[0039] As used herein, the term “umbrella lesion” or “radial lesion,” and like terms, refers to an ablation lesion delivered through an umbrella tip ablation catheter. Examples include, but are not limited to, lesions with five equilateral prongs extending from center point, lesions with four equilateral prongs extending from center point, lesions with three equilateral prongs extending from center point, and lesions with three to five non-equilateral prongs extending from center point.

[0040] As used herein, the term “coupler” refers to an element that connects the carrier assembly to the control shaft. Multiple shafts, or ends of the carrier assembly may connect to the coupler. Multiple carrier arms can have one or more of their ends attached to the coupler. The coupler may include anti-rotation means that work in combination with mating means in the tubular body member. Couplers may be constructed of one or more materials such as polyurethane, steel, titanium, and polyethylene.

[0041] As used herein, the term “carrier arm” refers to a wire-like shaft capable of interfacing with electrodes and the coupler. A carrier arm is not limited to any size or measurement. Examples include, but are not limited to: stainless steel shafts; Nitinol shafts; titanium shafts; polyurethane shafts; nylon shafts; and steel shafts. Carrier arms can be entirely flexible, or may include flexible and rigid segments.

[0042] As used herein, the term “carrier arm bend point” refers to a joint (e.g., junction, flexion point) located on a carrier arm. The degree of flexion for a carrier arm bend point may range from 0 to 360 degrees. The bend portion can be manufactured such that when the carrier assembly is fully expanded the bend point is positioned in a relatively straight portion, a curved portion, or in a discrete transition from a first direction to a second transition, such as a 45 degree bend transition. The bend portion can include one or more flexing means such as a spring, a reduced diameter segment, or a segment of increased flexibility.

[0043] The present invention provides structures that embody aspects of the ablation catheter. The present invention also provides tissue ablation systems and methods for using such ablation systems. The illustrated and preferred embodiments discuss these structures and techniques in the context of catheter-based cardiac ablation. These structures, systems, and techniques are well suited for use in the field of cardiac ablation.

[0044] However, it should be appreciated that the invention is applicable for use in other tissue ablation applications

such as tumor ablation procedures. For example, the various aspects of the invention have application in procedures for ablating tissue in the prostate, brain, gall bladder, uterus, and other regions of the body, preferably regions with an accessible wall or flat tissue surface, using systems that are not necessarily catheter-based.

[0045] The multifunctional catheters of the present invention have advantages over previous prior art devices. **FIGS. 1-12** show various preferred embodiments of the multifunctional catheters of the present invention. The present invention is not limited to these particular configurations.

[0046] **FIG. 1** illustrates the treatment to be accomplished with the devices and methods described herebelow. **FIG. 1** shows a cutaway view of the human heart **1** showing the major structures of the heart including the right atrium **2**, the left atrium **3**, the right ventricle **4**, and the left ventricle **5**. The atrial septum **6** separates the left and right atria. The fossa ovalis **7** is a small depression in the atrial septum that may be used as an access pathway to the left atrium from the right atrium. The fossa ovalis **7** can be punctured, and easily reseals and heals after procedure completion. In a patient suffering from atrial fibrillation, aberrant electrically conductive tissue may be found in the atrial walls **8** and **9**, as well as in the pulmonary veins **10** and the pulmonary arteries **11**. Ablation of these areas, referred to as arrhythmogenic foci (also referred to as drivers or rotors), is an effective treatment for atrial fibrillation. Though circumferential ablation of the pulmonary vein usually cures the arrhythmia that originates in the pulmonary veins, it may result in eventual stenosis of these pulmonary veins, a very undesirable condition. The catheters of the present invention provide means of creating lesions remote from these pulmonary veins and their ostia while easily being deployed to ablate the driver and rotor tissue.

[0047] To accomplish this, catheter **100** is inserted into the right atrium **2**, preferably through the inferior vena cava **20**, as shown in the illustration, or through the superior vena cava **21**. Catheter **100** may include an integral sheath, such as a tip deflecting sheath, or may work in combination with a separate sheath. When passing into the left atrium, the catheter passes through or penetrates the fossa ovalis **7**, such as over a guide wire placed by a trans-septal puncture device. The catheter **100** carries a structure carrying multiple ablation elements such as RF electrodes, carrier assembly **120**, into the left atrium. Carrier assembly **120** is adapted to be deformable such that pressing carrier assembly into left atrial wall **9** will cause one or more, and preferably all of electrodes **130** to make contact with tissue to be analyzed and/or ablated. Each of the electrodes **130** is attached via connecting wires to an energy delivery apparatus, RF delivery unit **200** which is also attached to patch electrode **25**, preferably a conductive pad attached to the back of the patient.

[0048] RF delivery unit **200** is configured to deliver RF energy in monopolar, bipolar or combination monopolar-bipolar energy delivery modes. In a preferred embodiment, monopolar energy delivery is followed by bipolar energy delivery, which is then followed a period without energy delivery, such as a sequence in which the three steps are have equal durations. In another preferred embodiment, RF delivery unit **200** is configured to also provide electrical mapping of the tissue that is contacted by one or more electrodes

integral to carrier assembly **120**. Electrodes **130** can also be configured to be mapping electrodes and/or additional electrodes can be integral to carrier assembly **120** to provide a mapping function. Carrier assembly **120** is configured to be engaged over an endocardial surface to map and/or ablate tissue on the surface. RF energy is delivered after a proper location of the electrodes **130** is confirmed with a mapping procedure. If the position is determined to be inadequate, carrier assembly **120** is repositioned through various manipulations at the proximal end of the ablation catheter **100**. In another preferred embodiment, RF delivery unit **200** is configured to deliver both RF energy and ultrasound energy the identical or different electrodes **130**. In another preferred embodiment, RF delivery unit **200** is configured to accept a signal from one or more sensors integral to ablation catheter **100**, not shown, such that the energy delivered can be modified via an algorithm which processes the information received from the one or more sensors.

[0049] Referring now to **FIG. 2**, a preferred embodiment of ablation catheter **100** is illustrated. Ablation catheter **100** includes a tubular body member which is an elongated, flexible, hollow tube, catheter shaft **101**, that connects at its proximal end to handle **110**. The material used for the construction of the catheter shaft **101** and each component which resides or is configured to be inserted through a lumen integral to catheter shaft **101**, are selected to provide the suitable flexibility, column strength and steerability to allow percutaneous introduction of ablation catheter **100** to various body locations including the left or right atrium of the heart. Catheter shaft **101** and other tubular conduits of ablation catheter **100** are constructed of materials such as Pebax™; polyimide; polyurethane; silicone; nylon; polyvinyl chloride (PVC); polyester; and combinations thereof. These types of conduits may be constructed of an outer layer, an inner layer and a braid residing therebetween. The braid may be constructed of various materials including stainless steel; Nitinol; monofilament fiber; a polymer; and combinations thereof.

[0050] Control shaft **150** extends from the proximal end to distal end **102** of catheter shaft **101** and resides in a lumen therebetween. Control shaft **150** is also constructed of material to provide suitable flexibility and column strength to be percutaneously introduced into the patient as well as perform other functions such as the advancement and contraction of carrier assembly **120**. Applicable materials for control shaft **150** are Nitinol™; stainless steel; titanium; gold; platinum; copper; a polymer; a polymer embedded with conductive material; an elastomer; a plastic; and combinations thereof. In a preferred embodiment, control shaft **150** is constructed of both stainless steel and Nitinol. In another preferred embodiment, control shaft **150** is selected from the group consisting of: a monofilament fiber; a spring coil; a wire; and combinations thereof. In another preferred embodiment, control shaft **150** has a guidewire construction such as a core with a tightly coiled wire sheath, the sheath surrounding a substantial length of the core. In another preferred embodiment, the control shaft **150** includes a lumen from its proximal end and its distal end **102** such as to permit over-the-wire introduction via that lumen.

[0051] Coupler **140**, located at the distal end **102** of control shaft **150** connects control shaft **150** to carrier assembly **120**. Carrier assembly **120** is a flexible filamentous assembly that includes at least one ablation element, such as

electrode **130**, to deliver energy to tissue. Carrier assembly **120** includes one or more carrier arms **123**, each of which has a proximal arm segment **125** and a distal arm segment **127**, which are connected by a resiliently flexible segment, carrier arm bend portion **121**. Bend portion **121** may include various elements to assist in bending such as a spring; a hinge; a reduced diameter segment; a bend created during a heat treatment of a wire such as the “training” of a Nitinol wire; and combinations thereof. Bend point **121** provides means for rotatably joining the distal arm segment **127** to the proximal arm segment **125**. Carrier arms **123** are preferably constructed of a wire, such as a ribbon wire, and may have segments with different levels of flexibility. Bend point **121** may comprises two or more wires bonded together with a joint. Carrier arms **123** may include no ablation elements, such as a carrier arm **123** to provide support only. Carrier arms **123** may also include mapping electrodes, thermal sensors or other sensors, with or without the inclusion of ablation elements. In a preferred embodiment, each carrier arm **123** includes at least one ablation element.

[0052] Carrier assembly **120** can be configured to assume various geometries when in its expanded condition, such as the umbrella configuration of **FIG. 2** through **4**. Carrier assembly **120**, coupler **140** and control shaft **150** are configured such that control shaft **150** can be retracted to constrain carrier assembly **120** within a lumen of catheter shaft **101** and advancement of control shaft **150** causes carrier assembly **120** to advance beyond distal end **102** of control shaft **101** thus allowing carrier assembly **120** to deploy to its fully expanded condition. Coupler **140** is preferably more rigid than control shaft **150**. Control shaft **150** extends proximally to a location inside handle **110** where it is operably connected to knob **111** that slides in slot **112**. Alternative to sliding knob **111** is a rotating knob or a mechanical or electromechanical linear actuator, not shown. Sliding knob **111** is configured such that an operator of the system can with minimal effort advance and deploy carrier assembly **120** to its distal position where it is fully deployed for engagement with tissue, as well as retract and constrain carrier assembly within a lumen at the distal end **102** of catheter shaft **101**. One or more knobs can work in conjunction with a cam assembly, or a series of gears, both not shown, such that motion or force can be multiplied with the resultant mechanical advantage.

[0053] Each electrode **130** of carrier assembly **120** of ablation catheter **100** is connected to one or more wires, not shown but preferably extending from each electrode **130** of the distal arm segment **127**, running parallel with the segment toward the axis of distal end **102** of the catheter shaft **101**, then traveling proximally toward coupler **140** and then through catheter shaft **101** to handle **110**. The wires may pass through coupler **140**, along side coupler **140**, or may be electrically connected to coupler **140** such that these wires connect to wires on the proximal end of coupler **140**. The wires may be within a lumen internal to control shaft **150**, a space between control shaft **150** and catheter shaft **101**, and a separate lumen of catheter shaft **101**. The wires are looped within handle **110** to provide the distension necessary for the resilient deployment of carrier assembly **120** as illustrated in **FIG. 2**.

[0054] The electrode **130** wires provide a drive signal and a ground signal, or two or more alternating drive signals to each electrode **130**. Electrodes **130** can be wired indepen-

dently, such that each electrode **130** can deliver energy independent of any other electrode, or two or more electrodes can be connected in parallel or serial fashion. In a preferred embodiment, ablation catheter **100** and an energy delivery apparatus can be configured to drive two ablation elements, such as electrodes **130**, independently or simultaneously. Handle **110** includes RF attachment port **181** which can be connected to a separate energy delivery apparatus such as an RF delivery apparatus. Mapping port **182** is also included, which can be used to connect to a mapping device to assist in determining and/or confirming the proper ablation location. Handle **110** further includes button **116**, which is connected to switch means, not shown, for starting and/or stopping the delivery of energy to one or more of electrodes **130**. In an alternative embodiment, an energy delivery apparatus is integrated into handle **110** such that a separate apparatus and port **181** are not needed. In this configuration, handle **110** may include a plug, not shown, for attachment to a power supply or wall outlet. In another alternative embodiment, handle **110** includes an audible transducer, such as an audible transducer that is activated when energy is being delivered to tissue, or an alarm condition has been entered. In another alternative embodiment, handle **110** includes a power supply, such as a battery or rechargeable battery, both not shown. In another alternative embodiment, ablation catheter **100** includes one or more elements requiring power such as from an integrated battery, these elements selected from the group consisting of: an integral a light such as an LED; a display such as a liquid crystal display or touch screen display; an audible transducer; a tactile transducer such as a vibration transducer which readily alerts anyone holding the device; a relay such as a relay which disconnects power to one or more ablation elements; mapping circuitry embedded in one or more components of ablation catheter **100**, or electrode **130**; and combinations thereof.

[0055] Referring now to **FIG. 3**, an end view of the distal end of the catheter of **FIG. 2** is illustrated, showing the umbrella tip configuration. Four carrier arms **123** extend radially out from the central axis of catheter shaft **101**, the arms positioned in a symmetric configuration with equal angles (ninety degrees in a four arm configuration) between each arm. In alternative embodiments, three or more arms can be separated by different angles. The four carrier arms **123** are connected to coupler **140** which is concentric with the axis of catheter shaft **101** and connected to control shaft **150**, not shown. Each arm is shown with two electrodes **130** mounted to distal arm segment **127**, preferably 1-4 mm in length and distributed in a radial pattern covering a range from 1 cm<sup>3</sup> to 12 cm<sup>3</sup>. In a preferred embodiment, a first electrode is a different length than a second electrode.

[0056] Referring now to **FIG. 4**, an enlarged portion of the catheter of **FIG. 2** at circle “A” is illustrated. Control shaft **150**, which exits the distal end of catheter shaft **101**, is connected to coupler **140**. Carrier assembly **120** includes carrier arms **123**, each of which includes proximal arm segment **125** and distal arm segment **127**. One end of distal arm segment **127** is attached to coupler **140** with glue **141**, near to the central axis of catheter shaft **101**. In an alternative embodiment, the connection is made with a press fit or crimp. The other end of distal arm segment **127** transitions to proximal arm segment **125** through bend point **121**. The other end of proximal arm segment **125** attaches to the distal

end of control shaft **140** such as with glue, a circumferential band, or other attachment means at arm fixation portion **126**.

[0057] Electrodes **130** are mounted to distal arm segment **127** of carrier arms **123**. These electrodes can consist of wire coils; conductive plates; semiconductor plates; and combinations thereof. Each electrode is connected to one or more wires, each wire traveling from the electrode inward toward the axis of catheter shaft axis, and then proximal toward the end of control shaft **150**. The wires are joined in a bundle, wire bundle **151** which travels along side control shaft **150**. Wire bundle **151** may be glued or banded to control shaft **150** to avoid binding. In an alternative embodiment, wire bundle **151** travels internal to control shaft **150**.

[0058] Carrier arm **123** includes proximal arm segment **125** and distal arm segment **127**, carrier arm bend point **121**. In the configuration of **FIGS. 2 through 4**, each proximal arm segment **125** resiliently bends radially outwardly from coupler **140**, while each distal arm segment **127** bends radially inwardly from the bend point **121** toward the longitudinally axis of catheter shaft **101**. The distal arm segments **127** are shown to also tend proximally, and to establish an obtuse angle with the proximal arm segment **125** from which it extends, and the angle is small such that the distal end of the distal arm segment **127** is proximal to the carrier arm bend point **121**. In an alternative embodiment, the distal arm segments **127** are configured to tend distally, and to establish an obtuse angle with proximal arm segment **125**. Proximal arm segment **125** and distal arm segment **127** are preferably Nitinol wires, such as a continuous flat wire that also includes bend point **121**. The Nitinol wires can be trained to be flexible, but resiliently biases in a pre-determined shape. Wires are preferably of a non-circular cross-section such as an oval, rectangle, trapezoid or parallelepiped. The cross-section may vary along its length, and may be configured to cause preferential bending at a specific location and/or in a specific direction. In an alternative embodiment, proximal arm segment **125**, distal arm segment **127** and/or bend point **121** are comprised of a non-metallic material such as a plastic, a monofilament flexible fiber or other non-metallic material. In a preferred embodiment, carrier assembly **120** is constructed such that it is more flexible than control shaft **150**. In another preferred embodiment, carrier assembly **120** includes one or more wire segments, such as ribbon wire. In another preferred embodiment, carrier assembly **120** includes flat Nitinol wires.

[0059] Referring now to **FIGS. 5a through 5c** which illustrate the distal end of an ablation catheter of the current invention in various deployment conditions, specifically where carrier assembly **120** is in a fully deployed, partially constrained and fully constrained condition. Referring to **FIG. 5a**, carrier assembly **120** is shown with two carrier arms **123** with integral electrodes **130** aligned to form a linear lesion. The distal arm segments **127** are also aligned such as when the control shaft **150** is advanced pressing carrier assembly **120** against tissue. Carrier assembly **120**, when deployed and flattened against a surface such as an endocardial surface, is preferably about 15 to 30 mm in diameter (to the outer extent of the carrier arm), with each distal arm segment **127** being about 7 to 15 mm long. The wire width of carrier assembly **120** shafts are preferably about 0.26 mm, and the distal face of the electrodes is preferably about 1 to 2 mm wide, and 2 to 3 mm long. Carrier assembly **120** is shown with two carrier arms **123**,

however any number can be used, and each arm can carry one or more electrodes, or be void of electrodes. Bipolar RF energy may be applied pairs of the electrodes, including an electrode near the distal portion of the ablation catheter but not integral to the carrier assembly, or monopolar energy may be applied to any of the electrodes **130**, the energy grounded to a surface electrode or a return electrode located proximally on the catheter body. **FIG. 5b** shows an end view of the catheter of **FIG. 5a** in the same deployment condition. **FIG. 5b** depicts the two carrier arms **123** and the linear arrangement of electrodes **130**. **FIG. 5c** shows a condition in which carrier assembly **120** is partially constrained, such as when control shaft **140** is retracted and/or catheter shaft **101** is advanced. Coupler **140** is shown completely within the lumen of catheter shaft **101**, and an end of proximal arm segment **125** and an end of distal arm segment **127** is also within the lumen such that the other ends of proximal arm segment **125** and distal arm segment **127** are rotated inward toward the central axis of catheter shaft **101**. **FIG. 5d** shows the carrier assembly in a completely constrained condition, such as when control shaft **140** is further retracted and/or catheter shaft **101** is further advanced. Now both ends of proximal arm segments **125** and distal arm segments **127** are constrained within the lumen of catheter shaft **101**. The lumen of catheter shaft **101** and electrodes **130** are sized and shaped to allow carrier assembly **120** to be constrained within the lumen but permit easy advancement and retraction. In a preferred embodiment, control shaft **150**, coupler **140** and carrier assembly **120** can be fully removed from catheter shaft **101**, allowing reinsertion of an assembly with a different configuration of control shaft **150**, coupler **140** and/or carrier assembly **120**.

[0060] Referring now to **FIGS. 6 and 6a**, another preferred embodiment of ablation catheter **100** and ablation system of the present invention is illustrated. Catheter **100** includes carrier assembly **120** configured in another umbrella tip configuration. Carrier assembly **120** includes three carrier arms **123**, each of which includes two electrodes **130**. In an alternative embodiment, different patterns of electrodes are employed, and one or more arms may be void of electrodes. Referring back to **FIG. 6**, carrier arms **123** extend radially out from the central axis of the distal end of catheter shaft **101**. Each carrier arm **123** includes proximal arm segment **125** and distal arm segment **127**, these segments connected at a bendable joint, bend point **121**. In a preferred embodiment, proximal arm segment **125** and distal arm segment **127** and bend point **121** are a continuous resiliently flexible wire, such as a "trained" Nitinol wire which creates the umbrella tip. Each electrode **130** is mounted to an insulator, insulating band **131** such that the electrode is electrically isolated from the wire segments of carrier assembly **120**. Each electrode **130** is connected to wires which extend along shafts of carrier assembly **120**, toward a lumen of catheter shaft **101**, and proximally to handle **110**. These wires, not shown but described in detail hereabove, include insulation to electrically isolate one wire from another. One end of each distal arm segment **127** is attached to a cylinder, coupler **140**, which is sized to be slidably received within a lumen of catheter shaft **101**.

[0061] Referring again to **FIGS. 6 and 6a**, coupler **140** can be flexible or rigid, and may contain both rigid and flexible portions along its length. Coupler **140** may provide electrical connection means to connect wires extending from the handle to wires from carrier assembly **120** electrodes.

The ends of the distal arm segments **127** and the ends of the proximal arm segments **125** can be attached to the outside of coupler **140**, the inside of coupler **140** or both. Coupler **140** includes along its outer surface, a projection, projection **142**, which has a cross section profile which mates with a recess, groove **106** of catheter shaft **101** which prevents undesired rotation of carrier assembly **120**. In an alternative embodiment, catheter shaft **101** includes a projection, and coupler **140** includes a groove to accomplish a similar prevention of rotation. In another alternative embodiment, control shaft **150** additionally or alternatively includes a projection or other means to mate with catheter shaft **101** to prevent undesired rotation of carrier assembly **120**. As depicted in **FIG. 6a**, control shaft **140** includes a thru lumen, lumen **152**, such that ablation catheter **101** can be inserted over a guidewire (guidewire exit on handle **110** not shown). Additionally or alternatively, lumen **150** may include one or more wires or other filamentous conduits extending from proximal handle **110** a point more distal.

[0062] Control shaft **150** is mechanically attached to coupler **140**. Control shaft **150** extends proximally to handle **110** and is operably connected to knob **115** such that rotation of knob **115** from a deployed position to a withdrawn position causes carrier assembly **120** to be constrained within a lumen of catheter shaft **101**, and rotation of knob **115** from a withdrawn position to a deployed position causes carrier assembly **120** to extend beyond the distal end of catheter shaft **101** to be in an expanded condition. In a preferred embodiment, knob **115** is operably connected to control shaft **150** via a cam, or set of gears, not shown, to provide a mechanical advantage in the distance traveled by control shaft **150**.

[0063] Catheter shaft **101** is preferably part of a steerable sheath, steering mechanism not shown, and includes flush port **170**, which is configured to be attachable to a flushing syringe, used to flush blood and other debris or contaminants from the lumen of an empty catheter shaft **101** (wherein control shaft **150**, coupler **140** and carrier assembly **120** have been removed) or for flushing the space between control shaft **150** and the inner wall of catheter shaft **101**. Catheter shaft **101** is not connected to handle **110**, such that handle **110** can be withdrawn, removing control shaft **150**, coupler **140** and carrier assembly **120** from catheter shaft **101**. This configuration is useful when these components are provided in a kit form, including combinations of different versions of these components, the different combinations made available to treat multiple patients, or a single patient requiring multiple electrode patterns. A preferred example of a kit would include the catheter shaft **101** and flush port **170** of **FIG. 6** acting as a sheath; kitted with handle **110**, control shaft **150**, coupler **140** and umbrella tipped carrier assembly **120** of **FIG. 6** as well as handle **110**, control shaft **150**, coupler **140** and spiral tipped carrier assembly **120** of **FIG. 7**.

[0064] Also depicted in **FIG. 6** is a system of the present invention, including in addition to ablation catheter **100**, RF delivery unit **200**, a energy delivery apparatus of the present invention which connects to handle **110** with a multi-conductor cable **202** attached to RF attachment port **181**. RF delivery unit **200** includes user interface **201**, such as a user interface including data input devices like touch screens, buttons, switches, keypads, magnetic readers and other input devices; and also including data output devices like screens,

lights, audible transducers, tactile transducers and other output devices. User interface **201** is used to select electrodes to receive energy (electrodes **130** of carrier assembly **120**), set power levels, durations, threshold levels and other ablation and other parameters, initiate power delivery, deactivate an alarm condition and other functions common to electronic medical devices. In a preferred embodiment, RF delivery unit **200** also includes cardiac mapping means, such that mapping attachment port **182** can be attached to RF delivery unit **200** avoiding the need for a separate piece of equipment in the system. In another preferred embodiment, RF delivery unit **200** can also deliver ultrasound and/or another form of energy, such energy delivered by one or more additional ablation elements integral to carrier assembly **120**, additional ablation elements not shown. Applicable types of energy include but are not limited to: sound energy such as acoustic energy and ultrasound energy; electromagnetic energy such as electrical, magnetic, microwave and radiofrequency energies; thermal energy such as heat and cryogenic energies; chemical energy; light energy such as infrared and visible light energies; mechanical energy; radiation; and combinations thereof.

[0065] In a preferred embodiment, ablation catheter **100** includes an embedded identifier (ID), an uploadable electronic or other code, which can be used by RF delivery unit **200** to confirm compatibility and other acceptability of the specific catheter **100** with the specific RF delivery unit **200**. The electronic code can be a bar code, not shown, on handle **110** which is read by RF delivery unit **200**, an electronic code which is transferred to RF delivery unit **200** via a wired or wireless connection, not shown, or other identifying means, such as an RF tag embedded in handle **110**. In another preferred embodiment, RF delivery unit **200** also includes an embedded ID, such as an ID which can be downloaded to catheter **100** for a second or alternative acceptability check. The embedded ID can also be used to automatically set certain parameters or certain parameter ranges, and can be used to increase safety by preventing inadvertent settings outside of an acceptable range for the specific catheter **100**.

[0066] Handle **110** includes two push buttons, first button **116** and second button **117**. These buttons can be used to perform one or more functions, and can work in cooperation with user input components of user interface **201** such that commands entered into user interface **201** set the action taken when either or both button **116** and button **117** are pressed. In a preferred embodiment, both button **116** and button **117** must be pressed simultaneously to deliver energy to one or more ablation elements of catheter **100**. At the distal end of catheter shaft **101** is a circumferential band, band **104**. Band **104** is preferably a visualization marker, such as a radiographic marker, ultrasound marker, electromagnetic marker, magnetic marker and combinations thereof. In an alternative embodiment, band **104** transmits or receives energy, such as when the marker is used as a ground or other electrode during an ablation. In another alternative embodiment, band **104** is an antenna used to determine the position of the distal end of catheter shaft **101** or the location of another component in relation to band **104**. In another preferred embodiment, band **104** is used to store energy, such as capacitively stored energy that can be used to generate a magnetic field or to deliver ablation energy.



[0067] Referring now to **FIG. 7**, another preferred embodiment of ablation catheter **100** and ablation system of the present invention is illustrated comprising a catheter with a deflecting tip and a spiral tip carrier assembly. Catheter **100** includes carrier assembly **120** configured in a spiral tip configuration. Carrier assembly **120** includes a continuous wire construction such as a Nitinol wire that has been trained to be resiliently biased, at body temperature, in the spiral shape shown. Carrier assembly **120** includes multiple electrodes, mounted at equal distances from each other and electrically isolated to the wire of carrier assembly **120**. Wires, attached to each electrode but not shown, are also electrically insulated from each other and travel along the spiral to the coupler **140**, and then proximally to attachment means incorporated into handle **110**. In an alternative embodiment, different patterns of electrodes are employed, such as a pattern of electrodes placed along a set of radial projections from the center of the spiral. Electrodes **130** may be conductive plates, coils, or other applicable structures for deploying energy, such as RF energy to tissue, and carrier assembly **130** can consist of electrodes with different construction materials and/or geometries.

[0068] Referring back to **FIG. 7**, each end of the spiral carrier assembly **120** is attached to coupler **140** which is sized to be slidably received within a lumen of distal end **102** of catheter shaft **101**. Coupler **140** can be flexible or rigid, and may contain both rigid and flexible portions along its length. Coupler **140** may provide electrical connection means to connect wires extending from the handle to wires from carrier assembly **120** electrodes. The ends of spiral carrier assembly **120** can be attached to the outside of coupler **140**, the inside of coupler **140** or both. Coupler **140** may include anti-rotation means, not shown but described in detail in reference to **FIGS. 6 and 6a**. Control shaft **140** may include a thru lumen, also not shown, such that ablation catheter **101** can be inserted over a guidewire (guidewire exit on handle **110** not shown).

[0069] Coupler **140** is mechanically attached to control shaft **150** which is mechanically attached to coupler **140**. Control shaft **150** extends proximally to handle **110** and is operably connected to sliding knob **111**, wherein sliding knob **111** can be distally advanced or proximally retracted in slot **112**. Retraction of knob **111** from a distal position to a proximal position causes carrier assembly **120** to be constrained within a lumen at distal end **102** of catheter shaft **101**, and advancement of knob **111** from a proximal position to a distal position causes carrier assembly **120** to extend beyond distal end **102** of catheter shaft **101**, carrier assembly **120** resiliently expanding to its spiral shaped tip. In a preferred embodiment, knob **111** is operably connected to control shaft **150** via a cam, or set of gears, not shown, to provide a mechanical advantage in the distance traveled by control shaft **150**, or the force exerted on control shaft **150**.

[0070] Catheter shaft **101** is part of a steerable sheath, including pull wire **105** which is secured at one end to the distal end of control shaft **150** and at the other end is operably attached to knob **113**, wherein sliding knob **113** can be distally advanced or proximally retracted in slot **114**. The pull wire is operably connected to the control knob **113** so that sliding of the control knob pulls pull wire **105** to effectuate steering of the distal end **102** of control shaft **150**. Retraction of knob **113** proximally causes distal end of control shaft **150** to deflect and advancement of knob **113**

distally causes the distal end of control shaft **150** to straighten. Using knob **113**, the operator can steer the carrier assembly **120** as needed to contact different areas of the atrium wall or other tissue surface. The pull wire **105** may be unsecured to the control shaft **150** along much of its length, or it may be embedded in the control shaft **150** wall or otherwise restrained to the control shaft **150**. The entire distal end of the ablation catheter **100** may also be steered with pull wire **105**, as the catheter shaft **101** is sufficiently flexible that it will deform along with the control shaft **150**. In an additional or alternative embodiment, a second pull wire, not shown, is attached to the distal end of catheter shaft **101**, this pull wire similarly attached to control means included in handle **101**. In a preferred embodiment, knob **112** is operably connected to pull wire **105** via a cam, or set of gears, not shown, to provide a mechanical advantage in the distance traveled by pull wire **105**, or the force exerted on pull wire **105**. In an alternative or additional embodiment, a pull wire and handle control means can be connected to either catheter shaft **101** and/or control shaft **150** and/or coupler **140** and/or carrier assembly **120** at any location along their length, to cause a specific deflection pattern. In another preferred embodiment, the shaft to which the pull wire is attached includes multiple discrete levels of stiffness and/or variable levels of stiffness, near the attachment point, such that non-continuous bending occurs, i.e. bending with multiple radii or continuously variable radii.

[0071] Catheter shaft **101** includes flush port **170**, which is configured to be attachable to a flushing syringe, used to flush blood and other contaminants from the lumen of an empty catheter shaft **101** (wherein control shaft **150**, coupler **140** and carrier assembly **120** have been removed) or for flushing the space between control shaft **150** and the inner wall of catheter shaft **101**. In a preferred embodiment, catheter shaft **101** is not connected to handle **110**, such that handle **110** can be withdrawn, removing control shaft **150**, coupler **140** and carrier assembly **120** from catheter shaft **101**. This configuration is useful when these components are provided in a kit form, including combinations of different versions of these components, these different combinations made available to treat multiple patients, or a single patient.

[0072] Also depicted in **FIG. 7** is a system of the present invention, including in addition to ablation catheter **100**, RF delivery unit **200**, a energy delivery apparatus of the present invention which connects to handle **110** with a multi-conductor cable **202** attached to RF attachment port **181**. RF delivery unit **200** includes user interface **201**, such as a user interface including data input devices like touch screens, buttons, switches, keypads, magnetic readers and other input devices; and also including data output devices like screens, lights, audible transducers, tactile transducers and other output devices. User interface **201** is used to select electrodes to receive energy (electrodes **130** of carrier assembly **120**) and perform other functions as has been described in detail in reference to **FIG. 6**. In a preferred embodiment, RF delivery unit **200** can also deliver ultrasound and/or another form of energy, such energy delivered by one or more additional ablation elements integral to carrier assembly **120**, additional ablation elements not shown. Applicable types of energy include but are not limited to: sound energy such as acoustic energy and ultrasound energy; electromagnetic energy such as electrical, magnetic, microwave and radiofrequency energies; thermal energy such as heat and cryogenic energies; chemical energy; light energy such as

infrared and visible light energies; mechanical energy; radiation; and combinations thereof.

[0073] In a preferred embodiment, ablation catheter **100** and/or RF delivery unit **200** include an embedded identifier (ID), an uploadable or downloadable electronic or other code, which can be used by the system to confirm component compatibility and/or other acceptability of the specific catheter **100** with the specific RF delivery unit **200**. The electronic code and some of its uses have been described in detail in reference to **FIG. 6**.

[0074] Referring now to **FIGS. 8a** and **8b**, another preferred embodiment of the ablation catheter of the present invention is illustrated comprising a carrier assembly and control shaft that collectively consist of a continuous wire with one or more electrodes secured to a mid-portion of the wire. Depicted in **FIGS. 8a** and **8b** is the distal end **102** of catheter shaft **101** which includes lumen **107**, which extends from distal end **102** to a handle mounted on the proximal end of catheter shaft **101**, handle not shown but similar in construction and function to the handles of previous figures. Included within lumen **107** is a wire assembly which comprises the control shaft and carrier assembly of the present invention. The wire assembly includes wire **129'** with a first end and a second end, and wire **129''** with a first end and a second end (both first ends not shown), such that both the first end of wire **129'** and the first end of wire **129''** exit the proximal end of catheter shaft **101**, the mid-portion of the wire assembly comprising carrier assembly **120** which resides near the distal end **102** of the catheter shaft **101**. The wire assembly has a length such that when the mid-portion, carrier assembly **120**, fully resides distal to the distal end **102** of catheter shaft **101** and wire **129'** and wire **129''** travel proximally within lumen **107** of catheter shaft **101**, both the second end of wire **129'** and the second end of wire **129''** are proximal to the proximal end of the catheter shaft **101** (proximal end not shown).

[0075] Included in the carrier assembly **120** are four electrodes **130**, noting that one or more electrodes should be considered within the scope of this application. Carrier assembly **120** includes a carrier wire **128**, to which the electrodes **130** are mounted. Carrier wire **128** is preferably a non-conductive wire, such as a Teflon™ coated Nitinol wire, or a braided nylon line such that the electrodes can be electrically isolated from carrier wire **128**. Alternatively, each electrode **130** can include an insulator. At each end of carrier assembly **120**, carrier wire **128** transitions to wire **129'** and wire **129''** through transition point **122'** and transition point **122''** respectively. Depicted in **FIGS. 8a** and **8b** carrier wire **128** has a smaller diameter than wire **129'** and wire **129''**, such that wire **129'** and wire **129''** provides support of carrier assembly **120**, in the configuration illustrated, such that carrier assembly **120** can be "pushed" into tissue while carrier wire **128** flexes in response to the tissue interaction. In alternative embodiments, various diameters, including continuous diameters and varied diameters can be used for each of the three components including a different diameter for each as well as a single diameter for the three, for example a single diameter Nitinol wire making up wire **129'**, transition point **122'**, carrier wire **128**, transition point **122''** and carrier wire **129''**. In an alternative embodiment, carrier wire **128** is a different material, with the same diameter or a different diameter, than one or more of wire **129'** and wire **129''**. The carrier assembly **120** of **FIGS. 8a**

and **8b** is resiliently biased in a linear shape such that when carrier assembly **120** is fully exterior to lumen **107** of catheter shaft **101**, as depicted in **FIG. 8a**, carrier wire **128** is relatively perpendicular to the axis of catheter shaft **101** and electrodes **130** are in a linear pattern. In an alternative embodiment, carrier wire **128** has a resiliently biased bowed shape, such as a bowed in shape or a bowed out shape. In another alternative embodiment, the electrodes **130** lie in multiple planes.

[0076] Carrier assembly **120** can be constrained within lumen **107** catheter shaft **101** by retracting wire **129'**, wire **129''** or both. Utilizing control means incorporated into a handle, both not shown but described in detail in reference to previous figures, these advancements can be accomplished by an operator. Referring specifically to **FIG. 8b**, wire **129''** has been retracted such that transition point **122'** first enters lumen **107**. Continued retraction of wire **129''** causes carrier wire **128** and its electrodes **130** to enter lumen **107**, followed by transition point **122'** and a small segment of wire **129'**. Alternatively or additionally, wire **129''** can be retracted with a similar, symmetrical result, or both wires can be retracted in similar or dissimilar amounts wherein all described retractions cause carrier assembly **120** to be constrained with lumen **107** of catheter shaft. Performing the opposite step of advancing wire **129'**, wire **129''** or both wires, such as with the same control that retracted the one or more wires, will cause carrier assembly **120** to advance past distal end **102** of catheter shaft **101**, carrier assembly **120** then expanding to its resiliently biased condition. The ablation catheter of **FIGS. 8a** and **8b** does not include the coupler of **FIGS. 1 through 7**, although in an alternative embodiment, two couplers can be incorporated onto the ends of carrier wire **128** and on to wire **129'** and wire **129''**. In another alternative embodiment, the ablation catheter of **FIGS. 8a** and **8b** can include two wire assemblies, each including a separate carrier assembly each having ends attached to wires extending proximally. The multiple wire assemblies can have carrier assemblies with different or similar components and resiliently biased patterns of electrodes.

[0077] Referring now to **FIG. 9**, an ablation element of the present invention is illustrated. Electrode **130**, shown mounted to distal arm segment **127**, such as a distal arm segment **127** of **FIGS. 2 through 4**. Included in electrode **130**, is ultrasound crystal **132** and thermocouple **133**. Wires, now shown, are attached to electrode **130**, ultrasound crystal **132** and thermocouple **133**, and travel along distal arm segment **127**, to the lumen of the ablation catheter and proximally to the handle of the ablation catheter, all not shown. These wires interface with electronics within the handle and/or connected to a energy delivery apparatus, such as the RF delivery apparatus of **FIGS. 6** and **7**. The ultrasound crystal can be used to deliver ultrasound energy, simultaneous with or at a different time from RF energy being delivered to the tissue. Thermocouple **133** can be used to measure the temperature local to thermocouple **133** such as prior to, during or after the delivery of ablation energy. When an ablation is performed in the left atrium, such as the posterior wall of the left atrium, maintaining the tissue at a temperature below a threshold is needed. This wall is fairly thin, and the patient's esophagus lies immediately behind this wall. Ablation in this area entails a risk of perforating the atrial wall and the esophagus. In a preferred embodiment, information recorded from the thermocouple **133** is used to

adjust energy delivery such as to start or stop one or more energy deliveries, or to increase, decrease, modify the frequency of, modify the bipolar or monopolar delivery means, or otherwise adjust the energy delivery based on a determined temperature or temperature information analysis. In another preferred embodiment, energy delivery is ceased when information from the thermocouple is one or more of: higher than a threshold, lower than a threshold such as lower than expected body temperature; or when the information is unavailable such as when the thermocouple is non-functional. In another preferred embodiment, in addition or alternative to the ultrasound energy, another form of energy is delivered by electrode 130. In another alternative embodiment, ultrasound crystal 133 and electrode 130 are two discrete components, located in proximity to one another on distal arm segment 127.

[0078] Referring now to FIG. 10, an electrode assembly of the present invention is illustrated with electrode assembly 230 connected to power, signal and ground wires. Electrode assembly 230 includes a semiconductor substrate, such as a silicon substrate, in which is embedded numerous components fabricated using one or more of: integrated circuit fabrication machinery; Micro Electro-Mechanical Systems (MEMS) fabrication machinery; nano-system fabrication machines; other semi-conductor fabrication machinery; and combinations thereof. Electrode assembly 230 includes relay 236, which is configured to connect and disconnect ablation electrode 231 from an energy delivery apparatus connected to the ablation catheter to which electrode assembly 230 is a component. Other forms of relays can be integrated with multiple poles and multiple throws. Relays can connect and disconnect sources of signals and/or power. Multiple electrode assemblies 230 can be attached to a single, continuous ablation power wire and return ground greatly reducing the number of wires needed to travel from the proximal handle to the carrier assembly. Individual, or combination control of each ablation electrode 231 can be provided however, through opening or closing of relay 236 which is accomplished via timing circuitry 235. Control signals are sent to the embedded electronics of timing circuitry 235 such that digital or analog information can be transferred into logic that open and closed each relay 236, at precise times, and utilizing specific electronic identifiers embedded in each electrode assembly 230, can independently control all of the components of electrode assembly 230. Timing circuitry 235 can interpret signals that it receives from another electrode assembly 230, or a device external to the patient. Timing circuitry 235 can produce pulse-width modulated opening and closing of relay 236, or other sophisticated timing patterns which may be specific to the construction or makeup of electrode assembly 230.

[0079] Electrode assembly 230 further includes sensor 233, which can be an individual sensor or bank of multiple sensors such as a sensor to sense one or more of: chemical activity, light characteristic such as intensity or wavelength, electrical activity, pH, temperature, pressure, fluid flow or other physiologic parameter. Electrode assembly 230 further includes sensor interface 234 which includes various electronic components and circuitry such as circuitry created in various doping and other integrated circuit building processes used in a semiconductor substrate such as silicon. The information provided by sensor 233 can be processed by sensor interface 234 and/or by circuitry included in a proximal handle or energy delivery apparatus. This information

can be used to start, stop, increase, decrease or otherwise modify energy delivery or control another function of electrode assembly 230 or another function of the ablation catheter of the present invention.

[0080] Electrode assembly 230 further includes mapping electrode 232 which provides recording of electrical signals of the heart, such as signals used to identify rotors to be ablated during the procedure. In an alternative embodiment, ablation electrode 231 is used to record the electrical signals of the heart. Electrode assembly 230 further includes functional element 237, which may include integrated circuit components described above, as well as MEMS or nano-machine components that are well known to being integrated into semiconductor substrates using the appropriate machinery. A preferred embodiment of FIG. 10 is the incorporation of a MEMS valve which is used to control fluid flow, such as fluid flow to cool electrode assembly 230 and/or ablation electrode 231 or a valve used to control the flow of or release cryogenic fluid used to ablate tissue. In another preferred embodiment, a MEMS pump can be used to pump fluid, such as a drug or other chemical used to chemically create a lesion in tissue. In another preferred embodiment a MEMS linear actuator is incorporated to deploy one or more microneedles used to deliver a fluid such as the described drug. In another preferred embodiment, microcontroller or microprocessor circuitry is embedded in a semiconductor portion of electrode assembly 230 such that sophisticated signal processing and/or controlled loop delivery of energy can be configured such that complicated energy delivery can be used with one or more less sophisticated energy delivery apparatus.

[0081] Multiple semiconductor portions can be integrated into electrode assembly 230, such as portions which are connected with an insulating material and/or a flexible material providing a flexible joint between rigid portions of electrode assembly 230. Utilizing semiconductor technology and/or MEMS or other semiconductor fabrication means, numerous functions can be incorporated into electrode assembly 230 to improve therapeutic benefit of the procedure, provide enhanced safety to the procedure, or provide other therapeutic or non-therapeutic benefit to the patient or the operator of the system. In an alternative embodiment, the electrode assembly further comprises a cooling element, such as a heat sink, not shown.

[0082] Referring now to FIG. 11, an end view of another preferred embodiment of the carrier assembly of the present invention is illustrated comprising a carrier assembly in a spiral tip configuration. Carrier assembly 120, shown in its resiliently expanded condition, includes a single wire, carrier wire 128 which has a first end 143 and a second end 144. First end 143 is attached to coupler 140, travels radially out from the center axis of catheter shaft 101 and carrier wire 128 begins to travel along a continuously increasing radius creating a multiple loop spiral. After the creation of six spirals, carrier wire 128 travels radially in toward the central axis of catheter shaft 101, such that second end 144 also attached to coupler 140. Referring to FIG. 11a, a side view of the carrier assembly 120 of FIG. 11 is depicted in its fully expanded condition wherein the spirals lie in multiple planes. FIG. 11b illustrates a side view of an alternative embodiment of the carrier assembly of FIG. 11, in which the spirals of the carrier assembly 120, depicted in its fully expanded condition, lie in a relatively single plane. The

spirals of both **FIGS. 11a** and **11b** include one or more electrodes **130**. The length and diameter of the carrier wire **128**, as well as the size of the electrodes, are chosen such that the control shaft **140**, which is connected to carrier assembly **120** by coupler **140**, can be retracted such that the entire carrier assembly **120** appropriately folds and is constrained within a lumen of catheter shaft **101**.

**[0083]** Another alternative embodiment of the ablation catheter of the present invention is also depicted in **FIG. 11a** wherein means of anchoring the carrier assembly **120** to the tissue to be ablated is provided. In the center portion of the spiral, suction port **153** is provided. Suction port **153** is fluidly attached to control shaft lumen **152** which is also fluidly attached to a port on the proximal handle, not shown. A vacuum apparatus, such as a locking syringe, also not shown, when attached to the proximal handle, and the carrier assembly **120** is brought in contact with tissue; and the vacuum is generated such as drawing back the plunger of the syringe and locking the plunger, will cause the carrier assembly to be anchored to the tissue. This anchoring embodiment is of particular value when first performing an assessment such as a mapping procedure or other analysis from electrodes or other sensors; after which an ablation is to be performed in the same location. In an alternative embodiment, suction port **153** is replaced with a deployable tissue penetrating anchor, such as a corkscrew wire or barbed wire.

**[0084]** Referring now to **FIG. 12**, an end view of another preferred embodiment of the carrier assembly of the present invention is illustrated comprising a carrier assembly with multiple wires, each with a proximal end and a distal end, wherein each proximal end and each distal end is secured to coupler **140**. Carrier assembly **120** includes multiple carrier wires **128**, each with a flower petal or petaloid shape when fully expanded. Each end of carrier wire **128** is secured to coupler **140**, which is attached to a control shaft, not shown. The control shaft is sized to be slidably received by catheter shaft **101**. Carrier wires **128** include one or more electrodes, and one or more carrier wires **128** may include no electrodes, all electrodes not shown. The carrier wire length and diameter, as well as the size of the electrodes, are chosen such that the control shaft can be retracted such that the entire carrier assembly **120** appropriately folds and is constrained within a lumen of catheter shaft **101**. In an alternative embodiment, each proximal end of carrier wire assembly is attached to coupler **140**, and each distal end is attached near the distal end of catheter shaft **101**, such as within the lumen of catheter shaft **101**, such that retraction of the control shaft causes coupler **140** and carrier assembly **120** to reside within a lumen of catheter shaft **101**.

**[0085]** It should be understood that numerous other configurations of the systems, devices and methods described herein can be employed without departing from the spirit or scope of this application. It should be understood that the system includes multiple functional components, such as the ablation catheter and the energy delivery apparatus. The ablation catheter consists of a catheter shaft, a carrier assembly for providing electrodes in a resiliently biased configuration, a control shaft for deploying and withdrawing the carrier assembly, and a coupler for attaching the control shaft to the carrier assembly. The carrier assembly is a support structure which is shiftable from a storage or confined configuration, such as a radially constrained configura-

tion, to a deployed or expanded configuration. The carrier assembly can include wires, ribbons, cables and struts, made of either metals, non-metals or combinations of both. The carrier assembly can be constructed of one or more materials, including both metals and non-metals. Typical metals chosen for carrier assembly construction include but are not limited to: stainless steel, Nitinol, Elgiloy™, other alloys and combinations thereof.

**[0086]** The ablation catheter of the present invention may include a steerable outer sheath, or may work in conjunction as a system with a separate steerable outer sheath. One or more tubular components of the ablation catheter may be steerable such as with the inclusion of a controllable pull wire at or near the distal end. The ablation catheter of the present invention may be inserted over the wire, such as via a lumen within one of the tubular conduits such as within a lumen of the tubular body member or control shaft, or alternatively the catheter may include a rapid exchange sidecar at or near its distal end, consisting of a small projection with a guidewire lumen therethrough. A guidewire lumen may be included solely for the guidewire, or may provide other functions such as a vacuum lumen for an integral suction port integrated at the distal portion of the carrier assembly.

**[0087]** The ablation catheter of the present invention further includes ablation elements. In preferred embodiments, one or more ablation elements are electrodes configured to deliver RF energy. Other forms of energy, alternative or in addition to RF, may be delivered, including but not limited to: acoustic energy and ultrasound energy; electromagnetic energy such as electrical, magnetic, microwave and radio-frequency energies; thermal energy such as heat and cryogenic energies; chemical energy; light energy such as infrared and visible light energies; mechanical energy; radiation; and combinations thereof. One or more ablation elements may comprise a drug delivery pump or a device to cause mechanical tissue damage such as a forwardly advanceable spike or needle. The ablation elements can deliver energy individually, in combination with or in serial fashion with other ablation elements. The ablation elements can be electrically connected in parallel, in series, individually, or combinations thereof. The ablation catheter may include cooling means to prevent undesired tissue damage and/or blood clotting. The ablation elements may be constructed of various materials, such as plates of metal and coils of wire for RF energy delivery. The electrodes can take on various shapes including shapes used to focus energy such as a horn shape to focus sound energy, and shapes to assist in cooling such as a geometry providing large surface area. Electrodes can vary within a single carrier assembly, such as a spiral array of electrodes or a umbrella tip configuration wherein electrodes farthest from the central axis of the catheter have the largest major axis. Wires and other flexible conduits are attached to the ablation elements, such as electrical energy carrying wires for RF electrodes or ultrasound crystals, and tubes for cryogenic delivery.

**[0088]** The ablation elements requiring electrical energy to ablate require wired connections to an electrical energy power source such as an RF power source. In configurations with large numbers of electrodes, individual pairs of wires for each electrode may be bulky and compromise the cross-sectional profile of the ablation catheter. In an alternative embodiment, one or more electrodes, connected in

serial fashion such that a reduced number of wires, such as two wires, can be attached to two or more electrodes, include switching means such that while a first electrode is powered, the remaining electrodes do not transmit ablative energy. Switching means may be a thermal switch, such that as a first electrode heats up, a single pole double throw switch change state disconnecting power from that electrode and attaching power to the next electrode in the serial connection. This integral temperature switch may have a first temperature to disconnect the electrode, and a second temperature to reconnect the electrode wherein the second temperature is lower than the first temperature, such as a second temperature below body temperature. In an alternative embodiment, each electrode is constructed of materials in their conductive path such that as when the temperature increased and reached a predetermined threshold, the resistance abruptly decreased to near zero, such that power dissipation, or heat, generated by the electrode was also near zero, and more power could be delivered to the next electrode incorporating the above switching means.

[0089] The ablation catheter of the present invention preferably includes a handle activating or otherwise controlling one or more functions of the ablation catheter. The handle may include various knobs, such as rotating or sliding knobs which are operably connected to advanceable conduits, or are operably connected to gear trains or cams which are connected to advanceable conduits. These knobs, such as knobs use to deflect a distal portion of a conduit, or to advance or retract the carrier assembly, preferably include a reversible locking mechanism such that a particular tip deflection or deployment amount can be maintained through various manipulations of the system.

[0090] The ablation catheter may include one or more sensors, such as sensors used to detect chemical activity; light; electrical activity; pH; temperature; pressure; fluid flow or another physiologic parameter. These sensors can be used to map electrical activity, measure temperature, or gather other information that may be used to modify the ablation procedure. In a preferred embodiment, one or more sensors, such as a mapping electrode, can also be used to ablate tissue.

[0091] Numerous components internal to the patient, such as the carrier assembly or electrodes, may include one or more visual markers such as radiopaque markers visible under fluoroscopy, or ultrasound markers.

[0092] Selection of the tissue to be ablated may be based on a diagnosis of aberrant conduit or conduits, or based on anatomical location. RF energy may be delivered first, followed by another energy type in the same location, such as when a single electrode can deliver more than one type of energy, such as RF and ultrasound energy. Alternatively or additionally, a first procedure may be performed utilizing one type of energy, followed by a second procedure utilizing a different form of energy. The second procedure may be performed shortly after the first procedure, such as within four hours, or at a later date such as greater than twenty-four hours after the first procedure. Numerous types of tissue can be ablated utilizing the devices, systems and methods of the present invention. For example, the various aspects of the invention have application in procedures for ablating tissue in the prostate, brain, gall bladder, uterus, other organs and regions of the body, and a tumor, preferably regions with an

accessible wall or flat tissue surface. In the preferred embodiment, heart tissue is ablated, such as left atrial tissue.

[0093] In another preferred embodiment of the system of the present invention, an ablation catheter and a heat sensing technology are included. The heat sensing technology, includes sensor means that may be placed on the chest of the patient, the esophagus or another area in close enough proximity to the tissue being ablated to directly measure temperature effects of the ablation, such as via a temperature sensor, or indirectly such as through the use of an infrared camera. In the described system, when a temperature or a surrogate temperature reaches a threshold, such as an adjustable threshold, the ablation energy is reduced or stopped, to one or more ablation elements. The threshold will depend on the location of the sensor means, as well as where the ablation energy is being delivered. The threshold may be adjustable, and may be automatically configured.

[0094] Numerous kit configurations are also to be considered within the scope of this application. An ablation catheter is provided with multiple carrier assemblies. These carrier assemblies can be removed for the tubular body member of the catheter, or may include multiple tubular body members in the kit. The multiple carrier assemblies can have different patterns, different types or amounts of electrodes, and have numerous other configurations including compatibility with different forms of energy.

[0095] Though the ablation device has been described in terms of its preferred endocardial and transcatheter method of use, the array may be used on the heart during open heart surgery, open chest surgery, or minimally invasive thoracic surgery. Thus, during open chest surgery, a short catheter or cannula carrying the carrier assembly and its electrodes may be inserted into the heart, such as through the left atrial appendage or an incision in the atrium wall, to apply the electrodes to the tissue to be ablated. Also, the carrier assembly and its electrodes may be applied to the epicardial surface of the atrium or other areas of the heart to detect and/or ablate arrhythmogenic foci from outside the heart.

[0096] Other embodiments of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the invention being indicated by the following claims. In addition, where this application has listed the steps of a method or procedure in a specific order, it may be possible, or even expedient in certain circumstances, to change the order in which some steps are performed, and it is intended that the particular steps of the method or procedure claim set forth herebelow not be construed as being order-specific unless such order specificity is expressly stated in the claim.

#### 1. An ablation catheter, comprising:

- (a) an elongated, flexible, tubular body member having a proximal end, a distal end and a lumen extending therebetween;
- (b) a control shaft coaxially disposed and slidably received within the lumen of the Tubular Body Member;

- (c) a flexible carrier assembly which includes at least one ablation element used to deliver energy to tissue; and
  - (d) a coupler which connects the control shaft to the carrier assembly;
- wherein retraction of the control shaft causes the carrier assembly to be constrained within the lumen of the tubular body member; and
- wherein advancement of the control shaft causes the carrier assembly to extend beyond the distal end of the tubular body member.
2. The catheter of claim 1 wherein the control shaft can be completely removed from the lumen of the tubular body member.
3. The catheter of claim 1 further comprising a visualization marker surrounding the tubular body member near the distal end of said tubular body member.
- 4-5. (canceled)
6. The catheter of claim 3 wherein the band transmits energy.
7. The catheter of claim 3 wherein the band is an antenna.
8. The catheter of claim 3 wherein the band facilitates the storage of energy
9. The catheter of claim 8 wherein the band provides a capacitive storage of energy.
- 10-13. (canceled)
14. The catheter of claim 1 wherein the tubular body member includes means to deflect the distal end of said tubular body member.
- 15-20. (canceled)
21. The catheter of claim 1 wherein the tubular body member includes at least two pull wires used to deflect the distal end of said tubular body member.
22. The catheter of claim 21 wherein a first pull wire causes bending at a first deflection point and a second pull wire causes bending at a second deflection point.
23. The catheter of claim 1 wherein the tubular member further comprises a first segment with a specific flexibility and a second segment with a different flexibility, such that the pull wire causes said first segment to bend at a radius different than said second segment.
- 24-29. (canceled)
30. The catheter of claim 1 wherein the ablation catheter includes means to deflect the distal end of said control shaft.
31. The catheter of claim 30 wherein the ablation catheter further includes means to deflect the distal end of said tubular body member.
- 32-40. (canceled)
41. The catheter of claim 1 wherein the carrier assembly is configured to be engaged over an endocardial surface to map and/or ablate tissue on said surface.
42. The catheter of claim 1 wherein the carrier assembly includes a plurality of resilient arms, each arm having a proximal arm segment and a distal arm segment resiliently or rotatably joined to each other at a bend point.
- 43-44. (canceled)
45. The catheter of claim 1 wherein the carrier assembly is more flexible than the control shaft.
46. The catheter of claim 1 wherein the carrier assembly has a pre-determined shape such that advancement of the control shaft causes said carrier assembly to expand to said pre-determined shape as said carrier assembly extends beyond the distal end of the tubular body member.
47. The catheter of claim 46 wherein the pre-determined shape is a spiral shape.
48. The catheter of claim 46 wherein the pre-determined shape includes multiple loops that approximate a single plane.
49. The catheter of claim 46 wherein the pre-determined shape includes multiple loops that lie in multiple planes.
50. The catheter of claim 46 wherein the predetermined shape includes at least three arms, each of said arms extending radially outward from the central axis of the distal end of the tubular body member.
51. The catheter of claim 50 wherein one or more arms includes one or more electrodes, said one or more electrodes being between 1 and 4 millimeters in length.
52. The catheter of claim 46 wherein the pre-determined shape includes four or more arms, each of said arms extending radially outward from the central axis of the distal end of the tubular body member.
53. The catheter of claim 52 wherein one or more arms includes one or more electrodes, said one or more electrodes being between 1 and 4 millimeters in length.
54. The catheter of claim 53 wherein the pre-determined shape is an umbrella shape.
55. The catheter of claim 54 wherein the umbrella shape includes two arms extending radially outward from the central axis of the distal end of the tubular body member.
56. The catheter of claim 55 wherein at least one of the arms is void of ablation elements.
57. The catheter of claim 54 wherein the umbrella shape includes at least three arms extending radially outward from the central axis of the distal end of the tubular body member.
58. The catheter of claim 57 wherein at least one of the arms is void of ablation elements.
59. The catheter of claim 46 wherein the pre-determined shape is a pattern of petaloids.
60. The catheter of claim 1 wherein the carrier assembly includes a midsection including one or more ablation elements, said midsection including a support portion at each end.
61. The catheter of claim 60 wherein either support portion is more rigid than the midsection.
62. The catheter of claim 60 wherein the midsection has a pre-determined bowed shape.
63. The catheter of claim 62 wherein the bowed portion extends radially outward from distal end of the tubular body member.
64. The catheter of claim 62 wherein the bowed portion extends radially inward toward the distal end of the tubular body member.
- 65-73. (canceled)
74. The catheter of claim 1 wherein the carrier assembly includes two carrier arm bend points.
75. The catheter of claim 74 wherein a carrier arm bend point includes approximately a ninety degree bend.
76. The catheter of claim 75 wherein a carrier arm bend point is a spring.
- 77-78. (canceled)
79. The catheter of claim 1 wherein the carrier assembly includes one or more segments with a non-circular cross-section.
80. The catheter of claim 79 wherein the non-circular cross-section is selected from the group consisting of: oval; rectangular; trapezoidal; parallelepiped; and combinations thereof.

**81.** The catheter of claim 80 wherein the non-circular cross-section portion causes the carrier assembly to bend in one or more preferred directions.

**82.** The catheter of claim 1 wherein the carrier assembly comprises two or more wires.

**83.** The catheter of claim 82 wherein two or more wires each include one or more ablation elements.

**84.** The catheter of claim 82 wherein two or more wires are attached to the coupler.

**85.** The catheter of claim 84 wherein the two or more wires form petaloid shaped arcs.

**86.** The catheter of claim 1 wherein the ablation element is an electrode.

**87.** The catheter of claim 1 wherein the ablation element includes elements selected from the group consisting of: wire coils; conductive plates; semiconductor plates; and combinations thereof.

**88.** The catheter of claim 87 wherein the semiconductor plates further include embedded circuitry.

**89.** The catheter of claim 88 wherein the embedded circuitry perform one or more functions selected from the group consisting of: electromagnetic sensing; modified energy delivery; pulse width modulated energy delivery; temperature sensing; physiologic sensing; signal processing and closed loop energy delivery.

**90.** The catheter of claim 1 further comprising a second ablation element.

**91.** The catheter of claim 90 wherein each ablation element can be independently controlled to deliver energy.

**92.** The catheter of claim 91 wherein the first ablation element and second ablation element can deliver energy simultaneously.

**93.** The catheter of claim 90 wherein the first ablation element and the second ablation element are connected serially.

**94.** The catheter of claim 90 wherein the second ablation element is powered after the first ablation element is powered.

**95.** The catheter of claim 94 wherein the second ablation element is powered after the first ablation element reaches a pre-determined temperature.

**96.** The catheter of claim 95 wherein the conductivity of the first ablation element significantly increases when said first ablation element reaches the predetermined temperature.

**97.** The catheter of claim 90 wherein the carrier assembly has a pre-determined shape that includes one or more spiral loops, and two or more ablation elements are located along a single spiral loop.

**98.** (canceled)

**99.** The catheter of claim 1 further comprising two or more additional ablation elements.

**100.** The catheter of claim 99 comprising one or more wires extending from the proximal end of the tubular body member, said wires transmitting the energy to be delivered by the ablation elements.

**101.** The catheter of claim 100 wherein the number of delivery wires is less than the number of ablation elements.

**102.** The catheter of claim 99 wherein a first ablation element delivers one form of energy and a second ablation element delivers a different form of energy.

**103.** The catheter of claim 102 wherein the first ablation element delivers RF energy and the second ablation element delivers ultrasound energy.

**104-107.** (canceled)

**108.** The catheter of claim 1 wherein the ablation element is approximately two to eight millimeters long.

**109.** The catheter of claim 1 wherein the ablation element is a drug delivery device delivering chemical energy.

**110.** The catheter of claim 109 wherein the drug delivery device includes one or more needles.

**111.** The catheter of claim 1 wherein the ablation element is also a sensor.

**112.** The catheter of claim 111 wherein the ablation element can sense one or more parameters selected from the group of: chemical activity; light; electrical activity; pH; temperature; pressure; fluid flow or other physiologic parameter.

**113.** The catheter of claim 111 wherein the sensor is used to map electrical activity.

**114.** The catheter of claim 111 wherein the sensor comprises a thermocouple.

**115.** The catheter of claim 114 wherein ablation energy delivery is ceased when information received from the thermocouple is one or more of: higher than a threshold, lower than a threshold such as lower than expected body temperature; or when the information is unavailable such as when the thermocouple is non-functional.

**116.** The catheter of claim 1 wherein the delivered energy is selected from the group consisting of: sound energy such as acoustic energy and ultrasound energy; electromagnetic energy such as electrical, magnetic, microwave and radio-frequency energies; thermal energy such as heat and cryogenic energies; chemical energy; light energy such as infrared and visible light energies; mechanical energy; radiation; and combinations thereof.

**117.** The catheter of claim 116 wherein the energy consists of two or more types of energy.

**118.** The catheter of claim 116 wherein the energy delivered is electrical energy.

**119.** The catheter of claim 118 wherein the electrical energy is delivered using monopolar; bipolar; and a combination of monopolar and bipolar means.

**120.** The catheter of claim 119 wherein the electrical energy is delivered using both monopolar and bipolar energy delivered sequentially.

**121.** The catheter of claim 119 wherein the monopolar energy delivery is followed by bipolar energy delivery which is then followed by a period of zero energy delivery.

**122.** The catheter of claim 121 wherein the three phases of delivery are of equal time duration.

**123.** The catheter of claim 1 wherein a single ablation element delivers more than one type of energy.

**124.** The catheter of claim 1 wherein the tissue is cardiac tissue.

**125.** The catheter of claim 124 wherein the cardiac tissue is atrial wall tissue.

**126.** The catheter of claim 125 wherein the atrial wall tissue is left atrial wall tissue.

**127.** The catheter of claim 1 wherein the tissue is selected from the group consisting of: prostate; brain; gall bladder; uterus; tumor; and combinations thereof.

**128.** (canceled)

**129.** The catheter of claim 1 wherein the coupler includes an anti-rotation groove that mates with a projection extending radially inward from a wall of the tubular body member.

**130.** The catheter of claim 1 wherein the coupler includes an anti-rotation projection that mates with a groove extending radially outward from the inside wall of the tubular body member.

**131-132.** (canceled)

**133.** The catheter of claim 1 wherein coupler comprises a hollow cylinder with an inside wall and an outside wall, and wherein the carrier assembly includes one or more arms which are mounted to said outside wall of said cylinder.

**134.** The catheter of claim 133 wherein the carrier assembly further includes one or more arms which are mounted to the inside wall of the cylinder.

**135.** The catheter of claim 1 wherein the coupler comprises a hollow cylinder with an inside wall and an outside wall, and wherein the carrier assembly includes arms which are mounted to said inside wall of said cylinder.

**136.** The catheter of claim 135 wherein the carrier assembly further includes one or more arms mounted to the inside wall of the tubular body member.

**137.** The catheter of claim 1 wherein the coupler provides an electrical connection between wires extending from the proximal end of said catheter and wires extending from the carrier assembly.

**138.** The catheter of claim 1 wherein the retraction of the control shaft causes the carrier assembly to collapse inward as said carrier assembly is constrained within the lumen of the tubular body member

**139-149.** (canceled)

**150.** The catheter of claim 1 further comprising one or more sensing elements.

**151.** The catheter of claim 150 wherein the sensing element measure one or more of: chemical activity, light, electrical activity, pH, temperature, pressure, fluid flow or other physiologic parameter.

**152.** The catheter of claim 150 wherein the sensing element is used to map electrical activity.

**153.** The catheter of claim 150 wherein the sensing element includes a thermocouple used to measure temperature.

**154-160.** (canceled)

**161.** A system comprising the ablation catheter of claim 1, said system further comprising a heat sensing device.

**162.** The system of claim 161 wherein the heat sensing device is placed in the esophagus.

**163.** The system of claim 161 wherein the energy delivered is reduced when the heat sensing device detects a temperature above a pre-determined threshold.

**164.** The system of claim 163 wherein the threshold is adjustable.

**165.** A system comprising the ablation catheter of claim 1, said system further comprising an energy delivery apparatus that provides the energy to be delivered to the tissue.

**166.** The system of claim 165 wherein the ablation catheter further comprises an embedded ID.

**167.** The system of claim 166 wherein the ID is uploaded by the energy source.

**168.** The system of claim 167 wherein the ID corresponds to specific parameters for the energy source.

**169.** The system of claim 166 wherein the ID is embedded in one or more of the control shaft; the connector; and the carrier assembly.

**170.** The system of claim 169 wherein the ablation catheter further comprises a handle.

**171.** The system of claim 170 wherein the ID is embedded in the handle.

**172.** The system of claim 165 wherein the energy provided includes a first energy type and a second energy type.

**173.** The system of claim 172 wherein the first energy type and the second energy type are selected from the group consisting of: sound energy such as acoustic energy and ultrasound energy; electromagnetic energy such as electrical, magnetic, microwave and radiofrequency energies; thermal energy such as heat and cryogenic energies; chemical energy; light energy such as infrared and visible light energies; mechanical and physical energy; radiation; and combinations thereof.

**174.** An ablation catheter, comprising:

- an elongated, flexible, tubular body member having a proximal end, a distal end and a lumen extending therebetween;

- a control shaft coaxially disposed and slidingly received within the lumen of the tubular body member;

- a flexible carrier assembly mechanically attached to the control shaft, said carrier assembly including at least one ablation element used to deliver energy to tissue, said carrier assembly further comprising one or more flexible arms, each arm with a proximal portion, a distal portion and a hinged portion therebetween; wherein said proximal portion is attached to the distal end of the tubular body member and said distal portion is attached to the control shaft;

wherein retraction of the control shaft causes the carrier assembly to collapse inwardly such that the distal portion of the carrier assembly is constrained within the lumen of the tubular body member prior to the mid portion being constrained; and

wherein advancement of the control shaft causes the carrier assembly to extend beyond the distal end of the tubular body member.

**175.** The catheter of claim 174 wherein said catheter is advanced toward the tissue with a steerable sheath.

**176.** The catheter of claim 174 further comprising a coupler which connects the control shaft to the carrier assembly.

**177.** An ablation catheter, comprising:

- an elongated, flexible, tubular body member having a proximal end, a distal end and a lumen extending therebetween;

- a control shaft coaxially disposed and slidingly received within a lumen of the tubular body member;

- a flexible carrier assembly, mechanically attached to the control shaft, said carrier assembly including multiple ablation elements used to deliver energy to tissue;

said ablation elements connected in series such that power is delivered to each ablation element sequentially.

**178.** The catheter of claim 177 comprising four or more ablation elements and further comprising less than five energy delivery wires extending from the proximal end of the tubular body member to the ablation elements.

**179.** The catheter of claim 177 further comprising a coupler which connects the control shaft to the carrier assembly.



**180.** An ablation catheter, comprising:

an elongated, flexible, tubular body member having a proximal end, a distal end and a lumen extending therebetween;

two or more control shafts coaxially disposed and slidably received within the lumen of the tubular body member;

two or more flexible carrier assemblies each mechanically attached to a corresponding control shaft, each of said carrier assemblies including at least one ablation element used to deliver energy to tissue;

wherein retraction of each control shaft causes the connected carrier assembly to be constrained within the lumen of the tubular body member; and

wherein advancement of the each control shaft causes the corresponding carrier assembly to extend beyond the distal end of the tubular body member.

**181.** The catheter of claim 180 further comprising two or more connectors each of which connect each control shaft to a corresponding carrier assembly.

**182.** The catheter of claim 180 wherein each control shaft and corresponding carrier assembly can be completely retracted from the lumen of the tubular body member.

**183.** An ablation catheter, comprising:

an elongated, flexible, tubular body member having a proximal end, a distal end and a lumen extending therebetween;

a flexible control shaft coaxially disposed and slidably received within the lumen of the Tubular Body Member, said control shaft including a proximal end, a distal end, and a mid-portion;

at least one ablation element mounted in the mid-portion of said control shaft

wherein the proximal end of the control shaft resides outside the proximal end of the tubular body member, the control shaft extending distally through the lumen of the control shaft such that the control shaft mid-portion resides outside the distal end of the tubular body member; the control shaft then extending proximally such that the distal end of the control shaft resides outside the proximal end of the tubular body member.

wherein retraction of either the proximal and distal ends of the control shaft causes the mid-portion of the control shaft to be constrained within the lumen of the distal end of the tubular body member.

**184.** The catheter of claim 183 comprising multiple ablation elements.

**185.** The catheter of claim 184 wherein the multiple ablation elements reside in a linear pattern when the mid-portion of the control shaft is extended from the distal end of the tubular body member.

**186-188.** (canceled)

**189.** The catheter of claim 183 wherein retraction of both the proximal and distal ends of the control wire causes the mid-portion of the control shaft to be constrained within the lumen of the distal end of the tubular body member.

**190.** The catheter of claim 183 wherein advancement of the proximal and/or distal ends of the control wire causes the mid portion of the control shaft to transition from a constrained condition to an expanded condition as said mid-portion advances past the distal end of the tubular body member.

**191-254.** (canceled)

\* \* \* \* \*