

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 May 2009 (22.05.2009)

PCT

(10) International Publication Number
WO 2009/063132 A1

(51) International Patent Classification:

D21F 7/00 (2006.01) *D21G 3/04* (2006.01)
D21G 9/00 (2006.01)

Silva 255, CEP 18017-187 Sorocaba, Sp (BR). **MER-ILÄINEN, Pekka** [FI/FI]; Heinämutka 8 A 13, FI-40250 Jyväskylä (FI). **TOIVANEN, Anssi** [FI/FI]; Kumpulankuja 2, FI-40270 Palokka (FI).

(21) International Application Number:

PCT/FI2008/050649

(74) Agent: **KESPAT OY**; P.O.Box 601, FI-40101 Jyväskylä (FI).

(22) International Filing Date:

11 November 2008 (11.11.2008)

(25) Filing Language:

Finnish

(26) Publication Language:

English

(30) Priority Data:

20075808 14 November 2007 (14.11.2007) FI

(71) Applicant (for all designated States except US): **METSO PAPER, INC.** [—/FI]; Fabianinkatu 9 A, FI-00130 Helsinki (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **AURANEN, Tuomo Pekka** [FI/FI]; Kloorantie 3, FI-40800 Vaajakoski (FI). **EERIKÄINEN, Hannu** [FI/FI]; Tuulastie 3 B, FI-78250 Varkaus (FI). **HASSINEN, Reijo** [FI/FI]; Vuoritie 5, FI-41310 Leppävesi (FI). **KOLJONEN, Veli-Pekka** [FI/FI]; Kuhalantie 74, FI-44610 Kärnä (FI). **LAITINEN, Kari-Matti** [FI/FI]; Teljintie 3, FI-40530 Jyväskylä (FI). **LATIKKA, Pertti** [—/BR]; R.Marcolino Rodrigues da


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

(54) Title: A METHOD, A BLADE HOLDER AND A DOCTOR APPARATUS FOR DETACHING A WEB THREADING TAIL FROM A MOVING SURFACE IN A FIBER WEB MACHINE



(57) Abstract: The invention relates to a method for detaching a web threading tail from a moving surface in a fiber web machine. In the method the web threading tail (12) is detached from a moving surface (23) by means of air that flows from a blow-off blow channel (19) included in a blade holder (14), a trailing blow (26) is directed to the web threading tail (12) using air that flows from a trailing blow channel (17) included in the blade holder (14), the blade holder (14) includes a flow surface (32), and the trailing blow (26) is blown to the same direction with or in a small angle relative to the flow surface (32). The invention also relates to a corresponding blade holder and a doctor apparatus for detaching a web threading tail from a moving surface in a fiber web machine.

WO 2009/063132 A1

**A METHOD, A BLADE HOLDER AND A DOCTOR APPARATUS FOR DETACHING
A WEB THREADING TAIL FROM A MOVING SURFACE IN A FIBER WEB
MACHINE**

- 5 The invention relates to a method for detaching a web threading tail from a moving surface in a fiber web machine. The invention also relates to a corresponding blade holder and a doctor apparatus.
- 10 Various tail threading constructions are known in prior art. Of these, publications EP 0479748 and WO 97/23690 are mentioned here. Publication EP 0479748 proposes detachment of a web threading tail with an air blow, more precisely with a blow-off air blow. In addition to detachment of a web threading tail,
- 15 publication WO 90/02225 proposes blowing of a web threading tail into contact with a fabric by means of trailing blows. With these systems, a web threading tail can be detached from a roll surface and blown into contact with the fabric with trailing blow means. Trailing blows are difficult to orientate.
- 20 In addition, the effect of trailing blows is of a short duration. On the other hand, the blow-off blow created by the blow-off air and the trailing blow created by the trailing air disturb each other.
- 25 The object of the invention is to provide a novel method which avoids the above mentioned problems and can be used to guide the web threading tail more accurately and over a longer distance. The characteristic features of this invention are that
- 30 - a web threading tail is detached from a moving surface using air that flows from a blow-off blow channel included in a blade holder,
- a trailing blow is directed to the web threading tail using air that flows from a trailing blow channel included in the blade holder,

- the blade holder includes a flow surface, and the trailing blow is blown parallel with or in a small angle relative to the flow surface.

5 Another object of the invention is to provide a novel blade holder which can be used to guide a web threading tail as desired even over a relatively long distance. The characteristic features of this invention are that the blade holder frame includes

- 10 - a blow-off blow channel with air flowing therefrom being adapted to generate a blow-off blow for detaching a web threading tail from a moving surface in a fiber web machine,
- a trailing blow channel with air flowing therefrom being adapted to generate a trailing blow for guiding the web threading tail further, and
15 - a flow surface relative to which the trailing blow is adapted to flow parallel with or in a small angle.

Still another object of the invention is to provide a novel doctor apparatus which allows guiding a web more extensively than before. The characteristic features of this invention are that

the blade holder frame includes

- 25 - a blow-off blow channel with air flowing therefrom being adapted to generate a blow-off blow for detaching a web threading tail from a moving surface in a fiber web machine,
- a trailing blow channel with air flowing therefrom being adapted to generate a trailing blow for guiding the web threading tail further, and
30 - a flow surface relative to which the trailing blow is adapted to flow parallel with or in a small angle.

A web threading tail formed from a web is guided in a fiber web machine for threading the web. The web refers to board and
35 paper webs. In turn, the web forming machine refers to fiber web machines used for producing paper or board. In the method,

a web threading tail is detached from a moving surface in a fiber web machine. More precisely, a web threading tail is detached from a moving surface using air that flows from a blow-off blow channel included in a blade holder. A trailing
5 blow is directed to the web threading tail using air that flows from a trailing blow channel included in the blade holder. The blade holder includes a flow surface, and the trailing blow is blown parallel with or in a small angle relative to the flow surface. Web threading to one or more machine sections of a
10 fiber web machine is performed using a narrow web threading tail. The sections can be a dryer section, a calender and a coating station, for example. Once threading is successfully carried out, the narrow web threading tail is widened to the full width for starting the production. The web threading tail
15 is detached from a moving surface with release means for the web threading tail. The moving surface can be, for example, a roll surface or a cylinder surface. Doctoring can be performed using merely air, but a mechanical doctor can be used along with air doctoring. In case a combination of air doctoring,
20 i.e. an air blade, and mechanical doctoring, i.e. a mechanical blade, is used for detaching the web threading tail, the air blade, i.e. a blow-off blow, is located before the mechanical blade in the rotation direction of a roll. The blow-off blow is oriented against the tail travel direction and directed near to
25 the contact point of the mechanical blade and the roll surface. Thus an air blade is typically sufficient for detaching the web threading tail from the vicinity of a moving surface whereby a mechanical blade serves as backup. In other words, the web threading tail is in contact with the moving surface from which
30 it is detached with an air blow. The mechanical blade is used to detach the web threading tail from the moving surface if the tail is still attached to the moving surface at the mechanical blade. Trailing blow means are used to direct a trailing blow to the web threading tail. In other words, air is blow with the
35 trailing blow means towards the travel direction of the web threading tail whereby a trailing blow is generated. Blowing

air towards the travel direction of the web threading tail means that the trailing blow has a component that is directed to the travel direction of the tail. The blade holder includes a flow surface, and the trailing blow means are used to blow the trailing blow parallel with or in a small angle relative to the flow surface. In other words, the trailing blow means are used to blow air substantially parallel with the flow surface included in the blade holder. A flow surface refers to a surface to the direction of which web guiding is started. The flow surface is a part of the blade holder; for example, a surface of a flow deflector included in the blade holder or directly a surface of the blade holder. Thus, in the vicinity of, i.e. beside the flow surface, a so-called Coanda effect is created in which the blown air is bent conforming to the surface by the internal viscosity. The flow surface is thus a surface in the vicinity of which the trailing blow creates a flow conforming to the Coanda effect. Furthermore, air conforming to the surface guides the web. Thus the web does not contact the blade holder, but, on the other hand, the web can be controllably guided over a long distance. In other words, blowing occurs substantially parallel with the flow surface, i.e. to the same direction or in a small angle relative to the flow surface, when a guiding flow is created in the vicinity of the flow surface utilizing a Coanda effect for guiding the web threading tail.

In an embodiment, the trailing blow is blown parallel with or in a small angle relative to the flow surface in two different positions. In other words, air is blown substantially parallel with the travel direction of the web threading tail, i.e. to the same direction or in a small angle relative to the flow surface, in two positions. There may be more than two positions. Two positions from which air is blown enable creating a Coanda effect over a longer distance in the vicinity of, i.e. beside the flow surface. In addition, multiple positions in the web travel direction enable multiple pressure zones in the web

travel direction whereby web guiding is more accurate than before.

In another embodiment, the blade holder is turned around the pivot point and the pivot point is in the web travel direction, after the first trailing blow channel. In case of multiple trailing blow channels, a trailing blow channel is preferably between trailing blow channels. When the blade holder is turned relative to such a pivot point which is located after the first trailing blow channel in the web travel direction or between trailing blow channels, very controllable turning is achieved. In addition, the blade holder can then be located in very many different positions.

In a third embodiment, pressure lower than the environment is created between the blow-off blow and the trailing blow. A lower pressure is generated when air flowing from the blow-off blow channel and air discharging from the trailing blow channel both draw air ejector-like from the zone between the blow-off blow and the trailing blow.

In a fourth embodiment, a mechanical blade is loaded with a presser means. In addition, a blow-off blow comes from the vicinity of the presser means for detaching a web threading tail from a moving surface. In other words, a blow-off blow comes from the presser means or passing by one of its surfaces. Then the blow-off blow is in contact with the presser means. In this case, the release means for the web threading tail include an air blade and a mechanical blade that are set very close to each other. Additionally, the blow-off blow can be directed accurately to the desired location since the presser means extends close to the tip of the mechanical blade.

In a fifth embodiment, a blow-off blow comes from a presser means for detaching a web threading tail from a moving surface. When the blow-off blow comes from within a presser means, it is

possible to use a standard blade, i.e. a conventional mechanical blade. In this way an advantageous entirety is achieved as regards costs. In this embodiment, fewer separate components are needed than before.

5

In a sixth embodiment, a trailing blow comes from a presser means substantially parallel with the flow surface. The trailing blow coming from a presser means enables guiding the web threading tail even earlier. In this case the web threading
10 tail is guided with the trailing blow in very close vicinity to the tip of the mechanical blade.

In a seventh embodiment, the doctor apparatus includes a mechanical blade. The presser means loading the mechanical
15 blade is a presser plate. In addition, a blow-off blow comes from between the mechanical blade and the presser plate for detaching a web threading tail from a moving surface. This embodiment enables using a relatively thin presser plate creating a blow-off blow in connection with the mechanical blade.
20 In other words, a blow-off blow goes beside the mechanical blade. In this case, air flows from between the mechanical blade and the presser plate. The entirety includes both a mechanical blade and an air blade. With air blowing from between the mechanical blade and the presser plate, the air flow
25 can be directed precisely to the desired point. With air blowing from between the mechanical blade and the presser plate, a construction external to the blade holder, which disturbs the travel of the web threading tail past the flow surface, is also avoided.

30

The invention is described below in detail by making reference to the enclosed drawings, which illustrate some of the embodiments of the invention, in which

35 Figure 1a shows a doctor apparatus according to the invention in connection with a double-fabric run,

Figure 1b shows doctor apparatus according to the invention in connection with a double-fabric run,

Figure 2a is a side view of a blade holder according to the invention,

5 Figure 2b is a top view of a blade holder according to the invention,

Figure 2c is a side view of a blade holder according to the invention,

10 Figure 2d is a side view of a blade holder according to the invention,

Figure 2e shows a blade holder according to the invention supported to the frame of a fiber web machine,

Figure 3a shows a doctor apparatus according to the invention,

15 Figure 3b shows a mechanical blade with a presser plate used in a doctor apparatus according to the invention,

Figure 4 shows another doctor apparatus according to the invention,

20 Figure 5 shows a third doctor apparatus according to the invention,

Figure 6 shows a fourth doctor apparatus according to the invention,

Figure 7 shows a fifth doctor apparatus according to the invention,

25 Figure 8 shows a slit nozzle casing in connection with a mechanical blade,

Figure 9 shows another slit nozzle casing in connection with a mechanical blade,

30 Figure 10a shows a third slit nozzle casing in connection with a mechanical blade, and

Figure 10b shows the mechanical blade of Figure 10a as seen from the side of the slit nozzle casing.

35 Figure 1 shows a doctor apparatus 10 according to the invention for detaching a web threading tail from a moving surface in a fiber web machine. The doctor apparatus 10 includes an adjusta-

ble blade holder 14. The blade holder 14 has a frame 71. Air comes from the blade holder frame creating a blow-off blow 27 for detaching a web threading tail 12 from a moving surface 23 in a fiber web machine. Air also comes out of the blade holder frame creating a trailing blow 26 to guide the web threading tail 12 further. The turning blade holder 14 includes a flow surface 32 relative to which the trailing blow 26 is adapted to flow parallel with or in a small angle. When the turning blade holder includes a flow surface, the flow surface turns with the blade holder.

Figure 1a shows a doctor apparatus 10 according to the invention in a dryer section of a fiber web machine in connection with a double fabric run 74. The doctor apparatus 10 is used to detach a web threading tail 12 from a moving surface 23 in the fiber web machine. The doctor apparatus 10 includes release means 11 for the web threading tail 12 and trailing blow means 29. The release means 11 are used to detach the web threading tail 12 formed out of the web from the moving surface 23, which is typically a roll surface or a cylinder surface 21. The trailing blow means 29 are adapted to form a trailing blow 26. In addition, the doctor apparatus 10 includes a flow surface 32, and the trailing blow means 29 are so directed that the trailing blow 26 generated by these is adapted to flow substantially parallel with the flow surface 32. With air flowing parallel with the flow surface, the doctor apparatus can guide the web threading tail and transport it further assisted by a Coanda effect.

The doctor apparatus 10 shown in Figure 1a includes release means 11 for the web threading tail 12 and trailing blow means 29. The trailing blow means 29 consist of a nozzle channel assembly formed by nozzle channels 30. From the nozzle channel 30, air is adapted to flow to generate a trailing blow 26 headed to the travel direction 42 of the web threading tail 12. The trailing blow means 29, more precisely the nozzle channels

30, are adapted to generate a trailing blow which is substantially parallel with the flow surface 32.

The release means included in the doctor apparatus shown in Figure 1a include a mechanical blade 16 and a blow channel for generating a blow-off blow 27. The purpose of the blow-off blow 27 is to detach the web threading tail. If the web threading tail is allowed to travel until to the mechanical blade, the mechanical blade will detach the web threading tail.

In the doctor apparatuses according to the invention shown in Figure 1a, the flow surface 32 is a surface 44 of a separate flow deflector 43. Thus the flow surface can be formed in a desired location irrespective of the blade holder position. Moreover, the fastening position of the blade holder can be freely selected.

In the doctor apparatuses 10 shown in Figure 1a, an air channel 22 is included within the blade holder 14. When the air channel is placed within the blade holder, the air channel is protected against impurities. In other words, the air channel does not form a profile in the blade holder which would collect dirt. When the blade holder is of a composite material, an air channel can be formed inside the blade holder already during the manufacturing stage, in which case the entirety is simple to manufacture.

Figure 1b shows a doctor apparatus 10 in a dryer section of a fiber web machine for detaching a web threading tail 12 from a moving surface 23. The doctor apparatus 10 includes an adjustable blade holder 14. By the adjustability of a blade holder, it is referred to that the blade holder can be turned and thus loaded relative to the moving surface included in a dryer section, typically relative to a cylinder included in a dryer section. In addition, the blade holder 14 further includes a blow-off blow channel 19, a trailing blow channel 17 and a flow

surface 32. More precisely, the blade holder includes a blow-off blow channel 19 with air flowing therefrom being adapted to generate a blow-off blow 27 for detaching the web threading tail 12 from a moving surface 23 in a fiber web forming machine. A blade holder is used here extensively to refer to blade holders in which the blade can be an air blade or an air blade combined with a mechanical blade. An air blade or an air doctor is used to doctor off a web threading tail from a moving surface. The trailing blow channel 17 included in the blade holder is a trailing blow channel 17 with air flowing therefrom being adapted to generate a trailing blow 26 for guiding the web threading tail 12 further. The flow surface 32 included in the blade holder 14 is a flow surface 32 relative to which the trailing blow 26 is adapted to flow parallel with or in a small angle, i.e. substantially to the same direction.

In the doctor apparatus 10 shown in Figure 1b, more precisely in the blade holder 14, trailing blow means 29 are located in two positions in the travel direction 2 of the web threading tail 12. This embodiment is particularly advantageous in connection with a double-fabric run 74, in which the web threading tail must be guided for a long distance separated from the fabric.

Figure 1b shows a section of a double-fabric run 74 in connection with which a doctor apparatus 10 according to the invention is advantageously used. The release means 11 for the web threading tail 12 included in the doctor apparatus 10 are a combination of an air blade 68 and a mechanical blade 16. Thus the air blade 68 formed by the blow-off blow 27 coming from the blow channel, i.e. the release blow channel 19, is located in the travel direction 42 of the web threading tail 12 prior to the mechanical blade 16. Typically an air blade is sufficient for detaching the web threading tail from the vicinity of a roll surface. The air blade 68 formed by the blow-off blow 27

coming from the air-blow channel 38 is directed towards an opening nip 78 between the web and the roll surface.

Figure 2a shows a blade holder 14 according to the invention for a fiber web machine, seen from the side of the blade holder. The blade holder 14 includes a frame 71. In addition, the frame 71 of the blade holder 14 includes a blow-off blow channel 19, a trailing blow channel 17, and a flow surface 32. Air blowing out from the blow-off blow channel 19 is adapted to generate a blow-off blow 27 for detaching a web threading tail from a moving surface in a fiber web machine. Air blowing out from the trailing blow channel 17 is adapted to generate a trailing blow 26 for guiding the web threading tail further. The trailing blow 26 is adapted to flow parallel with or in a small angle relative to the flow surface 32. When the blade holder frame includes a blow-off blow channel, a trailing blow channel and a flow surface, a compact entirety for guiding a web threading tail is achieved. This compact application can be very freely located in many positions in a fiber web machine.

20

The blow-off blow channels 19 included in the blade holder 14 shown in Figure 2a open to a surface of the blade holder as blow-off blow openings 45, which are visible in Figure 2b. Correspondingly, the trailing blow channels 17 included in the blade holder 14 shown in Figure 2a open to a surface of the blade holder as trailing blow openings 35, which are visible in Figure 2b. The blade holder also includes air channels 22, from which air is guided further to the blow-off blow channels and the trailing blow channels. The air channels 22 are continuous in the cross-direction (CD) of the blade holder 14, which is also the cross-direction of the fiber web machine. The trailing blow channels, in turn, which open to a surface of the blade holder as trailing blow openings, are separate in the cross-direction. Correspondingly, the blow-off blow channels, which open to a surface of the blade holder as blow-off blow openings, are separate in the cross-direction. Both the trai-

35

ling blow channels and the blow-off blow channels can be manufactured by drilling. Generally, it can be stated that the blade holder of Figure 2a is shown in Figure 2b from another direction.

5

As shown in Figure 2a, the flow surface 32 is flat. Advantageously, the height of the trailing blow openings 25 in the flat flow surface 32 is over 50%, advantageously over 70% of the height of an air-blow shoulder 37 provided in the flow surface 32. Except for the air-blow shoulders, the flow surface is flat excluding minimal surface differences due to the material and the manufacturing method. As such, the air blow surface can curve for guiding a web threading tail as desired. However, the flow surface is advantageously substantially straight as shown in Figure 2a.

15

Figures 2c and 2d show a blade holder according to the invention having a flow surface 32 and further a blade holder 14 that include several flow supports 70 connected to each other. In other words, the flow surface 32 is composed of several flow supports 70 which are connected to each other. Flow supports that are connectable to each other enable forming a flow surface with a desired length in connection with a standard main component even during the installation.

25

The flow support 70 included in the blade holder 14 shown in Figures 2c and 2d has a trailing blow channel 17 with air flowing therefrom being adapted to generate a trailing blow 26 for guiding the web threading tail further. When the flow surface is composed of several flow supports with trailing blow channels, a notably long flow surface can be assembled from the flow supports for guiding the web threading tail. A required number of flow supports are thus connectable to the blade holder whereby a flow surface of a desired length can be formed in the blade holder. When the flow supports are provided with trailing blow channels, the flow remains intensive even in

35

connection with a long flow surface assembled from flow supports. Thus the web threading tail can be guided as desired also for a long distance.

5 In the blade holders shown in Figures 2c and 2d, trailing blow channels 17 are located in two positions in the travel direction of the web threading tail. Several trailing blows enable guiding the web over a long distance without the blow weakening.

10

In the blade holder shown in Figures 2c and 2d, a guide surface 69 is included between the blow-off blow 27 and the trailing blow 26. A vacuum is created in connection with the guide surface or a vacuum surface, since there are blows with a different direction along both of its sides. As the blow-off blow 27 and the trailing blow convey air ejector-like to the relative directions, a depressurized guiding surface is created between them. For maintaining the vacuum or the pressure drop, the guide surface must be substantially flat. Advantageously, the guide surface is straight or almost straight. When the guide surface is flat, the pressure will not escape as described above, and the web will not bump into projections in the surface. Thus a flat surface cannot have pipes or similar projections.

25

In the blade holder according to the invention shown in Figures 2c and 2d, the angle α between the blow-off blow 27 and the trailing blow 26 is over 130° , advantageously over 150° . Thus the blow-off blow and the trailing blow enable both detaching the web threading tail from a moving surface and guiding the tail forward as desired. For example, the angle can be a straight angle 180° . When the blade holder is straight, considering also the flow surface portion of the blade holder, the maximum angle is typically 200° , advantageously 190° . The angle can exceed 180 degrees even in connection with a straight blade holder since the blow-off blow can be directed towards the

35

mechanical blade. With mechanical blades, conventional doctor blades are referred to, in which the doctoring result is based on a mechanical contact. Another example of an angle exceeding 180 degrees is in the condition of Figures 4 and 5 where the flat flow surface becomes curved. In these figures the angle is between 180° and 190°. In connection with a curving surface, the angle as such can exceed 200°, being for example 220°.

In Figure 2d, the fastening position 76 of the shaft 77 is a detachable fastening position 76', a part of the blade holder. The fastening position includes fastening positions for bolts, for example, by which the fastening position can be connected to the rest of the blade holder. Such an embodiment enables connecting different fastening positions for shafts in the same main component of a blade holder.

Figure 2e shows a blade holder 14 according to the invention including a fastening position 76 for a shaft 77. The shaft 77 and further the blade holder 14 are turned with a turning actuator 79. The turning actuator can be, as known in prior art, a pneumatic cylinder or a hydraulic cylinder, for example. The shaft thus functions as a bracket with which the blade holder turns. The shaft is fastened to the frame component 39 of the fiber web machine via bearings 41. In other words, the shaft is mounted with bearings to turn in a fiber web machine and to keep in place in the blade holder. Without a bearing assembly between the blade holder and the shaft, the blade holder can be very thin at the shaft as well. Even more essential is that loading the blade holder via the shaft is simple. Moreover, the cylinder can be taken out from between moving surfaces, i.e. cylinders.

Generally, it can be stated that a blade holder refers to a construction which becomes an air blade. In addition, the blade holder can have a mechanical blade connected thereto. The thickness of the blade holder is below 100 mm, advantageously

below 80 mm, which is shown in Figure 2a. Such a thickness enables locating the blade holder in very many places. The thickness of the blade holder refers to the maximum thickness of the blade holder, i.e. the maximum distance between the flow surface 32 and the background surface 47. In addition, the average thickness b of the blade holder 14 is below 90, advantageously below 70 mm. The doctor of Figure 3a has correspondingly a thickness a and an average thickness b. In addition, the doctor of Figure 3a is curved over its surface although the surface as such is flat.

The blade holder 14 shown in Figure 2 is made of an aluminum profile 75. The construction of the aluminum profile is shown in more detail in the combination of Figures 2a and 2b. Generally, the blade holder is of solid aluminum excluding the cross-directional air channels and machine-directional bores for air-blows formed during casting. In addition, cut-outs have been made in the aluminum profile for a mechanical blade, for example. A cross-directional hole is also provided for a shaft. In addition, holes and cut-outs can be provided for connecting flow supports to each other, for example. Air channels 22 can be relatively small since they are completely sufficient for conveying the required volume of air. Generally, the flow surface including a desired number of flow supports is very flat and straight, i.e. linear. Associated with the flow surface, there are after all trailing blows for leading the web threading tail forward as desired. The required reinforcement materials can be located on the bottom surface of the blade holder, i.e. on the opposite side of the blade holder relative to the flow surface. With this embodiment, a very low blade holder construction is also achieved.

Figure 3a shows a doctor apparatus 10 according to the invention including a blade holder 14, release means 11 for a web threading tail 12, and a nozzle channel 30. The release means 11 include a mechanical blade 16 and an air blade 68 formed by

a blow-off blow 27. The blade holder 14 has a first end 18 and a second end 20. The transportable web threading tail 12 travels past the doctor apparatus 10 away from the first end 18 of the blade holder 14. The mechanical blade 16 or a doctor blade is fastened to the vicinity of the first end 18 of the blade holder 14. More precisely, the nozzle channel 30 for generating a trailing blow 26 is in connection with the blade holder 14. More precisely, the nozzle channel 30 is inside the blade holder. In addition, the nozzle channel 30 is so oriented that the air blown therefrom is adapted to flow parallel with or in a small angle relative to a flow surface 32 included in the doctor apparatus 10. In other words, the doctor apparatus 10 also includes a flow surface 32 relative to which the trailing blow 26 is blown substantially parallel with. Thus the trailing blow 26 flows away from the first end 18 of the blade holder 14. Flows that are substantially parallel with the flow surface create a Coanda effect in the vicinity of the flow surface.

In the doctor apparatus according to the invention shown in Figure 3a, trailing blow means 29 are provided in two positions in the travel direction 42 of the web threading tail 12. More precisely, there are two nozzle channels 30 in the travel direction 42 of the web threading tail 12. Having trailing blow means in two positions enables creating a Coanda effect over a longer distance in the vicinity of the flow surface 32.

In the doctor apparatus shown in Figure 3a, the blade holder 14 is provided with an internal air channel 22 in the longitudinal direction of a blade holder 14 and a mechanical blade 16, i.e. in the cross-direction of the fiber web machine. Advantageously, the air channel 22 is divided into a first pressure channel 34 and a second pressure channel 36. Such an embodiment can be achieved, for example, when one channel has been formed in the blade holder during extrusion with a pipe placed therein later for forming the second pressure channel. Two pressure channels in the longitudinal direction of the blade holder enable modi-

5 fying flow parameters easily as one whole in the travel direction of the web threading tail. In other words, pressure levels and flows from the nozzle channels can be made as desired. Thus flow parameters can be adjusted to different settings in the travel direction of the web threading tail. An nozzle channel that is earlier in the travel direction of the web threading tail has thus different flow parameters than a later nozzle channel.

10 A doctor apparatus in which the trailing blow is oriented parallel with the flow surface can be used at the full web width when guiding the web to a pulper, for example. On the other hand, the trailing blow can be as narrow as the web threading tail. Although the trailing blow would be only as
15 wide as the web threading tail, the air channel can have the same length as the blade holder.

The doctor apparatus 10 according to the invention shown in Figure 3a includes a presser means 25 for loading a mechanical
20 blade 16. In addition, associated with the presser means 25, there is an air-blow channel 38 for generating a blow-off blow 27. When the air-blow channel is associated with the presser means, the air-blow channel can be inside the presser means or on the surface of the presser means. An air-blow channel 38
25 associated with the pressure means 25 enables orienting the air-blow precisely. Advantageously, the presser means is a removable presser plate 28 and the air-blow channel 38 is included between the presser plate 28 and the mechanical blade 16. Thus air flows from between the mechanical blade 16 and the
30 presser plate 28 generating the blow-off blow 27 for detaching a web threading tail 12 from a roll surface 24. In this way the flow direction of air can be better oriented to a desired point. With constructions inside the presser means, external constructions are avoided which can become soiled and unnecessarily affect the tail travel. In the figure, the mechanical
35 blade is shown wear-free.

In the doctor apparatus 10 according to the invention shown in Figure 3a, the blade holder 14 includes a blade groove 54 to which a mechanical blade 16 is connected. In addition, flow openings 60 are provided between the blade groove 54 and the air channel 22 for leading air from the air channel 22 to the blade groove 54. In this way, it is possible to lead pressurized air, which can be utilized further as desired, to the vicinity of the entirety formed by the mechanical blade and the presser plate.

Figure 3b shows a mechanical blade 16 used in a doctor apparatus according to the invention provided with a presser means 25, which is a presser plate 28. An air-blow channel 38 is provided between the presser plate 28 and the mechanical blade 16. Advantageously, the surface 48 on the side of the mechanical blade 16 of the presser plate 28 includes an air-blow groove 40 for creating the air-blow channel 38. There are several air-blow grooves in the longitudinal direction of the mechanical blade. The presser plate 28 extends within the blade holder 14 further than the mechanical blade 16, and the blade groove 54 includes a front part 56 and a rear part 58 (Figure 3a). Advantageously, a groove 62 for the presser plate 28 is provided between the front part 56 and the rear part 58. When the rear part 58 or the blade groove 54 is pressurized, air flows in the presser plate 28 from the rear part 58 of the blade groove 54 to between the mechanical blade 16 and the presser plate 28.

The presser plate 28 shown in Figure 3b is provided with an air-blow groove 40 having a tip 64 at the edge 66 of the presser plate 28 butting the mechanical blade 16. In addition, the air-blow groove 40 narrows in the thickness direction h of the presser plate 28 towards its tip 64. Thus air flows in such a way that its movement is directed partly towards the mechanical blade. With the movement directed partly towards the mechanical blade, air bounces back from the mechanical blade whereby the

movement direction of the rebounded air is towards the opening nip as desired (Figure 1b)

Figure 4 shows another doctor apparatus 10 according to the invention 10. In this doctor apparatus 10 the flow surface 32 is a surface 46 of the blade holder 14. The flow surface 46 is composed of several flow zones that are formed at the end of each nozzle channel 30. The shape of the flow surface can be, for example, curved. When the flow surface is a surface of the blade holder, the mass of the doctor apparatus can be reduced compared to an application provided with a flow deflector. The size of the doctor apparatus can also be smaller when the number of required components is smaller. Then the doctor apparatus is easy to locate in many applications.

15

Figure 5 shows a third doctor apparatus 10 according to the invention. In this doctor apparatus 10 the flow surface 32 is a surface 46 of the blade holder 14. Projections 80 are formed on the surface 46 of the blade holder 14 at the nozzle channels 30. In this way the flow can be guided towards the surface. In addition, the web threading tail cannot bump into the air-blow channels.

In the doctor apparatuses shown in Figure 5, there are three nozzle channels 30 in the travel direction 42 of the web threading tail 12. Thus, in connection with a flow surface, the web can be controlled over a long distance.

In the doctor apparatuses shown in Figures 4 and 5, the air channel 22 located within the blade holder 14, in the longitudinal direction of the blade holder 14 is divided into a first pressure channel 34 and a second pressure channel 36. The pressure channels 34, 36 are connected by a flow channel 82. The pressure channels 34, 36 are manufactured directly to the frame material of the blade holder whereby a simple constructional complex is achieved.

In Figure 4, the flow channel 82 between the pressure channels 34 and 36 is a flow channel assembly manufactured by drilling. Drilling is performed through the blade groove 54. Flow openings 60 are drilled at the same time. In turn in Figure 5, the flow channel 82 between the pressure channels 34 and 36 is a groove manufactured during casting.

The doctor apparatus 10 shown in Figure 6 includes release means 11 for the web threading tail 12 and trailing blow means 29 which are adapted to generate a trailing blow 26. The release means 11 for the web threading tail consist of a mechanical blade 16 and an air blade 68, which is formed by a blow-off blow 27. The purpose of the blow-off blow 27 is to detach the web threading tail 12 from a moving surface 23. The trailing blow 26 generated by the trailing blow means 29 is adapted to flow to the direction of the flow surface 32. The flow surface 32 is a surface 46 of the blade holder. The blade holder 14 has within it an air channel 22 with the trailing blow means 29 departing therefrom forming the nozzle channels 30.

20

The doctor apparatus 10 shown in Figure 6 includes a presser means 25 for loading the mechanical blade 16. In addition, associated with the presser means 25, there is an air-blow channel 38 for generating a blow-off blow 27. When the blow-off blow 27 is created via an air-blow channel 38 associated with the presser means 25, the blow-off blow 27 can be directed near to the tip of the mechanical blade 16 in a desired angle.

In the doctor apparatus shown in Figure 6, the presser means 25 includes a nozzle channel 30' for generating a trailing blow 26'. A presser means refers to a construction that loads the mechanical blade and extends over at least a part of the mechanical blade dimension, typically over the dimension of the mechanical blade. Then the nozzle channel is already beside the mechanical blade whereby the detached web threading tail can be taken into control with the trailing blow faster than before.

In the doctor apparatus shown in Figure 6, the presser means 25 is integrated as a part of the blade holder 14. Thus the presser means is an integrated presser construction 31. An integrated presser construction enables leading air to the vicinity of the mechanical blade in a simple way. The air channel 22 can then extend as a part of the integrated presser construction 31. The air channel extends over the entire length of the blade holder, but the nozzle channels and air-blow channels departing from it are holes. The air channel is typically formed when forming the blade holder by extrusion or pultrusion, for example. The nozzle channels and the air-blow channel, in turn, are made by drilling, for example.

The doctor apparatus 10 shown in Figure 7 includes release means 11 for the web threading tail 12 and trailing blow means 29 which are adapted to generate a trailing blow 26. The release means 11 for the web threading tail include a mechanical blade 16 and an air blade 68 formed by a blow-off blow 27. The trailing blow 26 generated by the trailing blow means 29 is adapted to flow to the direction of the flow surface 32, which is a surface 46 of the blade holder. The flow surface 32 is a surface 46 of the blade holder. The presser means 25 has within it air channels 22' departing from which there are nozzle channels 30' of the presser device 25 formed by the trailing blow means 29' located in the presser device 25. Associated with the presser means 25, there is also an air-blow channel 38 for generating a blow-off blow 27. The air-blow channel may be a continuous slit in the cross-direction of the fiber web machine or it may consist of several separate holes. When a blow-off blow 27 is created via an air-blow channel 38 associated with a presser means 25, the blow-off blow 27 can be directed as desired. The presser means forms the upper jaw of the blade holder with which the blade is loaded as desired. The blade is supported by the lower jaw of the blade holder further away from the blade tip, which is used to doctor the moving surface.

The flow surface starts immediately when the trailing blow discharges from the nozzle channel. A flow area is provided after each nozzle channel. The flow surface consists of one or more flow areas. The length of one flow area depends on the pressure level and design, but typically the length of one flow area is at least 30 cm, advantageously 20 cm. When there are several nozzle channels, there are several flow areas as well. The flow areas form together flow surfaces that can be relatively long and possibly with a varying shape. The flow surface can, for example, bend over its distance.

The presser means 25 shown in Figure 7 is a removable presser means 33. A removable presser means can be replaced when it damages without the need to replace the blade holder as a whole. A combination of a presser means and a blade holder can also be made more resistant when they are not connected by an air channel. A removable presser means 33 has a sufficient cross-sectional area for forming the required air channels 22' in it. A removable presser means includes a nozzle channel 30' for directing a trailing blow 26' substantially parallel with the flow surface 32 included in the doctor apparatus 10.

In the doctor apparatus shown in Figure 7, the air channels 22' are composed of two separate pressure channels 34', 36'. A nozzle channel 30' departs from the first pressure channel 34' in the removable presser means 33. In turn, an air-blow channel 38 departs from the second pressure channel 36' in the removable presser means 33 for generating a blow-off blow.

The presser means can consist of several presser components that are separate from each other. A presser means consisting of several components can be very similar to the one in Figure 7, but a presser plate is included in the presser means as a second presser component.

From the presser means shown in Figure 7, an embodiment can be manufactured in which the presser means is integrated as a part of the blade holder. The presser means can be as in Figure 7, but an integral part of the blade holder.

5

The presser means 25 according to Figure 7 provided with an air-blow channel 38 can extend over the entire dimension of the blade or it can be only in the tail threading area, which is typically 50 - 80 cm in width. If a presser means with air-blow channels extends only to the tail threading area, a conventional presser plate, for example, is used elsewhere. The material of both the blade holder and the presser means is typically fiber-reinforced plastic.

10

15 Figure 8 shows a doctor apparatus 10 having a slit nozzle casing 90 in connection with the mechanical blade 16. The mechanical blade 16 is included in the release means 11 for a web threading tail 12 which are used to detach a web threading tail 12 from a moving surface 23 in a fiber web machine. Besides the mechanical blade 16, the release means 11 for the web
20 threading tail 12 include an air blade 68. The purpose of the air blade 68 is to detach the web threading tail 12 from a moving surface 23, i.e. by providing an air-blow with the blow-off blow 27. The slit nozzle casing 90 includes a first
25 wall 92 or a cover surface. The blow-off blow 27 passes through a blow-off blow slit 88 located between the first wall 92 and the mechanical blade 16. The slit nozzle casing enables generating a blow-off blow as desired in connection with the mechanical blade without a presser means. When the slit nozzle
30 casing is a separate construction, the slit nozzle casing can be used in connection with several blades. More generally, the release means 11 included in the doctor apparatus include a mechanical blade 16. In addition, the doctor apparatus 10 includes a slit nozzle casing 90 having a first wall 92 and a
35 blow-off blow slit 88 between the first wall 92 and the mechanical blade 16.

In the doctor apparatus shown in Figure 8, a mechanical blade 16 is removably fastened to a slit nozzle casing 90. In other words, a separate slit nozzle casing 90 is fastened to the mechanical blade 16 with an openable connection 98. The connection being an openable connection, the mechanical blade can be replaced allowing thereby to use the slit nozzle casing in connection with several blades. Gluing or otherwise integrating the device as an integral part of the mechanical blade is not advantageous because then the replaceability of the casing from one mechanical blade to another will be lost and changes are produced in the behavior of the mechanical blade in an air-blow situation. In case the mechanical blade would be integrated as a part of the slit nozzle casing, the mechanical blade would yield in an air-blow condition. The openable connection 98 is advantageously a bolted connection 100, which is implementable in a simple way. When using a bolted connection, the slit nozzle casing can be continuous.

Such an openable connection can also be contemplated which is a form closure connection. A form closure connection enables replacing the mechanical blade more easily than a bolted connection. When using a form closure connection, the mechanical blade can be replaced by pushing the blade in place to the blade holder after which the slit nozzle casing is pushed in place to the vicinity of the mechanical blade. A problem with a form closure connection is the sufficiency of space beside a fiber web machine, since the slit nozzle casing is a rigid construction.

In an embodiment in which the counter air-blow does not come from within the blade holder, a slit nozzle casing is provided in connection with a mechanical blade. The slit nozzle casing includes a first wall. In other words, a slit nozzle casing is fastened to the mechanical blade. A blow-off blow passes through a blow-off blow slit located between the first wall and the mechanical blade. The slit nozzle casing enables forming

the blow-off blow slit very close to the tip of the mechanical blade since the first wall of the slit nozzle casing, i.e. the cover surface, can extend very close to the tip of the mechanical blade by which the moving surface is doctored.

5

In another embodiment in which the counter air-blow does not come from within the blade holder, the blow-off blow slit opens when the gap between the mechanical blade and the first wall is pressurized. In other words, the blow-off blow slit is closed
10 in the unpressurized state. When the blow-off blow slit is open only in the pressurized state, the blow-off blow slit does not get soiled as much as a blow-off blow slit that remains open all the time.

15 Generally, the release means include a mechanical blade. In addition, a slit nozzle casing with a first wall is provided in connection with the mechanical blade. A blow-off blow passes through a blow-off blow slit located between the first wall and the mechanical blade. Advantageously, the blow-off blow slit
20 opens when the gap between the mechanical blade and the first wall is pressurized.

In the doctor apparatus shown in Figure 8, the blow-off blow slit 88 opens when the gap between the mechanical blade 16 and
25 the first wall 92 is pressurized. The blow-off blow slit is then not in the unpressurized state and the blow-off blow slit can thus not get soiled in the unpressurized state.

In the doctor apparatus shown in Figure 8, a pipe 84 is provided within the slit nozzle casing 90 for leading air to the
30 slit nozzle casing 90. The pipe has an opening 86 for leading air from the pipe 84 to the slit nozzle casing 90 and for pressurizing the slit nozzle casing 90.

35 The doctor apparatus 10 shown in Figure 9 is used to detach a web threading tail 12 from a moving surface 23 by means of an

air blade 68 included in the release means 11 for the web threading tail 12. The air blade 68 is formed by a blow-off blow 27 coming from a blow-off blow slit 88. The doctor apparatus also includes trailing blow means 29 which are used to
5 direct a trailing blow 26 to the web threading tail 12. The trailing blow means 29 are used to blow the trailing blow 26 substantially to the same direction with the flow surface 32.

A slit nozzle casing 90 is provided in connection with the
10 mechanical blade 16 of the doctor apparatus shown in Figure 9. The mechanical blade 16 is included in the release means 11 for the web threading tail 12. The slit nozzle casing 90 includes a first wall 92, which is a cover surface. A blow-off blow slit 88 is provided between the first wall 92 and the mechanical
15 blade 16. The slit nozzle casing 90 is composed of a first wall 92 and a pipe 84 located in connection with it, which are removable from the mechanical blade 16. Thus the slit nozzle casing 90 can be used in connection with many mechanical blades 16. Advantageously, the first wall 92 is adapted to bend when
20 pressurizing the slit nozzle casing 90 whereby the blow-off blow slit 88 is adapted to be formed. As the air-blow slit is formed during pressurization of the gap between the first wall 92 and the mechanical blade 16, the air-blow slit 88 does not exist in the unpressurized state. Then dirt cannot access the
25 slit nozzle casing in the unpressurized state. In the pressurized state, in turn, air flows from the slit nozzle casing whereby dirt or impurities cannot access it.

Figure 10a is a cross-sectional view of the doctor apparatus 10
30 seen from the end of the mechanical blade 16. Figure 10b, in turn, shows the same doctor apparatus 10 seen from above the mechanical blade 16. In the doctor apparatus shown in Figure 10a, a pipe 84 is supplied with pressurized air which is led uniformly into a slit nozzle casing 90 through an opening 86 in
35 the pipe 84. As the pressure increases, a blow-off blow slit 88 is created between the first wall 92 or the cover surface and

the second wall 94 or the bottom surface. In other words, when the slit nozzle casing 90 is pressurized, the first wall 92 of the slit nozzle casing 90 bends. Then the blow-off blow 27 can pass through the blow-off blow slit 88 created between the first wall 92 and the mechanical blade 16. The blow-off blow slit 88 is created when the slit nozzle casing 90 is in the pressurized state. A slit nozzle casing that forms a blow-off blow slit 88 when pressurized does not get soiled in the unpressurized state.

The slit nozzle casing 90 shown in Figure 10a includes a second wall 94, whereby the pressure opening the air-blow slit 88 affects between the first wall 92 and the second wall 94 of the slit nozzle casing 90. Then a direct pressure is not applied to the blade at the slit nozzle casing. Advantageously, the second wall 94 is more rigid than the first wall 92, whereby the first wall bends as desired when pressurizing the slit whereas the second wall is non-bending. In this way forces affecting the load are not directed to the mechanical blade. More generally, the first wall 92 included in the doctor apparatus is adapted to bend when pressurizing the slit nozzle casing 90 whereby a blow-off blow slit 88 is adapted to be formed.

The slit nozzle casing 90 shown in Figure 10a set in connection with a mechanical blade is fastened to the mechanical blade 16 by its second wall 94 with an openable connection 98. Fastening the slit nozzle casing is particularly simple when it is performed via the non-bending second wall 94.

The first wall 92 of the slit nozzle casing 90 shown in Figure 10a has a front edge 93 and the second wall 94 has a front edge 95. The front edges 93, 95 extend towards the tip of the mechanical blade 16, by which the roll surface 24 is doctored, forming a very narrow blow-off blow slit 88. The blow-off blow 27 passes through the blow-off blow slit 88 located between the first wall 92 and the mechanical blade 16. The first wall 92

and the second wall 94 are sealed against each other when the slit nozzle casing is unpressurized. When the second wall is missing, the front edge 93 of the first wall 92 is sealed against the mechanical blade 16 (Figure 9).

5

In Figure 10b, the doctor apparatus of Figure 10a is shown from outside the slit nozzle casing 90, on the side of the first wall 92. The mechanical blade 16 is drawn partly with a broken line since the mechanical blade 16 is behind the slit nozzle casing 90. Correspondingly, the pipe 84 inside the slit nozzle casing 90 is drawn with a broken line, being located behind the first wall 92. A blow-off blow 27 comes from the slit nozzle casing 90. The slit nozzle casing can be equal in dimension with the entire blade or it can cover only the width of the web threading tail.

15

In the doctor apparatus 10 shown in Figure 10a, the slit nozzle casing 90 has a rear edge 99. An openable connection 98 is closer to the rear edge 99 of the slit nozzle casing 90 than to the front edge 93 of the first wall 92 of the slit nozzle casing. Then the blow-off blow 27 is correctly directed also when the slit nozzle casing is pressurized since the air-blow slit opens when the cover surface bends while the mechanical blade does not bend. The second wall or the bottom surface of the slit nozzle casing is machined plane in order that the slit nozzle casing seals against the surface of the mechanical blade. The ends of the slit nozzle casing are also sealed with labyrinth seals, for example, which prevent air-blows in the cross-machine direction within the casing. Advantageously, a rubber seal that completely prevents an air-blow from the end is placed in the outermost labyrinth.

20

25

30

CLAIMS

1. A method for detaching a web threading tail from a moving surface in a fiber web machine, characterized in that

- 5 - the web threading tail (12) is detached from a moving surface (23) by means of air that flows from a blow-off blow channel (19) included in a blade holder (14),
- a trailing blow (26) is directed to the web threading tail (12) using air that flows from a trailing blow
- 10 channel (17) included in the blade holder (14),
- the blade holder (14) includes a flow surface (32), and the trailing blow (26) is blown to the same direction with or in a small angle relative to the flow surface (32).

15 2. A method according to claim 1, characterized in that the trailing blow (26) is blownto the same direction with or in a small angle relative to the flow surface (32) in two different positions.

20 3. A method according to claim 2, characterized in that the blade holder is turned around a pivot point and the pivot point is located after a first trailing blow channel in the web travel direction.

25 4. A method according to any of claims 1 - 3, characterized in that a pressure lower than the environment is generated between the blow-off blow and the trailing blow.

30 5. A method according to any of claims 1 - 4, where the blade holder (11) includes a mechanical blade (16) which is loaded with a presser means (25), characterized in that a blow-off blow (27) comes from the vicinity of the presser means (25) for detaching a web threading tail (12) from a moving

35 surface (23).

6. A method according to claim 5, characterized in that the blow-off blow (27) comes from the presser means (25) for detaching a web threading tail (12) from a moving surface (23).

5 7. A method according to claim 5 or 6, characterized in that a trailing blow (26) comes from the presser means (25) substantially to the same direction with a flow surface (32).

10 8. A method according to any of claims 5 - 7, where the presser means (25) loading the mechanical blade (16) is a presser plate (28), characterized in that the blow-off blow (27) comes from between the mechanical blade (16) and the presser plate (28) for detaching a web threading tail (12) from a moving surface (23).

15

9. A blade holder for detaching a web threading tail from a moving surface in a fiber web machine, where the blade holder (14) includes a frame (71), characterized in that the frame (71) of the blade holder (14) includes

- 20 - a blow-off blow channel (19) with air flowing therefrom being adapted to generate a blow-off blow (27) for detaching a web threading tail (12) from a moving surface (23) in a fiber web machine,
- 25 - a trailing blow channel (17) with air flowing therefrom being adapted to generate a trailing blow (26) for guiding the web threading tail (12) further, and
- a flow surface (32) relative to which the trailing blow (26) is adapted to flow to the same direction with or in a small angle.

30

10. A blade holder according to claim 9, characterized in that the flow surface (32) and further the blade holder (14) include several flow supports (70) connected to each other.

35 11. A blade holder according to claim 10, characterized in that the flow support (70) includes a trailing blow channel

(17) with air flowing therefrom being adapted to generate a trailing blow (26) for guiding a web threading tail (12) further.

5 12. A blade holder according to claim 9, characterized in that trailing blow channels (17) are located in the blade holder (14) in two positions in the travel direction (42) of a web threading tail (12).

10 13. A blade holder according to claims 9 - 11, characterized in that a guide surface (69) is included between the blow-off blow (27) and the trailing blow (26).

14. A blade holder according to claim 13, characterized in
15 that the guide surface (69) is substantially plane.

15. A blade holder according to any of claims 9 - 14, characterized in that the angle between the blow-off blow (27) and the trailing blow (26) is over 130°, advantageously over 150°.

20

16. A blade holder according to any of claims 9 - 15, characterized in that the blade holder (14) includes a fastening position (76) for a shaft (77).

25 17. A blade holder according to any of claims 9 - 16, characterized in that the blade holder (14) is made of an aluminum profile (75).

18. A doctor apparatus for detaching a web threading tail
30 from a moving surface in a fiber web machine, where the doctor apparatus (10) includes an adjustable blade holder (14) and the blade holder (14) has a frame (71), characterized in that the frame (71) of the blade holder (14) includes

- a blow-off blow channel (19) with air flowing therefrom
35 being adapted to generate a blow-off blow (27) for de-

taching a web threading tail (12) from a moving surface (23) in a fiber web machine,

- a trailing blow channel (17) with air flowing therefrom being adapted to generate a trailing blow (26) for guiding the web threading tail (12) further, and
- a flow surface (32) relative to which the trailing blow (26) is adapted to flow to the same direction with or in a small angle.

10 19. A doctor apparatus according to claim 18, characterized in that trailing blow channels (29) are located in two positions in the travel direction (42) of the web threading tail (12).

15 20. A doctor apparatus according to claim 9 or 10, characterized in that the blade holder (10) includes a flow deflector (43) a surface (44) of which is a flow surface (32).

20 21. A doctor apparatus according to any of claims 18 - 20, characterized in that an air channel (22) is included within the blade holder (14), and the air channel (22) is arranged in a first pressure channel (34) and in a second pressure channel (36).

25 22. A doctor apparatus according to any of claims 18 - 21, where the blade holder (14) has a mechanical blade (16) connected thereto and a pressure means (25) for loading the mechanical blade (16), characterized in that an air-blow channel (38) is provided in the vicinity of the presser means (25)
30 for creating the blow-off blow (27).

23. A doctor apparatus according to claim 22, characterized in that an air-blow channel (38) is arranged between the presser means (25) and the mechanical blade (16) for creating the
35 blow-off blow (27).

24. A doctor apparatus according to claim 23, characterized in that an air-blow groove (40) is included in the surface (48) located on the side of the mechanical blade (16) of the presser means (25) for creating the air-blow channel (38).

5

25. A doctor apparatus according to claim 22, characterized in that an air-blow channel (38) is provided within the presser means (25) for creating the blow-off blow (27).

10 26. A doctor apparatus according to any of claims 22 - 25, characterized in that the presser means (25) comprises a nozzle channel (30) for creating the trailing blow (26).

27. A doctor apparatus according to any of claims 22 - 26,
15 characterized in that the presser means (25) is a removable presser plate (28).

28. A doctor apparatus according to any of claims 22 - 27, characterized in that the presser means (25) is an integrated
20 part of the blade holder (14).

29. A doctor apparatus according to any of claims 22 - 28, characterized in that the presser means (25) is a removable presser means (33).

25

30. A doctor apparatus according to claim 18, where the blade holder (14) includes a blade groove (54) to which the mechanical blade (16) is attached, characterized in that flow openings (60) are provided between the blade groove (54) and an
30 air channel (22).

31. A doctor apparatus according to claim 30, characterized in that the blade groove (54) comprises a front part (56) and a rear part (58), and a groove (62) for a presser plate (28) is
35 provided between the front part (56) and the rear part (58).




Fig. 1a




Fig. 1b




Fig. 2b

4/11




Fig. 2c

Fig. 2d

5/11




Fig. 2e

6/11




Fig. 3a




Fig. 3b




Fig. 4




Fig. 5




Fig. 6

9/11




Fig. 7

10/11




Fig. 8




Fig. 9

11/11




Fig. 10a




Fig. 10b

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI2008/050649

A. CLASSIFICATION OF SUBJECT MATTER

See extra sheet

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC: D21F, D21G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

FI, SE, NO, DK

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI, COMPDX, INSPEC, XPESP

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	GB 200600 A (OGDEN MINTON) 19 July 1923 (19.07.1923) page 1, lines 10-41, page 2, lines 41-87, 110-114, fig. 1-4	1-4, 9, 12-14, 18-20 26
X	FI 20030619 A (METSO PAPER INC) 25 October 2004 (25.10.2004), page 1, lines 9-10, page 6, lines 8-24, fig. 2-3	1, 3, 4, 9, 13, 14, 18, 20
X Y	DE 3941242 A1 (VOITH GMBH J M) 20 June 1991 (20.06.1991) column 1, lines 3-9, column 2, line 57-column 3, line 39, fig. 2-3	1, 3-6, 8, 9, 13, 14, 16-18, 20-25, 27-31 26
X Y	CA 2144623 A1 (VOITH GMBH J M) 22 September 1995 (22.09.1995) whole document, fig. 1	1-14, 16-24, 27-31 26
X	US 6145217 A (GOEBEL WERNER) 14 November 2000 (14.11.2000), whole document, fig. 1-3	1-4, 9, 12, 15, 18-20

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

23 January 2009 (23.01.2009)

Date of mailing of the international search report

26 February 2009 (26.02.2009)

Name and mailing address of the ISA/FI

National Board of Patents and Registration of Finland
P.O. Box 1160, FI-00101 HELSINKI, Finland

Facsimile No. +358 9 6939 5328

Authorized officer

Mari Ylönen

Telephone No. +358 9 6939 500

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/FI2008/050649

Patent document cited in search report	Publication date	Patent family members(s)	Publication date
GB 200600 A	19/07/1923	US 1595478 A FR 550984 A DE 413177 C	10/08/1926 24/03/1923 09/05/1925
FI 20030619 A	25/10/2004	DE 112004000672T T5 WO 2004094723 A1	09/03/2006 04/11/2004
DE 3941242 A1	20/06/1991	None	
CA 2144623 A1	22/09/1995	JP 7323946 A FI 951291 A EP 0674045 A2 BR 9500955 A DE 4409660 A1	12/12/1995 22/09/1995 27/09/1995 17/10/1995 18/08/1994
US 6145217 A	14/11/2000	EP 0887462 A2 DE 19726895 A1	30/12/1998 07/01/1999

INTERNATIONAL SEARCH REPORT

International application No.
PCT/FI2008/050649

CLASSIFICATION OF SUBJECT MATTER

Int.Cl.

D21F 7/00 (2006.01)

D21G 9/00 (2006.01)

D21G 3/04 (2006.01)