

19



Europäisches Patentamt  
European Patent Office  
Office européen des brevets

11

Publication number:

**0 217 597  
B1**

12

## EUROPEAN PATENT SPECIFICATION

45

Date of publication of the patent specification:  
19.09.90

21

Application number: 86307185.8

22

Date of filing: 18.09.86

51

Int. Cl.<sup>5</sup>: **C10M 173/00**  
// (C10N30/16,  
40:20), (C10M173/00, 129:24,  
137:04)

54

**Water-miscible metalworking lubricants.**

30

Priority: 26.09.85 DE 3534226

43

Date of publication of application:  
08.04.87 Bulletin 87/15

45

Publication of the grant of the patent:  
19.09.90 Bulletin 90/38

64

Designated Contracting States:  
AT BE CH DE FR GB IT LI LU NL SE

56

References cited:  
EP-A- 0 069 540  
EP-A- 0 147 760  
DE-A- 2 457 887

73

Proprietor: **MOBIL OIL CORPORATION, 150 East 42nd  
Street, New York New York 10017(US)**

72

Inventor: **Huebner, Juergen, Wientapperweg 9 E,  
D-2000 Hamburg 55(DE)**  
Inventor: **Sinning, Gudrun Klara Maria Elisabeth,  
Audeich 13, D-2081 Haselau(DE)**

74

Representative: **Cooper, John Anthony et al, Mobil  
Court 3 Clements Inn, London WC2A 2EB(GB)**

**EP 0 217 597 B1**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

## Description

This invention relates to water-miscible or aqueous metalworking lubricants.

Aqueous metalworking lubricants are excellent culture media for microorganisms, and as emulsions and solutions must therefore be protected against microbial attack or they will lose their utility and toxicological problems may arise owing to infection of the aqueous metalworking lubricant. For protection against microbial infestation, there is normally employed a biocide incorporated as an ingredient in the metalworking lubricant concentrate.

The so-called formaldehyde liberating biocides are widely used in this respect since they have broad antimicrobial activity at low concentrations. However, they have the disadvantage that their stability upon storage of the metalworking lubricant concentrates is insufficient so that upon preparation of the emulsion or solution, only a fraction of the original biocide is available.

The resulting underdosage of the biocide results in the biostability of the emulsion or solution being inadequate. The stability of such emulsions and solutions against microorganisms is, however, a decisive factor for their utility and service life. A microbial infestation of an emulsion can cause considerable toxicological problems (rapid multiplication of microorganisms, occurrence of coliformic germs with the risk of human pathological infections), it results in a drop of the pH-value (increased corrosivity of the aqueous metalworking lubricant) and incomplete breaking of the emulsion (which in turn necessitates not only replacement of existing emulsion and loss of broken emulsion, but also inadequate machining efficiency and reduced tool service life).

The speed of decomposition of the biocide depends upon the respective composition of the metalworking lubricant.

The present invention seeks to solve this problem by improving metalworking lubricants of this type in respect of their microbial stability to prevent or hinder decomposition of the biocide during storage of the metalworking lubricant concentrate.

In accordance with the invention, there is provided a water-miscible metalworking lubricant containing mineral oil, emulsifier, solubilizer, corrosion inhibitor biocide and acidic components, characterized in that the acidic component comprises an acidic organic phosphoric acid ester in an amount of preferably 3 to 12% by weight of the composition and that the biocide comprises a formaldehyde liberating compound.

Such a composition may have a composition in percentage by weight:

|                                      |          |
|--------------------------------------|----------|
| Mineral Oil                          | 50 to 55 |
| Petroleum Sulfonate                  | 16 to 20 |
| Glycol Ether                         | 12 to 16 |
| Boric Acid Amine Ester               | 7 to 10  |
| Acidic Organic Phosphoric Acid Ester | 3 to 7   |
| Biocide                              | 2 to 3   |

|    |                                      |          |
|----|--------------------------------------|----------|
|    | preferably                           |          |
|    | Mineral Oil                          | 30 to 35 |
|    | Petroleum Sulfonate                  | 18 to 22 |
|    | Glycol Ether                         | 12 to 16 |
| 5  | Boric Acid Amine Ester               | 5 to 8   |
|    | Fatty Acid Ester                     | 5 to 8   |
|    | Chlorinated paraffin                 | 8 to 12  |
|    | Acidic Organic Phosphoric Acid Ester | 6 to 9   |
|    | Biocide                              | 2 to 3   |
| 10 | and more preferably                  |          |
|    | Mineral Oil                          | 20 to 30 |
|    | Non-Ionic Emulsifier                 | 10 to 15 |
|    | Boric Acid Amine Ester               | 9 to 18  |
|    | Alkanolamine                         | 0 to 7   |
| 15 | Glycol Ether                         | 6 to 12  |
|    | Chlorinated paraffin                 | 16 to 20 |
|    | Water                                | 5 to 15  |
|    | Acidic Organic Phosphoric Acid Ester | 7 to 12  |
|    | Biocide                              | 2 to 5   |
| 20 | or                                   |          |
|    | Mineral Oil                          | 5 to 25  |
|    | Non-Ionic Emulsifier                 | 10 to 15 |
|    | Boric Acid Amine Ester               | 12 to 18 |
|    | Alkanolamine                         | 0 to 7   |
| 25 | Glycol Ether                         | 6 to 20  |
|    | Corrosion Inhibitor                  | 10 to 15 |
|    | Water                                | 5 to 20  |
|    | Acidic Organic Phosphoric Acid Ester | 5 to 10  |
|    | Biocide                              | 2 to 5   |

30 The compositions according to the invention provide prolonged inhibition of biocide decomposition by virtue of using instead of the conventional carboxylic acids (in particular fatty acids), acidic organic phosphoric acid esters. This markedly retarded biocide decomposition results in a considerably better microbial resistivity of the metalworking lubricants of the invention after storage as compared with conventional compositions.

40 It has been possible to demonstrate that such a composition of the metalworking lubricants displays a considerably improved frothing behavior for emulsions and solutions. For this aspect also, it is important that the compositions contain no or only very minor amounts of carboxylic acids (in particular fatty acids), and instead, acidic organic phosphoric acid esters.

45 Conventional water-miscible metalworking lubricants for metal machining contain biocides, predominantly formaldehyde liberating biocides, in the concentrate for protection against microbial attack of the working emulsions or solutions. These water-miscible metalworking lubricants contain also *inter alia* alkaline components (for example alkanolamines) as well as carboxylic acids (predominantly fatty acids), which perform a neutralizing, lubricating, and partly an emulsifying and corrosion inhibiting function.

50 The biocides, which in most cases are selected by microbiological tests, impart to the working emulsions and solutions a good or at least adequate resistance to microorganisms provided that the emulsions or solutions are prepared from concentrates which are freshly prepared or stored for short periods only.

Owing to the decomposition of the biocides upon prolonged storage of the concentrate, the biostability of the working emulsions and solutions is, however, often unsatisfactory or at least no longer completely sufficient since due to decay of the biocide during storage the biocide concentration necessary for microbial protection in the working solution or emulsion (minimum restraint concentration) is no longer available.

The resulting underdosage of the biocide results in the disadvantages and problems described above.

As regards the frothing tendency of conventional formulations (containing carboxylic acids), attempts have been made to suppress frothing by using skimmers (often containing silicon). However, such skimmers often become ineffective even after brief use (since they become adsorbed and discharged or altered in their particle structure). There is therefore a need for metalworking lubricant formulations which do not froth per se and do not require the use of skimmers.

In developing the compositions of the invention, biocides have also been investigated in which the effective mechanism does not reside in the release of anti-microbially acting formaldehyde. However, it has been found that these so-called formaldehyde-free biocides either do not have the necessary broad spectrum activity (against all bacteria, fungi and yeasts usually occurring in machining emulsions) or have doubtful toxicological or ecological effects. Moreover, these formaldehyde-free biocides often cannot be incorporated into concentrates.

Attempts were therefore made to determine by systematic variation of the composition of the concentrates whether the presence or absence of certain components influences the decomposition rate of the biocides concerned.

By systematic variation of the composition of the concentrates, it was possible to show that the decomposition rate of the biocides during storage of the concentrate can, to a specific extent, be influenced by the chemical composition of the concentrates. The presence or absence of certain components can favorably or unfavorably affect the decomposition speed.

It was in particular found that the incorporation of acidic organic phosphoric acid esters in metalworking lubricant formulations, while no carboxylic acid was present, resulted according to the invention in a marked hinderance of the biocide decay.

Moreover, it was possible to prove that the complete or at least extensive replacement of carboxylic acids (especially fatty acids) by acidic organic phosphoric acid esters leads to a considerably reduced frothing of emulsions and solutions.

Cooling lubricant formulations of this kind do not have a frothing tendency (as emulsions or solutions) in laboratory tests or under practical conditions (even in complex situations, for example high emulsion concentrations and under unfavorable conditions, for example in drilling a deep blind hole) compared with conventional products.

Acidic organic phosphoric acid esters are some-

times used as components for corrosion reduction (extreme pressure components) in metalworking lubricants. However, the stabilizing effect of acidic organic phosphoric acid esters on formaldehyde liberating biocides (restriction of biocide decomposition during storage of the concentrate) was not previously known. On the contrary, it was assumed that no phosphoric acid compounds should be present in view of the growth of microorganisms (and accordingly they were considered to be a drawback for the biostability of lubricants), since phosphorus belongs to the group of elements which are necessary for the metabolism of microorganisms.

The considerable reduction of frothing of water-miscible metalworking lubricants is also unexpected.

For the improved frothing property of the products described here, it is of importance that carboxylic acids (especially fatty acids) normally contained in conventional compositions are at least substantially replaced by acidic organic phosphoric acid esters.

In order to ensure that the improvements in accordance with the invention (biostability/inhibition of biocide decomposition during storage/frothing property) are achieved, it is not sufficient merely to add a certain amount of acid organic phosphoric acid ester to a conventional composition.

Particularly suitable acid phosphoric acid esters for use in the compositions of the invention, are monoalkyl phosphoric acid esters, dialkyl phosphoric acid esters, monoisoalkyl phosphoric acid esters, diisoalkyl phosphoric acid esters, monoalkenyl phosphoric acid esters, dialkenyl phosphoric acid esters, mono(alkylphenyl) phosphoric acid esters, di(alkylphenyl) phosphoric acid esters, mono (isoalkylphenyl) phosphoric acid esters, di(isoalkylphenyl) phosphoric acid esters as well as mono and dipolyether phosphoric acid esters, the polyether group comprising, if desired, as terminal group alkyl, isoalkyl, phenyl, alkylphenyl and isoalkylphenyl and hydrogen.

## Claims

1. A water-miscible metalworking lubricant, containing mineral oil, emulsifier, solubilizer, corrosion inhibitor, biocide and acidic components, characterized in that the acidic component comprises an acidic organic phosphoric acid ester in an amount of preferably 3 to 12% by weight of the composition and that the biocide comprises a formaldehyde liberating compound.

2. A water-miscible metalworking lubricant according to Claim 1, having the following composition in percentage by weight:

|                                      |          |
|--------------------------------------|----------|
| Mineral Oil                          | 50 to 55 |
| Pertroleum Sulfonate                 | 16 to 20 |
| Glycol Ether                         | 12 to 16 |
| Boric Acid Amine Ester               | 7 to 10  |
| Acidic Organic Phosphoric Acid Ester | 3 to 7   |
| Biocide                              | 2 to 3   |

3. A water-miscible metalworking lubricant according to Claim 1, having the following composition in percentage by weight:

|                                      |          |
|--------------------------------------|----------|
| Mineral Oil                          | 30 to 35 |
| Petroleum Sulfonate                  | 18 to 22 |
| Glycol Ether                         | 12 to 16 |
| Boric Acid Amine Ester               | 5 to 8   |
| Fatty Acid Ester                     | 5 to 8   |
| Chlorinated paraffin                 | 8 to 12  |
| Acidic Organic Phosphoric Acid Ester | 6 to 9   |
| Biocide                              | 2 to 3   |

4. A water-miscible metalworking lubricant according to Claim 1, having the following composition in percentage by weight:

|                                      |          |
|--------------------------------------|----------|
| Mineral Oil                          | 20 to 30 |
| Non-Ionic Emulsifier                 | 10 to 15 |
| Boric Acid Amine Ester               | 9 to 18  |
| Alkanolamine                         | 0 to 7   |
| Glycol Ether                         | 6 to 12  |
| Chlorinated paraffin                 | 16 to 20 |
| Water                                | 5 to 15  |
| Acidic Organic Phosphoric Acid Ester | 7 to 12  |
| Biocide                              | 2 to 5   |

5. A water-miscible metalworking lubricant according to Claim 1, having the following composition in percentage by weight:

|                                      |          |
|--------------------------------------|----------|
| Mineral Oil                          | 5 to 25  |
| Non-Ionic Emulsifier                 | 10 to 15 |
| Boric Acid Amine Ester               | 12 to 18 |
| Alkanolamine                         | 0 to 7   |
| Glycol Ether                         | 6 to 20  |
| Corrosion Inhibitor                  | 10 to 15 |
| Water                                | 5 to 10  |
| Acidic Organic Phosphoric Acid Ester | 5 to 10  |
| Biocide                              | 2 to 5   |

6. A water-miscible metalworking lubricant according to any one of Claims 1 to 5, in the form of an aqueous solution or emulsion.

### Patentansprüche

1. Wassermischbares Metallbearbeitungsschmiermittel, enthaltend Mineralöl, Emulgator, Lösungsvermittler, Korrosionsinhibitor, Biozid und saure Bestandteile, dadurch gekennzeichnet, daß der saure Bestandteil einen sauren organischen Phosphorsäureester in einer Menge von vorzugsweise 3 bis 12 Gew.-% der Zusammensetzung und das Biozid eine formaldehydfreisetzende Verbindung beinhaltet.

2. Wassermischbares Metallbearbeitungsschmiermittel nach Anspruch 1 mit der folgenden Zusammensetzung in Gewichtsprozent:

|                                       |           |
|---------------------------------------|-----------|
| Mineralöl                             | 50 bis 55 |
| Petroleumsulfonat                     | 16 bis 20 |
| Glykolether                           | 12 bis 16 |
| Borsäureaminester                     | 7 bis 10  |
| saurer organischer Phosphorsäureester | 3 bis 7   |
| Biozid                                | 2 bis 3   |

3. Wassermischbares Metallbearbeitungsschmiermittel nach Anspruch 1 mit der folgenden Zusammensetzung in Gewichtsprozent:

|                   |           |
|-------------------|-----------|
| Mineralöl         | 30 bis 35 |
| Petroleumsulfonat | 18 bis 22 |
| Glykolether       | 12 bis 16 |
| Borsäureaminester | 5 bis 8   |
| Fettsäureester    | 5 bis 8   |

|                                       |          |
|---------------------------------------|----------|
| chloriertes Paraffin                  | 8 bis 12 |
| saurer organischer Phosphorsäureester | 6 bis 9  |
| Biozid                                | 2 bis 3  |

4. Wassermischbares Metallbearbeitungsschmiermittel nach Anspruch 1 mit der folgenden Zusammensetzung in Gewichtsprozent:

|                                       |           |
|---------------------------------------|-----------|
| Mineralöl                             | 20 bis 30 |
| nichtionischer Emulgator              | 10 bis 15 |
| Borsäureaminester                     | 9 bis 18  |
| Alkanolamin                           | 0 bis 7   |
| Glykolether                           | 6 bis 12  |
| chloriertes Paraffin                  | 16 bis 20 |
| Wasser                                | 5 bis 15  |
| saurer organischer Phosphorsäureester | 7 bis 12  |
| Biozid                                | 2 bis 5   |

5. Wassermischbares Metallbearbeitungsschmiermittel nach Anspruch 1 mit der folgenden Zusammensetzung in Gewichtsprozent:

|                                       |           |
|---------------------------------------|-----------|
| Mineralöl                             | 5 bis 25  |
| nichtionischer Emulgator              | 10 bis 15 |
| Borsäureaminester                     | 12 bis 18 |
| Alkanolamin                           | 0 bis 7   |
| Glykolether                           | 6 bis 20  |
| Korrosionsinhibitor                   | 10 bis 15 |
| Wasser                                | 5 bis 20  |
| saurer organischer Phosphorsäureester | 5 bis 10  |
| Biozid                                | 2 bis 5   |

6. Wassermischbares Metallbearbeitungsschmiermittel nach einem der Ansprüche 1 bis 5 in Form einer wäßrigen Lösung oder Emulsion.

### Revendications

1. Lubrifiant d'usage des métaux miscibles à l'eau, contenant une huile minérale, un émulsifiant, un agent de solubilisation, un inhibiteur de corrosion, un biocide et un composant acide, caractérisé en ce que le composant acide comprend un ester d'acide phosphorique organique acide en quantités comprises de préférence entre 3 et 12% en poids par rapport au poids de la composition et en ce que le biocide comprend un dérivé pouvant libérer du formaldéhyde.

2. Un lubrifiant d'usage de métaux miscible à l'eau selon la revendication 1, présentant la composition suivante en pourcentage en poids:

|                                            |         |
|--------------------------------------------|---------|
| Huile minérale                             | 50 à 55 |
| Sulfonate de pétrole                       | 16 à 20 |
| Glycol éther                               | 12 à 16 |
| Amino ester d'acide borique                | 7 à 10  |
| Ester d'acide phosphorique organique acide | 3 à 7   |
| Biocide                                    | 2 à 3   |

3. Un lubrifiant d'usage de métaux miscible à l'eau selon la revendication 1, présentant la composition suivante en pourcentage en poids:

|                                            |         |
|--------------------------------------------|---------|
| Huile minérale                             | 30 à 35 |
| Sulfonate de pétrole                       | 18 à 22 |
| Glycol éther                               | 12 à 16 |
| Amino ester d'acide borique                | 5 à 8   |
| Ester d'acide gras                         | 5 à 8   |
| Paraffine chlorée                          | 8 à 12  |
| Ester d'acide phosphorique organique acide | 6 à 9   |
| Biocide                                    | 2 à 3   |

4. Un lubrifiant d'usinage de métaux miscible à l'eau selon la revendication 1, présentant la composition suivante en pourcentage en poids:

|                                      |         |    |
|--------------------------------------|---------|----|
| Huile minérale                       | 20 à 30 |    |
| Emulsifiant non-ionique              | 10 à 15 | 5  |
| Amino ester d'acide borique          | 9 à 18  |    |
| Alkanolamine                         | 0 à 7   |    |
| Glycol éther                         | 6 à 12  |    |
| Paraffine chlorée                    | 16 à 20 |    |
| Eau                                  | 5 à 15  | 10 |
| Ester d'acide phosphorique organique |         |    |
| acide                                | 7 à 12  |    |
| Biocide                              | 2 à 5   |    |

5. Un lubrifiant d'usinage de métaux miscible à l'eau selon la revendication 1, présentant la composition suivante en pourcentage en poids: 15

|                                      |         |    |
|--------------------------------------|---------|----|
| Huile minérale                       | 5 à 25  |    |
| Emulsifiant non-ionique              | 10 à 15 |    |
| Amino ester d'acide borique          | 12 à 18 |    |
| Alkanolamine                         | 0 à 7   | 20 |
| Glycol éther                         | 6 à 20  |    |
| Inhibiteur de corrosion              | 10 à 15 |    |
| Eau                                  | 5 à 20  |    |
| Ester d'acide phosphorique organique |         |    |
| acide                                | 5 à 10  | 25 |
| Biocide                              | 2 à 5   |    |

6. Un lubrifiant d'usinage de métaux miscible à l'eau selon l'une quelconque des revendications 1 à 5 se trouvant sous la forme d'une solution ou d'une émulsion aqueuse. 30

35

40

45

50

55

60

65

5