



(51) International Patent Classification:
B01D 3/32 (2006.01) **F25J 3/04** (2006.01)

(21) International Application Number:
PCT/EP2009/058816

(22) International Filing Date:
10 July 2009 (10.07.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
08305520.2 3 September 2008 (03.09.2008) EP

(71) Applicant (for all designated States except US): **L'Air Liquide, Société Anonyme pour l'Etude et l'Exploitation des Procédés Georges Claude** [FR/FR]; 75 Quai d'Orsay, F-75007 Paris (FR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **DEL CORSO, Fabrice** [FR/FR]; 10 bis rue Pasteur, F-91400 Saclay (FR). **ZICK, Golo** [FR/FR]; 27 allée des Deux Mondes, F-38100 Grenoble (FR).

(74) Agent: **MERCEY, Fiona**; Département Propriété Intellectuelle, L'AIR LIQUIDE SA, 75 Quai d'Orsay, F-75321 Paris Cedex 07 (FR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— with international search report (Art. 21(3))

(54) Title: METHOD FOR FABRICATING DIVIDED WALL COLUMNS




Figure 2

(57) Abstract: The invention relates to a method producing a portioned column by forming a first segment and a third segment into arcuate segments, and attaching these arcuate segments to a second z-shaped segment to form two contiguous volumes with approximately semi-circular cross-sections that combine to form a partitioned, approximately cylindrical segment.

METHOD FOR FABRICATING DIVIDED WALL COLUMNS

The present invention relates to a method for fabricating divided wall columns.

5 Distillation columns have, of course, been widely used to perform separations of all types in different industrial applications. Over fifty years ago, it was proposed to replace two distinct distillation columns with a single distillation column having a vertical partition (dividing wall column) within the column. This single, divided wall column could effect the separation of the column feed into
10 three constituent fractions. It was recognized then that a dividing wall column could reduce, or minimize, the size or cost of the equipment needed to produce overhead, bottoms, and sidedraw products.

Control systems for dividing wall distillation columns have been known since at least 1980, when US-A- 4230533 described a dividing wall distillation
15 column and its control system. In the late 1990's, control systems for dividing wall distillation columns have been studied in further detail by researchers.

Despite the advantages of the dividing wall column and despite much research and study, the processing industry has long felt reluctant to use dividing wall columns in commercial processes. This widespread reluctance has
20 been attributed to various concerns, including control problems, operational problems, complexity, simulation difficulties, and lack of design experience. General guidelines and considerations when substituting a dividing wall column for conventional columns have been established. Nevertheless, there are relatively few documented practical uses of dividing wall columns in commercial
25 plants.

It is known, for example, to provide a partition in such a column to thereby subdivide the interior of the column into an inlet region and a discharge region. The partition in this system serves to prevent transverse mixing of liquid and/or vapor streams over a limited height of the column. The apparatus reduces the
30 number of distillation columns required for the separation of multicomponent feed stocks.

The partitions can extend between opposite walls of the column and can have heights which, as a rule, can be greater than the column diameter and can be at least equal to the spacing between individual horizontal bottoms of the

column. The use of continuous partitions has, however, a number of drawbacks and these drawbacks are the more serious the greater the diameter of the column.

5 The incorporation of a one-piece partition in the column is difficult because of its weight and the need for a close fit of the partition in the column. From a certain size, the dimensions of such partitions ensures that they can only be handled with mechanical assistance which can lead to additional costs. Furthermore, with increasing weight, the partitions can pose a greater danger for the workers who are necessary for installation of the partition. It has been
10 found in practice that the partition can easily become canted during installation in the column and can thereby damage the inner wall of the column or result in poor sealing between the column and the partition. Irregularities in the shape of the column can also limit the sealing effectiveness. Since possible nonsealing regions may then have to be sealed up by additional acts, the costs of the
15 column and the partition can be prohibitive.

It is therefore the object of the present invention to propose fabrication methods adapted to present and future processes involving dividing wall columns for the transfer of gas/liquid material that serve to integrate a plurality of columns in the same shell in order to reduce the fabrication costs.

20 A further object of the present invention is to propose fabrication methods for divided wall columns for the transfer of gas/liquid material that serve to integrate a plurality of columns in the same shell in order to reduce the separation energy required.

For this purpose, the invention relates to a method of producing a
25 partitioned column segment, comprising a first sheet metal segment, a second sheet metal segment, and a third sheet metal segment. The first sheet metal segment comprises a first edge, and a second edge. The second sheet metal segment comprises a third edge, and a fourth edge. The third sheet metal segment comprises a fifth edge, and an sixth edge. The second edge is
30 attached to said third edge, and the fourth edge is attached to said fifth edge. The method comprises forming said first segment into a first arcuate bend in a first direction, wherein adjacent to said first edge comprises a first distal region. The method comprises forming said second segment into a z-shaped bend, wherein said z-shape consists of a first proximal region, a central region, and a

second proximal region. The method comprises forming said third segment into a second arcuate bend in a second direction, wherein adjacent to said sixth edge comprises a fourth distal region. The method comprises attaching said first distal region to said second proximate region, thereby producing a first approximately cylindrical segment, said first approximately cylindrical segment having an approximately semi-circular cross-section. And the method comprises attaching said second distal region to said first proximate region, thereby producing a second approximately cylindrical segment, said second approximately cylindrical segment having an approximately semi-circular cross-section.

In another embodiment, the arcuate bend is produced by rolling. In yet another embodiment, said second edge is attached to said third edge by being fabricated from the same sheet, and said fourth edge is attached to said fifth edge by being fabricated from the same sheet. In another embodiment said second edge is attached to said third edge by welding; and said fourth edge is attached to said fifth edge by welding. In yet another embodiment, at least one weld is a butt-weld. In another embodiment at least one weld is a lap-weld. In another embodiment, said second sheet metal segment comprises a thicker gauge metal than said first sheet metal segment and/or said third sheet metal segment.

In another embodiment, said first distal region is attached to said second proximate region by welding, and said second distal region is attached to said first proximate region by welding. In another embodiment, all welds are performed from the exterior of the said partitioned column. In yet another embodiment, said z-shaped bend has an angle α between said first proximal region and said central region, and said z-shaped bend has an angle β between said second proximal region and said central region. In another embodiment wherein said angle α is about 90 degrees, and wherein said angle β is about 90 degrees. In another embodiment said first proximal region has a length of about 30 mm, and said second proximal region has a length of about 30 mm.

In another embodiment, said second segment comprises two sheet metal segments attached together by butt-weld. In another embodiment, said second segment comprises two sheet metal segments attached together by lap-weld. In yet another embodiment, said second segment comprises two sheet metal

segments that are of equal length. In another embodiment, said two sheet metal segments are separated to form an insulating cavity. In another embodiment, said insulating cavity is filled by an insulating media. In another embodiment, said first approximately cylindrical segment and said second approximately cylindrical segment form an approximately cylindrical shape with a plane forming a common cord formed in part from said second sheet metal segment, and said pane forming a common cord being axially offset from said approximately cylindrical form to avoid weld crossing during the joining of successive partitioned column segments. Another embodiment comprises a method of producing a partitioned column by means of joining successive partitioned columns of the type in claim 17. Another embodiment comprises a partitioned column as produced by one of the preceding claims.

In another embodiment the first sheet metal segment, the second sheet metal segment and the third sheet metal segment may be comprised of different materials. The difference may include, but are not limited to, a different metallic composition or material of the same metallic composition but differing in thickness, surface texture or treatment. In another embodiment, the second sheet metal segment may have mechanical strengthening such as ribbing or the equivalent.

Other features and advantages of the invention will appear from a reading of the description that follows. Embodiments of the invention are provided as non-limiting examples.

Figure 1 is a schematic representation of one embodiment of the present invention.

Figure 2 is a schematic cross-sectional view of one embodiment of the present invention.

Figure 3 is a schematic cross-sectional view of one embodiment of the present invention.

Figure 4 is a schematic cross-sectional view of the second sheet metal segment, showing the z-shape profile

Figure 5 is a schematic cross-sectional view showing some of the various embodiments possible for the second sheet metal segment.

Figure 6 is a schematic cross-sectional view showing one embodiment with a insulating cavity.

Figure 7 is a schematic cross-sectional view showing one embodiment with the second sheet metal segment offset from the first sheet metal segment and the third sheet metal segment.

Figure 8 is a schematic view showing how the completed column
5 segments may be joined successively to form a partitioned column.

Figure 9 is a schematic cross-sectional view showing one embodiment of possible assembly and welding.

Figures 10 are schematic details showing other embodiments of possible welding techniques.

10 The application of dividing wall columns serves to obtain a gain in fabrication cost in processes involving a plurality of columns, particularly in air distillation processes comprising columns operating in parallel: argon columns (mixture and denitrogenation column), Etienne column, or mixture column. In fact, integrating two columns obtains in particular: the economy of a shell, the
15 reduction of the volume of the cold box (in the case of cryogenic distillation), and sometimes, the economy of connecting pipes between the columns. However, the methods for fabricating this type of column are more complex than those for conventional columns.

The present invention describes a method for fabricating dividing wall
20 columns mainly allowing: simpler fabrication of the shell (in particular by limiting the number of internal welds), better seal between the two parts separated by the partition, and operation with a high pressure differential between the two parts. The invention consists of a method for fabricating a dividing wall column by joining a series of main modules. These main modules have the feature of
25 each consisting of a single elementary part bent on itself, in order to form the outer envelope of the shell and the dividing wall. Secondary modules may be added to supplement the dividing wall column (ends, branches, specific stiffeners, etc.), as well as the column internals (packings, trays, distributors, etc.) and any other part or equipment required for its operation. These additions
30 can be made before, during or after the joining of the main modules.

One example of the method for fabricating the main module is shown in the Figures 1, 2 and 3. Turning first to Figure 1, the elementary part, consisting of plate metal, is illustrated. This elementary part comprises a first sheet metal segment 101, a second sheet metal segment 102, and a third sheet metal

segment 103. For purposes of illustration, these three sheet metal segments 101, 102, 103 are illustrated as being separate pieces, but in various embodiments of the present invention all three segments may comprise a single, unitary piece of metal. The second sheet metal segment 102 may be of
5 a different gauge metal, preferably a thicker gauge, than the first sheet metal segment 101 and/or the third sheet metal segment 103.

First sheet metal segment 101 further comprises a first edge, 104, a second edge 105, and a first distal region 110. Second sheet metal segment 102 further comprises a third edge, 106, a fourth edge 107, a first proximal
10 region, and a second proximal region 113. Third sheet metal segment 103 further comprises a fifth edge, 108, a sixth edge 109, and a second distal region 112.

Turning now to Figure 2, which maintains the above element numbering in the interest of clarity, first sheet metal segment 101 is bent into first arcuate
15 segment 201, with one end comprising the first distal region 110. Second sheet metal segment 102 is bent into a z-shaped, or s-shaped, form, with the two arms of the comprising the first proximal region 111 and the second proximal region 113. Third sheet metal segment 103 is bent into second arcuate segment 203, with one end comprising the second distal region 112. the arcuate
20 segments 201, 203 may be formed by rolling. The second edge 105 is attached to the third edge 106. The second edge 105 may be attached to the third edge 106 by welding. This may be a butt weld or a lap weld. The second edge 105 may be attached to the third edge 106 by being fabricated from the same sheet. The fourth edge 107 is attached to the fifth edge 108. The fourth edge 107 may
25 be attached to the fifth edge 108 by welding. This may be a butt weld or a lap weld. The fourth edge 107 may be attached to the fifth edge 108 b being fabricated from the same sheet.

Turning now to Figure 3, which also maintains the above numbering in the interest of clarity, first distal region 110 of first arcuate segment 201, is attached
30 to second proximal region 113, thereby forming a first approximately cylindrical segment 301 having an approximately semi-circular cross-section. The second distal region 112 is likewise attached to first proximal region 111, thereby forming a second approximately cylindrical segment 302 having an approximately semi-circular cross-section. The first distal region 110 may be

attached to the second proximal region 113 by welding. The second distal region 112 may be attached to the first proximal region 111 by welding. It is preferred that all welds are performed from the exterior of the partitioned column.

5 Turning now to Figures 4a and 4b, which also maintain the above numbering in the interest of clarity, the z-shape of the second sheet metal segment 102 comprises the first proximal region 111 bent into a first arm 401, the second proximal region 113 bent into a second arm 402, and an unbent central region 114. In this embodiment, the first arm 401 and second arm 402
10 are bent in a clockwise orientation, but a counterclockwise orientation is also possible. A combination of bends that incorporate a counterclockwise and a clockwise orientation (i.e. a c-shaped bend) is also possible. The first arm 401 and second arm 402 may be bent in such a manner as to be imparted with a curve of approximately equal radius to that of the overall column (i.e. an s-shaped cross section). First arm 401 and second arm 402 may be bent in such
15 a manner as to maintain a linear z-shaped cross section.

 The z-shape of the second sheet metal segment 102 may be bent so as to have an angle α between the first arm 401 (the first proximal region 111) and the central region 114. The angle α may have an angle of less than 90°. The
20 angle α may have an angle of about 90°. The angle α may have an angle of more than 90°. The z-shape of the second sheet metal segment 102 may be bent so as to have an angle β between the second arm 402 (the second proximal region 113) and the central region 114. The angle β may have an angle of less than 90 degrees. The angle α may have an angle of about 90
25 degrees. The angle β may have an angle of more than 90 degrees. The first arm 401 may have a length of about 30 mm. The first arm 401 may have a length approximately equal to the diameter of the roller in the forming apparatus. The second arm 402 may have a length of about 30 mm. The second arm 402 may have a length approximately equal to the diameter of the
30 roller in the forming apparatus.

 Turning now to Figures 5a, 5b, and 5c which also maintain the above numbering in the interest of clarity, the second sheet metal segment 102 may comprise two separate sheets of metal that are subsequently connected together. As indicated in Figure 5a, the two sheets comprising second sheet

metal segment 102 may be attached at their edges, by means of a butt-weld. As indicated in Figure 5b, the two sheets comprising second sheet metal segment 102 may be overlapped and connected by means of a lap-weld. The degree of overlap is a design choice, but typically the degree of overlap would be less than $\frac{1}{2}$ of the overall length of the central region 114, preferably less than $\frac{1}{4}$ of the overall length of central region 114. Preferably this overlap would be less than 20 cm, and more preferably this overlap would be less than 10 cm. This technique provides additional structural rigidity by means of the rib created by this overlap butt-weld.

As indicated in Figure 5c, the two sheets comprising second sheet metal segment 102 may be fully overlapped, with each overlapping segment spanning approximately the full width of central region 114. As indicated in Figure 6, these two overlapping segments may be separated by a space to form an insulating cavity 501. This insulating cavity may be filled with ambient air, it may be evacuated to form a partial vacuum, or it may be filled with an insulating media.

Turning now to Figures 7a and 7b, which also maintain the above numbering in the interest of clarity, the second sheet metal segment 102 may be axially offset Y from the first sheet metal segment 101 and third sheet metal segment 103. As can be seen in Figure 7b, once the first approximately cylindrical segment 301 and the second approximately cylindrical segment 302 form an approximately cylindrical shape, the second sheet metal segment 102 assumes the nature of a plane forming a common cord within this approximately cylindrical shape. This cord may be a diameter. This cord may be a minor cord, with the first approximately cylindrical segment 301 and the second approximately cylindrical segment 302 being of unequal crosssectional area. The axial offset Y of the second sheet metal segment 102 results in tab 701 at one end and slot 702 at the other end of the resulting approximately cylindrical segment.

Turning now to Figures 8a and 8b, as multiple subassemblies that have been fabricated according to this invention are stacked together, tab 701 of the superior unit fits into slot 702 of the inferior unit, thereby allowing welding without cross welding of any joints. A partitioned column may be fabricated by joining successive partiions of the type described above.

In one alternative of the invention, the main modules may consist of a plurality of elementary parts. The mechanical joining of these parts has the special feature of being carried out with access via the exterior of the part. This alternative therefore allows an easy assembly of the main modules because of
5 the external access and the ease of shaping of the elementary parts. It also serves to guarantee a good seal of the main module with regard to the exterior, and also a good seal between the parts of the column.

The same method can be applied to divide the column into two or more parts. In another alternative, the invention consists in joining the main modules
10 from a single or a plurality of elementary parts, but with at least one mechanical joint made with access from the interior of the elementary part. In another alternative, it is possible to use the method previously described with elementary parts having heterogeneous mechanical characteristics, in particular thicknesses, or heterogeneous materials in the case of metal plates (to better
15 withstand the pressure differentials).

Turning now to figures 9 and 10 (a-d), more details on illustrative embodiments of the above discussed welds are disclosed. Note that, as before, the numbering system has been maintained in the interest of clarity. Figure 9 illustrates how the unbent central region 114 may have an effectively linear (i.e.
20 effectively non-curved) first proximal region 111 and an effectively linear second proximal region 113. These linear first proximal region 111 and linear second proximal region 114 may then act as conventional backing strips to allow the first sheet metal segment 101 and second sheet metal segment 102 to be more easily welded together.

25 Figures 10 (a-d) illustrate alternative embodiments by which the effectively linear first proximal region 111 and the effectively linear second proximal region 113 may serve as conventional backing strips.

CLAIMS

1. A method of producing a partitioned column segment, comprising:
- a first sheet metal segment (101), a second sheet metal segment (102),
5 and a third sheet metal segment (103),
wherein said first sheet metal segment (101) comprises a first edge (104), and a second edge (105),
wherein said second sheet metal segment (102) comprises a third edge (106), and a fourth edge (107),
10 wherein said third sheet metal segment (103) comprises a fifth edge (108), and a sixth edge (109),
wherein said second edge (105) is attached to said third edge (106),
wherein said fourth edge (107) is attached to said fifth edge (108),
15 • forming said first segment (101) into a first arcuate bend in a first direction, wherein adjacent to said first edge (104) comprises a first distal region (110),
• forming said second segment (102) into a z-shaped bend, wherein said z-shape consists of a first proximal region (111), a central region (114),
20 and a second proximal region (113),
• forming said third segment (103) into a second arcuate bend in a second direction, wherein adjacent to said sixth edge (109) comprises a second distal region (112),
• attaching said first distal region (110) to said second proximate region (113), thereby producing a first approximately cylindrical segment, said
25 first approximately cylindrical segment having an approximately semi-circular cross-section,
• attaching said second distal region (112) to said first proximate region (111), thereby producing a second approximately cylindrical segment,
30 said second approximately cylindrical segment having an approximately semi-circular cross-section.
2. The method of producing a partitioned column segment of claim 1, wherein;

- said second edge (105) is attached to said third edge (106) by being fabricated from the same sheet, and
- said fourth edge (107) is attached to said fifth edge (108) by being fabricated from the same sheet.

5

3. The method of producing a partitioned column segment of claim 1 or 2, wherein:

- said second edge (105) is attached to said third edge (106) by welding; and

10

- said fourth edge (107) is attached to said fifth edge (108) by welding.

4. The method of producing a partitioned column segment of any preceding claim, wherein said second sheet metal segment (102) comprises a thicker gauge metal than said first sheet metal segment (101) and/or said third sheet metal segment (103).

15

5. The method of claim 4, wherein said first sheet metal segment (101), said second sheet metal segment (102) and said third sheet metal segment (103) are comprised of different material.

20

6. The method of claims 4 or 5, wherein the edges (104, 105, 106, 107, 108, 109) may be attached by brazing, rivets or bonding.

7. The method of producing a partitioned column segment of any preceding claim, wherein:

25

- said first distal region (110) is attached to said second proximate region (113) by welding, and
- said second distal region (112) is attached to said first proximate region (111) by welding.

30

8. The method of producing a partitioned column segment of any preceding claim, wherein all welds are performed from the exterior of the said partitioned column.




- 9 The method of producing a partitioned column segment of any preceding claim, wherein:
- said z-shaped bend has an angle α between said first proximal region (111) and said central region (114),
 - said z-shaped bend has an angle β between said second proximal region (113) and said central region (114),
10. The method of claim 7, wherein said proximal regions (111, 113) are straight and form a conventional backing strip.
11. The method of producing a partitioned column segment of claim 9,
- wherein said angle α is 90° , and
 - wherein said angle β is 90° .
12. The method of producing a partitioned column segment of claim any preceding claim, wherein said second segment (102) comprises two sheet metal segments attached together by butt-weld or lap-weld.
13. The method of producing a partitioned column segment of any preceding claim, wherein said second segment (102) comprises two sheet metal segments (114a, 114b) that are of equal length.
14. The method of producing a partitioned column segment of claim 13, wherein said two sheet metal segments (114a, 114b) are separated to form an insulating cavity.
15. The method of producing a partitioned column segment of any preceding claim, wherein
- said first approximately cylindrical segment and said second approximately cylindrical segment form an approximately cylindrical

shape with a plane forming a common cord formed in part from said second sheet metal segment (102),

- wherein said pane forming a common cord being axially offset from said approximately cylindrical form to avoid weld crossing during the joining of successive partitioned column segments.

16.A method of producing a partitioned column by means of joining successive partitioned columns of the type in claim 15.

10 17.A partitioned column as produced by one of the preceding claims.






Figure 4a



Figure 4b




Figure 5a




Figure 5b




Figure 5c

Figure 6




Figure 7a




Figure 7b




Figure 8a





Figure 8b






Figure 9








Figure 10a



INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2009/058816

A. CLASSIFICATION OF SUBJECT MATTER
INV. B01D3/32 F25J3/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
F25J B01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 43 36 983 A1 (MONTZ GMBH JULIUS [DE]) 4 May 1995 (1995-05-04)	17
A	abstract; figures column 1, line 50 - line 55 column 1, line 61 - line 67	1-16
X	DE 43 36 986 A1 (MONTZ GMBH JULIUS [DE]) 4 May 1995 (1995-05-04)	17
A	abstract; figures column 1, line 3 - line 19 column 1, line 25 - line 27 column 1, line 31 - line 36 column 1, line 58 - line 66	1-16
----- -/--		

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

1 December 2009

Date of mailing of the international search report

08/12/2009

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Lapeyrère, Jean

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2009/058816

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 914 012 A (KAIBEL GERD [DE] ET AL) 22 June 1999 (1999-06-22) abstract; figures column 1, line 47 - line 51 column 1, line 59 - line 65 column 2, line 25 - line 27 column 2, line 40 - line 53 -----	1-17
A	WO 99/01193 A (M W KELLOGG LIMITED [GB]; LESTAK FRIGYES [GB]; REAY DEREK WILLIAM [GB]) 14 January 1999 (1999-01-14) abstract; figures page 6, line 33 - page 7, line 4 page 7, line 23 - line 33 -----	1-17
A	US 2001/052453 A1 (RUST HARALD [DE] ET AL) 20 December 2001 (2001-12-20) abstract; figures page 1, paragraph 19 - page 2, paragraph 21 -----	1-17

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2009/058816

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 4336983	A1	04-05-1995	NONE
DE 4336986	A1	04-05-1995	NONE
US 5914012	A	22-06-1999	CA 2203821 A1 30-10-1997 CN 1177513 A 01-04-1998 DE 19617210 A1 06-11-1997 EP 0804951 A2 05-11-1997 ES 2183038 T3 16-03-2003 JP 10033901 A 10-02-1998
WO 9901193	A	14-01-1999	AU 8230798 A 25-01-1999
US 2001052453	A1	20-12-2001	AT 333927 T 15-08-2006 DE 10021624 A1 08-11-2001 EP 1151781 A2 07-11-2001