




(86) Date de dépôt PCT/PCT Filing Date: 2014/12/17 (87) Date publication PCT/PCT Publication Date: 2015/06/25 (45) Date de délivrance/Issue Date: 2019/04/23 (85) Entrée phase nationale/National Entry: 2016/06/14 (86) N° demande PCT/PCT Application No.: CN 2014/094053 (87) N° publication PCT/PCT Publication No.: 2015/090197 (30) Priorité/Priority: 2013/12/17 (CN201310695461.0)	(51) Cl.Int./Int.Cl. <i>G06F 9/50</i> (2006.01) (72) Inventeurs/Inventors: LU, GANG, CN; ZHAN, JIANFENG, CN; GAO, YUNWEI, CN; TAN, CHONGKANG, CN; XUE, DONGLIANG, CN (73) Propriétaire/Owner: HUAWEI TECHNOLOGIES CO., LTD., CN (74) Agent: SMART & BIGGAR
---	---

(54) **Titre :** PROCÉDE DE TRAITEMENT DE RESSOURCE, SYSTÈME D'EXPLOITATION ET DISPOSITIF
(54) **Title:** RESOURCE PROCESSING METHOD, OPERATING SYSTEM, AND DEVICE



(57) **Abrégé/Abstract:**
Embodiments of the present invention provide a resource processing method, an operating system, and a device. The method is applied to a multi-core operating system, where the multi-core operating system includes a management operating system and

(57) Abrégé(suite)/Abstract(continued):

multiple load operating systems that run on a host machine and includes a physical resource pool. The method includes: allocating, by the management operating system to each load operating system, a physical resource set exclusively used by each load operating system; constructing a startup mirror for each load operating system; setting, for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the startup mirror; determining, in processor cores allocated to a first load operating system, a startup processor core that starts up the first load operating system; instructing the startup processor core to read a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a startup mirror of the first load operating system; and instructing the startup processor core to execute the startup mirror pre-constructed for the first load operating system.

ABSTRACT

Embodiments of the present invention provide a resource processing method, an operating system, and a device. The method is applied to a multi-core operating system, where the multi-core operating system includes a management operating system and multiple load operating systems that run on a host machine and includes a physical resource pool. The method includes: allocating, by the management operating system to each load operating system, a physical resource set exclusively used by each load operating system; constructing a startup mirror for each load operating system; setting, for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the startup mirror; determining, in processor cores allocated to a first load operating system, a startup processor core that starts up the first load operating system; instructing the startup processor core to read a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a startup mirror of the first load operating system; and instructing the startup processor core to execute the startup mirror pre-constructed for the first load operating system.

RESOURCE PROCESSING METHOD, OPERATING SYSTEM, AND DEVICE

TECHNICAL FIELD

Embodiments of the present invention relate to communications technologies, and in
5 particular, to a resource processing method, an operating system, and a device.

BACKGROUND

Currently, processors have entered an age of multi-core processors, and most multi-core
processors support a virtualization technology. In a multi-core processor, multiple processor
cores are integrated into one chip, thereby making parallel execution possible. Moreover, one
10 physical computer can be converted to multiple virtual computers by using the virtualization
technology. Therefore, with a multi-core processor and the virtualization technology
combined, multiple operating systems can run on one physical computer simultaneously.

In an existing heterogeneous multi-kernel operating system architecture, one management
operating system and multiple load operating systems run on one physical computer (host
15 machine). The management operating system is configured to provide an execution
environment for various application programs and the multiple load operating systems. The
load operating systems are configured to provide an execution environment for various
application programs. The management operating system provides physical resources
corresponding to the execution environment for the load operating systems by using a
20 hypervisor (Hypervisor), where the physical resources mainly include a processor core, a
physical memory, an external device, and the like. Each load operating system uses one or
more processor cores in an exclusive manner, and shares a physical memory, an external

device, and the like with another load operating system in a time division multiplexing manner.

Because multiple load operating systems share a physical memory, an external device, and the like in a time division multiplexing manner, when there are a relatively large quantity of
5 load operating systems, a delay is caused for running of the load operating systems, thereby reducing overall performance of the load operating systems.

SUMMARY

Embodiments of the present invention provide a resource processing method, an operating system, and a device, so as to improve overall performance of a load operating system.

10 According to a first aspect, an embodiment of the present invention provides a resource processing method, where the method is applied to a multi-kernel operating system, the multi-kernel operating system includes a management operating system and multiple load operating systems that run on a host machine and includes a physical resource pool, the physical resource pool includes processor cores and a physical memory that are of the host
15 machine, and the method includes:

allocating, by the management operating system to each load operating system, a physical resource set exclusively used by each load operating system, constructing a boot image for each load operating system, and setting, for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is
20 required for executing the boot image, where each physical resource set includes some of the processor cores of the host machine and a part of the physical memory of the host machine;

determining, by the management operating system and in processor cores allocated to a first load operating system, a startup processor core that starts up the first load operating system, where the first load operating system is any one of the load operating
25 systems;

instructing, by the management operating system, the startup processor core to

read a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system and is pre-constructed by the management operating system, so as to enable the startup processor core to access, in a process of executing the boot image and according to the mapping

5 relationship, the physical memory address; and instructing the startup processor core to execute the boot image pre-constructed for the first load operating system, where the boot image includes a startup parameter of the first load operating system, the startup parameter includes identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system.

10 With reference to the first aspect, in a first possible implementation manner of the first aspect, the instructing, by the management operating system, the startup processor core to read a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system and is pre-constructed by the management operating system, and the instructing the startup

15 processor core to execute the boot image pre-constructed for the first load operating system include:

sending, by the management operating system, an inter-core interrupt message to the startup processor core, where the inter-core interrupt message instructs the startup processor core to execute an initialization program that is configured to initialize the startup

20 processor core and that is corresponding to the first load operating system; and

instructing, by the management operating system by instructing the startup processor core to execute the initialization program corresponding to the first load operating system, the startup processor core to read, from the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that

25 is required for executing the boot image of the first load operating system; and instructing the startup processor core to jump, after running of the initialization program ends, to the location that is of the boot image and is in the physical memory, so as to execute the boot image of the

first load operating system.

With reference to the first possible implementation manner of the first aspect, in a second possible implementation manner of the first aspect, before the setting, by the management operating system for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image, the method further includes:

presetting, by the management operating system for the first load operating system, an initialization program that is configured to initialize the first load operating system, and presetting, in the initialization program, the location that is of the boot image of the first load operating system and that is in the physical memory address; and

the setting, by the management operating system for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image includes:

setting, by the management operating system for the first load operating system and in the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image.

With reference to the first aspect, in a third possible implementation manner of the first aspect, before the determining, by the management operating system and in processor cores allocated to a first load operating system, a startup processor core that starts up the first load operating system, the method further includes:

acquiring, by the management operating system, available processor cores of a second load operating system, where the second load operating system is a logged-out load operating system, other than the first load operating system, in the multiple load operating systems, the available processor cores include a processor core that has been started up, and a physical resource set of the first load operating system includes the available processor cores; and

the determining, by the management operating system and in processor cores

allocated to a first load operating system, a startup processor core that starts up the first load operating system includes:

when the physical resource set of the first load operating system includes the available processor cores, determining, by the management operating system and in the available processor cores, the startup processor core that starts up the first load operating system.

With reference to the third possible implementation manner of the first aspect, in a fourth possible implementation manner of the first aspect, after the determining, by the management operating system and in the available processor cores, the startup processor core that starts up the first load operating system, the method further includes:

presetting, by the management operating system for the first load operating system, a daemon on the startup processor core, and presetting, in the daemon, a location that is of the boot image of the first load operating system and that is in the physical memory address; and

the setting, by the management operating system for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image includes:

setting, by the management operating system for the first load operating system and in the daemon, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image.

With reference to the fourth possible implementation manner of the first aspect, in a fifth possible implementation manner of the first aspect, the instructing, by the management operating system, the startup processor core to read a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system and is pre-constructed by the management operating system, and the instructing the startup processor core to execute the boot image pre-constructed for the first load operating system include:

sending, by the management operating system, an inter-core interrupt message to

- the daemon running on the startup processor core, where the inter-core interrupt message instructs the startup processor core to read, from the daemon, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image and is pre-constructed by the management operating system for the
- 5 first load operating system; and the location that is of the boot image corresponding to the first load operating system, that is in the physical memory address, and that is preset in the daemon by the management operating system instructs the startup processor core to jump to the location that is in the physical memory address and in which the boot image is located, so as to execute the boot image of the first load operating system.
- 10 With reference to the first aspect, or any possible implementation manner of the first to the fifth possible implementation manners of the first aspect, in a sixth possible implementation manner of the first aspect, the allocating, by the management operating system to each load operating system, a physical resource set exclusively used by each load operating system includes:
- 15 performing, by the management operating system according to a quantity of the load operating systems, first-time division on available physical resources that are in the physical resource pool and that are corresponding to identifiers of physical resources in a list of the available physical resources in the resource pool, to obtain multiple physical resource sets, where a quantity of the physical resource sets equals the quantity of the load operating
- 20 systems, and determining, by the management operating system, a correspondence between each load operating system and each physical resource set; and
- allocating, by the management operating system to each load operating system according to the correspondence, the physical resource set exclusively used by each load operating system.
- 25 With reference to the sixth possible implementation manner of the first aspect, in a seventh possible implementation manner of the first aspect, each physical resource set further includes some external devices of the host machine; and

the startup parameter further includes an identifier of an external device allocated to the first load operating system and a device description information table corresponding to the external device.

With reference to the seventh possible implementation manner of the first aspect, in an eighth possible implementation manner of the first aspect, after the instructing, by the management operating system, the startup processor core to execute the boot image pre-constructed for the first load operating system, the method further includes:

monitoring, by the management operating system, running of the first load operating system;

when utilization of a physical resource allocated to the first load operating system is less than a first preset threshold, determining that a physical resource needs to be reduced for the first load operating system, and determining a type identifier of the physical resource that needs to be reduced, where the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource, a physical memory resource, or an external device resource; and

performing, by the management operating system according to the type identifier of the physical resource that needs to be reduced, second-time division on the available physical resources that are in the physical resource pool and that are corresponding to the identifiers of the physical resources in the list of the available physical resources in the resource pool, and reducing the physical resource of the first load operating system, where the reduced physical resource is a physical resource corresponding to the type identifier of the physical resource that needs to be reduced.

With reference to the seventh possible implementation manner of the first aspect, in a ninth possible implementation manner of the first aspect, after the instructing, by the management operating system, the startup processor core to execute the boot image pre-constructed for the first load operating system, the method further includes:

monitoring, by the management operating system, running of the first load

operating system;

when utilization of a physical resource allocated to the first load operating system is greater than a second preset threshold, determining that a physical resource needs to be added for the first load operating system, and determining a type identifier of the physical resource that needs to be added, where the type identifier of the physical resource is used to distinguish whether the physical resource that needs to be added is a processor core resource, a physical memory resource, or an external device resource; and

performing, by the management operating system according to the type identifier of the physical resource that needs to be added, second-time division on the available physical resources that are in the physical resource pool and that are corresponding to the identifiers of the physical resources in the list of the available physical resources in the resource pool, and adding the physical resource of the first load operating system, where the added physical resource is a physical resource corresponding to the type identifier of the physical resource that needs to be added.

According to a second aspect, an embodiment of the present invention provides a resource processing method, where the method is applied to a multi-kernel operating system, the multi-kernel operating system includes a management operating system and multiple load operating systems that run on a host machine and includes a physical resource pool, the physical resource pool includes processor cores and a physical memory that are of the host machine, wherein in an embodiment the management operating system is configured to manage the multiple load operating systems, which includes allocating, to the multiple load operating systems, physical resources exclusively used by the multiple load operating systems, and being responsible for startup of the load operating systems, wherein each load operating system exclusively uses, and in an embodiment accesses, a physical resource set allocated by the management operating system, and each physical resource set includes some of the processor cores of the host machine and a part of the physical memory of the host machine; the management operating system pre-constructs a boot image for each load

operating system, and sets, for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image; and the method includes:

- 5 reading, by a startup processor core of a first load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system, where the mapping relationship is used to enable the startup processor core of the first load operating system to access the physical memory address, and the first load operating system is any load operating system in the multi-kernel operating system;
- 10 jumping, by the startup processor core of the first load operating system according to an instruction that is set by the management operating system and that is for executing a boot image jump, to a location that is of the boot image corresponding to the first load operating system and that is in the physical memory address, and executing, according to the mapping relationship, the boot image corresponding to the first load operating system;
- 15 acquiring, by the startup processor core of the first load operating system and in a process of executing the boot image of the first load operating system, a startup parameter of the first load operating system from the boot image of the first load operating system, where the startup parameter includes identifiers of processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load
- 20 operating system; and
- determining, by the first load operating system according to the identifiers of the processor cores and the identifier of the physical memory address of the first load operating system, a physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system.
- 25 With reference to the second aspect, in a first possible implementation manner of the second aspect, the reading, by a startup processor core of a first load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is

required for executing a boot image of the first load operating system includes:

receiving, by the startup processor core of the first load operating system, an inter-core interrupt message sent by the management operating system, where the startup processor core executes, according to an instruction of the inter-core interrupt message, an initialization program that is configured to initialize the startup processor core and that is
5 corresponding to the first load operating system; and

executing, by the startup processor core of the first load operating system, the initialization program, and reading, from the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required
10 for executing the boot image and is pre-constructed by the management operating system for the first load operating system; and

the jumping, by the startup processor core of the first load operating system according to an instruction that is set by the management operating system and that is for executing a boot image jump, to a location that is of the boot image corresponding to the first
15 load operating system and that is in the physical memory address includes:

executing, by the startup processor core of the first load operating system, the initialization program, reading, from the initialization program, a jump instruction that is preset in the initialization program by the management operating system, and jumping to the location that is of the boot image corresponding to the first load operating system and that is
20 in the physical memory address.

With reference to the second aspect, in a second possible implementation manner of the second aspect, the startup processor core of the first load operating system is a processor core that has been started up and that is determined by the management operating system, a daemon runs on the startup processor core of the first load operating system, the daemon is
25 preset by the management operating system for the first load operating system, the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address and the mapping relationship that is from the virtual memory

address to the physical memory address and that is required for executing the boot image are set in the daemon;

the reading, by a startup processor core of a first load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is
5 required for executing a boot image of the first load operating system includes:

receiving, by the daemon running on the startup processor core of the first load operating system, an inter-core interrupt message sent by the management operating system, and reading, by the startup processor core according to an instruction of the inter-core interrupt message and from the daemon, the mapping relationship that is from the virtual
10 memory address to the physical memory address and that is required for executing the boot image and is pre-constructed by the management operating system for the first load operating system; and

the jumping, by the startup processor core of the first load operating system according to an instruction that is set by the management operating system and that is for
15 executing a boot image jump, to a location that is of the boot image corresponding to the first load operating system and that is in the physical memory address includes:

reading, by the startup processor core of the first load operating system, a jump instruction that is preset in the daemon by the management operating system, and jumping to the location that is of the boot image corresponding to the first load operating system and that
20 is in the physical memory address.

With reference to the second aspect, or the first or the second possible implementation manner of the second aspect, in a third possible implementation manner of the second aspect, each physical resource set further includes some external devices of the host machine; and

the startup parameter further includes an identifier of an external device allocated
25 by the management operating system to the first load operating system and a device description information table corresponding to the external device.

According to a third aspect, an embodiment of the present invention provides a management

operating system, where the management operating system is applied to a multi-kernel operating system, the multi-kernel operating system includes the management operating system and multiple load operating systems that run on a host machine and includes a physical resource pool, the physical resource pool includes processor cores and a physical memory that are of the host machine, and the management operating system includes:

a resource allocating module, configured to allocate, to each load operating system, a physical resource set exclusively used by each load operating system, where each physical resource set includes some of the processor cores of the host machine and a part of the physical memory of the host machine;

a mapping relationship setting module, configured to: construct a boot image for each load operating system, and set, for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image;

a startup processor core determining module, configured to determine, in processor cores allocated to a first load operating system, a startup processor core that starts up the first load operating system, where the first load operating system is any one of the load operating systems;

an instructing module, configured to instruct the startup processor core to read a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system and is pre-constructed by the mapping relationship setting module, so as to enable the startup processor core to access, in a process of executing the boot image and according to the mapping relationship, the physical memory address; and instruct the startup processor core to execute the boot image pre-constructed for the first load operating system, where the boot image includes a startup parameter of the first load operating system, the startup parameter includes identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system.

With reference to the third aspect, in a first possible implementation manner of the third aspect, the instructing module is specifically configured to:

5 send an inter-core interrupt message to the startup processor core, where the inter-core interrupt message instructs the startup processor core to execute an initialization program that is configured to initialize the startup processor core and that is corresponding to the first load operating system; and

10 instruct, by instructing the startup processor core to execute the initialization program corresponding to the first load operating system, the startup processor core to read, from the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image of the first load operating system; and instruct the startup processor core to jump, after running of the initialization program ends, to the location that is of the boot image and is in the physical memory, so as to execute the boot image of the first load operating system.

15 With reference to the first possible implementation manner of the third aspect, in a second possible implementation manner of the third aspect, the management operating system further includes:

20 an initialization program configuring module, configured to: before the mapping relationship setting module sets, for each load operating system, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image, preset, for the first load operating system, an initialization program that is configured to initialize the first load operating system, and preset, in the initialization program, the location that is of the boot image of the first load operating system and that is in the physical memory address; and

25 the mapping relationship setting module is specifically configured to set, in the initialization program and for the first load operating system, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image.

With reference to the third aspect, in a third possible implementation manner of the third aspect, the management operating system further includes:

an available-processor-core acquiring module, configured to acquire available processor cores of a second load operating system before the startup processor core determining module determines, in the processor cores allocated to the first load operating system, the startup processor core that starts up the first load operating system, where the second load operating system is a logged-out load operating system, other than the first load operating system, in the multiple load operating systems, the available processor cores include a processor core that has been started up, and a physical resource set of the first load operating system includes the available processor cores; and

the startup processor core determining module is specifically configured to: when the physical resource set of the first load operating system includes the available processor cores, determine, in the available processor cores, the startup processor core that starts up the first load operating system.

With reference to the third possible implementation manner of the third aspect, in a fourth possible implementation manner of the third aspect, the management operating system further includes:

a daemon configuring module, configured to preset, for the first load operating system, a daemon on the startup processor core after the startup processor core determining module determines, in the available processor cores, the startup processor core that starts up the first load operating system, and preset, in the daemon, a location that is of the boot image of the first load operating system and that is in the physical memory address; and

the mapping relationship setting module is specifically configured to set, for the first load operating system and in the daemon, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image.

With reference to the fourth possible implementation manner of the third aspect, in a fifth

possible implementation manner of the third aspect, the instructing module is specifically configured to: send an inter-core interrupt message to the daemon running on the startup processor core, where the inter-core interrupt message instructs the startup processor core to read, from the daemon, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image and is pre-constructed by the management operating system for the first load operating system; and the location that is of the boot image corresponding to the first load operating system, that is in the physical memory address, and that is preset in the daemon by the daemon configuring module instructs the startup processor core to jump to the location that is in the physical memory address and in which the boot image is located, so as to execute the boot image of the first load operating system.

With reference to the third aspect, or any possible implementation manner of the first to the fifth possible implementation manners of the third aspect, in a sixth possible implementation manner of the third aspect, the resource allocating module is specifically configured to:

perform, according to a quantity of the load operating systems, first-time division on available physical resources that are in the physical resource pool and that are corresponding to identifiers of physical resources in a list of the available physical resources in the resource pool, to obtain multiple physical resource sets, where a quantity of the physical resource sets equals the quantity of the load operating systems, and the management operating system determines a correspondence between each load operating system and each physical resource set; and

allocate, to each load operating system according to the correspondence, the physical resource set exclusively used by each load operating system.

With reference to the sixth possible implementation manner of the third aspect, in a seventh possible implementation manner of the third aspect, each physical resource set further includes some external devices of the host machine; and

the startup parameter further includes an identifier of an external device allocated

to the first load operating system and a device description information table corresponding to the external device.

With reference to the seventh possible implementation manner of the third aspect, in an eighth possible implementation manner of the third aspect, the management operating system
5 further includes:

a first monitoring module, configured to monitor, after the instructing module instructs the startup processor core to execute the boot image pre-constructed for the first load operating system, running of the first load operating system; and

a first resource managing module, configured to determine that a physical
10 resource needs to be reduced for the first load operating system if a monitoring result of the first monitoring module is that utilization of a physical resource allocated to the first load operating system is less than a first preset threshold, and determine a type identifier of the physical resource that needs to be reduced, where the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource, a physical
15 memory resource, or an external device resource; and

the resource allocating module is further configured to perform, according to the type identifier of the physical resource that needs to be reduced, second-time division on the available physical resources that are in the physical resource pool and that are corresponding to the identifiers of the physical resources in the list of the available physical resources in the
20 resource pool, and reduce the physical resource of the first load operating system, where the reduced physical resource is a physical resource corresponding to the type identifier of the physical resource that needs to be reduced.

With reference to the seventh possible implementation manner of the third aspect, in a ninth possible implementation manner of the third aspect, the management operating system further
25 includes:

a second monitoring module, configured to monitor, after the instructing module instructs the startup processor core to execute the boot image pre-constructed for the first load

operating system, running of the first load operating system; and

a second resource managing module, configured to determine that a physical resource needs to be added for the first load operating system if a monitoring result of the second monitoring module is that utilization of a physical resource allocated to the first load operating system is greater than a second preset threshold, and determine a type identifier of the physical resource that needs to be added, where the type identifier of the physical resource is used to distinguish whether the physical resource that needs to be added is a processor core resource, a physical memory resource, or an external device resource; and

the resource allocating module is further configured to perform, according to the type identifier of the physical resource that needs to be added, second-time division on the available physical resources that are in the physical resource pool and that are corresponding to the identifiers of the physical resources in the list of the available physical resources in the resource pool, and add the physical resource of the first load operating system, where the added physical resource is a physical resource corresponding to the type identifier of the physical resource that needs to be added.

With reference to the seventh possible implementation manner of the third aspect, in a tenth possible implementation manner of the third aspect, the management operating system further includes:

a first receiving module, configured to receive, after the instructing module instructs the startup processor core to execute the boot image pre-constructed for the first load operating system, a resource reducing request message sent by the first load operating system, where the resource reducing request message includes a type identifier of a physical resource that needs to be reduced, and the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource, a physical memory resource, or an external device resource; and

the resource allocating module is further configured to perform, according to the type identifier, of the physical resource that needs to be reduced, in the resource reducing

request message, second-time division on the available physical resources that are in the physical resource pool and that are corresponding to the identifiers of the physical resources in the list of the available physical resources in the resource pool, and reduce the physical resource of the first load operating system, where the reduced physical resource is a physical
5 resource corresponding to the type identifier of the physical resource that needs to be reduced.

According to a fourth aspect, an embodiment of the present invention provides a load operating system, where the load operating system is applied to a multi-kernel operating system, the multi-kernel operating system includes a management operating system and
10 multiple load operating systems that run on a host machine and includes a physical resource pool, the physical resource pool includes processor cores and a physical memory that are of the host machine, each load operating system exclusively uses a physical resource set allocated by the management operating system, and each physical resource set includes some of the processor cores of the host machine and a part of the physical memory of the host
15 machine; the management operating system pre-constructs a boot image for each load operating system, and sets, for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image; and the load operating system includes:

a mapping relationship acquiring module, configured to read a mapping
20 relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of a first load operating system, where the mapping relationship is used to enable a startup processor core of the first load operating system to access the physical memory address, and the first load operating system is any load operating system in the multi-kernel operating system;

25 an instruction executing module, configured to jump, according to an instruction that is set by the management operating system and that is for executing a boot image jump, to a location that is of the boot image corresponding to the first load operating system and

that is in the physical memory address, and execute, according to the mapping relationship, the boot image corresponding to the first load operating system;

a startup parameter acquiring module, configured to acquire, in a process of executing the boot image of the first load operating system by the instruction executing module, a startup parameter of the first load operating system from the boot image of the first load operating system, where the startup parameter includes identifiers of processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system; and

a physical resource set acquiring module, configured to determine, according to the identifiers of the processor cores and the identifier of the physical memory address of the first load operating system, a physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system.

With reference to the fourth aspect, in a first possible implementation manner of the fourth aspect, the mapping relationship acquiring module is specifically configured to:

receive an inter-core interrupt message sent by the management operating system, where the startup processor core executes, according to an instruction of the inter-core interrupt message, an initialization program that is configured to initialize the startup processor core and that is corresponding to the first load operating system; and

execute the initialization program, and read, from the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image and is pre-constructed by the management operating system for the first load operating system; and

the instruction executing module is specifically configured to: execute the initialization program, read, from the initialization program, a jump instruction that is preset in the initialization program by the management operating system, and jump to the location that is of the boot image corresponding to the first load operating system and that is in the

physical memory address.

With reference to the fourth aspect, in a second possible implementation manner of the fourth aspect, the startup processor core of the first load operating system is a processor core that has been started up and that is determined by the management operating system, a daemon
5 runs on the startup processor core of the first load operating system, the daemon is preset by the management operating system for the first load operating system, the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address and the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image are set in the
10 daemon;

the mapping relationship acquiring module is specifically configured to read, from the daemon and according to an instruction of an inter-core interrupt message after the daemon running on the startup processor core receives the inter-core interrupt message sent by the management operating system, the mapping relationship that is from the virtual
15 memory address to the physical memory address and that is required for executing the boot image and is pre-constructed by the management operating system for the first load operating system; and

the instruction executing module is specifically configured to: read a jump instruction that is preset in the daemon by the management operating system, and jump to the
20 location that is of the boot image corresponding to the first load operating system and that is in the physical memory address.

With reference to the fourth aspect, or the first or the second possible implementation manner of the fourth aspect, in a third possible implementation manner of the fourth aspect, each physical resource set further includes some external devices of the host machine; and

25 the startup parameter further includes an identifier of an external device allocated by the management operating system to the first load operating system and a device description information table corresponding to the external device.

According to a fifth aspect, an embodiment of the present invention provides a multi-kernel operating system, including:

the management operating system running on a host machine described in the third aspect;

5 the multiple load operating systems described in the fourth aspect; and

a physical resource pool, where the physical resource pool includes processor cores, a physical memory, and an external device that are of the host machine.

According to a sixth aspect, an embodiment of the present invention provides a host machine, including a processor and a memory, where the memory stores an execution instruction, and

10 when the host machine runs, the processor communicates with the memory, and the processor executes the execution instruction, so as to enable the host machine to execute the resource processing method described in the first aspect, or any possible implementation manner of the first to the ninth possible implementation manners of the first aspect.

According to a seventh aspect, an embodiment of the present invention provides a host

15 machine. The host machine includes a physical resource pool and includes, in a multi-kernel operating system in an embodiment, a management operating system and multiple load operating systems that run on the host machine. The physical resource pool includes processor cores and a physical memory that are of the host machine. In an embodiment, the management operating system is configured to manage the multiple load operating systems, which includes allocating, to the multiple load operating systems, physical resources
20 exclusively used by the multiple load operating systems, and being responsible for startup of the load operating systems, wherein a load operating system is configured to exclusively use and access a physical resource allocated by the management operating system after the load operating system is started up. The management operating system includes:

25 a resource allocating module, configured to allocate, to a first load operating system, a physical resource set exclusively used by the first load operating system, where the physical resource set comprises some of the processor cores and a part of the physical memory that are

of the host machine, and the first load operating system is any load operating system in the multiple load operating systems;

5 a startup processor core determining module, configured to determine, in processor cores allocated to the first load operating system, a startup processor core that starts up the first load operating system; and

an instructing module, configured to instruct the startup processor core to read a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system and is pre-constructed by the management operating system, and configured to instruct the startup
10 processor core to execute the boot image pre-constructed for the first load operating system, so as to start up the first load operating system, where the physical memory address comprises a location of the boot image corresponding to the first load operating system, the boot image comprises a startup parameter of the first load operating system, and the startup parameter comprises identifiers of the processor cores allocated to the first load operating
15 system and an identifier of the physical memory address allocated to the first load operating system; and

the first load operating system includes:

a mapping relationship acquiring module, configured to read the mapping relationship that is from the virtual memory address to the physical memory address and that is required
20 for executing the boot image of the first load operating system, where the mapping relationship is used to enable the startup processor core of the first load operating system to access the physical memory address;

an instruction executing module, configured to jump, according to an instruction that is set by the management operating system and that is for executing a boot image jump, to the
25 location that is of the boot image corresponding to the first load operating system and that is in the physical memory address, and execute, according to the mapping relationship, the boot image corresponding to the first load operating system;

a startup parameter acquiring module, configured to acquire, in a process of executing the boot image of the first load operating system, the startup parameter of the first load operating system from the boot image of the first load operating system; and

5 a physical resource set acquiring module, configured to determine, according to the identifiers of the processor cores and the identifier of the physical memory address of the first load operating system, the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system.

10 With reference to the seventh aspect, in a first possible implementation manner of the seventh aspect, the management operating system further includes:

a mapping relationship setting module, configured to: construct the boot image for the first load operating system, and set, for the first load operating system, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image.

15 With reference to the seventh aspect, or the first possible implementation manner of the seventh aspect, in a second possible implementation manner of the seventh aspect, the instructing module is specifically configured to:

20 send an inter-core interrupt message to the startup processor core, where the inter-core interrupt message instructs the startup processor core to execute an initialization program that is configured to initialize the startup processor core and that is corresponding to the first load operating system;

25 instruct, by instructing the startup processor core to execute the initialization program corresponding to the first load operating system, the startup processor core to read, from the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image of the first load operating system; and

instruct the startup processor core to jump, after running of the initialization program

ends, to the location that is of the boot image and is in the physical memory, so as to execute the boot image of the first load operating system;

the mapping relationship acquiring module is specifically configured to:

receive the inter-core interrupt message sent by the management operating system,
 5 where the inter-core interrupt message is used to instruct the startup processor core to execute the initialization program that is configured to initialize the startup processor core and that is corresponding to the first load operating system; and

execute the initialization program, and read, from the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address
 10 and that is required for executing the boot image and is pre-constructed by the management operating system for the first load operating system; and

the instruction executing module is specifically configured to: execute the initialization program, read, from the initialization program, a jump instruction that is preset in the initialization program by the management operating system, and jump to the location that is
 15 of the boot image corresponding to the first load operating system and that is in the physical memory address.

With reference to the seventh aspect, or the first possible implementation manner of the seventh aspect, in a third possible implementation manner of the seventh aspect, the management operating system further includes:

20 an available-processor-core acquiring module, configured to acquire available processor cores of a second load operating system before the startup processor core that starts up the first load operating system is determined in the processor cores allocated to the first load operating system, where the second load operating system is a logged-out load operating system, other than the first load operating system, in the multiple load operating systems, the
 25 available processor cores comprise a processor core that has been started up; and

the startup processor core determining module is specifically configured to: when the physical resource set of the first load operating system comprises the available processor

cores, determine, in the available processor cores, the startup processor core that starts up the first load operating system.

With reference to the seventh aspect, or the first possible implementation manner of the seventh aspect, in a fourth possible implementation manner of the seventh aspect, the instruction executing module is further configured to execute, by using the processor cores allocated to the first load operating system, a privileged instruction delivered by the management operating system.

With reference to the seventh aspect, in a fifth possible implementation manner of the seventh aspect, the management operating system further includes:

10 a first monitoring module, configured to monitor running of the first load operating system after the startup processor core is instructed to execute the boot image pre-constructed for the first load operating system; and

the resource allocating module is further configured to: when utilization of a physical resource allocated to the first load operating system is less than a first preset threshold, determine a type identifier of a physical resource that needs to be reduced for the first load operating system, and reduce the physical resource of the first load operating system according to the type identifier of the physical resource that needs to be reduced; or

when utilization of a physical resource allocated to the first load operating system is greater than a second preset threshold, determine a type identifier of a physical resource that needs to be added for the first load operating system, and add the physical resource of the first load operating system according to the type identifier of the physical resource that needs to be added, where

the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource or a physical memory resource.

25 With reference to the seventh aspect, in a sixth possible implementation manner of the seventh aspect, the first load operating system further includes:

a first monitoring module, configured to monitor a physical resource of the first load

operating system; and

a first sending module, configured to: if the first load operating system determines that utilization of the physical resource allocated by the management operating system to the first load operating system is less than a first preset threshold, send a resource reducing request message to the management operating system, where the resource reducing request message comprises a type identifier of a physical resource that needs to be reduced, and the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource or a physical memory resource; and

the management operating system further comprises:

10 a first receiving module, configured to receive the resource reducing request message sent by the first load operating system; and

the resource allocating module is further configured to reduce the physical resource of the first load operating system according to the type identifier of the physical resource that needs to be reduced.

15 With reference to the seventh aspect, in a seventh possible implementation manner of the seventh aspect, the first load operating system further includes:

a second monitoring module, configured to monitor a physical resource of the first load operating system; and

a second sending module, configured to: when the first load operating system determines that utilization of the physical resource allocated by the management operating system to the first load operating system is greater than a second preset threshold, send a resource adding request message to the management operating system, where the resource adding request message comprises a type identifier of a physical resource that needs to be added, and the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource or a physical memory resource; and

the management operating system further comprises:

a second receiving module, configured to receive the resource adding request message

sent by the first load operating system; and

the resource allocating module is further configured to add the physical resource of the first load operating system according to the type identifier of the physical resource that needs to be added.

5 With reference to the fifth or the seventh possible implementation manner of the seventh aspect, in the eighth possible implementation manner of the seventh aspect, the resource allocating module is specifically configured to:

mark a processor core, which needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and send a resource adding
10 message to the first load operating system, where the resource adding message comprises an identifier of the processor core that needs to be added; and

send a jump instruction to the added processor core, where the jump instruction is used to instruct the added processor core to execute a kernel program of the first load operating system, and the kernel program comprises all mapping relationships that are from virtual
15 memory addresses to physical memory addresses and that are required for executing the first load operating system; and

the physical resource set acquiring module is further specifically configured to:

determine, according to the identifier of the processor core that needs to be added, the processor core added by the management operating system for the first load operating system;
20 and

receive, by using the added processor core of the first load operating system, the jump instruction sent by the management operating system, execute the kernel program of the first load operating system according to the jump instruction, and read, from the kernel program, all the mapping relationships that are from the virtual memory addresses to the physical
25 memory addresses and that are required for executing the first load operating system.

With reference to the fifth or the seventh possible implementation manner of the seventh aspect, in the ninth possible implementation manner of the seventh aspect, if the physical

resource that needs to be added is a physical memory resource,

the resource allocating module is specifically configured to: mark a physical memory address, which needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and send a resource adding message to the first
5 load operating system, where the resource adding message comprises an identifier of the physical memory address that needs to be added; and

the physical resource set acquiring module is specifically configured to: receive the resource adding message sent by the management operating system, and determine, according to the identifier of the physical memory address that needs to be added, the physical memory
10 address added by the management operating system for the first load operating system.

With reference to the fifth or the sixth possible implementation manner of the seventh aspect, in the tenth possible implementation manner of the seventh aspect, if the physical resource that needs to be reduced is a processor core or a physical memory resource,

the physical resource set acquiring module is specifically configured to: receive a
15 resource reducing message sent by the management operating system, and release the physical resource according to the identifier, carried by the resource reducing message, of the physical resource that needs to be released; and

the resource allocating module is specifically configured to acquire the identifier of the physical resource released by the first load operating system, and add the identifier of the
20 released physical resource to a list of available physical resources in the resource pool.

According to an eighth aspect, an embodiment of the present invention provides a resource processing method. The method is applied to a multi-kernel operating system. The multi-kernel operating system comprises a management operating system and multiple load operating systems that run on a host machine. The host machine includes a physical resource
25 pool. The physical resource pool includes processor cores and a physical memory that are of the host machine. In an embodiment, the management operating system is configured to manage the multiple load operating systems, which includes allocating, to the multiple load

operating systems, physical resources exclusively used by the multiple load operating systems, and being responsible for startup of the load operating systems, wherein a load operating system is configured to exclusively use and access a physical resource allocated by the management operating system after the load operating system is started up. After
5 determining, by the management operating system and in processor cores allocated to a first load operating system in an embodiment, a startup processor core that starts up the first load operating system in processor cores allocated to a first load operating system, the management operating system instructs the startup processor core to read a mapping relationship that is from a virtual memory address to a physical memory address and that is
10 required for executing a boot image of the first load operating system and is pre-constructed by the management operating system, where the physical memory address comprises a location of the boot image corresponding to the first load operating system. The first load operating system is any load operating system in the multiple load operating systems. The management operating system pre-allocates, to the first load operating system, a physical
15 resource set exclusively used by the first load operating system, and the physical resource set includes some of the processor cores and a part of the physical memory that are of the host machine. Then, the management operating system instructs the startup processor core to execute the boot image pre-constructed for the first load operating system, so as to start up the first load operating system, where the boot image includes a startup parameter of the first
20 load operating system, and the startup parameter includes identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system.

According to a ninth aspect, an embodiment of the present invention provides a host machine, wherein the host machine is configured to run, in a multi-kernel operating system in
25 an embodiment, a management operating system and multiple load operating systems, the multiple load operating systems comprise a first load operating system. In an embodiment, the management operating system is configured to manage the multiple load operating

systems, which includes allocating, to the multiple load operating systems, physical resources exclusively used by the multiple load operating systems, and being responsible for startup of the load operating systems, wherein a load operating system is configured to exclusively use and access a physical resource allocated by the management operating system after the load

5 operating system is started up. The host machine comprises a physical resource pool, the physical resource pool comprises processor cores and a physical memory that are of the host machine, and when the host machine runs, the management operating system is configured to:

determine, in processor cores allocated to the first load operating system, a startup

10 processor core that starts up the first load operating system, wherein the first load operating system is any load operating system in the multiple load operating systems, the management operating system allocates, to the first load operating system, a physical resource set exclusively used by the first load operating system, and the physical resource set comprises some of the processor cores and a part of the physical memory that are of the host machine;

15 instruct the startup processor core to read a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system and is pre-constructed by the management operating system, wherein the physical memory address comprises a location of the boot image corresponding to the first load operating system; and

20 instruct the startup processor core to execute the boot image pre-constructed for the first load operating system, so as to start up the first load operating system, wherein the boot image comprises a startup parameter of the first load operating system, and the startup parameter comprises identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating

25 system; and

the first load operating system is configured to:

read the mapping relationship that is from the virtual memory address to the physical

memory address and that is required for executing the boot image of the first load operating system, wherein the mapping relationship is used to enable the startup processor core of the first load operating system to access the physical memory address;

jump, according to an instruction that is set by the management operating system and
5 that is for executing a boot image jump, to the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address, and execute, according to the mapping relationship, the boot image corresponding to the first load operating system;

acquire, in a process of executing the boot image of the first load operating system, the
10 startup parameter of the first load operating system from the boot image of the first load operating system; and

determine, according to the identifiers of the processor cores and the identifier of the physical memory address of the first load operating system, the physical resource set that is allocated by the management operating system to the first load operating system and that is
15 exclusively used by the first load operating system.

According to another aspect of the present disclosure, there is provided a resource processing method, wherein the method is applied to a multi-kernel operating system, the multi-kernel operating system comprises a management operating system and multiple load operating systems that run on a host machine, the host machine comprises a physical resource
20 pool, the physical resource pool comprises processor cores and a physical memory that are of the host machine, wherein the management operating system is configured to manage the multiple load operating systems, which includes allocating, to the multiple load operating systems, physical resources exclusively used by the multiple load operating systems, and being responsible for startup of the load operating systems, wherein a load operating system
25 is configured to exclusively use and access a physical resource allocated by the management operating system after the load operating system is started up, and wherein the method comprises:

determining, by the management operating system and in processor cores allocated to a first load operating system, a startup processor core that starts up the first load operating system, wherein the first load operating system is any load operating system in the multiple load operating systems, the management operating system pre-allocates, to the first load operating system, a physical resource set exclusively used by the first load operating system, and the physical resource set comprises some of the processor cores and a part of the physical memory that are of the host machine;

sending, by the management operating system, an inter-core interrupt message to the startup processor core, wherein the inter-core interrupt message instructs the startup processor core to execute an initialization program, the initialization program configured to initialize the startup processor core, wherein the initialization program is executed to read a mapping relationship, from a virtual memory address to a physical memory address, for executing a boot image of the first load operating system, wherein the physical memory address comprises a location of the boot image corresponding to the first load operating system; and

instructing, by the management operating system, the startup processor core to execute the boot image to start up the first load operating system, wherein the boot image comprises a startup parameter of the first load operating system, and the startup parameter comprises identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system.

According to another aspect of the present disclosure, there is provided a resource processing method, wherein the method is applied to a multi-kernel operating system, the multi-kernel operating system comprises a management operating system and multiple load operating systems that run on a host machine, the host machine comprises a physical resource pool, the physical resource pool comprises processor cores and a physical memory that are of the host machine, wherein the management operating system is configured to manage the multiple load operating systems, which includes allocating, to the multiple load operating systems, physical resources exclusively used by the multiple load operating systems, and

being responsible for startup of the load operating systems, wherein each load operating system exclusively uses and accesses a physical resource set allocated by the management operating system, each physical resource set comprises some of the processor cores of the host machine and a part of the physical memory of the host machine, and the management
5 operating system pre-constructs a boot image for each load operating system, and sets, for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image, and the method comprises:

receiving an inter-core interrupt message from the management operating system, the
10 inter-core interrupt message instructing a startup processor core to execute an initialization program, the initialization program configured to initialize the startup processor core;

reading, by the startup processor core from the initialization program, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system in a process of
15 executing the initialization program, wherein the mapping relationship is used to enable the startup processor core of the first load operating system to access the physical memory address, and the first load operating system is any load operating system in the multiple load operating systems;

jumping, by the startup processor core of the first load operating system according to an
20 instruction that is set by the management operating system and that is for executing a boot image jump, to a location that is of the boot image corresponding to the first load operating system and that is in the physical memory address;

executing, by the startup processor core according to the mapping relationship, the boot image corresponding to the first load operating system;

25 acquiring, by the startup processor core of the first load operating system and in a process of executing the boot image of the first load operating system, a startup parameter of the first load operating system from the boot image of the first load operating system,

wherein the startup parameter comprises identifiers of processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system; and

5 determining, by the first load operating system according to the identifiers of the processor cores and the identifier of the physical memory address of the first load operating system, a physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system.

According to another aspect of the present disclosure, there is provided a host machine, wherein the host machine is configured to run a multi-kernel operating system including a management operating system and multiple load operating systems, the multiple load operating systems comprise a first load operating system, the host machine comprises a physical resource pool, the physical resource pool comprises processor cores and a physical memory that are of the host machine, wherein the management operating system is configured to manage the multiple load operating systems, which includes allocating, to the multiple load operating systems, physical resources exclusively used by the multiple load operating systems, and being responsible for startup of the load operating systems, wherein a load operating system is configured to exclusively use and access a physical resource allocated by the management operating system after the load operating system is started up, and wherein when the host machine runs, the management operating system is configured to:

20 determine, in processor cores allocated to the first load operating system, a startup processor core that starts up the first load operating system, wherein the first load operating system is any load operating system in the multiple load operating systems, the management operating system allocates, to the first load operating system, a physical resource set exclusively used by the first load operating system, and the physical resource set comprises some of the processor cores and a part of the physical memory that are of the host machine;

send an inter-core interrupt message to the startup processor core, wherein the inter-core interrupt message instructs the startup processor core to execute an initialization program, the

initialization program configured to initialize the startup processor core, wherein the initialization program is executed to read a mapping relationship, from a virtual memory address to a physical memory address, for executing a boot image of the first load operating system, wherein the physical memory address comprises a location of the boot image
5 corresponding to the first load operating system; and

instruct the startup processor core to execute the boot image to start up the first load operating system, wherein the boot image comprises a startup parameter of the first load operating system, and the startup parameter comprises identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address
10 allocated to the first load operating system; and

the first load operating system is configured to:

receive, by the startup processor core of the processor cores for the first load operating system, the inter-core interrupt message from the management operating system;

read, from the initialization program, the mapping relationship that is from the virtual
15 memory address to the physical memory address and that is required for executing the boot image of the first load operating system in a process of executing the initialization program, wherein the mapping relationship is used to enable the startup processor core of the first load operating system to access the physical memory address;

jump, according to an instruction that is set by the management operating system and
20 that is for executing a boot image jump, to the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address;

execute, according to the mapping relationship, the boot image corresponding to the first load operating system;

acquire, in a process of executing the boot image of the first load operating system, the
25 startup parameter of the first load operating system from the boot image of the first load operating system; and

determine, according to the identifiers of the processor cores and the identifier of the physical memory address of the first load operating system, the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system.

5 According to another aspect of the present disclosure, there is provided a host machine, wherein the host machine comprises a physical resource pool and comprises a multi-kernel operating system including a management operating system and multiple load operating systems that run on the host machine, the physical resource pool comprises processor cores and a physical memory that are of the host machine, wherein the management operating
10 system is configured to manage the multiple load operating systems, which includes allocating, to the multiple load operating systems, physical resources exclusively used by the multiple load operating systems, and being responsible for startup of the load operating systems, wherein a load operating system is configured to exclusively use and access a physical resource allocated by the management operating system after the load operating
15 system is started up, and wherein

the management operating system comprises:

a resource allocating module, configured to allocate, to a first load operating system, a physical resource set exclusively used by the first load operating system, wherein the physical resource set comprises some of the processor cores and a part of the physical memory that are
20 of the host machine, and the first load operating system is any load operating system in the multiple load operating systems;

a startup processor core determining module, configured to determine, in processor cores allocated to the first load operating system, a startup processor core that starts up the first load operating system; and

25 an instructing module, configured to send an inter-core interrupt message to the startup processor core, wherein the inter-core interrupt message instructs the startup processor core to execute an initialization program, the initialization program configured to initialize the

startup processor core, wherein the initialization program is executed to read a mapping relationship, from a virtual memory address to a physical memory address, for executing a boot image of the first load operating system, and instruct the startup processor core to execute the boot image to start up the first load operating system, wherein the physical
5 memory address comprises a location of the boot image corresponding to the first load operating system, the boot image comprises a startup parameter of the first load operating system, and the startup parameter comprises identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system; and

10 the first load operating system comprises:

a mapping relationship acquiring module, configured to receive, by the startup processor core of the processor cores for the first load operating system, the inter-core interrupt message from the management operating system;

read, from the initialization program, the mapping relationship that is from the virtual
15 memory address to the physical memory address and that is required for executing the boot image of the first load operating system in a process of executing the initialization program, wherein the mapping relationship is used to enable the startup processor core of the first load operating system to access the physical memory address;

an instruction executing module, configured to jump, according to an instruction that is
20 set by the management operating system and that is for executing a boot image jump, to the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address, and execute, according to the mapping relationship, the boot image corresponding to the first load operating system;

a startup parameter acquiring module, configured to acquire, in a process of executing
25 the boot image of the first load operating system, the startup parameter of the first load operating system from the boot image of the first load operating system; and

a physical resource set acquiring module, configured to determine, according to the identifiers of the processor cores and the identifier of the physical memory address of the first load operating system, the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first
5 load operating system.

The embodiments of the present invention provide a resource processing method, an operating system and a device. According to the method, a management operating system allocates, to each load operating system, a physical resource set exclusively used by each load operating system, constructs a boot image for each load operating system, and sets, for each
10 load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image; the management operating system determines, in processor cores allocated to a first load operating system, a startup processor core that starts up the first load operating system; the management operating system instructs the startup processor core to read a mapping relationship that is from a
15 virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system, so as to enable the startup processor core to access the physical memory address according to the mapping relationship, instructs the

startup processor core to execute the boot image pre-constructed for the first load operating system, where the boot image includes a startup parameter of the first load operating system, and the startup parameter includes identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system; the management operating system writes the startup parameter into the boot image, so as to allocate, to a load operating system, a physical resource exclusively used by the load operating system, without requiring involvement of a hypervisor, thereby simplifying a process of allocating the physical resource by the management operating system to the load operating system. Further, each load operating system can exclusively use a physical resource, so as to construct an independent page table, running clock, runtime environment, and the like on the physical resource exclusively used by each load operating system, thereby improving overall performance of the load operating systems.

BRIEF DESCRIPTION OF DRAWINGS

To describe the technical solutions in the embodiments of the present invention or in the prior art more clearly, the following briefly introduces the accompanying drawings required for describing the embodiments or the prior art. Apparently, the accompanying drawings in the following description show some embodiments of the present invention, and persons of ordinary skill in the art may still derive other drawings from these accompanying drawings without creative efforts.

FIG. 1 is a schematic diagram of an architecture of a multi-kernel operating system according to the present invention;

FIG. 2 is a schematic flowchart of Embodiment 1 of a resource processing method according to the present invention;

FIG. 3 is a schematic flowchart of Embodiment 2 of a resource processing method according to the present invention;

FIG. 4 is a schematic flowchart of Embodiment 3 of a resource processing method according

to the present invention;

FIG. 5 is a schematic flowchart of Embodiment 4 of a resource processing method according to the present invention;

FIG. 6 is a schematic flowchart of Embodiment 5 of a resource processing method according to the present invention;

FIG. 7 is a schematic flowchart of Embodiment 6 of a resource processing method according to the present invention;

FIG. 8A is a schematic flowchart for adding a processor core for a first load operating system according to the present invention;

FIG. 8B is a schematic flowchart for releasing a processor core by a first load operating system according to the present invention;

FIG. 9A is a schematic flowchart for adding a physical memory address for a first load operating system according to the present invention;

FIG. 9B is a schematic flowchart for releasing a physical memory address by a first load operating system according to the present invention;

FIG. 10A is a schematic flowchart for adding an external device for a first load operating system according to the present invention;

FIG. 10B is a schematic flowchart for reducing an external device for a first load operating system according to the present invention;

FIG. 11 is a schematic structural diagram of Embodiment 1 of a management operating system according to the present invention;

FIG. 12 is a schematic structural diagram of Embodiment 2 of a management operating system according to the present invention;

FIG. 13 is a schematic structural diagram of Embodiment 3 of a management operating system according to the present invention;

FIG. 14 is a schematic structural diagram of Embodiment 1 of a load operating system according to the present invention;

FIG. 15 is a schematic structural diagram of Embodiment 2 of a load operating system according to the present invention;

FIG. 16 is a schematic diagram of an architecture of a multi-core system on a heterogeneous platform; and

5 FIG. 17 is a schematic structural diagram of Embodiment 1 of a host machine according to the present invention.

DESCRIPTION OF EMBODIMENTS

To make the objectives, technical solutions, and advantages of the embodiments of the present invention clearer, the following clearly and completely describes the technical
10 solutions in the embodiments of the present invention with reference to the accompanying drawings in the embodiments of the present invention. Apparently, the described embodiments are some but not all of the embodiments of the present invention. All other embodiments obtained by persons of ordinary skill in the art based on the embodiments of the present invention without creative efforts shall fall within the protection scope of the present
15 invention.

FIG. 1 is a schematic diagram of an architecture of a multi-kernel operating system according to the present invention. As shown in FIG. 1, the multi-kernel operating system provided in this embodiment includes a management operating system and multiple load operating systems that run on a host machine and includes a physical resource pool. The host machine
20 is an actual physical node, and the management operating system manages the multiple load operating systems, which mainly includes allocating, to the multiple load operating systems, physical resources exclusively used by the multiple load operating systems, and being responsible for startup and logout of the load operating systems. The multiple load operating systems include a load operating system that has not been started up and a load operating
25 system that is running. In particular, after a load operating system is started up, the load operating system may exclusively use a physical resource allocated by the management

operating system, and access the physical resource; the load operating system constructs an independent page table, an independent clock, an independent runtime library, and the like on the physical resource exclusively used by the load operating system, without requesting help from a hypervisor; the load operating system uses the independent page table, the independent clock, the independent runtime library, and the like, so that the management operating system and the load operating system share system buses, including an address bus, a data bus, and a control bus. Communication between the management operating system and a load operating system and communication between a load operating system and another load operating system are implemented by an internal communication mechanism (an inter-instance communication module). The management operating system and each load operating system have an independent page table separately, each load operating system uses an independent physical resource, and the management operating system performs management but is not involved in access, communication, or the like that is performed by a load operating system on a physical resource. The physical resource pool includes processor cores and a physical memory that are of the host machine; optionally, the physical resource pool further includes an external device such as a network adapter array.

FIG. 2 is a schematic flowchart of Embodiment 1 of a resource processing method according to the present invention. An execution body of this embodiment is a management operating system that runs on a host machine, where the management operating system may be specifically the management operating system shown in the embodiment in FIG. 1. As shown in FIG. 2, the resource processing method provided in this embodiment includes:

Step 201: The management operating system allocates, to each load operating system, a physical resource set exclusively used by each load operating system, constructs a boot image for each load operating system, and sets, for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image.

Each physical resource set includes some of the processor cores of the host machine and a

part of the physical memory of the host machine.

Step 202: The management operating system determines, in processor cores allocated to a first load operating system, a startup processor core that starts up the first load operating system.

- 5 The first load operating system is any one of the load operating systems.

Step 203: The management operating system instructs the startup processor core to read a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system and is pre-constructed by the management operating system, and instructs the startup processor core
10 to execute the boot image pre-constructed for the first load operating system.

The boot image includes a startup parameter of the first load operating system, and the startup parameter includes identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system.

- 15 An application scenario of this embodiment may be that shown in the embodiment in FIG. 1, and no detail is repeatedly described herein in this embodiment. In this embodiment, the resource processing method provided in this embodiment is described in detail by using a management operating system as an execution body. The management operating system may be specifically the management operating system shown in FIG. 1.

- 20 In a specific implementation process, in step 201, that the management operating system allocates, to each load operating system, a physical resource set exclusively used by each load operating system may be implemented in the following manner:

The management operating system determines available physical resources that are in the physical resource pool and that are corresponding to identifiers of physical resources in a list
25 of the available physical resources in the resource pool. Specifically, the management operating system maintains the list of the available physical resources in the resource pool, where identifiers of all available physical resources in the physical resource pool are recorded

in the list. The available physical resources are physical resources that are not currently used by the management operating system or the load operating systems. The management operating system performs, according to a quantity of the load operating systems, first-time division on the available physical resources in the physical resource pool, to obtain multiple
5 physical resource sets, where a quantity of the physical resource sets equals the quantity of the load operating systems; the management operating system determines a correspondence between each load operating system and each physical resource set, and allocates, to each load operating system and according to the correspondence, a physical resource set exclusively used by each load operating system. Each physical resource set includes some of
10 the processor cores of the host machine and a part of the physical memory of the host machine.

Optionally, the management operating system may further allocate, to a load operating system, an external device exclusively used by the load operating system, and the physical resource set further includes an external device of the host machine. The external device may
15 be a network adapter or a magnetic disk, or the like.

A specific embodiment is used as an example. Still refer to FIG. 1. In FIG. 1, a black area in the physical resource pool is a physical resource that is being used, and a physical resource, other than the black area, is an available physical resource. There are two load operating systems, which are referred to as a first load operating system and a second load operating
20 system. The management operating system performs the first-time division on the available physical resources, and obtains two physical resource sets. In a specific implementation process, the management operating system performs physical division on the physical resources, and the division may be performed in the following manner:

Processor core: A processor core is used as a minimum functional unit for the division, or a
25 processor may be used as a unit. For a heterogeneous platform, a heterogeneous processor core and a coprocessor core may also be classified as global computing resources.

Physical memory: A continuous or discontinuous segment of a physical memory is used as a

unit for the division, and a specific size of a memory block may be a size of a signal block or a size of a hybrid block.

With respect to an external device, the division may mainly be performed in the following manner:

- 5 Network: A physical network adapter is used as a unit for the division. When a physical network adapter is not sufficient, a physical network adapter having a multi-array function or supporting server virtualization (for example, Single-Root I/O Virtualization, SR-IOV for short) is used, and is divided according to an array or a virtual function (Virtual Function, VF for short). Only when neither a physical network adapter nor an independent physical
- 10 function of the network adapter is sufficient, it may be considered to share a physical network adapter and provide multiple virtual network adapters for an operating system instance, in a manner of virtualizing front and back ends of the network adapter.

- Magnetic disk: A physical magnetic disk is used as a unit for the division. When a physical magnetic disk is not sufficient, a magnetic disk that may support an SR-IOV technology in
- 15 the future may be divided by using a disk virtualization function. A single physical magnetic disk is shared in a manner of logically partitioning the magnetic disk, and finally technologies such a network file system (Network File System, NFS for short) and a random access memory disk (RAM) may be used to replace a function of a conventional disk file system.

- Terminal: Because using of a terminal device (a monitor or a keyboard), a serial port, or the
- 20 like consumes no resource, in a premise that system performance is not affected, multiple sets of device resources such as serial ports and terminals may be obtained by virtualization in a hardware abstraction layer virtualization manner, to meet an upper-layer need.

- With respect to the resource division, in this embodiment, it is ensured that the processor cores and the physical memory are divided in physical space, and a physical unit division
- 25 manner is also used on a peripheral, but an alternative solution in which time division multiplexing is performed when physical division is inadequate is also supported.

The management operating system constructs, according to types of an operating system

instance running on the first load operating system and an operating system instance running on the second load operating system, correspondences between the physical resource sets and the load operating systems. When the management operating system needs, according to the type of the operating system instance running on the first load operating system, more
5 physical resources, the management operating system allocates, to the first load operating system, a physical resource corresponding to a shadow area; correspondingly, the management operating system allocates, to the second load operating system, a physical resource corresponding to a white area.

After the management operating system allocates, to each load operating system, a physical
10 resource exclusively used by each load operating system, the management operating system pre-constructs, for each load operating system, a boot image used to start up each load operating system. The boot image refers to a program that configures hardware required for core running and constructs a data structure required for the core running, for a load operating system when the hardware and the core data structure that are required for running of the load
15 operating system have not been configured or have not been sufficiently prepared. The boot image is specifically implemented in a manner of a program so that a startup processor core can update a status of the startup processor core, where the program that is configured for the load operating system after the hardware and the core data structure have been prepared and that starts up each core service and loads each core module, so as to finally start up the load
20 operating system.

Further, the management operating system further sets, for each load operating system, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing a respective boot image of each load operating system. Persons skilled in the art can understand that, the mapping relationship that is from the virtual
25 memory address to the physical memory address and that is required for executing the boot image and involved in this embodiment specifically refer to a mapping relationship that is from the virtual memory address in virtual memory addresses corresponding to the boot

image to the physical memory address, and the management operating system may implement the mapping relationship in a manner of a page table.

In a specific implementation process, a startup processor core of a load operating system first acquires a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image and are set by the management operating system for the load operating system, and the load operating system may directly access the physical memory address according to the mapping relationship and does not need to perform address translation. After the boot image of the load operating system has been started up, the boot image is configured to start up the load operating system. In a running process, the boot image directly accesses the physical memory address according to the mapping relationship that is from the virtual memory address to the physical memory address and that is corresponding to the boot image. Persons skilled in the art can understand that, the management operating system may set, for the boot image, some mapping relationships that are from virtual memory addresses to physical memory addresses, or may set, for the boot image, all mapping relationships that are from virtual memory addresses to physical memory addresses. When the management operating system sets, for the boot image, some mapping relationships that are from the virtual memory addresses to the physical memory addresses, and when the startup processor core that has been allocated to the load operating system is in a process of executing startup of the boot image, the startup processor core may set all the mapping relationships that are from the virtual memory addresses to the physical memory addresses and that are required for executing the boot image. After the load operating system has been started up, the load operating system sets all mapping relationships that are from virtual memory addresses to physical memory addresses and that are required for executing the load operating system.

In step 202, that the management operating system determines, in processor cores allocated to a first load operating system, a startup processor core includes the following possible implementation manners: the management operating system determines the startup processor

core according to a preset policy; the management operating system randomly chooses, in the processor cores allocated to the first load operating system, one processor core as the startup processor core; the management operating system acquires a user instruction, and determines the startup processor core according to the user instruction. This embodiment imposes no special limitation on a specific implementation process of determining the startup processor core by the management operating system.

In step 203, the management operating system instructs the startup processor core to read the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image of the first load operating system.

Specifically, the startup processor core may directly access the physical memory address by reading the mapping relationship and does not need to perform an address translation process. Further, in step 203, the management operating system further instructs the startup processor core to execute the boot image pre-constructed by the management operating system for the first load operating system. Because the boot image includes the startup parameter of the first load operating system, the startup processor core reads, in the process of executing the boot image, the startup parameter from the boot image, where the startup parameter includes the identifiers of the processor cores allocated to the first load operating system and the identifier of the physical memory address allocated to the first load operating system, so that the first load operating system acquires, according to the startup parameter, a physical resource set allocated by the management operating system to the first load operating system. Running of the boot image is for starting up the load operating system. The running of the boot image equals a startup process of the first load operating system.

Optionally, when the physical resource set includes some external devices of the host machine, the startup parameter further includes an identifier of an external device allocated to the first load operating system and a device description information table corresponding to the external device. The device description information table includes configuration information of the external device, for example, configuration of a physical memory address

of the external address, and a mapping relationship from a virtual memory address to the physical memory address. This embodiment imposes no special limitation on specific content included in the device description information table.

According to the resource processing method provided in this embodiment, a management
5 operating system allocates, to each load operating system, a physical resource set exclusively used by each load operating system, constructs a boot image for each load operating system, and sets, for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image; the management operating system determines, in processor cores allocated to a first load
10 operating system, a startup processor core that starts up the first load operating system; the management operating system instructs the startup processor core to read a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system, so as to enable the startup processor core to access the physical memory address according to the mapping
15 relationship, instructs the startup processor core to execute the boot image pre-constructed for the first load operating system, where the boot image includes a startup parameter of the first load operating system, and the startup parameter includes identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system; the management operating system writes the
20 startup parameter into the boot image, so as to allocate, to a load operating system, a physical resource exclusively used by the load operating system, without requiring involvement of a hypervisor, thereby simplifying a process of allocating the physical resource by the management operating system to the load operating system. Further, each load operating system can exclusively use a physical resource, so as to construct an independent page table,
25 clock, runtime environment, and the like on the physical resource exclusively used by each load operating system, thereby improving overall performance of the load operating systems. The following uses several specific embodiments to describe in detail the technical solutions

of the method embodiment shown in FIG. 2.

A specific embodiment may be that shown in FIG. 3. FIG. 3 is a schematic flowchart of Embodiment 2 of a resource processing method according to the present invention. As shown in FIG. 3, the resource processing method provided in this embodiment of the present invention includes:

Step 301: The management operating system allocates, to each load operating system, a physical resource set exclusively used by each load operating system, and constructs a boot image for each load operating system.

Each physical resource set includes some of the processor cores of the host machine and a part of the physical memory of the host machine.

Step 302: The management operating system presets, for the first load operating system, an initialization program that is configured to initialize the first load operating system, and presets, in the initialization program, a location that is of the boot image corresponding to the first load operating system and that is in the physical memory address.

Step 303: The management operating system sets, for the first load operating system and in the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image.

Step 304: The management operating system sends an inter-core interrupt message to the startup processor core.

The inter-core interrupt message instructs the startup processor core to execute the initialization program that is configured to initialize the startup processor core and that is corresponding to the first load operating system.

Step 305: The management operating system instructs, by instructing the startup processor core to execute the initialization program corresponding to the first load operating system, the startup processor core to read, from the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image of the first load operating system, and instructs the startup

processor core to jump, after running of the initialization program ends, to the location that is of the boot image and is in the physical memory, so as to execute the boot image of the first load operating system.

The boot image includes the startup parameter of the first load operating system, and the
5 startup parameter includes the identifiers of the processor cores allocated to the first load operating system and the identifier of the physical memory address allocated to the first load operating system.

In step 301, a process in which the management operating system allocates, to each load operating system, the physical resource set exclusively used by each load operating system
10 and constructs the boot image for each load operating system is similar to that in step 201, and no detail is repeatedly described herein in this embodiment.

In step 302, the management operating system presets, for the first load operating system, the initialization program that is configured to initialize the first load operating system, and presets, in the initialization program, the location that is of the boot image corresponding to
15 the first load operating system and that is in the physical memory address.

Persons skilled in the art can understand that, the management operating system presets, for each load operating system, an initialization program corresponding to each load operating system, and presets, in the initialization program, a location that is of the boot image corresponding to each load operating system and that is in the physical memory address.

20 Persons skilled in the art can understand that, a location that is of a boot image corresponding to each load operating system and that is in the virtual memory address may also be preset in the initialization program, and the startup processor core may acquire, according to the mapping relationship that is from the virtual memory address to the physical memory address, the location that is in the physical memory address and in which the boot image is located.

25 In step 303, the management operating system sets, for the first load operating system and in the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image.

In step 304, the management operating system sends the inter-core interrupt message to the startup processor core, where the inter-core interrupt message instructs the startup processor core to execute the initialization program that is configured to initialize the startup processor core and that is corresponding to the first load operating system.

- 5 Persons skilled in the art can understand that, a value is transferred by the inter-core interrupt message and may be referred to as an interrupt vector, and both the value corresponding to the inter-core interrupt message and an execution process corresponding to the value are agreed on by the management operating system and the first load operating system in advance. When the management operating system sends the inter-core interrupt message to
10 the startup processor core, the inter-core interrupt message instructs the startup processor core to execute the initialization program that is configured to initialize the startup processor core and that is corresponding to the first load operating system.

After receiving the inter-core interrupt message, the startup processor core of the first load operating system searches for the initialization program in a preset fixed physical memory,
15 runs the initialization program, and completes initialization of the startup processor core, where the initialization of the startup processor core is a startup process of the startup processor core. In a running process of the initialization program, the startup processor core reads, from the running initialization program, the location that is of the boot image corresponding to the first load operating system, that is in the physical memory address, and
20 that is preset by the management operating system for the first load operating system, so as to start up the boot image.

In step 305, the management operating system instructs the startup processor core to execute the initialization program corresponding to the first load operating system; in a process of executing the initialization program, the startup processor core reads the mapping relationship
25 that is from the virtual memory address to the physical memory address and that is required for executing the boot image of the first load operating system.

That the management operating system instructs the startup processor core to jump, after

running of the initialization program ends, to a location that is in the physical memory and in which the boot image is located, so as to execute the boot image of the first load operating system is implemented in the following manner:

5 A last instruction of the initialization program is used to instruct the startup processor core to jump to the boot image. When running the last instruction of the initialization program, the startup processor core jumps to the boot image to execute the boot image, where the boot image includes the startup parameter of the first load operating system, and the startup parameter includes the identifiers of the processor cores allocated to the first load operating system and the identifier of the physical memory address allocated to the first load operating system.

10 The first load operating system determines, according to the identifiers of the processor cores allocated to the first load operating system and the identifier of the physical memory address allocated to the first load operating system, the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system.

15 According to the resource processing method provided in this embodiment, a management operating system pre-constructs an initialization program for a load operating system, presets, in the initialization program and for the load operating system, a location that is of a boot image corresponding to a first load operating system and that is in a physical memory address, and presets, in the initialization program and for the first load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image; a startup processor core of the load operating system executes the initialization program, reads a startup parameter from the boot image, acquires a physical resource set according to the startup parameter, and completes a startup process of the load operating system. The management operating system allocates, to a load operating system, a physical resource exclusively used by the load operating system, without requiring involvement of a hypervisor, thereby simplifying a process of allocating the physical resource

by the management operating system to the load operating system; further, each load operating system can exclusively use a physical resource, thereby improving overall performance of the load operating systems.

Another specific embodiment may be that shown in FIG. 4. FIG. 4 is a schematic flowchart of Embodiment 3 of a resource processing method according to the present invention. As shown in FIG. 4, the resource processing method provided in this embodiment of the present invention includes:

Step 401: The management operating system acquires available processor cores of a second load operating system.

10 The second load operating system is a logged-out load operating system, other than the first load operating system, in the multiple load operating systems, the available processor cores include a processor core that has been started up, and a physical resource set of the first load operating system includes the available processor cores.

Step 402: When a physical resource set of the first load operating system includes the available processor cores, the management operating system determines, in the available processor cores, the startup processor core that starts up the first load operating system.

Step 403: The management operating system presets, for the first load operating system, a daemon on the startup processor core, and presets, in the daemon, a location that is of the boot image corresponding to the first load operating system and that is in the physical memory address.

Step 404: The management operating system sets, for the first load operating system and in the daemon, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image.

Step 405: The management operating system sends an inter-core interrupt message to the daemon running on the startup processor core, where the location that is of the boot image corresponding to the first load operating system, that is in the physical memory address, and that is preset in the daemon by the management operating system instructs the startup

processor core to jump to the location that is in the physical memory address and in which the boot image is located, so as to execute the boot image of the first load operating system.

The inter-core interrupt message instructs the startup processor core to read, from the daemon, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image and is pre-constructed by the management operating system for the first load operating system.

In step 401, that the management operating system acquires available processor cores of a second load operating system may include the following possible implementation manners: the management operating system forcibly makes the second load operating system log out in a running process of the second load operating system; the management operating system makes the second load operating system log out after running of the second load operating system ends; the second load operating system automatically logs out after running ends. After the second load operating system logs out, the management operating system acquires the available processor cores of the second load operating system, where the available processor cores include a startup processor core of the second load operating system and another processor core that runs another application program.

Persons skilled in the art can understand that, the physical resource set of the first load operating system may include the available processor cores, or may not include the available processor cores.

In particular, in this embodiment, the second load operating system is made to log out, but the startup processor core of the second load operating system has run the initialization program; the management operating system may use the startup processor core of the second load operating system as the startup processor core of the first load operating system. When the startup processor core of the second load operating system acts as the startup processor core of the first load operating system, it is not required to run the initialization program again to complete an initialization process; however, when an processor core, which is in the available processor cores and runs another application program, acts as the startup processor core, it is

still required to run the initialization program to complete initialization.

In step 402, when the physical resource set of the first load operating system includes the available processor cores, the management operating system determines, in the available processor cores, the startup processor core that starts up the first load operating system.

- 5 Persons skilled in the art can understand that, when the physical resource set of the first load operating system includes the available processor cores, the management operating system may determine, in the available processor cores, the startup processor core of the first load operating system, or may determine the startup processor core in other processor cores in the physical resource set.
- 10 When the management operating system determines the startup processor core in the available processor cores, the following manners may be used for implementation: the management operating system determines the startup processor core in the available processor cores according to a preset policy; the management operating system randomly selects, from the available processor cores, one processor core as the startup processor core;
- 15 the management operating system acquires a user instruction, and determines the startup processor core in the available processor cores according to the user instruction.

In step 403, the management operating system sets, for the first load operating system, the daemon on the startup processor core; after the setting is complete, the daemon runs all the time on the startup processor core that has been started up, and waits for various system

20 commands sent by the management operating system. The daemon is preset by the management operating system for the first load operating system. The management operating system further presets, in the daemon, the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address.

Further, in step 404, the management operating system presets, in the daemon, the mapping

25 relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image of the first load operating system.

In step 405, the management operating system sends the inter-core interrupt message to the

daemon running on the startup processor core, and an instruction corresponding to the inter-core interrupt message is agreed on by the management operating system and the first load operating system in advance. After the daemon running on the startup processor core receives the inter-core interrupt message sent by the management operating system, the startup processor core reads, from the daemon, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image and is pre-constructed by the management operating system for the first load operating system; in a process of executing the boot image by the startup processor core, the startup processor core accesses the physical memory address according to the mapping relationship.

The management operating system instructs the startup processor core to jump to the location that is in the physical memory address and in which the boot image is located, so as to execute the boot image of the first load operating system, where a jump command is set in the daemon, so that the startup processor core acquires, from the daemon, the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address, and jumps to the location that is in the physical memory address and in which the boot image is located, so as to execute the boot image of the first load operating system.

According to the resource processing method provided in this embodiment, a management operating system sets a jump command in a daemon, so that a startup processor core acquires, from the daemon, a location that is of a boot image corresponding to a first load operating system and that is in a physical memory address, and jumps to the location that is in the physical memory address and in which the boot image is located, so as to execute the boot image of the first load operating system and acquire a startup parameter from the boot image.

The management operating system allocates, to a load operating system, a physical resource exclusively used by the load operating system, without requiring involvement of a hypervisor, thereby simplifying a process of allocating the physical resource by the management

operating system to load operating system; further, each load operating system can exclusively use a physical resource, thereby improving overall performance of the load operating systems.

FIG. 5 is a schematic flowchart of Embodiment 4 of a resource processing method according to the present invention. The resource processing method in this embodiment is applied to a multi-kernel operating system, the multi-kernel operating system includes a management operating system and multiple load operating systems that run on a host machine and includes a physical resource pool, the physical resource pool includes processor cores and a physical memory that are of the host machine, each load operating system exclusively uses a physical resource set allocated by the management operating system, and each physical resource set includes some of the processor cores of the host machine and a part of the physical memory of the host machine; the management operating system pre-constructs a boot image for each load operating system, and sets, for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image. An execution body of this embodiment is any load operating system in the multiple load operating systems. For ease of description, in this embodiment, the execution body is referred to as a first load operating system. As shown in FIG. 5, the resource processing method provided in this embodiment includes:

Step 501: A startup processor core of the first load operating system reads a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system.

The mapping relationship is used to enable the startup processor core of the first load operating system to access the physical memory address, and the first load operating system is any load operating system in the multi-kernel operating system.

Step 502: The startup processor core of the first load operating system jumps, according to an instruction that is set by the management operating system and that is for executing a boot image jump, to a location that is of the boot image corresponding to the first load operating

system and that is in the physical memory address, and executes, according to the mapping relationship, the boot image corresponding to the first load operating system.

Step 503: The startup processor core of the first load operating system acquires, in a process of executing the boot image of the first load operating system, a startup parameter of the first
5 load operating system from the boot image of the first load operating system.

The startup parameter includes identifiers of processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system.

Step 504: The first load operating system determines, according to identifiers of the processor
10 cores and an identifier of the physical memory address of the first load operating system, a physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system.

An application scenario of this embodiment may be that shown in the embodiment in FIG. 1, and no detail is repeatedly described herein in this embodiment. In this embodiment, the
15 resource processing method provided in this embodiment is described in detail by using the first load operating system as the execution body. The first load operating system may be specifically any load operating system in the load operating systems shown in FIG. 1.

In step 501, after the management operating system determines the startup processor core for the first load operating system, the startup processor core of the first load operating system
20 first acquires the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image and is set by the management operating system for the first load operating system, and the first load operating system may directly access the physical memory address according to the mapping relationship and does not need to perform address translation.

25 In step 502, the startup processor core of the first load operating system receives the instruction that is preset by the management operating system for the first load operating system and that is for executing the boot image jump, the first load operating system jumps,

according to the instruction that is set by the management operating system and that is for executing the boot image jump, to the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address; when the startup processor core of the first load operating system executes the boot image, the first load
5 operating system directly accesses the physical memory address according to the mapping relationship that is from the virtual memory address to the physical memory address and that is corresponding to the boot image, so as to complete a startup process of the boot image.

In step 503, the startup processor core of the first load operating system acquires, in a process of executing the boot image of the first load operating system, the startup parameter of the
10 first load operating system from the boot image of the first load operating system, where the startup parameter includes the identifiers of the processor cores allocated by the management operating system to the first load operating system and the identifier of the physical memory address allocated by the management operating system to the first load operating system.

Optionally, when the physical resource set includes some external devices of the host
15 machine, the startup parameter further includes an identifier of an external device allocated by the management operating system to the first load operating system and a device description information table corresponding to the external device. The device description information table includes configuration information of the external device, for example, configuration of a physical memory address of the external address, and a mapping
20 relationship from a virtual memory address to the physical memory address. This embodiment imposes no special limitation on specific content included in the device description information table.

In step 504, the first load operating system may determine, according to the identifiers of the processor cores and the identifier of the physical memory address of the first load operating
25 system, the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system, and the first load operating system may construct an independent page table, clock, runtime

environment, and the like on a physical resource that is exclusively used by the first load operating system.

Persons skilled in the art can understand that, an objective of executing the boot image by the first load operating system is to start up the first load operating system; after running of the boot image ends, startup of the first load operating system is complete, and the first load operating system enters a running stage.

According to the resource processing method provided in this embodiment of the present invention, a startup processor core of a first load operating system reads a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system, jumps, according to an instruction that is set by a management operating system and that is for executing a boot image jump, to a location that is of the boot image corresponding to the first load operating system and that is in the physical memory address, executes, according to the mapping relationship, the boot image corresponding to the first load operating system, and acquires, in a process of executing the boot image of the first load operating system, a startup parameter of the first load operating system from the boot image of the first load operating system, where the startup parameter includes identifiers of processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system. The first load operating system determines, according to the identifiers of the processor cores and the identifier of the physical memory address of the first load operating system, a physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system. The first load operating system reads the startup parameter from the boot image, so as to acquire the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the load operating system, without requiring involvement of a hypervisor, thereby simplifying a process of allocating a physical resource by the management operating system to the load

operating system. Further, each load operating system can exclusively use a physical resource, so as to construct an independent page table, clock, runtime environment, and the like on the physical resource exclusively used by each load operating system, thereby improving overall performance of the load operating systems.

- 5 The following uses several specific embodiments to describe in detail the technical solutions of the method embodiment shown in FIG. 5.

A specific embodiment may be that shown in FIG. 6. FIG. 6 is a schematic flowchart of Embodiment 5 of a resource processing method according to the present invention. As shown in FIG. 6, the resource processing method provided in this embodiment of the present
10 invention includes:

Step 601: The startup processor core of the first load operating system receives an inter-core interrupt message sent by the management operating system, where the startup processor core executes, according to an instruction of the inter-core interrupt message, an initialization program that is configured to initialize the startup processor core and that is corresponding to
15 the first load operating system.

Step 602: The startup processor core of the first load operating system executes the initialization program, reads, from the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image and is pre-constructed by the management operating system for the
20 first load operating system, reads a jump instruction that is preset in the initialization program by the management operating system, jumps to the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address, and executes, according to the mapping relationship, the boot image corresponding to the first load operating system.

25 Step 603: The startup processor core of the first load operating system acquires, in a process of executing the boot image of the first load operating system, the startup parameter of the first load operating system from the boot image of the first load operating system.

The startup parameter includes the identifiers of the processor cores allocated to the first load operating system and the identifier of the physical memory address allocated to the first load operating system.

Step 604: The first load operating system determines, according to the identifiers of the
5 processor cores and the identifier of the physical memory address of the first load operating system, the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system.

In this embodiment, step 603 is similar to step 503 and step 604 is similar to step 504, and no detail is repeatedly described herein in this embodiment.

10 In step 601, the startup processor core of the first load operating system receives the inter-core interrupt message sent by the management operating system, where the startup processor core executes, according to the instruction of the inter-core interrupt message, the initialization program that is configured to initialize the startup processor core and that is corresponding to the first load operating system.

15 Specifically, a value is transferred by the inter-core interrupt message and may be referred to as an interrupt vector, and both the value corresponding to the inter-core interrupt message and an execution process corresponding to the value are agreed on by the management operating system and the first load operating system in advance. The management operating system sends the inter-core interrupt message to the startup processor core of the first load
20 operating system, and the inter-core interrupt message instructs the startup processor core to execute the initialization program that is configured to initialize the startup processor core and that is corresponding to the first load operating system.

After receiving the inter-core interrupt message sent by the management operating system, the startup processor core of the first load operating system searches for the initialization
25 program in a preset fixed physical memory, and runs the initialization program to complete initialization of the startup processor core, and the initialization of the startup processor core is a startup process of the startup processor core.

In step 602, the startup processor core of the first load operating system reads, in the process of executing the initialization program and from the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image and is pre-constructed by the management operating system for the first load operating system; after the startup processor core of the first load operating system reads the mapping relationship, in a subsequent process of executing the boot image, the startup processor core of the first load operating system may directly access the physical memory address according to the mapping relationship and does not need to perform address translation.

Further, a last instruction of the initialization program is used to instruct the startup processor core to jump to the boot image and may be construed as a jump instruction. The startup processor core of the first load operating system reads, from the initialization program, the jump instruction that is preset in the initialization program by the management operating system, jumps to the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address, and directly accesses the physical memory address according to the mapping relationship, so as to execute the boot image corresponding to the first load operating system.

According to the resource processing method provided in this embodiment of the present invention, a first load operating system reads, from an initialization program, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image and is pre-constructed by a management operating system for the first load operating system, reads a jump instruction that is preset in the initialization program by the management operating system, jumps to a location that is of the boot image corresponding to the first load operating system and that is in the physical memory address, executes, according to the mapping relationship, the boot image corresponding to the first load operating system, reads a startup parameter from the boot image, acquires a physical resource set according to the startup parameter, and completes a

startup process of the first load operating system. The management operating system allocates, to a load operating system, a physical resource exclusively used by the load operating system, without requiring involvement of a hypervisor, thereby simplifying a process of allocating the physical resource by the management operating system to load operating system; further, 5 each load operating system can exclusively use a physical resource, thereby improving overall performance of the load operating systems.

Another specific embodiment is as follows: In this embodiment, the startup processor core of the first load operating system is a processor core that has been started up and that is determined by the management operating system, a daemon runs on the startup processor 10 core of the first load operating system, the daemon is preset by the management operating system for the first load operating system, the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address and the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image are set in the daemon. FIG. 7 is a 15 schematic flowchart of Embodiment 6 of a resource processing method according to the present invention. As shown in FIG. 7, the resource processing method provided in this embodiment of the present invention includes:

Step 701: The daemon running on the startup processor core of the first load operating system receives an inter-core interrupt message sent by the management operating system, and the 20 startup processor core reads, from the daemon according to an instruction of the inter-core interrupt message, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image and is pre-constructed by the management operating system for the first load operating system.

Step 702: The startup processor core of the first load operating system reads a jump 25 instruction that is preset in the daemon by the management operating system, jumps to the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address, and executes, according to the mapping relationship, the

boot image corresponding to the first load operating system.

Step 703: The startup processor core of the first load operating system acquires, in a process of executing the boot image of the first load operating system, the startup parameter of the first load operating system from the boot image of the first load operating system.

- 5 The startup parameter includes the identifiers of the processor cores allocated to the first load operating system and the identifier of the physical memory address allocated to the first load operating system.

Step 704: The first load operating system determines, according to the identifiers of the processor cores and the identifier of the physical memory address of the first load operating
 10 system, the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system.

A difference between this embodiment and the embodiment in FIG. 6 lies in that the startup processor core in this embodiment is a processor core that has been started up, that is, an initialization process does not need to be performed on the startup processor core. Step 703 in
 15 this embodiment is similar to step 503 in the embodiment in FIG. 5 and step 704 is similar to step 504 in the embodiment in FIG. 5, and no detail is repeated described herein in this embodiment. In a specific implementation process, the management operating system presets, for the first load operating system, the daemon on the startup processor core; after the setting is complete, the daemon runs all the time on the startup processor core that has been started
 20 up.

In step 701, the management operating system sends the inter-core interrupt message to the daemon running on the startup processor core, and an instruction corresponding to the inter-core interrupt message is agreed on by the management operating system and the first load operating system in advance. After the daemon running on the startup processor core of
 25 the first load operating system receives the inter-core interrupt message sent by the management operating system, the startup processor core reads, from the daemon, the mapping relationship that is from the virtual memory address to the physical memory address

and that is of the boot image and is pre-constructed by the management operating system for the first load operating system; in a process of executing the boot image by the startup processor core, the startup processor core accesses the physical memory address according to the mapping relationship.

- 5 In step 702, the startup processor core of the first load operating system reads the jump instruction that is preset in the daemon by the management operating system, jumps to the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address, and executes, according to the mapping relationship, the boot image corresponding to the first load operating system.
- 10 According to the resource processing method provided in this embodiment, a startup processor core of a first load operating system acquires, from a preset daemon, a location that is of a boot image corresponding to the first load operating system and that is in a physical memory address, jumps to the location that is in the physical memory address and in which the boot image is located, so as to execute the boot image of the first load operating system
- 15 and acquire a startup parameter from the boot image. A management operating system allocates, to a load operating system, a physical resource exclusively used by the load operating system, without requiring involvement of a hypervisor, thereby simplifying a process of allocating the physical resource by the management operating system to the load operating system; further, each load operating system can exclusively use a physical resource,
- 20 thereby improving overall performance of the load operating systems.

Based on the embodiments in FIG. 5 to FIG. 7, the startup processor core executes the boot image and completes the startup of the first load operating system. After the first load operating system has been started up, the first load operating system constructs all mapping relationships that are from virtual memory addresses to physical memory addresses and that

25 are required for executing the first load operating system; the processor core of the first load operating system converts, according to the mapping relationships, the virtual memory addresses to the physical memory addresses, and directly accesses the physical memory

addresses.

Further, in a running process of the first load operating system, the first load operating system may execute, by using a processor core allocated to the first load operating system, a privileged instruction delivered by the management operating system. In a specific
5 implementation process, the processor core that executes the privileged instruction may be the startup processor core, or may be another processor core other than the startup processor core, as long as the processor core that executes the privileged instruction is a processor core allocated by the management operating system to the first load operating system. The privileged instruction is applied to an operating system and generally is not directly provided
10 for a user. The privileged instruction is mainly used for resource allocation and management, including detecting a user access right, creating and switching a task, and the like.

In this embodiment, the first load operating system directly executes the privileged instruction, without a step of translating or performing hypercall (hypercall) on a privileged operation in a virtualization technology. Specifically, the management operating system may
15 deliver a privileged instruction, which does not affect a normal running status of the host machine, to the first load operating system for the first load operating system to perform execution.

The embodiments in FIG. 2 to FIG. 7 describe in detail the process of allocating a physical resource by the management operating system to the first load operating system, and further
20 describe in detail how the first load operating system executes the boot image to complete the startup process of the first load operating system.

In the running process of the first load operating system, the physical resource of the first load operating system further needs to be dynamically adjusted. In a specific implementation process, there are two possible implementation manners for dynamically adjusting the first
25 load operating system.

One possible implementation manner is that the management operating system monitors running of the first load operating system and adjusts the physical resource of the first load

operating system, which specifically includes two possible situations.

In one possible situation: the management operating system monitors the running of the first load operating system; and

when utilization of a physical resource allocated to the first load operating system
5 is less than a first preset threshold, determines that a physical resource needs to be reduced for the first load operating system, and determines a type identifier of the physical resource that needs to be reduced, where the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource, a physical memory resource, or an external device resource; and

10 the management operating system performs, according to the type identifier of the physical resource that needs to be reduced, second-time division on the available physical resources that are in the physical resource pool and that are corresponding to the identifiers of the physical resources in the list of the available physical resources in the resource pool, and reduces the physical resource of the first load operating system, where the reduced physical
15 resource is a physical resource corresponding to the type identifier of the physical resource that needs to be reduced.

In the other possible situation: the management operating system monitors the running of the first load operating system; and

when utilization of a physical resource allocated to the first load operating system
20 is greater than a second preset threshold, determines that a physical resource needs to be added for the first load operating system, and determines a type identifier of the physical resource that needs to be added, where the type identifier of the physical resource is used to distinguish whether the physical resource that needs to be added is a processor core resource, a physical memory resource, or an external device resource; and

25 the management operating system performs, according to the type identifier of the physical resource that needs to be added, second-time division on the available physical resources that are in the physical resource pool and that are corresponding to the identifiers of

the physical resources in the list of the available physical resources in the resource pool, and adds the physical resource of the first load operating system, where the added physical resource is a physical resource corresponding to the type identifier of the physical resource that needs to be added.

- 5 Specifically, in this embodiment, the physical resources allocated by the management operating system to the first load operating system include a processor core resource, a physical memory resource, and an external device resource. The management operating system monitors, in the running process of the first load operating system, utilization of the physical resources that have been allocated to the first load operating system, that is, monitors
10 the utilization of the processor core resource, the physical memory resource, and the external device resource.

When the management operating system determines that utilization of a physical resource allocated to the first load operating system is less than the first preset threshold, it indicates that the management operating system allocates too many physical resources to the first load
15 operating system when allocating, to the first load operating system, the physical resource set that is exclusively used by the first load operating system; in this case, the management operating system determines that a physical resource needs to be reduced for the first load operating system. Because there are three types of physical resources, the management operating system determines, according to utilization of each physical resource, a type
20 identifier of the physical resource that needs to be reduced, and then the management operating system performs, according to the type identifier of the physical resource that needs to be reduced, the second-time division on the available physical resources that are in the physical resource pool and that are corresponding to the identifiers of the physical resources in the list of the available physical resources in the resource pool, and reduces the physical
25 resource of the first load operating system. In a specific implementation process, the management operating system may perform, according to utilization of a physical resource of the first load operating system and utilization of a physical resource of another load operating

system, the second-time division on the available physical resources, so as to reduce the physical resource of the first load operating system. The reduced physical resource is a physical resource corresponding to the type identifier of the physical resource that needs to be reduced.

- 5 When the management operating system determines that utilization of a physical resource allocated to the first load operating system is greater than the second preset threshold, it indicates that the management operating system allocates too few physical resources to the first load operating system when allocating, to the first load operating system, the physical resource set that is exclusively used by the first load operating system; in this case, the
- 10 management operating system determines that a physical resource needs to be added for the first load operating system. Because there are three types of physical resources, the management operating system determines, according to utilization of each physical resource, a type identifier of the physical resource that needs to be added, and then the management operating system performs, according to the type identifier of the physical resource that needs
- 15 to be added, the second-time division on the available physical resources in the physical resource pool, and adds the physical resource of the first load operating system. In a specific implementation process, the management operating system may perform, according to utilization of a physical resource of the first load operating system and utilization of a physical resource of another load operating system, the second-time division on the available
- 20 physical resources, so as to add the physical resource of the first load operating system. The added physical resource is a physical resource corresponding to the type identifier of the physical resource that needs to be added.

The other possible implementation manner is that: the first load operating system monitors a use status of a physical resource of the first load operating system, so that the management

25 operating system adjusts the physical resource of the first load operating system. Two possible situations may be specifically included:

In one possible situation: the first load operating system monitors a physical resource of the

first load operating system; and

if the first load operating system determines that utilization of a physical resource allocated by the management operating system to the first load operating system is less than a first preset threshold, the first load operating system sends a resource reducing request
5 message to the management operating system, where the resource reducing request message includes a type identifier of a physical resource that needs to be reduced, and the type identifier of the physical resource is used to distinguish whether the physical resource that needs to be reduced is a processor core resource, a physical memory resource, or an external device resource.

10 In the other possible situation: the first load operating system monitors a physical resource of the first load operating system; and

if the first load operating system determines that utilization of a physical resource allocated by the management operating system to the first load operating system is greater than a second preset threshold, the first load operating system sends a resource adding request
15 message to the management operating system, where the resource adding request message includes a type identifier of a physical resource that needs to be added, and the type identifier of the physical resource is used to distinguish whether the physical resource that needs to be added is a processor core resource or a physical memory resource.

Specifically, in this embodiment, the first load operating system determines that the physical
20 resources allocated by the management operating system to the first load operating system include a processor core resource, a physical memory resource, and an external device resource. The first load operating system monitors, in the running process, utilization of the physical resources that have been allocated by the management operating system to the first load operating system, that is, monitors the utilization of the processor core resource, the
25 physical memory resource, and the external device resource.

When the first load operating system determines that utilization of a physical resource allocated to the first load operating system is less than the first preset threshold, it indicates

that the management operating system allocates too many physical resources to the first load operating system when allocating, to the first load operating system, the physical resource set exclusively used by the first load operating system; in this case, the first load operating system determines that a physical resource needs to be reduced for the first load operating system, and sends a resource reducing request message to the management operating system. Because there are three types of physical resources, the first load operating system determines, according to utilization of each physical resource, a type identifier of the physical resource that needs to be reduced. Therefore, the resource reducing request message includes the type identifier of the physical resource that needs to be reduced, where the type identifier of the physical resource is used to distinguish whether the physical resource that needs to be reduced is a processor core resource, a physical memory resource, or an external device resource.

When the first load operating system determines that utilization of a physical resource allocated to the first load operating system is greater than the second preset threshold, it indicates that the management operating system allocates too few physical resources to the first load operating system when allocating, to the first load operating system, the physical resource set exclusively used by the first load operating system; in this case, the first load operating system determines that a physical resource needs to be added for the first load operating system, and sends a resource adding request message to the management operating system. Because there are three types of physical resources, the first load operating system determines, according to utilization of each physical resource, a type identifier of the physical resource that needs to be added. Therefore, the resource adding request message includes the type identifier of the physical resource that needs to be added, where the type identifier of the physical resource is used to distinguish whether the physical resource that needs to be added is a processor core resource, a physical memory resource, or an external device resource.

The foregoing two possible implementation manners separately describe, from perspectives of the management operating system and the first load operating system, that a physical

resource of the first load operating system needs to be added or reduced. The following describes in detail, according to a type of a physical resource, adding or reduction of each physical resource.

FIG. 8A is a schematic flowchart for adding a processor core for the first load operating system when the physical resource is a processor core according to the present invention. FIG. 8B is a schematic flowchart for releasing a processor core by the first load operating system according to the present invention.

As shown in FIG. 8A, adding the processor core for the first load operating system includes the following steps:

Step 8101: The management operating system marks the processor core, which needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and sends a resource adding message to the first load operating system.

The resource adding message includes an identifier of the processor core that needs to be added.

Specifically, the management operating system marks the processor core, which needs to be added for the first load operating system, as the physical resource that belongs to the first load operating system, where the added processor core is not used as an available physical resource in the physical resource pool, and the management operating system and the first load operating system monitor utilization of the added processor core.

Step 8102: The first load operating system receives the resource adding message sent by the management operating system, where the resource adding message includes an identifier of the processor core that needs to be added.

Step 8103: The first load operating system determines, according to the identifier of the processor core that needs to be added, the processor core added by the management operating system for the first load operating system.

Step 8104: The management operating system sends a jump instruction to the added processor core.

The jump instruction is used to instruct the added processor core to execute a kernel program of the first load operating system, and instruct the added processor core to read, from the kernel program, all mapping relationships that are from virtual memory addresses to physical memory addresses and that are required for executing the first load operating system.

- 5 The management operating system sets, for the first load operating system, the kernel program in a preset fixed physical memory, and the management operating system and the first load operating system agree in advance on that the first load operating system may write, into the kernel program, all the mapping relationships that are from the virtual memory addresses to the physical memory addresses and that are required for executing the first load
- 10 operating system. Persons skilled in the art can understand that the kernel program may further include other information required for running the added processor core, on which this embodiment imposes no special limitation.

- Step 8105: The added processor core of the first load operating system receives the jump instruction sent by the management operating system, executes a kernel program of the first
- 15 load operating system according to the jump instruction, and reads, from the kernel program, all mapping relationships that are from virtual memory addresses to physical memory addresses and that are required for executing the first load operating system.

As shown in FIG. 8B, releasing the processor core by the first load operating system includes the following steps:

- 20 Step 8201: The management operating system sends a resource reducing message to the first load operating system.

The resource reducing message includes an identifier of the processor core that needs to be released.

- Step 8202: The first load operating system receives the resource reducing message sent by the
- 25 management operating system, where the resource reducing message includes an identifier of the processor core that needs to be released.

Step 8203: The first load operating system determines, according to the identifier of the

processor core that needs to be released, the processor core that needs to be released by the first load operating system.

Step 8204: The first load operating system releases the processor core, where the released processor core is a processor core corresponding to the identifier of the processor core that
5 needs to be released.

That the first load operating system releases the processor core refers to that the first load operating system no longer uses the processor core.

Step 8205: The management operating system acquires the identifier of the processor core released by the first load operating system, and adds the identifier of the released processor
10 core to a list of available physical resources in the resource pool, where the released processor core is a processor core corresponding to the identifier of the processor core that needs to be reduced.

FIG. 9A is a schematic flowchart for adding a physical memory address for the first load operating system when the physical resource is a physical memory resource according to the
15 present invention. FIG. 9B is a schematic flowchart for releasing a physical memory address by the first load operating system according to the present invention.

As shown in FIG. 9A, adding the physical memory address for the first load operating system includes the following steps:

Step 9101: The management operating system marks the physical memory address, which
20 needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and sends a resource adding message to the first load operating system.

The resource adding message includes an identifier of the physical memory address that needs to be added.

25 The management operating system marks the physical memory address, which needs to be added for the first load operating system, as the physical resource that belongs to the first load operating system, where the added physical memory address is not used as an available

physical resource in the physical resource pool, and the management operating system and the first load operating system monitor utilization of the added physical memory address; the first load operating system further constructs a mapping relationship that is from a virtual memory address to the added physical memory address.

- 5 Step 9102: The first load operating system receives the resource adding message sent by the management operating system, where the resource adding message includes an identifier of the physical memory address that needs to be added.

Step 9103: The first load operating system determines, according to the identifier of the physical memory address that needs to be added, the physical memory address added by the
10 management operating system for the first load operating system.

As shown in FIG. 9B, releasing the physical memory address by the first load operating system includes the following steps:

Step 9201: The management operating system sends a resource reducing message to the first load operating system.

- 15 The resource reducing message includes an identifier of the physical memory address that needs to be released.

Step 9202: The first load operating system receives the resource reducing message sent by the management operating system, where the resource reducing message includes an identifier of the physical memory address that needs to be released.

- 20 Step 9203: The first load operating system determines, according to the identifier of the physical memory address that needs to be released, the physical memory address that needs to be released by the first load operating system.

Step 9204: The first load operating system releases the physical memory address, where the released physical memory address is a physical memory address corresponding to the
25 identifier of the physical memory address that needs to be released.

Step 9205: The management operating system acquires the identifier of the physical memory address released by the first load operating system, and adds the identifier of the released

physical memory address to a list of available physical resources in the resource pool, where the released physical memory address is a physical memory address corresponding to the identifier of the physical memory address that needs to be released.

FIG. 10A is a schematic flowchart for adding an external device for the first load operating system when the physical resource is an external device resource according to the present invention. FIG. 10B is a schematic flowchart for reducing an external device for the first load operating system according to the present invention.

As shown in FIG. 10A, adding the external device for the first load operating system includes the following steps:

10 Step 10101: The management operating system marks the external device, which needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and sends a hot-insertion message to the first load operating system.

The hot-insertion message is used to instruct the first load operating system to acquire an identifier of the external device that needs to be added and a device description information table corresponding to the added external device.

Specifically, the management operating system marks the external device, which needs to be added for the first load operating system, as the physical resource that belongs to the first load operating system, where the added external device is not used as an available physical resource in the physical resource pool, and the management operating system and the first load operating system monitor utilization of the added external device.

That the hot-insertion message is used to instruct the first load operating system to acquire an identifier of the external device that needs to be added and a device description information table corresponding to the added external device includes two possible implementation manners:

25 In one possible implementation manner: the management operating system sends the hot-insertion message to the first load operating system, where the hot-insertion message includes the identifier of the external device that needs to be added and the device description

information table corresponding to the added external device.

In the other possible implementation manner: the management operating system sends a hot-insertion instruction message to the first load operating system, where the hot-insertion instruction message is used to instruct the first load operating system to read, from a preset
 5 fixed physical memory, the identifier of the external device that needs to be added and the device description information table corresponding to the added external device.

Step 10102: The first load operating system receives the hot-insertion message sent by the management operating system.

Step 10103: The first load operating system executes, according to an identifier of the
 10 external device that needs to be added and a device description information table corresponding to the added external device, a hot-insertion operation on an external device corresponding to the identifier of the external device that needs to be added.

As shown in FIG. 10B, reducing the external device for the first load operating system includes the following steps:

15 Step 10201: The management operating system sends a hot-removal message to the first load operating system.

The hot-removal message includes an identifier of the external device that needs to be reduced.

Step 10202: The first load operating system receives the hot-removal message sent by the
 20 management operating system, where the hot-removal message includes an identifier of the external device that needs to be reduced.

Step 10203: The first load operating system performs, according to the identifier of the external device that needs to be reduced, a hot-removal operation on an external device corresponding to the identifier of the external device that needs to be reduced.

25 Step 10204: The management operating system acquires the identifier of the external device that is reduced for the first load operating system, adds the identifier of the reduced external device to a list of available physical resources in the resource pool, where the reduced

external device is the external device corresponding to the identifier of the external device that needs to be reduced.

In the embodiments of the present invention, dynamic adjustment of a physical resource is implemented in the foregoing manners, so that not only a first load operating system can
5 exclusively use a physical resource, but also utilization of a physical resource is improved by adding or reducing a physical resource of the first load operating system.

FIG. 11 is a schematic structural diagram of Embodiment 1 of a management operating system according to the present invention. The management operating system in this embodiment is applied to the multi-kernel operating system shown in FIG. 1, where the
10 multi-kernel operating system includes the management operating system and multiple load operating systems that run on a host machine and includes a physical resource pool, and the physical resource pool includes processor cores and a physical memory that are of the host machine. As shown in FIG. 11, the management operating system 110 provided in this embodiment includes a resource allocating module 1101, a mapping relationship setting
15 module 1102, a startup processor core determining module 1103, and an instructing module 1104.

The resource allocating module 1101 is configured to allocate, to each load operating system, a physical resource set exclusively used by each load operating system, where each physical resource set includes some of the processor cores of the host machine and a part of the
20 physical memory of the host machine.

The mapping relationship setting module 1102 is configured to: construct a boot image for each load operating system, and set, for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image.

25 The startup processor core determining module 1103 is configured to determine, in processor cores allocated to a first load operating system, a startup processor core that starts up the first load operating system, where the first load operating system is any one of the load operating

systems.

The instructing module 1104 is configured to instruct the startup processor core to read a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system and is
 5 pre-constructed by the mapping relationship setting module, so as to enable the startup processor core to access, in a process of executing the boot image and according to the mapping relationship, the physical memory address; and instruct the startup processor core to execute the boot image pre-constructed for the first load operating system, where the boot image includes a startup parameter of the first load operating system, the startup parameter
 10 includes identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system.

The management operating system provided in this embodiment may execute the technical solutions of the foregoing resource processing method embodiments, and has a similar implementation principle and technical effect, and no detail is repeatedly described herein in
 15 this embodiment.

FIG. 12 is a schematic structural diagram of Embodiment 2 of a management operating system according to the present invention. This embodiment is implemented based on the embodiment in FIG. 11, and is specifically as follows:

Optionally, the instructing module 1104 is specifically configured to:

20 send an inter-core interrupt message to the startup processor core, where the inter-core interrupt message instructs the startup processor core to execute an initialization program that is configured to initialize the startup processor core and that is corresponding to the first load operating system; and

instruct, by instructing the startup processor core to execute the initialization
 25 program corresponding to the first load operating system, the startup processor core to read, from the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image of

the first load operating system; and instruct the startup processor core to jump, after running of the initialization program ends, to the location that is of the boot image and is in the physical memory, so as to execute the boot image of the first load operating system.

Optionally, the management operating system further includes an initialization program
 5 configuring module 1105, configured to: before the mapping relationship setting module sets, for each load operating system, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image, preset, for the first load operating system, an initialization program that is configured to initialize the first load operating system, and preset, in the initialization program, the location
 10 that is of the boot image of the first load operating system and that is in the physical memory address.

The mapping relationship setting module 1102 is specifically configured to set, in the initialization program and for the first load operating system, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for
 15 executing the boot image.

The management operating system provided in this embodiment may execute the technical solutions of the foregoing resource processing method embodiments, and has a similar implementation principle and technical effect, and no detail is repeatedly described herein in this embodiment.

20 FIG. 13 is a schematic structural diagram of Embodiment 3 of a management operating system according to the present invention. This embodiment is implemented based on the embodiment in FIG. 11, and is specifically as follows:

Optionally, the management operating system further includes an available-processor-core acquiring module 1106, configured to acquire available processor cores of a second load
 25 operating system before the startup processor core determining module determines, in the processor cores allocated to the first load operating system, the startup processor core that starts up the first load operating system, where the second load operating system is a

logged-out load operating system, other than the first load operating system, in the multiple load operating systems, the available processor cores include a processor core that has been started up, and a physical resource set of the first load operating system includes the available processor cores.

- 5 The startup processor core determining module 1103 is specifically configured to: when the physical resource set of the first load operating system includes the available processor cores, determine, in the available processor cores, the startup processor core that starts up the first load operating system.

Optionally, the management operating system further includes a daemon configuring module
 10 1107, configured to preset, for the first load operating system, a daemon on the startup processor core after the startup processor core determining module determines, in the available processor cores, the startup processor core that starts up the first load operating system, and preset, in the daemon, a location that is of the boot image of the first load operating system and that is in the physical memory address.

- 15 The mapping relationship setting module 1102 is specifically configured to set, for the first load operating system and in the daemon, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image.

Optionally, the instructing module 1104 is specifically configured to: send an inter-core
 20 interrupt message to the daemon running on the startup processor core, where the inter-core interrupt message instructs the startup processor core to read, from the daemon, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image and is pre-constructed by the management operating system for the first load operating system; and the location that is of the boot image
 25 corresponding to the first load operating system, that is in the physical memory address, and that is preset in the daemon by the daemon configuring module instructs the startup processor core to jump to the location that is in the physical memory address and in which the boot

image is located, so as to execute the boot image of the first load operating system.

The management operating system provided in this embodiment may execute the technical solutions of the foregoing resource processing method embodiments, and has a similar implementation principle and technical effect, and no detail is repeatedly described herein in
5 this embodiment.

Based on the embodiments in FIG. 12 and FIG. 13, the resource allocating module is specifically configured to:

perform, according to a quantity of the load operating systems, first-time division
on available physical resources that are in the physical resource pool and that are
10 corresponding to identifiers of physical resources in a list of the available physical resources
in the resource pool, to obtain multiple physical resource sets, where a quantity of the
physical resource sets equals the quantity of the load operating systems, and the management
operating system determines a correspondence between each load operating system and each
physical resource set; and

15 allocate, to each load operating system according to the correspondence, the
physical resource set exclusively used by each load operating system.

Optionally, each physical resource set further includes some external devices of the host
machine.

The startup parameter further includes an identifier of an external device allocated to the first
20 load operating system and a device description information table corresponding to the
external device.

Based on the embodiments in FIG. 12 and FIG. 13, when the management operating system
monitors running of the first load operating system, a structure of the management operating
system includes two possible implementation manners.

25 One possible implementation manner is that the management operating system further
includes:

a first monitoring module, configured to monitor, after the instructing module

instructs the startup processor core to execute the boot image pre-constructed for the first load operating system, running of the first load operating system; and

a first resource managing module, configured to determine that a physical resource needs to be reduced for the first load operating system if a monitoring result of the first monitoring module is that utilization of a physical resource allocated to the first load operating system is less than a first preset threshold, and determine a type identifier of the physical resource that needs to be reduced, where the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource, a physical memory resource, or an external device resource.

The resource allocating module is further configured to perform, according to the type identifier of the physical resource that needs to be reduced, second-time division on the available physical resources that are in the physical resource pool and that are corresponding to the identifiers of the physical resources in the list of the available physical resources in the resource pool, and reduce the physical resource of the first load operating system, where the reduced physical resource is a physical resource corresponding to the type identifier of the physical resource that needs to be reduced.

The other possible implementation manner is that the management operating system further includes:

a second monitoring module, configured to monitor, after the instructing module instructs the startup processor core to execute the boot image pre-constructed for the first load operating system, running of the first load operating system; and

a second resource managing module, configured to determine that a physical resource needs to be added for the first load operating system if a monitoring result of the second monitoring module is that utilization of a physical resource allocated to the first load operating system is greater than a second preset threshold, and determine a type identifier of the physical resource that needs to be added, where the type identifier of the physical resource is used to distinguish whether the physical resource that needs to be added is a

processor core resource, a physical memory resource, or an external device resource.

The resource allocating module is further configured to perform, according to the type identifier of the physical resource that needs to be added, second-time division on the available physical resources that are in the physical resource pool and that are corresponding to the identifiers of the physical resources in the list of the available physical resources in the resource pool, and add the physical resource of the first load operating system, where the added physical resource is a physical resource corresponding to the type identifier of the physical resource that needs to be added.

Based on the embodiments in FIG. 12 and FIG. 13, when the management operating system monitors running of the first load operating system, a structure of the management operating system includes two possible implementation manners.

One possible implementation manner is that the management operating system further includes:

a first receiving module, configured to receive, after the instructing module instructs the startup processor core to execute the boot image pre-constructed for the first load operating system, a resource reducing request message sent by the first load operating system, where the resource reducing request message includes a type identifier of a physical resource that needs to be reduced, and the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource, a physical memory resource, or an external device resource.

The resource allocating module is further configured to perform, according to the type identifier, of the physical resource that needs to be reduced, in the resource reducing request message, second-time division on the available physical resources that are in the physical resource pool and that are corresponding to the identifiers of the physical resources in the list of the available physical resources in the resource pool, and reduce the physical resource of the first load operating system, where the reduced physical resource is a physical resource corresponding to the type identifier of the physical resource that needs to be reduced.

The other possible implementation manner is that the management operating system further includes:

- 5 a second receiving module, configured to receive, after the instructing module instructs the startup processor core to execute the boot image pre-constructed for the first load operating system, a resource adding request message sent by the first load operating system, where the resource adding request message includes a type identifier of a physical resource that needs to be added, and the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource, a physical memory resource, or an external device resource.
- 10 The resource allocating module is further configured to perform, according to the type identifier, of the physical resource that needs to be added, in the resource adding request message, second-time division on the available physical resources that are in the physical resource pool and that are corresponding to the identifiers of the physical resources in the list of the available physical resources in the resource pool, and add the physical resource of the
- 15 first load operating system, where the added physical resource is a physical resource corresponding to the type identifier of the physical resource that needs to be added.

Based on the foregoing embodiments, if the physical resource that needs to be added is a processor core, the resource allocating module is further specifically configured to:

- 20 mark the processor core, which needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and send a resource adding message to the first load operating system, where the resource adding message includes an identifier of the processor core that needs to be added; and

- send a jump instruction to the added processor core, where the jump instruction is used to instruct the added processor core to execute a kernel program of the first load
- 25 operating system, and instruct the added processor core to read, from the kernel program, all mapping relationships that are from virtual memory addresses to physical memory addresses and that are required for executing the first load operating system.

Based on the foregoing embodiments, if the physical resource that needs to be reduced is a processor core, the resource allocating module is further specifically configured to:

5 send a resource reducing message to the first load operating system, where the resource reducing message includes an identifier of the processor core that needs to be released; and

 acquire the identifier of the processor core released by the first load operating system, and add the identifier of the released processor core to the list of the available physical resources in the resource pool, where the released processor core is a processor core corresponding to the identifier of the processor core that needs to be reduced.

10 Based on the foregoing embodiments, if the physical resource that needs to be added is a physical memory resource, the resource allocating module is further specifically configured to: mark a physical memory address, which needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and send a resource adding message to the first load operating system, where the resource adding
15 message includes an identifier of the physical memory address that needs to be added.

 Based on the foregoing embodiments, if the physical resource that needs to be reduced is a physical memory resource, the resource allocating module is further specifically configured to: send a resource reducing message to the first load operating system, where the resource reducing message includes an identifier of a physical memory address that needs to be
20 released; and

 acquire an identifier of the physical memory address released by the first load operating system, and add the identifier of the released physical memory address to the list of the available physical resources in the resource pool, where the released physical memory address is a physical memory address corresponding to the identifier of the physical memory
25 address that needs to be released.

Based on the foregoing embodiments, if the physical resource that needs to be added is an external device resource, the resource allocating module is further specifically configured to:

mark an external device, which needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and send a hot-insertion message to the first load operating system, where the hot-insertion message is used to instruct the first load operating system to acquire an identifier of the external device that needs to be added and a device description information table corresponding to the added external device.

Based on the foregoing embodiments, if the physical resource that needs to be reduced is an external device resource, the resource allocating module is further specifically configured to: send a hot-removal message to the first load operating system, where the hot-removal message includes an identifier of an external device that needs to be reduced; and

acquire the identifier of the external device reduced for the first load operating system, and add the identifier of the reduced external device to the list of the available physical resources in the resource pool, where the reduced external device is an external device corresponding to the identifier of the external device that needs to be reduced.

The management operating system provided in this embodiment may execute the technical solutions of the foregoing resource processing method embodiments, and has a similar implementation principle and technical effect, and no detail is repeatedly described herein in this embodiment.

Based on the embodiments in FIG. 11 to FIG. 13, the management operating system may further include another module required for running, for example:

an inter-instance communication module, configured to implement bottom-layer communication between the management operating system and another load operating system, where notification and response are generally performed not by using a network but in an inter-processor interrupt manner;

a resource runtime assisting module, where because of a limitation of a hardware function, when an interrupt of an external device cannot be directly routed to a load operating system, the resource runtime assisting module of the management operating system may forward the interrupt, and help to implement normal response to the interrupt; or when the

hardware function fully supports automatic routing of an interrupt and free configuration of direct memory access (Direct Memory Access, DMA for short), that is, when an interrupt of an external device is directly routed to a load operating system, the resource runtime assisting module may be canceled;

5 a terminal service module: configured to prepare a virtual terminal device for a Light OS that needs a terminal (a keyboard, a mouse, or a graphics card), ensure communication efficiency by using a mechanism such as memory sharing, and provide support in running; and

 an application managing module, configured to virtualize a user-oriented
10 management interface of a system, make it easy for a user to manage a complicated application, and develop an appropriate application scheduling policy.

FIG. 14 is a schematic structural diagram of Embodiment 1 of a load operating system according to the present invention. The load operating system provided in this embodiment is applied to the multi-kernel operating system shown in FIG. 1, where the multi-kernel
15 operating system includes a management operating system and multiple load operating systems that run on a host machine and includes a physical resource pool, the physical resource pool includes processor cores and a physical memory that are of the host machine, each load operating system exclusively uses a physical resource set allocated by the management operating system, and each physical resource set includes some of the processor
20 cores of the host machine and a part of the physical memory of the host machine; the management operating system pre-constructs a boot image for each load operating system, and sets, for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the boot image; and the load operating system 140 includes a mapping relationship acquiring module 1401, an
25 instruction executing module 1402, a startup parameter acquiring module 1403, and a physical resource set acquiring module 1404.

The mapping relationship acquiring module 1401 is configured to read a mapping

relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of a first load operating system, where the mapping relationship is used to enable a startup processor core of the first load operating system to access the physical memory address, and the first load operating system is any load operating system in the multi-kernel operating system.

The instruction executing module 1402 is configured to jump, according to an instruction that is set by the management operating system and that is for executing a boot image jump, to a location that is of the boot image corresponding to the first load operating system and that is in the physical memory address, and execute, according to the mapping relationship, the boot image corresponding to the first load operating system.

The startup parameter acquiring module 1403 is configured to acquire, in a process of executing the boot image of the first load operating system by the instruction executing module, a startup parameter of the first load operating system from the boot image of the first load operating system, where the startup parameter includes identifiers of processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system.

The physical resource set acquiring module 1404 is configured to determine, according to the identifiers of the processor cores and the identifier of the physical memory address of the first load operating system, a physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system.

The load operating system provided in this embodiment may execute the technical solutions of the foregoing resource processing method embodiments, and has a similar implementation principle and technical effect, and no detail is repeatedly described herein in this embodiment.

FIG. 15 is a schematic structural diagram of Embodiment 2 of a load operating system according to the present invention. This embodiment is implemented based on the

embodiment in FIG. 14, and is specifically as follows:

Optionally, the mapping relationship acquiring module 1401 is specifically configured to:

5 receive an inter-core interrupt message sent by the management operating system, where the startup processor core executes, according to an instruction of the inter-core interrupt message, an initialization program that is configured to initialize the startup processor core and that is corresponding to the first load operating system; and

10 execute the initialization program, and read, from the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image and is pre-constructed by the management operating system for the first load operating system.

The instruction executing module 1402 is specifically configured to: execute the initialization program, read, from the initialization program, a jump instruction that is preset in the initialization program by the management operating system, and jump to the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address.

15 Optionally, the startup processor core of the first load operating system is a processor core that has been started up and that is determined by the management operating system, a daemon runs on the startup processor core of the first load operating system, the daemon is preset by the management operating system for the first load operating system, the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address and the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image are set in the daemon.

25 Optionally, the mapping relationship acquiring module 1401 is specifically configured to read, from the daemon and according to an instruction of an inter-core interrupt message after the daemon running on the startup processor core receives the inter-core interrupt message sent by the management operating system, the mapping relationship that is from the virtual

memory address to the physical memory address and that is required for executing the boot image and is pre-constructed by the management operating system for the first load operating system.

5 The instruction executing module 1402 is specifically configured to: read a jump instruction that is preset in the daemon by the management operating system, and jump to the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address.

Optionally, each physical resource set further includes some external devices of the host machine; and

10 the startup parameter further includes an identifier of an external device allocated by the management operating system to the first load operating system and a device description information table corresponding to the external device.

Optionally, the load operating system further includes a mapping relationship constructing module 1405, configured to construct, after the physical resource set acquiring module
15 determines the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system, all mapping relationships that are from virtual memory addresses to physical memory addresses and that are required for executing the first load operating system; and

access the physical memory address according to all the mapping relationships
20 that are from the virtual memory addresses to the physical memory addresses and that are required for executing the first load operating system.

Optionally, the instruction executing module 1402 is further configured to: after the physical resource set acquiring module determines the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used
25 by the first load operating system, execute, by using the processor cores allocated to the first load operating system, a privileged instruction delivered by the management operating system.

The load operating system provided in this embodiment may execute the technical solutions of the foregoing resource processing method embodiments, and has a similar implementation principle and technical effect, and no detail is repeatedly described herein in this embodiment.

- 5 Based on the embodiment in FIG. 15, the first load operating system monitors a physical resource of the first load operating system, and implements dynamic resource adjustment; optionally, the load operating system further includes:

 a first monitoring module, configured to monitor a physical resource of the first load operating system after the physical resource set acquiring module determines the
10 physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system; and

 a first sending module, configured to send a resource reducing request message to the management operating system if a monitoring result of the first monitoring module is that utilization of the physical resource allocated by the management operating system to the first
15 load operating system is less than a first preset threshold, where the resource reducing request message includes a type identifier of a physical resource that needs to be reduced, and the type identifier of the physical resource is used to distinguish whether the physical resource that needs to be reduced is a processor core resource, a physical memory resource, or an external device resource.

- 20 Optionally, the load operating system further includes:

 a second monitoring module, configured to monitor a physical resource of the first load operating system after the physical resource set acquiring module determines the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system; and

25 a second sending module, configured to send a resource adding request message to the management operating system if a monitoring result of the first monitoring module is that utilization of the physical resource allocated by the management operating system to the first

load operating system is greater than a second preset threshold, where the resource adding request message includes a type identifier of a physical resource that needs to be added, and the type identifier of the physical resource is used to distinguish whether the physical resource that needs to be added is a processor core resource or a physical memory resource.

5 Optionally, if the physical resource that needs to be added is a processor core, the physical resource set acquiring module is further specifically configured to: after the second sending module sends the resource adding request message to the management operating system,

 receive a resource adding message sent by the management operating system, where the resource adding message includes an identifier of the processor core that needs to
10 be added; and

 determine, according to the identifier of the processor core that needs to be added, the processor core added by the management operating system for the first load operating system; and

 when the added processor core of the first load operating system receives a jump
15 instruction sent by the management operating system, execute a kernel program of the first load operating system according to the jump instruction, and read, from the kernel program, all mapping relationships that are from virtual memory addresses to physical memory addresses and that are required for executing the first load operating system, where the first
20 load operating system presets, in the kernel program, all the mapping relationships that are from the virtual memory addresses to the physical memory addresses and that are required for executing the first load operating system.

Optionally, if the physical resource that needs to be reduced is a processor core, the physical resource set acquiring module is further specifically configured to: after the first sending module sends the resource reducing request message to the management operating system,

25 receive a resource reducing message sent by the management operating system, where the resource reducing message includes an identifier of the processor core that needs to be released;

determine, according to the identifier of the processor core that needs to be released, the processor core that needs to be released by the first load operating system; and

release the processor core, where the released processor core is a processor core corresponding to the identifier of the processor core that needs to be reduced.

- 5 Optionally, if the physical resource that needs to be added is a physical memory resource, the physical resource set acquiring module is further specifically configured to: after the second sending module sends the resource adding request message to the management operating system,

- 10 receive a resource adding message sent by the management operating system, where the resource adding message includes an identifier of a physical memory address that needs to be added; and

determine, according to the identifier of the physical memory address that needs to be added, the physical memory address added by the management operating system for the first load operating system.

- 15 Optionally, if the physical resource that needs to be reduced is a physical memory resource, the physical resource set acquiring module is further specifically configured to: after the first sending module sends the resource reducing request message to the management operating system,

- 20 receive a resource reducing message sent by the management operating system, where the resource reducing message includes an identifier of a physical memory address that needs to be released;

determine, according to the identifier of the physical memory address that needs to be released, the physical memory address that needs to be released by the first load operating system, and

- 25 release the physical memory address, where the released physical memory address is a physical memory address corresponding to the identifier of the physical memory address that needs to be released.

Optionally, if the physical resource that needs to be added is an external device resource, the physical resource set acquiring module is further specifically configured to: after the second sending module sends the resource adding request message to the management operating system,

5 receive a hot-insertion message sent by the management operating system, where the hot-insertion message is used to instruct the first load operating system to acquire an identifier of an external device that needs to be added and a device description information table corresponding to the added external device;

 execute, according to the identifier of the external device that needs to be added
10 and the device description information table corresponding to the added external device, a hot-insertion operation on the external device corresponding to the identifier of the external device that needs to be added.

Optionally, if the physical resource that needs to be reduced is a physical memory resource, the physical resource set acquiring module is further specifically configured to: after the first
15 sending module sends the resource reducing request message to the management operating system,

 receive a hot-removal message sent by the management operating system, where the hot-removal message includes an identifier of an external device that needs to be reduced;

 execute, according to the identifier of the external device that needs to be reduced,
20 a hot-removal operation on the external device corresponding to the identifier of the external device that needs to be reduced.

The load operating system provided in this embodiment may execute the technical solutions of the foregoing resource processing method embodiments, and has a similar implementation principle and technical effect, and no detail is repeatedly described herein in this
25 embodiment.

Based on the embodiments in FIG. 14 and FIG. 15, the load operating system may further include another module required for running, for example:

an inter-instance communication module, configured to perform fast communication that is in the host machine and that is between the load operating system and the management operating system or another load operating system;

5 a virtual terminal, where by using a terminal virtualization service provided by the management operating system, the load operating system may be directly operated by a user in a terminal manner; and

an application managing module, configured to receive an application deployed by the management operating system or by another application, and run and manage execution of the application.

10 FIG. 16 is a schematic diagram of an architecture of a multi-core system on a heterogeneous platform. As shown in FIG. 16, in this embodiment of a virtualization system according to the present invention, on a heterogeneous node, there are processors such as a data processing unit (Data Processing Unit, DPU for short), a Xeon (Xeon) processor, and a general purpose graphic processing unit (General Purpose Graphic Processing Unit, GPGPU for short). Each
15 processor includes multiple processor cores, and heterogeneous processors are interconnected by using a PCI-E bus and are combined in a non-uniform memory access (Non-uniform Memory Access, NUMA for short) manner. On the heterogeneous platform, there are also resources such as a physical memory, a disk array, and a network adapter array, which are connected by using devices such as a front side bus, an input/output control center, and a PCI
20 bus.

In this embodiment, a management operating system and some load operating systems run on a processor core corresponding to the Xeon processor, and another customized load operating system runs on a processor core corresponding to another processor, for example, a GPGPU is suitable to run a computing task with a high degree of parallelism, and a DPU is suitable to
25 run a data processing service. Therefore, load operating systems are separately customized for the GPGPU and the DPU according to a service type of each processor, for example, a load operating system customized for the GPGPU includes only a runtime library support for

a basic matrix operation, and mainly supports languages such as computer unified device architecture (Compute Unified Device Architecture, CUDA for short); and a load operating system customized for the DPU includes only a package support for data processing, mainly supports applications such as a distributed system infrastructure (for example, Hadoop), and
5 excludes other computing components.

The management operating system may further manage a memory (for example, DRAM) connected by a PCI-E switch, start up, according to a configuration file designated by an administrator, multiple load operating systems that are on the DPU, and send a task to a load operating system by using an application management program. Optionally, for a data
10 processing application, because a requirement of the application on a quantity of processes and threads is not high, when multiple cores optimize a data channel processing capability, support for data structures such as concurrent threads and processes may be reduced, thereby reducing space or performance overheads, and improving performance.

FIG. 17 is a schematic structural diagram of Embodiment 1 of a host machine according to
15 the present invention. As shown in FIG. 17, a host machine 170 provided in this embodiment includes a processor 1701 and a memory 1702, where the memory 1702 stores an execution instruction, and when the host machine 170 runs, the processor 1701 communicates with the memory 1702, and the processor 1701 executes the execution instruction that is in the memory 1702, to enable the host machine 170 to execute an operation of the technical
20 solutions of the foregoing resource processing methods.

The host machine in this embodiment may be configured to execute the technical solutions of the foregoing virtual machine system management method embodiment according to the present invention, and has a similar implementation principle and technical effect, and no detail is repeatedly described herein.

25 In the several embodiments provided in the present application, it should be understood that the disclosed system and method may be implemented in other manners. For example, the described system embodiment is merely exemplary. For example, the module division is

merely logical function division and may be other division in actual implementation. For example, a plurality of modules or components may be combined or integrated into another system, or some features may be ignored or not performed. In addition, the displayed or discussed mutual couplings or direct couplings or communication connections may be
5 implemented through some interfaces. The indirect couplings or communication connections between the modules may be implemented in electronic, mechanical, or other forms.

Persons of ordinary skill in the art can understand that all or some of the steps of the method embodiments may be implemented by a program instructing relevant hardware. The program may be stored in a computer-readable storage medium. When the program runs, the steps of
10 the method embodiments are performed. The foregoing storage medium includes: any medium that can store program code, such as a ROM, a RAM, a magnetic disc, or an optical disc.

Finally, it should be noted that the foregoing embodiments are merely intended for describing the technical solutions of the present invention, but not for limiting the present invention.
15 Although the present invention is described in detail with reference to the foregoing embodiments, persons of ordinary skill in the art should understand that they may still make modifications to the technical solutions described in the foregoing embodiments or make equivalent replacements to some or all technical features thereof, without departing from the scope of the technical solutions of the embodiments of the present invention.

CLAIMS:

1. A resource processing method, wherein the method is applied to a multi-kernel operating system, the multi-kernel operating system comprises a management operating system and multiple load operating systems that run on a host machine, the host machine
 5 comprises a physical resource pool, the physical resource pool comprises processor cores and a physical memory that are of the host machine, wherein the management operating system is configured to manage the multiple load operating systems, which includes allocating, to the multiple load operating systems, physical resources exclusively used by the multiple load operating systems, and being responsible for startup of the load operating systems, wherein a
 10 load operating system is configured to exclusively use and access a physical resource allocated by the management operating system after the load operating system is started up, and wherein the method comprises:

determining, by the management operating system and in processor cores allocated to a first load operating system, a startup processor core that starts up the first load operating
 15 system, wherein the first load operating system is any load operating system in the multiple load operating systems, the management operating system pre-allocates, to the first load operating system, a physical resource set exclusively used by the first load operating system, and the physical resource set comprises some of the processor cores and a part of the physical memory that are of the host machine;

20 sending, by the management operating system, an inter-core interrupt message to the startup processor core, wherein the inter-core interrupt message instructs the startup processor core to execute an initialization program, the initialization program configured to initialize the startup processor core, wherein the initialization program is executed to read a mapping relationship, from a virtual memory address to a physical memory address, for executing a
 25 boot image of the first load operating system, wherein the physical memory address comprises a location of the boot image corresponding to the first load operating system; and

instructing, by the management operating system, the startup processor core to execute the boot image to start up the first load operating system, wherein the boot image comprises a startup parameter of the first load operating system, and the startup parameter comprises identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system.

2. The method according to claim 1, wherein the method further comprises:

constructing, by the management operating system, the boot image for the first load operating system; and

setting, by the management operating system for the first load operating system, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image.

3. The method according to claim 1 or 2, wherein before the determining a startup processor core that starts up the first load operating system, the method further comprises:

acquiring, by the management operating system, available processor cores of a second load operating system, wherein the second load operating system is a logged-out load operating system, other than the first load operating system, in the multiple load operating systems, the available processor cores comprise a processor core that has been started up; and

the determining a startup processor core that starts up the first load operating system comprises:

when the physical resource set of the first load operating system comprises the available processor cores, determining, by the management operating system and in the available processor cores, the startup processor core that starts up the first load operating system.

4. The method according to claim 1, wherein after the instructing the startup processor core to execute the boot image, the method further comprises:

monitoring, by the management operating system, running of the first load operating system; and

when utilization of a physical resource allocated to the first load operating system is less than a first preset threshold, determining, by the management operating system, a type identifier of a physical resource that needs to be reduced for the first load operating system, and reducing the physical resource of the first load operating system according to the type
5 identifier of the physical resource that needs to be reduced; or

when utilization of a physical resource allocated to the first load operating system is greater than a second preset threshold, determining, by the management operating system, a type identifier of a physical resource that needs to be added for the first load operating system, and adding the physical resource of the first load operating system according to the type
10 identifier of the physical resource that needs to be added, wherein

the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource or a physical memory resource.

5. The method according to claim 1, wherein

the physical resource set further comprises some external devices of the host machine;
15 the startup parameter further comprises an identifier of an external device allocated to the first load operating system and a device description information table corresponding to the external device; and

after the instructing, by the management operating system, the startup processor core to execute the boot image pre-constructed for the first load operating system, the method further
20 comprises:

receiving, by the management operating system, a resource reducing request message sent by the first load operating system, wherein the resource reducing request message comprises a type identifier of a physical resource that needs to be reduced, and the type identifier of the physical resource is used to distinguish whether the physical resource is a
25 processor core resource, a physical memory resource, or an external device resource; and

reducing, by the management operating system, the physical resource of the first load operating system according to the type identifier of the physical resource that needs to be reduced.

6. The method according to claim 1, wherein the physical resource set further comprises
5 some external devices of the host machine; the startup parameter further comprises an identifier of an external device allocated to the first load operating system and a device description information table corresponding to the external device; and

after the instructing, by the management operating system, the startup processor core to execute the boot image pre-constructed for the first load operating system, the method further
10 comprises:

receiving, by the management operating system, a resource adding request message sent by the first load operating system, wherein the resource adding request message comprises a type identifier of a physical resource that needs to be added, and the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core
15 resource, a physical memory resource, or an external device resource; and

adding, by the management operating system, the physical resource of the first load operating system according to the type identifier of the physical resource that needs to be added.

7. The method according to claim 4 or 6, wherein if the physical resource that needs to
20 be added is a processor core, the adding, by the management operating system, the physical resource of the first load operating system comprises:

marking, by the management operating system, the processor core, which needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and sending a resource adding message to the first load operating system,
25 wherein the resource adding message comprises an identifier of the processor core that needs to be added; and

sending, by the management operating system, a jump instruction to the added processor core, wherein the jump instruction is used to instruct the added processor core to execute a kernel program of the first load operating system, and the kernel program comprises all mapping relationships that are from virtual memory addresses to physical memory addresses
 5 and that are required for executing the first load operating system.

8. The method according to claim 4 or 5, wherein if the physical resource that needs to be reduced comprises a processor core or a physical memory resource, the reducing, by the management operating system, the physical resource of the first load operating system according to the type identifier of the physical resource that needs to be reduced comprises:

10 sending, by the management operating system, a resource reducing message to the first load operating system, wherein the resource reducing message comprises an identifier of the physical resource that needs to be released; and

acquiring, by the management operating system, the identifier of the physical resource released by the first load operating system, and adding the identifier of the released physical
 15 resource to a list of available physical resources in the resource pool.

9. The method according to claim 4 or 6, wherein if the physical resource that needs to be added is a physical memory resource, the adding, by the management operating system, the physical resource of the first load operating system comprises:

20 marking, by the management operating system, a physical memory address, which needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and sending a resource adding message to the first load operating system, wherein the resource adding message comprises an identifier of the physical memory address that needs to be added.

25 10. A resource processing method, wherein the method is applied to a multi-kernel operating system, the multi-kernel operating system comprises a management operating system and multiple load operating systems that run on a host machine, the host machine comprises a physical resource pool, the physical resource pool comprises processor cores and

a physical memory that are of the host machine, wherein the management operating system is configured to manage the multiple load operating systems, which includes allocating, to the multiple load operating systems, physical resources exclusively used by the multiple load operating systems, and being responsible for startup of the load operating systems, wherein
5 each load operating system exclusively uses and accesses a physical resource set allocated by the management operating system, each physical resource set comprises some of the processor cores of the host machine and a part of the physical memory of the host machine, and the management operating system pre-constructs a boot image for each load operating system, and sets, for each load operating system, a mapping relationship that is from a virtual
10 memory address to a physical memory address and that is required for executing the boot image, and the method comprises:

receiving an inter-core interrupt message from the management operating system, the inter-core interrupt message instructing a startup processor core to execute an initialization program, the initialization program configured to initialize the startup processor core;

15 reading, by the startup processor core from the initialization program, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a boot image of the first load operating system in a process of executing the initialization program, wherein the mapping relationship is used to enable the startup processor core of the first load operating system to access the physical memory
20 address, and the first load operating system is any load operating system in the multiple load operating systems;

jumping, by the startup processor core of the first load operating system according to an instruction that is set by the management operating system and that is for executing a boot image jump, to a location that is of the boot image corresponding to the first load operating
25 system and that is in the physical memory address;

executing, by the startup processor core according to the mapping relationship, the boot image corresponding to the first load operating system;

acquiring, by the startup processor core of the first load operating system and in a process of executing the boot image of the first load operating system, a startup parameter of the first load operating system from the boot image of the first load operating system, wherein the startup parameter comprises identifiers of processor cores allocated to the first
5 load operating system and an identifier of the physical memory address allocated to the first load operating system; and

determining, by the first load operating system according to the identifiers of the processor cores and the identifier of the physical memory address of the first load operating system, a physical resource set that is allocated by the management operating system to the
10 first load operating system and that is exclusively used by the first load operating system.

11. The method according to claim 10, wherein after the determining, by the first load operating system, a physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system, the method further comprises:

15 constructing, by the first load operating system, all mapping relationships that are from virtual memory addresses to physical memory addresses and that are required for executing the first load operating system;

accessing, by the processor cores of the first load operating system, the physical memory address according to all the mapping relationships that are from the virtual memory addresses
20 to the physical memory addresses and that are required for executing the first load operating system.

12. The method according to claim 10, wherein after the determining, by the first load operating system, a physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load
25 operating system, the method further comprises:

executing, by the first load operating system by using the processor cores allocated to the first load operating system, a privileged instruction delivered by the management operating system.

13. The method according to claim 10, wherein after the determining, by the first load
5 operating system, a physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system, the method further comprises:

monitoring, by the first load operating system, a physical resource of the first load operating system; and

10 if the first load operating system determines that utilization of the physical resource allocated by the management operating system to the first load operating system is less than a first preset threshold, sending, by the first load operating system, a resource reducing request message to the management operating system, wherein the resource reducing request message comprises a type identifier of a physical resource that needs to be reduced; or

15 if the first load operating system determines that utilization of the physical resource allocated by the management operating system to the first load operating system is greater than a second preset threshold, sending, by the first load operating system, a resource adding request message to the management operating system, wherein the resource adding request message comprises a type identifier of a physical resource that needs to be added, wherein

20 the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource or a physical memory resource.

14. The method according to claim 13, wherein if the physical resource that needs to be added is a processor core, after the sending, by the first load operating system, a resource adding request message to the management operating system, the method further comprises:

25 receiving, by the first load operating system, a resource adding message sent by the management operating system, wherein the resource adding message comprises an identifier of the processor core that needs to be added;

determining, by the first load operating system according to the identifier of the processor core that needs to be added, the processor core added by the management operating system for the first load operating system; and

receiving, by the added processor core of the first load operating system, a jump instruction sent by the management operating system, executing a kernel program of the first load operating system according to the jump instruction, and reading, from the kernel program, all mapping relationships that are from virtual memory addresses to physical memory addresses and that are required for executing the first load operating system, wherein the first load operating system presets, in the kernel program, all the mapping relationships that are from the virtual memory addresses to the physical memory addresses and that are required for executing the first load operating system.

15. The method according to claim 13, wherein if the physical resource that needs to be reduced is a processor core or a physical memory resource, after the sending, by the first load operating system, a resource reducing request message to the management operating system, the method further comprises:

receiving, by the first load operating system, a resource reducing message sent by the management operating system, wherein the resource reducing message comprises an identifier of the physical resource that needs to be released; and

releasing, by the first load operating system, the physical resource according to the identifier of the physical resource that needs to be released.

16. The method according to claim 13, wherein if the physical resource that needs to be added is a physical memory resource, after the sending, by the first load operating system, a resource adding request message to the management operating system, the method further comprises:

receiving, by the first load operating system, a resource adding message sent by the management operating system, wherein the resource adding message comprises an identifier of a physical memory address that needs to be added; and

determining, by the first load operating system according to the identifier of the physical memory address that needs to be added, the physical memory address added by the management operating system for the first load operating system.

17. A host machine, wherein the host machine is configured to run a multi-kernel
 5 operating system including a management operating system and multiple load operating systems, the multiple load operating systems comprise a first load operating system, the host machine comprises a physical resource pool, the physical resource pool comprises processor cores and a physical memory that are of the host machine, wherein the management operating system is configured to manage the multiple load operating systems, which includes
 10 allocating, to the multiple load operating systems, physical resources exclusively used by the multiple load operating systems, and being responsible for startup of the load operating systems, wherein a load operating system is configured to exclusively use and access a physical resource allocated by the management operating system after the load operating system is started up, and wherein when the host machine runs, the management operating
 15 system is configured to:

determine, in processor cores allocated to the first load operating system, a startup processor core that starts up the first load operating system, wherein the first load operating system is any load operating system in the multiple load operating systems, the management operating system allocates, to the first load operating system, a physical resource set
 20 exclusively used by the first load operating system, and the physical resource set comprises some of the processor cores and a part of the physical memory that are of the host machine;

send an inter-core interrupt message to the startup processor core, wherein the inter-core interrupt message instructs the startup processor core to execute an initialization program, the initialization program configured to initialize the startup processor core, wherein the
 25 initialization program is executed to read a mapping relationship, from a virtual memory address to a physical memory address, for executing a boot image of the first load operating

system, wherein the physical memory address comprises a location of the boot image corresponding to the first load operating system; and

instruct the startup processor core to execute the boot image to start up the first load operating system, wherein the boot image comprises a startup parameter of the first load operating system, and the startup parameter comprises identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system; and

the first load operating system is configured to:

receive, by the startup processor core of the processor cores for the first load operating system, the inter-core interrupt message from the management operating system;

read, from the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image of the first load operating system in a process of executing the initialization program, wherein the mapping relationship is used to enable the startup processor core of the first load operating system to access the physical memory address;

jump, according to an instruction that is set by the management operating system and that is for executing a boot image jump, to the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address;

execute, according to the mapping relationship, the boot image corresponding to the first load operating system;

acquire, in a process of executing the boot image of the first load operating system, the startup parameter of the first load operating system from the boot image of the first load operating system; and

determine, according to the identifiers of the processor cores and the identifier of the physical memory address of the first load operating system, the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system.

18. The host machine according to claim 17, wherein the management operating system is further configured to:

construct the boot image for the first load operating system; and

5 set, for the first load operating system, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image.

19. The host machine according to claim 17 or 18, wherein the management operating system is further configured to:

10 acquire available processor cores of a second load operating system before determining, in the processor cores allocated to the first load operating system, the startup processor core that starts up the first load operating system, wherein the second load operating system is a logged-out load operating system, other than the first load operating system, in the multiple load operating systems, the available processor cores comprise a processor core that has been started up; and

15 when the physical resource set of the first load operating system comprises the available processor cores, determine, in the available processor cores, the startup processor core that starts up the first load operating system.

20. The host machine according to claim 17 or 18, wherein the first load operating system is further configured to:

20 after determining the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system, construct all mapping relationships that are from virtual memory addresses to physical memory addresses and that are required for executing the first load operating system; and

25 access the physical memory address according to all the mapping relationships that are from the virtual memory addresses to the physical memory addresses and that are required for executing the first load operating system.

21. The host machine according to claim 17 or 18, wherein the first load operating system is further configured to:

execute, by using the processor cores allocated to the first load operating system, a privileged instruction delivered by the management operating system.

5 22. The host machine according to claim 17, wherein the management operating system is further configured to:

monitor running of the first load operating system after instructing the startup processor core to execute the boot image pre-constructed for the first load operating system; and

10 when utilization of a physical resource allocated to the first load operating system is less than a first preset threshold, determine a type identifier of a physical resource that needs to be reduced for the first load operating system, and reduce the physical resource of the first load operating system according to the type identifier of the physical resource that needs to be reduced; or

15 when utilization of a physical resource allocated to the first load operating system is greater than a second preset threshold, determine a type identifier of a physical resource that needs to be added for the first load operating system, and add the physical resource of the first load operating system according to the type identifier of the physical resource that needs to be added, wherein

20 the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource or a physical memory resource.

23. The host machine according to claim 17, wherein the first load operating system is further configured to:

monitor a physical resource of the first load operating system; and

25 if the first load operating system determines that utilization of the physical resource allocated by the management operating system to the first load operating system is less than a first preset threshold, send a resource reducing request message to the management operating system, wherein the resource reducing request message comprises a type identifier of a

physical resource that needs to be reduced, and the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource or a physical memory resource; and

the management operating system is further configured to:

5 receive the resource reducing request message sent by the first load operating system; and

reduce the physical resource of the first load operating system according to the type identifier of the physical resource that needs to be reduced.

24. The host machine according to claim 17, wherein:

10 the first load operating system is further configured to:

monitor a physical resource of the first load operating system; and

when the first load operating system determines that utilization of the physical resource allocated by the management operating system to the first load operating system is greater than a second preset threshold, send a resource adding request message to the management
15 operating system, wherein the resource adding request message comprises a type identifier of a physical resource that needs to be added, and the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource or a physical memory resource; and

the management operating system is further configured to:

20 receive the resource adding request message sent by the first load operating system; and

add the physical resource of the first load operating system according to the type identifier of the physical resource that needs to be added.

25 25. The host machine according to claim 22 or 24, wherein if the physical resource that needs to be added is a processor core, the management operating system is specifically configured to:

mark the processor core, which needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and send a resource adding

message to the first load operating system, wherein the resource adding message comprises an identifier of the processor core that needs to be added; and

send a jump instruction to the added processor core, wherein the jump instruction is used to instruct the added processor core to execute a kernel program of the first load operating system, and the kernel program comprises all mapping relationships that are from virtual memory addresses to physical memory addresses and that are required for executing the first load operating system; and

the first load operating system is specifically configured to:

receive the resource adding message sent by the management operating system;

10 determine, according to the identifier of the processor core that needs to be added, the processor core added by the management operating system for the first load operating system; and

receive, by using the added processor core of the first load operating system, the jump instruction sent by the management operating system, execute the kernel program of the first load operating system according to the jump instruction, and read, from the kernel program, all the mapping relationships that are from the virtual memory addresses to the physical memory addresses and that are required for executing the first load operating system.

26. The host machine according to claim 22 or 24, wherein if the physical resource that needs to be added is a physical memory resource, the management operating system is specifically configured to:

mark a physical memory address, which needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and send a resource adding message to the first load operating system, wherein the resource adding message comprises an identifier of the physical memory address that needs to be added; and

25 the first load operating system is specifically configured to:

receive the resource adding message sent by the management operating system; and

determine, according to the identifier of the physical memory address that needs to be added, the physical memory address added by the management operating system for the first load operating system.

27. The host machine according to claim 22 or 23, wherein if the physical resource that
5 needs to be reduced is a processor core or a physical memory resource,

the management operating system is specifically configured to: send a resource reducing message to the first load operating system, wherein the resource reducing message comprises an identifier of the physical resource that needs to be released;

the first load operating system is specifically configured to: receive the resource
10 reducing message sent by the management operating system, and release the physical resource according to the identifier of the physical resource that needs to be released; and

the management operating system acquires the identifier of the physical resource released by the first load operating system, and adds the identifier of the released physical resource to a list of available physical resources in the resource pool.

15 28. A host machine, wherein the host machine comprises a physical resource pool and comprises a multi-kernel operating system including a management operating system and multiple load operating systems that run on the host machine, the physical resource pool comprises processor cores and a physical memory that are of the host machine, wherein the management operating system is configured to manage the multiple load operating systems,
20 which includes allocating, to the multiple load operating systems, physical resources exclusively used by the multiple load operating systems, and being responsible for startup of the load operating systems, wherein a load operating system is configured to exclusively use and access a physical resource allocated by the management operating system after the load operating system is started up, and wherein

25 the management operating system comprises:

a resource allocating module, configured to allocate, to a first load operating system, a physical resource set exclusively used by the first load operating system, wherein the physical

resource set comprises some of the processor cores and a part of the physical memory that are of the host machine, and the first load operating system is any load operating system in the multiple load operating systems;

5 a startup processor core determining module, configured to determine, in processor cores allocated to the first load operating system, a startup processor core that starts up the first load operating system; and

an instructing module, configured to send an inter-core interrupt message to the startup processor core, wherein the inter-core interrupt message instructs the startup processor core to execute an initialization program, the initialization program configured to initialize the startup processor core, wherein the initialization program is executed to read a mapping relationship, from a virtual memory address to a physical memory address, for executing a boot image of the first load operating system, and instruct the startup processor core to execute the boot image to start up the first load operating system, wherein the physical memory address comprises a location of the boot image corresponding to the first load operating system, the boot image comprises a startup parameter of the first load operating system, and the startup parameter comprises identifiers of the processor cores allocated to the first load operating system and an identifier of the physical memory address allocated to the first load operating system; and

the first load operating system comprises:

20 a mapping relationship acquiring module, configured to receive, by the startup processor core of the processor cores for the first load operating system, the inter-core interrupt message from the management operating system;

read, from the initialization program, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image of the first load operating system in a process of executing the initialization program, wherein the mapping relationship is used to enable the startup processor core of the first load operating system to access the physical memory address;

an instruction executing module, configured to jump, according to an instruction that is set by the management operating system and that is for executing a boot image jump, to the location that is of the boot image corresponding to the first load operating system and that is in the physical memory address, and execute, according to the mapping relationship, the boot
5 image corresponding to the first load operating system;

a startup parameter acquiring module, configured to acquire, in a process of executing the boot image of the first load operating system, the startup parameter of the first load operating system from the boot image of the first load operating system; and

a physical resource set acquiring module, configured to determine, according to the
10 identifiers of the processor cores and the identifier of the physical memory address of the first load operating system, the physical resource set that is allocated by the management operating system to the first load operating system and that is exclusively used by the first load operating system.

29. The host machine according to claim 28, wherein the management operating system
15 further comprises:

a mapping relationship setting module, configured to: construct the boot image for the first load operating system, and set, for the first load operating system, the mapping relationship that is from the virtual memory address to the physical memory address and that is required for executing the boot image.

20 30. The host machine according to claim 28 or 29, wherein the management operating system further comprises:

an available-processor-core acquiring module, configured to acquire available processor cores of a second load operating system before the startup processor core that starts up the first load operating system is determined in the processor cores allocated to the first load
25 operating system, wherein the second load operating system is a logged-out load operating system, other than the first load operating system, in the multiple load systems, the available

processor cores comprise a processor core that has been started up, and the physical resource set of the first load operating system comprises the available processor cores; and

the startup processor core determining module is specifically configured to: when the physical resource set of the first load operating system comprises the available processor
5 cores, determine, in the available processor cores, the startup processor core that starts up the first load operating system.

31. The host machine according to claim 28 or 29, wherein:

the instruction executing module is further configured to execute, by using the processor cores allocated to the first load operating system, a privileged instruction delivered by the
10 management operating system.

32. The host machine according to claim 28, wherein the management operating system further comprises:

a first monitoring module, configured to monitor running of the first load operating system after the startup processor core is instructed to execute the boot image pre-constructed
15 for the first load operating system; and

the resource allocating module is further configured to: when utilization of a physical resource allocated to the first load operating system is less than a first preset threshold, determine a type identifier of a physical resource that needs to be reduced for the first load operating system, and reduce the physical resource of the first load operating system
20 according to the type identifier of the physical resource that needs to be reduced; or

when utilization of a physical resource allocated to the first load operating system is greater than a second preset threshold, determine a type identifier of a physical resource that needs to be added for the first load operating system, and add the physical resource of the first load operating system according to the type identifier of the physical resource that needs
25 to be added, wherein

the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource or a physical memory resource.

33. The host machine according to claim 28, wherein the first load operating system further comprises:

a first monitoring module, configured to monitor a physical resource of the first load operating system; and

5 a first sending module, configured to: if the first load operating system determines that utilization of the physical resource allocated by the management operating system to the first load operating system is less than a first preset threshold, send, by the first load operating system, a resource reducing request message to the management operating system, wherein the resource reducing request message comprises a type identifier of a physical resource that
10 needs to be reduced, and the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource or a physical memory resource; and

the management operating system further comprises:

a first receiving module, configured to receive the resource reducing request message
15 sent by the first load operating system; and

the resource allocating module is further configured to reduce the physical resource of the first load operating system according to the type identifier of the physical resource that needs to be reduced.

34. The host machine according to claim 28, wherein the first load operating system
20 further comprises:

a second monitoring module, configured to monitor a physical resource of the first load operating system; and

a second sending module, configured to: when the first load operating system determines that utilization of the physical resource allocated by the management operating
25 system to the first load operating system is greater than a second preset threshold, send a resource adding request message to the management operating system, wherein the resource adding request message comprises a type identifier of a physical resource that needs to be

added, and the type identifier of the physical resource is used to distinguish whether the physical resource is a processor core resource or a physical memory resource; and

the management operating system further comprises:

5 a second receiving module, configured to receive the resource adding request message sent by the first load operating system; and

the resource allocating module is further configured to add the physical resource of the first load operating system according to the type identifier of the physical resource that needs to be added.

10 35. The host machine according to claim 32 or 34, wherein the resource allocating module is specifically configured to:

mark a processor core, which needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and send a resource adding message to the first load operating system, wherein the resource adding message comprises an identifier of the processor core that needs to be added; and

15 send a jump instruction to the added processor core, wherein the jump instruction is used to instruct the added processor core to execute a kernel program of the first load operating system, and the kernel program comprises all mapping relationships that are from virtual memory addresses to physical memory addresses and that are required for executing the first load operating system; and

20 the physical resource set acquiring module is further specifically configured to:

determine, according to the identifier of the processor core that needs to be added, the processor core added by the management operating system for the first load operating system; and

25 receive, by using the added processor core of the first load operating system, the jump instruction sent by the management operating system, execute the kernel program of the first load operating system according to the jump instruction, and read, from the kernel program,

all the mapping relationships that are from the virtual memory addresses to the physical memory addresses and that are required for executing the first load operating system.

36. The host machine according to claim 32 or 34, wherein if the physical resource that needs to be added is a physical memory resource,

5 the resource allocating module is specifically configured to: mark a physical memory address, which needs to be added for the first load operating system, as a physical resource that belongs to the first load operating system, and send a resource adding message to the first load operating system, wherein the resource adding message comprises an identifier of the physical memory address that needs to be added; and

10 the physical resource set acquiring module is specifically configured to: receive the resource adding message sent by the management operating system, and determine, according to the identifier of the physical memory address that needs to be added, the physical memory address added by the management operating system for the first load operating system.

37. The host machine according to claim 32 or 33, wherein if the physical resource that
15 needs to be reduced is a processor core or a physical memory resource,

the physical resource set acquiring module is specifically configured to: receive a resource reducing message sent by the management operating system, and release the physical resource according to the identifier, carried by the resource reducing message, of the physical resource that needs to be released; and

20 the resource allocating module is specifically configured to acquire the identifier of the physical resource released by the first load operating system, and add the identifier of the released physical resource to a list of available physical resources in the resource pool.

1/15




FIG. 1




FIG. 2

2/15




FIG. 3

3/15




FIG. 4

4/15




FIG. 5

5/15




FIG. 6

6/15




FIG. 7

7/15




FIG. 8A

8/15




FIG. 8B

9/15




FIG. 9A

10/15




FIG. 9B

11/15




FIG. 10A




FIG. 10B

12/15




FIG. 11




FIG. 12

13/15




FIG. 13




FIG. 14

14/15




FIG. 15




FIG. 16

15/15




FIG. 17

A management operating system allocates, to each load operating system, a physical resource set exclusively used by each load operating system, constructs a startup mirror for each load operating system, and sets, for each load operating system, a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing the startup mirror

201

The management operating system determines, in processor cores allocated to a first load operating system, a startup processor core that starts up the first load operating system

202

The management operating system instructs the startup processor core to read a mapping relationship that is from a virtual memory address to a physical memory address and that is required for executing a startup mirror of the first load operating system and is pre-established by the management operating system, and instructs the startup processor core to execute the startup mirror pre-established for the first load operating system

203