

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 April 2010 (22.04.2010)

(10) International Publication Number
WO 2010/044816 A1

(51) International Patent Classification:
A61B 17/3207 (2006.01) A61B 17/32 (2006.01)
A61B 17/22 (2006.01) A61B 19/00 (2006.01)
A61B 17/00 (2006.01) A61B 17/34 (2006.01)

(21) International Application Number:
PCT/US2009/004553

(22) International Filing Date:
7 August 2009 (07.08.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/104,868 13 October 2008 (13.10.2008) US
12/461,261 5 August 2009 (05.08.2009) US

(71) Applicant (for all designated States except US):
BRIDGEPOINT MEDICAL, INC. [US/US]; 2800
Campus Drive #50, Plymouth, MN 55441 (US).

(72) Inventors; and

(71) Applicants : OLSON, Matthew, Jonathan [US/US];
5808 32nd Avenue, Crystal, MN 55422 (US). KUGLER,
Chad, John [US/US]; 584 Halsey Avenue Se, Buffalo,
MN 55313 (US). OLSON, Ross, Arlen [US/US]; 1250
Benton Street, Anoka, MN 55303 (US). ROBINSON,
David, B. [US/US]; 25 Pleasant View Road, Chanhassen,
MN 55317 (US).

(74) Agent: GARRETT, Arthur, S.; Finnegan, Henderson,
Farabow, Garrett, & Dunner, L.L.P., 901 New York Avenue
NW, Washington, DC 20001-4413 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: ENDOVASCULAR DEVICE WITH A TISSUE PIERCING DISTAL PROBE AND ASSOCIATED METHODS




FIG. 17

(57) Abstract: Devices, systems and methods for treating diseases and disorders effecting the cardiovascular system of the human body are disclosed. An exemplary blood vessel in accordance with this disclosure comprises a shaft, tip member fixed to the shaft, and a probe extending beyond a distal surface of the tip member. In some useful embodiments, the tip member is relatively atraumatic and the probe is shaped so as to be more likely to produce trauma than the tip member.

ENDOVASCULAR DEVICE WITH A TISSUE PIERCING DISTAL PROBE AND ASSOCIATED METHODS

DESCRIPTION OF THE INVENTION

CROSS REFERENCE TO RELATED APPLICATIONS

[001] This is a continuation-in-part of Application No. 12/320,792, filed February 4, 2009, which claims the benefit of U.S. Provisional Application No. 61/063,756, filed February 5, 2008. This Application claims the right to priority based on Provisional Application No. 61/104,868, filed October 13, 2008. The contents of the above-noted applications are expressly incorporated herein by reference in their entirety.

FIELD OF THE INVENTION

[002] The inventions described herein relate to devices and associated methods for the treatment of chronic total occlusions. More particularly, the inventions described herein relate to devices and methods for crossing chronic total occlusions and establishing a pathway blood flow past the chronic total occlusions.

BACKGROUND OF THE INVENTION

[003] Due to age, high cholesterol and other contributing factors, a large percentage of the population has arterial atherosclerosis that totally occludes portions of the patient's vasculature and presents significant risks to patient health. For example, in the case of a total occlusion of a coronary artery, the result may be painful angina, loss of cardiac tissue or patient death. In another example, complete occlusion of the femoral and/or popliteal arteries in the leg may result in limb threatening ischemia and limb amputation.

[004] Commonly known endovascular devices and techniques are either inefficient (time consuming procedure), have a high risk of perforating a vessel (poor safety) or fail to cross the occlusion (poor efficacy). Physicians currently have difficulty visualizing the native vessel lumen, can not accurately direct endovascular devices toward the visualized

lumen, or fail to advance devices through the lesion. Bypass surgery is often the preferred treatment for patients with chronic total occlusions, but less invasive techniques would be preferred.

BRIEF SUMMARY

[005] Devices, systems and methods for treating diseases and disorders effecting the cardiovascular system of the human body are disclosed. An exemplary blood vessel in accordance with this disclosure comprises a shaft, tip member fixed to the shaft, and a probe extending beyond a distal surface of the tip member. In some useful embodiments, the tip member is relatively atraumatic and the probe is shaped so as to be more likely to produce trauma than the tip member.

BRIEF DESCRIPTION OF THE FIGURES

[006] Figure 1 is a somewhat stylized representation of a human heart. The heart includes a plurality of coronary arteries, all of which are susceptible to occlusion.

[007] Figure 2 is an enlarged view further illustrating a portion of the heart shown in the previous figure. In figure 2, a total occlusion is shown within a coronary artery.

[008] Figure 3 is a perspective view of a blood vessel (e.g., a coronary artery). In figure 3, the wall of the blood vessel is shown having three layers (the intima, the media, and the adventitia).

[009] Figure 4 is a lateral cross-sectional view of the artery shown in the previous figure. In figure 4, an orienting device is shown disposed between the adventitia and the intima of the artery.

[010] Figure 5 is a longitudinal cross-sectional view of an artery having an occlusion blocking the true lumen.

[011] Figure 6 is an additional cross-sectional view of the artery shown in the previous figure. In the embodiment of figure 6, a crossing device has been advanced over a guidewire so that a distal portion of crossing device is disposed in proximal segment of the true lumen.

[012] Figure 7 is a plan view showing an assembly including crossing device shown in the previous figure.

[013] Figure 8 is an additional view of an artery. In the embodiment of figure 8, the distal end of the crossing device has been advanced in a distal direction so that the tip of the crossing device is adjacent an occlusion that is blocking the true lumen of the artery.

[014] Figure 9 is an additional view of the artery and the crossing device shown in the previous figure. In the embodiment of figure 9, the distal end of the crossing device has been advanced between the intima and the adventitia of the wall of the artery.

[015] Figure 10 is an additional view of the artery shown in the previous figure. In the embodiment of figure 10, the crossing device has been withdrawn and a guidewire remains in the position formerly occupied by the crossing device.

[016] Figure 11 is an additional view of the artery and the guidewire shown in the previous figure. In the embodiment of figure 11, an orienting device 100 been advanced over the guidewire.

[017] Figure 12 is an additional view of the artery and the orienting device shown in the previous figure.

[018] Figure 13 is an enlarged partial cross-sectional view showing a portion of the orienting device shown in the previous figure. In the embodiment of figure 13, a re-entry device has been advanced into the central lumen of orienting device.

[019] Figure 14 is an additional partial cross-sectional view showing a portion of the re-entry device and the orienting device shown in figure 13. For purposes of illustration, figure 14 is enlarged and simplified relative to the items shown in figure 13.

[020] Figure 15 is an enlarged partial cross-sectional view showing a portion of the re-entry device and the orienting device shown in the previous figure. In the embodiment of figure 15, the re-entry device has been positioned so that a distal portion of the re-entry device has entered the first aperture of the orienting device.

[021] Figure 16 is an enlarged partial cross-sectional view showing a portion of a re-entry device and the intima of a blood vessel. In the embodiment of figure 16, a probe of the re-entry device is contacting the intima.

[022] Figure 17 is an enlarged partial cross-sectional view showing a portion of the re-entry device shown in the previous figure. In the embodiment of figure 17, the probe of the re-entry device has pierced the intima of the blood vessel. When this is the case, the probe may anchor the distal tip of the re-entry device to the intima. Additionally, the piercing of the intima with the probe may serve to weaken the intima.

[023] Figure 18 is an enlarged partial cross-sectional view showing a portion of the re-entry device shown in the previous figure. In the embodiment of figure 18, the distal end of the re-entry device has been advanced through the intima of a blood vessel and is disposed in the true lumen of the blood vessel.

[024] Figure 19 is a partial cross-sectional view of the re-entry device shown in the previous figure. Figure 19 has a different scale than the previous figure so that more of the surrounding context is visible in figure 19. In figure 19, the distal end of the re-entry device can be seen residing in the true lumen of the blood vessel.

[025] Figure 20 is an additional view of the blood vessel shown in the previous figure. In the embodiment of figure 20, the orienting device has been withdrawn leaving the re-entry device in the position shown in figure 20. Devices such as balloon angioplasty catheters, atherectomy catheters, and stent delivery catheters may be advanced over the re-entry device. In this way, these devices may be used in conjunction with the re-entry device to establish a blood flow path between around an occlusion in a blood vessel.

[026] Figure 21 is a partial cross-sectional view of an exemplary re-entry device.

[027] Figure 22 is a plan view of an exemplary re-entry device.

[028] Figure 23 is a partial cross-sectional view of an exemplary re-entry device.

[029] Figure 24 is a partial cross-sectional view of an exemplary re-entry device.

[030] Figure 25 is a plan view of an exemplary re-entry device.

[031] Figure 26 is a cross-sectional view of an exemplary re-entry device.

[032] Figure 27 is a cross-sectional view of an exemplary re-entry device.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

[033] The following detailed description should be read with reference to the drawings in which similar elements in different drawings are numbered the same. The drawings, which are not necessarily to scale, depict illustrative embodiments and are not intended to limit the scope of the invention.

[034] Figure 1 is a somewhat stylized representation of a human heart 50. Heart 50 includes a plurality of coronary arteries 52, all of which are susceptible to occlusion. Under certain physiological circumstances and given sufficient time, some occlusions may become total or complete, such as total occlusion 36 shown in figure 1.

[035] As used herein, the terms total occlusion and complete occlusion are intended to refer to the same or similar degree of occlusion with some possible variation in the age of the occlusion. Generally, a total occlusion refers to a vascular lumen that is ninety percent or more functionally occluded in cross-sectional area, rendering it with little to no blood flow therethrough and making it difficult or impossible to pass a conventional guide wire therethrough. Also generally, the older the total occlusion the more organized the occlusive material will be and the more fibrous and calcified it will become. According to one accepted clinical definition, a total occlusion is considered chronic if it is greater than two weeks old from symptom onset.

[036] Figure 2 is an enlarged view further illustrating a portion of heart 50 shown in the previous figure. In figure 2, a total occlusion 36 is shown within a coronary artery 52. Generally, the proximal segment 32 of artery 52 (i.e., the portion of artery 52 proximal of total occlusion 36) has adequate blood flow to supply the surrounding cardiac muscle and may be easily accessed using endovascular devices. In contrast, the distal segment 34 of artery 52 (i.e., the portion of artery 52 distal of total occlusion 36) is not easily accessed with interventional devices. Additionally, distal segment 34 has significantly reduced blood flow as compared to proximal segment 32.

[037] Figure 3 is a perspective view of an artery 20 having a wall 22. In figure 3, wall 22 of artery 20 is shown having three layers. The outermost layer of wall 22 is the adventitia 24 and the innermost layer of wall 22 is the intima 26. Intima 26 defines a true lumen 30 of artery 20. The tissues extending between intima 26 and adventitia 24 may be collectively referred to as the media 28. For purposes of illustration, intima 26, media 28 and adventitia 24 are each shown as a single homogenous layer in figure 3. In the human body, however, the intima and the media each comprise a number of sub-layers. The transition between the external most portion of the intima and the internal most portion of the media is sometimes referred to as the subintimal space 40.

[038] With reference to figure 3, it will be appreciated that the subintimal space 40 has a generally annular shape with its radial center at the center of the true lumen. Some of the devices and methods discussed in this detailed description may take advantage of the position and geometry of the subintimal space 40 relative to the true lumen of the blood vessel. For example, some orienting devices described herein may be adapted to orient themselves within that space. Once the orientation of the orienting device is established, the orienting device may be used to direct a re-entry device toward the true lumen.

[039] Figure 4 is a lateral cross-sectional view of artery 20 shown in the previous figure. In figure 4, an orienting device 100 is shown disposed between adventitia 24 and intima 26 of artery 20. Orienting device 100 comprises a distal shaft 102 having an outer wall 128 defining a central lumen 104. Orienting device 100 comprises an orienting element 120 that is coupled to distal shaft 102.

[040] In the embodiment of figure 4, orienting element 120 comprises an inflatable member 126. The top of inflatable member 126 may be fixed to distal shaft 102, for example, at a first interface 190A. The bottom of inflatable member 126 may be fixed to distal shaft 102, for example, at a second interface 190B.

[041] Orienting element 120 comprises a first portion 106 and a second portion 108. First portion 106 of orienting element 120 extends in a first direction away from distal shaft 102. Second portion 108 of orienting element 120 extends away from distal shaft 102 in a second direction that is generally opposite the first direction.

[042] Distal shaft 102 defines a first aperture 130 and a second aperture 132. First aperture 130 extends in a third direction through distal shaft 102. Second aperture 132 extends through distal shaft 102 in a forth direction that is generally opposite the third direction. First aperture 130 and second aperture 132 are generally oriented at a right angle to a tangent plane TP. In figure 4, tangent plane TP is tangent to subintimal space 40.

[043] When inflatable member 126 is inflated, the number of directions that first aperture 130 and second aperture 132 may be facing is reduced. This may be conceptualized in terms of degrees of freedom. When inflatable member 126 of orienting element 120 is inflated, the number of directions that an aperture may be facing is reduced from 360 degrees of freedom to two degrees of freedom, 180 degrees apart.

[044] When inflatable member 126 of orienting element 120 is inflated between adventitia 24 and intima 26 of artery 20 orienting device 100 will orient itself within artery 20 so that either first aperture 130 or second aperture 132 opens toward a true lumen 30 of artery 20. In the embodiment of figure 4, orienting device 100 has been positioned so that first aperture 130 opens toward intima 26 of artery 20 and second aperture 132 opens toward adventitia 24. In figure 4, a re-entry device 180 is shown extending through first aperture 130 and intima 26. A distal end of re-entry device 180 is disposed in true lumen 30 of blood vessel 20. Orienting device 100 and re-entry device 180 may be used to establish fluid communication between a proximal segment and a distal segment that are separated by

an occlusion. Exemplary methods for establishing this fluid communication will be described below.

[045] Figure 5 is a longitudinal cross-sectional view of an artery 20 having an occlusion 36 blocking true lumen 30 thereof. Occlusion 36 divides true lumen 30 into a proximal segment 32 and a distal segment 34. In figure 5, a distal portion of a guidewire 60 is shown extending into proximal segment 32 of true lumen 30. The methods described in this document may include the step of advancing a guidewire to a location proximate an occlusion in a blood vessel. The exemplary methods described in this document may also include the step of advancing guidewire 60 between occlusion 36 and adventitia 24 of wall 22. In some cases, however, the nature of the occlusion and the blood vessel will be such that the guidewire is unlikely to advance beyond the occlusion. When this is the case, the guidewire may be used to guide additional endovascular devices to a location proximate occlusion 36.

[046] Figure 6 is an additional cross-sectional view of artery 20 shown in the previous figure. In the embodiment of figure 6, a crossing device 70 has been advanced over guidewire 60 so that a distal portion of crossing device 70 is disposed in proximal segment 32 of true lumen 30. Crossing device 70 of figure 6 comprises a tip 74 that is fixed to a distal end of a shaft 72. Crossing device 70 may be used in conjunction with a method for establishing a channel between proximal segment 32 and distal segment 34. The methods described in this document may include the step of advancing a crossing device over a guidewire.

[047] In some useful methods in accordance with the present disclosure, crossing device 70 may be rotated about its longitudinal axis and moved in a direction parallel to its longitudinal axis simultaneously. When this is the case, rotation of crossing device 70 may reduce resistance to the axial advancement of crossing device 70. These methods take advantage of the fact that the kinetic coefficient of friction is usually less than the static coefficient of friction for a given frictional interface. Rotating crossing device 70 assures that the coefficient of friction at the interface between the crossing device and the surround tissue will be a kinetic coefficient of friction and not a static coefficient of friction.

[048] Figure 7 is a plan view showing an assembly including crossing device 70 shown in the previous figure. In the embodiment of figure 7, a handle assembly 76 is coupled to crossing device 70. In figure 7, handle assembly 76 is shown disposed about a proximal portion of a shaft 152 of crossing device 70. In figure 7, a portion of handle

assembly 76 is positioned between the thumb and forefinger of a left hand LH. A second portion of handle assembly 76 is disposed between the thumb and forefinger of a right hand RH. With reference to figure 7, it will be appreciated that handle assembly 76 is long enough to receive the thumb and forefingers of a physician's right and left hands. When this is the case, a physician can use two hands to rotate handle assembly 76.

[049] Rotation of crossing device 70 can be achieved by rolling handle assembly 76 between the thumb and forefinger of one hand. Two hands may also be used to rotate handle assembly 76 as shown in figure 7. In some useful methods, crossing device 70 can be rotated and axially advanced simultaneously.

[050] In some useful methods in accordance with the present disclosure, crossing device 70 is rotated at a rotational speed of between about 2 revolutions per minute and about 200 revolutions per minute. In some particularly useful methods in accordance with the present disclosure, crossing device 70 is rotated at a rotational speed of between about 50 revolutions per minute and about 150 revolutions per minute.

[051] Crossing device 70 may be rotated by hand as depicted in figure 7. It is also contemplated that a mechanical device (e.g., an electric motor) may be used to rotate crossing device 70. Rotating crossing device 70 assures that the coefficient of friction at the interface between the crossing device and the surround tissue will be a kinetic coefficient of friction and not a static coefficient of friction.

[052] Figure 8 is an additional longitudinal cross-sectional view of artery 20. In the embodiment of figure 8, the distal end of crossing device 70 has been advanced in a distal direction so that tip 74 is adjacent occlusion 36. With reference to figure 8, it will be appreciated that tip 74 has passed beyond intima 26 and is disposed between occlusion 36 and adventitia 24 of artery 20. Some methods described in this document may include the step of advancing a crossing device between an occlusion and the adventitia of an artery.

[053] Figure 9 is an additional view of artery 20 and crossing device 70 shown in the previous figure. In the embodiment of figure 9, the distal end of crossing device 70 has been advanced in an axial direction past occlusion 36. Methods described herein may include the step of advancing a crossing device beyond an occlusion. In the embodiment of figure 9, crossing device has crossed occlusion 36 by advancing between occlusion 36 and adventitia 24 of wall 22.

[054] It is to be appreciated that other methods of crossing an occlusion are within the spirit and scope of this disclosure. For example, the crossing device 70 may pass

through occlusion 36 while remaining disposed inside true lumen 30. In figure 9, tip 74 of crossing device 70 is shown residing between intima 26 and adventitia 24 of artery 20. As tip 74 moves in an axial direction between intima 26 and adventitia 24, tip 74 may cause blunt dissection of the layers forming wall 22 of artery 20. Alternatively, tip 74 may cause blunt dissection of the materials comprising the occlusion 36.

[055] In the embodiment of figure 9, tip 74 of crossing device 70 is disposed between intima 26 and adventitia 24. When this is the case, fluid communication between proximal segment 32 and distal segment 34 may be achieved by creating an opening through intima 26. Such an opening may be created, for example, using a re-entry device and an orienting device that directs the advancement of the re-entry device toward intima 26.

[056] Figure 10 is an additional view of artery 20 shown in the previous figure. In the embodiment of figure 10, crossing device 70 has been withdrawn from true lumen 30 of artery 20. With reference to figure 10, it will be appreciated that guidewire 60 remains in the position formerly occupied by crossing device 70.

[057] The position of guidewire 60 shown in figure 10 may be achieved using crossing device 70. Guidewire 60 may be positioned, for example, by first placing crossing device 70 in the position shown in the previous figure, then advancing guidewire 60 through lumen 122 defined by shaft 72 of crossing device 70. Alternately, guidewire 60 may be disposed within lumen 122 while crossing device 70 is advanced beyond occlusion 36.

[058] With guidewire 60 in the position shown in figure 10, guidewire 60 may be used to direct other devices between occlusion 36 and adventitia 24. For example, a catheter may be advanced over guidewire 60 until the distal end of the catheter extends between an occlusion and the adventitia. After reaching this location, the catheter may be used to dilate the tissue surrounding the catheter. Examples of catheters that may be used to dilate tissue include balloon angioplasty catheters, atherectomy catheters, and stent delivery catheters.

[059] Figure 11 is an additional view of artery 20 and guidewire 60 shown in the previous figure. In the embodiment of figure 11, an orienting device 100 has been advanced over guidewire 60. Orienting device 100 includes a distal shaft 102 comprising a outer wall 128 defining a central lumen 104. A first aperture 130 and a second aperture 132 are also defined by outer wall 128. In the embodiment of figure 11, first aperture 130 and second aperture 132 are both in fluid communication with central lumen 104.

[060] In the embodiment of figure 11, orienting device 100 has been positioned so that first aperture 130 opens toward intima 26 of artery 20 and second aperture 132 opens toward adventitia 24. In the embodiment of figure 11, first aperture 130 and second aperture 132 are longitudinally separated from one another. Orienting device 100 includes a first radiopaque marker that is located between first aperture 130 and second aperture 132. A second radiopaque marker of orienting device 100 is located distally of second aperture 132.

[061] Figure 12 is an additional view of artery 20 and orienting device 100 shown in the previous figure. In the embodiment of figure 12, guidewire 60 has been withdrawn leaving orienting device 100 in the position shown in figure 12. With reference to figure 12, it will be appreciated that orienting device 100 extends beyond occlusion 36. In figure 12, occlusion 36 is shown blocking true lumen 30. Occlusion 36 divides true lumen 30 into a proximal segment 32 and a distal segment 34. When an orienting device in accordance with some embodiments disclosed herein is advanced between the adventitia and the intima of an artery, the orienting device may be used to direct a re-entry device toward true lumen 30. Fluid communication between proximal segment 32 and distal segment 34 may be achieved by re-entering the true lumen with a re-entry device.

[062] Figure 13 is an enlarged partial cross-sectional view showing a portion of orienting device 100 shown in the previous figure. In the embodiment of figure 13, a re-entry device 180 has been advanced into central lumen 104 of orienting device 100. With reference to figure 13, it will be appreciated that re-entry device 180 includes a bend 134 near distal end 136 of re-entry device 180.

[063] Figure 14 is an additional partial cross-sectional view showing a portion of re-entry device 180 and orienting device 100. For purposes of illustration, figure 14 is enlarged and simplified relative to the items shown in the previous figure. In the embodiment of figure 14, re-entry device 180 is biased to assume a bent shape including a bend 134. Also in the embodiment of figure 14, distal shaft 102 of orienting device 100 is holding re-entry device 180 in a somewhat compressed state. When this is the case, re-entry device 180 can be inserted through first aperture 130 by positioning distal end 136 over first aperture 130 and allowing bend 134 to assume its natural state (i.e., bent at a sharper angle). Re-entry device 180 can be inserted through first aperture 130 until it comes into contact with intima 26.

[064] In the embodiment of figure 14, distal end 136 of re-entry device 180 is axially aligned with first aperture 130, however, bend 134 is causing distal end 136 to point away from first aperture 130. When this is the case, distal end 136 may be positioned over first aperture 130 by rotating re-entry device 180 central lumen 104 of orienting device 100.

[065] Figure 15 is an enlarged partial cross-sectional view showing a portion of re-entry device 180 and orienting device 100 shown in the previous figure. In the embodiment of figure 15, re-entry device 180 has been positioned so that a distal portion of re-entry device 180 has entered first aperture 130. Intima 26 is shown below first aperture 130 in figure 15.

[066] Figure 16 is an enlarged partial cross-sectional view showing a portion of re-entry device 180 and intima 26. In figure 16, re-entry device 180 is shown extending through central lumen 104 and first aperture 130. With reference to figure 16, it will be appreciated that re-entry device 180 comprises a distal surface 144 and a probe 146 extending beyond distal surface 144. In the embodiment of figure 16, probe 146 of re-entry device 180 is contacting intima 26.

[067] Figure 17 is an enlarged partial cross-sectional view showing a portion of re-entry device 180. In the embodiment of figure 17, probe 146 of re-entry device 180 has pierced intima 26. When this is the case, probe 146 may anchor the distal tip of re-entry device 180 to intima 26. Additionally, the piercing of intima 26 with probe 146 may serve to weaken intima 26.

[068] Figure 18 is an enlarged partial cross-sectional view showing a portion of re-entry device 180. In the embodiment of figure 18, the distal end 136 of re-entry device 180 has been advanced through intima 26. With reference to figure 18, it will be appreciated that distal end 136 of re-entry device 180 is disposed in true lumen 30 defined by intima 26.

[069] Figure 19 is a partial cross-sectional view of re-entry device 180 shown in the previous figure. Figure 19 has a different scale than the previous figure so that more of the surrounding context is visible in figure 19. In figure 19, distal end 136 of re-entry device 180 can be seen residing in true lumen 30.

[070] Figure 20 is an additional view of artery 20 shown in the previous figure. In the embodiment of figure 20, orienting device 100 has been withdrawn leaving re-entry device 180 in the position shown in figure 20. Devices such as balloon angioplasty catheters, atherectomy catheters, and stent delivery catheters may be advanced over re-entry device 180. In this way, these devices may be used in conjunction with re-entry device 180

to establish a blood flow path between proximal segment 32 of true lumen 30 and distal segment 34 of true lumen 30. This path allows blood to flow around occlusion 36.

[071] Figure 21 is a partial cross-sectional view of an exemplary re-entry device 280 in accordance with the present detailed description. Re-entry device 280 comprises a tip member 242 that is fixed to a shaft 240 and a coil 248 that is disposed about a distal portion of the shaft 240. Shaft 240 comprises a proximal segment 250 that extends between a proximal end PE and a first tapered segment 252. In the embodiment of figure 21, coil 248 extends between first tapered segment 252 and tip member 242.

[072] A first intermediate segment 262 of shaft 240 extends between first tapered segment 252 and a second tapered segment 254. A second intermediate segment 264 of shaft 240 extends between second tapered segment 254 and a third tapered segment 256. A distal segment 260 of shaft 240 extends between third tapered segment 256 and tip member 242. With reference to figure 21, it will be appreciated that tip member 242 is fixed to distal segment 260 of shaft 240. In the embodiment of figure 21, a probe 246 of re-entry device 280 extends distally beyond a distal surface 244 of tip member 242.

[073] Figure 22 is a plan view of an exemplary re-entry device 380 in accordance with the present detailed description. Re-entry device 380 comprises a tip member 342 having a distal surface 344. In the embodiment of figure 22, distal surface 344 of tip member has a generally convex shape. In some cases, tip member 342 may have a generally hemispherical shape. A probe 346 of re-entry device 380 extends distally beyond distal surface 344. Probe 346 terminates at a distal face 358. In figure 22, distal face 358 is shown as a straight line representing a substantially flat surface. With reference to figure 22, it will be appreciated that distal face 358 is substantially perpendicular to the longitudinal axis of probe 346.

[074] A number of exemplary dimensions associated with probe 346 are illustrated in figure 22. In the embodiment of Figure 22, probe 346 extends beyond distal surface 344 of tip member 342 by a distance L. Also in the embodiment of Figure 22, probe 346 has a diameter DA and tip member 342 has a diameter DB. With reference to Figure 22, it will be appreciated that diameter DB of tip member 342 is generally greater than diameter DA of probe 346.

[075] In some useful embodiments, diameter DA of probe 346 is between about 0.0020 inches and about 0.0055 inches. In some useful embodiments, diameter DB of tip member 342 is between about 0.008 inches and about 0.035 inches. In some useful

embodiments, length L of probe 346 is between about 0.003 inches and about 0.032 inches. In figure 22, a coil 348 is shown extending between tip member 342 and a first tapered segment 352. Shaft 340 comprises a proximal segment 350 that extends between a proximal end PE and a first tapered segment 352.

[076] Figure 23 is a partial cross-sectional view of an exemplary re-entry device 480 in accordance with the present detailed description. Re-entry device 480 comprises a tip member 442 that is fixed to a distal segment 460 of a shaft 440. In the embodiment of figure 23, tip member 442 comprises a distal surface 444 and a probe 446 extending distally beyond distal surface 444. In the embodiment of figure 23, distal surface 444 of tip member has a generally hemispherical shape and probe 446 has a generally cylindrical shape terminating at a flat distal face 458. With reference to figure 23, it will be appreciated that distal face 458 is substantially perpendicular to the longitudinal axis of probe 446.

[077] Various processes may be used to fabricate a tip member having a shape similar to tip member 442 shown in figure 23. A tip member may be formed, for example, using various manufacturing processes such as, for example, casting and molding. A tip member may also be fabricated by a manufacturing process comprising removing material from a piece of stock material to produce a desired profile. Examples of processes that may be used to remove material from a piece of stock material include grinding and machining (e.g., turning on a lathe).

[078] In the embodiment of Figure 23, probe 446 extends beyond distal surface 444 of tip member 442 by a distance L. Also in the embodiment of Figure 23, probe 446 has a diameter DA and tip member 442 has a diameter DB. In some useful embodiments, the these dimensions fall with the numerical ranges mentioned in the detailed description of figure 22.

[079] Figure 24 is a partial cross-sectional view of an exemplary re-entry device 580 in accordance with the present detailed description. Re-entry device 580 comprises a shaft 540 and a tip member 542 that is fixed to a distal segment 560 of shaft 540. A probe 546 of re-entry device 580 extends distally beyond a distal surface 544 of tip member 542. In the embodiment of figure 24, probe 546 comprises a portion of distal segment 560 that extends beyond distal surface 544. A coil 548 of re-entry device 580 extends between tip member 542 and a first tapered segment 552 of shaft 540. Coil 548 is fixed to first tapered section 552 at a joint 566. Joint 566 and tip member 542 may comprise, for example, silver

(e.g., silver solder and/or silver braze). Joint 566 and tip member 542 may be formed using various manufacturing processes (e.g., soldering, brazing, and welding).

[080] In the embodiment of Figure 24, distal segment 560 of shaft 540 terminates at a substantially flat distal face 558. Probe 546 comprises a portion of distal segment 560 that extends beyond distal surface 544 of tip member 542 by a distance L. Also in the embodiment of Figure 24, probe 546 has a diameter DA and tip member 542 has a diameter DB. In some useful embodiments, the these dimensions fall with the numerical ranges mentioned in the detailed description of figure 22.

[081] Figure 25 is a plan view of an exemplary re-entry device 680 in accordance with the present detailed description. Re-entry device 680 comprises a tip member 642 having a distal surface 644. In the embodiment of figure 25, distal surface 644 of tip member has a generally convex shape. In some cases, tip member 642 may have a generally hemispherical shape. A probe 646 of re-entry device 680 extends distally beyond distal surface 644. Probe 646 terminates at a distal face 658. In figure 25, distal face 658 is shown as a straight line representing a substantially flat surface.

[082] In figure 25, re-entry device 600 is shown being bent at an angle A. Accordingly, it can be said that re-entry device 600 includes a bend 630. In some useful embodiments of re-entry device 600, angle A is between about 90 degrees and about 180 degrees. In some particularly useful embodiments of re-entry device 600, angle A is between about 120 degrees and about 150 degrees. Re-entry device 680 has a distal leg 668 disposed distally of bend 634 and a proximal leg 670 disposed proximally of bend 634.

[083] Figure 26 is a cross-sectional view of an exemplary re-entry device 780 in accordance with the present detailed description. Re-entry device 780 comprises a core wire 772 and a jacket 774 that is disposed about a portion of core wire 772. Jacket 774 terminates at a distal surface 744. A probe 746 of re-entry device 780 extends distally beyond distal surface 744. In the embodiment of figure 26, probe 746 comprises a distal segment 760 of core wire 772.

[084] Figure 27 is a cross-sectional view of an exemplary re-entry device 780 in accordance with the present detailed description. Re-entry device 780 comprises a core wire 772 and a jacket 774 that is disposed about a portion of core wire 772. With reference to Figure 27, it will be appreciated that re-entry device 780 includes a bend 734 near its distal end. Re-entry device 780 has a distal leg 768 disposed distally of bend 734 and a proximal leg 770 disposed proximally of bend 734. Distal leg 768 and proximal leg 770

define an angle A. In some useful embodiments of re-entry device 700, angle A is between about 90 degrees and about 180 degrees. In some particularly useful embodiments of re-entry device 700, angle A is between about 120 degrees and about 150 degrees. Jacket 774 of re-entry device 780 terminates at a distal surface 744. A probe 746 of re-entry device 780 extends distally beyond distal surface 744. In the embodiment of figure 27, probe 746 comprises a distal segment 760 of core wire 772.

[085] From the foregoing, it will be apparent to those skilled in the art that the present invention provides, in exemplary non-limiting embodiments, devices and methods for the treatment of chronic total occlusions. Further, those skilled in the art will recognize that the present invention may be manifested in a variety of forms other than the specific embodiments described and contemplated herein. Accordingly, departures in form and detail may be made without departing from the scope and spirit of the present invention as described in the appended claims.

CLAIMS

What is claimed is:

1. A device, comprising:
a shaft;
a tip member fixed to the shaft; and
the tip member including a probe extending beyond a distal surface of the tip member.

2. A device, comprising:
a shaft;
a tip member fixed to the shaft; and
wherein a distal portion of the shaft extends beyond a distal surface of the tip member.

3. The device of claim 2, wherein the distal portion of the shaft extends beyond the tip member by a distance that is greater than about 0.003 inches and less than about 0.012 inches.

4. The device of claim 3, wherein the distal portion of the shaft extends beyond the tip member by a distance that is greater than about 0.004 inches and less than about 0.008 inches.

5. The device of claim 2, wherein the distal portion of the shaft has a diameter that is greater than about 0.002 inches and less than about 0.006 inches.

6. The device of claim 2, wherein the distal portion of the shaft has an aspect ratio of length to diameter that is greater than about 1.

7. The device of claim 6, wherein the distal portion of the shaft has an aspect ratio of length to diameter that is greater than about 2.

8. The device of claim 2, wherein:

the distal portion of the shaft has a maximum diameter DW;
the tip member has a maximum diameter DT; and
the maximum diameter DT is greater than the maximum diameter DW of the distal portion of the shaft.

9. The device of claim 8, wherein a ratio of the maximum diameter DT of the tip member to the maximum diameter DW of the distal portion of the shaft is greater than about 3.

10. The device of claim 2, wherein the shaft comprises a proximal leg, a distal leg, and a bend disposed between the proximal leg and a distal leg.

11. The device of claim 10, wherein the bend extends through an angular range that is greater than about 90 degrees and less than about 180 degrees.

12. The device of claim 11, wherein the bend extends through an angular range that is greater than about 120 degrees and less than about 150 degrees.

13. The device of claim 10, wherein the distal leg has a length that is greater than about 0.040 inch and less than about 0.300 inch.

14. The device of claim 2, further comprising a coil having a proximal end fixed to the shaft and a distal end fixed to the tip member.

15. The device of claim 2, wherein the tip member comprises a metal.

16. The device of claim 15, wherein the metal comprises silver.

17. A device, comprising:
a shaft;
a tip member fixed to the shaft; and
a probe extending beyond a distal surface of the tip member.

18. The device of claim 17, wherein the distal probe and the tip member are monolithic.

19. The device of claim 17, wherein the distal probe and the tip member are both formed from a single piece of material.

20. The device of claim 17, wherein the distal probe and the tip member are both formed by removing material from a single piece of material.

21. The device of claim 17, wherein the distal probe is formed by removing material from a single piece of material.

22. The device of claim 17, wherein the distal probe and the tip member are integrally formed from a single material.

23. A medical device, comprising:

a shaft;

a tip connected to a distal end of the shaft, the tip having a generally convex distal surface with a maximum tip diameter; and

a probe extending from the distal surface of the tip, the probe having a maximum probe diameter less than a length of the probe and less than the maximum tip diameter.

24. The medical device of claim 23, wherein the probe has a generally cylindrical shape.

25. The medical device of claim 23, wherein the probe has a substantially flat distal face.

26. The medical device of claim 25, wherein the substantially flat distal face is substantially perpendicular to a longitudinal axis of the shaft.

27. The medical device of claim 23, wherein the maximum tip diameter is between about 0.008 inches and about 0.035 inches, and the maximum probe diameter is between about 0.0020 inches and about 0.0055 inches.

28. The medical device of claim 23, wherein the probe extends distally from the generally convex distal surface between about 0.003 inches and about 0.032 inches.

29. The medical device of claim 23, wherein the probe is configured to pierce tissue.

30. The medical device of claim 23, wherein the tip and the probe are integrally formed from a single piece of material.

31. The medical device of claim 23, wherein the shaft extends through the tip, and the probe is a distalmost portion of the shaft.

32. The medical device of claim 23, wherein the shaft terminates within the tip.

33. The medical device of claim 23, further comprising a coil having a proximal end attached to the shaft and a distal end attached to the tip.

34. The medical device of claim 23, wherein the shaft includes a plurality of tapered segments.

35. The medical device of claim 23, wherein the tip has a generally hemispherical shape.

36. The medical device of claim 23, wherein the shaft includes a bend proximate the distal end of the shaft.

37. A medical device, comprising:
a core wire;

a jacket surrounding at least a portion of the core wire, the jacket having a generally convex distal surface with a maximum tip diameter; and

a probe extending from the distal surface of the jacket, the probe having a maximum probe diameter less than a length of the probe and less than the maximum tip diameter.

38. The medical device of claim 37, wherein the probe has a generally cylindrical shape.

39. The medical device of claim 37, wherein the probe has a substantially flat distal face.

40. The medical device of claim 39, wherein the substantially flat distal face is substantially perpendicular to a longitudinal axis of the core wire.

41. The medical device of claim 37, wherein the probe is configured to pierce tissue.

42. The medical device of claim 37, wherein the probe and the core wire are integrally formed from a single piece of material.

43. The medical device of claim 37, wherein the core wire includes a bend proximate a distal end of the core wire.

44. The medical device of claim 37, wherein the jacket surrounds the entire core wire.

FIG. 1






FIG. 2








FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17





FIG. 19






FIG. 20




FIG. 21






FIG. 22








FIG. 25




FIG. 26




FIG. 27

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2009/004553

A. CLASSIFICATION OF SUBJECT MATTER

INV. A61B17/3207

ADD. A61B17/22

A61B17/00

A61B17/32

A61B19/00

A61B17/34

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2003/028200 A1 (BERG TODD ALLEN [US] ET AL) 6 February 2003 (2003-02-06) paragraph [0089] - paragraph [0091]; figures 18,19 -----	1-44
X	US 2006/135984 A1 (KRAMER THOMAS [US] ET AL) 22 June 2006 (2006-06-22) paragraph [0160] - paragraph [0161]; figures 4a-j,7a-9b paragraph [0164] paragraph [0178] - paragraph [0179] paragraph [0194] - paragraph [0198] -----	1-44
X	US 2004/158143 A1 (FLAHERTY J CHRISTOPHER [US] ET AL) 12 August 2004 (2004-08-12) paragraph [0060]; figure 1 ----- -/-	1-44

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

4 November 2009

Date of mailing of the international search report

11/11/2009

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Moers, Roelof

INTERNATIONAL SEARCH REPORT

International application No PCT/US2009/004553

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2007/083220 A1 (SHAMAY NOAM [IL]) 12 April 2007 (2007-04-12) paragraph [0077] – paragraph [0078]; figures 18,19 paragraph [0190]; figure 26 -----	1-44
X	US 6 569 129 B1 (HOLMES JR DAVID R [US] ET AL) 27 May 2003 (2003-05-27) abstract; figures 13,14 -----	1,2,17
E	WO 2009/100129 A (KUGLER CHAD JOHN [US]; OLSON MATTHEW JONATHAN [US]; OLSON ROSS ARLEN []) 13 August 2009 (2009-08-13) paragraph [0067]; figure 12 -----	1,2,17, 23

INTERNATIONAL SEARCH REPORT
Information on patent family members
International application No
PCT/US2009/004553

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
US 2003028200	A1 06-02-2003	AT 296590 T		15-06-2005
		AU 1609200 A		29-05-2000
		DE 69925627 D1		07-07-2005
		DE 69925627 T2		27-10-2005
		EP 1126796 A1		29-08-2001
		WO 0027312 A1		18-05-2000
		US 6475222 B1		05-11-2002
		US 2002188302 A1		12-12-2002
US 2006135984	A1 22-06-2006	NONE		
US 2004158143	A1 12-08-2004	NONE		
US 2007083220	A1 12-04-2007	AU 2005251558 A1		22-12-2005
		CA 2563827 A1		22-12-2005
		CN 101262903 A		10-09-2008
		EP 1753500 A2		21-02-2007
		WO 2005120628 A2		22-12-2005
		JP 2008504940 T		21-02-2008
		ZA 200608501 A		30-04-2008
US 6569129	B1 27-05-2003	US 2007270740 A1		22-11-2007
WO 2009100129	A 13-08-2009	US 2009209910 A1		20-08-2009