



(51) International Patent Classification:

H04L 29/08 (2006.01) *G05B 23/02* (2006.01)

(21) International Application Number:

PCT/US2019/059088

(22) International Filing Date:

31 October 2019 (31.10.2019)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/791,878	13 January 2019 (13.01.2019)	US
62/827,166	31 March 2019 (31.03.2019)	US
62/869,011	30 June 2019 (30.06.2019)	US
62/914,998	14 October 2019 (14.10.2019)	US

(71) Applicant: **STRONG FORCE IOT PORTFOLIO 2016, LLC** [US/US]; Suite F-125, 2500 Broadway, Santa Monica, California 90404 (US).

(72) Inventors: **CELLA, Charles**; 34 Old West Elm, Pembroke, Massachusetts 02358 (US). **EL-TAHRY, Teymour**; Floor 3, 1570 Woodward Avenue, Detroit, Michigan 48226 (US). **SPITZ, Richard**; Suite F-125, 2500 Broadway, Santa

Monica, California 90404 (US). **MCGUCKIN, Jeffrey P.**; 100 Geiger Road, Philadelphia, Pennsylvania 19115 (US). **DUFFY, JR., Gerald William**; 100 Geiger Road, Philadelphia, Pennsylvania 19115 (US).

(74) Agent: **SCHALDENBRAND, Michael A.**; RMCK Law Group PLC, P.O. Box 210280, Auburn Hills, Michigan 48321 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,

(54) Title: METHODS, SYSTEMS, KITS AND APPARATUSES FOR MONITORING AND MANAGING INDUSTRIAL SETTINGS




FIG. 1

(57) Abstract: A variety of kits are provided that are configured with components, systems and methods for monitoring various industrial settings, including kits with self-configuring sensor networks, communication gateways, and automatically configured back end systems.



TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

**METHODS, SYSTEMS, KITS AND APPARATUSES
FOR MONITORING AND MANAGING INDUSTRIAL SETTINGS**

CROSS-REFERENCE TO RELATED APPLICATIONS

5 [0001] This application claims priority to U.S. Provisional Patent Application number 62/791,878 filed on January 13, 2019, U.S. Provisional Patent Application number 62/827,166 filed on March 31, 2019, U.S. Provisional Patent Application number 62/869,011 filed on June 30, 2019, and U.S. Provisional Patent Application number 62/914,998 filed on October 14, 2019, each entitled
10 METHODS, SYSTEMS, KITS, AND APPARATUSES FOR MONITORING INDUSTRIAL SETTINGS. Each of the above-identified applications is hereby incorporated by reference in its entirety as if fully set forth herein.

FIELD

15 [0002] The present disclosure relates to various configurations of Internet of Things (IoT) systems in conveniently deployed kits that monitor or manage industrial settings using various configurations of sensors, edge computing devices, networking systems, and artificial intelligence.

BACKGROUND

20 [0003] The Internet of Things (IoT) is a network of connected devices, systems, components, services, programs, vehicles, appliances, machines, and other electronic items that communicate via a set of communication networks and communication interfaces and protocols. While much of the development in the IoT space has centered on consumer products, such as wearable devices, home monitoring systems, smart appliances, and the like, there are many industrial applications for IoT devices and systems, including embodiments described throughout this disclosure and in
25 the documents incorporated herein. For example, IoT sensors can be used to monitor industrial facilities, such as factories, refineries, oil and gas fields, manufacturing lines, energy production facilities, mining environments, and the like, as well as the many machines and systems disposed in such environments. While machines may include embedded sensors and instrumentation, such as onboard diagnostic systems, many machines do not have such embedded sensors, and others
30 only have a limited set of sensors; accordingly, a need and an opportunity exist for vastly more data collection, such as via the location (which may be temporary (such as with portable or mobile data collectors as described in documents incorporated by reference, or by drones, autonomous vehicles, or the like), semi-permanent (such as with modular interfaces for convenient connection and disconnection), or permanent) of large numbers of heterogeneous sensors of various types on,
35 in or around machines in industrial environments.

[0004] There are a number of issues, however, that arise in the Industrial IoT setting. For example, while many industrial IoT devices may be configured to communicate using cellular protocols, such as the 3G, 4G, LTE or 5G communication protocols, those protocols may not be natively well suited for communication in the industrial setting, as heavy machinery and thick dense structures may adversely affect communication between devices. Wi-Fi systems may also provide network connections within facilities; however, Wi-Fi systems may also experience challenges due to the adverse physical environments involved in industrial settings. For example, Wi-Fi systems are not typically well designed to communicate through obstructions, such as slabs of concrete or brick. Also, many devices in an industrial setting may be mobile, such that Wi-Fi and cellular systems have difficulty resolving which devices are communicating at a given time.

[0005] Another issue that may arise is related to bandwidth. As hundreds or thousands of sensors may be placed in an area to be monitored (e.g., factory, assembly line, oil field, etc.), and those sensors may capture multiple readings every second, the amount of data that is being collected may put a strain on the computing resources of even the most robust computing systems. A need exists for methods and systems that address challenges of efficient and effective bandwidth utilization.

[0006] Another issue is security. IoT devices can be perceived as security risks when the devices are connected to computer networks, such as ones used to operate mission critical machines. IoT devices have historically experienced security vulnerabilities and have frequently been points of attack on networks and devices.

[0007] Concerns about bandwidth, reliability, latency and/or security may deter organizations from integrating IoT sensor systems into their industrial environments and computer networks. A need exists for systems that provide the benefits of the IoT while addressing networking needs and security risks.

[0008] Another challenge for organizations considering IoT deployments is that such deployments require sophisticated integration of IoT devices with networking systems and with platforms (e.g., cloud platforms) where analysis of IoT-collected data is performed and where both human and automated controls are provided for industrial settings. Organizations may lack the range of expertise or available staff to undertake effective IoT integrations. A need exists for simplified deployment systems that offer the benefits of the IoT.

30

SUMMARY

[0009] Provided herein are methods and systems for monitoring and managing industrial settings, including through a variety of configurable kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring and managing industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security. The practical

35

implementation of an IoT solution may include a set of components that may comprise an appropriate set of sensors each configured for various respective industrial settings, a set of communication devices, a set of edge computing devices and a set of communication capabilities (including various protocols, ports, gateways, connectors, interfaces and the like) that collectively
5 provide automatically configured and/or pre-configured processing and transmission of sensor data from the sensor kits to a set of backend systems (e.g., cloud-deployed systems or on-premises systems) via appropriate protocols, and a set of backend systems that are automatically configured and/or preconfigured to provide monitoring and/or management information to owners and operators of industrial settings from the particular sensor kits that are registered to their industrial
10 settings. As used herein “set” may include a set with a single member. References to “monitoring” and/or to “management” should be understood, except where context indicates otherwise, to encompass various actions or activities that may benefit from the information shared via the IoT, such as monitoring machine performance, reporting on status, states, or conditions, managing states, conditions, parameters, undertaking remote control, supporting autonomous functions that
15 depend on status or state information, supporting analytics, supporting self-configuration, supporting artificial intelligence, supporting machine learning, and the like.

[0010] According to some embodiments of the present disclosure, a sensor kit configured for monitoring an industrial setting is disclosed. In embodiments, the sensor kit includes an edge device and a plurality of sensors, i.e., a set of sensors, that capture sensor data and transmit the
20 sensor data via a self-configuring sensor kit network. The plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type. At least one sensor of the plurality of sensors includes a sensing component that captures sensor measurements and outputs instances of sensor data; a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet
25 includes routing data and one or more instances of sensor data; and a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol. The edge device includes a communication system having: a first communication device that receives reporting packets from the plurality of sensors via the self-
30 configuring sensor kit network and a second communication device that transmits sensor kit packets to a backend system via a public network. The edge device further includes a processing system having one or more processors that execute computer-executable instructions that cause the processing system to: receive the reporting packets from the communication system; perform one or more edge operations on the instances of sensor data in the reporting packets; generate the sensor
35 kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least

one instance of sensor data; and output the sensor kits packets to the communication system, wherein the communication system transmits the reporting packets to the backend system via the public network.

[0011] In some embodiments, the sensor kit further includes a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device. In some of these embodiments, the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. Alternatively, in some embodiments, the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

[0012] In some embodiments, the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

[0013] In some embodiments, the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

[0014] In some embodiments, the edge device further includes one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of an industrial component of the industrial setting and/or the industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors. In some of these embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction. In some of these embodiments, selectively encoding the one or more instances of sensor data includes: compressing the one or more instances of sensor data using a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting. In some of these embodiments, compressing the one or more instances of sensor data using the lossy codec includes: normalizing the one or more instances of sensor data into respective pixel

values; encoding the respective pixel values into a video frame; and compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data. In some embodiments, selectively encoding the one or more instances of sensor data includes compressing the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting. In some embodiments, selectively encoding the one or more instances of sensor data includes refraining from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting. In some embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification. In some embodiments, selectively storing the one or more instances of sensor data includes in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting, storing the one or more instances of sensor data in the storage device with an expiry, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry. In some embodiments, selectively storing the one or more instances of sensor data includes in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, storing the one or more instances of sensor data in the storage device indefinitely.

[0015] In embodiments, the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

[0016] In embodiments, the self-configuring sensor kit network is a mesh network such that the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors, and at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

[0017] In embodiments, the self-configuring sensor kit network is a hierarchical network. In some of these embodiments, the sensor kit further includes one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device.

[0018] In embodiments, the self-configuring sensor kit network is a ring network that communicates using a serial data protocol.

[0019] In embodiments, the sensor kit network is a mesh network.

[0020] In embodiments, at least one of the sensors in the sensor kit network is a multi-axis vibration sensor.

[0021] In embodiments, the edge device includes a rule-based network protocol adaptor for selecting a network protocol by which to send sensor kit packets via the public network.

[0022] According to some embodiments of the present disclosure, a method for monitoring an industrial setting using a sensor kit having a plurality of sensors and an edge device including a processing system is disclosed. In embodiments, the method includes receiving, by the processing system, reporting packets from one or more respective sensors of the plurality of sensors, wherein each reporting packet is sent from a respective sensor and indicates sensor data captured by the respective sensor; performing, by the processing system, one or more edge operations on one or more instances of sensor data received in the reporting packets; generating, by the processing system, one or more sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data; and outputting, by the processing system, the sensor kit packets to a backend system via a public network. In some embodiments, the reporting packets received from one or more respective sensors of the plurality of sensors include a sensor identifier of the respective sensor. In embodiments, receiving the reporting packets from the one or more respective sensors is performed using a first communication device implementing a first communication protocol and outputting the sensor kit packets to the backend system is performed using a second communication device implementing a second communication protocol.

In some embodiments, the second communication device is a satellite terminal device, and outputting the sensor kit packets includes transmitting the sensor kit packets to a satellite using the satellite terminal device, wherein the satellite routes the sensor kit packets to the public network. In embodiments, outputting the sensor kit packets to a backend system includes transmitting the sensor kit packets to a gateway device of the sensor kit. In some embodiments, transmitting the sensor kit packets to the gateway device includes transmitting the sensor kit packets to the gateway via a wired communication link between the edge device and the gateway device. In embodiments, the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. In some embodiments, the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider. In embodiments, the method further includes storing, by one or more storage devices of the edge device, a model data store that stores one or more machine-learned models. In some embodiments, the one or more machine-learned models are trained to predict or classify a condition of an industrial component of the industrial setting and/or of the industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors.

[0023] In some embodiments performing one or more edge operations includes generating a feature of vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to a machine-learned model of the one or more machine-learned models to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction. In some embodiments, selectively encoding the one or more instances of sensor data includes: compressing the one or more instances of sensor data using a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting. In embodiments, compressing the one or more instances of sensor data using the lossy codec includes: normalizing the one or more instances of sensor data into respective pixel values; encoding the respective pixel values into a video frame; and compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data. In some embodiments, selectively encoding the one or more instances of sensor data includes compressing the one or more instances of sensor data using a

lossless codec in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting. In embodiments, selectively encoding the one or more instances of sensor data includes refraining from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

[0024] In some embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification. In embodiments, selectively storing the one or more instances of sensor data includes storing the one or more instances of sensor data in the storage device with an expiry such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry, wherein storing the one or more instances of sensor data in the storage device with an expiry is performed in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting. In some embodiments, selectively storing the one or more instances of sensor data includes storing the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

[0025] In some embodiments, the method further includes: capturing, by a sensing component of a sensor of the plurality of sensors, sensor measurements; generating, by a processor of the sensor, one or more reporting packets based on the captured sensor measurements; and transmitting, by a communication unit of the sensor, the one or more reporting packets to the edge device via a self-configuring sensor kit network. In some of these embodiments, the method further includes initiating, by the processing system, configuration of the self-configuring sensor kit network, wherein the self-configuring sensor kit network is a star network. In some embodiments, the reporting packets are received directly from respective sensors using a short-range communication protocol. In embodiments, the method further includes initiating, by the processing system,

configuration of the self-configuring sensor kit network, wherein the self-configuring sensor kit network is a mesh network. In some embodiments, the method further includes: establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors; receiving, by the at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device via the mesh network.

[0026] In some embodiments, the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices that participate in the hierarchical network.

In some of these embodiments, the method further includes receiving, by a collection device of the one or more collection devices, reporting packets from a set of sensors of the plurality of sensors that communicate with the collection device using a first short-range communication protocol; and routing, by the one or more collection devices, the reporting packets to the edge device using one of the first short-range communication protocol or a second short-range communication protocol that is different than the second-range communication protocol.

[0027] In some embodiments, the edge device includes a rule-based network protocol adaptor. In some of these embodiments, the method further includes: selecting, by the rule-based network protocol adaptor, a network protocol; and sending, by the edge device, sensor kit packets by the network protocol via the public network.

[0028] In some embodiments, the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.

[0029] According to some embodiments of the present disclosure, a sensor kit configured for monitoring an industrial setting is disclosed. In embodiments, the sensor kit includes an edge device and a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network. The plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type. At least one sensor of the plurality of sensors includes a sensing component that captures sensor measurements and outputs instances of sensor data; a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol. The edge device includes one or more storage devices that store a model data store that stores a plurality of machine-learned models that are each trained to predict or classify a condition of an industrial component of the industrial setting or of the industrial setting based on a set of features that are

derived from instances of sensor data captured by one or more of the plurality of sensors. The edge device further includes a communication system that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network using a first communication protocol and that transmits sensor kit packets to a backend system via a public network using a second communication protocol that is different from the first communication protocol. The edge device further includes a processing system having one or more processors that execute computer-executable instructions that cause the processing system to: receive the reporting packets from the communication system; generate a set of feature vectors based on one or more respective instances of sensor data received in the reporting packets; for each respective feature vector, input the respective feature vector into a respective machine-learned model that corresponds to the feature vector to obtain a respective prediction or classification relating to a condition of a respective industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the respective prediction or classification; selectively encode the one or more instances of sensor data prior to transmission to the backend system based on the respective predictions or classifications outputted by the machine-learned models in response to the respective feature vector to obtain one or more sensor kit packets; and output the sensor kits packets to the communication system, wherein the communication system transmits the reporting packets to the backend system via the public network.

[0030] In some embodiments, the sensor kit further includes a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device. In some of these embodiments, the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. Alternatively, in some embodiments, the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

[0031] In some embodiments, the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

[0032] In embodiments, the one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

[0033] In embodiments, selectively encoding the one or more instances of sensor data includes, in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the

industrial setting, compressing the one or more instances of sensor data using a lossy codec. In some embodiments, compressing the one or more instances of sensor data using the lossy codec includes: normalizing the one or more instances of sensor data into respective pixel values; encoding the respective pixel values into a video frame; and compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data. In some of these embodiments, selectively encoding the one or more instances of sensor data includes: in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, compressing the one or more instances of sensor data using a lossless codec.

[0034] In some embodiments, selectively encoding the one or more instances of sensor data includes: in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, refraining from compressing the one or more instances of sensor data.

[0035] In embodiments, the computer-executable instructions further cause the one or more processors of the edge device to selectively store the one or more instances of sensor data in the one or more storage devices of the edge device based on the respective predictions or classifications. In some of these embodiments, selectively storing the one or more instances of sensor data includes, in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting, storing the one or more instances of sensor data in the storage device with an expiry, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry. In some embodiments, selectively storing the one or more instances of sensor data includes, in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, storing the one or more instances of sensor data in the storage device indefinitely.

[0036] In embodiments, the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

[0037] In some embodiments, the self-configuring sensor kit network is a mesh network such that: the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors, and at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

[0038] In embodiments, the self-configuring sensor kit network is a hierarchical network. In some of these embodiments, the sensor kit includes one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device.

[0039] According to some embodiments of the present disclosure, a method for monitoring an industrial setting using a sensor kit having a plurality of sensors and an edge device including a processing system is disclosed. The method includes: receiving, by the processing system, reporting packets from one or more respective sensors of the plurality of sensors, wherein each reporting packet includes routing data and one or more instances of sensor data; generating, by the processing system, a set of feature vectors based on one or more respective instances of sensor data received in the reporting packets; inputting, by the processing system, each respective feature vector into a respective machine-learned model of a plurality of machine-learned models that are each trained to predict or classify a respective condition of an industrial component of the industrial setting or of the industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors; obtaining, by the processing system, a respective prediction or classification and a degree of confidence corresponding to the respective prediction or classification from each respective machine-learned model based on the respective feature vector inputted into the respective machine-learned model; selectively encoding, by the processing system, the one or more instances of sensor data based on the respective prediction or classification to obtain one or more sensor kit packets; and transmitting, by the processing system, the sensor kit packets to a backend system via a public network. In some embodiments, the sensor kit includes a gateway device configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device. In embodiments, the gateway device includes a satellite terminal device that transmits the sensor kit packets to a satellite that routes the sensor kit packets to the public network. In some embodiments, the gateway device includes a cellular chipset that

transmits the sensor kit packets to a cellphone tower of a preselected cellular provider. In embodiments, receiving the reporting packets from the one or more respective sensors is performed using a first communication device implementing a first communication protocol and transmitting the sensor kit packets to the backend system is performed using a second communication device
5 implementing a second communication protocol. In some embodiments, the second communication device of the edge device is a satellite terminal device and transmitting the sensor kit packets to the backend system includes transmitting, by the satellite terminal device, the sensor kit packets to a satellite that routes the sensor kit packets to the public network

[0040] In some embodiments, the method further includes compressing, by the processing system,
10 the one or more instances of sensor data using a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of the respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting. In some of these embodiments, compressing the one or more instances of sensor data using the lossy codec
15 includes: normalizing the one or more instances of sensor data into respective pixel values; encoding the respective pixel values into a video frame; and compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of the sensor data. In some embodiments, the method includes compressing, by
20 the processing system, the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting. In embodiments, the method includes refraining, by the processing system, from compressing the one or more instances of sensor data
25 in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

[0041] In some embodiments, the edge communication device includes one or more storage devices that store the plurality of machine-learned models. In some of these embodiments, the one
30 or more storage devices store instances of the sensor data captured by the plurality of sensors of the sensor kit. In some embodiments, the method further includes selectively storing, by the processing system, the one or more instances of sensor data in the one or more storage devices based on the respective predictions or classifications. In embodiments, the method further includes storing, by the processing system, the one or more instances of sensor data in the storage device
35 with an expiry such that the one or more instances of sensor data are purged from the storage device

in accordance with the expiry, wherein the processing system stores the one or more instances of sensor data in the storage device with the expiry in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting. In some embodiments, the method further includes storing, by the processing system, the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting

[0042] In some embodiments, the method further includes capturing, by the plurality of sensors, sensor data; and transmitting, by the plurality of sensors, the sensor data via a self-configuring sensor kit network. In some of these embodiments, transmitting the sensor data via the self-configuring sensor kit network includes directly transmitting, by each sensor of the plurality of sensors, instances of sensor data with the edge device using a short-range communication protocol, wherein the self-configuring sensor kit network is a star network. In some embodiments, the method further includes initiating, by the processing system, configuration of the self-configuring sensor kit network. In embodiments, the self-configuring sensor kit network is a mesh network and each sensor of the plurality of sensors includes a communication device. In embodiments, the method further includes: establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors; receiving, by at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device.

[0043] In some embodiments, the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices. In some of these embodiments, the method further includes: receiving, by at least one collection device of the plurality of collection devices, reporting packets from one or more sensors of the plurality of sensors; and routing, by the at least one collection device of the plurality of collection devices, the reporting packets to the edge device.

[0044] In embodiments, the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.

[0045] According to some embodiments of the present disclosure, a sensor kit configured for monitoring an industrial setting is disclosed. In embodiments, the sensor kit includes an edge device and a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network. The plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type. At least one sensor of the plurality of

sensors includes a sensing component that captures sensor measurements and outputs instances of sensor data; a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol. The edge device includes a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network; and a second communication device that transmits sensor kit packets to a backend system via a public network. The edge device further includes a processing system having one or more processors that execute computer-executable instructions that cause the processing system to: receive the reporting packets from the communication system; generate a block of media content frames, wherein each media content frame includes a plurality of frame values, each frame value being indicative of a respective instance of sensor data; compress the block of media content frames using a media codec; generate one or more server kit packets based on the block of media content frames; and transmit the one or more server kit packets to the backend system via the public network.

[0046] In some embodiments, the sensor kit further includes a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device. In some of these embodiments, the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. Alternatively, in some embodiments, the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

[0047] In some embodiments, the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

[0048] In embodiments, the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

[0049] In embodiments, the edge device further includes one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of an industrial component of the industrial setting and/or the industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors. In some embodiments, performing one or more edge operations

includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence
5 corresponding to the prediction or classification; and selecting the codec used to compress the block of media frames based on the condition or prediction. In some embodiments, selecting the codec includes, in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the
10 industrial setting and the industrial setting, selecting a lossy codec. In some of these embodiments, selectively encoding the one or more instances of sensor data includes, in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, selecting a lossless codec.

15 **[0050]** In some embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the
20 prediction or classification; and selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification. In some of these embodiments, selectively storing the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there
25 are likely no issues relating to any industrial component of the industrial setting and the industrial setting, storing the one or more instances of sensor data in the storage device with an expiry, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry. In some embodiments, selectively storing the one or more instances of sensor data includes: in response to obtaining a prediction or classification relating to a condition of a particular
30 industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, storing the one or more instances of sensor data in the storage device indefinitely.

[0051] In embodiments, the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device
35 directly using a short-range communication protocol. In some of these embodiments, the computer-

executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

[0052] In some embodiments, the self-configuring sensor kit network is a mesh network such that: the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors, and at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

[0053] In embodiments, the self-configuring sensor kit network is a hierarchical network. In some of these embodiments, the sensor kit includes one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device.

[0054] In some embodiments, generating the block of media frames includes: for each instance of sensor data that is to be included in a media frame, normalizing the instance of sensor data into a respective normalized media frame value that is within of range of media frame values that are permitted by an encoding standard corresponding to the media frame; and embedding each respective normalized media frame value into the media frame. In some of these embodiments, wherein each media frame is a video frame including a plurality of pixels and the respective normalized media frame values are pixel values. In some embodiments, embedding each respective normalized media frame value into the media frame includes: determining a pixel of the plurality of pixels corresponding to the respective normalized media frame based on a mapping that maps respective sensors of the plurality of sensors to respective pixels of the plurality of pixels; and setting a value of the determined pixel equal to the respective normalized media frame value. In embodiments, the codec is an H.264/MPEG-4 codec. In embodiments, the codec is an H.265/MPEG-H codec. In embodiments, the codec is an H.263/MPEG-4 codec.

[0055] According to some embodiments of the present disclosure, a method for monitoring an industrial setting using a sensor kit having a plurality of sensors and an edge device including a processing system is disclosed. The method includes: receiving, by the processing system, reporting packets from one or more respective sensors of the plurality of sensors, wherein each reporting packet includes routing data and one or more instances of sensor data; generating, by the processing system, a block of media content frames, wherein each media content frame includes a plurality of frame values, each frame value being indicative of a respective instance of sensor data;

compressing, by the processing system, the block of media content frames using a media codec to obtain a compressed block; generating, by the processing system, one or more server kit packets based on the compressed block; and transmitting, by the processing system, the one or more server kit packets to a backend system via a public network. In some embodiments, the sensor kit includes
5 a gateway device configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device. In embodiments, the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. In some embodiments, the gateway device includes a cellular
10 chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

[0056] In embodiments, receiving the reporting packets from the one or more respective sensors is performed using a first communication device that receives reporting packets from the plurality of sensors via a self-configuring sensor kit network and transmitting the sensor kit packets to the
15 backend system is performed using a second communication device. In some of these embodiments, the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. In some embodiments, the method further includes capturing, by the plurality of sensors, sensor data; and transmitting, by the plurality of sensors, the sensor data to the edge device
20 via the self-configuring sensor kit network. In some embodiments, transmitting the sensor data via the self-configuring sensor kit network includes directly transmitting, by each sensor of the plurality of sensors, instances of sensor data with the edge device using a short-range communication protocol, wherein the self-configuring sensor kit network is a star network. In embodiments, the method further includes initiating, by the processing system, configuration of
25 the self-configuring sensor kit network.

[0057] In some embodiments, the self-configuring sensor kit network is a mesh network and each sensor of the plurality of sensors includes a communication device. In some of these embodiments, the method further includes establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of
30 sensors; receiving, by at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device.

[0058] In some embodiments, the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices. In some of these embodiments, the method
35 further includes receiving, by at least one collection device of the plurality of collection devices,

reporting packets from one or more sensors of the plurality of sensors; and routing, by the at least one collection device of the plurality of collection devices, the reporting packets to the edge device.

[0059] In some embodiments, the method further includes storing, by one or more storage devices of the edge device, instances of sensor data captured by the plurality of sensors of the sensor kit.

5 [0060] In embodiments, the edge device further includes one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of an industrial component of the industrial setting and/or the industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors. In some of these embodiments, the method further includes:

10 generating, by the processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting, by the processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and selecting

15 the media codec used to compress the block of media content frames based on the classification or prediction. In some embodiments, selecting the media codec includes selecting a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the

20 industrial setting. In embodiments, selecting the media codec includes selecting a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

[0061] In some embodiments, the method further includes: generating, by the processing system,

25 a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting, by the processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and selectively storing, by the processing system,

30 the one or more instances of sensor data in the storage device of the edge device based on the prediction or classification. In embodiments, selectively storing the one or more instances of sensor data in the storage device includes storing the one or more instances of sensor data in the storage device with an expiry such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry, wherein storing the one or more instances of sensor data in

35 the storage device with an expiry is performed in response to obtaining one or more predictions or

classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting. In some embodiments, selectively storing the one or more instances of sensor data in the storage device includes storing the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

[0062] In some embodiments, generating the block of media content frames includes: normalizing, by the processing system, for each instance of sensor data that is to be included in a media content frame, the instance of sensor data into a respective normalized media content frame value that is within of range of media content frame values that are permitted by an encoding standard corresponding to the media content frame; and embedding, by the processing system, each respective normalized media content frame value into the media content frame. In some of these embodiments, each media content frame is a video frame including a plurality of pixels and the respective normalized media frame values are pixel values. In embodiments, embedding each respective normalized media content frame value into the media content frame includes: determining, by the processing system, a pixel of the plurality of pixels corresponding to the respective normalized media content frame based on a mapping that maps respective sensors of the plurality of sensors to respective pixels of the plurality of pixels; and setting a value of the determined pixel equal to the respective normalized media content frame value. In some embodiments, the codec is an H.264/MPEG-4 codec. In some embodiments, the codec is an H.265/MPEG-H codec. In some embodiments, the codec is an H.263/MPEG-4 codec.

[0063] In embodiments, the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.

[0064] According to some embodiments of the present disclosure, a system is disclosed. The system includes a backend system and a sensor kit configured to monitor an industrial setting, the sensor kit. The sensor kit includes a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of the plurality of sensors includes: a sensing component that captures sensor measurements and outputs instances of sensor data; a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and a communication device configured to receive reporting packets from the processing unit and to

transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol. The edge device includes a communication system having: a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network; and a second communication device that
5 transmits sensor kit packets to a backend system via a public network. The edge device includes a processing system having one or more processors that execute computer-executable instructions that cause the processing system to: receive the reporting packets from the communication system; perform one or more edge operations on the instances of sensor data in the reporting packets; generate the sensor kit packets based on the instances of sensor data, wherein each sensor kit packet
10 includes at least one instance of sensor data; and output the sensor kits packets to the communication system, wherein the communication system transmits the reporting packets to the backend system via the public network. The backend system includes a backend storage system that stores a sensor kit data store that stores sensor data received from one or more respective sensor kits, including the sensor kit; and a backend processing system having one or more processors that
15 execute computer-executable instructions that cause the backend processing system to: receive the sensor kit packets from the sensor kit; determine sensor data collected by the sensor kit based on the sensor kit packets; perform one or more backend operations on the sensor data collected by the sensor kit; and store the sensor data collected by the sensor kit in the sensor kit data store.

[0065] In some embodiments, the sensor kit further includes a gateway device that is configured
20 to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device. In some of these embodiments, the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. Alternatively, in some embodiments, the gateway device includes a cellular chipset that
25 is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

[0066] In some embodiments, the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

30 [0067] In embodiments, the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

[0068] In embodiments, the edge device further includes one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict
35 or classify a condition of an industrial component of the industrial setting and/or the industrial

setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors. In some of these embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction. In some embodiments, selectively encoding the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting, compressing the one or more instances of sensor data using a lossy codec. In some embodiments, compressing the one or more instances of sensor data using the lossy codec includes: normalizing the one or more instances of sensor data into respective pixel values; encoding the respective pixel values into a video frame; and compressing a block of video frames using the lossy codec to obtain a compressed block of frames, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data. In some embodiments, the backend system receives the compressed block of frames in one or more sensor kit packets and determines the sensor data collected by the sensor kit by decompressing the compressed block of frames using the lossy codec. In some embodiments, selectively encoding the one or more instances of sensor data includes, in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, compressing the one or more instances of sensor data using a lossless codec. In some embodiments, selectively encoding the one or more instances of sensor data includes, in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, refraining from compressing the one or more instances of sensor data. In some embodiments, selectively encoding the one or more instances of sensor data includes selecting a stream of sensor data instances for uncompressed transmission. In some embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or

classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification. In some of these embodiments, selectively storing the one or more instances of sensor data includes, in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting, storing the one or more instances of sensor data in the storage device with an expiry, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry. In some embodiments, selectively storing the one or more instances of sensor data includes, in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, storing the one or more instances of sensor data in the storage device indefinitely.

[0069] In embodiments, the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

[0070] In some embodiments, the self-configuring sensor kit network is a mesh network such that: the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors, and at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

[0071] In embodiments, the self-configuring sensor kit network is a hierarchical network. In some of these embodiments, the sensor kit includes one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device.

[0072] In embodiments, the backend operations include performing one or more analytics tasks using the sensor data; performing one or more artificial intelligence tasks using the sensor data;

issuing a notification to a human user associated with the industrial setting based on the sensor data; and/or controlling at least one component of the industrial setting based on the sensor data.

[0073] According to some embodiments of the present disclosure, a method for monitoring an industrial setting using a sensor kit in communication with a backend system, the sensor kit including a plurality of sensors and an edge device is disclosed. The method includes: receiving, by an edge processing system of the edge device, reporting packets from one or more respective sensors of the plurality of sensors, wherein each reporting packet includes routing data and one or more instances of sensor data; performing, by the edge processing system, one or more edge operations on the instances of sensor data in the reporting packets; generating, by the edge processing system, a plurality of sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data; transmitting, by the edge processing system, the sensor kit packets to the backend system via a public network; receiving, by a backend processing system of the backend system, the sensor kit packets from the sensor kit via the public network; determining, by the backend processing system, the sensor data collected by the sensor kit based on the sensor kit packets; performing, by the backend processing system, one or more backend operations on the sensor data collected by the sensor kit; and storing, by the backend processing system, the sensor data collected by the sensor kit in a sensor kit data store residing in a backend storage system of the backend system. In some embodiments, the sensor kit further includes a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device. In some embodiments, the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. In embodiments, the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

[0074] In embodiments, receiving the reporting packets from the one or more respective sensors is performed using a first communication device of the edge device that receives reporting packets from the plurality of sensors via a self-configuring sensor kit network and transmitting the sensor kit packets to the backend system is performed using a second communication device of the edge device. In some of these embodiments, the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. In embodiments, the method further includes capturing, by the plurality of sensors, sensor data; and transmitting, by the plurality of sensors, the sensor data to the edge device via the self-configuring sensor kit network. In some embodiments, transmitting the sensor data via the self-configuring sensor kit network includes directly transmitting, by each

sensor of the plurality of sensors, instances of sensor data with the edge device using a short-range communication protocol, wherein the self-configuring sensor kit network is a star network. In embodiments, the method further includes initiating, by the edge processing system, configuration of the self-configuring sensor kit network. In some embodiments, the self-configuring sensor kit network is a mesh network and each sensor of the plurality of sensors includes a communication device. In some embodiments, the method further includes: establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors; receiving, by at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device.

[0075] In some embodiments, the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices. In some of these embodiments, the method further includes: receiving, by at least one collection device of the plurality of collection devices, reporting packets from one or more sensors of the plurality of sensors; and routing, by the at least one collection device of the plurality of collection devices, the reporting packets to the edge device.

[0076] In embodiments, the method further includes storing, by one or more storage devices of the edge device, instances of sensor data captured by the plurality of sensors of the sensor kit.

[0077] In some embodiments, the edge device further includes one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of an industrial component of the industrial setting and/or the industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors. In some of these embodiments, performing one or more edge operations includes: generating, by the edge processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and selectively encoding, by the edge processing system, the one or more instances of sensor data prior to transmission to the backend system based on the prediction or classification. In some embodiments, selectively encoding the one or more instances of sensor data includes compressing, by the edge processing system, the one or more instances of sensor data using a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the

industrial setting and the industrial setting. In some embodiments, compressing the one or more instances of sensor data using a lossy codec includes: normalizing, by the edge processing system, the one or more instances of sensor data into respective pixel values; encoding, by the edge processing system, the respective pixel values into a media content frame; and compressing, by the edge processing system, a block of media content frames using the lossy codec to obtain a compressed block, wherein the lossy codec is a video codec and the compressed block includes the media content frame and one or more other media content frames that include normalized pixel values of other instances of sensor data. In embodiments, the backend system receives the compressed block in one or more sensor kit packets and determines the sensor data collected by the sensor kit by decompressing the compressed block using the lossy codec.

[0078] In some embodiments, selectively encoding the one or more instances of sensor data includes compressing, by the edge processing system, the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting. In embodiments, selectively encoding the one or more instances of sensor data includes refraining, by the edge processing system, from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting. In some embodiments, selectively encoding the one or more instances of sensor data includes selecting, by the edge processing system, a stream of sensor data instances for uncompressed transmission.

[0079] In some embodiments, performing one or more edge operations includes: generating, by the edge processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and selectively storing, by the edge processing system, the one or more instances of sensor data in a storage device of the one or more storage devices based on the prediction or classification. In some embodiments, selectively storing the one or more instances of sensor data includes storing, by the edge processing system, the one or more instances of sensor data in the storage device with an expiry in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial

setting, wherein storing the one or more instances of sensor data in the storage device with an expiry is performed such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry. In some embodiments, selectively storing the one or more instances of sensor data includes storing, by the edge processing system, the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

[0080] In some embodiments, the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.

[0081] According to some embodiments of the present disclosure, a sensor kit configured to monitor an indoor agricultural facility is disclosed. The sensor kit includes an edge device and a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type. At least one sensor of the plurality of sensors includes: a sensing component that captures sensor measurements and outputs instances of sensor data; a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol. The plurality of sensors includes two or more sensor types selected from the group including: light sensors, humidity sensors, temperature sensors, carbon dioxide sensors, fan speed sensors, weight sensors, and camera sensors. The edge device includes a communication system having a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network and a second communication device that transmits sensor kit packets to a backend system via a public network. The edge device also includes a processing system having one or more processors that execute computer-executable instructions that cause the processing system to: receive the reporting packets from the communication system, perform one or more edge operations on the instances of sensor data in the reporting packets; generate the sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data; and output the sensor kits packets to the communication system, wherein the communication system transmits the reporting packets to the backend system via the public network.

[0082] In embodiments, the sensor kit includes an edge device and a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network. The plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type. At least one sensor of the plurality of sensors includes a sensing component
5 that captures sensor measurements and outputs instances of sensor data; a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network
10 in accordance with a first communication protocol.

[0083] In embodiments, the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

[0084] In embodiments, the edge device further includes one or more storage devices that store a
15 model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of a component of the indoor agricultural setting and/or the indoor agricultural setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors. In some of these embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data
20 received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the indoor agricultural setting or the indoor agricultural setting and a degree of confidence corresponding to the prediction or classification; and selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition
25 or prediction. In some embodiments, selectively encoding the one or more instances of sensor data includes compressing the one or more instances of sensor data using a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the indoor agricultural setting and the indoor agricultural setting that collectively indicate that there are likely no issues relating to any component of the indoor agricultural setting
30 and the indoor agricultural setting. In some embodiments, compressing the one or more instances of sensor data using the lossy codec includes: normalizing the one or more instances of sensor data into respective pixel values; encoding the respective pixel values into a video frame; and compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames
35 that include normalized pixel values of other instances of sensor data. In some embodiments,

selectively encoding the one or more instances of sensor data includes: compressing the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting. In embodiments, selectively encoding the one or more instances of sensor data includes refraining from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular component or the indoor agricultural setting that indicates that there is likely an issue relating to the particular component or the indoor agricultural setting. In embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the indoor agricultural setting or the indoor agricultural setting and a degree of confidence corresponding to the prediction or classification; and selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification. In some of these embodiments, selectively storing the one or more instances of sensor data includes storing the one or more instances of sensor data in the storage device with an expiry in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the indoor agricultural setting and the indoor agricultural setting that collectively indicate that there are likely no issues relating to any component of the indoor agricultural setting and the indoor agricultural setting, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry. In some embodiments, selectively storing the one or more instances of sensor data includes storing the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular component or the indoor agricultural setting.

[0085] In embodiments, the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

[0086] In embodiments, the self-configuring sensor kit network is a mesh network such that: the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors; and at least one

sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

[0087] In embodiments, the self-configuring sensor kit network is a hierarchical network. In some of these embodiments, the sensor kit further includes one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device. In embodiments, each collection device is installed in a different respective room of the indoor agricultural setting and collects sensor data from sensors of the plurality of sensors that are deployed in the respective room.

[0088] According to some embodiments of the present disclosure, a sensor kit configured to monitor an indoor agricultural setting is disclosed. The sensor kit includes an edge device and a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type. At least one sensor of the plurality of sensors includes: a sensing component that captures sensor measurements and outputs instances of sensor data; a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol. The plurality of sensors includes two or more sensor types selected from the group including: infrared sensors, ground penetrating sensors, light sensors, humidity sensors, temperature sensors, chemical sensors, fan speed sensors, rotational speed sensors, weight sensors, and camera sensors. The edge device includes a communication system having a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network and a second communication device that transmits sensor kit packets to a backend system via a public network. The edge device further includes a processing system having one or more processors that execute computer-executable instructions that cause the processing system to: receive the reporting packets from the communication system; perform one or more edge operations on the instances of sensor data in the reporting packets; generate the sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data; and output the

sensor kits packets to the communication system, wherein the communication system transmits the reporting packets to the backend system via the public network.

[0089] In some embodiments, the sensor kit further includes a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device. In some of these embodiments, the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. Alternatively, in some embodiments, the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

[0090] In some embodiments, the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

[0091] In embodiments, the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

[0092] In embodiments, the edge device further includes one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of a component of the indoor agricultural setting and/or the indoor agricultural setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors. In some embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the indoor agricultural setting or the indoor agricultural and a degree of confidence corresponding to the prediction or classification; and selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction.

[0093] In embodiments, selectively encoding the one or more instances of sensor data includes compressing the one or more instances of sensor data using a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective components of the indoor agricultural setting and the indoor agricultural setting that collectively indicate that there are likely no issues relating to any component of the indoor agricultural setting and the indoor agricultural setting. In embodiments, compressing the one or more instances of sensor data using the lossy codec includes: normalizing the one or more instances of sensor data into respective pixel

values; encoding the respective pixel values into a video frame; and compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data. In embodiments, selectively encoding the one or more instances of sensor data includes compressing the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular component or the indoor agricultural setting that indicates that there is likely an issue relating to the particular component or the indoor agricultural setting. In embodiments, selectively encoding the one or more instances of sensor data includes refraining from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular component or the indoor agricultural setting that indicates that there is likely an issue relating to the particular component or the indoor agricultural setting.

[0094] In some embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the indoor agricultural setting or the indoor agricultural setting and a degree of confidence corresponding to the prediction or classification; and selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification. In embodiments, selectively storing the one or more instances of sensor data includes storing the one or more instances of sensor data in the storage device with an expiry in response to obtaining one or more predictions or classifications relating to conditions of respective components of the indoor agricultural setting and the indoor agricultural setting that collectively indicate that there are likely no issues relating to any component of the indoor agricultural setting and the indoor agricultural setting, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry. In embodiments, selectively storing the one or more instances of sensor data includes storing the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular component or the indoor agricultural setting that indicates that there is likely an issue relating to the particular component or the indoor agricultural setting.

[0095] In some embodiments, the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type selected from the group including: light sensors, humidity sensors, temperature sensors, carbon dioxide sensors, fan speed sensors, weight sensors, and camera sensors.

[0096] According to some embodiments of the present disclosure, a sensor kit configured to monitor a pipeline setting is disclosed. The sensor kit includes an edge device and a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network. The plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type. At least one sensor of the plurality of sensors includes: a sensing component that captures sensor measurements and outputs instances of sensor data; a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol. The plurality of sensors includes two or more sensor types selected from the group including: infrared sensors, metal penetrating sensors, concrete penetrating sensors, light sensors, strain sensors, rust sensors, biological sensors, humidity sensors, temperature sensors, chemical sensors, valve integrity sensors, vibration sensors, flow sensors, cavitation sensors, pressure sensors, weight sensors, and camera sensors. The edge device includes a communication system having: a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network and a second communication device that transmits sensor kit packets to a backend system via a public network. The edge device further includes a processing system having one or more processors that execute computer-executable instructions that cause the processing system to: receive the reporting packets from the communication system; perform one or more edge operations on the instances of sensor data in the reporting packets; generate the sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data; and output the sensor kits packets to the communication system, wherein the communication system transmits the reporting packets to the backend system via the public network.

[0097] In some embodiments, the sensor kit further includes a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device. In some of these embodiments, the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. Alternatively, in some embodiments, the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

[0098] In some embodiments, the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

5 [0099] In embodiments, the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

[00100] In embodiments, the edge device further includes one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of a pipeline component of the pipeline setting and/or the pipeline setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors. In some of these embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular pipeline component of the pipeline setting or the pipeline setting and a degree of confidence corresponding to the prediction or classification; and selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction. In embodiments, selectively encoding the one or more instances of sensor data includes compressing the one or more instances of sensor data using a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective pipeline components of the pipeline setting and the pipeline setting that collectively indicate that there are likely no issues relating to any pipeline component of the pipeline setting and the pipeline setting. In embodiments, compressing the one or more instances of sensor data using the lossy codec includes: normalizing the one or more instances of sensor data into respective pixel values; encoding the respective pixel values into a video frame; and compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data. In embodiments, selectively encoding the one or more instances of sensor data includes compressing the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular pipeline component or the pipeline setting that indicates that there is likely an issue relating to the particular pipeline component or the pipeline setting. In embodiments, selectively encoding the one or more instances of sensor data includes refraining from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular pipeline component or the pipeline setting that indicates that there is likely an issue relating to the particular

10
15
20
25
30
35

pipeline component or the pipeline setting. In embodiments, performing one or more edge operations includes generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular pipeline component of the pipeline setting or the pipeline setting and a degree of confidence corresponding to the prediction or classification; and selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification. In embodiments, selectively storing the one or more instances of sensor data includes storing the one or more instances of sensor data in the storage device with an expiry in response to obtaining one or more predictions or classifications relating to conditions of respective pipeline components of the pipeline setting and the pipeline setting that collectively indicate that there are likely no issues relating to any pipeline component of the pipeline setting and the pipeline setting, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry. In embodiments, selectively storing the one or more instances of sensor data includes storing the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular pipeline component or the pipeline setting that indicates that there is likely an issue relating to the particular pipeline component or the pipeline setting.

[0101] In embodiments, the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

[0102] In embodiments, the self-configuring sensor kit network is a mesh network such that: the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors; and at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

[0103] In embodiments, the self-configuring sensor kit network is a hierarchical network. In some of these embodiments, the sensor kit further includes one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the

reporting packets to the edge device. In embodiments, each collection device is installed in a different respective section of the pipeline setting and collects sensor data from sensors of the plurality sensors that are deployed in the respective room.

[0104] According to some embodiments of the present disclosure, a method of monitoring a pipeline setting using a sensor kit including an edge device and a plurality of sensors is disclosed. The method includes: receiving, by an edge processing system of the edge device, reporting packets from a plurality of sensors via a self-configuring sensor kit network, each reporting packet containing routing data and one or more instances of sensor data captured by a respective sensor of the plurality of sensors, wherein the plurality of sensors includes two or more sensor types selected from the group including: light sensors, humidity sensors, temperature sensors, carbon dioxide sensors, fan speed sensors, weight sensors, and camera sensors; performing, by the edge processing system, one or more edge operations on the instances of sensor data in the reporting packets; generating, by the edge processing system, one or more edge operations on the instances of sensor data in the reporting packets; and transmitting, by the edge processing system, the sensor kit packets to an edge communication system of the edge device, wherein the edge communication system transmits the reporting packets to a backend system via a public network. In some embodiments, the sensor kit further includes a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device. In embodiments, the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. In some embodiments, the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider. In embodiments, receiving the reporting packets from the one or more respective sensors is performed using a first communication device of the edge device that receives reporting packets from the plurality of sensors via a self-configuring sensor kit network and transmitting the sensor kit packets to the backend system is performed using a second communication device of the edge device. In some embodiments, the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

[0105] In some embodiments, the method further includes capturing, by the plurality of sensors, sensor data; and transmitting, by the plurality of sensors, the sensor data to the edge device via the self-configuring sensor kit network. In some of these embodiments, transmitting the sensor data via the self-configuring sensor kit network includes directly transmitting, by each sensor of the plurality of sensors, instances of sensor data with the edge device using a short-range

communication protocol, wherein the self-configuring sensor kit network is a star network. In some embodiments, the method further includes initiating, by the edge processing system, configuration of the self-configuring sensor kit network.

5 [0106] In embodiments, the self-configuring sensor kit network is a mesh network and each sensor of the plurality of sensors includes a communication device. In some of these embodiments, the method further includes: establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors; receiving, by at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and routing, by the at least one sensor of the plurality
10 of sensors, the received instances of the sensor data towards the edge device.

[0107] In some embodiments, the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices. In some of these embodiments, the method further includes: receiving, by at least one collection device of the plurality of collection devices, reporting packets from one or more sensors of the plurality of sensors; and routing, by the at least
15 one collection device of the plurality of collection devices, the reporting packets to the edge device. In some embodiments, each collection device is installed in a different respective section of the pipeline setting and collects sensor data from sensors of the plurality sensors that are deployed in the respective room.

[0108] In some embodiments, the method further includes storing, by one or more storage devices
20 of the edge device, instances of sensor data captured by the plurality of sensors of the sensor kit. In embodiments, the edge device further includes one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of a component of the agricultural setting and/or the agricultural setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality
25 of sensors.

[0109] In some embodiments, performing one or more edge operations includes: generating, by the edge processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a
30 condition of a particular component of the agricultural setting or the agricultural setting and a degree of confidence corresponding to the prediction or classification; and selectively encoding, by the edge processing system, the one or more instances of sensor data prior to transmission to the backend system based on the prediction or classification. In some of these embodiments, selectively encoding the one or more instances of sensor data includes compressing, by the edge
35 processing system, the one or more instances of sensor data using a lossy codec in response to

obtaining one or more predictions or classifications relating to conditions of respective components of the agricultural setting and the agricultural setting that collectively indicate that there are likely no issues relating to any component of the agricultural setting and the agricultural setting. In some embodiments, compressing the one or more instances of sensor data using a lossy codec includes:

5 normalizing, by the edge processing system, the one or more instances of sensor data into respective pixel values; encoding, by the edge processing system, the respective pixel values into a media content frame; and compressing, by the edge processing system, a block of media content frames using the lossy codec to obtain a compressed block, wherein the lossy codec is a video codec and the compressed block includes the media content frame and one or more other media

10 content frames that include normalized pixel values of other instances of sensor data. In some embodiments, the backend system receives the compressed block in one or more sensor kit packets and determines the sensor data collected by the sensor kit by decompressing the compressed block using the lossy codec.

[0110] In some embodiments, selectively encoding the one or more instances of sensor data

15 includes compressing, by the edge processing system, the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular component or the agricultural setting that indicates that there is likely an issue relating to the particular component or the agricultural setting. In embodiments, encoding the one or more instances of sensor data includes refraining, by the edge processing system, from

20 compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular component or the agricultural setting that indicates that there is likely an issue relating to the particular component or the agricultural setting. In some embodiments, selectively encoding the one or more instances of sensor data includes selecting, by the edge processing system, a stream of sensor data instances for uncompressed

25 transmission.

[0111] In some embodiments, performing one or more edge operations includes: generating, by the edge processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a

30 condition of a particular component of the agricultural setting or the agricultural setting and a degree of confidence corresponding to the prediction or classification; and selectively storing, by the edge processing system, the one or more instances of sensor data in a storage device of the one or more storage devices based on the prediction or classification. In some of these embodiments, selectively storing the one or more instances of sensor data includes storing, by the edge processing

35 system, the one or more instances of sensor data in the storage device with an expiry in response

to obtaining one or more predictions or classifications relating to conditions of respective components of the agricultural setting and the agricultural setting that collectively indicate that there are likely no issues relating to any component of the agricultural setting and the agricultural setting, wherein storing the one or more instances of sensor data in the storage device with an expiry is performed such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry. In some embodiments, selectively storing the one or more instances of sensor data includes storing, by the edge processing system, the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular component or the agricultural setting that indicates that there is likely an issue relating to the particular component or the agricultural setting. In some embodiments, the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type selected from the group including: light sensors, humidity sensors, temperature sensors, carbon dioxide sensors, fan speed sensors, weight sensors, and camera sensors.

[0112] According to some embodiments of the present disclosure, a sensor kit configured to monitor an industrial manufacturing setting is disclosed. The sensor kit includes an edge device and a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type. At least one sensor of the plurality of sensors includes a sensing component that captures sensor measurements and outputs instances of sensor data; a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol. The plurality of sensors includes two or more sensor types selected from the group including: metal penetrating sensors, concrete penetrating sensors, vibration sensors, light sensors, strain sensors, rust sensors, biological sensors, temperature sensors, chemical sensors, valve integrity sensors, rotational speed sensors, vibration sensors, flow sensors, cavitation sensors, pressure sensors, weight sensors, and camera sensors. The edge device includes a communication system having a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network; and a second communication device that transmits sensor kit packets to a backend system via a public network. The edge device further includes a processing system having one or more processors that execute computer-executable instructions that cause the processing system to: receive the reporting packets from the communication system; perform one

or more edge operations on the instances of sensor data in the reporting packets; generate the sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data; and output the sensor kits packets to the communication system, wherein the communication system transmits the reporting packets to the backend system via the public network.

[0113] In some embodiments, the sensor kit further includes a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device. In some of these embodiments, the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. Alternatively, in some embodiments, the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

[0114] In some embodiments, the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

[0115] In embodiments, the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

[0116] In embodiments, the edge device further includes one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of an industrial component of the industrial manufacturing setting and/or the industrial manufacturing setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors. In some embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial manufacturing setting or the industrial manufacturing setting and a degree of confidence corresponding to the prediction or classification; and selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction. In some of these embodiments, selectively encoding the one or more instances of sensor data includes compressing the one or more instances of sensor data using a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial manufacturing setting and the industrial manufacturing setting that collectively indicate that there

are likely no issues relating to any industrial component of the industrial manufacturing setting and the industrial manufacturing setting. In some embodiments, compressing the one or more instances of sensor data using the lossy codec includes: normalizing the one or more instances of sensor data into respective pixel values; encoding the respective pixel values into a video frame; and
5 compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data. In embodiments, selectively encoding the one or more instances of sensor data includes compressing the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating
10 to a condition of a particular industrial component or the industrial manufacturing setting that indicates that there is likely an issue relating to the particular industrial component or the industrial manufacturing setting. In embodiments, selectively encoding the one or more instances of sensor data includes refraining from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular industrial component
15 or the industrial manufacturing setting that indicates that there is likely an issue relating to the particular industrial component or the industrial manufacturing setting. In embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to
20 a condition of a particular industrial component of the industrial manufacturing setting or the industrial manufacturing setting and a degree of confidence corresponding to the prediction or classification; and selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification. In embodiments, selectively storing the one or more instances of sensor data includes storing the one or more instances of sensor data
25 in the storage device with an expiry, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial manufacturing setting and the industrial manufacturing setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial manufacturing
30 setting and the industrial manufacturing setting. In embodiments, selectively storing the one or more instances of sensor data includes storing the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial manufacturing setting that indicates that there is likely an issue relating to the particular industrial component or the industrial
35 manufacturing setting.

[0117] In embodiments, the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

[0118] In embodiments, the self-configuring sensor kit network is a mesh network such that: the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors; and at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

[0119] In embodiments, the self-configuring sensor kit network is a hierarchical network. In some of these embodiments, the sensor kit further includes one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device. In embodiments, each collection device is installed in a different respective room of the industrial manufacturing setting and collects sensor data from sensors of the plurality of sensors that are deployed in the respective room.

[0120] According to some embodiments of the present disclosure, a sensor kit configured to monitor an underwater industrial setting is disclosed. The sensor kit includes an edge device and a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type. At least one sensor of the plurality of sensors includes: a sensing component that captures sensor measurements and outputs instances of sensor data; a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol. The plurality of sensors includes two or more sensor types selected from the group including: infrared sensors, sonar sensors, LIDAR sensors, water penetrating sensors, light sensors, strain sensors, rust sensors, biological sensors, temperature sensors, chemical sensors, valve integrity sensors, vibration sensors, flow sensors, cavitation sensors, pressure sensors, weight sensors, and camera

sensors. The edge device includes a communication system having a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network and a second communication device that transmits sensor kit packets to a backend system via a public network. The edge device further includes a processing system having one or more processors that execute computer-executable instructions that cause the processing system to: receive the reporting packets from the communication system; perform one or more edge operations on the instances of sensor data in the reporting packets; generate the sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data; and output the sensor kits packets to the communication system, wherein the communication system transmits the reporting packets to the backend system via the public network.

[0121] In some embodiments, the sensor kit further includes a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device. In some of these embodiments, the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. Alternatively, in some embodiments, the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

[0122] In some embodiments, the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

[0123] In embodiments, the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

[0124] In embodiments, the edge device further includes one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of an industrial component of the underwater industrial setting and/or the underwater industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors. In some embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the underwater industrial setting or the underwater industrial setting and a degree of confidence corresponding to the prediction or classification; and selectively

encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction. In embodiments, selectively encoding the one or more instances of sensor data includes compressing the one or more instances of sensor data using a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the underwater industrial setting and the underwater industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the underwater industrial setting and the underwater industrial setting. In embodiments, compressing the one or more instances of sensor data using the lossy codec includes: normalizing the one or more instances of sensor data into respective pixel values; encoding the respective pixel values into a video frame; and compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data. In embodiments, selectively encoding the one or more instances of sensor data includes compressing the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the underwater industrial setting that indicates that there is likely an issue relating to the particular industrial component or the underwater industrial setting. In embodiments, selectively encoding the one or more instances of sensor data includes refraining from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the underwater industrial setting that indicates that there is likely an issue relating to the particular industrial component or the underwater industrial setting. In embodiments, performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors; inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the underwater industrial setting or the underwater industrial setting and a degree of confidence corresponding to the prediction or classification; and selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification. In embodiments, selectively storing the one or more instances of sensor data includes storing the one or more instances of sensor data in the storage device with an expiry in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the underwater industrial setting and the underwater industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the underwater industrial setting and the underwater industrial setting, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry. In embodiments, selectively storing the one

or more instances of sensor data includes storing the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the underwater industrial setting that indicates that there is likely an issue relating to the particular industrial component or the underwater industrial setting.

[0125] In embodiments, the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

[0126] In embodiments, the self-configuring sensor kit network is a mesh network such that: the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors; and at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

[0127] In some embodiments, the self-configuring sensor kit network is a hierarchical network. In some of these embodiments, the sensor kit further includes one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device. In some of these embodiments, wherein each collection device is installed in a different respective section of the underwater industrial setting and collects sensor data from sensors of the plurality of sensors that are deployed in the respective section.

[0128] According to some embodiments of the present disclosure, a system for monitoring an industrial setting is disclosed. The system includes a set of sensor kits each having a set of sensors that are registered to respective industrial settings and configured to monitor physical characteristics of the industrial settings. The system also includes a set of communication gateway for communicating instances of sensor values from the sensor kits to a backend system. The backend system is configured to process the instances of sensor values to monitor the industrial setting, wherein upon receiving registration data for a sensor kit to an industrial setting, the backend system automatically configures and populates a dashboard for an owner or operator of the

industrial setting. The dashboard provides monitoring information that is based on the instances of sensor values for the industrial setting.

[0129] In embodiments, the registration of the sensor kit includes an interface for specifying a type of entity or industrial setting to be monitored. In some of these embodiments, the backend system configures the dashboard based on the registered type of entity or industrial setting. In
5 embodiments, the backend system includes an analytics facility that is configured based on the type of entity or industrial setting. In embodiments, the backend system includes a machine learning facility that is configured based on the type of entity or industrial setting.

[0130] In embodiments, the communication gateway is configured to provide a virtual container
10 for instances of sensor values such that only a registered owner or operator of the industrial setting can access the sensor values.

[0131] In embodiments, upon registration of a sensor kit to an industrial setting, a user may select a set or parameters for monitoring and wherein a set of services and capabilities of the backend system is automatically provisioned based on the selected parameters.

[0132] In embodiments, at least one of the sensor kit, the communication gateway and the backend
15 system includes an edge computation system for automatically calculating a metric for an industrial setting based on a plurality of instances of sensor values from a set of sensor kits.

[0133] In embodiments, the sensor kit is a self-configuring sensor kit network. In some
embodiments, the sensor kit network is a star network such that each sensor of the plurality of
20 sensors transmits respective instances of sensor data with the communication gateway directly using a short-range communication protocol. In some embodiments, computer-executable instructions cause one or more processors of the communication gateway device to initiate configuration of the self-configuring sensor kit network. In some embodiments, the self-configuring sensor kit network is a mesh network such that: a communication device of each sensor
25 of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors; and at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the communication gateway.

In some embodiments, the computer-executable instructions further cause the one or more
30 processors of the communication gateway to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the communication gateway initiating configuration of the self-configuring sensor kit network. In some embodiments, the self-configuring sensor kit network is a hierarchical network.

[0134] According to some embodiments of the present disclosure, a system for monitoring an
35 industrial setting is disclosed. The system includes: a set of sensor kits each having a set of sensors

that are registered to respective industrial settings and configured to monitor physical characteristics of the industrial settings; a set of communication gateways for communicating instances of sensor values from the sensor kits to a backend system; and said backend system for processing the instances of sensor values to monitor the industrial setting, wherein upon receiving registration data for a sensor kit to an industrial setting, the backend system automatically configures and populates a dashboard for an owner or operator of the industrial setting, wherein the dashboard provides monitoring information that is based on the instances of sensor values for the industrial setting. In some embodiments, the registration of the sensor kit includes an interface for specifying a type of entity or industrial setting to be monitored. In embodiments, the backend system configures the dashboard based on the registered type of entity or industrial setting. In some embodiments, the backend system includes an analytics facility that is configured based on the type of entity or industrial setting. In embodiments, the backend system includes a machine learning facility that is configured based on the type of entity or industrial setting.

[0135] In some embodiments, the communication gateway is configured to provide a virtual container for instances of sensor values such that only a registered owner or operator of the industrial setting can access the sensor values. In embodiments, upon registration of a sensor kit to an industrial setting, a user may select a set of parameters for monitoring and wherein a set of services and capabilities of the backend system is automatically provisioned based on the selected parameters. In some embodiments, at least one of the sensor kit, the communication gateway and the backend system includes an edge computation system for automatically calculating a metric for an industrial setting based on a plurality of instances of sensor values from a set of sensor kits.

[0136] In some embodiments, the sensor kit is a self-configuring sensor kit network. In some of these embodiments, the sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the communication gateway directly using a short-range communication protocol. In embodiments, computer-executable instructions cause one or more processors of the communication gateway device to initiate configuration of the self-configuring sensor kit network.

[0137] In some embodiments, the self-configuring sensor kit network is a mesh network such that: a communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors; and at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the communication gateway. In some of these embodiments, the computer-executable instructions further cause the one or more processors of the communication gateway to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the

mesh network in response to the communication gateway initiating configuration of the self-configuring sensor kit network. In some embodiments, the self-configuring sensor kit network is a hierarchical network.

5 [0138] According to some embodiments of the present disclosure, a method of monitoring a plurality of industrial settings using a set of sensors kits, a set of communication gateways, and a backend system is disclosed. The method includes: registering each sensor kit of the plurality of sensor kits to a respective industrial setting of the plurality of industrial settings; configuring each sensor kit of the plurality of sensor kits to monitor physical characteristics of the respective industrial setting to which the sensor kit is registered; transmitting, by each communication
10 gateway of the set of communication gateways, instances of sensor data from a respective sensor kit of the plurality of sensor kits to the backend system; processing, by the backend system, the instances of sensor data received from each sensor kit of the plurality of sensor kits; automatically configuring and populating, by the backend system, a dashboard for an owner or operator of the respective industrial setting upon receiving registration data for a sensor kit of the plurality of
15 sensor kits; and providing, by the dashboard, monitoring information that is based on the instances of sensor data for the respective industrial setting.

[0139] In some embodiments, registering each sensor kit includes providing an interface for specifying a type of entity or industrial setting to be monitored. In some of these embodiments, configuring each sensor kit to monitor physical characteristics of the respective industrial setting
20 includes configuring, by the backend system, the dashboard based on the registered type of entity or industrial setting. In some embodiments, the backend system includes an analytics facility that is configured based on the type of entity of the industrial setting. In embodiments, the backend system includes a machine learning facility that is configured based on the type of entity or industrial setting.

25 [0140] In some embodiments, the method further includes providing, by each communication gateway of the plurality of communication gateways, a virtual container for instances of sensor data such that only a registered owner or operator of the respective industrial setting can access the sensor data. In embodiments, upon registration of a sensor kit to an industrial setting, a user may select a set of parameters for monitoring. In some embodiments, the method further includes
30 automatically provisioning, by the backend system, a set of services and capabilities of the backend system based on the selected parameters. In embodiments, at least one of a sensor kit of the plurality of sensor kits, a communication gateway of the plurality of communication gateways, and the backend system includes an edge computation system for automatically calculating a metric for an industrial setting based on a plurality of instances of sensor data from a set of sensor kits.

[0141] In some embodiments, at least one sensor kit of the plurality of sensor kits is a self-configuring sensor kit network including a plurality of sensors. In some of these embodiments, the method further includes: capturing, by the plurality of sensors, sensor data; and transmitting, by the plurality of sensors, the sensor data to and edge device via the self-configuring sensor kit network. In some embodiments, transmitting the sensor data via the self-configuring sensor kit network includes directly transmitting, by each sensor of the plurality of sensors, instances of sensor data with the edge device using a short-range communication protocol, wherein the self-configuring sensor kit network is a star network. In some embodiments, the method further includes initiating, by the edge processing system, configuration of the self-configuring sensor kit network.

[0142] In embodiments, the self-configuring sensor kit network is a mesh network and each sensor of the plurality of sensors includes a communication device. In some of these embodiments, the method further includes: establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors; receiving, by at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device.

[0143] In some embodiments, the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices. In some embodiments, the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.

[0144] According to some embodiments of the present disclosure, a sensor kit configured for monitoring an industrial setting is disclosed. The sensor kit includes: an edge device; and a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of the plurality of sensors includes: a sensing component that captures sensor measurements and outputs instances of sensor data; a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol. The edge device includes: a communication system having: a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network; and a second communication device that transmits sensor kit packets to a backend system via a public

network; a processing system having one or more processors that execute computer-executable instructions that cause the processing system to: receive the reporting packets from the communication system; generate a data block based on sensor data obtained from the reporting packets, wherein the data block includes (i) a block header that defines an address of the data block and (ii) a block body that defines the sensor data and a parent address of another data block to which the data block will be linked; and transmit the data block to one or more node computing devices that collectively store a distributed ledger that is comprised of a plurality of data blocks.

[0145] In some embodiments, generating the data block includes generating a hash value of the block body. In embodiments, generating the data block includes encrypting the block body.

[0146] In some embodiments, the distributed ledger includes a smart contract that defines one or more conditions relating to collected sensor data and one or more actions that are initiated by the smart contract in response to the one or more conditions being satisfied. In some embodiments, the smart contract receives the data block from the sensor kit and determines whether the one or more conditions are satisfied based on at least the sensor data stored in the data block. In embodiments, the smart contract corresponds to an insurer. In some embodiments, the action defined in the smart contract triggers a transfer of funds to an account associated with an operator associated with the sensor kit in response to satisfying the one or more conditions. In embodiments, the one or more conditions include a first condition that determines whether the sensor kit has reported a sufficient amount of sensor data and a second condition that determines whether the reported sensor data indicates that the industrial setting is operating without issue.

[0147] In some embodiments, the smart contract corresponds to a regulatory body. In some of these embodiments, the action defined in the smart contract triggers an issuance of a token to an operator associated with the sensor kit in response to satisfying the one or more conditions. In embodiments, the one or more conditions include a first condition that requires a certain amount of reported sensor data to be reported by a sensor kit and a second condition that requires the reported sensor data to be compliant with the reporting regulations.

[0148] In some embodiments, the edge device is one of the node computing devices.

[0149] According to some embodiments of the present disclosure, a method for monitoring an industrial setting using a sensor kit having a plurality of sensors and an edge device including a processing system is disclosed. The method includes: receiving, by the processing system, reporting packets from one or more respective sensors of the plurality of sensors, wherein each reporting packet includes routing data and one or more instances of sensor data; generating, by the processing system, a data block based on sensor data obtained from the reporting packets, wherein the data block includes (i) a block header that defines an address of the data block and (ii) a block body that defines the sensor data and a parent address of another data block to which the data block

will be linked; and transmitting, by the processing system, the data block to one or more node computing devices that collectively store a distributed ledger that is comprised of a plurality of data blocks. In some embodiments, generating the data block includes generating, by the processing system, a hash value of the block body. In embodiments, generating the data block includes encrypting, by the processing system, the block body.

[0150] In some embodiments, the distributed ledger includes a smart contract that defines one or more conditions relating to collected sensor data and one or more actions that are initiated by the smart contract in response to the one or more conditions being satisfied. In some of these embodiments, the smart contract receives the data block from the sensor kit and determines whether the one or more conditions are satisfied based on at least the sensor data stored in the data block. In some embodiments, the smart contract corresponds to an insurer. In embodiments, the action defined in the smart contract triggers a transfer of funds to an account associated with an operator associated with the sensor kit in response to satisfying the one or more conditions. In some embodiments, the one or more conditions include a first condition that determines whether the sensor kit has reported a sufficient amount of sensor data and a second condition that determines whether the reported sensor data indicates that the industrial setting is operating without issue.

[0151] In some embodiments, the smart contract corresponds to a regulatory body. In some of these embodiments, the action defined in the smart contract triggers an issuance of a token to an operator associated with the sensor kit in response to satisfying the one or more conditions.

[0152] In some embodiments, the one or more conditions include a first condition that requires a certain amount of reported sensor data to be reported by a sensor kit and a second condition that requires the reported sensor data to be compliant with the reporting regulations.

[0153] In some embodiments, the edge device is one of the node computing devices.

[0154] In some embodiments, the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.

[0155] According to some embodiments of the present disclosure, a system is disclosed. The system includes: a backend system including one or more servers configured to deploy a smart contract to a distributed ledger on behalf of a user, wherein the smart contract defines one or more conditions relating to collected sensor data and one or more actions that are initiated by the smart contract in response to the one or more conditions being satisfied; a sensor kit configured for monitoring an industrial setting, the sensor kit including: an edge device; and a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of the plurality of sensors includes: a sensing component that captures sensor measurements and outputs instances of sensor data; a

processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol. The edge device includes: a communication system having a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network, and a second communication device that transmits sensor kit packets to a backend system via a public network; a processing system having one or more processors that execute computer-executable instructions that cause the processing system to: receive the reporting packets from the communication system; generate a data block based on sensor data obtained from the reporting packets, wherein the data block includes (i) a block header that defines an address of the data block and (ii) a block body that defines the sensor data and a parent address of another data block to which the data block will be linked; and transmit the data block to one or more node computing devices that collectively store a distributed ledger that is comprised of a plurality of data blocks.

[0156] In some embodiments, generating the data block includes generating a hash value of the block body. In some embodiments, generating the data block includes encrypting the block body.

[0157] In some embodiments, the smart contract receives the data block from the sensor kit and determines whether the one or more conditions are satisfied based on at least the sensor data stored in the data block. In some of these embodiments, the smart contract corresponds to an insurer. In some embodiments, the action defined in the smart contract triggers a transfer of funds to an account associated with an operator associated with the sensor kit in response to satisfying the one or more conditions. In embodiments, the one or more conditions include a first condition that determines whether the sensor kit has reported a sufficient amount of sensor data and a second condition that determines whether the reported sensor data indicates that the industrial setting is operating without issue. In some embodiments, the smart contract corresponds to a regulatory body. In embodiments, the action defined in the smart contract triggers an issuance of a token to an operator associated with the sensor kit in response to satisfying the one or more conditions. In some embodiments, the one or more conditions include a condition that determines whether the sensor kit has reported a required amount of sensor data as defined by a regulation.

[0158] In some embodiments, the edge device is one of the node computing devices.

[0159] According to some embodiments of the present disclosure, a method for monitoring an industrial setting using a sensor kit in communication with a backend system, the sensor kit including a plurality of sensors and an edge device, is disclosed. The method includes: deploying, by the backend system, a smart contract to a distributed ledger on behalf of a user, wherein the

smart contract defines one or more conditions relating to collected sensor data and one or more actions that are initiated by the smart contract in response to the one or more conditions being satisfied; receiving, by an edge processing system of the edge device, reporting packets from one or more respective sensors of the plurality of sensors, wherein each reporting packet includes routing data and one or more instances of sensor data; generating, by the edge processing system, a data block based on sensor data obtained from the reporting packets, wherein the data block includes (i) a block header that defines an address of the data block and (ii) a block body that defines the sensor data and a parent address of another data block to which the data block will be linked; and transmitting, by the edge processing system, the data block to one or more node computing devices that collectively store a distributed ledger that is comprised of a plurality of data blocks.

[0160] In some embodiments, generating the data block includes generating, by the edge processing system, a hash value of the block body. In embodiments, generating the data block includes encrypting, by the edge processing system, the block body.

[0161] In some embodiments, the distributed ledger receives the data block from the sensor kit and determines whether the one or more conditions of the smart contract are satisfied based on at least the sensor data stored in the data block. In some of these embodiments, the smart contract corresponds to an insurer. In embodiments, the action defined in the smart contract triggers a transfer of funds to an account associated with an operator associated with the sensor kit in response to satisfying the one or more conditions. In some embodiments, the one or more conditions include a first condition that determines whether the sensor kit has reported a sufficient amount of sensor data and a second condition that determines whether the reported sensor data indicates that the industrial setting is operating without issue.

[0162] In some embodiments, the smart contract corresponds to a regulatory body. In some of these embodiments, the action defined in the smart contract triggers an issuance of a token to an operator associated with the sensor kit in response to satisfying the one or more conditions. In some embodiments, the one or more conditions include a condition that determines whether the sensor kit has reported a required amount of sensor data as defined by a regulation. In embodiments, the edge device is one of the node computing devices. In some embodiments, the backend system is one of the node computing devices. In embodiments, the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.

[0163] A more complete understanding of the disclosure will be appreciated from the description and accompanying drawings and the claims, which follow.

BRIEF DESCRIPTION OF THE DRAWINGS

[0164] The accompanying drawings, which are included to provide a better understanding of the disclosure, illustrate embodiment(s) of the disclosure and together with the description serve to explain the principle of the disclosure. In the drawings:

5 [0165] FIG. 1 is a schematic illustrating an example of a sensor kit deployed in an industrial setting according to some embodiments of the present disclosure.

[0166] FIG. 2A is a schematic illustrating an example of a sensor kit network having a star network topology according to some embodiments of the present disclosure.

10 [0167] FIG. 2B is a schematic illustrating an example of a sensor kit network having a mesh network topology according to some embodiments of the present disclosure.

[0168] FIG. 2C is a schematic illustrating an example of a sensor kit network having a hierarchical network topology according to some embodiments of the present disclosure.

[0169] FIG. 3A is a schematic illustrating an example of a sensor according to some embodiments of the present disclosure.

15 [0170] FIG. 3B is a schematic illustrating an example schema of a reporting packet according to some embodiments of the present disclosure.

[0171] FIG. 4 is a schematic illustrating an example of an edge device of a sensor kit according to some embodiments of the present disclosure.

20 [0172] FIG. 5 is a schematic illustrating an example of a backend system that receives sensor data from sensor kits deployed in industrial settings according to some embodiments of the present disclosure.

[0173] FIG. 6 is a flow chart illustrating an example set of operations of a method for encoding sensor data captured by a sensor kit according to some embodiments of the present disclosure.

25 [0174] FIG. 7 is a flow chart illustrating an example set of operations of a method for decoding sensor data provided to a backend system by a sensor kit according to some embodiments of the present disclosure.

[0175] FIG. 8 is a flow chart illustrating an example set of operations of a method for encoding sensor data captured by a sensor kit using a media codec according to some embodiments of the present disclosure.

30 [0176] FIG. 9 is a flow chart illustrating an example set of operations of a method for decoding sensor data provided to a backend system by a sensor kit using a media codec according to some embodiments of the present disclosure.

35 [0177] FIG. 10 is a flow chart illustrating an example set of operations of a method for determining a transmission strategy and/or a storage strategy for sensor data collected by a sensor kit based on the sensor data, according to some embodiments of the present disclosure

[0178] FIGS. 11-15 are schematics illustrating different configurations of sensor kits according to some embodiments of the present disclosure.

[0179] FIG. 16 is a flowchart illustrating an example set of operations of a method for monitoring industrial settings using an automatically configured backend system, according to some
5 embodiments of the present disclosure.

[0180] FIG. 17 is a plan view of a manufacturing facility illustrating an exemplary implementation of a sensor kit including an edge device, according to some embodiments of the present disclosure.

[0181] FIG. 18 is a plan view of a surface portion of an underwater industrial facility illustrating an exemplary implementation of a sensor kit including an edge device, according to some
10 embodiments of the present disclosure.

[0182] FIG. 19 is a plan view of an indoor agricultural facility illustrating an exemplary implementation of a sensor kit including an edge device, according to some embodiments of the present disclosure.

15 DETAILED DESCRIPTION

[0183] Various configurations of sensor kits are disclosed. A sensor kit may be a purpose-configured system that includes sensors for monitoring a specific type of industrial setting, wherein the sensors are provided in a unified kit, optionally along with other devices, systems and components, such as ones that provide communication, processing and intelligence capabilities. In
20 embodiments, an owner or operator of an industrial setting may purchase or otherwise obtain the sensor kit. During the purchase process, the owner or operator, or a user associated with the industrial setting, may provide or indicate one or more features of the industrial setting (e.g., type of the setting, location of the setting, size of the setting, whether the setting is indoors or outdoors, the components and/or types of components being monitored, the number of each component
25 and/or type of component being monitored, and the like). In embodiments, the sensor kit may be preconfigured based on features and requirements of the industrial operator or owner. The sensor kit may be preconfigured such that the owner or operator may install the sensor kit in a “plug-and-play” manner, whereby the owner or operator does not need to configure a sensor kit network on which the devices of the sensor kit communicate.

30 [0184] FIG. 1 - Sensor Kit Environment

[0185] FIG. 1 is a schematic illustrating an industrial setting 120 at which a sensor kit 100 has been installed. In embodiments, the sensor kit 100 may refer to a fully deployable, purpose-configured industrial IoT system that is provided in a unified kit and is ready for deployment in the industrial setting 120 by a consumer entity (e.g., owner or operator of an industrial setting 120).

35 In embodiments, the sensor kit 100 allows the owner or operator to install and deploy the sensor

kit with no or minimal configuration (e.g., setting user permissions, setting passwords, and/or setting notification and/or display preferences). The term “sensor kit” 100 may refer to a set of devices that are installed in an industrial setting 120 (e.g., a factory, a mine, an oil field, an oil pipeline, a refinery, a commercial kitchen, an industrial complex, a storage facility, a building site, and the like). The collection of devices comprising the sensor kit 100 includes a set of one or more internet of things (IoT) sensors 102 and a set of one or more edge devices 104. For purposes of discussion, references to “sensors” or “sensor devices” should be understood to mean IoT sensors, unless specifically stated otherwise.

[0186] In embodiments, the sensor kit 100 includes a set of IoT sensors 102 that are configured for deployment in, on, or around an industrial component, a type of an industrial component (e.g., a turbine, a generator, a fan, a pump, a valve, an assembly line, a pipe or pipeline, a food inspection line, a server rack, and the like), an industrial setting 120, and/or a type of industrial setting 120 (e.g., indoor, outdoor, manufacturing, mining, drilling, resource extraction, underground, underwater, and the like) and a set of edge devices capable of handling inputs from the sensors and providing network-based communications. In embodiments, an edge device 104 may include or may communicate with a local data processing system (e.g., a device configured to compress sensor data, filter sensor data, analyze sensor data, issue notifications based on sensor data and the like) capable of providing local outputs, such as of signals and of analytic results that result from local processing. In embodiments, the edge device 104 may include or may communicate with a communication system (e.g., a Wi-Fi chipset, a cellular chipset, a satellite transceiver, cognitive radio, one or more Bluetooth chips and/or other networking device) that is capable of communicating data (e.g., raw and/or processed sensor data, notifications, command instructions, etc.) within and outside the industrial environment. In embodiments, the communication system is configured to operate without reliance on the main data or communication networks of an industrial setting 120. In embodiments, the communication system is provided with security capabilities and instructions that maintain complete physical and data separation from the main data or communication networks of an industrial setting 120. For example, in embodiments, Bluetooth-enabled edge devices may be configured to permit pairing only with pre-registered components of a kit, rather than with other Bluetooth-enabled devices in an industrial setting 120.

[0187] In embodiments, an IoT sensor 102 is a sensor device that is configured to collect sensor data and to communicate sensor data to another device using at least one communication protocol. In embodiments, IoT sensors 102 are configured for deployment in, on, or around a defined type of an industrial entity. The term industrial entity may refer to any object that may be monitored in an industrial setting 120. In embodiments, industrial entities may include industrial components (e.g., a turbine, a generator, a fan, a pump, a valve, an assembly line, a pipe or pipe line, a food

inspection line, a server rack, and the like). In embodiments, industrial entities may include organisms that are associated with an industrial setting 120 (e.g., humans working in the industrial setting 120 or livestock being monitored in the industrial setting 120). Depending on the intended use, setting, or purpose of the sensor kit 100, the configuration and form factor of an IoT sensor 102 will vary. Examples of different types of sensors include: vibration sensors, inertial sensors, temperature sensors, humidity sensors, motion sensors, LIDAR sensors, smoke/fire sensors, current sensors, pressure sensors, pH sensors, light sensors, radiation sensors, and the like.

[0188] In embodiments, an edge device 104 may be a computing device configured to receive sensor data from the one or more IoT sensors 102 and perform one or more edge-related processes relating to the sensor data. An edge-related process may refer to a process that is performed at an edge device 104 in order to store the sensor data, reduce bandwidth on a communication network, and/or reduce the computational resources required at a backend system. Examples of edge processes can include data filtering, signal filtering, data processing, compression, encoding, quick-predictions, quick-notifications, emergency alarming, and the like.

[0189] In embodiments, a sensor kit 100 is pre-configured such that the devices (e.g., sensors 102, edge devices 104, collection devices, gateways, etc.) within the sensor kit 100 are configured to communicate with one another via a sensor kit network without a user having to configure the sensor kit network. A sensor kit network may refer to a closed communication network that is established between the various devices of the sensor kit and that utilizes two or more different communication protocols and/or communication mediums to enable communication of data between the devices and to a broader communication network, such as a public communication network 190 (e.g., the Internet, a satellite network, and/or one or more cellular networks). For example, while some devices in a sensor kit network may communicate using a Bluetooth communication protocol, other devices may communicate with one another using a near-field communication protocol, a Zigbee protocol, and/or a Wi-Fi communication protocol. In some implementations, a sensor kit 100 may be configured to establish a mesh network having various devices acting as routing nodes within the sensor kit network. For example, sensors 102 may be configured to collect data and transmit the collected data to the edge device 104 via the sensor kit network, but may also be configured to receive and route data packets from other sensors 102 within the sensor kit network towards an edge device 104.

[0190] In embodiments, a sensor kit network may include additional types of devices. In embodiments, a sensor kit 100 may include one or more collection devices (not shown in FIG. 1) that act as routing nodes in the sensor network, such that the collection devices may be part of a mesh network. In embodiments, a sensor kit 100 may include a gateway device (not shown in FIG. 1) that enable communication with a broader network, whereby the gateway device may

communicate with the edge device 104 over a wired or wireless communication medium in industrial settings 120 that would prevent an edge device 104 from communicating with the public communication network 190 (e.g., in a factory having very thick concrete walls). Embodiments of the sensor kit 100 may include additional devices without departing from the scope of the disclosure.

[0191] In embodiments, the sensor kit 100 is configured to communicate with a backend system 150 via a communication network, such as the public communication network 190. In embodiments, the backend system 150 is configured to receive sensor data from a sensor kit 100 and to perform one or more backend operations on the received sensor data. Examples of backend operations may include storing the sensor data in a database, performing analytics tasks on the sensor data, providing the results of the analytics and/or visualizations of the sensor data to a user via a portal and/or a dashboard, training one or more machine-learned models using the sensor data, determining predictions and/or classifications relating to the operation of the industrial setting 120 and/or industrial devices of the industrial setting 120 based on the sensor data, controlling an aspect and/or an industrial device of the industrial setting 120 based on the predictions and/or classifications, issuing notifications to the user via the portal and/or the dashboard based on the predictions and/or classifications, and the like.

[0192] It is appreciated that in some embodiments, the sensor kit 100 may provide additional types of data to the backend system 150. For example, the sensor kit 100 may provide diagnostic data indicating any detected issues (e.g., malfunction, battery levels low, etc.) or potential issues with the sensors 102 or other devices in the sensor kit 100.

[0193] In embodiments, the sensor kit 100 is configured to self-monitor for failing components (e.g., failing sensors 102) and to report failing components to the operator. For example, in some embodiments, the edge device 104 may be configured to detect failure of a sensor 102 based on a lack of reporting from a sensor, a lack of response to requests (e.g., “pings”), and/or based on unreliable data (e.g., data regularly falling out of the expected sensor readings). In some embodiments, the edge device 104 can maintain a sensor kit network map indicating where each device in the sensor kit network is located and can provide approximate locations and/or identifiers of failed sensors to a user.

[0194] In embodiments, the sensor kit 100 may be implemented to allow post-installation configuration. A post-installation configuration may refer to an update to the sensor kit 100 by adding devices and/or services to the sensor kit 100 after the sensor kit 100 has been installed. In some of these embodiments, users (e.g., operators of the industrial setting 120) of the system may subscribe to or purchase certain edge “services.” For example, the sensor kit 100 may be configured to execute certain programs installed on one or more devices of the sensor kit 100 only if the user

has a valid subscription or ownership permission to access the edge service supported by the program. When the user no longer has the valid subscription and/or ownership permission, the sensor kit 100 may preclude execution of those programs. For example, a user may subscribe to unlock AI-based edge services, mesh networking capabilities, self-monitoring services, compression services, in-facility notifications, and the like.

[0195] In some embodiments, users can add new sensors 102 to the sensor kit post-installation in a plug-and-play-like manner. In some of these embodiments, the edge device 104 and the sensors 102 (or other devices to be added to the sensor kit 100) may include respective short-range communication capabilities (e.g., near-field communication (NFC) chips, RFID chips, Bluetooth chips, Wi-Fi adapters, and the like). In these embodiments, the sensors 102 may include persistent storage that stores identifying data (e.g., a sensor identifier value) and any other data that would be used to add the sensor 102 to the sensor kit 100 (e.g., an industrial device type, supported communication protocols, and the like). In some embodiments, a user may initiate a post-installation addition to the sensor kit 100 by pressing a button on the edge device 104, and/or by bringing the sensor 102 into the vicinity of the edge device 104. In some embodiments, in response to a user initiating a post-installation addition to the sensor kit, the edge device 104 may emit a signal (e.g., a radio frequency). The edge device 104 may emit the signal, for example, as a result of a human user pushing a button or at a predetermined time interval. The emitted signal may trigger a sensor 102 proximate enough to receive the signal and to transmit the sensor ID of the sensor 102 and any other suitable configuration data (e.g., device type, communication protocols, and the like). In response to the sensor 102 transmitting its configuration data (e.g., sensor ID and other relevant configuration data) to the edge device 104, the edge device 104 may add the sensor 102 to the sensor kit 100. Adding the sensor 102 to the sensor kit 100 may include updating a data store or manifest stored at the edge device 104 that identifies the devices of the sensor kit 100 and data relating thereto. Non-limiting examples of data that may be stored in the manifest relating to each respective sensor 102 may include the communication protocol used by the sensor 102 to communicate with the edge device 104 (or intermediate devices), the type of sensor data provided by the sensor 102 (e.g., vibration sensor data, temperature data, humidity data, etc.), models used to analyze sensor data from the sensor 102 (e.g., a model identifier), alarm limits associated with the sensor 102, and the like.

[0196] In embodiments, the sensor kit 100 (e.g., the edge device 104) may be configured to update a distributed ledger 162 with sensor data captured by the sensor kit 100. In embodiments, a distributed ledger 162 is a Blockchain or any other suitable distributed ledger 162. The distributed ledger 162 may be a public ledger or a private ledger. Private ledgers reduce power consumption requirements of maintaining the distributed ledger 162, while public ledgers consume more power

but offer more robust security. In embodiments, the distributed ledger 162 may be distributed amongst a plurality of node computing devices 160. The node computing devices 160 may be any suitable computing device, including physical servers, virtual servers, personal computing devices, and the like. In some embodiments, the node computing devices 160 are approved (e.g., via a consensus mechanism) before the node computing devices 160 may participate in the distributed ledger. In some embodiments, the distributed ledger 162 may be privately stored. For example, a distributed ledger may be stored amongst a set of preapproved node computing devices, such that the distributed ledger 162 is not accessible by non-approved devices. In some embodiments, the node computing devices 160 are edge devices 104 of the sensor kit 102 and other sensor kits 102.

10 [0197] In embodiments, the distributed ledger 162 is comprised of a set of linked data structures (e.g., blocks, data records, etc.), such that the linked data structures form an acyclic graph. For purposes of explanation, the data structures will be referred to as blocks. In embodiments, each block may include a header that includes a unique ID of the block and a body that includes the data that is stored in the block, and a pointer. In embodiments, the pointer is the block ID of a parent

15 block of the block, wherein the parent block is a block that was created prior to the block being written. The data stored in a respective block can be sensor data captured by a respective sensor kit 100. Depending on the implementation, the types of sensor data and the amount of sensor data stored in a respective body of a block may vary. For example, a block may store a set of sensor measurements from one or more types of sensors 102 of the sensor kit 100 captured over a period

20 of time (e.g., sensor data 102 captured from all of the sensors 102 in the sensor kit 100 over a period one hour or one day) and metadata relating thereto (e.g., sensor identifiers of each sensor measurement and a timestamp of each sensor measurement or group of sensor measurements). In some embodiments, a block may store sensor measurements determined to be anomalous (e.g., outside a standard deviation of expected sensor measurements or deltas in sensor measurements

25 that are above a threshold) and/or sensor measurements indicative of an issue or potential issue, and related metadata (e.g., sensor IDs of each sensor measurement and a timestamp of each sensor measurement or group of sensor measurements). In some embodiments, the sensor data stored in a block may be compressed and/or encoded sensor data, such that the edge device 104 compresses/encodes the sensor data into a more compact format. In embodiments, the edge device

30 104 may generate a hash of the body, such that the contents of the body (e.g., block ID of the parent block and the sensor data) are hashed and cannot be altered without changing the value of the hash. In embodiments, the edge device 104 may encrypt the content within the block, so that the content may not be read by unauthorized devices.

[0198] As mentioned, the distributed ledger 162 may be used for different purposes. In some

35 embodiments, the distributed ledger 162 may further include one or more smart contracts. A smart

contract is a self-executing digital contract. A smart contract may include code (e.g., executable instructions) that defines one or more conditions that trigger one or more actions. A smart contract may be written by a developer in a scripting language (e.g., JavaScript), an object code language (e.g., Java), or a compiled language (e.g., C++ or C). Once written, a smart contract may be encoded in a block and deployed to the distributed ledger 162. In embodiments, the backend system 150 is configured to receive the smart contract from a user and write the smart contract to a respective distributed ledger 162. In embodiments, an address of the smart contract (e.g., the block ID of the block containing the smart contract) may be provided to one or more parties to the smart contract, such that respective parties may invoke the smart contract using the address. In some embodiments, the smart contract may include an API that allows a party to provide data (e.g., addresses of blocks) and/or to transmit data (e.g., instructions to transfer funds to an account).

[0199] In example implementations, an insurer may allow insured owners and/or operators of an industrial setting 120 to agree to share sensor data with the insurer to demonstrate that the equipment in the facility is functioning properly and, in return, the insurer may issue a rebate or refund to the owners and/or operators if the owners and/or operators are compliant with an agreement with the insurers. Compliance with the agreement may be verified electronically by participant nodes in the distributed ledger and/or the sensor kit 100 via a smart contract. In embodiments, the insurer may deploy the smart contract (e.g., by adding the smart contract to a distributed ledger 162) that triggers the issuance of rebates or refunds on portions of insurance premiums when the sensor kit 100 provides sufficient sensor data to the insurer via the distributed ledger that indicates the facility is operating without issue. In some of these embodiments, the smart contract may include a first condition that requires a certain amount of sensor data to be reported by a facility and a second condition that each instance of the sensor data equals a value (e.g., there are no classified or predicted issues) or range of values (e.g., all sensor measurements are within a predefined range of values). In some embodiments, the action taken in response to one or more of the conditions being met may be to deposit funds (e.g., a wire transfer or cryptocurrency) into an account. In this example, the edge device 104 may write blocks containing sensor data to the distributed ledger. The edge device 104 may also provide the addresses of these blocks to the smart contract (e.g., using an API of the smart contract). Upon the smart contract verifying the first and second conditions of the contract, the smart contract may initiate the transfer of funds from an account of the insurer to the account of the insured.

[0200] In another example, a regulatory body (e.g., a state, local, or federal regulatory agency) may require facility operators to report sensor data to ensure compliance with one or more regulations. For instance, the regulatory body may regulate food inspection facilities, pharmaceutical manufacturing facilities, e.g., manufacturing facility 1700, indoor agricultural

facilities, e.g., indoor agricultural facility 1800, offshore oil extraction facilities, e.g., underwater industrial facility 1900, or the like. In embodiments, the regulatory body may deploy a smart contract that is configured to receive and verify the sensor data from an industrial setting 120, and in response to verifying the sensor data issues a compliance token (or certificate) to an account of the facility owner. In some of these embodiments, the smart contract may include a condition that requires a certain amount of sensor data to be reported by a facility and a second condition that requires the sensor data to be compliant with the reporting regulations. In this example, the edge device 104 may write blocks containing sensor data to the distributed ledger 162. The edge device 104 may also provide the addresses of these blocks to the smart contract (e.g., using an API of the smart contract). Upon the smart contract verifying the first and second conditions of the contract, the smart contract may generate a token indicating compliance by the facility operator and may initiate the transfer of funds to an account (e.g., a digital wallet) associated with the facility.

[0201] A distributed ledger 162 may be adapted for additional or alternative applications without departing from the scope of the disclosure.

[0202] FIGS. 2A, 2B, and 2C - Components and Networking

[0203] FIGS. 2A, 2B, and 2C illustrate example configurations of a sensor kit network 200. Depending on the sensor kit 100 and the industrial setting 120 that the sensor kit 100 is installed in, the sensor kit network 200 may communicate in different manners.

[0204] FIG. 2A illustrates an example sensor kit network 200A that is a star network. In these embodiments, the sensors 102 communicate directly with the edge device 104. In these embodiments, the communication protocol(s) utilized by the sensor devices 102 and the edge device 104 to communicate are based on one or more of the physical area of the sensor kit network 102, the power sources available, and the types of sensors 102 in the sensor kit 100. For example, in settings where the area being monitored is a relatively small area and where the sensors 102 are not able to connect to a power supply, the sensors 102 may be fabricated with a Bluetooth Low Energy (BLE) microchip that communicates using a Bluetooth Low Energy protocol (e.g., the Bluetooth 5 protocol maintained by the Bluetooth Special Interest Group). In another example, in a relatively small area where lots of sensors 102 are to be deployed, the sensors 102 may be fabricated with the Wi-Fi microchip that communicates using the IEEE 802.11 protocol. In the embodiments of FIG. 2A, the sensors 102 may be configured to perform one-way or two-way communication. In embodiments where the edge device 104 does not need to communicate data and/or instructions to the sensors 102, the sensors 102 may be configured for one-way communication. In embodiments where the edge device 104 does communicate data and/or instructions to the sensors 102, the sensors 102 may be configured with transceivers that perform

two-way communication. A star network may be configured with devices having other suitable communication devices without departing from the scope of the disclosure.

[0205] FIG. 2B illustrates an example sensor kit network 200B that is a mesh network where the nodes (e.g., sensors 102) connect to each other directly, dynamically, and/or non-hierarchically to cooperate with one another to efficiently route data to and from the edge device 104. In some embodiments, the devices in the mesh network (e.g., the sensors 102, the edge device 104, and/or any other devices in the sensor kit network 200B) may be configured to self-organize and self-configure the mesh network, such that the sensors 102 and/or the edge device 104 may determine which devices route data on behalf of other devices, and/or redundancies for transmission should a routing node (e.g., sensor 102) fail. In embodiments, the sensor kit 100 may be configured to implement a mesh network in industrial settings 120 where the area being monitored is relatively large (e.g., greater than 100 meters in radius from the edge device 104) and/or where the sensors 102 in the sensor kit 100 are intended to be installed in close proximity to one another. In the latter scenario, the power consumption of each individual sensor 102 may be reduced in comparison to sensors 102 in a star network, as the distance that each respective sensor 102 needs to transmit over is relatively less than the distance that the respective sensor 102 would need to transmit over in a star network. In embodiments, a sensor 102 may be fabricated with a Zigbee® microchips, a Digi XBee® microchip, a Bluetooth Low Energy microchip, and/or any other suitable communication devices configured to participate in a mesh network.

[0206] FIG. 2C illustrates an example of a sensor kit network 200C that is a hierarchical network. In these embodiments, the sensor kit 100 includes a set of collection devices 206. A collection device 206 may refer to a non-sensor device that receives sensor data from a sensor device 104 and routes the sensor data to an edge device 104, either directly or via another collection device 206. In embodiments, a hierarchical network may refer to a network topography where one or more intermediate devices (e.g., collection devices 206) route data from one or more respective peripheral devices (e.g., sensor devices 102) to a central device (e.g., edge device 104). A hierarchical network may include wired and/or wireless connections. In embodiments, a sensor device 102 may be configured to communicate with a collection device 206 via any suitable communication device (e.g., Bluetooth Low Energy microchips, Wi-Fi microchips, Zigbee microchips, or the like). In embodiments, hierarchical sensor kit networks may be implemented in industrial settings 120 where power sources are available to power the collection devices 206 and/or where the sensors 102 are likely to be spaced too far apart to support a reliable mesh network.

[0207] The examples of FIGS. 2A-2C are provided for examples of different topologies of a sensor kit network. These examples are not intended to limit the types of sensor kit networks 200 that may

be formed by a sensor kit 100. Furthermore, sensor kit networks 200 may be configured as hybrids of star networks, hierarchical networks, and/or mesh networks, depending on the industrial settings 120 in which respective sensor kits 200 are being deployed.

[0208] FIGS. 3A, 3B, 4, and 5 – Example Configurations of Sensors, Edge Devices, and Backend Systems

[0209] FIG. 3A illustrates an example IoT sensor 102 (or sensor) according to embodiments of the present disclosure. Embodiments of the IoT sensor 102 may include, but are not limited to, one or more sensing components 302, one or more storage devices 304, one or more power supplies 306, one or more communication devices 308, and a processing device 310. In embodiments, the processing device 310 may execute an edge reporting module 312.

[0210] A sensor 102 includes at least one sensing component 302. A sensing component 302 may be any digital, analog, chemical, and/or mechanical component that outputs raw sensor data to the processing device 310. It is appreciated that different types of sensors 102 are fabricated with different types of sensing components. In embodiments, sensing components 302 of an inertial sensor may include one or more accelerometers and/or one or more gyroscopes. In embodiments, sensing components 302 of a temperature sensor may include one or more thermistors or other temperature sensing mechanisms. In embodiments, sensing components 302 of a heat flux sensor may include, for example, thin film sensors, surface mount sensors, polymer-based sensors, chemical sensors and others. In embodiments, sensing components 302 of a motion sensor may include a LIDAR device, a radar device, a sonar device, or the like. In embodiments, sensing components 302 of an occupancy sensor may include a surface being monitored for occupancy, a pressure activated switch embedded under the surface of the occupancy sensor and/or a piezoelectric element integrated into the surface of the occupancy sensor, such that an electrical signal is generated when an object occupies the surface being monitored for occupancy. In embodiments, sensing components 302 of a humidity sensor may include a capacitive element (e.g., a metal oxide between two electrodes) that outputs an electrical capacity value corresponding to the ambient humidity; a resistive element that includes a salt medium having electrodes on two sides of the medium, whereby the variable resistance measured at the electrodes corresponds to the ambient humidity; and/or a thermal element that includes a first thermal sensor that outputs a temperature of a dry medium (e.g., dry nitrogen) and a second thermal sensor that outputs an ambient temperature of the sensor's environment, such that the humidity is determined based on the change, i.e., the delta, between the temperature in the dry medium and the ambient temperature. In embodiments, sensing components 302 of a vibration sensor may include accelerometer components, position sensing components, torque sensing components, and others. It is appreciated that the list of sensor types and sensing components thereof is provided for example.

Additional or alternative types of sensors and sensing components may be integrated into a sensor 102 without departing from the scope of the disclosure. Furthermore, in some embodiments, the sensors 102 of a sensor kit 100 may include audio, visual, or audio/visual sensors, in addition to non-audio/visual sensors 102 (i.e., sensors that do not capture video or audio). In these
5 embodiments, the sensing components 392 may include a camera and/or one or more microphones. In some embodiments, the microphones may be directional microphones, such that a direction of a source of audio may be determined.

[0211] A storage device 304 may be any suitable medium for storing data that is to be transmitted to the edge device 104. In embodiments, a storage device 304 may be a persistent storage medium,
10 such as a flash memory device. In embodiments, a storage device 304 may be a transitory storage medium, such as a random access memory device. In embodiments, a storage device 304 may be a circuit configured to store charges, whereby the magnitude of the charge stored by the component is indicative of a sensed value, or incremental counts. In these embodiments, this type of storage device 304 may be used where power availability and size are concerns, and/or where the sensor
15 data is count-based (e.g., a number of detection events). It is appreciated that any other suitable storage devices 304 may be used. In embodiments, the storage device 304 may include a cache 314, such that the cache 314 stores sensor data that is not yet reported to the edge device 104. In these embodiments, the edge reporting module 312 may clear the cache 314 after the sensor data being stored in the cache 314 is transmitted to the edge device 104.

[0212] A power supply 306 is any suitable component that provides power to the other components of the sensor 102, including the sensing components 302, storage devices 304, communication devices 306, and/or the processing device 308. In embodiments, a power supply 306 includes a wired connection to an external power supply (e.g., alternating current delivered from a power outlet, or direct current delivered from a battery or solar power supply). In embodiments, the power
25 supply 306 may include a power inverter that converts alternating currents to direct currents (or vice-versa). In embodiments, a power supply 306 may include an integrated power source, such as a rechargeable lithium ion battery or a solar element. In embodiments, a power supply 306 may include a self-powering element, such as a piezoelectric element. In these embodiments, the piezoelectric element may output a voltage upon a sufficient mechanical stress or force being applied to the element. This voltage may be stored in a capacitor and/or may power a sensing
30 element 302. In embodiments, the power supply may include an antenna (e.g., a receiver or transceiver) that receives a radio frequency that energizes the sensor 102. In these embodiments, the radio frequency may cause the sensor 102 to “wake up” and may trigger an action by the sensor 102, such as taking sensor measurements and/or reporting sensor data to the edge device 104. A
35 power supply 306 may include additional or alternative components as well.

[0213] In embodiments, a communication device 308 is a device that enables wired or wireless communication with another device in the sensor kit network 200. In most sensor kit configurations 100, the sensors 102 are configured to communicate wirelessly. In these embodiments, a communication device 308 may include a transmitter or transceiver that transmits data to other devices in the sensor kit network 200. Furthermore, in some of these embodiments, communication devices 308 having transceivers may receive data from other devices in the sensor kit network 200. In wireless embodiments, the transceiver may be integrated into a chip that is configured to perform communication using a respective communication protocol. In some embodiments, a communication device 308 may be a Zigbee® microchip, a Digi XBee® microchip, a Bluetooth microchip, a Bluetooth Low Energy microchip, a Wi-Fi microchip, or any other suitable short-range communication microchip. In embodiments where the sensor kit 200 supports a mesh network, the communication device 308 may be a microchip that implements a communication protocol that supports mesh networking (e.g., ZigBee PRO mesh networking protocol, Bluetooth Mesh, 802.11a/b/g/n/ac, and the like). In these embodiments, a communication device 308 may be configured to establish the mesh network and handle the routing of data packets received from other devices in accordance with the communication protocol implemented by the communication device 308. In some embodiments, a sensor 102 may be configured with two or more communication devices 308. In these embodiments, the sensors 102 may be added to different sensor kit 100 configurations and/or may allow for flexible configuration of the sensor kit 102 depending on the industrial setting 120.

[0214] In embodiments, the processing device 310 may be a microprocessor. The microprocessor may include memory (e.g., read-only memory (ROM)) that stores computer-executable instructions and one or more processors that execute the computer-executable instructions. In embodiments, the processing device 310 executes an edge reporting module 312. In embodiments, the edge reporting module 312 is configured to transmit data to the edge device 104. Depending on the configuration of the sensor kit network 200 and location of the sensors 102 with respect to the edge device 104, the edge reporting module 312 may transmit data (e.g., sensor data) either directly to the edge device 104, or to an intermediate device (e.g., a collection device 206 or another sensor device 102) that routes the data towards the edge device 104. In embodiments, the edge reporting module 312 obtains raw sensor data from a sensing component 302 or from a storage device 304 and packetizes the raw sensor data into a reporting packet 320.

[0215] FIG. 3B illustrates an example reporting packet 320 according to some embodiments of the present disclosure. In some of these embodiments, the edge reporting module 312 may populate a reporting packet template to obtain a reporting packet 320. In embodiments, a reporting packet 320 may include a first field 322 indicating a sensor ID of the sensor 102 and a second field 326

indicating the sensor data. Additionally, the reporting packet 320 may include additional fields, such as a routing data field 324 indicating a destination of the packet (e.g., an address or identifier of the edge device 104), a time stamp field 328 indicating a time stamp, and/or a checksum field 330 indicating a checksum (e.g., a hash value of the contents of the reporting packet). The reporting packet may include additional or alternative fields (e.g., error codes) without departing from the scope of the disclosure.

[0216] Referring back to FIG. 3A, in embodiments, the edge reporting module 312 may generate a reporting packet 320 for each instance of sensor data. Alternatively, the edge reporting module 312 may generate a reporting packet 320 that includes a batch of sensor data (e.g., the previous N sensor readings or all the sensor readings maintained in a cache 314 of the sensor 102 since the cache 314 was last purged). Upon generating a reporting packet 320, the edge reporting module 312 may output the reporting packet 320 to the communication device 308, which transmits the reporting packet 320 to the edge device 104 (either directly or via one or more intermediate devices). The edge reporting module 312 may generate and transmit reporting packets 320 at predetermined intervals (e.g., every second, every minute, every hour), continuously, or upon being triggered (e.g., upon being activated via the power supply or upon being command by the edge device 104).

[0217] In embodiments, the edge reporting module 312 instructs the sensing component(s) 302 to capture sensor data. In embodiments, the edge reporting module 312 may instruct a sensing component 302 to capture sensor data at predetermined intervals. For example, the edge reporting module 312 may instruct the sensing component 302 to capture sensor data every second, every minute, or every hour. In embodiments, the edge reporting module 312 may instruct a sensing component 302 to capture sensor data upon the power supply 306 being energized. For example, the power supply 306 may be energized by a radio frequency or upon a pressure-switch being activated and closing a circuit. In embodiments, the edge reporting module 312 may instruct a sensing component 302 to capture sensor data in response to receiving a command to report sensor data from the edge device 104 or a human user (e.g., in response to the user pressing a button).

[0218] In embodiments, a sensor 102 includes a housing (not shown). The sensor housing may have any suitable form factor. In embodiments where the sensor 102 is being used outdoors, the sensor may have a housing that is waterproof and/or resistant to extreme cold and/or extreme heat. In embodiments, the housing may have suitable coupling mechanisms to removably couple to an industrial component.

[0219] The foregoing is an example of a sensor 102. The sensor 102 may have additional or alternative components without departing from the scope of the disclosure.

[0220] FIG. 4 illustrates an example of an edge device 104. In embodiments, the edge device 104 may include a storage system 402, a communication system 404, and a processing system 406. The edge device 104 may include additional components not shown, such as a power supply, a user interface, and the like.

5 [0221] The storage system 402 includes one or more storage devices. The storage devices may include persistent storage mediums (e.g., flash memory drive, hard disk drive) and/or transient storage devices (e.g., RAM). The storage system 402 may store one or more data stores. A data store may include one or more databases, tables, indexes, records, filesystems, folders and/or files. In the illustrated embodiments, the storage device stores a configuration data store 410, a sensor
10 data store 412, and a model data store 414. A storage system 402 may store additional or alternative data stores without departing from the scope of the disclosure.

[0222] In embodiments, the configuration data store 410 stores data relating to the configuration of the sensor kit 100, including the devices of the sensor kit 100. In some embodiments, the configuration data store 410 may maintain a set of device records. The device records may indicate
15 a device identifier that uniquely identifies a device of the sensor kit 100. The device records may further indicate the type of device (e.g., a sensor, a collection device, a gateway device, etc.). In embodiments where the network paths from each device to the edge device 104 do not change, a device record may also indicate the network path of the device to the edge device 104 (e.g., any intermediate devices in the device's network path). In the case that a device record corresponds to
20 a sensor 102, the device record may indicate the type of sensor (e.g., a sensor type identifier) and/or a type of data that is provided by the sensor 102.

[0223] In embodiments, the configuration data store 410 may maintain a set of sensor type records, where each record corresponds to a different type of sensor 102 in the sensor kit 100. A sensor type record may indicate a type identifier that identifies the type of sensor and/or the type of sensor
25 data provided by the sensor. In embodiments, a sensor type record may further indicate relevant information relating to the sensor data, including maximum or minimum values of the sensor data, error codes output by sensors 102 of the sensor type, and the like.

[0224] In embodiments, the configuration data store 410 may maintain a map of the sensor kit network 200. The map of the sensor kit network 200 may indicate a network topology of the sensor
30 kit network 200, including network paths of the collection of devices in the sensor kit 100. In some embodiments, the map may include physical locations of the sensors as well. The physical location of a sensor 102 may be defined as a room or area that the sensor 102 is in, a specific industrial component that the sensor 102 is monitoring, a set of coordinates relative of the edge device 104 (e.g., x, y, z coordinates relative to the edge device 104, or an angle and distance of the sensor 102

relative to the edge device 104), an estimated longitude and latitude of the sensor 102, or any other suitable format of relative or absolute location determination and/or measurement.

[0225] In embodiments, a sensor data store 412 stores sensor data collected from the sensors 102 of the sensor kit 100. In embodiments, the sensor data store 412 maintains sensor data that is collected over a period of time. In some of these embodiments, the sensor data store 412 may be a cache that stores sensor data until it is reported and backed up at the backend system 150. In these embodiments, the cache may be cleared when sensor data is reported to the backend system 150. In some embodiments, the sensor data store 412 stores all sensor data collected by the sensor kit 412. In these embodiments, the sensor data store 412 may provide a backup for all the sensor data collected by the sensor kit 100 over time, thereby ensuring that the owner of the sensor kit 100 maintains ownership of its data.

[0226] In embodiments, a model data store 414 stores machine-learned models. The machine-learned models may include any suitable type of models, including neural networks, deep neural networks, recursive neural networks, Bayesian neural networks, regression-based models, decision trees, prediction trees, classification trees, Hidden Markov Models, and/or any other suitable types of models. A machine-learned model may be trained on training data, which may be expert generated data, historical data, and/or outcome-based data. Outcome-based data may be data that is collected after a prediction or classification is made that indicates whether the prediction or classification was correct or incorrect and/or a realized outcome. A training data instance may refer to a unit of training data that includes a set of features and a label. In embodiments, the label in a training data instance may indicate a condition of an industrial component or an industrial setting 120 at a given time. Examples of conditions will vary greatly depending on the industrial setting 120 and the conditions that the machine-learned model is being trained to predict or classify. Examples of labels in a manufacturing facility may include, but are not limited to, no issues detected, a mechanical failure of a component, an electrical failure of a component, a chemical leak detected, and the like. Examples of labels in a mining facility may include, but are not limited to, no issues detected, an oxygen deficiency, the presence of a toxic gas, a failing structural component, and the like. Examples of labels in an oil and/or gas facility (e.g., oil field, gas field, oil refinery, pipeline) may include, but are not limited to, no issues detected, a mechanical failure of a component (e.g., a failed valve or failed O-ring), a leak, and the like. Examples of labels in an indoor agricultural facility may include, but are not limited to, no issues detected, a plant died, a plant wilted, a plant turned a certain color (e.g., brown, purple, orange, or yellow), mold found, and the like. In each of these examples, there are certain features that may be relevant to a condition and some features that may have little or no bearing on the condition. Through a machine-learning process (which may be performed at the backend system 150 or another system), the model is

trained to determine predictions or classifications based on a set of features. Thus, the set of features in a training data instance may include sensor data that is temporally proximate to a time when a condition of the industrial component or industrial setting 120 occurred (e.g., the label associated with the industrial component or industrial setting 120).

5 [0227] In embodiments, the machine-learned models may include prediction models that are used to predict potential issues relating to an industrial component being monitored. In some of these embodiments, a machine-learned model may be trained on training data (expert generated data and/or historical data) that corresponds to one or more conditions relating to a particular component. In some of these embodiments, the training data sets may include sensor data
10 corresponding to scenarios where maintenance or some intervening action was later required and sensor data corresponding to scenarios where maintenance or some intervening action was ultimately not required. In these example embodiments, the machine-learned model may be used to determine a prediction of one or more potential issues that may arise with respect to one or more industrial components being monitored and/or the industrial setting 120 being monitored.

15 [0228] In embodiments, the machine-learned models may include classification models that classify a condition of an industrial component being monitored and/or the industrial setting 120. In some of these embodiments, a machine-learned model may be trained on training data (e.g., expert generated data and/or historical data) that corresponds to one or more conditions relating to a particular component. In some of these embodiments, the training data sets may include sensor
20 data corresponding to scenarios where respective industrial components and/or respective industrial settings 120 were operating in a normal condition and sensor data where the respective industrial components and/or respective industrial settings 120 were operating in an abnormal condition. In training data instances where there was an abnormal condition, the training data instance may include a label indicating the type of abnormal condition. For example, a training
25 data instance corresponding to an indoor agricultural facility that was deemed too humid for ideal growing conditions may include a label that indicates the facility was too humid.

[0229] In embodiments, the communication system 404 includes two or more communication devices, including at least one internal communication device that communicates with the sensor kit network 200 and at least one external communication device that communicates with a public
30 communication network (e.g., the Internet) either directly or via a gateway device. The at least one internal communication devices may include Bluetooth chips, Zigbee chips, XBee chips, Wi-Fi chips, and the like. The selection of the internal communication devices may depend on the environment of the industrial setting 120 and the impacts thereof on the sensors 102 to be installed therein (e.g., whether the sensors 102 have reliable power sources, whether the sensors 102 will be
35 spaced in proximity to one another, whether the sensors 102 need to transmit through walls, and

the like). The external communication devices may perform wired or wireless communication. In embodiments, the external communication devices may include cellular chipsets (e.g., 4G or 5G chipsets), Ethernet cards, satellite communication cards, or other suitable communication devices. The external communication device(s) of an edge device 104 may be selected based on the environment of the industrial setting 120 (e.g., indoors v. outdoors, thick walls that prevent wireless communication v. thin walls that allow wireless communication, located near cellphone towers v. located in remote areas) and the preferences of an operator of the industrial setting 120 (e.g., the operator allows the edge device 104 to access a private network of the industrial setting 120, or the operator does not allow the edge device 104 to access a private network of the industrial setting 120).

[0230] In embodiments, the processing system 406 may include one or more memory devices (e.g., ROM and/or RAM) that store computer-executable instructions and one or more processors that execute the computer-executable instructions. The processing system 406 may execute one or more of a data processing module 420, an encoding module 422, a quick-decision AI module 424, a notification module 426, a configuration module 428, and a distributed ledger module 430. The processing system 406 may execute additional or alternative modules without departing from the scope of the disclosure. Furthermore, the modules discussed herein may include submodules that perform one or more functions of a respective module.

[0231] In embodiments, the data processing module 420 receives sensor data from the sensor kit network 200 and performs one or more data processing operations on the received sensor data. In embodiments, the data processing module 420 receives reporting packets 320 containing sensor data. In some of these embodiments, the data processing module 420 may filter data records that are duplicative (e.g., filtering out one out of two reporting packets 320 received from two respective sensors monitoring the same component for redundancy). The data processing module 420 may additionally or alternatively filter and/or flag reporting packets 320 containing sensor data that is clearly erroneous (e.g., sensor not within a tolerance range given the type of sensor 102 or contains an error code). In embodiments, the data processing module 420 may store and/or index the sensor data in the sensor data store.

[0232] In embodiments, the data processing module 420 may aggregate sensor data received over a period of time from the sensors 102 of the sensor kit 100 or a subset thereof and may transmit the sensor data to the backend system 150. In transmitting sensor data to the backend system 150, the data processing module 420 may generate a sensor kit reporting packet that includes one or more instances of sensor data. The sensor data in the sensor kit reporting packet may be compressed or uncompressed. In embodiments, the sensor kit reporting packet may indicate a sensor kit identifier that identifies the source of the data packet to the backend system 150. In embodiments,

the data processing module 420 may transmit the sensor data upon receipt of the sensor data from a sensor 102, at predetermined intervals (e.g., every second, every minute, every hour, every day), or in response to a triggering condition (e.g., a prediction or classification that there is an issue with an industrial component or the industrial setting 120 based on received sensor data). In some
5 embodiments, the sensor data may be encoded/compressed, such that sensor data collected from multiple sensors 102 and/or over a period of time may be more efficiently transmitted. In embodiments, the data processing module 420 may leverage the quick-decision AI module 424 to determine whether the industrial components of the industrial setting 120 and/or the industrial setting 120 itself is likely in a normal condition. If the quick-decision AI module 424 determines
10 that the industrial components and/or the industrial setting 120 are in a normal condition with a high degree of certainty, then the data processing module 420 may delay or forgo transmitting the sensor data used to make the classification to the backend system 150. Additionally or alternatively, if the quick-decision AI module 424 determines that the industrial components and/or the industrial setting 120 are in a normal condition with a high degree of certainty, then the data
15 processing module 420 may compress the sensor data and may be compressed at a greater rate. The data processing module 420 may perform additional or alternative functions without departing from the scope of the disclosure.

[0233] In embodiments, the encoding module 422 receives sensor data and may encode, compress, and/or encrypt the sensor data. The encoding module 422 may employ other techniques to
20 compress the sensor data. In embodiments, the encoding module 422 may employ horizontal or compression techniques to compress the sensor data. For example, the encoding module 422 may use the Lempel-Zev-Welch algorithm or variations thereof. In some embodiments, the encoding module 522 may represent sensor data in an original integer or “counts format” and with relevant calibration coefficients and offsets at the time of collection. In these embodiments, the coefficients
25 and offsets may be coalesced at the time of collection when a precise signal path is known, such that one floating-point coefficient and one integer offset is stored for each channel.

[0234] In embodiments, the encoding module 422 may employ one or more codecs to compress the sensor data. The codecs may be proprietary codecs and/or publicly available codecs. In some embodiments, the encoding module 422 may use a media compression codec (e.g., a video
30 compression codec) to compress the sensor data. For example, the encoding module 422 may normalize the sensor data into values that fall within a range and format of a media frame (e.g., normalizing sensor data into acceptable pixel values for inclusion into a video frame) and may embed the normalized sensor data into the media frame. The encoding module 422 may embed the normalized sensor data collected from the sensors 102 of the sensor kit 100 into the media frame
35 according to a predefined mapping (e.g., a mapping of respective sensors 102 to one or more

respective pixels in a media frame). The encoding module 422 may generate a set of consecutive media frames in this manner and may compress the media frames using a media codec (an H.264/MPEG-4 codec, an H.265/MPEG-H codec, an H.263/MPEG-4 codec, proprietary codecs, and the like) to obtain a sensor data encoding. The encoding module 422 may then transmit sensor data encoding to the backend system, which may decompress and recalculate the sensor data based on the normalized values. In these embodiments, the codec used for compression and the mappings of sensors to pixels may be selected to reduce lossiness or to increase compression rates. Furthermore, the foregoing technique may be applied to sensor data that tends to be more static and less changing between samplings and/or where sensor data collected from different sensors tend to have little variation when sampled at the same time. The encoding module 422 may employ additional or alternative encoding/compression techniques without departing from the scope of the disclosure.

[0235] In embodiments, the quick-decision AI module 424 may utilize a limited set of machine-learned models to generate predictions and/or classifications of a condition of an industrial component being monitored and/or of the industrial setting 120 being monitored. In embodiments, the quick-decision AI module 424 may receive a set of features (e.g., one or more sensor data values) and request for a specific type of prediction or classification based thereon. In embodiments, the quick-decision AI module 424 may leverage a machine-learned model corresponding to the requested prediction or classification. The quick-decision AI module 424 may generate a feature vector based on the received features, such that the feature vector includes one or more sensor data values obtained from one or more sensors 102 of the sensor kit 100. The quick-decision AI module 424 may feed the feature vector to the machine-learned model. The machine-learned model may output a prediction or classification and a degree of confidence in the prediction or classification. In embodiments, the quick-decision AI module 424 may output the prediction or classification to the data processing module 420 (or another module that requested a prediction or classification). For example, in embodiments the data processing module 420 may use classifications that the industrial components and/or the industrial setting 120 are in a normal condition to delay or forgo transmission of sensor data and/or to compress sensor data. In embodiments, the data processing module 420 may use a prediction or classification that the industrial components and/or the industrial setting 120 are likely to encounter a malfunction to transmit uncompressed sensor data to the backend system 150, which may further analyze the sensor data and/or notify a human user of a potential issue.

[0236] In embodiments, the notification module 426 may provide notifications or alarms to users based on the sensor data. In some of these embodiments, the notification module 426 may apply a set of rules that trigger a notification or alarm if certain conditions are met. The conditions may

define sensor data values that are strongly correlated with an undesirable (e.g., emergency) condition. Upon receiving sensor data from the data processing module 420, the notification module 426 may apply one or more rules to the sensor data. If the conditions to trigger an alarm or notification are met, the notification module 426 may issue an alarm or notification to a human user. The manner by which an alarm or notification is provided to the human user (e.g., to a user device, or triggering an audible alarm) may be predefined or, in some embodiments, may be defined by an operator of the industrial setting 120.

[0237] In embodiments, the configuration module 428 configures the sensor kit network 200. In embodiments, the configuration module 428 may transmit configuration requests to the other devices in the sensor kit 100, upon the sensors 102, edge device 104, and any other devices being installed in the industrial setting 120. In some of these embodiments, the sensors 102 and/or other devices may establish a mesh network or a hierarchical network in response to the configuration requests. In embodiments, the sensors 102 and other devices in the sensor kit network may respond to the configuration requests, in response to the configuration requests. In embodiments, the configuration module 428 may generate device records corresponding to the devices that responded based on the device IDs of those devices and any additional data provided in the responses to the configuration requests.

[0238] In embodiments, the configuration module 428 adds new devices to the sensor kit 100. In these embodiments, the configuration module 428 adds new sensors 102 to the sensor kit 100 post-installation in a plug-and-play-like manner. In some of these embodiments, the communication devices 404, 308 of the edge device 104 and the sensors 102 (or other devices to be added to the sensor kit 100) may include respective short-range communication capabilities (e.g., near-field communication (NFC) chips). In these embodiments, the sensors 102 may include persistent storage that stores identifying data (e.g., a sensor id value) and any other data that would be used to add the sensor to the sensor kit (e.g., device type, supported communication protocols, and the like). In response to a user initiating a post-installation addition to the sensor kit 100 (e.g., the user pressing a button on the edge device 104 and/or bringing the sensor 102 into the vicinity of the edge device 104), the configuration module 428 may cause the communication system 404 to emit a signal (e.g., a radio frequency). The emitted signal may trigger a sensor 102 proximate enough to receive the signal to transmit its sensor ID and any other suitable configuration data (e.g., device type, communication protocols, and the like). In response to the sensor 102 transmitting its configuration data (sensor ID and other relevant configuration data) to the edge device 104, the configuration module 428 may add the new sensor 102 to the sensor kit 102. In embodiments, adding the sensor 102 to the sensor kit 104 may include generating a new device record corresponding to the new sensor 102 based on the sensor id updating the configuration data store

410 with the new device record. The configuration module 428 may add a new sensor 102 to the sensor kit 100 in any other suitable manner.

[0239] In embodiments, the edge device 104 may include a distributed ledger module 430. In embodiments, the distributed ledger module 430 may be configured to update a distributed ledger 162 with sensor data captured by the sensor kit 100. In embodiments, the distributed ledger may be distributed amongst a plurality of node computing devices 160. As discussed, in embodiments, a distributed ledger 162 is comprised of a set of linked data structures (e.g., blocks, data records, etc.). For purposes of explanation, the data structures will be referred to as blocks.

[0240] As discussed, each block may include a header that includes a unique ID of the block and a body that includes the data that is stored in the block and a pointer of a parent block. In embodiments, the pointer in the block is the block ID of a parent block of the block. The data stored in a respective block can be sensor data captured by a respective sensor kit 100. Depending on the implementation, the types of sensor data and the amount of sensor data stored in a respective body of a block may vary. For example, a block may store a set of sensor measurements from one or more types of sensors 102 in the sensor kit 100 captured over a period of time (e.g., sensor data 102 captured from all of the sensors 102 in the sensor kit 100 over a period one hour or one day) and metadata relating thereto (e.g., sensor IDs of each sensor measurement and a timestamp of each sensor measurement or group of sensor measurements). In some embodiments, a block may store sensor measurements determined to be anomalous (e.g., outside a standard deviation of expected sensor measurements or deltas in sensor measurements that are above a threshold) and/or sensor measurements indicative of an issue or potential issue, and related metadata (e.g., sensor IDs of each sensor measurement and a timestamp of each sensor measurement or group of sensor measurements). In some embodiments, the sensor data stored in a block may be compressed and/or encoded sensor data, such that the encoding module 422 compresses/encodes the sensor data into a more compact format. In embodiments, the distributed ledger module 430 may generate a hash of the body, such that the contents of the body (e.g., block ID of the parent block and the sensor data) are hashed and cannot be altered without changing the value of the hash. In embodiments, the distributed ledger module 430 may encrypt the content within the block, so that the content may not be read by unauthorized devices.

[0241] In embodiments, the distributed ledger module 430 generates a block in response to a triggering event. Examples of triggering events may include a predetermined time (e.g., every minute, every hour, every day), when a potential issue is classified or predicted, when one or more sensor measurements are outside of a tolerance threshold, or the like. In response to the triggering event, the distributed ledger module 430 may generate a block based on sensor data that is to be reported. Depending on the configuration of the server kit 100 and the intended use of the

distributed ledger 162, the amount of data and type of data that is included in a block may vary. For example, in a manufacturing or resource extraction setting such as the manufacturing facility 1700 or the underwater industrial setting 1800, the distributed ledger 162 may be used to demonstrate functional machinery and/or to predict maintenance needs. In this example, the distributed ledger module 430 may be accessible by insurance providers to set insurance rates and/or issue refunds. Thus, in this example, the distributed ledger module 430 may include any sensor measurements (and related metadata) that are outside of a tolerance threshold or instance where an issue is classified or predicted. In another example, the distributed ledger may be accessible by a regulatory body to ensure that a facility is operating in accordance with one or more regulations. In these embodiments, the distributed ledger module 430 may store a set of one or more sensor measurements (and related metadata) in a block, such that the sensor measurements may be analyzed by the regulatory agency. In some of these embodiments, the sensor measurements may be compressed to store more sensor data in a single block. In response to generating a block, the distributed ledger module 430 may transmit the block to one or more node computing devices 160. Upon the block being verified (e.g., using a consensus mechanism), each node computing device 160 may update the distributed ledger 162 with the new block.

[0242] As discussed, in some embodiments the distributed ledger may further include smart contracts. Once written, a smart contract may be encoded in a block and deployed to the distributed ledger 162. The address of the smart contract (e.g., the block ID of the block containing the smart contract) may be provided to one or more parties to the smart contract, such that respective parties may invoke the smart contract using the address. In some of these embodiments, the address of the smart contract may be provided to the distributed ledger module 430, such that the distributed ledger module 430 may report items to the smart contract. In some embodiments, the distributed ledger module 430 may leverage the API of a smart contract to report the items to the smart contract.

[0243] In example implementations discussed above, an insurer may utilize a smart contract to allow insured facility owners and/or operators to demonstrate that the equipment in the facility is functioning properly. In some embodiments, the smart contract may trigger the issuance of rebates or refunds on portions of insurance premiums when an owner and/or operator of a facility provides sufficient sensor data that indicates the facility is operating without issue. In some of these embodiments, the smart contract may include a first condition that requires a certain amount of sensor data to be reported by a facility and a second condition that each instance of the sensor data equals a value (e.g., no classified or predicted issues) or range of values (e.g., all sensor measurements within a predefined range of values). In some embodiments, the action may be to deposit funds (e.g., a wire transfer or cryptocurrency) into an account in response to the first and

second conditions being met. In this example, the distributed ledger module 430 may write blocks containing sensor data to the distributed ledger 162. The distributed ledger module 430 may also provide the addresses of these blocks to the smart contract (e.g., via an API of the smart contract). Upon the smart contract verifying the first and second conditions of the contract, the smart contract
5 may initiate the transfer of funds from an account of the insurer to the account of the insured.

[0244] In another example discussed above, a regulatory body (e.g., a state, local, or federal regulatory agency) may utilize a smart contract that monitors facilities (e.g., food inspection facilities, pharmaceutical manufacturing facilities, indoor agricultural facilities, offshore oil extraction facilities, or the like) based on reported sensor data to ensure compliance with one or
10 more regulations. In embodiments, the smart contract may be configured to receive and verify the sensor data from a facility (e.g., via an API of the smart contract), and in response to verifying the sensor data issues a compliance token (or certificate) to an account of the facility owner. In some of these embodiments, the smart contract may include a first condition that requires a certain amount of sensor data to be reported by a facility and a second condition that requires the sensor
15 data to be compliant with the reporting regulations. In this example, the distributed ledger module 430 may write blocks containing sensor data to the distributed ledger. The sensor kit 100 may also provide the addresses of these blocks to the smart contract (e.g., using an API of the smart contract). Upon the smart contract verifying the first and second conditions of the contract, the smart contract may generate a token indicating compliance by the facility operator, and may initiate the transfer
20 of funds to an account (e.g., a digital wallet) associated with the facility.

[0245] FIG. 5 illustrates an example backend system 150 according to some embodiments of the present disclosure. In embodiments, the backend system 150 may be implemented as a cloud service that is executed at one or more physical server devices. In embodiments, the backend system 150 may include a storage system 502, a communication system 504, and a processing
25 system 506. The backend system 150 may include additional components not shown.

[0246] A storage system 502 includes one or more storage devices. The storage devices may include persistent storage mediums (e.g., flash memory drive, hard disk drive) and/or transient storage devices (e.g., RAM). The storage system 502 may store one or more data stores. A data store may include one or more databases, tables, indexes, records, filesystems, folders and/or files.
30 In the illustrated embodiments, the storage system 502 stores a sensor kit data store 510 and a model data store 512. A storage system 502 may store additional or alternative data stores without departing from the scope of the disclosure.

[0247] In embodiments, the sensor kit data store 510 stores data relating to respective sensor kits 100. In embodiments, the sensor kit data store 510 may store sensor kit data corresponding to each
35 installed sensor kit 100. In embodiments, the sensor kit data may indicate the devices in a sensor

kit 100, including each sensor 102 (e.g., a sensor ID) in the sensor kit 100. In some embodiments, the sensor kit data may indicate the sensor data captured by the sensor kit 100. In some of these embodiments, the sensor kit data may identify each instance of sensor data captured by the sensor kit 100, and for each instance of sensor data, the sensor kit data may indicate the sensor 102 that captured the sensor data and, in some embodiments, a time stamp corresponding to the sensor data.

[0248] In embodiments, the model data store 512 stores machine-learned models that are trained by the AI system 524 based on training data. The machine-learned models may include prediction models and classification models. In embodiments, the training data used to train a particular model includes data collected from one or more sensor kits 100 that monitor the same type of industrial setting 120. The training data may additionally or alternatively may include historical data and/or expert generated data. In embodiments, each machine-learned model may pertain to a respective type of industrial setting 120. In some of these embodiments, the AI system 524 may periodically update a machine-learned model pertaining to a type of industrial setting 120 based on sensor data collected from sensor kits 100 monitoring those types of industrial setting 120 and outcomes obtained from those industrial setting 120. In embodiments, machine-learned models pertaining to a type of industrial setting 120 may be provided to the edge devices 104 of sensor kits 100 monitoring that type of industrial setting 120.

[0249] In embodiments, a communication system 504 includes one or more communication devices, including at least one external communication device that communicates with a public communication network (e.g., the Internet) ether. The external communication devices may perform wired or wireless communication. In embodiments, the external communication devices may include cellular chipsets (e.g., 4G or 5G chipsets), Ethernet cards and/or Wi-Fi cards, or other suitable communication devices.

[0250] In embodiments, the processing system 506 may include one or more memory devices (e.g., ROM and/or RAM) that store computer-executable instructions and one or more processors that execute the computer-executable instructions. The processors may execute in a parallel or distributed manner. The processors may be located in the same physical server device or in different server devices. The processing system 506 may execute one or more of a decoding module 520, a data processing module 522, an AI module 524, a notification module 526, an analytics module 528, a control module 530, a dashboard module 532, a configuration module 534, and a distributed ledger management module 536. The processing system 406 may execute additional or alternative modules without departing from the scope of the disclosure. Furthermore, the modules discussed herein may include submodules that perform one or more functions of a respective module.

[0251] In embodiments, a sensor kit 100 may transmit encoded sensor kit packets containing sensor data to the backend system 150. In these embodiments, the decoding module 520 may receive encoded sensor data from an edge device 104 and may decrypt, decode, and/or decompress the encoded sensor kit packets to obtain the sensor data and metadata relating to the received sensor data (e.g., a sensor kit id and one or more sensor ids of sensors that captured the sensor data). The decoding module 520 may output the sensor data and any other metadata to the data processing module 522.

[0252] In embodiments, the data processing module 522 may process the sensor data received from the sensor kits 100. In some embodiments, the data processing module 522 may receive the sensor data and may store the sensor data in the sensor kit data store 510 in relation to the sensor kit 100 that provided to the sensor data. In embodiments, the data processing system 522 may provide AI-related requests to the AI module 524. In these embodiments, the data processing system 522 may extract relevant sensor data instances from the received sensor data and may provide the extracted sensor data instances to the AI module 524 in a request that indicates the type of request (e.g., what type of prediction or classification) and the sensor data to be used. In the event a potential issue is predicted or classified, the data processing module 522 may execute a workflow associated with the potential issue. A workflow may define the manner by which a potential issue is handled. For instance, the workflow may indicate that a notification should be transmitted to a human user, a remedial action should be initiated, and/or other suitable actions. The data processing module 522 may perform additional or alternative processing tasks without departing from the scope of the disclosure.

[0253] In embodiments, the AI module 524 trains machine-learned models that are used to make predictions or classifications. The machine-learned models may include any suitable type of models, including neural networks, deep neural networks, recursive neural networks, Bayesian neural networks, regression-based models, decision trees, prediction trees, classification trees, Hidden Markov Models, and/or any other suitable types of models. The AI module 524 may train a machine-learned model on a training data set. A training data set may include expert-generated data, historical data, and/or outcome-based data. Outcome-based data may be data that is collected after a prediction or classification is made that indicates whether the prediction or classification was correct or incorrect and/or a realized outcome. A training data instance may refer to a unit of training data that includes a set of features and a label. In embodiments, the label in a training data instance may indicate a condition of an industrial component or an industrial setting 120 at a given time. Examples of conditions will vary greatly depending on the industrial setting 120 and the conditions that the machine-learning model is being trained to predict or classify. Examples of labels in a manufacturing facility may include, but are not limited to, no issues detected, a

mechanical failure of a component, an electrical failure of a component, a chemical leak detected, and the like. Examples of labels in a mining facility may include, but are not limited to, no issues detected, an oxygen deficiency, the presence of a toxic gas, a failing structural component, and the like. Examples of labels in an oil and/or gas facility (e.g., oil field, gas field, oil refinery, pipeline) may include, but are not limited to, no issues detected, a mechanical failure of a component (e.g., a failed valve or failed O-ring), a leak, and the like. Examples of labels in an indoor agricultural facility may include, but are not limited to, no issues detected, a plant died, a plant wilted, a plant turned a certain color (e.g., brown, purple, orange, or yellow), mold found, and the like. In each of these examples, there are certain features that may be relevant to a condition and some features that may have little or no bearing on the condition. In embodiments, the AI module 524 may reinforce the machine-learned models as more sensor data and outcomes relating to the machine-learned models are received. In embodiments, the machine-learned models may be stored in the model data store 512. Each model may be stored with a model identifier, which may be indicative of (e.g., mapped to) the type of industrial setting 120 that the model makes, the type of prediction or classification made by the model, and the features that the model receives. In some embodiments, one or more machine-learned models (and subsequent updates thereto) may be pushed to respective sensor kits 100, whereby the edge devices 104 of the respective sensor kits 100 may use one or more machine-learned model to make predictions and/or classifications without having to rely on the backend system 150.

[0254] In embodiments, the AI module 524 receives requests for predictions and/or classifications and determines predictions and/or classifications based on the requests. In embodiments, a request may indicate a type of prediction or classification that is being requested and may include a set of features for making the prediction or classification. In response to the request, the AI module 524 may select a machine-learned model to leverage based on the type of prediction or classification being requested, whereby the selected model receives a certain set of features. The AI module 524 may then generate a feature vector that includes one or more instances of sensor data and may feed the feature vector into the selected model. In response to the feature vector, the selected model may output a prediction or classification, and a degree of confidence (e.g., a confidence score) in the prediction or classification. The AI module 524 may output the prediction or classification, as well as the degree of confidence therein, to the module that provided the request.

[0255] In embodiments, the notification module 526 may issue notifications to users and/or respective industrial setting 120 when an issue is detected in a respective setting. In embodiments, a notification may be sent to a user device of a user indicating the nature of the issue. The notification module 526 may implement an API (e.g., a REST API), whereby a user device of a user associated with the industrial setting 120 may request notifications from the backend system

150. In response to the request, the notification module 526 may provide any notifications, if any, to the user device. In embodiments, a notification may be sent to a device located at an industrial setting 120, whereby the device may raise an alarm at the industrial setting 120 in response to the industrial setting 120.

5 [0256] In embodiments, the analytics module 528 may perform analytics related tasks on sensor data collected by the backend system 150 and stored in the sensor kit data store 510. In embodiments, the analytics tasks may be performed on sensor data received from individual sensor kits. Additionally, or alternatively, the analytics tasks may be performed on sensor data Examples of analytics tasks that may be performed on sensor data obtained from various sensor kits 100
10 monitoring different industrial setting 120. Examples of analytics tasks may include energy utilization analytics, quality analytics, process optimization analytics, financial analytics, predictive analytics, yield optimization analytics, fault prediction analytics, scenario planning analytics, and many others.

[0257] In embodiments, the control module 530 may control one or more aspects of an industrial
15 setting 120 based on a determination made by the AI system 524. In embodiments, the control module 530 may be configured to provide commands to a device or system at the industrial setting 120 to take a remedial action in response to a particular issue being detected. For example, the control module 530 may issue a command to a manufacturing facility to stop an assembly line in response to a determination that a critical component on the assembly line is likely failing or likely
20 failed. In another example, the control module 530 may issue a command to an agricultural facility to activate a dehumidifier in response to a determination that the humidity levels are too high in the facility. In another example, the control module 530 may issue a command to shut a valve in an oil pipeline in response to a determination that a component in the oil pipeline downstream to the valve is likely failing or likely failed. For a particular industrial setting 120, the control module
25 530 may perform remedial actions defined by a human user associated with the industrial setting 120, such that the human user may define what conditions may trigger the remedial action.

[0258] In embodiments, the dashboard module 532 presents a dashboard to human users via a user device 140 associated with the human user. In embodiments, the dashboard provides a graphical user interface that allows the human user to view relating to a sensor kit 100 with which the human
30 user is associated (e.g., an employee at the industrial setting 120). In these embodiments, the dashboard module 532 may retrieve and display raw sensor data provided by the sensor kit, analytical data relating to the sensor data provided by the sensor kit 100, predictions or classifications made by the backend system 150 based on the sensor data, and the like.

[0259] In embodiments, the dashboard module 532 allows human users to configure aspects of the
35 sensor kits 100. In embodiments, the dashboard module 532 may present a graphical user interface

that allows a human user to configure one or more aspects of a sensor kit 100 with which the human user is associated. In embodiments, the dashboard may allow a user to configure alarm limits with respect to one or more sensor types and/or conditions. For example, a user may define a temperature value at which a notification is sent to a human user. In another example, the user may define a set of conditions, which if predicted by the AI module and/or the edge device, trigger an alarm. In embodiments, the dashboard may allow a user to define which users receive a notification when an alarm is triggered. In embodiments, the dashboard may allow a user to subscribe to additional features of the backend system 150 and/or an edge device 104.

[0260] In embodiments, the dashboard may allow a user to add one or more subscriptions to a sensor kit 100. The subscriptions may include access to backend services and/or edge services. A user may select a service to add to a sensor kit 100 and may provide payment information to pay for the services. Upon verification of the payment information, the backend system 150 may provide the sensor kit 100 access to those features. Examples of services that may be subscribed to include analytics services, AI-services, notification services, and the like. The dashboard may allow the user to perform additional or alternative configurations.

[0261] In embodiments, the configuration module 534 maintains configurations of respective sensor kits 100. Initially, when a new sensor kit 100 is deployed in an industrial setting 120, the configuration module 534 may update the sensor kit data store 510 with the device IDs of each device in the newly installed sensor kit 100. Once the sensor kit data store 510 has updated the sensor kit data store 510 to reflect the newly installed sensor kit 100, the backend system 150 may begin storing sensor data from the sensor kit 100. In embodiments, new sensors 102 may be added to respective sensor kits 100. In these embodiments, an edge device 104 may provide an add request to the backend system 150 upon an attempt to add a device to the sensor kit 100. In embodiments, the request may indicate a sensor ID of the new sensor. In response to the request, the configuration module 534 may add the sensor ID of the new sensor to the sensor kit data of the requesting sensor kit 100 in the sensor kit data store 510.

[0262] In embodiments, the backend system 150 includes a distributed ledger management module 536. In some of these embodiments, the distributed ledger management module 536 allows a user to update and/or configure a distributed ledger. In some of these embodiments, the distributed ledger management module 536 allows a user to define or upload a smart contract. As discussed, the smart contract may include one or more conditions that are verified by the smart contract and one or more actions that are triggered when the conditions are verified. In embodiments, the user may provide one or more conditions that are to be verified to the distributed ledger management module 536 via a user interface. In some of these embodiments, the user may provide the code (e.g., JavaScript code, Java code, C code, C++ code, etc.) that defines the conditions. The user may

also provide the actions that are to be performed in response to certain conditions being met. In response to a smart contract being uploaded/created, the distributed ledger management module 536 may deploy the smart contract. In embodiments, the distributed ledger management module 536 may generate a block containing the smart contract. The block may include a header that defines an address of the block, and a body that includes an address to a previous block and the smart contract. In some embodiments, the distributed ledger management module 536 may determine a hash value based on the body of the block and/or may encrypt the block. The distributed ledger management module 536 may transmit the block to one or more node computing devices 160, which in turn update the distributed ledger with the block containing the smart contract. The distributed ledger management module 536 may further provide the address of the block to one or more parties that may access the smart contract. The distributed ledger management module 536 may perform additional or alternative functions without departing from the scope of the disclosure.

[0263] The backend system 150 may include additional or alternative components, data stores, and/or modules that are not discussed.

[0264] FIGS. 6-9 – Exemplary Methods of Encoding and/or Decoding Sensor Data

[0265] FIG. 6 illustrates an example set of operations of a method 600 for compressing sensor data obtained by a sensor kit 100. In embodiments, the method 600 may be performed by an edge device 104 of a sensor kit 100.

[0266] At 610, the edge device 104 receives sensor data from one or more sensors 102 of the sensor kit 100 via a sensor kit network 200. In embodiments, the sensor data from a respective sensor 102 may be received in a reporting packet. Each reporting packet may include a device identifier of the sensor 102 that generated the reporting packet and one or more instances of sensor data captured by sensor 102. The reporting packet may include additional data, such as a timestamp or other metadata.

[0267] At 612, the edge device 104 processes the sensor data. In embodiments, the edge device 104 may dedupe any reporting packets that are duplicative. In embodiments, the edge device 104 may filter out sensor data that is clearly erroneous (e.g., outside of a tolerance range). In embodiments, the edge device 104 may aggregate the sensor data obtained from multiple sensors 102. In embodiments, the edge device 104 may perform one or more AI related tasks, such as determining a prediction or classification relating to a condition of one or more industrial components of the industrial setting 120. In some of these embodiments, the decision to compress the sensor data may depend on whether the edge device 104 determines that there are any potential issues with the industrial component. For example, the edge device 104 may compress the sensor data when there have been no issues predicted or classified. In other embodiments, the edge device

104 may compress any sensor data that is being transmitted to the backend system or certain types of sensor data (e.g., sensor data obtained from temperature sensors).

[0268] At 614, the edge device 104 may compress the sensor data. The edge device 104 may employ any suitable compression techniques for compressing the sensor data. For example, the edge device 104 may employ vertical or horizontal compression techniques. The edge device 104 may be configured with a codec that compresses the sensor data. The codec may be a proprietary codec or an “off-the-shelf” codec.

[0269] At 616, the edge device 104 may transmit the compressed sensor data to the backend system 150. In embodiments, the edge device 104 may generate a sensor kit packet that contains the compressed data. The sensor kit packet may designate the source of the sensor kit packet (e.g., a sensor kit ID or edge device ID) and may include additional metadata (e.g., a timestamp). In embodiments, the edge device 104 may encrypt the sensor kit packet prior to transmitting the sensor kit packet to the backend system 150. In embodiments, the edge device 104 transmits the sensor kit packet to the backend system 150 directly (e.g., via a cellular connection, a network connection, or a satellite uplink). In other embodiments, the edge device 104 transmits the sensor kit packet to the backend system 150 via a gateway device, which transmits the sensor kit packet to the backend system 150 directly (e.g., via a cellular connection or a satellite uplink).

[0270] FIG. 7 illustrates an example set of operations of a method 700 for processing compressed sensor data received from a sensor kit 100. In embodiments, the method 700 is executed by a backend system 150.

[0271] At 710, the backend system 150 receives compressed sensor data from a sensor kit. In embodiments, the compressed sensor data may be received in a sensor kit packet.

[0272] At 712, the backend system 150 decompresses the received sensor data. In embodiments, the backend system may utilize a codec to decompress the received sensor data. Prior to decompressing the received sensor data, the backend system 150 may decrypt a sensor kit packet containing the compressed sensor data.

[0273] At 714, the backend system 150 performs one or more backend operations on the decompressed sensor data. The backend operations may include storing the data, filtering the data, performing AI-related tasks on the sensor data, issuing one or more notifications in relation to the results of the AI-related tasks, performing one or more analytics related tasks, controlling an industrial component of the industrial setting 120, and the like.

[0274] FIG. 8 illustrates an example set of operations of a method 800 for streaming sensor data from a sensor kit 100 to a backend system 150. In embodiments, the method 800 may be executed by an edge device 104 of the sensor kit 100.

[0275] At 810, the edge device 104 receives sensor data from one or more sensors 102 of the sensor

kit 100 via a sensor kit network 200. In embodiments, the sensor data from a respective sensor 102 may be received in a reporting packet. Each reporting packet may include a device identifier of the sensor 102 that generated the reporting packet and one or more instances of sensor data captured by sensor 102. The reporting packet may include additional data, such as a timestamp or other metadata. In embodiments, the edge device 104 may process the sensor data. For example, the edge device 104 may dedupe any reporting packets that are duplicative and/or may filter out sensor data that is clearly erroneous (e.g., outside of a tolerance range). In embodiments, the edge device 104 may aggregate the sensor data obtained from multiple sensors 102.

[0276] At 812, the edge device 104 may normalize and/or transform the sensor data into a media-frame compliant format. In embodiments, the edge device 104 may normalize and/or transform each sensor data instance into a value that adheres to the restrictions of a media frame that will contain the sensor data. For example, in embodiments where the media frames are video frames, the edge device 104 may normalize and/or transform instances of sensor data into acceptable pixel frames. The edge device 104 may employ one or more mappings and/or normalization functions to transform and/or normalize the sensor data.

[0277] At 814, the edge device 104 may generate a block of media frames based on the transformed and/or normalized sensor data. For example, in embodiments where the media frames are video frames, the edge device 104 may populate each instance of transformed and/or normalized sensor data into a respective pixel of the video frame. The manner by which the edge device 104 assigns an instance of transformed and/or normalized sensor data to a respective pixel may be defined in a mapping that maps respective sensors to respective pixel values. In embodiments, the mapping may be defined so as to minimize variance between the values in adjacent pixels. In embodiments, the edge device 104 may generate a series of time-sequenced media frames, such that each successive media frame corresponds to a subsequent set of sensor data instances.

[0278] At 816, the edge device 104 may encode the block of the media frame. In embodiments, the edge device 104 may employ an encoder of a media codec (e.g., a video codec) to compress the block of media frames. The codec may be a proprietary codec or an “off-the-shelf” codec. For example, the media codec may be an H.264/MPEG-4 codec, an H.265/MPEG-H codec, an H.263/MPEG-4 codec, proprietary codecs, and the like. The codec receives the block of media frames and generates an encoded media block based thereon.

[0279] At 818, the edge device 104 may transmit the encoded media block to the backend system 150. In embodiments, the edge device 104 may stream the encoded media blocks to the backend system 150. Each encoded block may designate the source of the block (e.g., a sensor kit ID or edge device ID) and may include additional metadata (e.g., a timestamp and/or a block identifier). In embodiments, the edge device 104 may encrypt the encoded media blocks prior to transmitting

encoded media blocks to the backend system 150. The edge device 104 may transmit the encoded media blocks to the backend system 150 directly (e.g., via a cellular connection, a network connection, or a satellite uplink) or via a gateway device, which transmits the encoded media block to the backend system 150 directly (e.g., via a cellular connection or a satellite uplink).

5 [0280] The edge device 104 may continue to execute the foregoing method 800, so as to deliver a stream of live sensor data from a sensor kit. The foregoing method 900 may be performed in settings where there are many sensors deployed within the setting and the sensors are sampled frequently or continuously. In this way, the bandwidth required to provide the sensor data to the backend system is reduced.

10 [0281] FIG. 9 illustrates an example set of operations of a method 900 for ingesting a sensor data stream from an edge device 104. In embodiments, the method 900 is executed by a backend system.

[0282] At 910, the backend system 150 receives an encoded media block from a sensor kit. The backend system 150 may receive encoded media blocks as part of a sensor data stream.

15 [0283] At 912, the backend system 150 decodes the encoded block using a decoder corresponding to the codec of the codec used to encode the media block to obtain a set of successive media frames. As discussed with respect to the encoding operation, the codec may be a proprietary codec or an “off-the-shelf” codec. For example, the media codec may be an H.264/MPEG-4 codec, an H.265/MPEG-H codec, an H.263/MPEG-4 codec, proprietary codecs, and the like. The codec receives the encoded block of media frames and decodes the encoded block to obtain a set of sequential media frames.

20 [0284] At 914, the backend system 150 recreates the sensor data based on the media frame. In embodiments, the backend system 150 determines the normalized and/or transformed sensor values embedded in each respective media frame. For example, in embodiments where the media frames are video frames, the backend system 150 may determine pixel values for each pixel in the media frame. A pixel value may correspond to respective sensor 102 of a sensor kit 100 and the value may represent a normalized and/transformed instance of sensor data. In embodiments, the backend system 150 may recreate the sensor data by inverting the normalization and/or transformation of the pixel value. In embodiments, the backend system 150 may utilize an inverse transformation and/or an inverse normalization function to obtain each recreated sensor data instance.

25 [0285] AT 918, the backend system 150 performs one or more backend operations based on the recreated sensor data. The backend operations may include storing the data, filtering the data, performing AI-related tasks on the sensor data, issuing one or more notifications in relation to the results of the AI-related tasks, performing one or more analytics related tasks, controlling an industrial component of the industrial setting 120, and the like.

[0286] FIG. 10 – Exemplary Method of Determining Transmission Strategy

[0287] FIG. 10 illustrates a set of operations of a method 1000 for determining a transmission strategy and/or a storage strategy for sensor data collected by a sensor kit 100 based on the sensor data. A transmission strategy may define a manner that sensor data is transmitted (if at all) to the backend system. For example, sensor data may be compressed using an aggressive lossy codec, compressed using a lossless codec, and/or transmitted without compression. A storage strategy may define a manner by which sensor data is stored at the edge device 104. For example, sensor data may be stored permanently (or until a human removes the sensor data), may be stored for a period of time (e.g., one year) or may be discarded. The method 1000 may be executed by an edge device 104. The method 1000 may be executed to reduce the network bandwidth consumed by the sensor kit 100 and/or reduce the storage constraints at the edge device 104.

[0288] At 1010, the edge device 104 receives sensor data from the sensors 102 of the sensor kit 100. The data may be received continuously or intermittently. In embodiments, the sensors 102 may push the sensor data to the edge device 104 and/or the edge device 104 may request the sensor data 102 from the sensors 102 periodically. In embodiments, the edge device 104 may process the sensor data upon receipt, including deduping the sensor data.

[0289] In embodiments, the edge device 104 may be configured to perform one or more AI-related tasks prior to transmission via the satellite uplink. In some of these embodiments, the edge device 104 may be configured to determine whether there are likely no issues relating to any of the components and/or the industrial setting 120 based on the sensor data and one or more machine-learned models.

[0290] At 1012, the edge device 104 may generate one or more feature vectors based on the sensor data. The feature vectors may include sensor data from a single sensor 102, a subset of sensors 102, or all of the sensors 102 of the sensor kit 100. In scenarios where a single sensor or a subset of sensors 102 are included in the feature vector, the machine-learned model may be trained to identify one or more issues relating to an industrial component or the industrial setting 120, but may not be sufficient to fully deem the entire setting as likely safe/free from issues. Additionally or alternatively, the feature vectors may correspond to a single snapshot in time (e.g., all sensor data in the feature vector corresponds to the same sampling event) or over a period of time (sensor data samples from a most recent sampling event and sensor data samples from previous sampling events). In embodiments where the feature vectors define sensor data from a single snapshot, the machine-learned models may be trained to identify potential issues without any temporal context. In embodiments where the feature vectors define sensor data over a period of time, the machine-learned models may be trained to identify potential issues with the context of what the sensor(s) 102 was/were reporting previously. In these embodiments, the edge device 104 may maintain a

cache of sensor data that is sampled over a predetermined time (e.g., previous hour, previous day, previous N days), such that the cache is cleared out in a first-in-first-out manner. In these embodiments, the edge device 104 may retrieve the previous sensor data samples from the cache to use to generate feature vectors that have data samples spanning a period of time.

5 [0291] At 1014, the edge device 104 may input the one or more feature vectors into one or more respective machine-learned models. A respective model may output a prediction or classification relating to an industrial component and/or the industrial setting 120, and a confidence score relating to the prediction or classification.

[0292] At 1016, the edge device 104 may determine a transmission strategy and/or a storage
10 strategy based on the output of the machine-learned models. In some embodiments, the edge device 104 may make determinations relating to the manner by which sensor data is transmitted to the backend system 150. In some embodiments, the edge device 104 may make determinations relating to the manner by which sensor data is transmitted to the backend system 150 and/or stored at the edge device. In some of these embodiments, the edge device 104 may compress sensor data when
15 there are no likely issues across the entire industrial setting 120 and individual components of the industrial setting 120. For example, if the machine-learned models predict that there are likely no issues and classify that there are currently no issues with a high degree of confidence (e.g., the confidence score is greater than .98), the edge device 104 may compress the sensor data. Alternatively, in the scenario where the machine-learned models predict that there are likely no
20 issues and classify that there are currently no issues with a high degree of confidence, the edge device 104 may forego transmission but may store the sensor data at the edge device 104 for a predefined period of time (e.g., a one-year expiry). In scenarios where a machine-learned model predicts a potential issue or classifies a current issue, the edge device 104 may transmit the sensor data without compressing the sensor data or using a lossless compression codec. Additionally or
25 alternatively, in scenarios where a machine-learned model predicts a potential issue or classifies a current issue, the edge device 104 may store the sensor data used to make the prediction or classification indefinitely, as well as data that was collected prior to and/or after the condition was predicted or classified.

[0293] FIGS. 11-15 – Exemplary Sensor Kit Configurations

30 [0294] FIG. 11 illustrates an example configuration of a sensor kit 1100 according to some embodiments of the present disclosure. In the illustrated example, the sensor kit 1100 is configured to communicate with a communication network 180 via an uplink 1108 to a satellite 1110. In embodiments, the sensor kit 1100 of FIG. 11 is configured for use in industrial setting 120 located in remote locations, where cellular coverage is unreliable or non-existent. In embodiments, the
35 sensor kit 1100 may be installed in natural resource extraction, natural resource transportation

systems, power generation facilities, and the like. For example, the sensor kit 1100 may be deployed in an oil or natural gas fields, off-shore oil rigs, mines, oil or gas pipelines, solar fields, wind farms, hydroelectric power stations, and the like.

[0295] In the example of FIG. 11, the server kit 1100 includes an edge device 104 and a set of
5 sensors 102. The sensors 102 may include various types of sensors 102, which may vary depending on the industrial setting 120. In the illustrated example, the sensors 102 communicate with the edge device 104 via a mesh network. In these embodiments, the sensors 102 may communicate sensor data to proximate sensors 102, so as to propagate the sensor data to the edge device 104 located at the remote/peripheral areas of the industrial setting 120 to the edge device 104. While a mesh
10 network is shown, the sensor kits 1100 of FIG. 11 may include alternative network topologies, such as a hierarchal topology (e.g., some or all of the sensors 102 communicate with the edge device 104 via respective collection devices) or a star topology (e.g., sensors 102 communicate to the edge device directly).

[0296] In the embodiments of FIG. 11, the edge device 104 includes a satellite terminal with a
15 directional antenna that communicates with a satellite. The satellite terminal may be pre-configured to communicate with a geosynchronous or low Earth orbit satellites. The edge device 104 may receive sensor data from the sensor kit network established by the sensor kit 1100. The edge device 104 may then transmit the sensor data to the backend system 150 via the satellite 1110.

[0297] In embodiments, the configurations of the server kit 1100 are suited for industrial setting
20 120 covering a remote area where external power sources are not abundant. In embodiments, the sensor kit 1100 may include external power sources, such as batteries, rechargeable batteries, generators, and/or solar panels. In these embodiments, the external power sources may be deployed to power the sensors 102, the edge device 104, and any other devices in the sensor kit 1100.

[0298] In embodiments, the configurations of the server kit 1100 are suited for outdoor industrial
25 setting 120. In embodiments, the sensors 102, the edge device 104, and other devices of the sensor kit 100 (e.g., collection devices) may be configured with weatherproof housings. In these embodiments, the sensor kit 1100 may be deployed in an outdoor setting.

[0299] In embodiments, the edge device 104 may be configured to perform one or more AI-related tasks prior to transmission via the satellite uplink. In some of these embodiments, the edge device
30 104 may be configured to determine whether there are likely no issues relating to any of the components and/or the industrial setting 120 based on the sensor data and one or more machine-learned models. In embodiments, the edge device 104 may receive the sensor data from the various sensors and may generate one or more feature vectors based thereon. The feature vectors may include sensor data from a single sensor 102, a subset of sensors 102, or all of the sensors 102 of
35 the sensor kit 1100. In scenarios where a single sensor or a subset of sensors 102 are included in

the feature vector, the machine-learned model may be trained to identify one or more issues relating to an industrial component or the industrial setting 120, but may not be sufficient to fully deem the entire setting as likely safe/free from issues. Additionally or alternatively, the feature vectors may correspond to a single snapshot in time (e.g., all sensor data in the feature vector corresponds to the same sampling event) or over a period of time (sensor data samples from a most recent sampling event and sensor data samples from previous sampling events). In embodiments where the feature vectors define sensor data from a single snapshot, the machine-learned models may be trained to identify potential issues without any temporal context. In embodiments where the feature vectors define sensor data over a period of time, the machine-learned models may be trained to identify potential issues with the context of what the sensor(s) 102 was/were reporting previously. In these embodiments, the edge device 104 may maintain a cache of sensor data that is sampled over a predetermined time (e.g., previous hour, previous day, previous N days), such that the cache is cleared out in a first-in-first-out manner. In these embodiments, the edge device 104 may retrieve the previous sensor data samples from the cache to use to generate feature vectors that have data samples spanning a period of time.

[0300] In embodiments, the edge device 104 may feed the one or more feature vectors into one or more respective machine-learned models. A respective model may output a prediction or classification relating to an industrial component and/or the industrial setting 120, and a confidence score relating to the prediction or classification. In some embodiments, the edge device 104 may make determinations relating to the manner by which sensor data is transmitted to the backend system 150 and/or stored at the edge device. For instance, in some embodiments, the edge device 104 may compress sensor data based on the prediction or classification. In some of these embodiments, the edge device 104 may compress sensor data when there are no likely issues across the entire industrial setting 120 and individual components of the industrial setting 120. For example, if the machine-learned models predict that there are likely no issues and classify that there are currently no issues with a high degree of confidence (e.g., the confidence score is greater than .98), the edge device 104 may compress the sensor data. Alternatively, in the scenario where the machine-learned models predict that there are likely no issues and classify that there are currently no issues with a high degree of confidence, the edge device 104 may forego transmission but may store the sensor data at the edge device 104 for a predefined period of time (e.g., one year). In scenarios where a machine-learned model predicts a potential issue or classifies a current issue, the edge device 104 may transmit the sensor data without compressing the sensor data or using a lossless compression codec. In this way, the amount of bandwidth that is transmitted via the satellite uplink may be reduced, as the majority of the time the sensor data will be compressed or not transmitted.

[0301] In embodiments, the edge device 104 may apply one or more rules to determine whether a triggering condition exists. In embodiments, the one or more rules may be tailored to identify potentially dangerous and/or emergency situations. In these embodiments, the edge device 104 may trigger one or more notifications or alarms when a triggering condition exists. Additionally or alternatively, the edge device 104 may transmit the sensor data without any compression when a triggering condition exists.

[0302] FIG. 12 illustrates an example configuration of a sensor kit 1200 according to some embodiments of the present disclosure. In the illustrated example, the sensor kit 1200 is configured to include a gateway device 1206 that communicates with a communication network 180 via an uplink 1108 to a satellite 1110. In embodiments, the sensor kit 1200 of FIG. 12 is configured for use in industrial setting 120 located in remote locations, where cellular coverage is unreliable or non-existent, and where the edge device 104 is located in a location where physical transmission to a satellite is unreliable or impossible. In embodiments, the sensor kit 1100 may be installed in underground or underwater facilities, or in facilities having very thick walls. For example, the sensor kit 1100 may be deployed in underground mines, underwater oil or gas pipelines, underwater hydroelectric power stations, and the like.

[0303] In the example of FIG. 12, the server kit 1200 includes an edge device 104, a set of sensors 102, and a gateway device 1206. In embodiments, the gateway device 1206 is a communication device that includes a satellite terminal with a directional antenna that communicates with a satellite. The satellite terminal may be pre-configured to communicate with a geosynchronous or low Earth orbit satellites. In embodiments, the gateway device 1206 may communicate with the edge device 104 via a wired communication link 1208 (e.g., Ethernet). The edge device 104 may receive sensor data from the sensor kit network established by the sensor kit 1200. The edge device 104 may then transmit the sensor data to the gateway device 1206 via the wired communication link 1208. The gateway device 1206 may then communicate the sensor data to the backend system 150 via the satellite uplink 1108.

[0304] The sensors 102 may include various types of sensors 102, which may vary depending on the industrial setting 120. In the illustrated example, the sensors 102 communicate with the edge device 104 via a mesh network. In these embodiments, the sensors 102 may communicate sensor data to proximate sensors 102, so as to propagate the sensor data to the edge device 104 located at the remote/peripheral areas of the industrial setting 120 to the edge device 104. While a mesh network is shown, the sensor kits 1200 of FIG. 12 may include alternative network topologies, such as a hierarchal topology (e.g., some or all of the sensors 102 communicate with the edge device 104 via respective collection devices) or a star topology (e.g., sensors 102 communicate to the edge device directly).

[0305] In embodiments, the configurations of the server kit 1200 are suited for industrial setting 120 covering a remote area where external power sources are not abundant. In embodiments, the sensor kit 1200 may include external power sources, such as batteries, rechargeable batteries, generators, and/or solar panels. In these embodiments, the external power sources may be deployed to power the sensors 102, the edge device 104, and any other devices in the sensor kit 1200.

[0306] In embodiments, the configurations of the server kit 1200 are suited for underground or underwater industrial setting 120. In embodiments, the sensors 102, the edge device 104, and other devices of the sensor kit 100 (e.g., collection devices) may be configured with waterproof housings or otherwise airtight housings (to prevent dust from entering the edge device 104 and/or sensor devices 102). Furthermore, as the gateway device 1208 is likely to be situated outdoors, the gateway device 1208 may include a weatherproof housing.

[0307] In embodiments, the edge device 104 may be configured to perform one or more AI-related tasks prior to transmission via the satellite uplink. In some of these embodiments, the edge device 104 may be configured to determine whether there are likely no issues relating to any of the components and/or the industrial setting 120 based on the sensor data and one or more machine-learned models. In embodiments, the edge device 104 may receive the sensor data from the various sensors and may generate one or more feature vectors based thereon. The feature vectors may include sensor data from a single sensor 102, a subset of sensors 102, or all of the sensors 102 of the sensor kit 1200. In scenarios where a single sensor or a subset of sensors 102 are included in the feature vector, the machine-learned model may be trained to identify one or more issues relating to an industrial component or the industrial setting 120, but may not be sufficient to fully deem the entire setting as likely safe/free from issues. Additionally or alternatively, the feature vectors may correspond to a single snapshot in time (e.g., all sensor data in the feature vector corresponds to the same sampling event) or over a period of time (sensor data samples from a most recent sampling event and sensor data samples from previous sampling events). In embodiments where the feature vectors define sensor data from a single snapshot, the machine-learned models may be trained to identify potential issues without any temporal context. In embodiments where the feature vectors define sensor data over a period of time, the machine-learned models may be trained to identify potential issues with the context of what the sensor(s) 102 was/were reporting previously. In these embodiments, the edge device 104 may maintain a cache of sensor data that is sampled over a predetermined time (e.g., previous hour, previous day, previous N days), such that the cache is cleared out in a first-in-first-out manner. In these embodiments, the edge device 104 may retrieve the previous sensor data samples from the cache to use to generate feature vectors that have data samples spanning a period of time.

[0308] In embodiments, the edge device 104 may feed the one or more feature vectors into one or

more respective machine-learned models. A respective model may output a prediction or classification relating to an industrial component and/or the industrial setting 120, and a confidence score relating to the prediction or classification. In some embodiments, the edge device 104 may make determinations relating to the manner by which sensor data is transmitted to the backend system 150 and/or stored at the edge device. For instance, in some embodiments, the edge device 104 may compress sensor data based on the prediction or classification. In some of these embodiments, the edge device 104 may compress sensor data when there are no likely issues across the entire industrial setting 120 and individual components of the industrial setting 120. For example, if the machine-learned models predict that there are likely no issues and classify that there are currently no issues with a high degree of confidence (e.g., a confidence score is greater than .98), the edge device 104 may compress the sensor data. Alternatively, in the scenario where the machine-learned models predict that there are likely no issues and classify that there are currently no issues with a high degree of confidence, the edge device 104 may forego transmission but may store the sensor data at the edge device 104 for a predefined period of time (e.g., one year). In scenarios where a machine-learned model predicts a potential issue or classifies a current issue, the edge device 104 may transmit the sensor data without compressing the sensor data or using a lossless compression codec. In this way, the amount of bandwidth that is transmitted via the satellite uplink may be reduced, as the majority of the time the sensor data will be compressed or not transmitted.

[0309] In embodiments, the edge device 104 may apply one or more rules to determine whether a triggering condition exists. In embodiments, the one or more rules may be tailored to identify potentially dangerous and/or emergency situations. In these embodiments, the edge device 104 may trigger one or more notifications or alarms when a triggering condition exists. Additionally or alternatively, the edge device 104 may transmit the sensor data (via the gateway device 1206) without any compression when a triggering condition exists.

[0310] FIG. 13 illustrates an example configuration of a server kit 1300 according to some embodiments of the present disclosure. In the example of FIG. 13, the server kit 1300 includes an edge device 104, a set of sensors, and a set of collection devices. In embodiments, the configurations of the server kit 1300 are suited for industrial setting 120 covering a large area and where power sources are abundant; but where the industrial operator does not wish to connect the sensor kit 1400 to the private network of the industrial setting 120. In embodiments, the edge device 104 includes a cellular communication device (e.g., a 4G LTE chipset or 5G LTE chipset) with a transceiver that communicates with a cellular tower 1310. The cellular communication may be pre-configured to communicate with a cellular data provider. For example, in embodiments, the edge device 104 may include a SIM card that is registered with a cellular provider having a cellular

tower 1310 that is proximate to the industrial setting 120. The edge device 104 may receive sensor data from the sensor kit network established by the sensor kit 1400. The edge device 104 may process the sensor data and then transmit the sensor data to the backend system 150 via the cellular tower 1310.

- 5 [0311] The sensors 102 may include various types of sensors 102, which may vary depending on the industrial setting 120. In the illustrated example, the sensors 102 communicate with the edge device 104 via a hierarchical network. In these embodiments, the sensors 102 may communicate sensor data to collection devices 206, which, in turn, may communicate the sensor data to edge device 104 via a wired or wireless communication link. The hierarchical network may be deployed
10 where the area being monitored is rather larger (e.g., over 40,000 sq. ft.) and power supplies are abundant, such as in a factory, a power plant, a food inspection facility, an indoor grow facility, and the like. While a hierarchal network is shown, the sensor kits 1300 of FIG. 13 may include alternative network topologies, such as a mesh topology or a star topology (e.g., sensors 102 communicate to the edge device directly).
- 15 [0312] In embodiments, the edge device 104 may be configured to perform one or more AI-related tasks prior to transmission via the satellite uplink. In some of these embodiments, the edge device 104 may be configured to determine whether there are likely no issues relating to any of the components and/or the industrial setting 120 based on the sensor data and one or more machine-learned models. In embodiments, the edge device 104 may receive the sensor data from the various
20 sensors and may generate one or more feature vectors based thereon. The feature vectors may include sensor data from a single sensor 102, a subset of sensors 102, or all of the sensors 102 of the sensor kit 1300. In scenarios where a single sensor or a subset of sensors 102 are included in the feature vector, the machine-learned model may be trained to identify one or more issues relating to an industrial component or the industrial setting 120, but may not be sufficient to fully deem the
25 entire setting as likely safe/free from issues. Additionally or alternatively, the feature vectors may correspond to a single snapshot in time (e.g., all sensor data in the feature vector corresponds to the same sampling event) or over a period of time (sensor data samples from a most recent sampling event and sensor data samples from previous sampling events). In embodiments where the feature vectors define sensor data from a single snap shot, the machine-learned models may be trained to
30 identify potential issues without any temporal context. In embodiments where the feature vectors define sensor data over a period of time, the machine-learned models may be trained to identify potential issues with the context of what the sensor(s) 102 was/were reporting previously. In these embodiments, the edge device 104 may maintain a cache of sensor data that is sampled over a predetermined time (e.g., previous hour, previous day, previous N days), such that the cache is
35 cleared out in a first-in-first-out manner. In these embodiments, the edge device 104 may retrieve

the previous sensor data samples from the cache to use to generate feature vectors that have data samples spanning a period of time.

[0313] In embodiments, the edge device 104 may feed the one or more feature vectors into one or more respective machine-learned models. A respective model may output a prediction or classification relating to an industrial component and/or the industrial setting 120, and a confidence score relating to the prediction or classification. In some embodiments, the edge device 104 may make determinations relating to the manner by which sensor data is transmitted to the backend system 150 and/or stored at the edge device. For instance, in some embodiments, the edge device 104 may compress sensor data based on the prediction or classification. In some of these embodiments, the edge device 104 may compress sensor data when there are no likely issues across the entire industrial setting 120 and individual components of the industrial setting 120. For example, if the machine-learned models predict that there are likely no issues and classify that there are currently no issues with a high degree of confidence (e.g., a confidence score is greater than .98), the edge device 104 may compress the sensor data. Alternatively, in the scenario where the machine-learned models predict that there are likely no issues and classify that there are currently no issues with a high degree of confidence, the edge device 104 may forego transmission but may store the sensor data at the edge device 104 for a predefined period of time (e.g., one year). In scenarios where a machine-learned model predicts a potential issue or classifies a current issue, the edge device 104 may transmit the sensor data without compressing the sensor data or using a lossless compression codec. In this way, the amount of bandwidth that is transmitted via the cellular tower may be reduced, as the majority of the time the sensor data will be compressed or not transmitted.

[0314] In embodiments, the edge device 104 may apply one or more rules to determine whether a triggering condition exists. In embodiments, the one or more rules may be tailored to identify potentially dangerous and/or emergency situations. In these embodiments, the edge device 104 may trigger one or more notifications or alarms when a triggering condition exists. Additionally or alternatively, the edge device 104 may transmit the sensor data without any compression when a triggering condition exists.

[0315] FIG. 14 illustrates an example configuration of a server kit 1400 according to some embodiments of the present disclosure. In the example of FIG. 14, the server kit 1400 includes an edge device 104, a set of sensors 102, a set of collection devices 206, and a gateway device 1406. In embodiments, the configurations of the server kit 1400 are suited for industrial setting 120 covering a large area and where power sources are abundant; but where the industrial operator does not wish to connect the sensor kit 1400 to the private network of the industrial setting 120 and the walls of the industrial setting 120 make wireless communication (e.g., cellular communication)

unreliable or impossible. In embodiments, the gateway device 1406 is a cellular network gateway device that includes a cellular communication device (e.g., 4G, 5G chipset) with a transceiver that communicates with a cellular tower 1310. The cellular communication may be pre-configured to communicate with a cellular data provider. For example, in embodiments, the gateway device may include a SIM card that is registered with a cellular provider having a tower 1310 that is proximate to the industrial setting 120. In embodiments, the gateway device 1406 may communicate with the edge device 104 via a wired communication link 1408 (e.g., Ethernet). The edge device 104 may receive sensor data from the sensor kit network established by the sensor kit 1400. The edge device 104 may then transmit the sensor data to the gateway device 1406 via the wired communication link 1408. The gateway device 1406 may then communicate the sensor data to the backend system 150 via the cellular tower 1310.

[0316] The sensors 102 may include various types of sensors 102, which may vary depending on the industrial setting 120. In the illustrated example, the sensors 102 communicate with the edge device 104 via a hierarchical network. In these embodiments, the sensors 102 may communicate sensor data to collection devices 206, which, in turn, may communicate the sensor data to edge device 104 via a wired or wireless communication link. The hierarchical network may be deployed where the area being monitored is rather larger (e.g., over 40,000 sq. ft.) and power supplies are abundant, such as in a factory, a power plant, a food inspection facility, an indoor grow facility, and the like. While a hierarchical network is shown, the sensor kits 1400 of FIG. 14 may include alternative network topologies, such as a mesh topology or a star topology (e.g., sensors 102 communicate to the edge device directly).

[0317] In embodiments, the edge device 104 may be configured to perform one or more AI-related tasks prior to transmission via the satellite uplink. In some of these embodiments, the edge device 104 may be configured to determine whether there are likely no issues relating to any of the components and/or the industrial setting 120 based on the sensor data and one or more machine-learned models. In embodiments, the edge device 104 may receive the sensor data from the various sensors and may generate one or more feature vectors based thereon. The feature vectors may include sensor data from a single sensor 102, a subset of sensors 102, or all of the sensors 102 of the sensor kit 1400. In scenarios where a single sensor or a subset of sensors 102 are included in the feature vector, the machine-learned model may be trained to identify one or more issues relating to an industrial component or the industrial setting 120, but may not be sufficient to fully deem the entire setting as likely safe/free from issues. Additionally or alternatively, the feature vectors may correspond to a single snapshot in time (e.g., all sensor data in the feature vector corresponds to the same sampling event) or over a period of time (sensor data samples from a most recent sampling event and sensor data samples from previous sampling events). In embodiments where the feature

vectors define sensor data from a single snapshot, the machine-learned models may be trained to identify potential issues without any temporal context. In embodiments where the feature vectors define sensor data over a period of time, the machine-learned models may be trained to identify potential issues with the context of what the sensor(s) 102 was/were reporting previously. In these
5 embodiments, the edge device 104 may maintain a cache of sensor data that is sampled over a predetermined time (e.g., previous hour, previous day, previous N days), such that the cache is cleared out in a first-in-first-out manner. In these embodiments, the edge device 104 may retrieve the previous sensor data samples from the cache to use to generate feature vectors that have data samples spanning a period of time.

10 [0318] In embodiments, the edge device 104 may feed the one or more feature vectors into one or more respective machine-learned models. A respective model may output a prediction or classification relating to an industrial component and/or the industrial setting 120, and a confidence score relating to the prediction or classification. In some embodiments, the edge device 104 may make determinations relating to the manner by which sensor data is transmitted to the backend
15 system 150 and/or stored at the edge device. For instance, in some embodiments, the edge device 104 may compress sensor data based on the prediction or classification. In some of these embodiments, the edge device 104 may compress sensor data when there are no likely issues across the entire industrial setting 120 and individual components of the industrial setting 120. For example, if the machine-learned models predict that there are likely no issues and classify that
20 there are currently no issues with a high degree of confidence (e.g., the confidence score is greater than .98), the edge device 104 may compress the sensor data. Alternatively, in the scenario where the machine-learned models predict that there are likely no issues and classify that there are currently no issues with a high degree of confidence, the edge device 104 may forego transmission but may store the sensor data at the edge device 104 for a predefined period of time (e.g., one year).

25 In scenarios where a machine-learned model predicts a potential issue or classifies a current issue, the edge device 104 may transmit the sensor data without compressing the sensor data or using a lossless compression codec. In this way, the amount of bandwidth that is transmitted via the cellular tower may be reduced, as the majority of the time the sensor data will be compressed or not transmitted.

30 [0319] In embodiments, the edge device 104 may apply one or more rules to determine whether a triggering condition exists. In embodiments, the one or more rules may be tailored to identify potentially dangerous and/or emergency situations. In these embodiments, the edge device 104 may trigger one or more notifications or alarms when a triggering condition exists. Additionally or alternatively, the edge device 104 may transmit the sensor data without any compression when a
35 triggering condition exists.

[0320] FIG. 15 illustrates an example configuration of a server kit 1500 for installation in an agricultural setting 1520 according to some embodiments of the present disclosure. In the example of FIG. 15, the server kit 1500 is configured for installation in an indoor agricultural setting 1520 that may include, but is not limited to, a control system 1522, an HVAC system 1524, a lighting system 1526, a power system 1528, and/or an irrigation system 1530. In this example, various features and components of the agricultural setting include components that are monitored by a set of sensors 102. In embodiments, the sensors 102 capture instances of sensor data and provide the respective instances of sensor data to an edge device 104. In the example embodiments of FIG. 15, the sensor kit 1500 includes a set of collection devices 206 that route sensor data from the sensors 102 to the edge device 104. Sensor kits 1500 for deployment in agricultural settings may have different sensor kit network topologies as well. For instance, in facilities not having more than two or three rooms being monitored, the sensor kit network may be a mesh or star network, depending on the distances between the edge device 104 and the furthest potential sensor location. For example, if the distance between the edge device 104 and the furthest potential sensor location is greater than 150 meters, then the sensor kit network may be configured as a mesh network. In the embodiments of FIG. 15, the edge device 104 transmits the sensor data to the backend system 150 directly. In these embodiments, the edge device 104 includes a cellular communication device that communicates with a cellular tower 1310 of a preset cellular provider via a preconfigured cellular connection to a cellular tower 1310. In other embodiments of the disclosure, the edge device 104 transmits the sensor data to the backend system 150 via a gateway device (e.g., gateway device 1406) that includes a cellular communication device that communicates with a cellular tower 1310 of a preset cellular provider.

[0321] In embodiments, a server kit 1500 may include any suitable combination of light sensors 1502, weight sensors 1504, temperature sensors 1506, CO₂ sensors 1508, humidity sensors 1510, fan speed sensors 1512, and/or audio/visual (AV) sensors 1514 (e.g., cameras). Sensor kits 1500 may be arranged with additional or alternative sensors 102. In embodiments, the sensor data collected by the edge device 104 may include ambient light measurements indicating an amount of ambient light detected in the area of a light sensor 1502. In embodiments, the sensor data collected by the edge device 104 may include a weight or mass measurements indicating a weight or mass of an object (e.g., a pot or tray containing one or more plants) that is resting upon a weight sensor 1504. In embodiments, the sensor data collected by the edge device 104 may include temperature measurements indicating an ambient temperature in the vicinity of a temperature sensor 1506. In embodiments, the sensor data collected by the edge device 104 may include humidity measurements indicating an ambient humidity in the vicinity of a humidity sensor 1510 or moisture measurements indicating a relative amount of moisture in a medium (e.g., soil)

monitored by a humidity sensor 1510. In embodiments, the sensor data collected by the edge device 104 may include CO₂ measurements indicating ambient levels of CO₂ in the vicinity of a CO₂ sensor 1508. In embodiments, the sensor data collected by the edge device 104 may include temperature measurements indicating an ambient temperature in the vicinity of a temperature sensor 1506. In embodiments, the sensor data collected by the edge device 104 may include fan speed measurements indicating a measured speed of a fan (e.g., a fan of an HVAC system 1524) as measured by a fan speed sensor 1512. In embodiments, the sensor data collected by the edge device 104 may include video signals captured by an AV sensor 1516. The sensor data captured by sensors 102 and collected by the edge device 104 may include additional or alternative types of sensor data without departing from the scope of the disclosure.

[0322] In embodiments, the edge device 104 is configured to perform one or more edge operations on the sensor data. For example, the edge device 104 may pre-process the received sensor data. In embodiments, the edge device 104 may predict or classify potential issues with one or more components of the HVAC system 1524, lighting system 1526, power system 1528, the irrigation system 1530; the plants growing in the agricultural facility; and/or the facility itself. In embodiments, the edge device 104 may analyze the sensor data with respect to a set of rules that define triggering conditions. In these embodiments, the edge device 104 may trigger alarms or notifications in response to a triggering condition being met. In embodiments, the edge device 104 may encode, compress, and/or encrypt the sensor data, prior to transmission to the backend system 150. In some of these embodiments, the edge device 104 may selectively compress the sensor data based on predictions or classifications made by the edge device 104 and/or upon one or more triggering conditions being met.

[0323] In embodiments, the edge device 104 may be configured to perform one or more AI-related tasks prior to transmission via the satellite uplink. In some of these embodiments, the edge device 104 may be configured to determine whether there are likely no issues relating to any of the components and/or the industrial setting 120 based on the sensor data and one or more machine-learned models. In embodiments, the edge device 104 may receive the sensor data from the various sensors and may generate one or more feature vectors based thereon. The feature vectors may include sensor data from a single sensor 102, a subset of sensors 102, or all of the sensors 102 of the sensor kit 1300. In scenarios where a single sensor or a subset of sensors 102 are included in the feature vector, the machine-learned model may be trained to identify one or more issues relating to an industrial component or the industrial setting 120, but may not be sufficient to fully deem the entire setting as likely safe/free from issues. Additionally or alternatively, the feature vectors may correspond to a single snapshot in time (e.g., all sensor data in the feature vector corresponds to the same sampling event) or over a period of time (sensor data samples from a most recent sampling

event and sensor data samples from previous sampling events). In embodiments where the feature vectors define sensor data from a single snapshot, the machine-learned models may be trained to identify potential issues without any temporal context. In embodiments where the feature vectors define sensor data over a period of time, the machine-learned models may be trained to identify potential issues with the context of what the sensor(s) 102 was/were reporting previously. In these embodiments, the edge device 104 may maintain a cache of sensor data that is sampled over a predetermined time (e.g., previous hour, previous day, previous N days), such that the cache is cleared out in a first-in-first-out manner. In these embodiments, the edge device 104 may retrieve the previous sensor data samples from the cache to use to generate feature vectors that have data samples spanning a period of time.

[0324] In embodiments, the edge device 104 may feed the one or more feature vectors into one or more respective machine-learned models. A respective model may output a prediction or classification relating to an industrial component and/or the industrial setting 120, and a confidence score relating to the prediction or classification. In some embodiments, the edge device 104 may make determinations relating to the manner by which sensor data is transmitted to the backend system 150 and/or stored at the edge device. For instance, in some embodiments, the edge device 104 may compress sensor data based on the prediction or classification. In some of these embodiments, the edge device 104 may compress sensor data when there are no likely issues across the entire industrial setting 120 and individual components of the industrial setting 120. For example, if the machine-learned models predict that there are likely no issues and classify that there are currently no issues with a high degree of confidence (e.g., the confidence score is greater than .98), the edge device 104 may compress the sensor data. Alternatively, in the scenario where the machine-learned models predict that there are likely no issues and classify that there are currently no issues with a high degree of confidence, the edge device 104 may forego transmission but may store the sensor data at the edge device 104 for a predefined period of time (e.g., one year). In scenarios where a machine-learned model predicts a potential issue or classifies a current issue, the edge device 104 may transmit the sensor data without compressing the sensor data or using a lossless compression codec. In this way, the amount of bandwidth that is transmitted via the cellular tower may be reduced, as the majority of the time the sensor data will be compressed or not transmitted.

[0325] In embodiments, the edge device 104 may apply one or more rules to the sensor data to determine whether a triggering condition exists. In embodiments, the one or more rules may be tailored to identify potentially dangerous and/or emergency situations. In these embodiments, the edge device 104 may trigger one or more notifications or alarms when a triggering condition exists. Additionally or alternatively, the edge device 104 may transmit the sensor data without any

compression when a triggering condition exists. In some embodiments, the edge device 104 may selectively compress and/or transmit the sensor data based on the application of the one or more rules to the sensor data.

[0326] In embodiments, the backend system 150 may perform one or more backend operations based on received sensor data. In embodiments, the backend system 150 may decode/decompress/decrypt the sensor data received from respective sensor kits 1500. In embodiments, the backend system 150 may preprocess received sensor data. In embodiments, the backend system 150 may preprocess sensor data received from a respective server kit 1500. For example, the backend system 150 may filter, dedupe, and/or structure the sensor data. In embodiments, the backend system 150 may perform one or more AI-related tasks using the sensor data. In some of these embodiments, the backend system 150 may extract features from the sensor data, which may be used to predict or classify certain conditions or events relating to the agricultural setting. For example, the backend system 150 may deploy models used to predict yields of a crop based on weight measurements, temperature measurements, CO₂ measurements, light measurements, and/or other extracted features. In another example, the backend system 150 may deploy models used to predict or classify mold-inducing states in a room or area of the agricultural facility based on temperature measurements, humidity measurements, video signals or images, and/or other extracted features. In embodiments, the backend system 150 may perform one or more analytics tasks on the sensor data and may display the results to a human user via a dashboard. In some embodiments, the backend system 150 may receive control commands from a human user via the dashboard. For example, a human resource with sufficient login credentials may control an HVAC system 1524, a lighting system 1526, a power system 1528, and/or an irrigation system 1530 of the industrial setting 120. In some of these embodiments, the backend system 150 may telemetrically monitor the actions of the human user, and may train one or more machine-learned models (e.g., neural networks) on actions to take in response to displaying the analytics results to the human user. In other embodiments, the backend system 150 may execute one or more workflows associated with the HVAC system 1524, the lighting system 1526, the power system 1528, and/or the irrigation system 1530, in order to control one or more of the systems of the agricultural setting 1520 based on a prediction or classification made by the backend system in response to the sensor data. In embodiments, the backend system 150 provides one or more control commands to a control system 1522 of an agricultural setting 1520, which in turn may control the HVAC system 1524, the lighting system 1526, the power system 1528, and/or the irrigation system 1530 based on the received control commands. In embodiments, the backend system 150 may provide or utilize an API to provide control commands to the agricultural setting 1520.

[0327] FIG 16 – Exemplary Method of Monitoring Industrial Settings

[0328] FIG. 16 illustrates an example set of operations of a method 1600 for monitoring industrial setting 120 using an automatically configured backend system 150. In embodiments, the method 1600 may be performed by the backend system 150, the sensor kit 100, and the dashboard module 532.

[0329] At 1602, the backend system 150 registers the sensor kit 100 to a respective industrial setting 120. In some embodiments, the backend system 150 registers a plurality of sensor kits 100 and registers each sensor kit 100 of the plurality of sensor kits 100 to a respective industrial setting 120. In embodiments, the backend system 150 provides an interface for specifying a type of entity or industrial setting 120 to be monitored. In some embodiments, a user may select a set of parameters for monitoring of the respective industrial setting 120 of the sensor kit 100. The backend system 150 may automatically provision a set of services and capabilities of the backend system 150 based on the selected parameters.

[0330] At 1604, the backend system 150 configures the sensor kit 100 to monitor physical characteristics of the respective industrial setting 120 to which the sensor kit 100 is registered. For example, when the respective industrial setting 120 is a natural resource extraction setting, the backend system 150 may configure one or more of infrared sensors, ground penetrating sensors, light sensors, humidity sensors, temperature sensors, chemical sensors, fan speed sensors, rotational speed sensors, weight sensors, and camera sensors to monitor and collect sensor data relating to metrics and parameters of the natural resource extraction setting and equipment used therein.

[0331] At 1606, the sensor kit 100 transmits instances of sensor data to the backend system 150. In some embodiments, the sensor kit 100 transmits the instances of sensor data to the backend system 150 via a gateway device. The gateway device may provide a virtual container for instances of the sensor data such that only a registered owner or operator of the respective industrial setting 120 can access the sensor data via the backend system 150.

[0332] At 1608, the backend system 150 processes instances of sensor data received from the sensor kit 100. In some embodiments, the backend system 150 includes an analytics facility and/or a machine learning facility. The analytics facility and/or the machine learning facility may be configured based on the type of the industrial setting 120 and may process the instances of sensor data received from the sensor kit 100. In some embodiments, the backend system 150 updates and/or configures a distributed ledger based on the processed instances of sensor data.

[0333] At 1610, the backend system 150 configures and populates the dashboard. In embodiments, the backend system 150 configures the dashboard to retrieve and display one or more of raw sensor data provided by the sensor kit, analytical data relating to the sensor data provided by the sensor

kit 100, predictions or classifications made by the backend system 150 based on the sensor data, and the like. In some embodiments, the backend system 150 configures alarm limits with respect to one or more sensor types and/or conditions based on the industrial setting 120. The backend system 150 may define which users receive a notification when an alarm is triggered. In
5 embodiments, the backend system 150 may subscribe to additional features of the backend system 150 and/or an edge device 104 based on the industrial setting 120.

[0334] At 1612, the dashboard provides monitoring information to a human user. In embodiments, the dashboard provides monitoring information to the user by displaying the monitoring information on a device, e.g., a computer terminal, a smartphone, a monitor, or any other suitable
10 device for displaying information. The monitoring information may be provided via a graphical user interface.

[0335] FIG. 17 illustrates an exemplary manufacturing facility 1700 according to some embodiments of the present disclosure. The manufacturing facility 1700 may include a plurality of industrial machines 1702 including, by way of example, conveyor belts, assembly machines, die
15 machines, turbines, and power systems. The manufacturing facility 1700 may further include a plurality of products 1704. The manufacturing facility may have the sensor kit 100 installed therein, the sensor kit 100 including the plurality of sensors 102 and the edge device 104. By way of example, one or more of the sensors 102 may be installed on some or all of the industrial machines 1702 and the products 1704.

[0336] FIG. 18 illustrates a surface portion of an exemplary underwater industrial facility 1800 according to some embodiments of the present disclosure. The underwater industrial facility 1800 may include a transportation and communication platform 1802, a storage platform 1804, and a
20 pumping platform 1806. The underwater industrial facility 1800 may have the sensor kit 100 installed therein, the sensor kit 100 including the plurality of sensors 102 and the edge device 104. By way of example, one or more of the sensors 102 may be installed on some or all of the
25 transportation and communication platform 1802, the storage platform 1804, and the pumping platform 1806, and on individual components and machines thereof.

[0337] FIG. 19 illustrates an exemplary indoor agricultural facility 1900 according to some embodiments of the present disclosure. The indoor agricultural facility 1900 may include a
30 greenhouse 1902 and a plurality of wind turbines 1904. The indoor agricultural facility 1900 may have the sensor kit 100 installed therein, the sensor kit 100 including the plurality of sensors 102 and the edge device 104. By way of example, one or more of the sensors 102 may be installed on some or all components of the greenhouse 1904 and on some or all components of the wind turbines 1904.

[0338] In embodiments, provided herein are methods and systems for monitoring industrial
35

settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the

public network on behalf of the edge device and having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having sensors and an edge device that compresses sensor data collected by the sensor using a media codec. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having sensors and an edge device that are configured to monitor an indoor agricultural setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth,

latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having sensors and an edge device that are configured to monitor a natural resource extraction setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having sensors and an edge device that are configured to monitor a pipeline setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having sensors and an edge device that are configured to monitor a manufacturing facility. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having sensors and an edge device that are configured to monitor an underwater industrial setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while

mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data.

In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth,

latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial

action in response to a particular issue being detected. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings,

including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security including a gateway device that is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0339] In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device

of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second

communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having sensors and an edge device that compresses sensor data collected by the sensor using a media codec. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having sensors and an edge device that are configured to monitor an indoor agricultural setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having sensors and an edge device that are configured to monitor a natural resource extraction setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having sensors and an edge device that are configured to monitor a pipeline setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets

to a satellite that routes the sensor kits to the public network and having sensors and an edge device that are configured to monitor a manufacturing facility. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having sensors and an edge device that are configured to monitor an underwater industrial setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having an

edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating

5 issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein are methods and

10 systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and

15 having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating

20 issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein are

25 methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the

30 public network and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically

35 provisioned capabilities for monitoring industrial settings while mitigating issues of complexity,

integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring

and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a sensor kit and a backend system that

includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating

issues of complexity, integration, bandwidth, latency and security having the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0340] In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring

industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having sensors and an edge device that compresses sensor data collected by the sensor using a media codec. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having sensors and an edge device that are configured to monitor an indoor agricultural setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having sensors and an edge device that are configured to monitor a natural resource extraction setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having sensors and an edge device that are configured to monitor a pipeline setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store

a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having sensors and an edge device that are configured to monitor a manufacturing facility. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having sensors and an edge device that are configured to monitor an underwater industrial setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having an edge device that includes a data processing

module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more

storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge

device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor

kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the edge device further includes one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit and having a sensor, an edge device, and a gateway device

that communicates with a communication network on behalf of the sensor kit.

[0341] In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol.

In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor.

In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model.

In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having sensors and an edge device that compresses sensor data collected by the sensor using a media codec.

In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol

and having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having sensors and an edge device that are configured to monitor an indoor agricultural setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having sensors and an edge device that are configured to monitor a natural resource extraction setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having sensors and an edge device that are configured to monitor a pipeline setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having sensors and an edge device that are configured to monitor a manufacturing facility. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range

communication protocol and having sensors and an edge device that are configured to monitor an underwater industrial setting. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of

the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by

the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit

5 network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-

10 the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having a backend system that includes a data processing

15 module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring

20 sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial

25 settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol

30 and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration,

35 bandwidth, latency and security having the self-configuring sensor kit network is a star network

such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a

sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein are methods and systems for monitoring industrial settings, including through a variety of kits that provide out-of-the-box, self-configuring and automatically provisioned capabilities for monitoring

industrial settings while mitigating issues of complexity, integration, bandwidth, latency and security having the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0342] In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having sensors and an edge device that compresses sensor data collected by the sensor using a media codec. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having sensors and an edge device that are configured to monitor an indoor agricultural setting. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having sensors and an edge device that are configured to monitor a natural resource extraction setting. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having sensors and an edge device that are configured to monitor a pipeline setting. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having sensors and an edge device that are configured to monitor a manufacturing facility. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having sensors and an edge device that are configured to monitor an underwater industrial setting. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on

sensor data obtained from the sensor and having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having a backend system that includes a

decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In
embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an
edge device that performs one or more backend operations on sensor data obtained from the sensor
and having a backend system that includes a data processing module that executes a workflow
5 associated with a potential issue based on sensor data captured by the sensor kit. In embodiments,
provided herein is a sensor kit having sensors in a self-configuring network and an edge device
that performs one or more backend operations on sensor data obtained from the sensor and having
a backend system that includes an AI module that trains machine-learned models to make
predictions or classifications related to sensor data captured by a sensor kit. In embodiments,
10 provided herein is a sensor kit having sensors in a self-configuring network and an edge device
that performs one or more backend operations on sensor data obtained from the sensor and having
a backend system that includes a notification module that issues notifications to users when an
issue is detected in an industrial setting based on collected sensor data. In embodiments, provided
herein is a sensor kit having sensors in a self-configuring network and an edge device that performs
15 one or more backend operations on sensor data obtained from the sensor and having a backend
system that includes an analytics module that performs analytics tasks on sensor data received from
the sensor kit. In embodiments, provided herein is a sensor kit having sensors in a self-configuring
network and an edge device that performs one or more backend operations on sensor data obtained
from the sensor and having a backend system that includes a control module that provides
20 commands to a device or system in an industrial setting to take remedial action in response to a
particular issue being detected. In embodiments, provided herein is a sensor kit having sensors in
a self-configuring network and an edge device that performs one or more backend operations on
sensor data obtained from the sensor and having a backend system that includes a dashboard
module that presents a dashboard to a human user that provides the human user with raw sensor
25 data, analytical data, and/or predictions or classifications based on sensor data received from the
sensor kit. In embodiments, provided herein is a sensor kit having sensors in a self-configuring
network and an edge device that performs one or more backend operations on sensor data obtained
from the sensor and having a backend system that includes a dashboard module that presents a
dashboard to a human user that provides a graphical user interface that allows the user to configure
30 the sensor kit system. In embodiments, provided herein is a sensor kit having sensors in a self-
configuring network and an edge device that performs one or more backend operations on sensor
data obtained from the sensor and having a sensor kit and a backend system that includes a
configuration module that maintains configurations of the sensor kit and configures a sensor kit
network by transmitting configuration requests to sensor devices, generating device records based
35 on responses to the configuration requests, and/or adding new sensors to the sensor kit. In

embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit having sensors in a self-

5 configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained

10 from the sensor and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having sensor kit and a backend system that updates a smart contract, wherein the smart

15 contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors in a self-configuring network and an edge device that performs one or more backend operations on sensor data obtained from the sensor and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

20 **[0343]** In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having sensors and an edge device that

25 compresses sensor data collected by the sensor using a media codec. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data. In embodiments, provided

30 herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having sensors and an edge device that are configured to monitor an indoor agricultural setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an

35 appropriate model and having sensors and an edge device that are configured to monitor a natural

resource extraction setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having sensors and an edge device that are configured to monitor a pipeline setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having sensors and an edge device that are configured to monitor a manufacturing facility. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having sensors and an edge device that are configured to monitor an underwater industrial setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and

having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and

5 having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an

10 appropriate model and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and

15 having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having

20 sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based

25 on sensor data obtained from the sensor using an appropriate model and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having a backend system

30 that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response

35 to a particular issue being detected. In embodiments, provided herein is a sensor kit having sensors

and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge device that stores multiple models and performs AI-related tasks based on sensor data obtained from the sensor using an appropriate model and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0344] In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having sensors and an edge device that are configured to monitor an indoor agricultural setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having sensors and an edge device that are configured to monitor a natural resource extraction setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having sensors and an edge device that are configured to monitor a pipeline setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having sensors and an edge device that are configured to monitor a manufacturing facility. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having sensors and an edge device that are configured to monitor an underwater industrial setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor

using a media codec and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by

the sensor using a media codec and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that
5 compresses sensor data collected by the sensor using a media codec and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having a sensor kit and a backend system that
10 includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having a sensor kit and a
15 backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors
20 and an edge device that compresses sensor data collected by the sensor using a media codec and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having sensor kit and a backend system that updates a smart
25 contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge device that compresses sensor data collected by the sensor using a media codec and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

30 [0345] In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having sensors and an edge
35 device that are configured to monitor an indoor agricultural setting. In embodiments, provided

herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having sensors and an edge device that are configured to monitor a natural resource extraction setting. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having sensors and an edge device that are configured to monitor a pipeline setting. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having sensors and an edge device that are configured to monitor a manufacturing facility. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having sensors and an edge device that are configured to monitor an underwater industrial setting. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having an edge device that includes a quick-decision AI module that uses machine-learned

models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having an edge device that includes

5 a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests

10 to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data

15 captured by the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system

20 configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more

25 backend operations on the sensor data and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having a backend system that includes a

30 notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the

35 sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend

system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit

5 system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system

10 having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to

15 receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided

20 herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform

25 one or more backend operations on the sensor data and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having a distributed ledger that is

30 at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions

35 put forth by a regulatory body with respect to compliance with a regulation or regulatory action.

In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system configured to receive sensor data collected by the sensor kit and perform one or more backend operations on the sensor data and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

- 5 [0346] In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having sensors and an edge device that are configured to monitor a natural resource extraction setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that are
- 10 configured to monitor an indoor agricultural setting and having sensors and an edge device that are configured to monitor a pipeline setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having sensors and an edge device that are configured to monitor a manufacturing facility. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured
- 15 to monitor an indoor agricultural setting and having sensors and an edge device that are configured to monitor an underwater industrial setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data. In embodiments, provided
- 20 herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor
- 25 kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having an edge device that includes an encoding module that
- 30 encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In
- 35 embodiments, provided herein is a sensor kit having sensors and an edge device that are configured

to monitor an indoor agricultural setting and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having an edge device that

5 includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having an edge device that includes a distributed ledger module configured to update a

10 distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and

15 having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a

20 sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having

25 a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments,

30 provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured

35 to monitor an indoor agricultural setting and having a backend system that includes a dashboard

module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an indoor agricultural setting and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0347] In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having sensors and an edge device that are configured to monitor a pipeline setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having sensors and an edge device that are configured to monitor a manufacturing facility. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having sensors and an edge device that are configured to monitor an underwater industrial setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having a sensor kit that collects sensor data and a backend system that receives the sensor data from the

sensor kits and updates a distributed ledger based on the sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data.

10 In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In

25 embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having

35 sensors and an edge device that are configured to monitor a natural resource extraction setting and

having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a natural resource extraction setting and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors

and an edge device that are configured to monitor a natural resource extraction setting and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge
5 device that are configured to monitor a natural resource extraction setting and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0348] In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting. In embodiments, provided herein is a sensor kit having
10 sensors and an edge device that are configured to monitor a pipeline setting and having sensors and an edge device that are configured to monitor a manufacturing facility. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having sensors and an edge device that are configured to monitor an underwater industrial setting. In embodiments, provided herein is a sensor kit having sensors and
15 an edge device that are configured to monitor a pipeline setting and having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments,
20 provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having
an edge device that includes a data processing module that deduplicates, filters, flags, and/or
25 aggregates sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having an edge device that includes a quick-
30 decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor
35 data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are

configured to monitor a pipeline setting and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor

kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In
5 embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that
10 are configured to monitor a pipeline setting and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth
15 by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a pipeline setting and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0349] In embodiments, provided herein is a sensor kit having sensors and an edge device that are
20 configured to monitor a manufacturing facility. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having sensors and an edge device that are configured to monitor an underwater industrial setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having a sensor kit that collects sensor data and
25 a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing
30 facility and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge
35 device that are configured to monitor a manufacturing facility and having an edge device that

includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data.

5 In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments,

10
15
20
25
30
35

provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In

5 embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having

10 sensors and an edge device that are configured to monitor a manufacturing facility and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors

15 and an edge device that are configured to monitor a manufacturing facility and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and

20 an edge device that are configured to monitor a manufacturing facility and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having sensor kit and a backend system that updates a smart contract, wherein the smart contract

25 verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor a manufacturing facility and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

30 **[0350]** In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data. In

35 embodiments, provided herein is a sensor kit having sensors and an edge device that are configured

to monitor an underwater industrial setting and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is

a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body

with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge device that are configured to monitor an underwater industrial setting and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

5 [0351] In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding

new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that

receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a sensor kit that collects sensor data and a backend system that receives the sensor data from the sensor kits and updates a distributed ledger based on the sensor data and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0352] In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In embodiments, provided herein is a sensor kit having sensors

and an edge device that is configured to add new sensors to the sensor kit and having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having an edge device that includes an
5 encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In
10 embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having an edge device that includes a
15 configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having an edge device that includes a distributed ledger module configured to update a distributed ledger
20 with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having a backend system
25 that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments,
30 provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having a backend system that includes
35 an analytics module that performs analytics tasks on sensor data received from the sensor kit. In

embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit
5 having sensors and an edge device that is configured to add new sensors to the sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor
10 kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a
15 sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments,
20 provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having a distributed ledger that is at least
25 partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory
30 action. In embodiments, provided herein is a sensor kit having sensors and an edge device that is configured to add new sensors to the sensor kit and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0353] In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit. In
35 embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device

that communicates with a communication network on behalf of the sensor kit and having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having a backend system that includes a notification module that issues notifications to users when an issue is

detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In

5 embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments,

10 provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having

15 sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having a sensor kit and a backend system that includes a configuration module

20 that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having a sensor kit and a backend system

25 that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit

30 having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and

35 having sensor kit and a backend system that updates a smart contract, wherein the smart contract

verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having sensors, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0354] In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having a backend system that includes

an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having a backend system that includes a notification module that issues
5 notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device
10 that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having
15 a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having a backend system that includes a dashboard module that presents
20 a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting
25 configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In
30 embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or
35 aggregates sensor data and having a distributed ledger that is at least partially shared with a

regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having an edge device that includes a data processing module that deduplicates, filters, flags, and/or aggregates sensor data and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

5

10 [0355] In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor

15

20

25

30

35

data captured by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data

5 data captured by a sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having an edge device that includes

10 an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having a backend system

15 that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having a backend system that includes a dashboard module that presents a dashboard to a human user that

20 provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user

25 interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices,

30 generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein

35 is a sensor kit having an edge device that includes an encoding module that encodes, compresses,

and/or encrypts sensor data according to one or more media codecs and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having an edge device that includes an encoding module that encodes, compresses, and/or encrypts sensor data according to one or more media codecs and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0356] In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data and having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data and having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial

components based on features of collected sensor data and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or

5 classifications of industrial components based on features of collected sensor data and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components

10 based on features of collected sensor data and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data

15 and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data and having a backend system that includes

20 an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data and having a backend system that includes a control module that provides commands to a device or system in

25 an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data and having a backend system that includes a dashboard module that presents a dashboard to a human user that

30 provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data and having a backend system that includes a dashboard module that

35 presents a dashboard to a human user that provides a graphical user interface that allows the user

to configure the sensor kit system. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having an edge device that includes a quick-decision AI module that uses machine-learned models to generate predictions related to and/or classifications of industrial components based on features of collected sensor data and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0357] In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having an edge device that includes a

configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In

embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having an edge device that includes a notification module that provides notifications and/or alarms to users based on sensor data and/or rules applied to the sensor data and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0358] In embodiments, provided herein is a sensor kit having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a configuration module that configures a sensor kit network by

transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device

5 that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having an edge device that includes a

10 configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device

15 that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is

20 a sensor kit having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments,

25 provided herein is a sensor kit having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit

30 having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In

35 embodiments, provided herein is a sensor kit having an edge device that includes a configuration

module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In 5 embodiments, provided herein is a sensor kit having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a backend system that includes a dashboard module that 10 presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and 15 having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a configuration module that configures a sensor kit network by transmitting 20 configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor 25 devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests 30 to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration 35 requests to sensor devices, generating device records based on responses to the configuration

requests, and/or adding new sensors to the sensor kit and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having an edge device that includes a configuration module that configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0359] In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having a backend

system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit having an edge device that includes a distributed ledger module configured to update a distributed ledger with sensor data captured by the sensor kit and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0360] In embodiments, provided herein is a sensor kit system having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets. In embodiments, provided herein is a sensor kit system having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit

packets and having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets and

5 having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets and having a backend

10 system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit system having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes

15 a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit system having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit

20 packets and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets and having a backend

25 system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit system having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets and having a sensor kit

30 and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets and having a sensor kit and a backend system that updates a distributed

35 ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor

kit system having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a backend system that includes a decoding module that decrypts, decodes, and/or decompresses encoded sensor kit packets and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0361] In embodiments, provided herein is a sensor kit system having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit and having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit system having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit system having a backend system that

includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit system having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a backend system that includes a data processing module that executes a workflow associated with a potential issue based on sensor data captured by the sensor kit and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0362] In embodiments, provided herein is a sensor kit system having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit and having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit system having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit system having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit system having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes an

AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a backend system that includes an AI module that trains machine-learned models to make predictions or classifications related to sensor data captured by a sensor kit and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0363] In embodiments, provided herein is a sensor kit system having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. In embodiments, provided herein is a sensor kit system having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data and having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected. In embodiments, provided herein is a sensor kit system having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. and having a backend system that includes a dashboard

module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit system having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. and having

5 a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a notification module that issues notifications to

10 users when an issue is detected in an industrial setting based on collected sensor data. and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. and having a sensor kit and a backend system

15 that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance

20 with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory

25 action. In embodiments, provided herein is a sensor kit system having a backend system that includes a notification module that issues notifications to users when an issue is detected in an industrial setting based on collected sensor data. and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0364] In embodiments, provided herein is a sensor kit system having a backend system that

30 includes an analytics module that performs analytics tasks on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit and having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being

35 detected. In embodiments, provided herein is a sensor kit system having a backend system that

includes an analytics module that performs analytics tasks on sensor data received from the sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided
5 herein is a sensor kit system having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit system having a backend system that includes an analytics module
10 that performs analytics tasks on sensor data received from the sensor kit and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a
15 backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit and having a sensor kit and a backend system that
20 updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory
25 action. In embodiments, provided herein is a sensor kit system having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system
30 having a backend system that includes an analytics module that performs analytics tasks on sensor data received from the sensor kit and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0365] In embodiments, provided herein is a sensor kit system having a backend system that includes a control module that provides commands to a device or system in an industrial setting to
35 take remedial action in response to a particular issue being detected. In embodiments, provided

herein is a sensor kit system having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In 5 embodiments, provided herein is a sensor kit system having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided 10 herein is a sensor kit system having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based 15 on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based 25 on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a backend system that includes a control module that provides commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein 35 is a sensor kit system having a backend system that includes a control module that provides

commands to a device or system in an industrial setting to take remedial action in response to a particular issue being detected and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0366] In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit and having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with

raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides the human user with raw sensor data, analytical data, and/or predictions or classifications based on sensor data received from the sensor kit and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

5

10 [0367] In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system. In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user

15 to configure the sensor kit system and having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a

20 dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user

25 interface that allows the user to configure the sensor kit system and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system

30 and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system and having sensor kit and a backend system that updates a smart

35 contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body

with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a backend system that includes a dashboard module that presents a dashboard to a human user that provides a graphical user interface that allows the user to configure the sensor kit system and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0368] In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a sensor kit and a backend system that updates a smart contract defining a condition that may trigger an action based on sensor data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system that includes a configuration module that maintains configurations of the sensor kit and configures a sensor kit network by transmitting

configuration requests to sensor devices, generating device records based on responses to the configuration requests, and/or adding new sensors to the sensor kit and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

5 [0369] In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system that updates a distributed ledger based on sensor data provided by the sensor kit. In
embodiments, provided herein is a sensor kit system having a sensor kit and a backend system that
updates a distributed ledger based on sensor data provided by the sensor kit and having a sensor
kit and a backend system that updates a smart contract defining a condition that may trigger an
10 action based on sensor data received from the sensor kit. In embodiments, provided herein is a
sensor kit system having a sensor kit and a backend system that updates a distributed ledger based
on sensor data provided by the sensor kit and having a distributed ledger that is at least partially
shared with a regulatory body to provide information related to compliance with a regulation or
regulatory action. In embodiments, provided herein is a sensor kit system having a sensor kit and
15 a backend system that updates a distributed ledger based on sensor data provided by the sensor kit
and having sensor kit and a backend system that updates a smart contract, wherein the smart
contract verifies one or more conditions put forth by a regulatory body with respect to compliance
with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system
having a sensor kit and a backend system that updates a distributed ledger based on sensor data
20 provided by the sensor kit and having a sensor, an edge device, and a gateway device that
communicates with a communication network on behalf of the sensor kit.

[0370] In embodiments, provided herein is a sensor kit system having a sensor kit and a backend
system that updates a smart contract defining a condition that may trigger an action based on sensor
data received from the sensor kit. In embodiments, provided herein is a sensor kit system having a
25 sensor kit and a backend system that updates a smart contract defining a condition that may trigger
an action based on sensor data received from the sensor kit and having a distributed ledger that is
at least partially shared with a regulatory body to provide information related to compliance with
a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a
sensor kit and a backend system that updates a smart contract defining a condition that may trigger
30 an action based on sensor data received from the sensor kit and having sensor kit and a backend
system that updates a smart contract, wherein the smart contract verifies one or more conditions
put forth by a regulatory body with respect to compliance with a regulation or regulatory action.
In embodiments, provided herein is a sensor kit system having a sensor kit and a backend system
that updates a smart contract defining a condition that may trigger an action based on sensor data
35 received from the sensor kit and having a sensor, an edge device, and a gateway device that

communicates with a communication network on behalf of the sensor kit.

[0371] In embodiments, provided herein is a sensor kit system having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action and having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having a distributed ledger that is at least partially shared with a regulatory body to provide information related to compliance with a regulation or regulatory action and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0372] In embodiments, provided herein is a sensor kit system having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action. In embodiments, provided herein is a sensor kit system having sensor kit and a backend system that updates a smart contract, wherein the smart contract verifies one or more conditions put forth by a regulatory body with respect to compliance with a regulation or regulatory action and having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0373] In embodiments, provided herein is a sensor kit having a sensor, an edge device, and a gateway device that communicates with a communication network on behalf of the sensor kit.

[0374] Detailed embodiments of the present disclosure are disclosed herein; however, it is to be understood that the disclosed embodiments are merely exemplary of the disclosure, which may be embodied in various forms. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ the present disclosure in virtually any appropriately detailed structure.

[0375] The terms “a” or “an,” as used herein, are defined as one or more than one. The term “another,” as used herein, is defined as at least a second or more. The terms “including” and/or “having,” as used herein, are defined as comprising (i.e., open transition).

[0376] While only a few embodiments of the present disclosure have been shown and described, it will be obvious to those skilled in the art that many changes and modifications may be made thereunto without departing from the spirit and scope of the present disclosure as described in the following claims. All patent applications and patents, both foreign and domestic, and all other

publications referenced herein are incorporated herein in their entireties to the full extent permitted by law.

[0377] The methods and systems described herein may be deployed in part or in whole through a machine that executes computer software, program codes, and/or instructions on a processor. The present disclosure may be implemented as a method on the machine, as a system or apparatus as part of or in relation to the machine, or as a computer program product embodied in a computer readable medium executing on one or more of the machines. In embodiments, the processor may be part of a server, cloud server, client, network infrastructure, mobile computing platform, stationary computing platform, or other computing platforms. A processor may be any kind of computational or processing device capable of executing program instructions, codes, binary instructions and the like. The processor may be or may include a signal processor, digital processor, embedded processor, microprocessor or any variant such as a co-processor (math co-processor, graphic co-processor, communication co-processor and the like) and the like that may directly or indirectly facilitate execution of program code or program instructions stored thereon. In addition, the processor may enable the execution of multiple programs, threads, and codes. The threads may be executed simultaneously to enhance the performance of the processor and to facilitate simultaneous operations of the application. By way of implementation, methods, program codes, program instructions and the like described herein may be implemented in one or more threads. The thread may spawn other threads that may have assigned priorities associated with them; the processor may execute these threads based on priority or any other order based on instructions provided in the program code. The processor, or any machine utilizing one, may include non-transitory memory that stores methods, codes, instructions and programs as described herein and elsewhere. The processor may access a non-transitory storage medium through an interface that may store methods, codes, and instructions as described herein and elsewhere. The storage medium associated with the processor for storing methods, programs, codes, program instructions or other type of instructions capable of being executed by the computing or processing device may include but may not be limited to one or more of a CD-ROM, DVD, memory, hard disk, flash drive, RAM, ROM, cache and the like.

[0378] A processor may include one or more cores that may enhance speed and performance of a multiprocessor. In embodiments, the process may be a dual core processor, quad core processors, other chip-level multiprocessor and the like that combine two or more independent cores (called a die).

[0379] The methods and systems described herein may be deployed in part or in whole through a machine that executes computer software on a server, client, firewall, gateway, hub, router, or other such computer and/or networking hardware. The software program may be associated with a server

that may include a file server, print server, domain server, Internet server, intranet server, cloud server, and other variants such as a secondary server, host server, distributed server and the like. The server may include one or more of memories, processors, computer readable media, storage media, ports (physical and virtual), communication devices, and interfaces capable of accessing
5 other servers, clients, machines, and devices through a wired or a wireless medium, and the like. The methods, programs, or codes as described herein and elsewhere may be executed by the server. In addition, other devices required for execution of methods as described in this application may be considered as a part of the infrastructure associated with the server.

[0380] The server may provide an interface to other devices including, without limitation, clients,
10 other servers, printers, database servers, print servers, file servers, communication servers, distributed servers, social networks, and the like. Additionally, this coupling and/or connection may facilitate remote execution of programs across the network. The networking of some or all of these devices may facilitate parallel processing of a program or method at one or more locations without deviating from the scope of the disclosure. In addition, any of the devices attached to the
15 server through an interface may include at least one storage medium capable of storing methods, programs, code and/or instructions. A central repository may provide program instructions to be executed on different devices. In this implementation, the remote repository may act as a storage medium for program code, instructions, and programs.

[0381] The software program may be associated with a client that may include a file client, print
20 client, domain client, Internet client, intranet client and other variants such as secondary client, host client, distributed client and the like. The client may include one or more of memories, processors, computer readable media, storage media, ports (physical and virtual), communication devices, and interfaces capable of accessing other clients, servers, machines, and devices through a wired or a wireless medium, and the like. The methods, programs, or codes as described herein
25 and elsewhere may be executed by the client. In addition, other devices required for the execution of methods as described in this application may be considered as a part of the infrastructure associated with the client.

[0382] The client may provide an interface to other devices including, without limitation, servers,
other clients, printers, database servers, print servers, file servers, communication servers,
30 distributed servers and the like. Additionally, this coupling and/or connection may facilitate remote execution of programs across the network. The networking of some or all of these devices may facilitate parallel processing of a program or method at one or more locations without deviating from the scope of the disclosure. In addition, any of the devices attached to the client through an interface may include at least one storage medium capable of storing methods, programs,
35 applications, code and/or instructions. A central repository may provide program instructions to be

executed on different devices. In this implementation, the remote repository may act as a storage medium for program code, instructions, and programs.

[0383] The methods and systems described herein may be deployed in part or in whole through network infrastructures. The network infrastructure may include elements such as computing devices, servers, routers, hubs, firewalls, clients, personal computers, communication devices, routing devices and other active and passive devices, modules and/or components as known in the art. The computing and/or non-computing device(s) associated with the network infrastructure may include, apart from other components, a storage medium such as flash memory, buffer, stack, RAM, ROM and the like. The processes, methods, program codes, instructions described herein and elsewhere may be executed by one or more of the network infrastructural elements. The methods and systems described herein may be adapted for use with any kind of private, community, or hybrid cloud computing network or cloud computing environment, including those which involve features of software as a service (SaaS), platform as a service (PaaS), and/or infrastructure as a service (IaaS).

[0384] The methods, program codes, and instructions described herein and elsewhere may be implemented on a cellular network having multiple cells. The cellular network may either be frequency division multiple access (FDMA) network or code division multiple access (CDMA) network. The cellular network may include mobile devices, cell sites, base stations, repeaters, antennas, towers, and the like. The cell network may be a GSM, GPRS, 3G, EVDO, mesh, or other network types.

[0385] The methods, program codes, and instructions described herein and elsewhere may be implemented on or through mobile devices. The mobile devices may include navigation devices, cell phones, mobile phones, mobile personal digital assistants, laptops, palmtops, netbooks, pagers, electronic book readers, music players and the like. These devices may include, apart from other components, a storage medium such as a flash memory, buffer, RAM, ROM and one or more computing devices. The computing devices associated with mobile devices may be enabled to execute program codes, methods, and instructions stored thereon. Alternatively, the mobile devices may be configured to execute instructions in collaboration with other devices. The mobile devices may communicate with base stations interfaced with servers and configured to execute program codes. The mobile devices may communicate on a peer-to-peer network, mesh network, or other communications network. The program code may be stored on the storage medium associated with the server and executed by a computing device embedded within the server. The base station may include a computing device and a storage medium. The storage device may store program codes and instructions executed by the computing devices associated with the base station.

[0386] The computer software, program codes, and/or instructions may be stored and/or accessed

on machine readable media that may include: computer components, devices, and recording media that retain digital data used for computing for some interval of time; semiconductor storage known as random access memory (RAM); mass storage typically for more permanent storage, such as optical discs, forms of magnetic storage like hard disks, tapes, drums, cards and other types; processor registers, cache memory, volatile memory, non-volatile memory; optical storage such as CD, DVD; removable media such as flash memory (e.g., USB sticks or keys), floppy disks, magnetic tape, paper tape, punch cards, standalone RAM disks, Zip drives, removable mass storage, off-line, and the like; other computer memory such as dynamic memory, static memory, read/write storage, mutable storage, read only, random access, sequential access, location addressable, file addressable, content addressable, network attached storage, storage area network, bar codes, magnetic ink, and the like.

[0387] The methods and systems described herein may transform physical and/or intangible items from one state to another. The methods and systems described herein may also transform data representing physical and/or intangible items from one state to another.

[0388] The elements described and depicted herein, including in flowcharts and block diagrams throughout the figures, imply logical boundaries between the elements. However, according to software or hardware engineering practices, the depicted elements and the functions thereof may be implemented on machines through computer executable media having a processor capable of executing program instructions stored thereon as a monolithic software structure, as standalone software modules, or as modules that employ external routines, code, services, and so forth, or any combination of these, and all such implementations may be within the scope of the present disclosure. Examples of such machines may include, but may not be limited to, personal digital assistants, laptops, personal computers, mobile phones, other handheld computing devices, medical equipment, wired or wireless communication devices, transducers, chips, calculators, satellites, tablet PCs, electronic books, gadgets, electronic devices, devices having artificial intelligence, computing devices, networking equipment, servers, routers and the like. Furthermore, the elements depicted in the flowchart and block diagrams or any other logical component may be implemented on a machine capable of executing program instructions. Thus, while the foregoing drawings and descriptions set forth functional aspects of the disclosed systems, no particular arrangement of software for implementing these functional aspects should be inferred from these descriptions unless explicitly stated or otherwise clear from the context. Similarly, it will be appreciated that the various steps identified and described above may be varied and that the order of steps may be adapted to particular applications of the techniques disclosed herein. All such variations and modifications are intended to fall within the scope of this disclosure. As such, the depiction and/or description of an order for various steps should not be understood to require a

particular order of execution for those steps, unless required by a particular application, or explicitly stated or otherwise clear from the context.

[0389] The methods and/or processes described above, and steps associated therewith, may be realized in hardware, software or any combination of hardware and software suitable for a particular application. The hardware may include a general-purpose computer and/or dedicated computing device or specific computing device or particular aspect or component of a specific computing device. The processes may be realized in one or more microprocessors, microcontrollers, embedded microcontrollers, programmable digital signal processors or other programmable devices, along with internal and/or external memory. The processes may also, or instead, be embodied in an application specific integrated circuit, a programmable gate array, programmable array logic, or any other device or combination of devices that may be configured to process electronic signals. It will further be appreciated that one or more of the processes may be realized as a computer executable code capable of being executed on a machine-readable medium. The computer executable code may be created using a structured programming language such as C, an object oriented programming language such as C++, or any other high-level or low-level programming language (including assembly languages, hardware description languages, and database programming languages and technologies) that may be stored, compiled or interpreted to run on one of the above devices, as well as heterogeneous combinations of processors, processor architectures, or combinations of different hardware and software, or any other machine capable of executing program instructions.

[0390] Thus, in one aspect, methods described above and combinations thereof may be embodied in computer executable code that, when executing on one or more computing devices, performs the steps thereof. In another aspect, the methods may be embodied in systems that perform the steps thereof, and may be distributed across devices in a number of ways, or all of the functionality may be integrated into a dedicated, standalone device or other hardware. In another aspect, the means for performing the steps associated with the processes described above may include any of the hardware and/or software described above. All such permutations and combinations are intended to fall within the scope of the present disclosure.

[0391] While the disclosure has been disclosed in connection with the preferred embodiments shown and described in detail, various modifications and improvements thereon will become readily apparent to those skilled in the art. Accordingly, the spirit and scope of the present disclosure is not to be limited by the foregoing examples but is to be understood in the broadest sense allowable by law.

[0392] The use of the terms "a" and "an" and "the" and similar referents in the context of describing the disclosure (especially in the context of the following claims) is to be construed to cover both

the singular and the plural unless otherwise indicated herein or clearly contradicted by context. The terms "comprising," "having," "including," and "containing" are to be construed as open-ended terms (i.e., meaning "including, but not limited to,") unless otherwise noted. Recitations of ranges of values herein are merely intended to serve as a shorthand method of referring individually to
5 each separate value falling within the range, unless otherwise indicated herein, and each separate value is incorporated into the specification as if it were individually recited herein. All methods described herein may be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., "such as") provided herein, is intended merely to better illuminate the disclosure and does
10 not pose a limitation on the scope of the disclosure unless otherwise claimed. No language in the specification should be construed as indicating any non-claimed element as essential to the practice of the disclosure.

[0393] While the foregoing written description enables one skilled in the art to make and use what is considered presently to be the best mode thereof, those skilled in the art will understand and
15 appreciate the existence of variations, combinations, and equivalents of the specific embodiment, method, and examples herein. The disclosure should therefore not be limited by the above-described embodiment, method, and examples, but by all embodiments and methods within the scope and spirit of the disclosure.

[0394] Any element in a claim that does not explicitly state "means for" performing a specified
20 function, or "step for" performing a specified function, is not to be interpreted as a "means" or "step" clause as specified in 35 U.S.C. § 112(f). In particular, any use of "step of" in the claims is not intended to invoke the provision of 35 U.S.C. § 112(f).

[0395] Persons skilled in the art may appreciate that numerous design configurations may be possible to enjoy the functional benefits of the inventive systems. Thus, given the wide variety of
25 configurations and arrangements of embodiments of the present invention the scope of the invention is reflected by the breadth of the claims below rather than narrowed by the embodiments described above.

CLAIMS

What is claimed is:

- 5 1. A sensor kit configured for monitoring an industrial setting, the sensor kit comprising:
an edge device; and
a plurality of sensors that capture sensor data and transmit the sensor data via a self-
configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a
first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of
10 the plurality of sensors comprises:
a sensing component that captures sensor measurements and outputs instances of
sensor data;
a processing unit that generates reporting packets based on one or more instances
of sensor data and outputs the reporting packets, wherein each reporting packet includes
15 routing data and one or more instances of sensor data; and
a communication device configured to receive reporting packets from the
processing unit and to transmit the reporting packets to the edge device via the self-
configuring sensor kit network in accordance with a first communication protocol;
wherein the edge device comprises:
20 a communication system having:
a first communication device that receives reporting packets from the
plurality of sensors via the self-configuring sensor kit network; and
a second communication device that transmits sensor kit packets to a
backend system via a public network;
25 a processing system having one or more processors that execute computer-
executable instructions that cause the processing system to:
receive the reporting packets from the communication system;
perform one or more edge operations on the instances of sensor data in the
reporting packets;
30 generate the sensor kit packets based on the instances of sensor data,
wherein each sensor kit packet includes at least one instance of sensor data; and
output the sensor kits packets to the communication system, wherein the
communication system transmits the reporting packets to the backend system via
the public network.

2. The sensor kit of claim 1, further comprising a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device.
- 5 3. The sensor kit of claim 2, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.
4. The sensor kit of claim 2, wherein the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.
- 10 5. The sensor kit of claim 1, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.
6. The sensor kit of claim 1, wherein the edge device further comprises one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality
15 of sensors of the sensor kit.
7. The sensor kit of claim 1, wherein the edge device further comprises one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of an industrial component of the industrial setting and/or the industrial setting based on a set of features that are derived from instances of sensor data
20 captured by one or more of the plurality of sensors.
8. The sensor kit of claim 7, wherein performing one or more edge operations includes:
generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;
inputting the feature vector to the machine-learned model to obtain a prediction or
25 classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification;
and
selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction.
- 30 9. The sensor kit of claim 8, wherein selectively encoding the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting, compressing the one or more instances of sensor data
35 using a lossy codec.

10. The sensor kit of claim 9, wherein compressing the one or more instances of sensor data using the lossy codec includes:

normalizing the one or more instances of sensor data into respective pixel values;

encoding the respective pixel values into a video frame; and

5 compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data.

11. The sensor kit of claim 9, wherein selectively encoding the one or more instances of sensor data includes:

10 in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, compressing the one or more instances of sensor data using a lossless codec.

12. The sensor kit of claim 9, wherein selectively encoding the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, refraining from compressing the one or more instances of sensor data.

20 13. The sensor kit of claim 7, wherein performing one or more edge operations includes:

generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and

selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification.

14. The sensor kit of claim 13, wherein selectively storing the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting, storing the one or more instances of sensor data in the storage device with an expiry, such that the one or more instances of sensor data are purged from

35 the storage device in accordance with the expiry.

15. The sensor kit of claim 13, wherein selectively storing the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, storing the one or more instances of sensor data in the storage device indefinitely.

16. The sensor kit of claim 1, wherein the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol.

17. The sensor kit of claim 16, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

18. The sensor kit of claim 1, wherein the self-configuring sensor kit network is a mesh network such that:

the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors; and

at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device.

19. The sensor kit of claim 18, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

20. The sensor kit of claim 1, wherein the self-configuring sensor kit network is a hierarchical network.

21. The sensor kit of claim 20, further comprising one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device.

22. The sensor kit of claim 1, wherein the self-configuring sensor kit network is a ring network that communicates using a serial data protocol.

23. The sensor kit of claim 1, wherein the sensor kit network is a mesh network.

24. The sensor kit of claim 1, wherein at least one of the sensors in the sensor kit network is a multi-axis vibration sensor.

25. The sensor kit network of claim 1, wherein the edge device includes a rule-based network protocol adaptor for selecting a network protocol by which to send sensor kit packets via the public network.
26. A method for monitoring an industrial setting using a sensor kit having a plurality of sensors and an edge device including a processing system, comprising:
- 5 receiving, by the processing system, reporting packets from one or more respective sensors of the plurality of sensors, wherein each reporting packet is sent from a respective sensor and indicates sensor data captured by the respective sensor;
- performing, by the processing system, one or more edge operations on one or more
- 10 instances of sensor data received in the reporting packets;
- generating, by the processing system, one or more sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data; and
- outputting, by the processing system, the sensor kit packets to a backend system via a public network.
- 15 27. The method of claim 26, wherein the reporting packets received from one or more respective sensors of the plurality of sensors include a sensor identifier of the respective sensor.
28. The method of claim 26, wherein receiving the reporting packets from the one or more respective sensors is performed using a first communication device implementing a first communication protocol and outputting the sensor kit packets to the backend system is performed
- 20 using a second communication device implementing a second communication protocol.
29. The method of claim 28, wherein the second communication device is a satellite terminal device, and outputting the sensor kit packets includes transmitting the sensor kit packets to a satellite using the satellite terminal device, wherein the satellite routes the sensor kit packets to the public network
- 25 30. The method of claim 26, wherein outputting the sensor kit packets to a backend system includes transmitting the sensor kit packets to a gateway device of the sensor kit.
31. The method of claim 30, wherein transmitting the sensor kit packets to the gateway device includes transmitting the sensor kit packets to the gateway via a wired communication link between the edge device and the gateway device.
- 30 32. The method of claim 31, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.
33. The method of claim 32, wherein the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

34. The method of claim 26, further comprising storing, by one or more storage devices of the edge device, a model data store that stores one or more machine-learned models.

35. The method of claim 34, wherein:

the one or more machine-learned models are trained to predict or classify a condition of an industrial component of the industrial setting and/or of the industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors.

36. The method of claim 35, wherein performing one or more edge operations includes:

generating a feature of vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting the feature vector to a machine-learned model of the one or more machine-learned models to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and

selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction.

37. The method of claim 36, wherein selectively encoding the one or more instances of sensor data includes:

compressing the one or more instances of sensor data using a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting.

38. The method of claim 37, wherein compressing the one or more instances of sensor data using the lossy codec includes:

normalizing the one or more instances of sensor data into respective pixel values;

encoding the respective pixel values into a video frame; and

compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data.

39. The method of claim 38, wherein selectively encoding the one or more instances of sensor data includes:

compressing the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular industrial component

or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

40. The method of claim 38, wherein selectively encoding the one or more instances of sensor data includes:

5 refraining from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

41. The method of claim 35, wherein performing one or more edge operations includes:

10 generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

 inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification;

15 and

 selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification.

42. The method of claim 41, wherein selectively storing the one or more instances of sensor data includes: storing the one or more instances of sensor data in the storage device with an expiry
20 such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry, wherein storing the one or more instances of sensor data in the storage device with an expiry is performed in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the
25 industrial setting and the industrial setting.

43. The method of claim 41, wherein selectively storing the one or more instances of sensor data includes:

 storing the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular industrial
30 component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

44. The method of claim 26, further comprising:

 capturing, by a sensing component of a sensor of the plurality of sensors, sensor measurements;

generating, by a processor of the sensor, one or more reporting packets based on the captured sensor measurements; and

transmitting, by a communication unit of the sensor, the one or more reporting packets to the edge device via a self-configuring sensor kit network.

5 45. The method of claim 44, further comprising:

initiating, by the processing system, configuration of the self-configuring sensor kit network, wherein the self-configuring sensor kit network is a star network.

46. The method of claim 45, wherein the reporting packets are received directly from respective sensors using a short-range communication protocol.

10 47. The method of claim 44, further comprising:

initiating, by the processing system, configuration of the self-configuring sensor kit network, wherein the self-configuring sensor kit network is a mesh network.

48. The method of claim 47, further comprising:

15 establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors;

receiving, by the at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and

routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device via the mesh network.

20 49. The method of claim 44, wherein the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices that participate in the hierarchical network.

50. The method of claim 49, further comprising:

25 receiving, by a collection device of the one or more collection devices, reporting packets from a set of sensors of the plurality of sensors that communicate with the collection device using a first short-range communication protocol; and

routing, by the one or more collection devices, the reporting packets to the edge device using one of the first short-range communication protocol or a second short-range communication protocol that is different than the second-range communication protocol.

30 51. The method of claim 26, wherein the edge device includes a rule-based network protocol adaptor.

52. The method of claim 51 further comprising:

selecting, by the rule-based network protocol adaptor, a network protocol; and

35 sending, by the edge device, sensor kit packets by the network protocol via the public network.

53. The method of claim 26, wherein the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.

54. A sensor kit configured for monitoring an industrial setting, the sensor kit comprising:
an edge device; and

5 a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of the plurality of sensors comprises:

10 a sensing component that captures sensor measurements and outputs instances of sensor data;

a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and

15 a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol;
wherein the edge device comprises:

20 one or more storage devices that store a model data store that stores a plurality of machine-learned models that are each trained to predict or classify a condition of an industrial component of the industrial setting or of the industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors;

25 a communication system that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network using a first communication protocol and that transmits sensor kit packets to a backend system via a public network using a second communication protocol that is different from the first communication protocol;
and

a processing system having one or more processors that execute computer-executable instructions that cause the processing system to:

30 receive the reporting packets from the communication system;

generate a set of feature vectors based on one or more respective instances of sensor data received in the reporting packets;

35 for each respective feature vector, input the respective feature vector into a respective machine-learned model that corresponds to the feature vector to obtain a respective prediction or classification relating to a condition of a respective

industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the respective prediction or classification;

5 selectively encode the one or more instances of sensor data prior to transmission to the backend system based on the respective predictions or classifications outputted by the machine-learned models in response to the respective feature vector to obtain one or more sensor kit packets; and

10 output the sensor kits packets to the communication system, wherein the communication system transmits the sensor kit packets to the backend system via the public network.

55. The sensor kit of claim 54, further comprising a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device.

15 56. The sensor kit of claim 55, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kit packets to the public network.

20 57. The sensor kit of claim 55, wherein the gateway device includes a cellular chipset that is pre-configured to transmit the sensor kit packets to a cellphone tower of a preselected cellular provider.

58. The sensor kit of claim 54, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

25 59. The sensor kit of claim 54, wherein the one or more storage devices store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

30 60. The sensor kit of claim 54, wherein selectively encoding the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting, compressing the one or more instances of sensor data using a lossy codec.

61. The sensor kit of claim 60, wherein compressing the one or more instances of sensor data using the lossy codec includes:

35 normalizing the one or more instances of sensor data into respective pixel values;
encoding the respective pixel values into a video frame;

compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data.

62. The sensor kit of claim 60, wherein selectively encoding the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, compressing the one or more instances of sensor data using a lossless codec.

63. The sensor kit of claim 60, wherein selectively encoding the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, refraining from compressing the one or more instances of sensor data.

64. The sensor kit of claim 54, wherein the computer-executable instructions further cause the one or more processors of the edge device to selectively store the one or more instances of sensor data in the one or more storage devices of the edge device based on the respective predictions or classifications.

65. The sensor kit of claim 64, wherein selectively storing the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting, storing the one or more instances of sensor data in the storage device with an expiry, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry.

66. The sensor kit of claim 64, wherein selectively storing the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, storing the one or more instances of sensor data in the storage device indefinitely.

67. The sensor kit of claim 54, wherein the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol.

68. The sensor kit of claim 67, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

69. The sensor kit of claim 54, wherein the self-configuring sensor kit network is a mesh network such that:

the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors;

at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device.

70. The sensor kit of claim 69, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

71. The sensor kit of claim 54, wherein the self-configuring sensor kit network is a hierarchical network.

72. The sensor kit of claim 71, further comprising one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device.

73. A method for monitoring an industrial setting using a sensor kit having a plurality of sensors and an edge device including a processing system, comprising:

receiving, by the processing system, reporting packets from one or more respective sensors of the plurality of sensors, wherein each reporting packet includes routing data and one or more instances of sensor data;

generating, by the processing system, a set of feature vectors based on one or more respective instances of sensor data received in the reporting packets;

inputting, by the processing system, each respective feature vector into a respective machine-learned model of a plurality of machine-learned models that are each trained to predict or classify a respective condition of an industrial component of the industrial setting or of the industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors;

obtaining, by the processing system, a respective prediction or classification and a degree of confidence corresponding to the respective prediction or classification from each respective machine-learned model based on the respective feature vector inputted into the respective machine-learned model;

selectively encoding, by the processing system, the one or more instances of sensor data based on the respective prediction or classification to obtain one or more sensor kit packets; and transmitting, by the processing system, the sensor kit packets to a backend system via a public network.

5 74. The method of claim 73, wherein the sensor kit includes a gateway device configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device.

75. The method of claim 74, wherein the gateway device includes a satellite terminal device that transmits the sensor kit packets to a satellite that routes the sensor kit packets to the public
10 network.

76. The method of claim 74, wherein the gateway device includes a cellular chipset that transmits the sensor kit packets to a cellphone tower of a preselected cellular provider.

77. The method of claim 73, wherein receiving the reporting packets from the one or more respective sensors is performed using a first communication device implementing a first
15 communication protocol and transmitting the sensor kit packets to the backend system is performed using a second communication device implementing a second communication protocol.

78. The method of claim 77, wherein the second communication device of the edge device is a satellite terminal device and transmitting the sensor kit packets to the backend system includes transmitting, by the satellite terminal device, the sensor kit packets to a satellite that routes the
20 sensor kit packets to the public network.

79. The method of claim 73, further comprising:

compressing, by the processing system, the one or more instances of sensor data using a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of the respective industrial components of the industrial setting and the industrial setting
25 that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting.

80. The method of claim 79, wherein compressing the one or more instances of sensor data using the lossy codec includes:

normalizing the one or more instances of sensor data into respective pixel values;

30 encoding the respective pixel values into a video frame; and

compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of the sensor data.

81. The method of claim 79, further comprising:

compressing, by the processing system, the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

5 82. The method of claim 79, further comprising:

refraining, by the processing system, from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

10 83. The method of claim 73, wherein the edge communication device includes one or more storage devices that store the plurality of machine-learned models.

84. The method of claim 83, wherein the one or more storage devices store instances of the sensor data captured by the plurality of sensors of the sensor kit.

85. The method of claim 84, further comprising selectively storing, by the processing system,
15 the one or more instances of sensor data in the one or more storage devices based on the respective predictions or classifications.

86. The method of claim 85, further comprising:

storing, by the processing system, the one or more instances of sensor data in the storage device with an expiry such that the one or more instances of sensor data are purged from the storage
20 device in accordance with the expiry, wherein the processing system stores the one or more instances of sensor data in the storage device with the expiry in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting.

25 87. The method of claim 85, further comprising:

storing, by the processing system, the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

30 88. The method of claim 73, further comprising:

capturing, by the plurality of sensors, sensor data; and

transmitting, by the plurality of sensors, the sensor data via a self-configuring sensor kit network.

89. The method of claim 88, wherein transmitting the sensor data via the self-configuring
35 sensor kit network includes directly transmitting, by each sensor of the plurality of sensors,

instances of sensor data with the edge device using a short-range communication protocol, wherein the self-configuring sensor kit network is a star network.

90. The method of claim 89, further comprising initiating, by the processing system, configuration of the self-configuring sensor kit network.

5 91. The method of claim 88, wherein the self-configuring sensor kit network is a mesh network and each sensor of the plurality of sensors includes a communication device.

92. The method of claim 91, further comprising:

establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors;

10 receiving, by at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and

routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device.

93. The method of claim 88, wherein the self-configuring sensor kit network is a hierarchical
15 network and the sensor kit includes one or more collection devices.

94. The method of claim 93, further comprising:

receiving, by at least one collection device of the plurality of collection devices, reporting packets from one or more sensors of the plurality of sensors; and

20 routing, by the at least one collection device of the plurality of collection devices, the reporting packets to the edge device.

95. The method of claim 73, wherein the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.

96. A sensor kit configured for monitoring an industrial setting, the sensor kit comprising:
an edge device; and

25 a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of the plurality of sensors comprises:

30 a sensing component that captures sensor measurements and outputs instances of sensor data;

a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and

a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol; wherein the edge device comprises:

5 a communication system having:

a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network; and

a second communication device that transmits sensor kit packets to a backend system via a public network; and

10 a processing system having one or more processors that execute computer-executable instructions that cause the processing system to:

receive the reporting packets from the communication system;

generate a block of media content frames, wherein each media content frame includes a plurality of frame values, each frame value being indicative of a
15 respective instance of sensor data;

compress the block of media content frames using a media codec to obtain a compressed block;

generate one or more server kit packets based on the compressed block; and

transmit the one or more server kit packets to the backend system via the

20 public network.

97. The sensor kit of claim 96, further comprising a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device.

25 98. The sensor kit of claim 97, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

99. The sensor kit of claim 97, wherein the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

30 100. The sensor kit of claim 96, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

101. The sensor kit of claim 96, wherein the edge device further comprises one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality
35 of sensors of the sensor kit.

102. The sensor kit of claim 96, wherein the edge device further comprises one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of an industrial component of the industrial setting and/or the industrial setting based on a set of features that are derived from instances of sensor data
5 captured by one or more of the plurality of sensors.

103. The sensor kit of claim 102, wherein the edge device is configured to perform one or more edge operations, the edge operations including:

generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

10 inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and

selecting the media codec used to compress the block of media frames based on the
15 classification or prediction.

104. The sensor kit of claim 103, wherein selecting the media codec includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial
20 setting, selecting a lossy codec.

105. The sensor kit of claim 104, wherein selecting the media codec includes: in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, selecting a lossless codec.

25 106. The sensor kit of claim 102, wherein performing one or more edge operations includes:

generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification;
30 and

selectively storing the one or more instances of sensor data in the storage device of the edge device based on the prediction or classification.

107. The sensor kit of claim 106, wherein selectively storing the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting, storing the one or more instances of sensor data in the storage device with an expiry, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry.

108. The sensor kit of claim 106, wherein selectively storing the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, storing the one or more instances of sensor data in the storage device indefinitely.

109. The sensor kit of claim 96, wherein the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol.

110. The sensor kit of claim 109, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

111. The sensor kit of claim 96, wherein the self-configuring sensor kit network is a mesh network such that:

the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors; and

at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device.

112. The sensor kit of claim 111, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

5 113. The sensor kit of claim 96, wherein the self-configuring sensor kit network is a hierarchical network.

114. The sensor kit of claim 113 further comprising one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device.

10 115. The sensor kit of claim 96, wherein generating the block of media content frames includes:
for each instance of sensor data that is to be included in a media content frame, normalizing the instance of sensor data into a respective normalized media content frame value that is within of range of media content frame values that are permitted by an encoding standard corresponding to the media content frame; and

15 embedding each respective normalized media content frame value into the media content frame.

116. The sensor kit of claim 115, wherein each media content frame is a video frame comprising a plurality of pixels and the respective normalized media content frame values are pixel values.

20 117. The sensor kit of claim 116, wherein embedding each respective normalized media frame value into the media frame includes:

determining a pixel of the plurality of pixels corresponding to the respective normalized media content frame based on a mapping that maps respective sensors of the plurality of sensors to respective pixels of the plurality of pixels; and

25 setting a value of the determined pixel equal to the respective normalized media frame value.

118. The sensor kit of claim 116, wherein the codec is an H.264/MPEG-4 codec.

119. The sensor kit of claim 116, wherein the codec is an H.265/MPEG-H codec.

120. The sensor kit of claim 116, wherein the codec is an H.263/MPEG-4 codec.

30 121. A method for monitoring an industrial setting using a sensor kit having a plurality of sensors and an edge device including a processing system, comprising:

receiving, by the processing system, reporting packets from one or more respective sensors of the plurality of sensors, wherein each reporting packet includes routing data and one or more instances of sensor data;

generating, by the processing system, a block of media content frames, wherein each media content frame includes a plurality of frame values, each frame value being indicative of a respective instance of sensor data;

compressing, by the processing system, the block of media content frames using a media
5 codec to obtain a compressed block;

generating, by the processing system, one or more server kit packets based on the compressed block; and

transmitting, by the processing system, the one or more server kit packets to a backend system via a public network.

10 122. The method of claim 121, wherein the sensor kit includes a gateway device configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device.

123. The method of claim 122, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the
15 public network.

124. The method of claim 122, wherein the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

125. The method of claim 121, wherein receiving the reporting packets from the one or more respective sensors is performed using a first communication device that receives reporting packets
20 from the plurality of sensors via a self-configuring sensor kit network and transmitting the sensor kit packets to the backend system is performed using a second communication device.

126. The method of claim 125, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

25 127. The method of claim 125, further comprising:

capturing, by the plurality of sensors, sensor data; and

transmitting, by the plurality of sensors, the sensor data to the edge device via the self-configuring sensor kit network.

128. The method of claim 127, wherein transmitting the sensor data via the self-configuring
30 sensor kit network includes directly transmitting, by each sensor of the plurality of sensors, instances of sensor data with the edge device using a short-range communication protocol, wherein the self-configuring sensor kit network is a star network.

129. The method of claim 128, further comprising initiating, by the processing system, configuration of the self-configuring sensor kit network.

130. The method of claim 127, wherein the self-configuring sensor kit network is a mesh network and each sensor of the plurality of sensors includes a communication device.

131. The method of claim 130, further comprising:

establishing, by the communication device of each sensor of the plurality of sensors, a
5 communication channel with at least one other sensor of the plurality of sensors;

receiving, by at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and

routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device.

10 132. The method of claim 127, wherein the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices.

133. The method of claim 132, further comprising:

receiving, by at least one collection device of the plurality of collection devices, reporting packets from one or more sensors of the plurality of sensors; and

15 routing, by the at least one collection device of the plurality of collection devices, the reporting packets to the edge device.

134. The method of claim 121, further comprising storing, by one or more storage devices of the edge device, instances of sensor data captured by the plurality of sensors of the sensor kit.

135. The method of claim 121, wherein the edge device further comprises one or more storage
20 devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of an industrial component of the industrial setting and/or the industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors.

136. The method of claim 135, further comprising:

25 generating, by the processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting, by the processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the
30 prediction or classification; and

selecting the media codec used to compress the block of media content frames based on the classification or prediction.

137. The method of claim 136, wherein selecting the media codec includes:

selecting a lossy codec in response to obtaining one or more predictions or classifications
35 relating to conditions of respective industrial components of the industrial setting and the industrial

setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting.

138. The method of claim 136, wherein selecting the media codec includes:

selecting a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

139. The method of claim 131, further comprising:

generating, by the processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting, by the processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and

selectively storing, by the processing system, the one or more instances of sensor data in the storage device of the edge device based on the prediction or classification.

140. The method of claim 139, wherein selectively storing the one or more instances of sensor data in the storage device includes:

storing the one or more instances of sensor data in the storage device with an expiry such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry, wherein storing the one or more instances of sensor data in the storage device with an expiry is performed in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting.

141. The method of claim 139, wherein selectively storing the one or more instances of sensor data in the storage device includes:

storing the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

142. The method of claim 121, wherein generating the block of media content frames includes:

normalizing, by the processing system, for each instance of sensor data that is to be included in a media content frame, the instance of sensor data into a respective normalized media content frame value that is within of range of media content frame values that are permitted by an encoding standard corresponding to the media content frame; and

embedding, by the processing system, each respective normalized media content frame value into the media content frame.

143. The method of claim 142, wherein each media content frame is a video frame comprising a plurality of pixels and the respective normalized media frame values are pixel values.

5 144. The method of claim 143, wherein embedding each respective normalized media content frame value into the media content frame includes:

determining, by the processing system, a pixel of the plurality of pixels corresponding to the respective normalized media content frame based on a mapping that maps respective sensors of the plurality of sensors to respective pixels of the plurality of pixels; and

10 setting a value of the determined pixel equal to the respective normalized media content frame value.

145. The method of claim 143, wherein the codec is an H.264/MPEG-4 codec.

146. The method of claim 143, wherein the codec is an H.265/MPEG-H codec.

147. The method of claim 143, wherein the codec is an H.263/MPEG-4 codec.

15 148. The method of claim 121, wherein the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.

149. A system comprising:

a backend system; and

a sensor kit configured to monitor an industrial setting, the sensor kit comprising:

20 an edge device; and

a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of the plurality of sensors comprises:

25 a sensing component that captures sensor measurements and outputs instances of sensor data;

a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and

30 a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol; wherein the edge device comprises:

a communication system having:

- a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network; and
- a second communication device that transmits sensor kit packets to a backend system via a public network; and
- 5 a processing system having one or more processors that execute computer-executable instructions that cause the processing system to:
- receive the reporting packets from the communication system;
 - perform one or more edge operations on the instances of sensor data in the reporting packets;
 - 10 generate the sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data; and
 - output the sensor kits packets to the communication system, wherein the communication system transmits the sensor kit packets to the backend
 - 15 system via the public network;
- wherein the backend system comprises:
- a backend storage system that stores a sensor kit data store that stores sensor data received from one or more respective sensor kits, including the sensor kit; and
 - a backend processing system having one or more processors that execute
 - 20 computer-executable instructions that cause the backend processing system to:
 - receive the sensor kit packets from the sensor kit;
 - determine the sensor data collected by the sensor kit based on the sensor kit packets;
 - perform one or more backend operations on the sensor data collected by the
 - 25 sensor kit; and
 - store the sensor data collected by the sensor kit in the sensor kit data store.
150. The system of claim 149, wherein the sensor kit further comprises a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public
- 30 network on behalf of the edge device.
151. The system of claim 150, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.
152. The system of claim 150, wherein the gateway device includes a cellular chipset that is pre-
- 35 configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

153. The system of claim 149, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

154. The system of claim 149, wherein the edge device further comprises one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

155. The system of claim 149, wherein the edge device further comprises one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of an industrial component of the industrial setting and/or the industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors.

156. The system of claim 155, wherein performing one or more edge operations includes:

generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and

selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction.

157. The system of claim 156, wherein selectively encoding the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting, compressing the one or more instances of sensor data using a lossy codec.

158. The system of claim 157, wherein compressing the one or more instances of sensor data using the lossy codec includes:

normalizing the one or more instances of sensor data into respective pixel values;

encoding the respective pixel values into a media content frame; and

compressing a block of media content frames using the lossy codec to obtain a compressed block, wherein the lossy codec is a video codec and the compressed block includes the media content frame and one or more other media content frames that include normalized pixel values of other instances of sensor data.

159. The system of claim 158, wherein the backend system receives the compressed block in one or more sensor kit packets and determines the sensor data collected by the sensor kit by decompressing the compressed block using the lossy codec.

160. The system of claim 156, wherein selectively encoding the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, compressing the one or more instances of sensor data using a lossless codec.

161. The system of claim 156, wherein selectively encoding the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, refraining from compressing the one or more instances of sensor data.

162. The system of claim 156, wherein selectively encoding the one or more instances of sensor data includes selecting a stream of sensor data instances for uncompressed transmission.

163. The system of claim 155, wherein performing one or more edge operations includes:

generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and

selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification.

164. The system of claim 163, wherein selectively storing the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting, storing the one or more instances of sensor data in the storage device with an expiry, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry.

165. The system of claim 163, wherein selectively storing the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, storing the one or more instances of sensor data in the storage device indefinitely.

5 166. The system of claim 149, wherein the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol.

167. The system of claim 166, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor
10 kit network.

168. The system of claim 149, wherein the self-configuring sensor kit network is a mesh network such that:

the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors;

15 at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device.

169. The system of claim 168, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor
20 kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

170. The system of claim 149, wherein the self-configuring sensor kit network is a hierarchical network.

171. The system of claim 170, wherein the sensor kit further comprises one or more collection
25 devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device.

172. The system of claim 149, wherein the backend operations include performing one or more analytics tasks using the sensor data.

173. The system of claim 149, wherein the backend operations include performing one or more
30 artificial intelligence tasks using the sensor data.

174. The system of claim 149, wherein the backend operations include issuing a notification to a human user associated with the industrial setting based on the sensor data.

175. The system of claim 149, wherein the backend operations include controlling at least one component of the industrial setting based on the sensor data.

176. A method for monitoring an industrial setting using a sensor kit in communication with a backend system, the sensor kit comprising a plurality of sensors and an edge device, the method comprising:

receiving, by an edge processing system of the edge device, reporting packets from one or more respective sensors of the plurality of sensors, wherein each reporting packet includes routing data and one or more instances of sensor data;

performing, by the edge processing system, one or more edge operations on the instances of sensor data in the reporting packets;

generating, by the edge processing system, a plurality of sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data;

transmitting, by the edge processing system, the sensor kit packets to the backend system via a public network;

receiving, by a backend processing system of the backend system, the sensor kit packets from the sensor kit via the public network;

determining, by the backend processing system, the sensor data collected by the sensor kit based on the sensor kit packets;

performing, by the backend processing system, one or more backend operations on the sensor data collected by the sensor kit; and

storing, by the backend processing system, the sensor data collected by the sensor kit in a sensor kit data store residing in a backend storage system of the backend system.

177. The method of claim 176, wherein the sensor kit further comprises a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device.

178. The method of claim 177, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

179. The method of claim 177, wherein the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

180. The method of claim 176, wherein receiving the reporting packets from the one or more respective sensors is performed using a first communication device of the edge device that receives reporting packets from the plurality of sensors via a self-configuring sensor kit network and transmitting the sensor kit packets to the backend system is performed using a second communication device of the edge device.

181. The method of claim 180, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

182. The method of claim 180, further comprising:

5 capturing, by the plurality of sensors, sensor data; and
transmitting, by the plurality of sensors, the sensor data to the edge device via the self-configuring sensor kit network.

183. The method of claim 182, wherein transmitting the sensor data via the self-configuring sensor kit network includes directly transmitting, by each sensor of the plurality of sensors,
10 instances of sensor data with the edge device using a short-range communication protocol, wherein the self-configuring sensor kit network is a star network.

184. The method of claim 183, further comprising initiating, by the edge processing system, configuration of the self-configuring sensor kit network.

185. The method of claim 182, wherein the self-configuring sensor kit network is a mesh
15 network and each sensor of the plurality of sensors includes a communication device.

186. The method of claim 185, further comprising:

establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors;

receiving, by at least one sensor of the plurality of sensors, instances of sensor data from
20 one or more other sensors of the plurality of sensors; and

routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device.

187. The method of claim 182, wherein the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices.

25 188. The method of claim 187, further comprising:

receiving, by at least one collection device of the plurality of collection devices, reporting packets from one or more sensors of the plurality of sensors; and

routing, by the at least one collection device of the plurality of collection devices, the reporting packets to the edge device.

30 189. The method of claim 176, further comprising storing, by one or more storage devices of the edge device, instances of sensor data captured by the plurality of sensors of the sensor kit.

190. The method of claim 176, wherein the edge device further comprises one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of an industrial component of the industrial setting and/or

the industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors.

191. The method of claim 190, wherein performing one or more edge operations includes:

generating, by the edge processing system, a feature vector based on one or more instances
5 of sensor data received from one or more sensors of the plurality of sensors;

inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and

10 selectively encoding, by the edge processing system, the one or more instances of sensor data prior to transmission to the backend system based on the prediction or classification.

192. The method of claim 191, wherein selectively encoding the one or more instances of sensor data includes:

compressing, by the edge processing system, the one or more instances of sensor data using
15 a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting.

193. The method of claim 192, wherein compressing the one or more instances of sensor data
20 using a lossy codec includes:

normalizing, by the edge processing system, the one or more instances of sensor data into respective pixel values;

encoding, by the edge processing system, the respective pixel values into a media content frame; and

25 compressing, by the edge processing system, a block of media content frames using the lossy codec to obtain a compressed block, wherein the lossy codec is a video codec and the compressed block includes the media content frame and one or more other media content frames that include normalized pixel values of other instances of sensor data.

194. The method of claim 193, wherein the backend system receives the compressed block in
30 one or more sensor kit packets and determines the sensor data collected by the sensor kit by decompressing the compressed block using the lossy codec.

195. The method of claim 191, wherein selectively encoding the one or more instances of sensor data includes:

compressing, by the edge processing system, the one or more instances of sensor data using
35 a lossless codec in response to obtaining a prediction or classification relating to a condition of a

particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

196. The method of claim 191, wherein selectively encoding the one or more instances of sensor data includes:

5 refraining, by the edge processing system, from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting.

197. The method of claim 191, wherein selectively encoding the one or more instances of sensor
10 data includes selecting, by the edge processing system, a stream of sensor data instances for uncompressed transmission.

198. The method of claim 190, wherein performing one or more edge operations includes:

 generating, by the edge processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

15 inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial setting or the industrial setting and a degree of confidence corresponding to the prediction or classification; and

 selectively storing, by the edge processing system, the one or more instances of sensor data
20 in a storage device of the one or more storage devices based on the prediction or classification.

199. The method of claim 198, wherein selectively storing the one or more instances of sensor data includes:

 storing, by the edge processing system, the one or more instances of sensor data in the storage device with an expiry in response to obtaining one or more predictions or classifications
25 relating to conditions of respective industrial components of the industrial setting and the industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial setting and the industrial setting, wherein storing the one or more instances of sensor data in the storage device with an expiry is performed such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry.

30 200. The method of claim 198, wherein selectively storing the one or more instances of sensor data includes:

 storing, by the edge processing system, the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is
35 likely an issue relating to the particular industrial component or the industrial setting.

201. The method of claim 176, wherein the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.

202. A sensor kit configured to monitor an indoor agricultural facility comprising:

an edge device; and

5 a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of the plurality of sensors comprises:

10 a sensing component that captures sensor measurements and outputs instances of sensor data;

a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and

15 a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol;

wherein the plurality of sensors includes two or more sensor types selected from the group comprising: light sensors, humidity sensors, temperature sensors, carbon dioxide sensors, fan speed sensors, weight sensors, and camera sensors; and

20 wherein the edge device comprises:

a communication system having:

a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network; and

25 a second communication device that transmits sensor kit packets to a backend system via a public network; and

a processing system having one or more processors that execute computer-executable instructions that cause the processing system to:

receive the reporting packets from the communication system;

30 perform one or more edge operations on the instances of sensor data in the reporting packets;

generate the sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data; and

35 output the sensor kits packets to the communication system, wherein the communication system transmits the reporting packets to the backend system via the public network.

203. The sensor kit of claim 202, further comprising a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmits the sensor kit packets to the backend system via the public network on behalf of the edge device.

204. The sensor kit of claim 203, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

205. The sensor kit of claim 203, wherein the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

206. The sensor kit of claim 202, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

207. The sensor kit of claim 202, wherein the edge device further comprises one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

208. The sensor kit of claim 202, wherein the edge device further comprises one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of a component of the indoor agricultural setting and/or the indoor agricultural setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors.

209. The sensor kit of claim 208, wherein performing one or more edge operations includes:
generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the indoor agricultural setting or the indoor agricultural setting and a degree of confidence corresponding to the prediction or classification; and

selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction.

210. The sensor kit of claim 209, wherein selectively encoding the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the indoor agricultural setting and the indoor agricultural setting that collectively indicate that there are likely no issues relating to any

component of the indoor agricultural setting and the indoor agricultural setting, compressing the one or more instances of sensor data using a lossy codec.

211. The sensor kit of claim 210, wherein compressing the one or more instances of sensor data using the lossy codec includes:

- 5 normalizing the one or more instances of sensor data into respective pixel values;
 encoding the respective pixel values into a video frame;
 compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data.

10 212. The sensor kit of claim 210, wherein selectively encoding the one or more instances of sensor data includes:

- in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular industrial component or the industrial setting, compressing the one or more instances
15 of sensor data using a lossless codec.

213. The sensor kit of claim 210, wherein selectively encoding the one or more instances of sensor data includes:

- in response to obtaining a prediction or classification relating to a condition of a particular component or the indoor agricultural setting that indicates that there is likely an issue relating to
20 the particular component or the indoor agricultural setting, refraining from compressing the one or more instances of sensor data.

214. The sensor kit of claim 208, wherein performing one or more edge operations includes:

- generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;
- 25 inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the indoor agricultural setting or the indoor agricultural setting and a degree of confidence corresponding to the prediction or classification; and

- selectively storing the one or more instances of sensor data in a storage device of the edge
30 device based on the prediction or classification.

215. The sensor kit of claim 214, wherein selectively storing the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the indoor agricultural setting and the indoor agricultural setting that collectively indicate that there are likely no issues relating to any
35 component of the indoor agricultural setting and the indoor agricultural setting, storing the one or

more instances of sensor data in the storage device with an expiry, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry.

216. The sensor kit of claim 214, wherein selectively storing the one or more instances of sensor data includes:

5 in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial setting that indicates that there is likely an issue relating to the particular component or the indoor agricultural setting, storing the one or more instances of sensor data in the storage device indefinitely.

217. The sensor kit of claim 202, wherein the self-configuring sensor kit network is a star
10 network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol.

218. The sensor kit of claim 217, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

15 219. The sensor kit of claim 202, wherein the self-configuring sensor kit network is a mesh network such that:

 the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors; and

 at least one sensor of the plurality of sensors is configured to receive instances of sensor
20 data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device.

220. The sensor kit of claim 219, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device
25 initiating configuration of the self-configuring sensor kit network.

221. The sensor kit of claim 202, wherein the self-configuring sensor kit network is a hierarchical network.

222. The sensor kit of claim 221, further comprising one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the
30 reporting packets to the edge device.

223. The sensor kit of claim 221, wherein each collection device is installed in a different respective room of the indoor agricultural setting and collects sensor data from sensors of the plurality sensors that are deployed in the respective room.

224. A method of monitoring an indoor agricultural facility using a sensor kit including an edge
35 device and a plurality of sensors, the method comprising:

receiving, by an edge processing system of the edge device, reporting packets from a plurality of sensors via a self-configuring sensor kit network, each reporting packet containing routing data and one or more instances of sensor data captured by a respective sensor of the plurality of sensors, wherein the plurality of sensors includes two or more sensor types selected from the group comprising: light sensors, humidity sensors, temperature sensors, carbon dioxide sensors, fan speed sensors, weight sensors, and camera sensors;

performing, by the edge processing system, one or more edge operations on the instances of sensor data in the reporting packets;

generating, by the edge processing system, one or more edge operations on the instances of sensor data in the reporting packets; and

transmitting, by the edge processing system, the sensor kit packets to an edge communication system of the edge device, wherein the edge communication system transmits the reporting packets to a backend system via a public network.

225. The method of claim 224, wherein the sensor kit further comprises a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device.

226. The method of claim 225, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

227. The method of claim 225, wherein the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

228. The method of claim 224, wherein receiving the reporting packets from the one or more respective sensors is performed using a first communication device of the edge device that receives reporting packets from the plurality of sensors via a self-configuring sensor kit network and transmitting the sensor kit packets to the backend system is performed using a second communication device of the edge device.

229. The method of claim 228, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

230. The method of claim 228, further comprising:

capturing, by the plurality of sensors, sensor data; and

transmitting, by the plurality of sensors, the sensor data to the edge device via the self-configuring sensor kit network.

231. The method of claim 230, wherein transmitting the sensor data via the self-configuring sensor kit network includes directly transmitting, by each sensor of the plurality of sensors, instances of sensor data with the edge device using a short-range communication protocol, wherein the self-configuring sensor kit network is a star network.
- 5 232. The method of claim 231, further comprising initiating, by the edge processing system, configuration of the self-configuring sensor kit network.
233. The method of claim 230, wherein the self-configuring sensor kit network is a mesh network and each sensor of the plurality of sensors includes a communication device.
234. The method of claim 233, further comprising:
- 10 establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors;
- receiving, by at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and
- routing, by the at least one sensor of the plurality of sensors, the received instances of the
- 15 sensor data towards the edge device.
235. The method of claim 230, wherein the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices.
236. The method of claim 235, further comprising:
- receiving, by at least one collection device of the plurality of collection devices, reporting
- 20 packets from one or more sensors of the plurality of sensors; and
- routing, by the at least one collection device of the plurality of collection devices, the reporting packets to the edge device.
237. The method of claim 235, wherein each collection device is installed in a different respective room of the indoor agricultural setting and collects sensor data from sensors of the
- 25 plurality sensors that are deployed in the respective room.
238. The method of claim 235, further comprising storing, by one or more storage devices of the edge device, instances of sensor data captured by the plurality of sensors of the sensor kit.
239. The method of claim 224, wherein the edge device further comprises one or more storage devices that store a model data store that stores one or more machine-learned models that are each
- 30 trained to predict or classify a condition of a component of the agricultural setting and/or the agricultural setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors.
240. The method of claim 239, wherein performing one or more edge operations includes:
- generating, by the edge processing system, a feature vector based on one or more instances
- 35 of sensor data received from one or more sensors of the plurality of sensors;

inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the agricultural setting or the agricultural setting and a degree of confidence corresponding to the prediction or classification; and

5 selectively encoding, by the edge processing system, the one or more instances of sensor data prior to transmission to the backend system based on the prediction or classification.

241. The method of claim 240, wherein selectively encoding the one or more instances of sensor data includes:

 compressing, by the edge processing system, the one or more instances of sensor data using
10 a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective components of the agricultural setting and the agricultural setting that collectively indicate that there are likely no issues relating to any component of the agricultural setting and the agricultural setting.

242. The method of claim 241, wherein compressing the one or more instances of sensor data
15 using a lossy codec includes:

 normalizing, by the edge processing system, the one or more instances of sensor data into respective pixel values;

 encoding, by the edge processing system, the respective pixel values into a media content frame; and

20 compressing, by the edge processing system, a block of media content frames using the lossy codec to obtain a compressed block, wherein the lossy codec is a video codec and the compressed block includes the media content frame and one or more other media content frames that include normalized pixel values of other instances of sensor data.

243. The method of claim 242, wherein the backend system receives the compressed block in
25 one or more sensor kit packets and determines the sensor data collected by the sensor kit by decompressing the compressed block using the lossy codec.

244. The method of claim 240, wherein selectively encoding the one or more instances of sensor data includes:

 compressing, by the edge processing system, the one or more instances of sensor data using
30 a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular component or the agricultural setting that indicates that there is likely an issue relating to the particular component or the agricultural setting.

245. The method of claim 240, wherein selectively encoding the one or more instances of sensor data includes:

refraining, by the edge processing system, from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular component or the agricultural setting that indicates that there is likely an issue relating to the particular component or the agricultural setting.

5 246. The method of claim 240, wherein selectively encoding the one or more instances of sensor data includes selecting, by the edge processing system, a stream of sensor data instances for uncompressed transmission.

247. The method of claim 239, wherein performing one or more edge operations includes:
generating, by the edge processing system, a feature vector based on one or more instances
10 of sensor data received from one or more sensors of the plurality of sensors;

inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the agricultural setting or the agricultural setting and a degree of confidence corresponding to the prediction or classification; and

15 selectively storing, by the edge processing system, the one or more instances of sensor data in a storage device of the one or more storage devices based on the prediction or classification.

248. The method of claim 247, wherein selectively storing the one or more instances of sensor data includes:

storing, by the edge processing system, the one or more instances of sensor data in the
20 storage device with an expiry in response to obtaining one or more predictions or classifications relating to conditions of respective components of the agricultural setting and the agricultural setting that collectively indicate that there are likely no issues relating to any component of the agricultural setting and the agricultural setting, wherein storing the one or more instances of sensor data in the storage device with an expiry is performed such that the one or more instances of sensor
25 data are purged from the storage device in accordance with the expiry.

249. The method of claim 247, wherein selectively storing the one or more instances of sensor data includes:

storing, by the edge processing system, the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a
30 condition of a particular component or the agricultural setting that indicates that there is likely an issue relating to the particular component or the agricultural setting.

250. The method of claim 224, wherein the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type selected from the group comprising: light sensors, humidity sensors, temperature sensors, carbon dioxide sensors, fan
35 speed sensors, weight sensors, and camera sensors.

251. A sensor kit configured to monitor a natural resource extraction setting comprising:
an edge device; and

a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of the plurality of sensors comprises:

a sensing component that captures sensor measurements and outputs instances of sensor data;

a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and

a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol;

wherein the plurality of sensors includes two or more sensor types selected from the group comprising: infrared sensors, ground penetrating sensors, light sensors, humidity sensors, temperature sensors, chemical sensors, fan speed sensors, rotational speed sensors, weight sensors, and camera sensors; and

wherein the edge device comprises:

a communication system having:

a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network;

a second communication device that transmits sensor kit packets to a backend system via a public network; and

a processing system having one or more processors that execute computer-executable instructions that cause the processing system to:

receive the reporting packets from the communication system;

perform one or more edge operations on the instances of sensor data in the reporting packets;

generate the sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data; and

output the sensor kits packets to the communication system, wherein the communication system transmits the reporting packets to the backend system via the public network.

252. The sensor kit of claim 251, further comprising a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmits the sensor kit packets to the backend system via the public network on behalf of the edge device.

5 253. The sensor kit of claim 252, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

254. The sensor kit of claim 252, wherein the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

10 255. The sensor kit of claim 251, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

256. The sensor kit of claim 251, wherein the edge device further comprises one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality
15 of sensors of the sensor kit.

257. The sensor kit of claim 251, wherein the edge device further comprises one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of a component of the natural resource extraction setting and/or the natural resource extraction setting based on a set of features that are derived from
20 instances of sensor data captured by one or more of the plurality of sensors.

258. The sensor kit of claim 257, wherein performing one or more edge operations includes:

generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting the feature vector to the machine-learned model to obtain a prediction or
25 classification relating to a condition of a particular component of the natural resource extraction setting or the natural resource extraction setting and a degree of confidence corresponding to the prediction or classification; and

selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction.

30 259. The sensor kit of claim 258, wherein selectively encoding the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective components of the natural resource extraction setting and the natural resource extraction setting that collectively indicate that there are likely no issues relating to any component of the natural resource extraction setting and the natural resource extraction setting,
35 compressing the one or more instances of sensor data using a lossy codec.

260. The sensor kit of claim 259, wherein compressing the one or more instances of sensor data using the lossy codec includes:

normalizing the one or more instances of sensor data into respective pixel values;

encoding the respective pixel values into a video frame; and

5 compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data.

261. The sensor kit of claim 259, wherein selectively encoding the one or more instances of sensor data includes:

10 in response to obtaining a prediction or classification relating to a condition of a particular component or the natural resource extraction setting that indicates that there is likely an issue relating to the particular component or the natural resource extraction setting, compressing the one or more instances of sensor data using a lossless codec.

262. The sensor kit of claim 259, wherein selectively encoding the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular component or the natural resource extraction setting that indicates that there is likely an issue relating to the particular component or the natural resource extraction setting, refraining from compressing the one or more instances of sensor data.

20 263. The sensor kit of claim 257, wherein performing one or more edge operations includes:

generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the natural resource extraction setting or the natural resource extraction setting and a degree of confidence corresponding to the prediction or classification; and

selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification.

264. The sensor kit of claim 263, wherein selectively storing the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective components of the natural resource extraction setting and the natural resource extraction setting that collectively indicate that there are likely no issues relating to any component of the natural resource extraction setting and the natural resource extraction setting, storing the one or more instances of sensor data in the storage device with an expiry, such that the

one or more instances of sensor data are purged from the storage device in accordance with the expiry.

265. The sensor kit of claim 263, wherein selectively storing the one or more instances of sensor data includes:

5 in response to obtaining a prediction or classification relating to a condition of a particular component or the natural resource extraction setting that indicates that there is likely an issue relating to the particular component or the natural resource extraction setting, storing the one or more instances of sensor data in the storage device indefinitely.

266. The sensor kit of claim 251, wherein the self-configuring sensor kit network is a star
10 network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol.

267. The sensor kit of claim 266, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

15 268. The sensor kit of claim 251, wherein the self-configuring sensor kit network is a mesh network such that:

 the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors; and

 at least one sensor of the plurality of sensors is configured to receive instances of sensor
20 data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device.

269. The sensor kit of claim 268, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device
25 initiating configuration of the self-configuring sensor kit network.

270. The sensor kit of claim 251, wherein the self-configuring sensor kit network is a hierarchical network.

271. The sensor kit of claim 270, further comprising one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the
30 reporting packets to the edge device.

272. The sensor kit of claim 270, wherein each collection device is installed in a different respective section of the natural resource extraction setting and collects sensor data from sensors of the plurality sensors that are deployed in the respective section.

273. A method of monitoring a natural resource extraction setting using a sensor kit including
35 an edge device and a plurality of sensors, the method comprising:

receiving, by an edge processing system of the edge device, reporting packets from a plurality of sensors via a self-configuring sensor kit network, each reporting packet containing routing data and one or more instances of sensor data captured by a respective sensor of the plurality of sensors, wherein the plurality of sensors includes two or more sensor types selected from the group comprising: infrared sensors, ground penetrating sensors, light sensors, humidity sensors, temperature sensors, chemical sensors, fan speed sensors, rotational speed sensors, weight sensors, and camera sensors;

performing, by the edge processing system, one or more edge operations on the instances of sensor data in the reporting packets;

generating, by the edge processing system, one or more edge operations on the instances of sensor data in the reporting packets; and

transmitting, by the edge processing system, the sensor kit packets to an edge communication system of the edge device, wherein the edge communication system transmits the reporting packets to a backend system via a public network.

274. The method of claim 273, wherein the sensor kit further comprises a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device.

275. The method of claim 274, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

276. The method of claim 274, wherein the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

277. The method of claim 273, wherein receiving the reporting packets from the one or more respective sensors is performed using a first communication device of the edge device that receives reporting packets from the plurality of sensors via a self-configuring sensor kit network and transmitting the sensor kit packets to the backend system is performed using a second communication device of the edge device.

278. The method of claim 277, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

279. The method of claim 277, further comprising:

capturing, by the plurality of sensors, sensor data; and

transmitting, by the plurality of sensors, the sensor data to the edge device via the self-configuring sensor kit network.

280. The method of claim 279, wherein transmitting the sensor data via the self-configuring sensor kit network includes directly transmitting, by each sensor of the plurality of sensors, instances of sensor data with the edge device using a short-range communication protocol, wherein the self-configuring sensor kit network is a star network.

5 281. The method of claim 280, further comprising initiating, by the edge processing system, configuration of the self-configuring sensor kit network.

282. The method of claim 279, wherein the self-configuring sensor kit network is a mesh network and each sensor of the plurality of sensors includes a communication device.

283. The method of claim 282, further comprising:

10 establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors;

receiving, by at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and

15 routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device.

284. The method of claim 279, wherein the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices.

285. The method of claim 284, further comprising:

20 receiving, by at least one collection device of the plurality of collection devices, reporting packets from one or more sensors of the plurality of sensors; and

routing, by the at least one collection device of the plurality of collection devices, the reporting packets to the edge device.

286. The method of claim 284, wherein each collection device is installed in a different respective section of the natural resource extraction setting and collects sensor data from sensors 25 of the plurality of sensors that are deployed in the respective section.

287. The method of claim 273, further comprising storing, by one or more storage devices of the edge device, instances of sensor data captured by the plurality of sensors of the sensor kit.

288. The method of claim 273, wherein the edge device further comprises one or more storage devices that store a model data store that stores one or more machine-learned models that are each 30 trained to predict or classify a condition of an component of the natural resource extraction setting and/or the natural resource extraction setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors.

289. The method of claim 288, wherein performing one or more edge operations includes:

35 generating, by the edge processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the natural resource extraction setting or the natural resource extraction setting and a degree of confidence corresponding to the prediction or classification; and

5 selectively encoding, by the edge processing system, the one or more instances of sensor data prior to transmission to the backend system based on the prediction or classification.

290. The method of claim 289, wherein selectively encoding the one or more instances of sensor data includes:

compressing, by the edge processing system, the one or more instances of sensor data using
10 a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective components of the natural resource extraction setting and the natural resource extraction setting that collectively indicate that there are likely no issues relating to any component of the natural resource extraction setting and the natural resource extraction setting.

291. The method of claim 290, wherein compressing the one or more instances of sensor data
15 using a lossy codec includes:

normalizing, by the edge processing system, the one or more instances of sensor data into respective pixel values;

encoding, by the edge processing system, the respective pixel values into a media content frame; and

20 compressing, by the edge processing system, a block of media content frames using the lossy codec to obtain a compressed block, wherein the lossy codec is a video codec and the compressed block includes the media content frame and one or more other media content frames that include normalized pixel values of other instances of sensor data.

292. The method of claim 291, wherein the backend system receives the compressed block in
25 one or more sensor kit packets and determines the sensor data collected by the sensor kit by decompressing the compressed block using the lossy codec.

293. The method of claim 289, wherein selectively encoding the one or more instances of sensor data includes:

compressing, by the edge processing system, the one or more instances of sensor data using
30 a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular component or the natural resource extraction setting that indicates that there is likely an issue relating to the particular component or the natural resource extraction setting.

294. The method of claim 289, wherein selectively encoding the one or more instances of sensor data includes:

refraining, by the edge processing system, from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular component or the natural resource extraction setting that indicates that there is likely an issue relating to the particular component or the natural resource extraction setting.

5 295. The method of claim 289, wherein selectively encoding the one or more instances of sensor data includes selecting, by the edge processing system, a stream of sensor data instances for uncompressed transmission.

296. The method of claim 288, wherein performing one or more edge operations includes:
generating, by the edge processing system, a feature vector based on one or more instances
10 of sensor data received from one or more sensors of the plurality of sensors;

inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the natural resource extraction setting or the natural resource extraction setting and a degree of confidence corresponding to the prediction or classification; and

15 selectively storing, by the edge processing system, the one or more instances of sensor data in a storage device of the one or more storage devices based on the prediction or classification.

297. The method of claim 296, wherein selectively storing the one or more instances of sensor data includes:

storing, by the edge processing system, the one or more instances of sensor data in the
20 storage device with an expiry in response to obtaining one or more predictions or classifications relating to conditions of respective components of the natural resource extraction setting and the natural resource extraction setting that collectively indicate that there are likely no issues relating to any component of the natural resource extraction setting and the natural resource extraction setting, wherein storing the one or more instances of sensor data in the storage device with an
25 expiry is performed such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry.

298. The method of claim 296, wherein selectively storing the one or more instances of sensor data includes:

storing, by the edge processing system, the one or more instances of sensor data in the
30 storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular component or the natural resource extraction setting that indicates that there is likely an issue relating to the particular component or the natural resource extraction setting.

299. The method of claim 273, wherein the plurality of sensors includes a first set of sensors of
35 a first sensor type and a second set of sensors of a second sensor type selected from the group

comprising: infrared sensors, ground penetrating sensors, light sensors, humidity sensors, temperature sensors, chemical sensors, fan speed sensors, rotational speed sensors, weight sensors, and camera sensors.

300. A sensor kit configured to monitor a pipeline setting comprising:

5 an edge device; and

a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of the plurality of sensors comprises:

10 a sensing component that captures sensor measurements and outputs instances of sensor data;

a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and

15 a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol;

wherein the plurality of sensors includes two or more sensor types selected from the group comprising: infrared sensors, metal penetrating sensors, concrete penetrating sensors, light sensors, 20 strain sensors, rust sensors, biological sensors, humidity sensors, temperature sensors, chemical sensors, valve integrity sensors, vibration sensors, flow sensors, cavitation sensors, pressure sensors, weight sensors, and camera sensors; and

wherein the edge device comprises:

a communication system having:

25 a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network;

a second communication device that transmits sensor kit packets to a backend system via a public network; and

30 a processing system having one or more processors that execute computer-executable instructions that cause the processing system to:

receive the reporting packets from the communication system;

perform one or more edge operations on the instances of sensor data in the reporting packets;

generate the sensor kit packets based on the instances of sensor data,
wherein each sensor kit packet includes at least one instance of sensor data;
and

5 output the sensor kits packets to the communication system, wherein
the communication system transmits the reporting packets to the backend
system via the public network.

301. The sensor kit of claim 300, further comprising a gateway device, wherein the gateway
device is configured to receive sensor kit packets from the edge device via a wired communication
link and transmits the sensor kit packets to the backend system via the public network on behalf of
10 the edge device.

302. The sensor kit of claim 301, wherein the gateway device includes a satellite terminal device
that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the
public network.

303. The sensor kit of claim 301, wherein the gateway device includes a cellular chipset that is
15 pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

304. The sensor kit of claim 300, wherein the second communication device of the edge device
is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that
routes the sensor kits to the public network.

305. The sensor kit of claim 300, wherein the edge device further comprises one or more storage
20 devices that store a sensor data store that stores instances of sensor data captured by the plurality
of sensors of the sensor kit.

306. The sensor kit of claim 300, wherein the edge device further comprises one or more storage
devices that store a model data store that stores one or more machine-learned models that are each
trained to predict or classify a condition of a pipeline component of the pipeline setting and/or the
25 pipeline setting based on a set of features that are derived from instances of sensor data captured
by one or more of the plurality of sensors.

307. The sensor kit of claim 306, wherein performing one or more edge operations includes:
generating a feature vector based on one or more instances of sensor data received from
one or more sensors of the plurality of sensors;

30 inputting the feature vector to the machine-learned model to obtain a prediction or
classification relating to a condition of a particular pipeline component of the pipeline setting or
the pipeline setting and a degree of confidence corresponding to the prediction or classification;
and

 selectively encoding the one or more instances of sensor data prior to transmission to the
35 backend system based on the condition or prediction.

308. The sensor kit of claim 307, wherein selectively encoding the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective pipeline components of the pipeline setting and the pipeline setting that collectively indicate that there are likely no issues relating to any pipeline component of the pipeline setting and the pipeline setting, compressing the one or more instances of sensor data using a lossy codec.

309. The sensor kit of claim 308, wherein compressing the one or more instances of sensor data using the lossy codec includes:

normalizing the one or more instances of sensor data into respective pixel values;

encoding the respective pixel values into a video frame; and

compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data.

310. The sensor kit of claim 308, wherein selectively encoding the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular pipeline component or the pipeline setting that indicates that there is likely an issue relating to the particular pipeline component or the pipeline setting, compressing the one or more instances of sensor data using a lossless codec.

311. The sensor kit of claim 308, wherein selectively encoding the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular pipeline component or the pipeline setting that indicates that there is likely an issue relating to the particular pipeline component or the pipeline setting, refraining from compressing the one or more instances of sensor data.

312. The sensor kit of claim 306, wherein performing one or more edge operations includes:

generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular pipeline component of the pipeline setting or the pipeline setting and a degree of confidence corresponding to the prediction or classification; and

selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification.

313. The sensor kit of claim 312, wherein selectively storing the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective pipeline components of the pipeline setting and the pipeline setting that collectively indicate that there are likely no issues relating to any pipeline component of the pipeline setting and the pipeline setting, storing the one or more instances of sensor data in the storage device with an expiry, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry.

314. The sensor kit of claim 312, wherein selectively storing the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular pipeline component or the pipeline setting that indicates that there is likely an issue relating to the particular pipeline component or the pipeline setting, storing the one or more instances of sensor data in the storage device indefinitely.

315. The sensor kit of claim 300, wherein the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol.

316. The sensor kit of claim 315, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

317. The sensor kit of claim 300, wherein the self-configuring sensor kit network is a mesh network such that:

the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors; and

at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device.

318. The sensor kit of claim 317, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

319. The sensor kit of claim 300, wherein the self-configuring sensor kit network is a hierarchical network.

320. The sensor kit of claim 319, further comprising one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device.

321. The sensor kit of claim 319, wherein each collection device is installed in a different respective section of the pipeline setting and collects sensor data from sensors of the plurality sensors that are deployed in the respective section.

322. A method of monitoring a pipeline setting using a sensor kit including an edge device and
5 a plurality of sensors, the method comprising:

receiving, by an edge processing system of the edge device, reporting packets from a plurality of sensors via a self-configuring sensor kit network, each reporting packet containing routing data and one or more instances of sensor data captured by a respective sensor of the plurality of sensors, wherein the plurality of sensors includes two or more sensor types selected
10 from the group comprising: infrared sensors, metal penetrating sensors, concrete penetrating sensors, light sensors, strain sensors, rust sensors, biological sensors, humidity sensors, temperature sensors, chemical sensors, valve integrity sensors, vibration sensors, flow sensors, cavitation sensors, pressure sensors, weight sensors, and camera sensors;

performing, by the edge processing system, one or more edge operations on the instances
15 of sensor data in the reporting packets;

generating, by the edge processing system, one or more edge operations on the instances of sensor data in the reporting packets; and

transmitting, by the edge processing system, the sensor kit packets to an edge communication system of the edge device, wherein the edge communication system transmits the reporting packets to a backend system via a public network.
20

323. The method of claim 322, wherein the sensor kit further comprises a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device.

25 324. The method of claim 323, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

325. The method of claim 323, wherein the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

30 326. The method of claim 322, wherein receiving the reporting packets from the one or more respective sensors is performed using a first communication device of the edge device that receives reporting packets from the plurality of sensors via a self-configuring sensor kit network and transmitting the sensor kit packets to the backend system is performed using a second communication device of the edge device.

327. The method of claim 326, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

328. The method of claim 326, further comprising:

5 capturing, by the plurality of sensors, sensor data; and
transmitting, by the plurality of sensors, the sensor data to the edge device via the self-configuring sensor kit network.

329. The method of claim 328, wherein transmitting the sensor data via the self-configuring sensor kit network includes directly transmitting, by each sensor of the plurality of sensors,
10 instances of sensor data with the edge device using a short-range communication protocol, wherein the self-configuring sensor kit network is a star network.

330. The method of claim 329, further comprising initiating, by the edge processing system, configuration of the self-configuring sensor kit network.

331. The method of claim 328, wherein the self-configuring sensor kit network is a mesh
15 network and each sensor of the plurality of sensors includes a communication device.

332. The method of claim 331, further comprising:

establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors;

20 receiving, by at least one sensor of the plurality of sensors, instances of sensor data from
one or more other sensors of the plurality of sensors; and

routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device.

333. The method of claim 328, wherein the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices.

25 334. The method of claim 333, further comprising:

receiving, by at least one collection device of the plurality of collection devices, reporting packets from one or more sensors of the plurality of sensors; and

routing, by the at least one collection device of the plurality of collection devices, the reporting packets to the edge device.

30 335. The method of claim 333, wherein each collection device is installed in a different respective section of the pipeline setting and collects sensor data from sensors of the plurality sensors that are deployed in the respective section.

336. The method of claim 322, further comprising storing, by one or more storage devices of the edge device, instances of sensor data captured by the plurality of sensors of the sensor kit.

337. The method of claim 322, wherein the edge device further comprises one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of a component of the pipeline setting and/or the pipeline setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors.

338. The method of claim 337, wherein performing one or more edge operations includes:
generating, by the edge processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the pipeline setting or the pipeline setting and a degree of confidence corresponding to the prediction or classification; and

selectively encoding, by the edge processing system, the one or more instances of sensor data prior to transmission to the backend system based on the prediction or classification.

339. The method of claim 338, wherein selectively encoding the one or more instances of sensor data includes:

compressing, by the edge processing system, the one or more instances of sensor data using a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective components of the pipeline setting and the pipeline setting that collectively indicate that there are likely no issues relating to any component of the pipeline setting and the pipeline setting.

340. The method of claim 339, wherein compressing the one or more instances of sensor data using a lossy codec includes:

normalizing, by the edge processing system, the one or more instances of sensor data into respective pixel values;

encoding, by the edge processing system, the respective pixel values into a media content frame; and

compressing, by the edge processing system, a block of media content frames using the lossy codec to obtain a compressed block, wherein the lossy codec is a video codec and the compressed block includes the media content frame and one or more other media content frames that include normalized pixel values of other instances of sensor data.

341. The method of claim 340, wherein the backend system receives the compressed block in one or more sensor kit packets and determines the sensor data collected by the sensor kit by decompressing the compressed block using the lossy codec.

342. The method of claim 338, wherein selectively encoding the one or more instances of sensor data includes:

compressing, by the edge processing system, the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular component or the pipeline setting that indicates that there is likely an issue relating to the particular component or the pipeline setting.

343. The method of claim 338, wherein selectively encoding the one or more instances of sensor data includes:

refraining, by the edge processing system, from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular component or the pipeline setting that indicates that there is likely an issue relating to the particular component or the pipeline setting.

344. The method of claim 338, wherein selectively encoding the one or more instances of sensor data includes selecting, by the edge processing system, a stream of sensor data instances for uncompressed transmission.

345. The method of claim 337, wherein performing one or more edge operations includes:

generating, by the edge processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the pipeline setting or the pipeline setting and a degree of confidence corresponding to the prediction or classification; and

selectively storing, by the edge processing system, the one or more instances of sensor data in a storage device of the one or more storage devices based on the prediction or classification.

346. The method of claim 345, wherein selectively storing the one or more instances of sensor data includes:

storing, by the edge processing system, the one or more instances of sensor data in the storage device with an expiry in response to obtaining one or more predictions or classifications relating to conditions of respective components of the pipeline setting and the pipeline setting that collectively indicate that there are likely no issues relating to any component of the pipeline setting and the pipeline setting, wherein storing the one or more instances of sensor data in the storage device with an expiry is performed such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry.

347. The method of claim 345, wherein selectively storing the one or more instances of sensor data includes:

storing, by the edge processing system, the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular component or the pipeline setting that indicates that there is likely an issue relating to the particular component or the pipeline setting.

5 348. The method of claim 322, wherein the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type selected from the group comprising: infrared sensors, metal penetrating sensors, concrete penetrating sensors, light sensors, strain sensors, rust sensors, biological sensors, humidity sensors, temperature sensors, chemical sensors, valve integrity sensors, vibration sensors, flow sensors, cavitation sensors, pressure
10 sensors, weight sensors, and camera sensors.

349. A sensor kit configured to monitor an industrial manufacturing setting comprising:
an edge device; and

a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a
15 first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of the plurality of sensors comprises:

a sensing component that captures sensor measurements and outputs instances of sensor data;

a processing unit that generates reporting packets based on one or more instances
20 of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and

a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol;

25 wherein the plurality of sensors includes two or more sensor types selected from the group comprising: metal penetrating sensors, concrete penetrating sensors, vibration sensors, light sensors, strain sensors, rust sensors, biological sensors, temperature sensors, chemical sensors, valve integrity sensors, rotational speed sensors, vibration sensors, flow sensors, cavitation sensors, pressure sensors, weight sensors, and camera sensors; and

30 wherein the edge device comprises:

a communication system having:

a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network;

a second communication device that transmits sensor kit packets to a backend
35 system via a public network; and

a processing system having one or more processors that execute computer-executable instructions that cause the processing system to:

receive the reporting packets from the communication system;

5 perform one or more edge operations on the instances of sensor data in the reporting packets;

generate the sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data; and

10 output the sensor kits packets to the communication system, wherein the communication system transmits the reporting packets to the backend system via the public network.

350. The sensor kit of claim 349, further comprising a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmits the sensor kit packets to the backend system via the public network on behalf of the edge device.

15 351. The sensor kit of claim 350, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

352. The sensor kit of claim 350, wherein the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

20 353. The sensor kit of claim 349, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

354. The sensor kit of claim 349, wherein the edge device further comprises one or more storage devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

25 355. The sensor kit of claim 349, wherein the edge device further comprises one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of an industrial component of the industrial manufacturing setting and/or the industrial manufacturing setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors.

30 356. The sensor kit of claim 355, wherein performing one or more edge operations includes: generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

35 inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial

manufacturing setting or the industrial manufacturing setting and a degree of confidence corresponding to the prediction or classification; and

selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction.

5 357. The sensor kit of claim 356, wherein selectively encoding the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial manufacturing setting and the industrial manufacturing setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial manufacturing setting and the industrial manufacturing
10 setting, compressing the one or more instances of sensor data using a lossy codec.

358. The sensor kit of claim 357, wherein compressing the one or more instances of sensor data using the lossy codec includes:

normalizing the one or more instances of sensor data into respective pixel values;

encoding the respective pixel values into a video frame; and

15 compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data.

359. The sensor kit of claim 357, wherein selectively encoding the one or more instances of sensor data includes:

20 in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial manufacturing setting that indicates that there is likely an issue relating to the particular industrial component or the industrial manufacturing setting, compressing the one or more instances of sensor data using a lossless codec.

360. The sensor kit of claim 357, wherein selectively encoding the one or more instances of
25 sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial manufacturing setting that indicates that there is likely an issue relating to the particular industrial component or the industrial manufacturing setting, refraining from compressing the one or more instances of sensor data.

30 361. The sensor kit of claim 355, wherein performing one or more edge operations includes:

generating a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the industrial

manufacturing setting or the industrial manufacturing setting and a degree of confidence corresponding to the prediction or classification; and

selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification.

5 362. The sensor kit of claim 361, wherein selectively storing the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the industrial manufacturing setting and the industrial manufacturing setting that collectively indicate that there are likely no issues relating to any industrial component of the industrial manufacturing setting and the industrial manufacturing
10 setting, storing the one or more instances of sensor data in the storage device with an expiry, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry.

363. The sensor kit of claim 361, wherein selectively storing the one or more instances of sensor data includes:

15 in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the industrial manufacturing setting that indicates that there is likely an issue relating to the particular industrial component or the industrial manufacturing setting, storing the one or more instances of sensor data in the storage device indefinitely.

364. The sensor kit of claim 349, wherein the self-configuring sensor kit network is a star
20 network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol.

365. The sensor kit of claim 364, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

25 366. The sensor kit of claim 349, wherein the self-configuring sensor kit network is a mesh network such that:

the communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors; and

at least one sensor of the plurality of sensors is configured to receive instances of sensor
30 data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device.

367. The sensor kit of claim 366, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device
35 initiating configuration of the self-configuring sensor kit network.

368. The sensor kit of claim 349, wherein the self-configuring sensor kit network is a hierarchical network.

369. The sensor kit of claim 368, further comprising one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device.

370. The sensor kit of claim 368, wherein each collection device is installed in a different respective room of the industrial manufacturing setting and collects sensor data from sensors of the plurality of sensors that are deployed in the respective room.

371. A method of monitoring a manufacturing setting using a sensor kit including an edge device and a plurality of sensors, the method comprising:

receiving, by an edge processing system of the edge device, reporting packets from a plurality of sensors via a self-configuring sensor kit network, each reporting packet containing routing data and one or more instances of sensor data captured by a respective sensor of the plurality of sensors, wherein the plurality of sensors includes two or more sensor types selected from the group comprising: metal penetrating sensors, concrete penetrating sensors, vibration sensors, light sensors, strain sensors, rust sensors, biological sensors, temperature sensors, chemical sensors, valve integrity sensors, rotational speed sensors, vibration sensors, flow sensors, cavitation sensors, pressure sensors, weight sensors, and camera sensors;

performing, by the edge processing system, one or more edge operations on the instances of sensor data in the reporting packets;

generating, by the edge processing system, one or more edge operations on the instances of sensor data in the reporting packets; and

transmitting, by the edge processing system, the sensor kit packets to an edge communication system of the edge device, wherein the edge communication system transmits the reporting packets to a backend system via a public network.

372. The method of claim 371, wherein the sensor kit further comprises a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device.

373. The method of claim 372, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

374. The method of claim 372, wherein the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

375. The method of claim 371, wherein receiving the reporting packets from the one or more respective sensors is performed using a first communication device of the edge device that receives reporting packets from the plurality of sensors via a self-configuring sensor kit network and transmitting the sensor kit packets to the backend system is performed using a second
5 communication device of the edge device.

376. The method of claim 375, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

377. The method of claim 375, further comprising:

10 capturing, by the plurality of sensors, sensor data; and
transmitting, by the plurality of sensors, the sensor data to the edge device via the self-configuring sensor kit network.

378. The method of claim 377, wherein transmitting the sensor data via the self-configuring sensor kit network includes directly transmitting, by each sensor of the plurality of sensors,
15 instances of sensor data with the edge device using a short-range communication protocol, wherein the self-configuring sensor kit network is a star network.

379. The method of claim 378, further comprising initiating, by the edge processing system, configuration of the self-configuring sensor kit network.

380. The method of claim 377, wherein the self-configuring sensor kit network is a mesh
20 network and each sensor of the plurality of sensors includes a communication device.

381. The method of claim 380, further comprising:

establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors;

25 receiving, by at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and

routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device.

382. The method of claim 377, wherein the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices.

30 383. The method of claim 382, further comprising:

receiving, by at least one collection device of the plurality of collection devices, reporting packets from one or more sensors of the plurality of sensors; and

routing, by the at least one collection device of the plurality of collection devices, the reporting packets to the edge device.

384. The method of claim 382, wherein each collection device is installed in a different respective room of the manufacturing setting and collects sensor data from sensors of the plurality sensors that are deployed in the respective room.

385. The method of claim 371, further comprising storing, by one or more storage devices of the edge device, instances of sensor data captured by the plurality of sensors of the sensor kit.

386. The method of claim 371, wherein the edge device further comprises one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of a component of the manufacturing setting and/or the manufacturing setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors.

387. The method of claim 386, wherein performing one or more edge operations includes:

generating, by the edge processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the manufacturing setting or the manufacturing setting and a degree of confidence corresponding to the prediction or classification; and

selectively encoding, by the edge processing system, the one or more instances of sensor data prior to transmission to the backend system based on the prediction or classification.

388. The method of claim 387, wherein selectively encoding the one or more instances of sensor data includes:

compressing, by the edge processing system, the one or more instances of sensor data using a lossy codec in response to obtaining one or more predictions or classifications relating to conditions of respective components of the manufacturing setting and the manufacturing setting that collectively indicate that there are likely no issues relating to any component of the manufacturing setting and the manufacturing setting.

389. The method of claim 388, wherein compressing the one or more instances of sensor data using a lossy codec includes:

normalizing, by the edge processing system, the one or more instances of sensor data into respective pixel values;

encoding, by the edge processing system, the respective pixel values into a media content frame; and

compressing, by the edge processing system, a block of media content frames using the lossy codec to obtain a compressed block, wherein the lossy codec is a video codec and the

compressed block includes the media content frame and one or more other media content frames that include normalized pixel values of other instances of sensor data.

390. The method of claim 389, wherein the backend system receives the compressed block in one or more sensor kit packets and determines the sensor data collected by the sensor kit by decompressing the compressed block using the lossy codec.

391. The method of claim 387, wherein selectively encoding the one or more instances of sensor data includes:

compressing, by the edge processing system, the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular component or the manufacturing setting that indicates that there is likely an issue relating to the particular component or the manufacturing setting.

392. The method of claim 387, wherein selectively encoding the one or more instances of sensor data includes:

refraining, by the edge processing system, from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular component or the manufacturing setting that indicates that there is likely an issue relating to the particular component or the manufacturing setting.

393. The method of claim 387, wherein selectively encoding the one or more instances of sensor data includes selecting, by the edge processing system, a stream of sensor data instances for uncompressed transmission.

394. The method of claim 386, wherein performing one or more edge operations includes:

generating, by the edge processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the manufacturing setting or the manufacturing setting and a degree of confidence corresponding to the prediction or classification; and

selectively storing, by the edge processing system, the one or more instances of sensor data in a storage device of the one or more storage devices based on the prediction or classification.

395. The method of claim 394, wherein selectively storing the one or more instances of sensor data includes:

storing, by the edge processing system, the one or more instances of sensor data in the storage device with an expiry in response to obtaining one or more predictions or classifications relating to conditions of respective components of the manufacturing setting and the manufacturing setting that collectively indicate that there are likely no issues relating to any component of the

manufacturing setting and the manufacturing setting, wherein storing the one or more instances of sensor data in the storage device with an expiry is performed such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry.

396. The method of claim 394, wherein selectively storing the one or more instances of sensor data includes:

storing, by the edge processing system, the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular component or the manufacturing setting that indicates that there is likely an issue relating to the particular component or the manufacturing setting.

397. The method of claim 371, wherein the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type selected from the group comprising: metal penetrating sensors, concrete penetrating sensors, vibration sensors, light sensors, strain sensors, rust sensors, biological sensors, temperature sensors, chemical sensors, valve integrity sensors, rotational speed sensors, vibration sensors, flow sensors, cavitation sensors, pressure sensors, weight sensors, and camera sensors.

398. A sensor kit configured to monitor an underwater industrial setting comprising:

an edge device; and

a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of the plurality of sensors comprises:

a sensing component that captures sensor measurements and outputs instances of sensor data;

a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and

a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol;

wherein the plurality of sensors includes two or more sensor types selected from the group comprising: infrared sensors, sonar sensors, LIDAR sensors, water penetrating sensors, light sensors, strain sensors, rust sensors, biological sensors, temperature sensors, chemical sensors, valve integrity sensors, vibration sensors, flow sensors, cavitation sensors, pressure sensors, weight sensors, and camera sensors; and

wherein the edge device comprises:

a communication system having:

a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network;

5 a second communication device that transmits sensor kit packets to a backend system via a public network; and

a processing system having one or more processors that execute computer-executable instructions that cause the processing system to:

receive the reporting packets from the communication system;

10 perform one or more edge operations on the instances of sensor data in the reporting packets;

generate the sensor kit packets based on the instances of sensor data, wherein each sensor kit packet includes at least one instance of sensor data; and

15 output the sensor kits packets to the communication system, wherein the communication system transmits the reporting packets to the backend system via the public network.

399. The sensor kit of claim 398, further comprising a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a wired communication link and transmits the sensor kit packets to the backend system via the public network on behalf of
20 the edge device.

400. The sensor kit of claim 399, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

401. The sensor kit of claim 399, wherein the gateway device includes a cellular chipset that is
25 pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

402. The sensor kit of claim 398, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

403. The sensor kit of claim 398, wherein the edge device further comprises one or more storage
30 devices that store a sensor data store that stores instances of sensor data captured by the plurality of sensors of the sensor kit.

404. The sensor kit of claim 398, wherein the edge device further comprises one or more storage devices that store a model data store that stores one or more machine-learned models that are each trained to predict or classify a condition of an industrial component of the underwater industrial

setting and/or the underwater industrial setting based on a set of features that are derived from instances of sensor data captured by one or more of the plurality of sensors.

405. The sensor kit of claim 404, wherein performing one or more edge operations includes:

generating a feature vector based on one or more instances of sensor data received from
5 one or more sensors of the plurality of sensors;

inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the underwater industrial setting or the underwater industrial setting and a degree of confidence corresponding to the prediction or classification; and

10 selectively encoding the one or more instances of sensor data prior to transmission to the backend system based on the condition or prediction.

406. The sensor kit of claim 405, wherein selectively encoding the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the underwater industrial setting and the
15 underwater industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the underwater industrial setting and the underwater industrial setting, compressing the one or more instances of sensor data using a lossy codec.

407. The sensor kit of claim 406, wherein compressing the one or more instances of sensor data using the lossy codec includes:

20 normalizing the one or more instances of sensor data into respective pixel values;
encoding the respective pixel values into a video frame; and

compressing a block of video frames using the lossy codec, wherein the lossy codec is a video codec and the block of video frames includes the video frame and one or more other video frames that include normalized pixel values of other instances of sensor data.

25 408. The sensor kit of claim 406, wherein selectively encoding the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the underwater industrial setting that indicates that there is likely an issue relating to the particular industrial component or the underwater industrial setting, compressing the
30 one or more instances of sensor data using a lossless codec.

409. The sensor kit of claim 406, wherein selectively encoding the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the underwater industrial setting that indicates that there is likely an issue

relating to the particular industrial component or the underwater industrial setting, refraining from compressing the one or more instances of sensor data.

410. The sensor kit of claim 404, wherein performing one or more edge operations includes:

generating a feature vector based on one or more instances of sensor data received from
5 one or more sensors of the plurality of sensors;

inputting the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular industrial component of the underwater industrial setting or the underwater industrial setting and a degree of confidence corresponding to the prediction or classification; and

10 selectively storing the one or more instances of sensor data in a storage device of the edge device based on the prediction or classification.

411. The sensor kit of claim 410, wherein selectively storing the one or more instances of sensor data includes: in response to obtaining one or more predictions or classifications relating to conditions of respective industrial components of the underwater industrial setting and the
15 underwater industrial setting that collectively indicate that there are likely no issues relating to any industrial component of the underwater industrial setting and the underwater industrial setting, storing the one or more instances of sensor data in the storage device with an expiry, such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry.

20 412. The sensor kit of claim 410, wherein selectively storing the one or more instances of sensor data includes:

in response to obtaining a prediction or classification relating to a condition of a particular industrial component or the underwater industrial setting that indicates that there is likely an issue relating to the particular industrial component or the underwater industrial setting, storing the one
25 or more instances of sensor data in the storage device indefinitely.

413. The sensor kit of claim 398, wherein the self-configuring sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the edge device directly using a short-range communication protocol.

414. The sensor kit of claim 413, wherein the computer-executable instructions further cause the
30 one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network.

415. The sensor kit of claim 398, wherein the self-configuring sensor kit network is a mesh network such that:

the communication device of each sensor of the plurality of sensors is configured to
35 establish a communication channel with at least one other sensor of the plurality of sensors;

at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the edge device.

416. The sensor kit of claim 415, wherein the computer-executable instructions further cause the one or more processors of the edge device to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the edge device initiating configuration of the self-configuring sensor kit network.

417. The sensor kit of claim 398, wherein the self-configuring sensor kit network is a hierarchical network.

418. The sensor kit of claim 417, further comprising one or more collection devices configured to receive reporting packets from one or more sensors of the plurality of sensors and route the reporting packets to the edge device.

419. The sensor kit of claim 417, wherein each collection device is installed in a different respective section of the underwater industrial setting and collects sensor data from sensors of the plurality sensors that are deployed in the respective section.

420. A method of monitoring an underwater industrial setting using a sensor kit including an edge device and a plurality of sensors, the method comprising:

receiving, by an edge processing system of the edge device, reporting packets from a plurality of sensors via a self-configuring sensor kit network, each reporting packet containing routing data and one or more instances of sensor data captured by a respective sensor of the plurality of sensors, wherein the plurality of sensors includes two or more sensor types selected from the group comprising: infrared sensors, sonar sensors, LIDAR sensors, water penetrating sensors, light sensors, strain sensors, rust sensors, biological sensors, temperature sensors, chemical sensors, valve integrity sensors, vibration sensors, flow sensors, cavitation sensors, pressure sensors, weight sensors, and camera sensors;

performing, by the edge processing system, one or more edge operations on the instances of sensor data in the reporting packets;

generating, by the edge processing system, one or more edge operations on the instances of sensor data in the reporting packets; and

transmitting, by the edge processing system, the sensor kit packets to an edge communication system of the edge device, wherein the edge communication system transmits the reporting packets to a backend system via a public network.

421. The method of claim 420, wherein the sensor kit further comprises a gateway device, wherein the gateway device is configured to receive sensor kit packets from the edge device via a

wired communication link and transmit the sensor kit packets to the backend system via the public network on behalf of the edge device.

422. The method of claim 421, wherein the gateway device includes a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

423. The method of claim 421, wherein the gateway device includes a cellular chipset that is pre-configured to transmit sensor kit packets to a cellphone tower of a preselected cellular provider.

424. The method of claim 420, wherein receiving the reporting packets from the one or more respective sensors is performed using a first communication device of the edge device that receives reporting packets from the plurality of sensors via a self-configuring sensor kit network and transmitting the sensor kit packets to the backend system is performed using a second communication device of the edge device.

425. The method of claim 424, wherein the second communication device of the edge device is a satellite terminal device that is configured to transmit the sensor kit packets to a satellite that routes the sensor kits to the public network.

426. The method of claim 424, further comprising:
capturing, by the plurality of sensors, sensor data; and
transmitting, by the plurality of sensors, the sensor data to the edge device via the self-configuring sensor kit network.

427. The method of claim 426, wherein transmitting the sensor data via the self-configuring sensor kit network includes directly transmitting, by each sensor of the plurality of sensors, instances of sensor data with the edge device using a short-range communication protocol, wherein the self-configuring sensor kit network is a star network.

428. The method of claim 427, further comprising initiating, by the edge processing system, configuration of the self-configuring sensor kit network.

429. The method of claim 426, wherein the self-configuring sensor kit network is a mesh network and each sensor of the plurality of sensors includes a communication device.

430. The method of claim 429, further comprising:
establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors;
receiving, by at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and
routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device.

431. The method of claim 426, wherein the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices.

432. The method of claim 431, further comprising:

receiving, by at least one collection device of the plurality of collection devices, reporting
5 packets from one or more sensors of the plurality of sensors; and

routing, by the at least one collection device of the plurality of collection devices, the reporting packets to the edge device.

433. The method of claim 431, wherein each collection device is installed in a different
respective section of the underwater industrial setting and collects sensor data from sensors of the
10 plurality sensors that are deployed in the respective section.

434. The method of claim 420, further comprising storing, by one or more storage devices of
the edge device, instances of sensor data captured by the plurality of sensors of the sensor kit.

435. The method of claim 420, wherein the edge device further comprises one or more storage
devices that store a model data store that stores one or more machine-learned models that are each
15 trained to predict or classify a condition of a component of the underwater industrial setting and/or
the underwater industrial setting based on a set of features that are derived from instances of sensor
data captured by one or more of the plurality of sensors.

436. The method of claim 435, wherein performing one or more edge operations includes:

generating, by the edge processing system, a feature vector based on one or more instances
20 of sensor data received from one or more sensors of the plurality of sensors;

inputting, by the edge processing system, the feature vector to the machine-learned model
to obtain a prediction or classification relating to a condition of a particular component of the
underwater industrial setting or the underwater industrial setting and a degree of confidence
corresponding to the prediction or classification; and

25 selectively encoding, by the edge processing system, the one or more instances of sensor
data prior to transmission to the backend system based on the prediction or classification.

437. The method of claim 436, wherein selectively encoding the one or more instances of sensor
data includes:

compressing, by the edge processing system, the one or more instances of sensor data using
30 a lossy codec in response to obtaining one or more predictions or classifications relating to
conditions of respective components of the underwater industrial setting and the underwater
industrial setting that collectively indicate that there are likely no issues relating to any component
of the underwater industrial setting and the underwater industrial setting.

438. The method of claim 437, wherein compressing the one or more instances of sensor data
35 using a lossy codec includes:

normalizing, by the edge processing system, the one or more instances of sensor data into respective pixel values;

encoding, by the edge processing system, the respective pixel values into a media content frame; and

5 compressing, by the edge processing system, a block of media content frames using the lossy codec to obtain a compressed block, wherein the lossy codec is a video codec and the compressed block includes the media content frame and one or more other media content frames that include normalized pixel values of other instances of sensor data.

439. The method of claim 438, wherein the backend system receives the compressed block in one or more sensor kit packets and determines the sensor data collected by the sensor kit by decompressing the compressed block using the lossy codec.

440. The method of claim 436, wherein selectively encoding the one or more instances of sensor data includes:

15 compressing, by the edge processing system, the one or more instances of sensor data using a lossless codec in response to obtaining a prediction or classification relating to a condition of a particular component or the underwater industrial setting that indicates that there is likely an issue relating to the particular component or the underwater industrial setting.

441. The method of claim 436, wherein selectively encoding the one or more instances of sensor data includes:

20 refraining, by the edge processing system, from compressing the one or more instances of sensor data in response to obtaining a prediction or classification relating to a condition of a particular component or the underwater industrial setting that indicates that there is likely an issue relating to the particular component or the underwater industrial setting.

442. The method of claim 436, wherein selectively encoding the one or more instances of sensor data includes selecting, by the edge processing system, a stream of sensor data instances for uncompressed transmission.

443. The method of claim 435, wherein performing one or more edge operations includes:

generating, by the edge processing system, a feature vector based on one or more instances of sensor data received from one or more sensors of the plurality of sensors;

30 inputting, by the edge processing system, the feature vector to the machine-learned model to obtain a prediction or classification relating to a condition of a particular component of the underwater industrial setting or the underwater industrial setting and a degree of confidence corresponding to the prediction or classification; and

selectively storing, by the edge processing system, the one or more instances of sensor data in a storage device of the one or more storage devices based on the prediction or classification.

444. The method of claim 443, wherein selectively storing the one or more instances of sensor data includes:

storing, by the edge processing system, the one or more instances of sensor data in the storage device with an expiry in response to obtaining one or more predictions or classifications relating to conditions of respective components of the underwater industrial setting and the underwater industrial setting that collectively indicate that there are likely no issues relating to any component of the underwater industrial setting and the underwater industrial setting, wherein storing the one or more instances of sensor data in the storage device with an expiry is performed such that the one or more instances of sensor data are purged from the storage device in accordance with the expiry.

445. The method of claim 443, wherein selectively storing the one or more instances of sensor data includes:

storing, by the edge processing system, the one or more instances of sensor data in the storage device indefinitely in response to obtaining a prediction or classification relating to a condition of a particular component or the underwater industrial setting that indicates that there is likely an issue relating to the particular component or the underwater industrial setting.

446. The method of claim 420, wherein the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type selected from the group comprising: infrared sensors, sonar sensors, LIDAR sensors, water penetrating sensors, light sensors, strain sensors, rust sensors, biological sensors, temperature sensors, chemical sensors, valve integrity sensors, vibration sensors, flow sensors, cavitation sensors, pressure sensors, weight sensors, and camera sensors.

447. A system for monitoring an industrial setting, comprising:

a set of sensor kits each having a set of sensors that are registered to respective industrial settings and configured to monitor physical characteristics of the industrial settings;

a set of communication gateways for communicating instances of sensor values from the sensor kits to a backend system; and

said backend system for processing the instances of sensor values to monitor the industrial setting, wherein upon receiving registration data for a sensor kit to an industrial setting, the backend system automatically configures and populates a dashboard for an owner or operator of the industrial setting, wherein the dashboard provides monitoring information that is based on the instances of sensor values for the industrial setting.

448. The system of claim 447, wherein the registration of the sensor kit includes an interface for specifying a type of entity or industrial setting to be monitored.

449. The system of claim 448, wherein the backend system configures the dashboard based on the registered type of entity or industrial setting.

450. The system of claim 448, wherein the backend system includes an analytics facility that is configured based on the type of entity or industrial setting.

5 451. The system of claim 448, wherein the backend system includes a machine learning facility that is configured based on the type of entity or industrial setting.

452. The system of claim 447, wherein the communication gateway is configured to provide a virtual container for instances of sensor values such that only a registered owner or operator of the industrial setting can access the sensor values.

10 453. The system of claim 447, wherein upon registration of a sensor kit to an industrial setting, a user may select a set of parameters for monitoring and wherein a set of services and capabilities of the backend system is automatically provisioned based on the selected parameters.

454. The system of claim 447, wherein at least one of the sensor kit, the communication gateway and the backend system includes an edge computation system for automatically calculating a metric for an industrial setting based on a plurality of instances of sensor values from a set of sensor kits.

455. The system of claim 447, wherein the sensor kit is a self-configuring sensor kit network.

456. The system of claim 455, wherein the sensor kit network is a star network such that each sensor of the plurality of sensors transmits respective instances of sensor data with the communication gateway directly using a short-range communication protocol.

20 457. The system of claim 455, wherein computer-executable instructions cause one or more processors of the communication gateway device to initiate configuration of the self-configuring sensor kit network.

458. The system of claim 455, wherein the self-configuring sensor kit network is a mesh network such that:

25 a communication device of each sensor of the plurality of sensors is configured to establish a communication channel with at least one other sensor of the plurality of sensors; and

at least one sensor of the plurality of sensors is configured to receive instances of sensor data from one or more other sensors of the plurality of sensors and to route the received instances of the sensor data towards the communication gateway.

30 459. The system of claim 458, wherein the computer-executable instructions further cause the one or more processors of the communication gateway to initiate configuration of the self-configuring sensor kit network, wherein the plurality of sensors form the mesh network in response to the communication gateway initiating configuration of the self-configuring sensor kit network.

460. The system of claim 455, wherein the self-configuring sensor kit network is a hierarchical network.

461. A method of monitoring a plurality of industrial settings using a set of sensors kits, a set of communication gateways, and a backend system, the method comprising:

5 registering each sensor kit of the plurality of sensor kits to a respective industrial setting of the plurality of industrial settings;

 configuring each sensor kit of the plurality of sensor kits to monitor physical characteristics of the respective industrial setting to which the sensor kit is registered;

 transmitting, by each communication gateway of the set of communication gateways,
10 instances of sensor data from a respective sensor kit of the plurality of sensor kits to the backend system;

 processing, by the backend system, the instances of sensor data received from each sensor kit of the plurality of sensor kits;

 automatically configuring and populating, by the backend system, a dashboard for an owner
15 or operator of the respective industrial setting upon receiving registration data for a sensor kit of the plurality of sensor kits; and

 providing, by the dashboard, monitoring information that is based on the instances of sensor data for the respective industrial setting.

462. The method of claim 461, wherein registering each sensor kit includes providing an
20 interface for specifying a type of entity or industrial setting to be monitored.

463. The method of claim 462, wherein configuring each sensor kit to monitor physical characteristics of the respective industrial setting includes configuring, by the backend system, the dashboard based on the registered type of entity or industrial setting.

464. The method of claim 462, wherein the backend system includes an analytics facility that is
25 configured based on the type of entity of an industrial setting.

465. The method of claim 462, wherein the backend system includes a machine learning facility that is configured based on the type of entity or industrial setting.

466. The method of claim 461, further comprising providing, by each communication gateway of the plurality of communication gateways, a virtual container for instances of sensor data such
30 that only a registered owner or operator of the respective industrial setting can access the sensor data.

467. The method of claim 461, wherein upon registration of a sensor kit to an industrial setting, a user may select a set of parameters for monitoring.

468. The method of claim 467, further comprising automatically provisioning, by the backend
35 system, a set of services and capabilities of the backend system based on the selected parameters.

469. The method of claim 461, wherein at least one of a sensor kit of the plurality of sensor kits, a communication gateway of the plurality of communication gateways, and the backend system includes an edge computation system for automatically calculating a metric for an industrial setting based on a plurality of instances of sensor data from a set of sensor kits.

5 470. The method of claim 461, wherein at least one sensor kit of the plurality of sensor kits is a self-configuring sensor kit network including a plurality of sensors.

471. The method of claim 470, further comprising:

capturing, by the plurality of sensors, sensor data; and

10 transmitting, by the plurality of sensors, the sensor data to and edge device via the self-configuring sensor kit network.

472. The method of claim 471, wherein transmitting the sensor data via the self-configuring sensor kit network includes directly transmitting, by each sensor of the plurality of sensors, instances of sensor data with the edge device using a short-range communication protocol, wherein the self-configuring sensor kit network is a star network.

15 473. The method of claim 470, further comprising initiating, by the edge processing system, configuration of the self-configuring sensor kit network.

474. The method of claim 471, wherein the self-configuring sensor kit network is a mesh network and each sensor of the plurality of sensors includes a communication device.

475. The method of claim 474, further comprising:

20 establishing, by the communication device of each sensor of the plurality of sensors, a communication channel with at least one other sensor of the plurality of sensors;

receiving, by at least one sensor of the plurality of sensors, instances of sensor data from one or more other sensors of the plurality of sensors; and

25 routing, by the at least one sensor of the plurality of sensors, the received instances of the sensor data towards the edge device.

476. The method of claim 471, wherein the self-configuring sensor kit network is a hierarchical network and the sensor kit includes one or more collection devices.

477. The method of claim 470, wherein the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.

30 478. A sensor kit configured for monitoring an industrial setting, the sensor kit comprising:

an edge device; and

a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of
35 the plurality of sensors comprises:

a sensing component that captures sensor measurements and outputs instances of sensor data;

a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and

a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol; wherein the edge device comprises:

a communication system having:

a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network; and

a second communication device that transmits sensor kit packets to a backend system via a public network; and

a processing system having one or more processors that execute computer-executable instructions that cause the processing system to:

receive the reporting packets from the communication system;

generate a data block based on sensor data obtained from the reporting packets, wherein the data block includes (i) a block header that defines an address of the data block and (ii) a block body that defines the sensor data and a parent address of another data block to which the data block will be linked; and

transmit the data block to one or more node computing devices that collectively store a distributed ledger that is comprised of a plurality of data blocks.

479. The sensor kit of claim 478, wherein generating the data block includes generating a hash value of the block body.

480. The sensor kit of claim 478, wherein generating the data block includes encrypting the block body.

481. The sensor kit of claim 478, wherein the distributed ledger includes a smart contract that defines one or more conditions relating to collected sensor data and one or more actions that are initiated by the smart contract in response to the one or more conditions being satisfied.

482. The sensor kit of claim 481, wherein the smart contract receives the data block from the sensor kit and determines whether the one or more conditions are satisfied based on at least the sensor data stored in the data block.

483. The sensor kit of claim 481, wherein the smart contract corresponds to an insurer.

484. The sensor kit of claim 483, wherein the action defined in the smart contract triggers a transfer of funds to an account associated with an operator associated with the sensor kit in response to satisfying the one or more conditions.

485. The sensor kit of claim 484, wherein the one or more conditions include a first condition that determines whether the sensor kit has reported a sufficient amount of sensor data and a second condition that determines whether the reported sensor data indicates that the industrial setting is operating without issue.

486. The sensor kit of claim 481, wherein the smart contract corresponds to a regulatory body.

487. The sensor kit of claim 486, wherein the action defined in the smart contract triggers an issuance of a token to an operator associated with the sensor kit in response to satisfying the one or more conditions.

488. The sensor kit of claim 487, wherein the one or more conditions include a first condition that requires a certain amount of reported sensor data to be reported by a sensor kit and a second condition that requires the reported sensor data to be compliant with the reporting regulations.

489. The sensor kit of claim 478, wherein the edge device is one of the node computing devices.

490. A method for monitoring an industrial setting using a sensor kit having a plurality of sensors and an edge device including a processing system, comprising:

receiving, by the processing system, reporting packets from one or more respective sensors of the plurality of sensors, wherein each reporting packet includes routing data and one or more instances of sensor data;

generating, by the processing system, a data block based on sensor data obtained from the reporting packets, wherein the data block includes (i) a block header that defines an address of the data block and (ii) a block body that defines the sensor data and a parent address of another data block to which the data block will be linked; and

transmitting, by the processing system, the data block to one or more node computing devices that collectively store a distributed ledger that is comprised of a plurality of data blocks.

491. The method of claim 490, wherein generating the data block includes generating, by the processing system, a hash value of the block body.

492. The method of claim 490, wherein generating the data block includes encrypting, by the processing system, the block body.

493. The method of claim 490, wherein the distributed ledger includes a smart contract that defines one or more conditions relating to collected sensor data and one or more actions that are initiated by the smart contract in response to the one or more conditions being satisfied.

494. The method of claim 493, wherein the smart contract receives the data block from the sensor kit and determines whether the one or more conditions are satisfied based on at least the sensor data stored in the data block.

495. The method of claim 493, wherein the smart contract corresponds to an insurer.

5 496. The method of claim 495, wherein the action defined in the smart contract triggers a transfer of funds to an account associated with an operator associated with the sensor kit in response to satisfying the one or more conditions.

497. The method of claim 496, wherein the one or more conditions include a first condition that determines whether the sensor kit has reported a sufficient amount of sensor data and a second
10 condition that determines whether the reported sensor data indicates that the industrial setting is operating without issue.

498. The method of claim 493, wherein the smart contract corresponds to a regulatory body.

499. The method of claim 498, wherein the action defined in the smart contract triggers an issuance of a token to an operator associated with the sensor kit in response to satisfying the one
15 or more conditions.

500. The method of claim 499, wherein the one or more conditions include a first condition that requires a certain amount of reported sensor data to be reported by a sensor kit and a second condition that requires the reported sensor data to be compliant with the reporting regulations.

501. The method of claim 490, wherein the edge device is one of the node computing devices.

20 502. The method of claim 490, wherein the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.

503. A system comprising:

a backend system comprising one or more servers configured to deploy a smart contract to a distributed ledger on behalf of a user, wherein the smart contract defines one or more conditions
25 relating to collected sensor data and one or more actions that are initiated by the smart contract in response to the one or more conditions being satisfied;

a sensor kit configured for monitoring an industrial setting, the sensor kit comprising:

an edge device; and

30 a plurality of sensors that capture sensor data and transmit the sensor data via a self-configuring sensor kit network, wherein the plurality of sensors includes one or more sensors of a first sensor type and one or more sensors of a second sensor type, wherein at least one sensor of the plurality of sensors comprises:

a sensing component that captures sensor measurements and outputs instances of sensor data;

a processing unit that generates reporting packets based on one or more instances of sensor data and outputs the reporting packets, wherein each reporting packet includes routing data and one or more instances of sensor data; and

5 a communication device configured to receive reporting packets from the processing unit and to transmit the reporting packets to the edge device via the self-configuring sensor kit network in accordance with a first communication protocol; wherein the edge device comprises:

10 a communication system having a first communication device that receives reporting packets from the plurality of sensors via the self-configuring sensor kit network, and a second communication device that transmits sensor kit packets to a backend system via a public network; and

a processing system having one or more processors that execute computer-executable instructions that cause the processing system to:

15 receive the reporting packets from the communication system;
generate a data block based on sensor data obtained from the reporting packets, wherein the data block includes (i) a block header that defines an address of the data block and (ii) a block body that defines the sensor data and a parent address of another data block to which the data block will be linked; and
20 transmit the data block to one or more node computing devices that collectively store a distributed ledger that is comprised of a plurality of data blocks.

504. The system of claim 503, wherein generating the data block includes generating a hash value of the block body.

25 505. The system of claim 503, wherein generating the data block includes encrypting the block body.

506. The system of claim 503, wherein the smart contract receives the data block from the sensor kit and determines whether the one or more conditions are satisfied based on at least the sensor data stored in the data block.

30 507. The system of claim 506, wherein the smart contract corresponds to an insurer.

508. The system of claim 507, wherein the action defined in the smart contract triggers a transfer of funds to an account associated with an operator associated with the sensor kit in response to satisfying the one or more conditions.

509. The system of claim 508, wherein the one or more conditions include a first condition that
35 determines whether the sensor kit has reported a sufficient amount of sensor data and a second

condition that determines whether the reported sensor data indicates that the industrial setting is operating without issue.

510. The system of claim 506, wherein the smart contract corresponds to a regulatory body.

511. The system of claim 510, wherein the action defined in the smart contract triggers an issuance of a token to an operator associated with the sensor kit in response to satisfying the one or more conditions.

512. The system of claim 511, wherein the one or more conditions include a condition that determines whether the sensor kit has reported a required amount of sensor data as defined by a regulation.

513. The system of claim 503, wherein the edge device is one of the node computing devices.

514. A method for monitoring an industrial setting using a sensor kit in communication with a backend system, the sensor kit comprising a plurality of sensors and an edge device, the method comprising:

deploying, by the backend system, a smart contract to a distributed ledger on behalf of a user, wherein the smart contract defines one or more conditions relating to collected sensor data and one or more actions that are initiated by the smart contract in response to the one or more conditions being satisfied;

receiving, by an edge processing system of the edge device, reporting packets from one or more respective sensors of the plurality of sensors, wherein each reporting packet includes routing data and one or more instances of sensor data;

generating, by the edge processing system, a data block based on sensor data obtained from the reporting packets, wherein the data block includes (i) a block header that defines an address of the data block and (ii) a block body that defines the sensor data and a parent address of another data block to which the data block will be linked; and

transmitting, by the edge processing system, the data block to one or more node computing devices that collectively store a distributed ledger that is comprised of a plurality of data blocks.

515. The method of claim 514, wherein generating the data block includes generating, by the edge processing system, a hash value of the block body.

516. The method of claim 514, wherein generating the data block includes encrypting, by the edge processing system, the block body.

517. The method of claim 514, wherein the distributed ledger receives the data block from the sensor kit and determines whether the one or more conditions of the smart contract are satisfied based on at least the sensor data stored in the data block.

518. The method of claim 517, wherein the smart contract corresponds to an insurer.

519. The method of claim 518, wherein the action defined in the smart contract triggers a transfer of funds to an account associated with an operator associated with the sensor kit in response to satisfying the one or more conditions.

520. The method of claim 519, wherein the one or more conditions include a first condition that
5 determines whether the sensor kit has reported a sufficient amount of sensor data and a second condition that determines whether the reported sensor data indicates that the industrial setting is operating without issue.

521. The method of claim 517, wherein the smart contract corresponds to a regulatory body.

522. The method of claim 521, wherein the action defined in the smart contract triggers an
10 issuance of a token to an operator associated with the sensor kit in response to satisfying the one or more conditions.

523. The method of claim 522, wherein the one or more conditions include a condition that determines whether the sensor kit has reported a required amount of sensor data as defined by a regulation.

15 524. The method of claim 514, wherein the edge device is one of the node computing devices.

525. The method of claim 514, wherein the backend system is one of the node computing devices.

526. The method of claim 514, wherein the plurality of sensors includes a first set of sensors of a first sensor type and a second set of sensors of a second sensor type.




FIG. 1

2/22




FIG. 2A

3/22





FIG. 2B






FIG. 3A

6/22




FIG. 3B

7/22




FIG. 4

8/22




FIG. 5

9/22




FIG. 6

10/22




FIG. 7

11/22




FIG. 8

12/22




FIG. 9

13/22




FIG. 10




FIG. 11




FIG. 12

16/22




FIG. 13




FIG. 14




FIG. 15

19/22




FIG. 16





FIG. 17






FIG. 19

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2019/059088**A. CLASSIFICATION OF SUBJECT MATTER****H04L 29/08(2006.01)i, G05B 23/02(2006.01)i**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

H04L 29/08; G05B 19/418; G05B 23/02; G06F 13/38; G06F 19/00; H04L 12/24; H04L 12/26; H04L 29/06; H04N 005/225; H04N 7/18; H04W 12/04

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models

Japanese utility models and applications for utility models

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS(KIPO internal) & Keywords: self-configuring sensor kit network, machine-learned model, media content frame, compression, smart contract, data block

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y A	US 2018-0375743 A1 (GUANG-HE LEE et al.) 27 December 2018 paragraphs [0014]-[0048], [0066]-[0109]; claims 1, 5, 11; and figures 1-2	1-6, 16-25, 121, 135 , 142-145, 149, 155 , 172-175, 202 , 217-223, 503-513 54-66, 136-141 , 156-159
Y	US 2018-0321667 A1 (STRONGFORCE IOT PORTFOLIO 2016, LLC) 08 November 2018 paragraphs [0031], [0223]-[0364], [0561]-[0723], [0926]-[1107], [1531]-[1888] ; and figures 2, 49	1-6, 16-25, 135, 149 , 155, 172-175, 202 , 217-223
Y	US 2015-0134954 A1 (BROADCOM CORP.) 14 May 2015 paragraphs [0003]-[0013]; and figure 1	16, 17, 22, 217, 218
Y	WO 02-33558 A1 (PHYSICAL OPTICS CORP.) 25 April 2002 abstract; page 9, line 6 - page 39, line 18; page 93, line 28 - page 94, line 15; claims 1-18, 72-127, 299-300; and figure 5	121, 135, 142-145
Y	US 2004-0114047 A1 (POORVI L. VORA et al.) 17 June 2004 paragraphs [0006]-[0049]	144

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"D" document cited by the applicant in the international application

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

11 May 2020 (11.05.2020)

Date of mailing of the international search report

11 May 2020 (11.05.2020)

Name and mailing address of the ISA/KR

International Application Division

Korean Intellectual Property Office

189 Cheongsa-ro, Seo-gu, Daejeon, 35208, Republic of Korea

Facsimile No. +82-42-481-8578

Authorized officer

KIM, Sung Hee

Telephone No. +82-42-481-3516



INTERNATIONAL SEARCH REPORT

International application No.

PCT/US2019/059088

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 2017-190795 A1 (RWE INTERNATIONAL SE) 09 November 2017 page 1, line 12 - page 27, line 7; page 36, line 4 - page 43, line 28; and figure 5-6	503-513

INTERNATIONAL SEARCH REPORTInternational application No.
PCT/US2019/059088**Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)**

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☒ Claims Nos.: 7-15, 26-53, 67-120, 122-134, 146-148, 150-154, 160-171, 176-201, 203-216, 224-502, 514-526
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
See extra page
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of any additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

Regarding claims 7-15, 26-53, 67-120, 122-134, 146-148, 150-154, 160-171, 176-201, 203-216, 224-502 and 514-526, see form ISA/224 mailed on 11 March 2019. PCT Article 6 states that the claims shall be clear and concise, claims 7-15, 26-53, 67-120, 122-134, 146-148, 150-154, 160-171, 176-201, 203-216, 224-502 do not meet this requirement, even assuming for the sake of argument that the individual claims are clear and concise in themselves, because the lack of clarity of the claims as a whole arises from the lack of conciseness. No international search report will be established for claims 7-15, 26-53, 67-120, 122-134, 146-148, 150-154, 160-171, 176-201, 203-216, 224-502 and 514-526.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2019/059088

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2018-0375743 A1	27/12/2018	WO 2017-111832 A1	29/06/2017
US 2018-0321667 A1	08/11/2018	CA 3045439 A1	16/11/2017
		CN 109478057 A	15/03/2019
		CN 110073301 A	30/07/2019
		EP 3411265 A1	12/12/2018
		EP 3455684 A1	20/03/2019
		JP 2019-523425 A	22/08/2019
		KR 10-2000416 B1	15/07/2019
		KR 10-2018-0135089 A	19/12/2018
		KR 10-2019-0075160 A	28/06/2019
		US 10338553 B2	02/07/2019
		US 10338554 B2	02/07/2019
		US 10338555 B2	02/07/2019
		US 10416636 B2	17/09/2019
		US 10416637 B2	17/09/2019
		US 2018-0284735 A1	04/10/2018
		US 2018-0284745 A1	04/10/2018
		US 2018-0284746 A1	04/10/2018
		US 2018-0284747 A1	04/10/2018
		US 2018-0284754 A1	04/10/2018
		US 2019-0187654 A1	20/06/2019
		US 2019-0187655 A1	20/06/2019
		US 2019-0187680 A1	20/06/2019
		US 2019-0187681 A1	20/06/2019
		US 2019-0187682 A1	20/06/2019
		US 2019-0187683 A1	20/06/2019
		WO 2017-136489 A1	10/08/2017
		WO 2017-196821 A1	16/11/2017
		WO 2019-028269 A2	07/02/2019
		WO 2019-028269 A3	25/04/2019
		WO 2019-094721 A2	16/05/2019
		WO 2019-094721 A3	27/06/2019
		WO 2019-094729 A1	16/05/2019
US 2015-0134954 A1	14/05/2015	CN 104635663 A	20/05/2015
		CN 104635663 B	22/09/2017
		CN 104639601 A	20/05/2015
		CN 104639601 B	09/10/2018
		CN 104731756 A	24/06/2015
		HK 1206442 A1	08/01/2016
		HK 1206513 A1	08/01/2016
		HK 1207705 A1	05/02/2016
		US 2015-0134801 A1	14/05/2015
		US 2015-0135259 A1	14/05/2015
		US 2015-0135260 A1	14/05/2015
		US 2016-0050180 A1	18/02/2016
		US 9203803 B2	01/12/2015
		US 9294509 B2	22/03/2016

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2019/059088

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		US 9432332 B2	30/08/2016
WO 02-33558 A1	25/04/2002	AU 2002-13121 A1 TW 569570 A	29/04/2002 01/01/2004
US 2004-0114047 A1	17/06/2004	JP 2004-201311 A	15/07/2004
WO 2017-190795 A1	09/11/2017	EP 3452929 A1 EP 3452929 B1 IL 262777 A	13/03/2019 01/04/2020 30/05/2019