

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 September 2005 (15.09.2005)

PCT

(10) International Publication Number
WO 2005/084146 A2

(51) International Patent Classification: Not classified

(21) International Application Number:
PCT/KR2005/000612

(22) International Filing Date: 4 March 2005 (04.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2004-0015128 5 March 2004 (05.03.2004) KR

(71) Applicant (for all designated States except US): LG ELECTRONICS INC. [KR/KR]; 20, Yoido-dong, Youngdungpo-gu, Seoul 150-721 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): JIN, Young Suk [KR/KR]; 102, 929-3, Pyeongchon-dong, Dongan-gu,


Anyang-si, Gyeonggi-do 431-070 (KR). RYU, Gi Seon [KR/KR]; 208-810, Jugong Apt., Junggye 4-dong, Nowon-gu, Seoul, Korea 139-792 (KR). LEE, Chang Jae [KR/KR]; 102-404, Dae-a Apt. 85, Sinbu-dong, Cheonan-si, Chungcheongnam-do 330-795 (KR).

(74) Agents: KIM, Yong In et al.; KBK & Associates, 15th Floor Yo Sam Building, 648-23, Yeoksam-dong, Kangnam-gu, Seoul 135-080 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: MOBILE BROADBAND WIRELESS ACCESS SYSTEM FOR TRANSFERRING SERVICE INFORMATION DURING HANDOVER



(57) Abstract: The present invention is related to transmitting quality of service (QoS) information of a target base station for admitted service flows during a handover operation. The invention comprises providing a service to a mobile station from a serving base station and receiving at the serving base station a handover request from the mobile station. The serving base station then provides a handover notification to a target base station, wherein the handover notification comprises a QoS parameter associated with the service. The serving base station then receives from the target base station a handover notification response, wherein the handover notification response comprises service level prediction information that is determined in response to the QoS parameter associated with the service. Finally, the serving base station provides a handover response to the mobile station, the handover response comprising the service level prediction information.

WO 2005/084146 A2



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

**MOBILE BROADBAND WIRELESS ACCESS SYSTEM FOR TRANSFERRING
SERVICE INFORMATION DURING HANDOVER**

Technical Field

5 **[0001]** The present invention relates to a mobile broadband wireless access system for transferring service information during a handover operation, and more particularly, to transmitting quality of service (QoS) information to a target base station for admitted service flows during the handover operation.

10 **Background Art**

[0002] Generally, a handover operation can be performed in a broadband wireless access system according to a request by a mobile subscriber station (MSS) or a base station (BS). In performing the handover operation from a current serving base station to one of a plurality of target base stations, the mobile subscriber station must provide quality
15 of service (QoS) information for a service flow admitted in the current mobile subscriber station to the respective target base stations.

[0003] The QoS information provided to the target base stations includes a required bandwidth and a required service class name for the admitted service of the current mobile subscriber station. However, the target base stations are unable to
20 sufficiently guarantee the QoS of a specific service with the QoS information only. In case

a plurality of service flows are admitted in the mobile subscriber station, information indicating which one of the plurality of admitted service flows will be guaranteed is not provided.

[0004] For example, it is assumed that a mobile subscriber station receives both a
5 real-time moving picture download service and a fixed speed service, such as a Voice
Over Internet Protocol (VoIP), from a current serving base station. While the mobile
subscriber station is receiving the services, if a situation needing handover occurs, the
information about the required bandwidth and the service class name for one QoS
guarantee is delivered to target base stations. However, specific handover quality
10 information for maintaining a quality of service for each admitted service is not delivered to
the target base stations. Hence, it is difficult to decide which one of the respective
admitted service flows will be guaranteed for its QoS. Moreover, it is difficult for the target
base station to predict the estimated QoS level for each of the services.

15 **Disclosure of Invention**

[0005] The present invention is directed to transmitting quality of service (QoS)
information to a target base station for admitted service flows during a handover operation.

[0006] Additional features and advantages of the invention will be set forth in the
description which follows, and in part will be apparent from the description, or may be
20 learned by practice of the invention. The objectives and other advantages of the invention

will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

[0007] To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, the present invention is embodied in a method of receiving quality of service (QoS) information in a mobile station associated with a handover operation in a wireless communication system, the method comprising receiving at least one service from a serving base station, scanning at least one target base station to perform the handover operation, requesting a handover request with the serving base station, and receiving a handover response comprising service level prediction information from the serving base station, wherein the service level prediction information is determined by the at least one target base station in response to a QoS parameter associated with the at least one service received from the serving base station.

[0008] Preferably, the QoS parameter comprises at least one of latency information, reserved traffic rate, tolerable traffic rate and sustained traffic rate. The service level prediction information comprises at least one of (1) no service flow available for the mobile station, (2) all service flow available, (3) some service flow available, and (4) no service level prediction available. Moreover, the handover response further comprises a recommended target base station to where the mobile station should handover.

Preferably, the mobile station determines the at least one target base station to handover to.

[0009] In one aspect of the present invention, the method further comprises requesting the at least one service from the serving base station, and receiving a service approval message from the serving base station. Preferably, the service approval message comprises at least one of a QoS parameter value for the at least one service requested and an indication as to the possibility of activating the at least one service requested.

[0010] In one embodiment of the invention, a method of providing quality of service (QoS) information associated with a handover operation in a wireless communication system, comprises providing at least one service to a mobile station from a serving base station, receiving at the serving base station a handover request from the mobile station, providing a handover notification to at least one target base station, wherein the handover notification comprises a QoS parameter associated with the at least one service, receiving from the at least one target base station a handover notification response, wherein the handover notification response comprises service level prediction information that is determined in response to the QoS parameter associated with the at least one service, and providing a handover response to the mobile station, the handover response comprising the service level prediction information.

[0011] Preferably, the QoS parameter comprises at least one of latency information, reserved traffic rate, tolerable traffic rate and sustained traffic rate. The service level prediction information comprises at least one of (1) no service flow available for a mobile station, (2) all service flow available, (3) some service flow available, and (4) no service level prediction available. Moreover, the handover response further comprises

a recommended target base station to where the mobile station should handover.

Preferably, the mobile station determines the at least one target base station to handover to.

[0012] In one aspect of the present invention, the method further comprises
5 receiving a service request for at least one service from the mobile station, checking for the presence of radio resources available for the at least one service requested, allocating a radio resource to the mobile station having requested the at least one service if radio resources are available, and transmitting a service approval message to the mobile station.

[0013] Preferably, the service approval message comprises at least one of a QoS
10 parameter value for the at least one service requested and an indication as to the possibility of activating the at least one service requested. Furthermore, the serving base station transmits information regarding at least one admitted service flow to the target base station allowing a QoS parameter value for the at least one admitted service flow to be periodically provided to the target base station.

[0014] In another aspect of the present invention, the method further comprises
15 providing a handover confirmation to the at least one target base station, receiving at the serving base station a handover indication from the mobile station, and discontinuing communication between the serving base station and the mobile station.

[0015] In another embodiment, the present invention is embodied in a mobile
20 station for receiving quality of service (QoS) information associated with a handover operation in a wireless communication system, the mobile station comprising means for receiving at least one service from a serving base station, means for scanning at least one

target base station to perform the handover operation, and means for requesting a handover request with the serving base station, wherein the means for receiving the at least one service receives a handover response comprising service level prediction information from the serving base station, wherein the service level prediction information is determined by the at least one target base station in response to a QoS parameter associated with the at least one service received from the serving base station.

[0016] Preferably, the QoS parameter comprises at least one of latency information, reserved traffic rate, tolerable traffic rate and sustained traffic rate. The service level prediction information comprises at least one of (1) no service flow available for the mobile station, (2) all service flow available, (3) some service flow available, and (4) no service level prediction available. Moreover, the handover response further comprises a recommended target base station to where the mobile station should handover. Preferably, the mobile station determines the at least one target base station to handover to.

[0017] In one aspect of the present invention, the means for requesting the handover request requests the at least one service from the serving base station, and the means for receiving the at least one service receives a service approval message from the serving base station. Preferably, the service approval message comprises at least one of a QoS parameter value for the at least one service requested and an indication as to the possibility of activating the at least one service requested.

[0018] In one embodiment of the invention, a network for providing quality of service (QoS) information associated with a handover operation in a wireless

communication system, comprises means for providing at least one service to a mobile station from a serving base station and means for receiving at the serving base station a handover request from the mobile station, wherein the means for providing the at least one service provides a handover notification to at least one target base station, 5 wherein the handover notification comprises a QoS parameter associated with the at least one service, wherein the means for receiving the handover request receives from the at least one target base station a handover notification response, wherein the handover notification response comprising service level prediction information that is determined in response to the QoS parameter associated with the at least one service, wherein the 10 means for providing at least one service provides a handover response to the mobile station, the handover response comprising the service level prediction information.

[0019] Preferably, the QoS parameter comprises at least one of latency information, reserved traffic rate, tolerable traffic rate and sustained traffic rate. The service level prediction information comprises at least one of (1) no service flow available 15 for a mobile station, (2) all service flow available, (3) some service flow available, and (4) no service level prediction available. Moreover, the handover response further comprises a recommended target base station to where the mobile station should handover. Preferably, the mobile station determines the at least one target base station to handover to.

20 **[0020]** In one aspect of the present invention, the apparatus further comprises means for receiving a service request for at least one service from the mobile station, means for checking the presence of radio resources available for the at least one service

requested and allocating a radio resource to the mobile station having requested the at least one service if radio resources are available, and means for transmitting a service approval message to the mobile station.

5 | [0021] Preferably, the service approval message comprises at least one of a QoS parameter value for the at least one service requested and an indication as to the possibility of activating the at least one service requested. Furthermore, the serving base station transmits information regarding at least one admitted service flow to the target base station allowing a QoS parameter value for the at least one admitted service flow to be periodically provided to the target base station.

10 | [0022] In another aspect of the present invention, the network further comprises means for providing a handover confirmation to the at least one target base station, means for receiving at the serving base station a handover indication from the mobile station, and means for discontinuing communication between the serving base station and the mobile station.

15 | [0023] It is to be understood that both the foregoing general description and the following detailed description of the present invention are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

Brief Description of Drawings

20 | [0024] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this

application, illustrate embodiment(s) of the invention and together with the description serve to explain the principle of the invention.

[0025] FIG. 1 is a flowchart for transferring quality of service information in accordance with one embodiment of the present invention.

5 [0026] FIG. 2 is a flowchart for transferring quality of service information during handover in accordance with one embodiment of the present invention.

Best Mode for Carrying Out the Invention

[0027] The present invention relates to transmitting quality of service (QoS) information to a target base station for admitted service flows during handover in a broadband wireless access system.

[0028] Referring to FIG. 1, in one embodiment of the present invention, a mobile subscriber station (MSS) 11 transmits a service request message to a serving base station (BS #1) 12 to receive a specific application service (step S101). The service request message comprises information of a service flow to be activated and/or desired QoS parameters to receive the service.

[0029] The serving base station 12 having received the service request message checks for the presence of radio resources available for the service requested by the mobile subscriber station 11 (step S102). If radio resources are available, the serving base station 12 allocates a radio resource to the mobile subscriber station 11 having requested the service (step S103). Thereafter, information indicating whether the serving

base station 12 is capable of performing the service flow requested by the mobile subscriber station 11 is transmitted via a service approval message to the mobile subscriber station 11 (step S104). The service approval message includes QoS parameter values for the service flow requested by the mobile subscriber station 11 and an indication
5 as to the possibility of activating the requested service flow.

[0030] Once providing an application service to the mobile subscriber station 11 (step S105), the serving base station 12 transmits information regarding admitted service flows to target base stations (BS #2) 13 (step S106). In doing so, the QoS parameter values for the service flows can be periodically provided to the target base stations 13.

10 **[0031]** While the service flow is admitted in the above-explained manner, if the mobile subscriber station 11 transmits a handover request message (for example, MOB_MSSHO_REQ) (step S107), the serving base station 12 transmits a handover pre-notification message (HO-pre-notification) to the target base stations 13 (step S108). The handover pre-notification message (HO-pre-notification) may include required information
15 for maintaining the respective admitted service flows. Preferably, the required information for maintaining the respective admitted service flow includes a service flow identifier (SFID), a service class name, QoS parameters corresponding to each service flow, and specific values corresponding to the QoS parameters, respectively. For example, the QoS parameters may be maximum latency, minimum reserved traffic rate, minimum tolerable
20 traffic rate, maximum sustained traffic rate, etc.

[0032] Each of the target base stations 13 having received the handover pre-notification message (HO-pre-notification) decides whether it is capable of admitting a new

mobile subscriber station 11. The decision is then transmitted to the serving base station 12 via a handover pre-notification response message (HO-pre-notification-response) (step S109). The handover pre-notification response message (HO-pre-notification-response) may include information indicating estimated service levels of the admitted service flows which can be provided to the current mobile subscriber station 11 from the target base stations 13.

[0033] Subsequently, the serving base station 12 having received the handover pre-notification response messages (HO-pre-notification-response) from the target stations 13, respectively transmits the information regarding the service levels that can be provided by the target base stations 13 to the mobile subscriber station 11 (step S110).

[0034] Referring to FIG. 2, in another embodiment of the present invention, there exists a plurality of target base stations from which a mobile subscriber station (MSS) 21 can choose to perform a handover operation with. Preferably, once the mobile subscriber station 21 is provided with an application service, as described in steps S101-S105 of FIG. 1, for example, the mobile subscriber station 21 scans neighbor base stations 22, 23, 24 (step S201). If the mobile subscriber station 21 decides to perform handover, the mobile subscriber station 21 transmits a handover request message (MOB_MSSHO_REQ) to a serving base station 22 (BS #1) (step S202).

[0035] The serving base station 22 then transmits a handover request pre-notification message (HO-pre-notification) to notify target base stations 23 and 24 (BS #2 and BS #3, respectively) that there exists the mobile subscriber station 21 requesting the handover (steps S203 and S204).

[0036] For example, Table 1 and Table 2 show configurations for handover request pre-notification messages (HO-pre-notification).

[0037] [Table 1]

Field	Size	Contents
Global Header	152-bit	
For (j=0; J<Num Records; j++){		
MSS unique identifier	48-bit	48-bit unique identifier used by MSS (as provided by the MSS or by the I-am-host-of message)
Estimated Time to HO	16-bit	In milliseconds, relative to the time stamp. A value of 0 indicates that the estimated time is known.
N_NSIE		Number of Network Service Information Elements
For (k=0; k<N_NSIE; k++){		
Field Size	16-bit	Size of TLV encoded information field below
TLV encoded information	Variable	TLV information as allowed on a DSA_REQ MAC message
}		
}		
Security field	TBD	A means to authenticate this message

CRC field	32-bit	IEEE CRC-32
-----------	--------	-------------

[0038] [Table 2]

Field	Size	Contents
Global Header	152-bit	
For (j=0; J<Num Records; j++){		
MSS unique identifier	48-bit	48-bit unique identifier used by MSS (as provided by the MSS or by the I-am-host-of message
Estimated Time to HO	16-bit	In milliseconds, relative to the time stamp. A value of 0 indicates that the estimated time is known.
Required BW	8-bit	Bandwidth which is required by MSS (to guarantee minimum packet data transmission)
For (i=0; i<Num_SFID_Records;i++){		
SFID		
For (k=0;		

k<Num_QoS_Records;k++){		
Required QoS		
Field Size	Variable	QoS parameter definition encodings that in combination define an Admitted QoS ParamterSet specific to the SFID
}		
}		
}		
Security field	TBD	A means to authenticate this message

[0039] In the present invention, parameters associated with a QoS corresponding to each admitted service flow and values corresponding to the parameters are transmitted using the handover request pre-notification message (HO-pre-notification) transmitted during handover from the serving base station 22 to the target base stations 23 and 44. In other words, the handover request pre-notification message (HO-pre-notification) includes the QoS parameters and the values corresponding to the parameters.

[0040] Each of the target base stations 23 and 24 having received the handover request pre-notification message (HO-pre-notification) transmits a handover pre-notification response message (HO-pre-notification-response) to the serving base station

22 (steps S205 and S206). Preferably, the handover pre-notification response message (HO-pre-notification-response) includes QoS-associated information.

[0041] The QoS-associated information transmitted via the handover pre-notification response message (HO-pre-notification-response) preferably includes information regarding the presence of service estimation and information indicating estimated service levels of the admitted service flows which can be provided to the current mobile subscriber station 21 from each of the target base stations 23 and 24.

[0042] The QoS-associated information may be the same information as a service level prediction information that the serving base station 22 transfers to the mobile subscriber station 21 via a handover response message. Preferably, it is possible to divide the information to indicate "all service flows available," "several service flows available," "no service flows available," and the like.

[0043] One exemplary configuration of the handover pre-notification response message (HO-pre-notification-response) is shown in Table 3.

15 [0044] [Table 3]

Field	Size	Contents
Global Header	152-bit	
For (j=0; J<Num Records; j++){		
MSS unique	48-	48-bit unique identifier used by MSS (as provided

identifier	bit	by the MSS or by the I-am-host-of message
Service level prediction		<p style="text-align: center;">Expected service level</p> <p style="text-align: center;">0 = No service possible for this MSS.</p> <p style="text-align: center;">1 = some service is available for one or several Service Flows authorized for the MSS.</p> <p style="text-align: center;">2 = For each authorized Service Flow, a MAC connection can be established with QoS specified by the Authorized QoS parameter Set.</p> <p style="text-align: center;">3 = No service level prediction available.</p>
}		
Security field	TBD	A means to authenticate this message
CRC field	32-bit	IEEE CRC-32

[0045] The serving base station 22 selects one base station appropriate for the handover execution from the target base stations 23 and 24. The serving base station 22 then transmits a handover confirmation message (HO-confirm) to the selected target base station. In this case, the selected base station is the target base station 24 (step S207). The serving base station 22 recommends the target base station 24 as the selected base station to the mobile subscriber station 21 via a handover response message (MOB_HO_RSP) (step S208).

[0046] One exemplary configuration of the handover response message

(MOB_HO_RSP) is shown in Table 4.

[0047] [Table 4]

Syntax	Size	Contents
MOB_BSHO- RSP_Message_Format ()		
Management Message Type=53	8bit	
Estimated HO time	8bit	Target base stations shall be presented in an order such that the first presented is the one most recommended and the last presented is the least recommended. N_Recommended can be derived from the known length of the message.
For (j=0; j<N_Recommended; j++)		
Target BS-ID	48bit	
Service level prediction	8bit	Expected service level 0 = No service possible for this MSS. 1 = some service is available for one or

		<p>several Service Flows authorized for the MSS.</p> <p>2 = For each authorized Service Flow, a MAC connection can be established with QoS specified by the Authorized QoS parameter Set.</p> <p>3 = No service level prediction available.</p>
}		
}		

[0048] The mobile subscriber station 21 may follow the recommendation received from the serving base station 22 and decide to execute the handover to the recommended target base station 24; however, the mobile subscriber station 21 may also choose not to follow the recommendation of the serving base station 22 and decide to execute the handover to a different target base station or not execute the handover at all. If handover is executed to the recommended target base station 24, the mobile subscriber station 21 transmits a handover indication message (MOB_HO_Indication) to the serving base station 22 (step S209). The serving base station 22 then recognizes the mobile subscriber station 21 executing the handover to the target base station 24 and releases a connection for the mobile subscriber station 21 (step S210). The mobile subscriber station 21 then performs a ranging process with the target base station 24 to set a new serving base station to the target base station 24 (step S211).

[0049] The embodiments of the present invention explain that the handover is executed according to a request made by the mobile subscriber station 21. However, transmission of QoS information for the respective admitted service flows is applicable to a case where the handover is executed upon a request made by a base station. Accordingly, 5 the present invention can sustain the QoS for each of the admitted service flows in handover.

[0050] Although the present invention is described in the context of mobile communication, the present invention may also be used in any wireless communication systems using mobile devices, such as PDAs and laptop computers equipped with 10 wireless communication capabilities. Moreover, the use of certain terms to describe the present invention should not limit the scope of the present invention to certain type of wireless communication system, such as UMTS. The present invention is also applicable to other wireless communication systems using different air interfaces and/or physical layers, for example, TDMA, CDMA, FDMA, WCDMA, etc.

[0051] The preferred embodiments may be implemented as a method, apparatus 15 or article of manufacture using standard programming and/or engineering techniques to produce software, firmware, hardware, or any combination thereof. The term "article of manufacture" as used herein refers to code or logic implemented in hardware logic (e.g., an integrated circuit chip, Field Programmable Gate Array (FPGA), Application Specific 20 Integrated Circuit (ASIC), etc.) or a computer readable medium (e.g., magnetic storage medium (e.g., hard disk drives, floppy disks, tape, etc.), optical storage (CD-ROMs, optical

disks, etc.), volatile and non-volatile memory devices (e.g., EEPROMs, ROMs, PROMs, RAMs, DRAMs, SRAMs, firmware, programmable logic, etc.).

[0052] Code in the computer readable medium is accessed and executed by a processor. The code in which preferred embodiments are implemented may further be
5 accessible through a transmission media or from a file server over a network. In such cases, the article of manufacture in which the code is implemented may comprise a transmission media, such as a network transmission line, wireless transmission media, signals propagating through space, radio waves, infrared signals, etc. Of course, those skilled in the art will recognize that many modifications may be made to this configuration
10 without departing from the scope of the present invention, and that the article of manufacture may comprise any information bearing medium known in the art.

[0053] It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come
15 within the scope of the appended claims and their equivalents.

What is claimed is:

1. A method of receiving quality of service (QoS) information in a mobile station associated with a handover operation in a wireless communication system, the method comprising:

- 5 receiving at least one service from a serving base station;
scanning at least one target base station to perform the handover operation;
requesting a handover request with the serving base station; and
receiving a handover response comprising service level prediction information from the serving base station, wherein the service level prediction information is determined by
10 the at least one target base station in response to a QoS parameter associated with the at least one service received from the serving base station.

2. The method of claim 1, wherein the QoS parameter comprises at least one of latency information, reserved traffic rate, tolerable traffic rate and sustained traffic rate.

15

3. The method of claim 1, wherein the service level prediction information comprises at least one of (1) no service flow available for the mobile station, (2) all service flow available, (3) some service flow available, and (4) no service level prediction available.

4. The method of claim 1, wherein the handover response further comprises a recommended target base station to where the mobile station should handover.

5. The method of claim 1, wherein the mobile station determines the at least one target base station to handover to.

6. The method of claim 1, further comprising requesting the at least one service from the serving base station.

7. The method of claim 6, further comprising receiving a service approval message from the serving base station.

8. The method of claim 7, wherein the service approval message comprises at least one of:

15 a QoS parameter value for the at least one service requested; and
an indication as to the possibility of activating the at least one service requested.

9. A method of providing quality of service (QoS) information associated with a handover operation in a wireless communication system, the method comprising:

20 providing at least one service to a mobile station from a serving base station;
receiving at the serving base station a handover request from the mobile station;

providing a handover notification to at least one target base station, wherein the handover notification comprises a QoS parameter associated with the at least one service;

receiving from the at least one target base station a handover notification response, wherein the handover notification response comprises service level prediction information

5 that is determined in response to the QoS parameter associated with the at least one service; and

providing a handover response to the mobile station, the handover response comprising the service level prediction information.

10 10. The method of claim 9, wherein the QoS parameter comprises at least one of latency information, reserved traffic rate, tolerable traffic rate and sustained traffic rate.

11. The method of claim 9, wherein the service level prediction information comprises at least one of (1) no service flow available for a mobile station, (2) all service
15 flow available, (3) some service flow available, and (4) no service level prediction available.

12. The method of claim 9, wherein the handover response further comprises a recommended target base station to where the mobile station should handover.

20 13. The method of claim 9, wherein the mobile station determines the at least one target base station to handover to.

14. The method of claim 9, further comprising:

receiving a service request for at least one service from the mobile station;

checking for the presence of radio resources available for the at least one service

5 requested;

allocating a radio resource to the mobile station having requested the at least one

service if radio resources are available; and

transmitting a service approval message to the mobile station.

10 15. The method of claim 13, wherein the service approval message comprises
at least one of:

a QoS parameter value for the at least one service requested; and

an indication as to the possibility of activating the at least one service requested.

15 16. The method of claim 9, wherein the serving base station transmits
information regarding at least one admitted service flow to the at least one target base
station allowing a QoS parameter value for the at least one admitted service flow to be
periodically provided to the at least one target base station.

20 17. The method of claim 9, further comprising:

providing a handover confirmation to the at least one target base station;

receiving at the serving base station a handover indication from the mobile station;

and

discontinuing communication between the serving base station and the mobile station.

5

18. A mobile station for receiving quality of service (QoS) information associated with a handover operation in a wireless communication system, the mobile station comprising:

means for receiving at least one service from a serving base station;

10 means for scanning at least one target base station to perform the handover operation; and

means for requesting a handover request with the serving base station;

wherein the means for receiving the at least one service receives a handover response, the handover response comprising service level prediction information from the
15 serving base station, wherein the service level prediction information is determined by the at least one target base station in response to a QoS parameter associated with the at least one service received from the serving base station.

19. The mobile station of claim 18, wherein the QoS parameter comprises at
20 least one of latency information, reserved traffic rate, tolerable traffic rate and sustained traffic rate.

20. The mobile station of claim 18, wherein the service level prediction information comprises at least one of (1) no service flow available for the mobile station, (2) all service flow available, (3) some service flow available, and (4) no service level prediction available.

21. The mobile station of claim 18, wherein the handover response further comprises a recommended target base station to where the mobile station should handover.

10

22. The mobile station of claim 18, wherein the mobile station determines the at least one target base station to handover to.

23. The mobile station of claim 18, wherein the means for requesting the handover request requests the at least one service from the serving base station.

24. The mobile station of claim 23, wherein the means for receiving the at least one service receives a service approval message from the serving base station.

25. The mobile station of claim 24, wherein the service approval message comprises at least one of:

a QoS parameter value for the at least one service requested; and
an indication as to the possibility of activating the at least one service requested.

26. A network for providing quality of service (QoS) information associated with
- 5 a handover operation in a wireless communication system, the network comprising:
- means for providing at least one service to a mobile station from a serving base station; and
 - means for receiving at the serving base station a handover request from the mobile station;
- 10 wherein the means for providing the at least one service provides a handover notification to at least one target base station, wherein the handover notification comprises a QoS parameter associated with the at least one service;
- wherein the means for receiving the handover request receives from the at least one target base station a handover notification response, the handover notification
- 15 response comprising service level prediction information that is determined in response to the QoS parameter associated with the at least one service;
- wherein the means for providing the at least one service provides a handover response to the mobile station, the handover response comprising the service level prediction information.

27. The network of claim 26, wherein the QoS parameter comprises at least one of latency information, reserved traffic rate, tolerable traffic rate and sustained traffic rate.

5 28. The network of claim 26, wherein the service level prediction information comprises at least one of (1) no service flow available for a mobile station, (2) all service flow available, (3) some service flow available, and (4) no service level prediction available.

29. The network of claim 26, wherein the handover response further comprises
10 a recommended target base station to where the mobile station should handover.

30. The network of claim 26, wherein the mobile station determines the at least one target base station to handover to.

15 31. The network of claim 26, further comprising:
means for receiving a service request for at least one service from the mobile station;

means for checking the presence of radio resources available for the at least one service requested and allocating a radio resource to the mobile station having requested
20 the at least one service if radio resources are available; and

means for transmitting a service approval message to the mobile station.

32. The apparatus of claim 31, wherein the service approval message comprises at least one of:

- a QoS parameter value for the at least one service requested; and
- 5 an indication as to the possibility of activating the at least one service requested.

33. The apparatus of claim 26, wherein the serving base station transmits information regarding at least one admitted service flow to the at least one target base station allowing a QoS parameter value for the at least one admitted service flow to be

10 periodically provided to the at least one target base station.

34. The apparatus of claim 26, further comprising:

- means for providing a handover confirmation to the at least one target base station;
- means for receiving at the serving base station a handover indication from the
- 15 mobile station; and
- means for discontinuing communication between the serving base station and the mobile station.

FIG. 1




FIG. 2

