

(12) **United States Patent**
Nix

(10) **Patent No.:** US 10,204,233 B2
(45) **Date of Patent:** Feb. 12, 2019

(54) **CRYPTOGRAPHIC UNIT FOR PUBLIC KEY INFRASTRUCTURE (PKI) OPERATIONS**

(71) Applicant: **John A. Nix**, Evanston, IL (US)
 (72) Inventor: **John A. Nix**, Evanston, IL (US)
 (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/041,397**
 (22) Filed: **Jul. 20, 2018**

(65) **Prior Publication Data**
 US 2018/0330109 A1 Nov. 15, 2018

Related U.S. Application Data
 (63) Continuation of application No. 15/575,908, filed as application No. PCT/US2016/033096 on May 18, 2016.

(51) **Int. Cl.**
H04L 9/08 (2006.01)
G06F 21/62 (2013.01)
 (Continued)

(52) **U.S. Cl.**
 CPC **G06F 21/62** (2013.01); **G06F 21/606** (2013.01); **H04L 9/006** (2013.01); **H04L 9/0869** (2013.01);
 (Continued)

(58) **Field of Classification Search**
 USPC 713/150, 163, 171, 183; 726/2, 21, 36; 380/255, 264, 276
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,707,022 B2 * 4/2014 Haggerty H04W 8/265 713/150
 8,812,836 B2 * 8/2014 Meyerstein H04W 8/265 713/155

(Continued)

FOREIGN PATENT DOCUMENTS

CA 3018526 A1 12/2016
 EP 3374923 A1 9/2018

(Continued)

OTHER PUBLICATIONS

GSMA, Embedded SIM Remote Provisioning Architecture Version 1.1, Dec. 17, 2013, pp. 1-84.


(Continued)

Primary Examiner — Sharif E Ullah
 (74) *Attorney, Agent, or Firm* — McDonnell Boehnen Hulbert & Berghoff LLP

(57) **ABSTRACT**

A module such as an M2M device or a mobile phone can include a removable data storage unit. The removable data storage unit can include a nonvolatile memory, a noise amplifying memory, and a cryptographic unit. The nonvolatile memory can include (i) shared memory for access by both the module and the cryptographic unit, and (ii) protected memory accessible only by the cryptographic unit. The cryptographic unit can use a noise memory interface and noise amplifying operations in order to increase and distribute bit errors recorded in the noise amplifying memory. The cryptographic unit can (i) generate a random number using the noise amplifying memory and (ii) input the random number into a set of cryptographic algorithms in order to internally derive a PKI key pair. The private key can be recorded in protected memory and the public key signed by a certificate authority.

16 Claims, 13 Drawing Sheets



Related U.S. Application Data

- | | | | | | | | |
|------|--|--------------------|------------------|------------------|-----|-------|-----------------------|
| | | 2014/0329502 | A1* | 11/2014 | Lee | | H04W 12/06
455/411 |
| (60) | Provisional application No. 62/165,317, filed on May 22, 2015. | 2015/0143125 | A1* | 5/2015 | Nix | | H04W 4/70
713/171 |
| (51) | Int. Cl. | | | | | | |
| | G06F 21/60 | (2013.01) | | | | | |
| | H04L 9/32 | (2006.01) | | | | | |
| | H04W 4/60 | (2018.01) | | | | | |
| | H04W 4/70 | (2018.01) | | | | | |
| | H04L 9/00 | (2006.01) | | | | | |
| (52) | U.S. Cl. | | | | | | |
| | CPC | H04L 9/3247 | (2013.01); | H04W 4/60 | | | |
| | | (2018.02); | H04W 4/70 | (2018.02) | | | |

- | | | | | | |
|--|--------------|-----|---------|-----|------------------|
| | 2016/0269386 | A1 | 9/2016 | Nix | |
| | 2017/0373845 | A1 | 12/2017 | Nix | |
| | 2018/0144147 | A1* | 5/2018 | Nix | G06F 21/62 |

FOREIGN PATENT DOCUMENTS

- | | | | |
|----|-------------|----|---------|
| WO | 2015/036773 | A2 | 3/2015 |
| WO | 2015/036776 | A1 | 3/2015 |
| WO | 2015/052422 | A1 | 4/2015 |
| WO | 2016/191176 | A1 | 12/2016 |

OTHER PUBLICATIONS

(56) **References Cited**

U.S. PATENT DOCUMENTS

- | | | | | | |
|--------------|-----|---------|-----------------|-------|-------------------------|
| 8,843,179 | B2* | 9/2014 | Li | | H04W 8/20
455/558 |
| 8,868,041 | B2* | 10/2014 | O'Leary | | H04W 8/22
455/405 |
| 9,009,475 | B2* | 4/2015 | Hauck | | H04L 63/0853
370/338 |
| 9,100,175 | B2* | 8/2015 | Nix | | H04L 9/0869 |
| 9,319,223 | B2 | 4/2016 | Nix | | |
| 9,351,162 | B2 | 5/2016 | Nix | | |
| 9,742,562 | B2 | 8/2017 | Nix | | |
| 9,961,060 | B2 | 5/2018 | Nix | | |
| 2013/0091556 | A1* | 4/2013 | Horn | | H04W 4/00
726/4 |
| 2013/0205390 | A1* | 8/2013 | Hauck | | H04L 63/1408
726/22 |
| 2013/0227646 | A1* | 8/2013 | Haggerty | | H04L 63/0853
726/3 |
| 2013/0344864 | A1* | 12/2013 | Park | | H04W 8/18
455/432.3 |
| 2014/0004827 | A1* | 1/2014 | O'Leary | | H04W 8/22
455/411 |
| 2014/0031012 | A1* | 1/2014 | Park | | H04W 12/06
455/411 |
| 2014/0082358 | A1 | 3/2014 | Nakhjiri et al. | | |
| 2014/0195811 | A1* | 7/2014 | Braams | | H04L 9/3247
713/176 |
| 2014/0235210 | A1 | 8/2014 | Park et al. | | |
| 2014/0237101 | A1* | 8/2014 | Park | | H04L 67/303
709/223 |

- GSMA, Remote Provisioning Architecture for Embedded UICC Technical Specification Version 2.0 , Oct. 13, 2014, pp. 1-293.
- ETSI, Smart Cards; Embedded UICC; Requirements Specification (Release 12), Jun. 2013, pp. 1-20.
- International Standards Organization—9594-8, Public-key and Attribute Certificate Frameworks, Aug. 1, 2001, pp. 1-19.
- IETF, RFC 6090, Fundamental Elliptic Curve Cryptography Algorithms, Feb. 2011, pp. 1-41.
- Wikipedia, Elliptic Curve Diffie-Hellman, http://en.wikipedia.org/wiki/Elliptic_curve_Diffie%E2%80%93Hellman, Sep. 24, 2013, pp. 1-2.
- Park et al., Secure Profile Provisioning Architecture for Embedded UICC, 2013 IEEE, pp. 297-303.
- Wikipedia, Elliptic Curve Cryptography, http://en.wikipedia.org/wiki/Elliptic_curve_cryptography, Sep. 9, 2013, pp. 1-8.
- Wikipedia, Digital Signature, http://en.wikipedia.org/wiki/Digital_Signature, Sep. 9, 2013, pp. 1-10.
- Search Report and Written Opinion for PCT/US2016/033069. pp. 1-6.
- Extended European Search Report for EP App. No. 16800509.8 dated Dec. 13, 2018.
- Smith, I., "Embedded SIM Remote Provisioning Architecture," Retrieved from the Internet: <http://gsma.com/newsroom/wp-content/uploads/SGP.01-v1.12.pdf> [retrieved on Sep. 17, 2018], Jan. 30, 2014.
- ANSI: "Working Draft—Version 2.0 ANSI X9.63 Public key Cryptography for the Financial Services Industry: Elliptic Curve Key Agreement and Key Transport Schemes Contents," Retrieved from the Internet: URL: <ftp://ftp.iks-jena.de/mitarb/lutz/standards/ansi/X9/x963-7-5-98.pdf> [retrieved on Dec. 3, 2018], Jul. 5, 1998.

* cited by examiner




Figure 1a

Figure 1c




Figure 1b




Figure 1d




Figure 1f




Figure 2a





Figure 2b






Figure 3a




Figure 3b




Figure 4b




Figure 4a




Figure 6




Figure 5




Figure 7a

Module Certificate 122a

256 bit Elliptic Curve Key with SHA 256 Signature ("... " is long text removed)





Figure 7b

Cryptographic Unit Certificate 122b

283 bit Elliptic Curve Key with SHA 256 Signature ("... " is long text removed)



CRYPTOGRAPHIC UNIT FOR PUBLIC KEY INFRASTRUCTURE (PKI) OPERATIONS

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 15/575,908, filed Nov. 21, 2017, which is a U.S. National Phase Application pursuant to 35 U.S.C. § 371 of International Application No. PCT/US2016/033096 filed May 18, 2016, which claims priority to U.S. Provisional Patent Application No. 62/165,317 filed May 22, 2015. The entire disclosure contents of these applications are herewith incorporated by reference into the present application.

BACKGROUND

Technical Field

The present methods and systems relate to securing communications between a module and a network, and more particularly, to embedding a cryptographic unit within the module, where the module can use the cryptographic unit to securely derive and record private keys and perform public key infrastructure (PKI) operations.

Description of Related Art

The combination of “machine-to-machine” (M2M) communications and low-cost sensors, Internet connections, and processors is a promising and growing field. Among many potential benefits, M2M technologies allow the remote monitoring of people, assets, or a location where manual monitoring may not be economical. Many M2M applications significantly reduce costs by using automated monitoring instead of manual techniques. Prominent examples of M2M applications today include monitoring with vending machines, automobiles, alarm systems, and remote sensors. Fast growing markets for M2M applications today include tracking devices for shipping containers or pallets, health applications such as the remote monitoring of a person’s glucose levels or heartbeat, monitoring of industrial equipment deployed in the field, and also security systems. Many M2M applications leverage either wired Internet connections or wireless connections, and both types of connections continue to grow rapidly. M2M communications may also be referred to as “the Internet of things” (IoT).

M2M communications can provide remote control over actuators that may be connected to a M2M device, such as turning on or off a power switch, locking or unlocking a door, adjusting a speed of a motor, or similar remote control. A decision to change or adjust an actuator associated with an M2M device can utilize one or a series of sensor measurements. An M2M device may also be referred to as a “wireless module” or also simply a module. As one example, a M2M device connected to an automobile can periodically report engine status to a remote server, and if the engine is operating outside specifications such as being too hot, including potentially an “alarm” condition, then temperature and an alarm code can be reported to a central server by the M2M device. The server can subsequently instruct the driver and/or a specified mechanic to investigate the engine for potential mechanical malfunctions or other causes. The previous example is just one of many possible applications for M2M technology, and as the costs for computer and networking hardware continue to decline, together with the growing ease of obtaining either wired or wireless Internet

access for small form-factor devices, the number of economically favorable applications for M2M communications grows.

Many M2M applications can leverage wireless networking technologies. Wireless technologies such as wireless local area networks and wireless wide area networks have proliferated around the world over the past 15 years, and usage of these wireless networks is also expected to continue to grow. Wireless local area network (LAN) technologies include WiFi and wireless wide area network (WAN) technologies include 3rd Generation Partnership Project’s (3GPP) 3rd Generation (3G) Universal Mobile Telecommunications System (UMTS) and 4th Generation (4G) Long-term Evolution (LTE), LTE Advanced, and the Institute of Electrical and Electronics Engineers’ (IEEE) 802.16 standard, also known as WiMax. The use of wireless technologies with “machine-to-machine” communications creates new opportunities for the deployment of M2M modules in locations without fixed-wire Internet access, but also creates several new classes of problems that need to be solved.

Many of these problems relate to establishing security and trust between modules and a network in a manner that is both scalable and supportable over a relatively long operating lifetime of a module such as potentially 10 years or longer. Existing solutions to the problem of establishing security, such as installing a SIM card in the module or mobile phone (where the SIM card can include network access credentials), may not be efficient or feasible for M2M applications. Since M2M modules may be either (i) unattended, (ii) operating remotely, and/or (iii) traveling geographically or globally, consequently an end user or a module provider may not be able to feasibly or cost-effectively change a SIM card after the module initiates operation. A need exists in the art to allow for a deployed module to securely and automatically begin using either (i) new private and public keys (i.e. without human intervention such as swapping out a SIM card), or (ii) new network access credentials such as a new subscriber identity and shared secret key K.

Since the packets transmitted and received by a wireless module will likely traverse the public Internet for many applications, a need exists in the art to (i) prevent eavesdropping at intermediate points along the path of packets transmitted and received, (ii) allow endpoints to verify the identity of the source of packets received. A need exists in the art for a module and a server to leverage established public key infrastructure (PKI) techniques and algorithms. A need exists in the art for a module to securely derive and record PKI private keys in a manner that prevents exposure of the private key to third parties, including potentially software or firmware operating in a module or mobile phone. A need exists in the art for the private key to be securely recorded in a trusted environment protected by hardware, where the hardware recording a private key and associated cryptographic algorithms is compatible with existing and commonly deployed modules and form factors, such that new industry standards for hardware interfaces are not necessarily required. A need exists in the art for the trusted environment protected by hardware to be in a portable format, such that the portable format can readily be transported between entities such as a manufacturer, a module provider, separately from a module in which it can operate.

Multiple entities associated with a module may prefer for the module to have a certificate both (i) from a trusted certificate authority and (ii) recorded for a module public key and module identity used by the module. Consequently, a need exists in the art for a certificate authority to reliably

trust that a public key submitted to the certificate authority for signature is genuine and trusted. In other words, third parties may only be able to trust a certificate from the certificate authority to the extent the certificate authority can trust that the private key associated with the public key remains secure. Therefore, a need exists in the art for a certificate authority to trust that private keys for modules with its certificates remain reasonably secure. Further, entities associated with a module, such as an end user or a module provider, may prefer that the private key for the module is not recorded by any other entity besides a trusted environment in the module, in order to maintain full control and accountability for the private key. Therefore, a need exists in the art for methods and systems such that a private key can be recorded solely within a trusted environment, where the trusted environment can comprise a cryptographic unit.

The wide variety of operating systems and versions of operating systems for modules without a UICC creates significant challenges for a manufacturer of a storage unit to easily enable communication between a module and a cryptographic unit, given the wide diversity of modules that are desired to be supported. Therefore, a need exists in the art for the a module and a cryptographic unit to communicate with each other via established and widely deployed standards, such that new software drivers do not need to be distributed in order to enable communication with a cryptographic unit. There exists a related need in the art, for modules that lack (i) a UICC or SIM card interface, but support (ii) removable storage media such as SD cards, to easily communicate with a cryptographic unit without requiring firmware updates.

In addition, the utilization of PKI technologies in modules can increase security, but a number of technical challenges must be addressed. These challenges increase if (A) a deployed module requires updated private/public key pairs after (B) operation begins for a module deployed into the field. The typical paradigm of “swapping out a SIM card” (which also depend on a pre-shared secret key K_i embedded in the card) with mobile phones may not be applicable or cost effective with modules, where swapping out the SIM card could be burdensome. Newer PKI technologies may offer a wide variety of algorithms for ciphering with public keys, and a need exists in the art for the utilization of new public and private keys to support the wide variety of algorithms, even after a module has been installed. In other words, a system should preferably both be highly secure and also flexible enough to adopt new security keys and standards. A need exists in the art for a scalable and secure method of associating a module identity with a module public key, when the module begins utilizing a new public key. A need exists in the art for a module to efficiently be able to utilize multiple public/private key pairs at the same time, such as with different service providers or different applications simultaneously.

Although securing communications between a module and a network can be accomplished through the use of cryptographic algorithms and private keys, the use of cryptographic algorithms including key derivation or key generation can required the use of random numbers with a high degree of information entropy. In other words, a system of security may only be as strong as the “randomness” of random numbers used to generate keys to secure the system. However, a trusted environment used by a computer or a module, such as on relatively small cards such as a UICC, SD card, or in an embedded integrated circuit on a circuit board may operate in an environment desirably relatively

closed in order to enhance security. However, the relatively closed environment can reduce the available level of information entropy or randomness desired for the generation of random numbers. Therefore, a need exists in the art for methods and systems to provide a trusted environment with access to components in the trusted environment with a high level of information entropy or randomness for the generation of keys to secure communications. A need also exists in the art for the components used in the trusted environment to generate random numbers to leverage existing and widely deployed manufacturing techniques such that the components can readily be included and integrated into in the trusted environment in a small form factor such as a UICC, SD card, or embedded within an integrated circuit.

Sources of information entropy or randomness within a trusted environment, such as within an integrated circuit, for the creation of random numbers have encountered resistance in market acceptance. An example is the use of the RDSEED instruction in an Intel family of processors, where thermal noise in silicon is used in the generation of random numbers. A primary source of resistance for users of the trusted environment is that the source of information entropy is often highly dynamic and changing, such as measuring thermal noise within silicon for an integrated circuit. Externally auditing the values and source of the thermal noise or other sensors can be difficult because the values may constantly change. Consequently, it may not be feasible to reproduce the exact various noise levels at the time a random number is generated at a subsequent time after the random number is generated.

A need exists in the art such that a source of information entropy or noise used to generate a random number can optionally remain relatively static or fully and entirely re-created for auditing and analysis purposes. Thus, a need exists in the art for an option in a cryptographic unit where the complete state of the source of information entropy can be recorded, thereby allowing with the option for verification of the input state to support an audit or analysis of the system used to generate a random number. In this manner, users evaluating the source and “randomness” of the random numbers output can gain confidence in the system and thereby support market adoption. A need exists in the art for the same source of information entropy to also optionally and simply be continually changed, such as during normal operation and not during a period of external audit or analysis, such that random numbers output using the source of information entropy or noise can be trusted.

And other needs exist in the art as well, as the list recited above is not meant to be exhaustive but rather illustrative.

SUMMARY

Methods and systems are provided for (i) using a set of cryptographic unit for recoding private keys and (ii) using the keys in support of operations with the set of cryptographic algorithms The cryptographic unit and associated components for recording private keys can operated in any of (i) a removable storage unit such as a “secure digital” (SD) card, (ii) a universal integrated circuit card (UICC), including a UICC that contains an embedded UICC (eUICC) operating with the UICC, and (iii) an integrated circuit soldered to a circuit board. A module, such as a device for supporting “Machine to Machine” (M2M) communications, a mobile phone, or a general purpose computer such as a laptop can include the cryptographic unit and associated components. An objective of various embodiments of the invention is to address the needs in the art described above.

An exemplary embodiment may take the form of methods and systems for a removable storage unit to include a cryptographic unit, a nonvolatile memory, and a noise amplifying memory. The nonvolatile memory can include (i) shared memory for access by both the module and the cryptographic unit, (ii) protected memory accessible only by the cryptographic unit, and (iii) general memory for use by a module or mobile phone where the removable storage unit has been inserted. By providing access to the general memory for the mobile phone or module, the removable storage unit can operate as a traditional, commercially widespread removable storage media such as a “secure digital” (SD) card commonly found in electronic retailers in 2015.

By including the cryptographic unit and shared memory, the removable storage unit can provide useful capabilities of securely supporting PKI operations such as recording a private key within the cryptographic unit in addition to providing access to general memory. The private key can be recorded in a manner such that the private key cannot be feasibly directly read by a module or other entity in physical possession of the storage unit. In other words, only output of algorithms using the private key can be ready by a module where the storage unit has been inserted, thereby allowing the private key to be kept reasonably secure. The private key can be associated with a public key, and the public key can be optionally freely distributed.

The cryptographic unit can include components for operating a set of cryptographic algorithms, including a processor, random access memory, read only memory (after an initial write of data such as boot firmware and a cryptographic unit identity), and a data bus. The cryptographic unit can use a noise memory interface and noise amplifying operations in order to increase and distribute bit errors recorded in the noise amplifying memory. The noise amplifying memory can be connected to the data bus and comprise a non-volatile memory similar to the general memory, with the exceptions that (i) the use of error correction codes is omitted to promote bit errors and, (ii) overall bit errors or memory noise are desirable in the noise amplifying memory. The noise amplifying memory may also optionally have physical specifications or characteristics, such as different layer thicknesses within cells compared to cells used for general memory, in order to enhance or promote the occurrence of bit errors.

A noise memory interface can further enhance the generation of bit errors by applying voltage pulses for setting, reading, and erasing cells in a noise amplifying memory in a manner that increases bit errors, compared to a traditional memory core interface in the storage unit which operates on nonvolatile memory such as the general memory or shared memory, where bit errors are preferably minimized. Noise-inducing operations, such as reads, write, and erase operations performed by (A) the cryptographic unit through the noise memory interface on the noise amplifying memory can induce (B) a desired level or range of bit errors or memory noise in the noise amplifying memory.

The cryptographic unit can use a set of cryptographic parameters, a key generation algorithm, and a random number in order to internally derive a private key and a public key. By deriving the private key internally in the cryptographic unit, the private key can remain solely within the cryptographic unit and not be recorded by any other entity, including the manufacturer of the cryptographic unit, a module provider, or other locations with potential physical possession of the storage unit before being inserted into a module. In this manner, the security of the private key can

be enhanced, since the private key does not need to be (A) generated and recorded outside the cryptographic unit by any entity with possession of the storage unit during distribution, and then (B) subsequently written to the cryptographic unit.

The cryptographic unit can generate a random number using the noise amplifying memory. The cryptographic unit can read data from the noise amplifying memory, which includes bit errors or memory noise that have been induced in the noise amplifying memory in a random nature. The data read can be processed and used as a random number seed for input into a random number generator within the cryptographic unit, and the random number generator can output a random number. The random number and cryptographic parameters can be subsequently input into a key generation algorithm to derive a PKI key pair comprising a private key and a public key. The private key can be recorded in protected memory accessible only to the cryptographic unit, and the public key along with an identity transmitted by the cryptographic unit through an external electrical interface of the storage unit.

A certificate authority can subsequently receive the public key and identity, while also recording the cryptographic parameters used to generate the PKI keys, and issue a certificate for the public key. A module with the storage unit can use (i) the private key recorded in protected memory and (ii) the cryptographic unit to perform digital signature operations with the private key in order to authenticate with other nodes such as a server the module connects with via a network.

In an exemplary embodiment, the module and the cryptographic unit can communicate through a shared file system, where the shared file system resides in shared nonvolatile memory. The shared nonvolatile memory and cryptographic unit can be included in a removable storage unit. The shared nonvolatile memory can be configured with a standard file system supported by the module, and the cryptographic unit can read and write to the shared memory. The cryptographic unit can include firmware to support a wide variety of standard file systems for modules, and consequently after a module or module provider configures the shared memory and general memory in a storage unit with a file system, both the module and the cryptographic unit can read and write to the shared file system.

Continuing with this exemplary embodiment, a cryptographic unit can periodically poll for changes or updates in files written by a module, such as a file containing input into a digital signature algorithm within the cryptographic unit. A module can periodically poll for changes or updates in files written by a cryptographic unit, such as a file containing output from a digital signature algorithm within the cryptographic unit. In this manner, existing low-level file system drivers and physical interface drivers for removable storage such as an SD card can be utilized by a module, and primarily application level changes or programming can be required to access the functions of the cryptographic unit, thereby simplifying deployment and support of existing module firmware.

In another exemplary embodiment, a cryptographic unit and protected memory can be integrated within a processor operating within a module, and the removable storage unit can be omitted for this case. A noise amplifying memory can be connected to a data bus in the module via a noise memory controller. The processor can operate in a manner such that only the cryptographic unit is allowed routine or normal access to the noise amplifying memory. The noise amplifying memory and noise memory controller can operate in a

manner for these elements described above. The physical integrated circuit of the processor can contain the logic and components for the cryptographic unit, where the cryptographic unit includes support for both (i) the operation of cryptographic algorithms according to specified cryptographic parameters, and (ii) the recording of a private key processed by the cryptographic unit in the protected memory. A random number can be derived from the noise amplifying memory and subsequently input into key generation algorithms to derive a private key.

In another exemplary embodiment, the cryptographic unit can operate within a UICC, where the UICC can also include or function as an embedded UICC (eUICC). The UICC with the cryptographic unit and the eUICC can be inserted inside a module or a mobile phone. The cryptographic unit operating with the eUICC can generate a private key and a public key using a noise amplifying memory to obtain random numbers with a high level of information entropy. The UICC can forward the public key to a subscription manager. The UICC can subsequently receive an encrypted profile from the subscription manager, where the profile was encrypted using a public key associated with the private key. The encryption of the profile could be performed with a symmetric key, where the symmetric key is derived or communicated using the private key. The eUICC can decrypt the profile using the private key and record network access credentials for a wireless network, such values for an international mobile subscriber identity (IMSI) and a shared secret key K. In this manner a cryptographic unit within a UICC can support electronic distribution of network access credentials.

Exemplary embodiments can include the use of a differential fault protection unit (DFPU), which can manage both the input and output from a cryptographic unit. Since the manufacturer of the cryptographic unit or storage unit containing a cryptographic unit may not control the environmental conditions under which the cryptographic unit operates, a potential attacker could attempt to extract keys or similar activity by exposing the cryptographic or storage unit to environmental conditions outside the specified operating range. A DFPU can perform error checks such that data is not output unless the same output is derived multiple times, thereby reducing errors in the output. Further, a DFPU can provide increased resistance to side-channel attacks, including those where a potential attacker does not have physical access to the storage unit, such as (i) adding random delay to the timing of data output from a cryptographic unit, and (ii) limiting the rate at which a cryptographic unit will output data.

These as well as other aspects and advantages will become apparent to those of ordinary skill in the art by reading the following detailed description, with reference where appropriate to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Various exemplary embodiments are described herein with reference to the following drawings, wherein like numerals denote like entities.

FIG. 1a is a graphical illustration of an exemplary system, where a module with a cryptographic unit communicates with other nodes through a network, in accordance with exemplary embodiments;

FIG. 1b is a graphical illustration of hardware, firmware, and software components for a module, including a storage unit, in accordance with exemplary embodiments;

FIG. 1c is a graphical illustration of hardware, firmware, and software components for a module and a storage unit, in accordance with exemplary embodiments;

FIG. 1d is a graphical illustration of components in a set of cryptographic algorithms, in accordance with exemplary embodiments;

FIG. 1e is a graphical illustration of components within a storage unit, in accordance with exemplary embodiments;

FIG. 1f is a graphical illustration of the operation of a noise collecting memory over time, in accordance with exemplary embodiments;

FIG. 2a is a graphical illustration of a nonvolatile memory cell and a noise collection memory cell, in accordance with exemplary embodiments;

FIG. 2b is a flow chart illustrating exemplary steps for using data output from a noise amplifying memory in order to generate a private key and a public key, in accordance with exemplary embodiments;

FIG. 2c is a graphical illustration of an exemplary system, where a module and a cryptographic unit communicate through a shared nonvolatile memory interface, in accordance with exemplary embodiments;

FIG. 3a is a flow chart illustrating exemplary steps for configuring a cryptographic unit and generating a certificate for the cryptographic unit, in accordance with exemplary embodiments;

FIG. 3b is a flow chart illustrating exemplary steps for deriving a private key for a module using a cryptographic unit, and receiving a certificate for the corresponding public key, in accordance with exemplary embodiments;

FIG. 4a is a flow chart illustrating exemplary steps for creating a digital signature using a private key, parameters, and data input, in accordance with exemplary embodiments;

FIG. 4b is a flow chart illustrating exemplary steps for verifying a digital signature using a public key, parameters, and data input, in accordance with exemplary embodiments;

FIG. 5 is a graphical illustration of hardware, firmware, and software components for a module, where a cryptographic unit can be integrated with a processor, in accordance with exemplary embodiments;

FIG. 6 is a graphical illustration of hardware, firmware, and software components for a module, where a cryptographic unit can be integrated a universal integrated circuit card (UICC), in accordance with exemplary embodiments;

FIG. 7a is an illustration of a certificate for a module public key, in accordance with exemplary embodiments; and,

FIG. 7b is an illustration of a certificate for cryptographic unit public key, in accordance with exemplary embodiments.

DETAILED DESCRIPTION

FIG. 1a

FIG. 1a is a graphical illustration of an exemplary system, where a module with a cryptographic unit communicates with other nodes through a network, in accordance with exemplary embodiments. The system 100 includes a module 101 operating within a wireless network 102. System 100 can also include a module provider 122, a network 107, and an M2M service provider 108, a certificate authority 118, and a monitored unit 119. Network 107 could comprise a packet switched network such as the public Internet or a private intranet, and can also be referred to as Internet 107. M2M service provider 108 can include a server 105. System 100 is illustrated without specific packet transmissions between module 101 and M2M service provider 108, although elements can communicate with each other via

network **107**. Examples of the communications and messages pertaining to the present invention will be illustrated in later Figures.

As contemplated herein, machine-to-machine communications may comprise communication between a module **101** and other nodes through a network **107**, including a server **105**, such that data can be transferred between the module and other nodes with minimal manual intervention, although manual intervention can be required to set up system **100** and any occasional manual maintenance required. Also as contemplated herein, machine-to-machine communications may also be referred to as “the Internet of things” (IoT). Module **101** may comprise a wireless module, such that module **101** can communicate with wireless network **102** using a radio and an antenna. Thus, either a wireless or a wired configuration for module **101** can be utilized in the present invention, although a wireless configuration is depicted in FIG. **1a**.

If module **101** operates as a wireless module, module **101** and wireless network **102** can communicate using a base station **103**. Module **101** and wireless network **102** can utilize a variety of wireless technologies to communicate, including WiFi, WiMax, a 2nd generation wireless wide area network (WAN) technology such as General Packet Radio Services (GPRS) or Enhanced Data rates for GSM Evolution (EDGE), 3rd Generation Partnership Project (3GPP) technology such as 3G, 4G LTE, or 4G LTE Advanced, and other examples exist as well. A wired module **101** can connect to the Internet **107** via a wired connection such as an Ethernet, a fiber optic, or a Universal Serial Bus (USB) connection (not shown). Module **101** can include a module identity **110**, which could comprise a preferably unique alpha-numeric identifier for module **101**, such as an Ethernet MAC address, an International Mobile Equipment Identity (IMEI), an owner interface identifier in an IPv6 network, a serial number, or other sequence of digits to uniquely identify each of the many different possible units for module **101**.

Generally, the communication techniques, security steps, and message flows described herein can be independent of the network technologies utilized at the physical and data-link layers, so long as the underlying network provides access to the Internet **107** and supports Internet Protocols (IP). The Internet **107** can be an IPv4 or an IPv6 packet-switched based network that utilizes standards derived from the Internet Engineering Task Force, such as RFC 786 (User Datagram Protocol), RFC 793 (Transmission Control Protocol), and related protocols. The Internet **107** can be the public Internet comprising globally routable IP addresses, or a private network that utilizes private IP addresses. Although Internet **107** is illustrated as the globally routable public Internet in FIG. **1**, with an exemplary IPv6 address for the server **105**, Internet **107** could also be a private Internet that is (i) not globally routable and (ii) only accessible to authorized modules and servers. As one example of a private Internet **107**, Internet **107** could use private IP addresses for nodes on the network, and in this case Internet **107** could be referred to as an intranet or private network. Alternatively, Internet **107** could be a private network layered on top of the publicly routable Internet via secured and encrypted connections between nodes using public addresses and then communicating through private addresses inside the encrypted connection. The specific numbers for IP addresses and port numbers shown in Figure are illustrative and any valid IP address or port number can be used, including an IPv4 and an IPv6 address.

When operating in a wireless network configuration, module **101** can access the Internet **107** via the wireless

network **102**. When communicating with other elements such as a server **105**, module provider **122**, and/or certificate authority **118**, module **101** can be a wireless handset, a cellular phone, a smartphone, a tablet computer, a laptop, a computer with a radio, a tracking device, an M2M device, and intelligent sensor, or a circuit board with a radio that accesses wireless network **102**. Example manufactures of wireless modules that utilize a wireless WAN such as 3G and 4G LTE networking technologies in 2015 include Sierra Wireless® and Telit®. In a wired configuration (not shown in FIG. **1a**), module **101** can be a computer, security camera, security monitoring device, networked controller, etc. A more detailed depiction of exemplary components of a module **101** is included in FIG. **1b** and FIG. **1c** below.

Module **101** could also comprise a mobile phone operating as client for a payment terminal, such that a wireless antenna within module **101** could send payment information such as an account number from a credit card or similar account associated with either a bank or stored currency. In this case, the “monitored unit” **119** in FIG. **1a** could comprise a payment terminal. Module **101** could communicate with the payment terminal via a magnetic reader or near-field wireless communications, and in this case the magnetic reader or antenna for near-field communications can function as a sensor for module **101**. Module **101** could also operate as a “smartcard” such that an end user presents module **101** to merchants for payments. Credentials and keys for identification and payment could be included within storage unit **109**, and the credentials and keys for identification and payment can incorporate the methods and systems described below.

Wireless network **102** may comprise either a wireless local area network (LAN) such as an 802.11 WLAN, Bluetooth, or Zigbee among other possibilities, and module **101** operating in wireless mode could communicate with a base station **103** of a wireless network **102** using a radio and an antenna. Wireless network **102** could operate as a Mode II device according to FCC Memorandum Opinion and Order (FC-12-36) and related white space regulation documents. If module **101** supports IEEE 802.15.4, then wireless network **102** could be a Zigbee network, an ISA100.11a standards-based network, a 6LoWPAN network as described by IETF RFC 4944, or a client within the Thread protocol specification. Other possibilities exist as well for the wireless technology utilized by a wireless network **102** and module **101**, operating in a wireless mode, without departing from the scope of the present invention.

Module **101** can collect data regarding a monitored unit **119** and periodically report status to an M2M service provider **108** or a server **105**. Examples of a monitored unit **119** can include a vending machine, an alarm system, an automobile or truck, a standard 40-foot or 20-foot shipping container, or industrial equipment such as a transformer on an electrical grid or elevator in a building. Additional examples of a monitored unit **119** include can also include a pallet for shipping or receiving goods, an individual box of pharmaceuticals, a health monitoring device attached to a person such as a pacemaker or glucose monitor, and a gate or door for opening and closing. Other examples exist as well without departing from the scope of the present invention.

Module **101** can utilize a sensor to measure and collect data regarding a parameter of monitored unit **119** such as temperature, physical location potentially including geographical coordinates from a Global Positioning System (GPS) receiver, radiation, humidity, surrounding light levels, surrounding RF signals, weight, vibration and/or shock,

11

voltage, current, and/or similar measurements. If monitored unit 119 is a person or a health monitoring device associated with a person, then relevant health data could be recorded by module 101 in order to transmit to a M2M service provider 108, which could be associated with a health service such as a hospital, doctor's office, or a similar health service. Module 101 could also periodically record a picture, image, or video of or around monitored unit 119, using either visible or infrared light.

As illustrated in FIG. 1a, wireless network 102 may include a wireless network firewall 144 and M2M service provider 108 may include a server network firewall 124. These firewalls may be used to secure communication at the data link, network, transport, and/or application layers of communications using the Internet 107. Server network firewall 124 can (i) allow communication from a module 101 to a server 105 after module 101 has been properly authenticated using module identity 110, and (ii) deny communication with other nodes or hosts connected to network 107 that have not been authenticated. Wireless network firewall 144 can (i) allow communication from a server 105 to a module 101 after server 105 has been properly authenticated using server public key 114 or a server identity, and (ii) deny communication with other nodes or hosts connected to network 107 that have not been authenticated. Other possibilities exist as well for the operation of a firewall 144 and firewall 124 without departing from the scope of the present invention.

According to exemplary embodiments, module 101 can include a storage unit 109. Storage unit 109 can comprise either (i) a removable digital media card, or (ii) embedded storage operating within module 101 and electrically connected to a data bus within module 101. Storage unit 109 as a removable unit can comprise a removable device in order for data and files can be physically loaded or physically removed from a module 101. As contemplated herein, removable storage unit 109 can also be referred to as storage unit 109. Example form factors of removable storage unit 109 common in 2015 for M2M modules and portable computing devices include "secure digital" (SD) cards and also universal integrated circuit cards (UICC), also known as a Subscriber Mobile Identity (SIM) card. The UICC could also include an embedded universal integrated circuit card (eUICC). Example SD card form factors include a standard SD card (~32 mm×~24 mm), a mini SD card, and the micro SD card. Example UICC form factors include a mini-SIM (~25 mm×15 mm), a micro-SIM, and a nano-SIM. A removable storage unit could comprise other form-factors as well without departing from the scope of the present invention, such as device that connects through a universal serial bus (USB) port of module 101. Removable storage unit 109 can include flash memory in order to retain data and files when module 101 or removable storage unit 109 is not powered. Other possibilities for the non-volatile memory technology and physical interfaces for a storage unit 109 are possible as well without departing from the scope of the present invention.

According to exemplary embodiments, storage unit 109 may preferably record a module public key 172 in non-volatile memory such as flash memory. Module public key 172 can be associated with a module private key 173 (not shown). Module private key 173 can be recorded by a cryptographic unit 113 in a protected memory within storage unit 109 that is preferably and feasibly only accessible to the cryptographic unit 113. Keys 172 and 173 can be utilized by module 101 and cryptographic unit 113, respectively, in order to perform public key infrastructure operations such as

12

creating digital signatures, asymmetric ciphering, and also key derivation functions, as discussed below such as with FIG. 1d, FIG. 4a, and FIG. 4b. As contemplated herein, cryptographic unit 113 can internally generate, derive, or calculate the key pair comprising a module private key 173 and a module public key 172, where module private key 173 (i) is recorded or stored within storage unit 109 in a protected memory and (ii) may optionally not be received, loaded, shared, or transmitted with any entity outside module 101.

In exemplary embodiments, storage unit 109 can include a cryptographic unit 113, and cryptographic unit 113 can perform cryptographic operations using the PKI keys 172 and 173. Cryptographic unit 113 can be securely isolated from module 101 and other programs, software, or firmware operating on module 101, such that input to cryptographic unit 113 can be passed through storage unit 109 and output from cryptographic unit 113 can be passed through storage unit 109. Intermediate data, memory, and non-volatile storage utilized by cryptographic unit 113 to receive the input and process the output can remain separated and protected from software programs or firmware operating on module 101. Cryptographic unit 113 can record a cryptographic unit (CU) private key 112, which can be used with cryptographic operations and algorithms as described below such as with FIG. 1d. Cryptographic unit (CU) private key 112 can be associated with a cryptographic unit (CU) public key 111, where CU public key 111 is depicted in FIG. 1a as being recorded with a certificate authority 118.

As contemplated herein, both (i) public keys illustrated in FIG. 1a and subsequent figures, and (ii) digital signatures associated with public keys can optionally be freely transmitted and recorded across the various nodes such as a module 101, a module provider 122, and an M2M service provider network 108, so CU public key 111 could also be recorded by these other elements. In contrast, private keys such as CU private key 112 and module private key 173 may preferably not be communicated between nodes in FIG. 1a in order to enhance security. Exemplary embodiments discussed below provide methods and systems for the private keys to not be communicated between the elements in FIG. 1a. In exemplary embodiments, CU private key 112 is recorded in CU 113, and CU 113 operates within storage unit 109. Storage unit 109 containing CU 113 can be manually inserted or removed from module 101 in an exemplary embodiment.

Module 101 may also be associated with a module provider 122. Module provider 122 could be a manufacturer or distributor of module 101, or may also be the company that installs and services module 101 or associates module 101 with monitored unit 119. Module provider 122 can also operate or support a distribution channel in order to deliver module 101 to end users. Module provider 122 can receive storage unit 109 from a certificate authority 118 and manually load storage unit 109 into module 101. Or, module provider 122 could deliver module 101 and storage unit 109 separately to end users, and the end users could manually insert storage unit 109 in module 101. Module provider 122 could deliver module 101 to an end-user, where the end-user associates module 101 with monitored unit 119. An end-user could install storage unit 109 inside module 101, similar to end-users inserting SIM cards in mobile phones and SD cards in digital cameras. Module provider 122 can record a module public key 172 and a certificate 122a for module 101 with module identity 110 (where certificate 122a is illustrated below in FIG. 7a). Module public key 172 may be associated with a module public key identity 170 (illustrated

in FIG. 1a as recorded in certificate 122a by module provider 122), and module public key identity 170 could be an identifier of module public key 172 for embodiments where module 101 with module identity 110 uses different module public keys 172 over time.

Module 101 may utilize a plurality of module private keys 173 (not shown in FIG. 1a but shown in FIG. 1e and FIG. 3b) and module public keys 172 during the operation of a system 100 or the operational lifetime of module 101. Consequently an identifier of the module public key 172 can be helpful for various elements in FIG. 1a to keep track of the proper module public key 172 to utilize when communicating with module 101 at a given point in time. Module public key identity 170 can be used to select and/or identify the correct module public key 172. Module public key identity 170 could be a string or sequence number uniquely associated with each of a plurality of different module public keys 172 for a single module 101. In exemplary embodiments, module public key identity 170 can be globally unique for all modules 101 and all module public keys 172 in a system 100. Module public key identity 170 may preferably not be included in the string or number comprising module public key 172, but rather associated with the string or number comprising module public key 172, and in this case the two together (module public key identity 170 and the string or number for module public key 172) may be used to refer to module public key 172 as contemplated herein for some embodiments. In other words, when a node or element is referred to as using a module public key 172, the node or element can use module public key 172 in conjunction with a module public key identity 170 in order to ensure the proper module public key 172 is being utilized due to the possible nature of module public keys 172 changing over time.

The module public key 172 along with module identity 110 and module public key identity 170 can optionally be signed by a certificate authority 118 in order to confirm the identity of module 101. Module provider 122 may have its own provider public key 120 and provider private key 121. A module provider public key 120 can also be signed by a certificate authority 118 in order to confirm the identity of module provider 122. Module provider 122 may have its provider public key 120 signed by a certificate authority 118 and recorded in a certificate 122c (similar to exemplary certificates 122a and 122b illustrated in FIGS. 7a and 7b below, respectively). Module provider 122 could then also sign module public key 172 using module provider private key 121 and a signing step depicted in FIG. 4a below. In this manner, module provider 122 can also function as a certificate authority for module 101, where the “parent” certificate authority for certificates issued by module provider 122 can be certificate authority 118. Thus, in an exemplary embodiment, the validity of module public key 172 in a certificate issued for module 101 by module provider 122 could be verified with module provider 122 certificate 122c, and the public key 120 for module provider 122 in certificate 122c could be verified against certificate authority 118. Exemplary steps for verifying a signature are included in FIG. 4b below. Additional details for exemplary embodiments of utilizing public keys and certificates are depicted and described in figures below.

Public keys and private keys as contemplated in the present invention, including module public key 172, module private key 173 (not shown in FIG. 1a), CU public key 111, CU private key 112, and additional PKI keys described herein, may leverage established standards for Public Key Infrastructure (PKI). Certificates may be formatted accord-

ing to the X.509 series of standards, such as X.509 v3 certificates, and subsequent or future versions and these keys may be considered as a format for recording public keys. Public keys and identities can be recorded in X.509 certificates, as well as recorded in other locations such as a database associated with module provider 122, wireless network 102, certificate authority 118, or M2M service provider network 108. The keys can support standards such as the International Organization for Standardization (ISO) ISO/IEC 9594 series of standards (herein incorporated by reference) and the Internet Engineering Task Force (IETF) RFC 5280 titled “Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile” (herein incorporated by reference), including future updates to these standards.

Public keys and private keys as contemplated in the present invention, including module public key 172, module private key 173 (not shown in FIG. 1a), CU public key 111, CU private key 112, and additional PKI keys described herein, could be generated using standard software tools and libraries such as Openssl and libcrypt. Other, similar tools and algorithms can be utilized to generate public and private keys without departing from the scope of the present invention. Public and private keys as contemplated herein could be recorded in a file such as a *.pem file (Privacy-enhanced Electronic Mail), a file formatted according to Basic Encoding Rules (BER), Canonical Encoding Rules (CER), or Distinguished Encoding Rules (DER), or as text or binary files. Other formats for public and private keys may be utilized as well, including proprietary formats, without departing from the scope of the present invention. As contemplated herein, a key may also comprise either a public key or a private key. A public key as contemplated herein may also be considered a certificate or a public certificate. A private key as contemplated herein may also be considered a security key or a secret key.

Certificate authority 118 can include servers and processes in order to securely verify a module identity 110 and a module public key 172, including the support of a change in module public key 172 over time after the module 101 with module identity 110 has been deployed in the field. After the secure verification of a module identity 110 and a module public key 172, certificate authority 118 can issue a module certificate 122a, which is illustrated as recorded with a module provider 122 in FIG. 1a. In order to support the secure verification of the module public key 172 over time, the certificate authority 118 can utilize a cryptographic unit (CU) certificate 122b which can include a CU public key 111 and a CU identity 109e. An exemplary CU certificate 122b is depicted and described in connection with FIG. 7b below. In an exemplary embodiment, CU 113 records CU private key 112 in protected memory within storage unit 109 before distribution of the storage unit 109 to module provider 122. Subsequently, CA 118 can utilize CU private key 112 to authenticate or verify (i) a derived module public key 172 (shown in FIG. 2b below) or (ii) other data submitted by a module 101 with module identity 110 and cryptographic unit identity 109e. Other embodiments for the use and operation of CU private key 112, CU public key 111, certificate 122b, and certificate authority 118 are discussed below.

In exemplary embodiments, any of certificate authority 118, module provider 122, and wireless network 102 could operate a cryptographic unit (CU) configuration unit 104. Although these three elements are depicted as including a CU configuration unit 104, any could also optionally omit the CU configuration unit 104. CU configuration unit 104

could comprise a server or computer for configuring a storage unit **109** with CU **113** before distribution of storage unit **109** to an end user. Exemplary operation of a CU configuration unit is depicted and described in connection with FIG. **3a** and FIG. **3b**. Storage unit **109** could be inserted into CU configuration unit **104**, and CU configuration unit **104** could perform configuration steps on storage unit **109**, such as (i) loading firmware and data into an EEPROM within storage unit **109**, (ii) configuring memory in storage unit **109** to be sufficiently cryptographically secure, (iii) instructing CU **113** to generate PKI keys pairs, (iv) securely and authoritatively sending the public portion of the PKI keys to certificate authority **118** in order for CA **118** to process a certificate **122a** or **122b**, and (v) quality assurance and performance verification checks on the storage unit **109**.

CU configuration unit **104** can also provide a cryptographic audit mode **104a**, such that a complete record of relevant internal binary states used to generate a random number can be read when cryptographic audit mode **104** is activated. In this manner, the states could be used to verify internal processes used to generate a random number, thereby providing an “open book” for users and third parties as opposed to a closed “black box” common with noise generating systems based on thermal noise. As discussed above in the Description of Related Art, important market resistance against many embedded random number generation systems has been frequent use of “black box” technology in the embedded systems. This market and commercial concern can be addressed by support of a cryptographic audit mode **104a** in exemplary embodiments, also discussed in additional detail below in connection with FIG. **3a**. System **100**, CU configuration unit **104**, storage unit **109**, and CU **113** can take steps such that cryptographic audit mode **104** is not feasible (i) without inserting storage unit **109** into CU configuration unit **104**, and (ii) after storage unit **109** has been deployed with a module **101** for use by an end user.

Although a single module **101**, module provider **122**, wireless network **102**, certificate authority **118**, and M2M service provider network **108** are illustrated in FIG. **1a**, system **100** could comprise a plurality of each of these elements. Each of the elements could also be associated with a plurality of private keys and public keys. Module **101** could also record sensor data pertaining to a plurality of monitored units **119**. Module **101** could be mobile, such as physically attached to a truck or a pallet, and module **101** could connect to a series of different wireless networks **102** as module **101** moves geographically. The operation of a certificate authority **118** could be combined with any of module provider **122**, wireless network **102**, or M2M service provider network **108**. Other configurations combining or mixing the operation of various nodes or elements in FIG. **1a** are possible as well without departing from the scope of the present invention.

FIG. **1b**

FIG. **1b** is a graphical illustration of hardware, firmware, and software components for a module, including a storage unit, in accordance with exemplary embodiments. FIG. **1b** is illustrated to include many components that can be common within a module **101**, and module **101** may also operate in a wireless configuration in order to connect with a wireless network **102**. Module **101** may consist of multiple components in order to collect sensor data or control an actuator associated with a monitored unit **119**. In a wireless configuration, the physical interface **101a** of module **101** may support radio-frequency (RF) communications with networks including a wireless network **102** via standards such

as GSM, UMTS, mobile WiMax, CDMA, LTE, LTE Advanced, and/or other mobile-network technologies. In a wireless configuration, the physical interface **101a** may also provide connectivity to local networks such as 802.11 WLAN, Bluetooth, Zigbee, or an IEEE 802.15.4 network, among other possibilities. In a wireless configuration, module **101** could use a physical interface **101a** be connected with both a wireless WAN and wireless LAN simultaneously. In a wired configuration, the physical interface **101a** can provide connectivity to a wired network such as through an Ethernet connection or USB connection.

The physical interface **101a** can include associated hardware to provide connections to components such as radio-frequency (RF) chipsets, a power amplifier, an antenna, cable connectors, RF filters, etc. Device drivers **101g** can communicate with the physical interfaces **101a**, providing hardware access to higher-level functions on module **101**. Device drivers **101g** may also be embedded into hardware or combined with the physical interfaces. Device drivers **101g** can include a storage driver **101s**, which can be utilized by a module **101** and operating system **101h** in order to read and write data to storage unit **109**, including communicating with a cryptographic unit **113** within storage unit **109**. Additional details regarding the communication between module **101** and cryptographic unit **113** within storage unit **109** are described in additional figures below, including FIG. **2c**. Module **101** may preferably include an operating system **101h** to manage device drivers **101g** and hardware resources within module **101**. The operating systems described herein can also manage other resources such as memory and may support multiple software programs or software libraries operating on module **101**.

The operating system **101h** can include Internet protocol stacks such as a User Datagram Protocol (UDP) stack, Transmission Control Protocol (TCP) stack, a domain name system (DNS) stack, etc., and the operating system **101h** may include timers and schedulers for managing the access of software to hardware resources, including storage unit **109**. The operating system shown of **101h** can be appropriate for a low-power device with limited memory and CPU resources (compared to a server **105**). Example operating systems **101h** for a module **101** includes Linux, Android® from Google®, iOS from Apple®, Windows® Mobile, or Open AT® from Sierra Wireless®. Additional example operating systems **101h** for module **101** include eCos, uC/OS, LiteOs, Contiki, OpenWRT, Raspbian, and other possibilities exist as well without departing from the scope of the present invention.

A module program **101i** may be an application programmed in a language such as C, C++, Java, and/or Python, and could provide functionality to support M2M applications such as remote monitoring of sensors and remote activation of actuators. Module program **101i** could also be a software routine, subroutine, linked library, or software module, according to one preferred embodiment. As contemplated herein, a module program **101i** may be an application operating within a smartphone, such as an iPhone® or Android®-based smartphone, and in this case module **101** could comprise the smartphone. The application functioning as a module program **101i** could be downloaded from an “app store” associated with the smartphone. Module program **101i** can include data reporting steps **101x**, which can provide the functionality or CPU **101b** instructions for collecting sensor data, sending messages to server **105** or module provider **122**, and receiving responses from server **105**, as described in the present invention. Module program **101i** can also include the logic for connecting with a server

105, sending a module identity 110 to the server 105, receiving a challenge or nonce from server 105, and sending a digital signature for the challenge or nonce to the server, where the digital signature can be calculated in a cryptographic unit 113.

Many of the logical steps for operation of module 101 can be performed in software and hardware by various combinations of sensor 101f, actuator 101y, physical interface 101a, device driver 101g, operating system 101h, module program 101i, data reporting steps 101x, and storage unit 109. When module 101 is described herein as performing various actions such as acquiring an IP address, connecting to the wireless network, sending a module identity 110, receiving a challenge or nonce, sending a digital signature, monitoring a port, transmitting a packet, sending a message, receiving a response, or encrypting or signing data, specifying herein that module 101 performs an action can refer to software, hardware, and/or firmware operating within module 101 illustrated in FIG. 1b performing the action.

Note that module 101 may also optionally include user interface 101j which may include one or more devices for receiving inputs and/or one or more devices for conveying outputs. User interfaces are known in the art and generally are simple for modules such as a few LED lights or LCD display, and thus user interfaces are not described in detail here. User interface 101j could comprise a touch screen if module 101 operates as a smartphone or mobile phone. As illustrated in FIG. 1b, module 101 can optionally omit a user interface 101j, since no user input may be required for many M2M applications, although a user interface 101j could be included with module 101.

Module 101 may be a computing device that includes computer components for the purposes of collecting data from a sensor 101f or triggering an action by an actuator 101y. Module 101 may include a central processing unit (CPU) 101b, a random access memory (RAM) 101e, and a system bus 101d that couples various system components including the random access memory 101e to the processing unit 101b. The system bus 101d may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures including a data bus.

Module 101 may include a read-only memory (ROM) 101c which can contain a boot loader program. Although ROM 101c is illustrated as “read-only memory”, ROM 101c could comprise long-term memory storage chipsets or physical units that are designed primarily for writing once and reading many times, such as Electrically Erasable Programmable Read-Only Memory (EEPROM). As contemplated within the present invention, a read-only address could comprise an address within a read only memory such as a ROM 101c memory address or another hardware address for read-only operations accessible via bus 101d. Changing data recorded in a ROM 101c can require a technician have physical access to module 101, such as removing a cover or part of an enclosure, where the technician can subsequently connect equipment to a circuit board in module 101, including replacing ROM 101c. ROM 101c could also comprise a nonvolatile memory, such that data is stored within ROM 101c even if no electrical power is provided to ROM 101c. In exemplary embodiments, ROM 101c could be (i) optionally omitted and storage 109 used for nonvolatile memory within module 101, or (ii) included in a memory unit within CPU 101b (not shown).

Module 101 can include a storage unit 109, and storage unit 109 can be removable. Storage unit 109 is also depicted and described in connection with FIG. 1a above and addi-

tional details regarding storage unit 109 are depicted and described in connection with FIG. 1c and FIG. 1e below, as well as additional details for the operation of storage unit 109 in subsequent figures. An exemplary storage unit 109 form factor could comprise a standard SD card, a mini SD card, a micro SD card, a mini UICC, a micro UICC, or a nano UICC, and other possibilities exist as well without departing from the scope of the present invention. Storage unit 109 could also comprise a solid state hard drive with a suitable small form factor for operation with module 101. Storage unit 109 can include electrical contacts (such as external pins 109a depicted in FIG. 1c) which provide electrical connectivity to bus 101d.

Storage unit 109 can be inserted in a housing in module 101, such that storage unit 109 can be manually inserted into or manually removed from module 101 after module 101 is manufactured. The manual operation of insertion of storage unit 109 can be performed by entities such as module provider 122 or an end user of module 101. Storage unit 109 can include NAND or NOR flash memory in order to record data when module 101 is not powered, and other nonvolatile memory technologies can be used in a storage unit as well without departing from the scope of the present invention. Storage unit 109 can be separately manufactured from module 101 and accessed and loaded with data before insertion into module 101, when storage unit 109 includes support for operating as removable media. Storage unit 109 could also operate as an “embedded” unit, such that storage unit comprises an integrated circuit soldered to a circuit board in module 101, and in these embodiments storage unit 109 can be fixed and not removable.

In exemplary embodiments, storage unit 109 can include a cryptographic unit 113, and additional details regarding the components and operation of a cryptographic unit 113 are depicted and described in additional figures below, including FIG. 1c and FIG. 1e. The inclusion of cryptographic unit 113 and the operation of cryptographic unit 113 in storage unit 109 can add functionality for storage unit 109 that is not normally included in commercially available removable storage media in the market as of 2015, such as SD cards or UICC cards. Cryptographic unit (CU) 113 within storage unit 109 can include a processor, bus, and memory similar (but with less power and on a smaller scale) as the CPU 101b, bus 101d, and ROM 101c. CU 113 can perform cryptographic functions such as (i) internally deriving a private key such as module private key 173 in a cryptographically secure manner, (ii) recording the private key in a protected memory such that module 101 or external parties cannot feasibly or cost-effectively read the private key, and (ii) generating digital signatures using the module private key 173.

Although the exemplary environment described herein employs ROM 101c, RAM 101e, and storage unit 109, it should be appreciated by those skilled in the art that storage unit 109 could also comprise other types of computer readable media which can store data that is accessible by a module 101, such as memory cards, subscriber identity module (SIM) cards, local miniaturized hard disks, and the like, may also be used in the exemplary operating environment without departing from the scope of the invention. The memory and associated hardware illustrated in FIG. 1b provide nonvolatile storage of computer-executable instructions, data structures, program modules, module program 101i, and other data for computer or module 101. Note the module 101 may include a physical data connection at the physical interface 101a such as a miniaturized universal serial bus adapter, firewire, optical, or other another port and

the computer executable instructions such as module program **101i**, data reporting steps **101x**, operating system **101h**, or device driver **101g** can be initially loaded into memory such as ROM **101c** or storage unit **109** through the physical interface **101a** before module **101** is given to an end user, shipped by a manufacturer to a distribution channel, or installed by a technician. Further, module program **101i**, data reporting steps **101x**, operating system **101h**, or device driver **101g** can be separately loaded into storage unit **109** before or after distribution of module **101**, and then storage unit **109** can be inserted into module **101**.

A number of program modules may be stored in RAM **101e**, ROM **101c**, or storage unit **109**, including an operating system **101h**, device driver **101g**, an http client (not shown), a DNS client, and related software. Cryptographic unit **113** can record program modules as well, where the program modules in CU **113** may be focused on cryptographic operations and functions conducted within CU **113**. Program modules include routines, sub-routines, programs, objects, components, data structures, etc., which perform particular tasks or implement particular abstract data types. Aspects of the present invention may be implemented in the form of (i) a module program **101i** and/or data reporting steps **101x** which are executed by the module **101** working in conjunction with (ii) firmware on CU **113** (depicted as CU firmware **113x** in FIG. 1c) to authenticate module **101** with a server **105** using public key infrastructure. In exemplary embodiments, program modules for CU **113** in storage unit **109** can include cryptographic algorithms as depicted and described in connection with FIG. 1d below.

A user may enter commands and information into module **101** through an optional user interface **101j**, such as a keypad, keyboard (possibly miniaturized for a mobile phone form-factor), and a pointing device. Pointing devices may include a trackball, an electronic pen, or a touch screen. A user interface **101j** may also include a display (not shown) such as a module screen. A display may also be connected to system bus **101d** via an interface. The display can comprise any type of display devices such as a liquid crystal display (LCD), a plasma display, and an organic light-emitting diode (OLED) display. Module **101** may also include a camera (not shown) connected to or integrated with module **101** through a physical interface **101a**, and the camera can comprise a video camera for the module **101** to collect sensor data that includes video or images. The camera (not shown) can be a CCD (charge-coupled device) camera, a CMOS (complementary metal-oxide-semiconductor) camera, or a similar device to collect video input. Other arrangements could be used as well, without departing from the invention.

The module **101**, comprising a computer, may operate in a networked environment using logical connections to one or more remote computers, such as the server **105** illustrated in FIG. 1a. Server **105** can also function as a general purpose server to provide files, programs, disk storage, remote memory, and other resources to module **101** usually through a networked connection. Additional remote computers with which module **101** communicates may include another module **101** or mobile device, an M2M node within a capillary network, a personal computer, other servers, a client, a router, a network PC, a peer device, a wireless network **102**, or other common network node. The server **105** or a remote computer typically includes many of the elements described above relative to the module **101**, including a CPU, memory, and physical interfaces. It will be appreciated that the network connections shown throughout the present invention are exemplary and other means of establishing a wire-

less or wired communications link may be used between mobile devices, computers, servers, corresponding nodes, and similar computers. The operation of a cryptographic unit **113** within a storage unit **109** can be utilized to authenticate a module **101** in each or any of the above described networking environments.

The module program **101i** and data reporting steps **101x** operating within module **101** illustrated in FIG. 1b can provide computer executable instructions to hardware such as CPU **101b** through a system bus **101d** in order for a module **101** to (i) transmit and receive data with a module provider **122**, (ii) monitor a sensor and/or change the state of an actuator **101y**, (iii) send or receive packets with a server **105**, and (iv) authenticate with a server **105** or M2M service provider network **108**, thus allowing server **105** to remotely monitor or control a monitored unit **119** in an authenticated and secure manner. The module program **101i** and/or data reporting steps **101x** can enable the module **101** to authenticate and communicate with a server **105** by recording data in memory such as RAM **101e**, where the data can include sensor data, a destination IP address number such as the exemplary IP address number **106** in FIG. 1a, a packet or packet header value, an encryption or ciphering algorithm and key, a digital signature and public key, etc. The data recorded in RAM **101e** can be subsequently read by the operating system **101h** or the device driver **101g**. The operating system **101h** or the device driver **101g** can write the data to a physical interface **101a** using a system bus **101d** in order to use a physical interface **101a** to send data such as a digital signature for authentication to a server **105** using the Internet **107**. Alternatively, the module program **101i** and/or data reporting steps **101x** can write the data directly to the physical interface **101a** using the system bus **101d**.

In general, digital signatures for authentication with a server **105** can be performed in CU **113**, where the digital signature output is transferred from CU **113** to RAM **101e** before being transmitted from module **101** to server **105** through the IP network **107**. The data recorded in RAM **101e** such as a digital signature can be subsequently read by the operating system **101h** or the device driver **101g**. The operating system **101h** or the device driver **101g** can write the data to a physical interface **101a** using a system bus **101d** in order to use a physical interface **101a** to send data such as a digital signature for authentication to a server **105** using the Internet **107**. Alternatively, the module program **101i** and/or data reporting steps **101x** can write the data directly to the physical interface **101a** using the system bus **101d**. Other possibilities exist as well without departing from the scope of the present invention.

The module program **101i** and/or data reporting steps **101x**, or operating system **101h** can include steps to process the data recorded in memory such as encrypting data, selecting a destination address, or encoding sensor data acquired by (i) a sensor **101f** or (ii) through a physical interface **101a** such as a thermocouple, shock or vibration sensor, light sensor, or global positioning system (GPS) receiver, etc. The module **101** can use the physical interface **101a** such as a radio to transmit or send (i) the data from a sensor or (ii) a digital signature from CU **113** to a wireless network **102**. For those skilled in the art, other steps are possible as well for a module program **101i** or operating system **101h** to collect data from either (i) a sensor **101f** or (ii) a CU **113** and send the data in a packet without departing from the scope of the present invention.

Conversely, in order for module **101** to receive a packet or response from server **105**, which could include a challenge or nonce in order to authenticate a module **101** with a

21

server **105**, the physical interface **101a** can use a radio to receive the challenge or nonce from a wireless network **102**. The challenge or nonce received from the server **105** through the wireless network **102** could comprise a random number or a pseudo random string of digits, bits, and/or characters. The received data can include information from a server **105** and may also comprise a datagram, a source IP address number, a packet or header value, an instruction for module **101**, an acknowledgement to a packet that module **101** sent, a digital signature, and/or encrypted data. The operating system **101h** or device driver **101g** can use a system bus **101d** and CPU **101b** to record the received data such as a challenge or nonce from server **105** in memory such as RAM **101e**, and the module program **101i** or operating system **101h** may access the memory in order to process the received data and determine the next step for the module **101** after receiving the data. Processing the received data could include deciphering or decrypting received data with a key, sending the challenge or nonce to the CU **113**, reading an instruction from a server **105**, or similar transformations of the received data. The steps within this paragraph may also describe the steps a module program **101i** or data reporting steps **101x** can perform in order to receive a packet. For those skilled in the art, other steps are possible as well for a module program **101i**, data reporting steps **101x**, or module **101** to receive a packet or challenge or nonce from a server **105** without departing from the scope of the present invention.

Moreover, those skilled in the art will appreciate that the present invention may be implemented in other computer system configurations, including hand-held devices, notebooks, portable computers, multiprocessor systems, microprocessor based or programmable consumer electronics, network personal computers, minicomputers, mainframe computers, servers, and the like. The invention may also be practiced in distributed computing environments, where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both local and remote memory storage devices. In addition, the terms “mobile node”, “mobile station”, “mobile device”, “M2M module”, “M2M device”, “networked sensor”, or “industrial controller” can be used to refer to module **101** as contemplated herein.

In exemplary embodiments, a module **101** can include the functional capabilities of (i) collecting sensor data regarding a monitored unit **119**, (ii) changing state of an actuator **101y** associated with monitored unit **119**, (iii) communicating the data associated with a monitored unit **119** with a wireless network **102**, and/or receiving a challenge or nonce from a server **105** and sending a digital signature. The function of module **101** and cryptographic unit **113** could also be integrated (such as depicted and described in connection with FIG. **5** below), and in this case module **101** could also be referred to as a “sensor”, “intelligent sensor”, or “networked sensor”. The device driver **101i**, operating system **101i**, and/or module program **101i** could optionally be combined into an integrated system for providing the module **101** functionality. Other possibilities exist as well for the configuration or combination of components illustrated in FIG. **1b** without departing from the scope of the present invention.

FIG. **1c**

FIG. **1c** is a graphical illustration of hardware, firmware, and software components for a module and a storage unit, in accordance with exemplary embodiments. The illustrated exemplary components for a module **101** in FIG. **1c** can

22

include a module identity **110**, a random number generator **128**, a clock **160**, a battery **101k**, a radio **101z**, and RAM **101e**. The random number generator **128** in module **101** can include a random number generator seed **128b**. The RAM **101e** can include data recorded in module **101** for the operation of module **101** when collecting data regarding monitored unit **119** and communicating with server **105**. RAM **101e** can include a server public key **114**, cryptographic algorithms **141**, the module identity **110**, a certificate for module **101** using module identity **110**, and a symmetric key **127**. Note that both module **101** and CU **113** can record cryptographic algorithms **141**, and in exemplary embodiments module **101** can use a first set of cryptographic algorithms **141** in RAM **101e** for symmetric ciphering of data with a server **105** using a symmetric key **127**, while CU **113** can use a different, second set of cryptographic algorithms **141** within CU **113** for processing digital signatures and asymmetric ciphering using private keys such as key **112** and key **173**.

As depicted in FIG. **1c**, module identity **110** can be recorded both within a nonvolatile physical location in module **101** and also within RAM **101e** concurrently. Certificate **122a** for module **101** with module identity **110** can include a module public key **172** and a digital signature **125** from certificate authority **118**. Module **101** can send certificate **122a** to a server **105** for authentication with server **105**, such that server **105** can use the public key **172** to verify a digital signature (i) sent from module **101**, and (ii) processed by CU **113**. Symmetric key **127** can include an expiration time **133**, such that symmetric key **127** can be identified as expired by module **101** when expiration time **133** has transpired. Although not depicted in FIG. **1c**, certificate **122a** can also include an expiration time **133**, such as depicted for a certificate **122a** in FIG. **7a** below.

The illustrated components for a storage unit **109** in FIG. **1c** can include external pins **109e**, an interface driver **109b**, an interface controller **109c**, a memory core interface **109m**, a cryptographic unit **113**, a cryptographic unit only accessible memory **109g**, and non-volatile memory **109i**. The external pins **109e** of storage unit **109** can provide an electrical interface for storage unit **109** to connect with bus **101d** of module **101**, such that a CPU **101b** of module **101** can communicate with the internal elements of storage unit **109**, using storage driver **101s**. The external pins **109a** can include pads or electrical contacts for electrical input into storage unit **109** and such as a power voltage, electrical ground, a clock input, and data lines to communicate binary data. The external pins **109a** can support electrical output from storage unit **109** as well.

In an exemplary embodiment, the external pins of storage unit **109** could support a serial peripheral interface (SPI) bus mode with a micro SD card, such that pin **6** would be ground, pin **4** would be power, pin **3** would be serial data in, pin **7** would be serial data out, pin **5** would be a clock signal, etc. Other possibilities exist as well for the possible pin layouts and bus supported by the external pins **109e** of an SD card, such as a one-bit SD bus mode or a four-bit SD bus mode. If storage unit **109** comprises a UICC, then the PIN layout of external pins **109a** could comply with 3GPP standards and the interface, such as standard 3GPP TS 31.102. In another embodiment, external pins **109e** can support either (i) a parallel bus such as a member of the Peripheral Component Interconnect (PCI) standards or a Peripheral Component Interconnect Express (PCIe) standards, or (ii) other serial interfaces such as a universal serial bus (USB).

Interface driver **109b** within storage unit **109** can provide the firmware to support the selected physical bus type and communications protocol for the external pins **109a**. The interface driver **109b** can provide functionality similar to device driver **101g** in FIG. **1b**. For example, interface driver **109b** could support one-bit or four-bit SD bus mode for data transfer between the interface controller **109c** and CPU **101b** in module **101**, and other possibilities exist as well. Interface controller **109c** can comprise a processor similar to CPU **101b**, but embedded into the storage unit **109** and consequently typically with less resources than a CPU **101b**, such as (i) less cache memory, (ii) operating typically at a slower speed, (iii) fewer internal registers, (iv) lower power consumption due to reduced thermal dissipation for a storage unit **109** compared to module **101**, etc. Interface controller **109c** can also manage and sequence the flow of data between non-volatile memory **109i** and the external pins **109a**, among other functions such as receiving updated cryptographic unit firmware **113x** through external pins **109a**.

As of 2015, and for the foreseeable future, large capacity removable storage media, such as SD cards with a gigabyte of memory or more, can include non-volatile memory such as non-volatile memory **109j**. Properly managing reading and writing to the non-volatile memory **101j** can require relatively computationally intensive operations to be performed inside the removable storage media such as the SD card. These operations performed by interface controller **109c** include (i) error correcting codes to reduce or eliminate bit errors in nonvolatile memory **101j**, (ii) leveling write wearing in order to spread the number of data writes as uniformly as possible across the physical memory **109j**, (iii) registers and tables to keep track of memory, block and page addresses in order to perform operations such as reads and writes to a memory core interface **109m**, etc.

These operations can be relatively computationally intensive for a small form factor storage unit such as a micro SD card and can comprise thousands of machine code instructions for a single operation of (i) selecting a page of physical memory within a block of memory, (ii) reading the selected page of physical memory, (iii) error correcting the data read and also write the error corrections back to the physical memory, and (iv) transferring the data through electrical pins **109a**. The above exemplary operations be performed by a processor or multiple processors embedded in the storage unit **109** in the form of interface controller **109c**. Exemplary microcontrollers embedded in the SD card include modified versions of an 8051 processor or an ARM® processor, such as an exemplary processor that is a member of the ARM® 7 family of processors, and other possibilities exist as well without departing from the scope of the present invention.

Storage unit **109** can also include a memory core interface **109m**, where memory core interface **109m** provides controller **109c** and/or cryptographic unit **113** access to physical memory such as non-volatile memory **101j** and/or noise collecting memory **113a**. Controller **109c** and/or cryptographic unit **113** can read data from physical memory by writing an address of a memory page and/or block to memory core interface **109m**, and memory core interface **109m** returns the data from the page. Similarly, controller **109c** and/or cryptographic unit **113** can write data from physical memory by writing an address of a memory block and/or page to memory core interface **109m** plus the data to be recorded in physical memory, and memory core interface **109m** can subsequently write the data to physical memory at the block and page address specified. Other possibilities exist as well for the use of a memory core interface **109m** without departing from the scope of the present invention. In

exemplary embodiments, individual cells within a page can be addressed by a memory core interface **109m** as well, and other possibilities for the structure and naming conventions of memory are possible without departing from the scope of the present invention.

Storage unit **109** can include a cryptographic unit **113**, where cryptographic unit **113** can perform cryptographic operations for storage unit **109**. Cryptographic unit **113** can include cryptographic unit identity **109e**, a shared secret symmetric key **127**, cryptographic parameters **126**, cryptographic algorithms **141**, a private key **112**, a certificate authority public key **131**, random access memory **113e**, a CPU **113b**, and ROM **113c**. The cryptographic unit identifier **109e** can comprise a globally unique identifier for cryptographic unit **113**, such that nodes communicating with module **101** using storage unit **109** with cryptographic unit **113** can properly identify cryptographic unit **113** using the cryptographic unit (CU) identifier (ID) **109e**. Cryptographic unit identity **109e** can also be referred to as CU ID **109e**. CU ID **109e** can be a string or a number, such as a hexadecimal number with sufficient length such as an exemplary 8 bytes of data for the CU ID **109e**, although other possibilities exist as well without departing from the scope of the present invention.

CU ID **109e** can be used outside of CU **113** in a cryptographic unit certificate **122b** such as, but not limited to, cryptographic unit certificate **122b** depicted and described in connection with FIG. **7b** below. CU ID **109e** can be read from read only memory (ROM **113c**) in CU **113** or via a data bus within CU **113** such as bus **113d** depicted and described in connection with FIG. **1e** below. In exemplary embodiments, CU ID **109e** can be recorded in storage unit **109** either (i) upon manufacturing of storage unit **109**, or (ii) before distribution of storage unit **109** such that CU ID **109e** cannot be subsequently changed or altered after CU ID **109e** is recorded in storage unit **109**. Other possibilities exist as well for the format, recording location, and use of a cryptographic unit identity **109e** without departing from the scope of the present invention.

Secret symmetric key **127** within cryptographic unit **113** can be a secret key for use with symmetric ciphering algorithms as described in FIG. **1d** below. In exemplary embodiments, secret symmetric key **127** can be uniquely associated with cryptographic unit **113** using CU ID **109e** and can also be loaded in storage unit **109** either (i) upon manufacturing of storage unit **109**, or (ii) before distribution of storage unit **109** such that symmetric key **127** cannot be subsequently changed or altered after symmetric key **127** is recorded in storage unit **109**. A CU **113** can record multiple secret symmetric keys **127**, such (A) that a first key **127** remains permanently recorded in CU **113** before installation of CU **113** with a module **101**, while (B) subsequent keys **127** could be recorded in CU **113** after distribution of storage unit **109**. In other words, these subsequent symmetric keys **127** could be changed or altered after the first symmetric key **127** was written before distribution of storage unit **109**.

Symmetric key **127** could comprise a pseudo random number or random number of sufficient length such as an exemplary 128 or 256 bits, such that output of a symmetric ciphering algorithm such as the Advanced Encryption Standard (AES) could not feasibly be decrypted without the use of symmetric key **127**. Among many possible uses for symmetric key **127** in the present invention, symmetric key **127** could be utilized to decrypt cryptographic unit firmware **113x**, where symmetric key **127** was used to encrypt the cryptographic unit firmware **113x** before cryptographic unit firmware **113x** was loaded into storage unit **109**. In this

manner, cryptographic unit firmware **113x** can be resistant to reading or tampering by end users or other external parties other than the manufacturer of cryptographic unit **113** or authorized parties who also have symmetric key **127**.

Cryptographic algorithms **141** within cryptographic unit **113** in storage unit **109** are depicted and described in connection with FIG. **1d** below. Private key **112** in cryptographic unit **113** depicted in FIG. **1c** can also be referred to as cryptographic unit (CU) private key **112**. CU private key **112** can be the private key associated with CU public key **111**. CU private key **112** can be a key of sufficient length and format for use with either (i) RSA algorithms and cryptography or (ii) Elliptic Curve Cryptography (ECC) as described in FIG. **1d** below. Other cryptographic algorithms for CU private key **112** could be utilized by a cryptographic unit **113** as well. CU private key **112** can be either (i) loaded in storage unit **109** or (ii) internally derived within storage unit **109** using the steps depicted and described in connection with FIG. **3a** below.

For embodiments where CU private key **112** is loaded into storage unit **109**, the step of loading the CU private key **112** can take place either (i) upon manufacturing of storage unit **109**, or (ii) before distribution of storage unit **109**, such that private key **112** cannot be subsequently changed or altered after private key **112** is recorded in storage unit **109**. In addition, CU **113** can operate in a manner such that private key **112** cannot be transferred out of storage unit **109** or either directly or indirectly read by module **101**. CU **113** can (i) accept input via electrical pins **109a** and a bus **113d** described below in FIG. **1e**, and (ii) send output, where the output is processed using the private key **112**, but the private key **112** remains private and would be infeasible (or equivalently not cost effective) to obtain using the output CU **113** sends through electrical pins **109a**.

Cryptographic unit **113** in storage unit **109** depicted in FIG. **1c** can also include a certificate authority public key **131**. Although not illustrated in FIG. **1c**, certificate authority public key **131** can be recorded in a certificate authority certificate **133** (depicted in FIG. **1a**), where certificate authority certificate **133** can be similar to (i) the certificate for a module **101** in certificate **122a** illustrated in FIG. **7a** or (ii) certificate for a cryptographic unit **113** in certificate **122b** illustrated in FIG. **7b**. Certificate authority public key **131** can be recorded internally in CU **113** in a suitable file format such as a *.pem file or text file, and other possibilities exist as well without departing from the scope of the present invention. Certificate authority public key **131** can be useful for CU **113** to verify digital signatures for data received by storage unit **109** from a certificate authority **118**, such as a digital signature **125** for a module public key **173** (shown in FIG. **1e** below). Although not illustrated in FIG. **1c**, CU **113** could also include module provider public key **120**, and module provider **122** could load module provider public key **120** into CU **113** after module provider **122** receives storage unit **109** and before module provider **122** distributes module **101**. Module provider **122** could use a CU configuration unit **104** to load a module provider public key **120** in storage unit **109**.

The exemplary data elements for a CU **113** in FIG. **1c** such as CU private key **112**, certificate authority public key **131**, cryptographic parameters **126**, module provider public key **120**, can be recorded by CU **113** in a RAM **131e** memory while CU **113** is powered via the electrical pins **109a**, and these exemplary data elements could also be recorded in CU only accessible memory **109g**, such that when power is removed from CU **113**, CU **113** continues to record the data and the data is readily available for CU **113**

operations when power is restored. CU only accessible memory **109g** can comprise a portion of the non-volatile memory **109j** separated either logically or physically from general memory **109i** for module **101** by a memory controller **109k**. Although CU only accessible memory **109g** is illustrated as residing within a separate portion of non-volatile memory **109j** in FIG. **1c**, CU only accessible memory **109g** could alternatively be integrated within CU **113** and omitted from non-volatile memory **109j** in order to enhance security and further protect memory **109g** from access by elements external to storage unit **109**. In the case where CU only accessible memory **109g** operates within CU **113**, then memory controller **109k** could also operate within CU **113**, and other possibilities exist as well without departing from the scope of the present invention.

Although illustrated as a separate unit from interface controller **109c** in FIG. **1c**, in exemplary embodiments, cryptographic unit **113** could also be optionally combined with interface controller **109c**, such as depicted in FIG. **1e** below in exemplary embodiments. In other words, a single physical processor similar to CPU **101b** could perform the function of interface controller **109c** and CU **113**. Combining exemplary elements and operation of interface controller **109c** and CU **113** can be referred to as a processor or a storage unit processor. A single physical processor for both controller **109c** and CU **113** could be a processor belonging to the exemplary MIPS®, ARM®, or Intel® family of processors, and other possibilities exist as well. Cryptographic unit **113** could comprise also a trusted execution environment (TEE) or similar secured environment within the single, integrated physical processor. Or, CU **113** and controller **109c** could comprise separate physical processors or components within storage unit **109**.

Data utilized by cryptographic unit **113** may logically or physically separately from controller **109c** and interface driver **109b** through the use a memory controller **109k**. Memory controller **109k** can provide physical or logical isolation of CU **113** and cryptographic only accessible memory **109g** such that module **101** could not read or write to CU only accessible memory **109g**. As one example, the physical memory in storage unit **109** comprising non-volatile memory **109j** could have a portion of the physical addresses reserved for reading and writing by CU **113** only, such as an exemplary top 50 blocks of non-volatile memory **109j**. Memory controller **109k** could intentionally disallow the transfer of data from or to non-volatile memory **109j** to interface controller **109c** or other elements except CU **113**, where the block address is in the exemplary top 50 blocks. Memory controller **109k** could also operate on a lower level than a block address for non-volatile memory **109j** as well, such as only allowing CU **113** or processor **113b** (shown below in FIG. **1e**) to allow a specified range of pages within non-volatile memory **109j**, where the specified range of pages could belong to CU only accessible memory **109g**. In this manner, memory controller **109k** could operate as a firewall to restrict access to CU only accessible memory **109g**. Other possibilities exist as well for the operation of a memory controller **109k** in order to isolate and separate CU only accessible memory **109g** such that interface controller **109c** cannot utilize physical memory addresses for recording and reading data utilized in a CU only accessible memory **109g**.

In another embodiment, memory controller **109k** could perform hardware-based encryption/decryption using a symmetric key **127** to encrypt and decrypt data transferred between CU **113** and CU only accessible memory **109g**. In an exemplary embodiment, CU only accessible memory

109g can be formatted with a file system with a separate partition from the memory that module 101 accesses within memory 109f. A file system on CU only accessible memory 109g could be encrypted using a symmetric ciphering algorithm 141b discussed below and a symmetric key 127 recorded by CU 113, such that even if CU only accessible memory 109g could be accessed by module 101, no useful data could be extracted or tampered with. Although memory controller 109k is depicted in FIG. 1c as a separate element from memory core interface 109m, memory controller 109k could also be optionally integrated with memory core interface 109m, and other possibilities exist as well for the operation and location of a memory controller 109k for ciphering data or restricting access to data recorded in storage unit 109 for CU 113, without departing from the scope of the present invention.

Storage unit 109 can include non-volatile memory 109j. Non-volatile memory 109j can comprise a physical memory of NAND or NOR flash memory, such that data recorded in non-volatile memory 109j continues to be recorded when electrical power is removed from storage unit 109. The data within non-volatile memory 109j can subsequently be read and/or re-written when power is restored to storage unit 109. As of 2015, typical exemplary values for the amount of memory available non-volatile memory 109j for SD cards can range from 512 megabytes to 64 gigabytes, and other possibilities exist as well. Non-volatile memory 109j can include occasional bit errors due to the nature of the physical memory, such as small cell 230 sizes (where an exemplary cell 230 is depicted in FIG. 2a below), but error correcting codes operating in interface controller 109c can normally correct the errors, such as limiting errors in a file read by module 101 from non-volatile memory 109j to less than one part per billion during the normal, operating lifetime of storage unit 109. As contemplated herein, error correcting codes can comprise either (i) convolution codes operating on a bit by bit basis on memory or data from memory, such as a Viterbi decoder, or (ii) block codes, such as a Hamming codes or Reed-Solomon codes. Other possibilities for the physical structure of non-volatile memory 109j and error correcting codes exist as well without departing from the scope of the present invention, and generally (i) non-volatile memory 109j includes addresses and blocks, such that binary data can be recorded and subsequently read, and (ii) error correcting codes attempt to identify and correct the presence of bit errors in either physical memory and/or data read from the physical memory.

Non-volatile memory 109j in storage unit 109 can include module and CU accessible memory 109f and CU only accessible memory 109g. The two types of memory can be identified by separate addresses within the physical memory comprising non-volatile memory 109j, or similarly different sectors assigned by a file system written to the physical memory. In an exemplary embodiment the two types of memory 109f and 109g can be segmented logically, where memory 109g is encrypted with a symmetric key 127 within CU 113 by a memory controller 109k. Module and CU accessible memory 109f can include shared memory 109h, module general memory 109i, and cryptographic unit firmware 109x. Module general memory 109i can comprise memory that module 101 can access in non-volatile memory 109j such as recording firmware for module 101 or other long-term and non-volatile storage of data or files for module 101. In exemplary embodiments, operating system 101h for module 101 can be recorded in module general memory 109i. Module and CU accessible memory 109f can record a file system for both module 101 and CU 113 to

access, such as exemplary file systems of FAT16, FAT 32, NTFS, ext3, ext4, UDF, and other file systems for memory 109f and memory 109j are possible as well without departing from the scope of the present invention.

Shared memory 109h in nonvolatile memory 109j can include memory accessible by both a module 101 and CU 113, such as a portion of a file system recorded in memory 109j. Exemplary use of module and CU shared memory 109h is depicted and described in connection with FIG. 2c below. In exemplary embodiments, both module 101 and CU 113 can both read and write to module and CU shared memory 109h, which can also be referenced herein as shared memory 109h. As illustrated in FIG. 1c, shared memory 109h can be a subset of module and CU accessible memory 109f, and module and CU accessible memory 109f can also include general memory 109i for module 101. In exemplary embodiments, the CU 113 may have access to general memory 101i, such as a location for collecting additional noise or information entropy for input into a random number generator 128 for CU 113 as depicted in FIG. 1e below. In other words, CU 113 may read data from general memory 101i, but in an exemplary embodiment (i) CU 113 does not write to general memory 101i and (ii) CU 113 does write to shared memory 109h. Other possibilities for the configuration of a non-volatile memory are possible as well, such that storage unit 109 can provide nonvolatile memory (i) dedicated to module 101, (ii) dedicated to CU 113, and (iii) shared between module 101 and CU 113, without departing from the scope of the present invention.

Storage unit 109 can also include a noise collecting memory 113a, which can be included within the CU only accessible memory 109g discussed above. Noise amplifying memory 113a can utilize NAND or NOR memory in a configuration such that the memory is designed and manufactured to intentionally collect a higher level of bit errors over time compared to non-volatile memory 109j. Noise amplifying memory 113a can be identified separately from non-volatile memory 109j by a significantly higher bit error rate or frequency of recorded bit errors for noise amplifying memory 113a compared to non-volatile memory 109j. In an exemplary embodiment, noise amplifying memory 113a can have a bit error rate greater than an order of magnitude higher than non-volatile memory 109j, typically after operation of several minutes or longer with relatively intensive read/writes to the noise amplifying memory 113a. Further, noise amplifying memory 113a can be operated separately from non-volatile memory 109j, where the use of error correction codes on noise amplification memory 113a are intentionally omitted, while error correction codes are used on non-volatile memory 109j. Although different operations on noise amplifying memory 113a, such as programming or recording data, may concentrate errors in a particular set of memory cells, the collection of bit errors within noise amplifying memory 113a can be on a relatively random basis over time for large sample of bits or cells, such as a sample of 10,000 bits.

In a noise amplifying memory 113a, random errors in memory cells or recorded bits can be intentionally induced by operations from CU 113. The operations by CU 113 to intentionally induce errors can include (i) programming disturbances, where the voltage stress in cells not being programmed are elevated (such as memory cells nearby the cells being programmed), and (ii) read disturbances, where cells not being programmed are exposed to elevated voltage stress (such as memory cells nearby the cells being read). Note that noise amplifying memory 113a can also include some aspects of non-volatile memory 109j, such as memory

that does not essentially completely reset when power is removed, such as with RAM memory. In other words, with a noise amplifying memory **113a**, a majority or significant majority of the memory cells can retain their state or data (such as a logic level of “1” or a logic level of “0”) when power is removed from storage unit **109**.

As illustrated in FIG. 1c, module **101** may also contain a random number generator **128**. Random number generator **128** may contain a seed **128b**. The creation of random numbers with a high degree of entropy may be important the use of cryptographic algorithms **141**. A plurality of the data as a source for a random number seed **128b** could be appended together into a “module random seed file” **139** (depicted in FIG. 1d below) with a combined series or list of module states (i.e. a plurality of sensor **101f** measurements, radio **101z** measurements, clock **160** times or values, memory **101e** or memory **101w** states, operating system **101h** states, actuator **101y** states, and/or hardware **101a** or **101d** states). Note that values or data for each of the elements listed in the previous sentence could be utilized in a “module random seed file” **139** instead of or in addition to a state. In exemplary embodiments, random number generator **128** can include a secure hash algorithm **141b** (discussed in FIG. 1d below) operating on random number seed **128b**, where the output is a seemingly random number for an observer who does not know the random number seed **128b**. Other possibilities exist as well for the operation of a random number generator **128** without departing from the scope of the present invention.

FIG. 1d

FIG. 1d is a graphical illustration of the components in a set of cryptographic algorithms, in accordance with exemplary embodiments. As contemplated herein, a cryptographic unit **113** in a storage unit **109** can utilize a set of cryptographic algorithms **141** in order to support the secure communication between a module **101** and other nodes, such as a server **105**, a wireless network **102**, or module provider **122**. The cryptographic algorithms **141** used by cryptographic unit **113** or module **101**, can comprise a set of steps, procedures, or software routines for accomplishing tasks for ciphering, deciphering, signing, and verifying messages, including the generation of public keys, private keys, and derived shared keys. The generation of random numbers may also be required for cryptographic operations including private key generation, creating nonce or challenge values, and also creating digital signatures, such as an R-value in the elliptic curve digital signature algorithm (ECDSA). Cryptographic algorithms **141** can be implemented in software or firmware operating on (i) module **101** in the form of a module program **101i**, or (ii) cryptographic unit **113**. Example software or routines for a cryptographic algorithms **141** includes the libraries within the openssl, libmccrypt, and/or and Crypto++ open source libraries, and proprietary implementations are available as well.

In addition, cryptographic algorithms **141** may be implemented in hardware or firmware on any of module **101** or cryptographic unit **113**. Other nodes in FIG. 1a could implement cryptographic algorithms as well, such as a server **105**, CA **118**, module provider **122**, and wireless network **102**. Note that module **101**, cryptographic unit **113**, and server **105** could each utilize a different set of cryptographic algorithms **141**, although the sets of algorithms should preferably be fully interoperable (i.e. ciphering with a first symmetric ciphering algorithm **141b** and a symmetric key **127** on cryptographic unit **113** could be deciphered by a second symmetric ciphering algorithm **141b** on server **105** using the same symmetric key **127**, etc.). As illustrated in

FIG. 1d, cryptographic algorithms **141** may comprise an asymmetric ciphering algorithm **141a**, a symmetric ciphering algorithm **141b**, a secure hash algorithm **141c**, a digital signature algorithm **141d**, a key pair generation algorithm **141e**, a key derivation function **141f**, and a random number generator **128**.

Asymmetric ciphering algorithms **141a** can comprise algorithms utilizing public key infrastructure (PKI) techniques for both (i) encrypting with a public key and (ii) decrypting with a private key. Example algorithms within asymmetric algorithms **141a** include the RSA algorithms **153** and the Elliptic Curve Cryptography (ECC) algorithms **154**, and other asymmetric algorithms could be utilized as well. For example, either ECC algorithms **154** or RSA algorithms **153** can be used for encryption and decryption. A set of parameters **126** can include input into asymmetric ciphering algorithms **141a**, such as specifying key lengths, elliptic curves to utilize (if ECC), modulus (if RSA) or other parameters or settings required. As contemplated herein and described in additional detail below, the algorithms illustrated in FIG. 1d can perform both ciphering and deciphering, using the appropriate keys.

The use and application of RSA algorithms and cryptography are described within IETF RFC 3447 titled “Public-Key Cryptography Standards (PKCS) #1: RSA Cryptography Specifications Version 2.1”, herein incorporated by reference, among other published standards for the use of RSA algorithms **153**. The use of an RSA algorithm **153** for encryption and decryption, including with cryptographic algorithm and other description of encryption or decryption algorithms, can also be processed according to the description of the RSA algorithm according to the Wikipedia entry for “RSA (algorithm)” as of Sep. 9, 2013, which is incorporated by reference herein.

The use and application of ECC algorithms **154** for asymmetric ciphering algorithms **141a** within cryptographic algorithms **141** are described within IETF RFC 6090 titled “Fundamental Elliptic Curve Cryptography Algorithms” (herein incorporated by reference), among other published standards using ECC. ECC algorithms **154** can also utilize elliptic curve cryptography algorithms to the Wikipedia entry for “Elliptic curve cryptography” as of Sep. 9, 2013, which is incorporated by reference herein. ECC algorithms **154** may utilized according to exemplary preferred embodiments in order to maintain high security with smaller key lengths, compared to RSA, thereby helping to comparably reduce the message lengths, radio frequency spectrum utilization, and processing power required by CU **113**. Thus, the use of ECC algorithms **154** within various steps requiring ciphering or digital signatures may help conserve battery life of module **101** operating a CU **113** while maintaining the objective of securing system **100**. Note that as contemplated herein, other algorithms besides with ECC algorithms **154** and RSA algorithms **153** may be also be used in asymmetric algorithms **141a**.

Cryptographic algorithms **141** may also include a set of symmetric ciphering algorithms **141b**. Symmetric ciphering algorithms **141b** can utilize a symmetric key **127** by one node such as a module **101** with cryptographic unit **113** to encrypt or cipher data, and the encrypted data can be decrypted or deciphered by server **105** also using the symmetric key **127**. A server **105** could also encrypt data using a symmetric key **127** and the data could be decrypted by module **101** or CU **113** using the symmetric key. Or, cryptographic unit firmware **113x** could be ciphered with a symmetric key **127** by a module provider **122** or CA **118** and CU **113** could decrypt CU firmware **113x** using the sym-

metric key. Examples of symmetric ciphers include Advanced Encryption Standard 155 (AES), as specified in Federal Information Processing Standards (FIPS) Publication 197, and Triple Data Encryption Standard (Triple DES), as described in NIST Special Publication 800-67 Revision 1, “Recommendation for the Triple Data Encryption Algorithm (TDEA) Block Cipher (Revised January 2012)”.

Parameters **126** input into symmetric ciphering algorithms **141b** can include symmetric key **127** length, such as the selection of 128, 192, or 256 bits with AES 155 symmetric ciphering, and parameters **126** could also select a symmetric ciphering algorithm in a collections of symmetric ciphering algorithms **141b**. Other examples of symmetric ciphering algorithms **141b** may be utilized as well within cryptographic algorithms **141**. Also note that as contemplated herein, the term “symmetric ciphering” contemplates the use of a symmetric ciphering algorithm **141b** in order to encrypt or cipher data with a symmetric ciphering algorithm **141b**, and “asymmetric ciphering” contemplated the use of an asymmetric ciphering algorithm **141a** to encrypt or cipher data with a public key, such as module public key **172** or server public key **114**.

Cryptographic algorithms **141** may also include a set of secure hash algorithms **141c** in order to compute and output a secure hash value or number based on a string or file input into the secure hash algorithms **141c**. Example secure hash algorithms include SHA256 156 (also known as SHA-2) and SHA-3 157. SHA256 156 is specified in the National Institute of Standards and Technology (NIST) Federal Information Processing Standards Publication (FIPS PUB) 180-2 titled “Secure Hash Standard”. SHA-3 157 is specified in FIPS PUB 180-4. Parameters **126** input into secure hash algorithms **141c** can include the selection of the length of the secure hash, such as either 224, 256, or 512 bits with either SHA-2 or SHA-3, and other possibilities exist as well.

Cryptographic algorithms **141** may also include a set of digital signature algorithms **141d**, in order to sign and verify messages by a cryptographic unit **113**, module **101**, server **105**, wireless network **102**, module provider **122**, or certificate authority **118**. Digital signature algorithms **141d** can also verify signatures such as comparing that (i) a first secure hash value received in the form of a digital signature in a certificate (such as signature **125** in certificate **122a**) using a certificate authority private key **132** matches (ii) a second secure hash value independently calculated using the same input and CA public key **131**. Digital signature algorithms **141d** can utilize algorithms in National Institute of Standards (NIST) “FIPS 186-4: Digital Signature Standard”, or IETF RFC 6979 titled “Deterministic Usage of the Digital Signature Algorithm (DSA) and Elliptic Curve Digital Signature Algorithm (ECDSA)”. The use of ECDSA algorithm **158** within a set of digital signature algorithms **141d** may be preferred if keys such as cryptographic unit public key **111** and certificate authority public key **131** are based on elliptic curve cryptography. An exemplary embodiment of (i) using a private key to for generating digital signatures is depicted and described in connection with FIG. **4a** below and (ii) using a public key to verify digital signatures is depicted and described in connection with FIG. **4b** below.

Other PKI standards or proprietary techniques for securely verifying digital signatures may be utilized as well in digital signature algorithms **141d**. Parameters **126** input into digital signature algorithms **141d** can include the selection of a secure hash algorithms **141c** to utilize with digital signature algorithms **141d**, or the algorithm to utilize, such as ECDSA shown in FIG. **7a** or an RSA-based alternative for digital signatures is possible as well. Parameters input

into digital signature algorithms **141d** can also include (i) a padding scheme for use in a digital signature algorithm **141d**, or (ii) the selection of either deterministic usage of DSA or ECDSA such as specified in IETF RFC 6979 or the use of a random R value in the signature algorithm. Digital signature algorithms **141d** could also include an RSA digital signature algorithm for use with RSA-based public and private keys.

Cryptographic algorithms **141** may also include key pair generation algorithms **141e**, a key derivation function **141f**, and a random number generator **128**. Key pair generation algorithms **141e** can be utilized by cryptographic unit **113** to securely generate private and public keys. The key pair generation algorithms **141e** can also use input from a parameters **126**, such as the desired key lengths, or an ECC curve if the public key will support ECC algorithms **154**. According to an exemplary preferred embodiment, cryptographic unit **113** can derive a pair of module public key **173** and module private key **172** using key pair generation algorithms **141e** and the input from a random number generator **128**. Software tools such as openssl and libcrypt include libraries for the generation key pairs, and these and similar libraries can be used in a key pair generation algorithm **141e**.

Key derivation function **141f** can be used by module **101**, server **105**, certificate authority **118**, wireless network **102**, and/or module provider **122** in order to determine a common derived shared secret key **129**, using at least two respective public keys as input, and may also include the input of a private key. A key exchange to share a common symmetric key **127** (comprising a derived shared secret key **129**) can be performed using a key derivation function **141f** and parameters **126**. An exemplary algorithm within a key derivation function **141f** can be the Diffie-Hellman key exchange, which is used by tools such as secure socket layer (SSL) with RSA algorithms **153**. When using ECC algorithms **154**, module **101** and server **105** can utilize Elliptic Curve Diffie-Hellman (ECDH) algorithms **159**, and a summary of ECDH is included in the Wikipedia article titled “Elliptic Curve Diffie-Hellman” from Sep. 24, 2013, which is herein incorporated by reference.

Other algorithms to derive a shared secret key **129b** using public keys and a private key may also be utilized in a key derivation function **141f**, such as the American National Standards Institute (ANSI) standard X-9.63 160. Parameters **126** used with key derivation function **141f** with elliptic curve cryptography can include a common base point G for two nodes using the key derivation function **141f** and public keys. The base point G in a parameters **126** can be transmitted or sent from a module **101** to a server **105** in a message transmitted over network **107**, and the base point G can be sent from a server **105** to a module **101** in a response transmitted over network **107**, and other possibilities exist as well. Parameters **126** can also include other or additional information for using a key derivation function **141f** in order to derive a commonly shared symmetric key **127**.

Parameters **126** input into key pair generation algorithms **141e** can include the type of asymmetric ciphering algorithms **141a** used with the keys, the key length in bits, an elliptic curve utilized for ECC, a time-to-live for a public key that is derived, and similar settings. Additional parameters **126** for a public key can include a supported point formats extension, where the supported point formats extension could comprise uncompressed, compressed prime, or “compressed char2” formats, as specified in ANSI X-9.62. In other words, an ECC public key can have several formats and a set of parameters **126** can be useful to specify the

format. Although a set of parameters **126** is illustrated in FIG. **1d** as internal to cryptographic algorithms **141**, parameters **126** could be recorded in other locations in a cryptographic unit **113**, storage **109**, and/or module **101**. As one example, parameters **126** could be recorded in a server **105** and downloaded by module **101** using the Internet **107** and subsequently written to CU **113**. The various algorithms within cryptographic algorithms **141** may utilize a random number generator **128**, which is also depicted and described in connection with FIG. **1c** above and FIG. **1e** below.

According to a preferred exemplary embodiment, parameters **126** can include values to define an elliptic curve and/or use ECC algorithms **154**. The values could be constants or variables in a defining equation for an elliptic curve, or the parameters could simply name an existing, defined curve such as the standard named curve. Parameters **126** could include a set of ECC parameters **137** for using elliptic curve cryptography in ECC algorithms **154**, where the ECC parameters **137** can include the ECC parameters in section 3.3 of IETF RFC 6090, including: (i) a prime number p that indicates the order of a field F_p , (ii) a value “ a ” used in a curve equation, (iii) a value “ b ” used in the curve equation, (iii) a generator “ g ” of the subgroup, and (iv) an order “ n ” of the subgroup generated by “ g ”. Further, the ECC parameters **137** could include values used for elliptic curve cryptography as specified in IETF RFC 5639 titled “Elliptic Curve Cryptography (ECC) Brainpool Standard Curves and Curve Generation”, section 3: (i) a “ p ” value for the prime specifying the base field, (ii) “ A ” and “ B ” are coefficients for an equation such as $y^2 = x^3 + Ax + B \pmod p$ defining the elliptic curve, (iii) “ G ” = (x, y) as the base point, i.e., a point in E of prime order, (iv) “ q ” as the prime order of the group generated by G , and (v) “ h ” as the cofactor of G in E , i.e., $\#E(GF(p))/q$. Other possibilities exist as well for an ECC parameters **137** that can be used in a cryptographic algorithms. Parameters **126** could also include an ECC standard curve **138**, which could comprise a name and/or values for a standardized curve, such as the list of named curves included in section 5.1.1 of IETF RFC 4492 titled “Elliptic Curve Cryptography (ECC) Cipher Suites for Transport Layer Security (TLS).”

As contemplated herein, a set of cryptographic algorithms **141** may operate using either strings or numbers, and parameters **126** could include either strings or numbers as well. The processing of cryptographic algorithms within a cryptographic unit **113** can take place within a CPU **113b**, or module **101** could also process cryptographic algorithms **141** in a processor **101b**. Embodiments of the present invention contemplate that cryptographic algorithms **141** operating in cryptographic unit **113** perform select functions when communicating with a server **105**, such as calculating a digital signature using a private key, and other functions when communicating with a server **105** can be performed by CPU **101b** in module **101**, such as ciphering data transmitted between module **101** and server **105**.

FIG. **1e**

FIG. **1e** is a graphical illustration of components within a storage unit, in accordance with exemplary embodiments. FIG. **1e** depicts additional details for a cryptographic unit **113** and storage unit **109** illustrated in FIG. **1c**. Storage unit **109** can include module and CU accessible memory **109f**, CU only accessible memory **109g**, cryptographic unit **113**, noise amplifying memory **113a**, memory core interface **109m**, memory controller **109k**, noise memory interface **109p**, and data bus **109d**, and an internal bus **109q**. Cryptographic unit (CU) **113** can include a processor **113b**, RAM **113e**, a clock **160b**, a random number generator **128**, a

sensor **113f**, an interface controller **109c**, and EEPROM **113c**. Although not illustrated in FIG. **1e**, CU identity **109e** could also be written into hardware within CU **113**, such as at a physical address connected to bus **109d** or within processor **113b**, such that CU identity **109e** can be read from storage unit **109** regardless of a configuration or data recorded in EEPROM **113c**.

EEPROM **113c** could also comprise a read only memory, where the data in EEPROM **113c** is written once upon manufacturing of storage unit **109**. EEPROM **113c** could also function as a read only memory for CU **113** similar to ROM **101c** for module **101** above. In other words EEPROM **113c** does not need to be erasable and reprogrammable, although some data in EEPROM **113c** could be re-written in exemplary embodiments. Although interface controller **109c** is depicted inside CU **113** in FIG. **1e**, CU **113** could also comprise a logical or physical component in interface controller **109c**. Or, the function of interface controller **109c** and CU **113** could be combined, and for example interface controller **109c** and CU **113** could share a common processor **113b**. The components in CU **113** can be connected to data bus **109d** in order to transfer data between the various components in CU **113** and storage unit **109**.

The processor **113b** in CU **113** can function similar to processor **101b** for module **101** as described in connection with FIG. **1b** above, with a form factor, speed, and computational capacity suitable for CU **113**. Processor **113b** in CU **113** could be a processor belonging to the exemplary MIPS®, ARM®, or Intel® family of processors, and other possibilities exist as well. Processor **113b** can include components such as registers, accumulators, and logic elements to add, subtract, multiply, and divide numerical values, and processor **113b** can be connected to data bus **109d**. The timing of processor **113b** and data bus **109d** can be driven by a clock **160b**. Processor **113b** can provide the hardware for CU **113** to perform calculations for cryptographic algorithms **141** in addition to the general operation of

CU **113** and managing communication between CU **113** and module **101** through electrical pins **109a**. Processor **113b** could also be connected to internal bus **109q**.

Upon startup or powering of CU **113** and storage unit **109**, processor **113b** could load and operate on instructions provided by CU **113** boot firmware **181** from EEPROM **113c**. CU **113** boot firmware **181** and CU firmware **113x** can provide instructions to processor **113b** in the format of machine executable code. The instructions in CU **113** boot firmware can provide instructions for processor and CU **113** to initialize and subsequently load CU firmware **113x**. Processor **113b** for CU **113** can access noise amplifying memory **113a** through internal bus **109q** and noise memory interface **109p**. Internal bus **109q** is depicted in FIG. **1e** as connected to CU **113**, and CU **113** can include processor **113b**. In this manner and through this connection between processor **113b** and CU **113**, processor **113b** can read data from and write data to noise amplifying memory **113a** and CU only accessible memory **109g**.

Random access memory **113e** in CU **113** can function similar to RAM **101e** for module **101**, with a form factor, speed, and storage capacity suitable for CU **113**. RAM **113e** can be connected to data bus **109d** in storage unit **109**, and can store data for processor **113b** in a volatile state, such that data recorded in RAM **113e** can be essentially flushed or reset when electrical power to storage unit **109** and CU **113** is removed. Random access memory **113e** can store data such as tables of memory addresses and sectors for memory **109g** and memory **109f**, since these tables are ordinarily larger than the registers provided by CPU **113b**. Clock **160b** can

comprise an oscillator outputting a sine or CMOS signal at several megahertz or higher. Clock **160b** can be synchronized or operating at a multiple or fraction of clock **160** for module **101**. Clock **160b** can also be driven by a clock input pin on electrical pins **109a**, and clock **160b** can include 5 phased loop logic (PLL) to convert the frequency from a clock input pin on electrical pins **109a** from module **101** to a clock rate or frequency suitable for CU **113**. Clock **160b** can also drive internal bus **109q**, such that CU **113** can access noise amplifying memory **113a** using the timing and clock cycles generated by clock **160b**.

CU **113** can also include an embedded sensor **113f**. Sensor **113f** could comprise a sensor similar to sensor **101f** for module **101**, with a difference that sensor **113f** can be sufficiently small to be enclosed by the housing for storage unit **109** along with the other components illustrated in FIG. **1e**. In exemplary embodiments the analog output of sensor **113f** can be converted to digital form by processor **113b** and utilized as input, along with other data, into a random number seed **128b** within random number generator **128** in CU **113**. Sensor **113f** could collect analog data, such as temperature, pressure, thermal noise in silicon within CU **113**, or other environmental variables, with a sufficient number of significant digits, such that the trailing digits could comprise an effective noise value.

In exemplary embodiments, processor **113b** could include analog to digital inputs of sufficient width, such as an exemplary 16 bits, where an exemplary least significant 6 bits of data from the converted analog input into processor **113b** can essentially comprise a “noise” value **197** (depicted in FIG. **2b** below) since sensor **113f** may not provide resolution or accuracy of more than an exemplary 10 bits, although other possibilities exist as well to acquire noise from a sensor **113f**. Multiple samples of the least significant bits of data from sensor **113f** could be added together over 25 time in order to generate a number of adequate length for a noise value **197**. Although a single sensor **113** is depicted in FIG. **1e**, CU **113** or storage unit **109** could include multiple sensors **113f**. Random number generator **128** with random number seed **128b** in CU **113** can provide equivalent functionality as random number generator **128** depicted and described in connection with FIG. **1c** above.

Noise memory interface **109p** can be connected to internal bus **109q** within storage unit **109**, providing CU **113** and processor **113b** access to noise amplification memory **113a**, such as read and write operations. Noise memory interface **109p** can operate differently than memory core interface **109m** or memory controller **109k**, where noise memory interface **109p** can support read and write operations to noise amplification memory **113a**. Noise memory interface **109p** can operate in a manner to assist, enhance, or amplify the generation of memory noise **194** (depicted in Figure if below) or bit errors in noise amplification memory **113a**. In an exemplary embodiment, the memory cells within noise amplification memory **113a** can be manufactured with 55 memory cells that are functionally equivalent to memory cells in non-volatile memory **109j**. For reference, memory cells in non-volatile memory **109j** can also include general memory **109i** in storage unit **109** for module **101**, where bit errors are preferably minimized.

In exemplary embodiments, whereas memory core interface **109m** can operate within specifications to read and write data to non-volatile memory **109j** to minimize bit errors or memory noise **194**, noise memory interface **109p** can intentionally operate outside the specifications of 65 memory core interface **109m**. In an exemplary embodiment, a routine write operation of memory core interface **109m** on

non-volatile memory **109j** can introduce on the order of 1×10^{-4} bit errors or less before error correction operations to rectify errors, while a similar routine write operation of noise memory interface **109p** on noise amplification memory **113a** can introduce on the order of 1×10^{-3} bit errors or more, including possibly a level of 1×10^{-2} or higher bit errors per operation. In addition, the use of a noise amplification memory **113a** preferably omits error correction code operations in order to aggregate bit errors over time. Other possibilities exist as well for the value of bit error introduced by a noise memory interface **109p** and memory core interface **109m** without departing from the scope of the present invention.

In exemplary embodiments, noise memory interface **109p** can apply voltages to memory cells in noise amplification memory that are higher than or lower than the specified voltages for memory core interface **109m**. In an exemplary embodiment, memory core interface **109m** could be specified to access a page of memory cells in non-volatile memory **109j** by applying 5 volts pulses in order to change selected memory cells from a value of “1” to a value of “0”. Continuing with this exemplary embodiment, noise memory interface **109p** can apply a voltage pulse of 4 volts instead of 5 volts when changing the equivalent memory cells from a value of “1” to a value of “0” in noise amplification memory **113a**. Whereas memory core interface **109m** operating at 5 volts pulses would effectively change the memory state of all or essentially all selected memory cells in non-volatile memory **109j** (such that resulting bit errors are below a manufacturer specified threshold), noise memory interface **109p** using the lower voltage pulses of 4 volts may change only a portion of the selected memory cells from a value of “1” to a value of “0”, thereby introducing noise or random bit errors into noise amplification memory **113a** (such that resulting bit errors are above the manufacturer specified threshold for a memory core interface **109m**).

In this manner, in exemplary embodiments the voltage used by a noise memory interface **109p** when operating on a noise amplifying memory **113a** can be different or less than the voltage used by a memory core interface **109m** when operating on nonvolatile memory **101j**. In addition, noise memory interface **109p** would not conduct or pass error correction code operations in order to rectify bit errors resulting from read and write operations in a noise amplifying memory **113a**. The above voltages of 5 volts for **109m** and 4 volts for **109p** are exemplary, and other voltages or similar differences in voltage values may be suitable for different types of flash NAND, NOR, or similar non-volatile memory technologies, without departing from the scope of the present invention.

Further, noise memory interface **109p** can operate outside specifications of memory core interface **109m** using parameters other than voltages in pluses to set bits or collection of bits, or a combination of other parameters with voltages. In an exemplary embodiment, memory core interface **109m** could be specified to access a page of memory cells in non-volatile memory **109j** by applying voltage pulses with duration 1 microsecond ± 0.2 microseconds in order to change selected memory cells from a value of “1” to a value of “0”. Continuing with this exemplary embodiment, noise memory interface **109p** can apply a voltage pulses with duration of 0.7 microseconds ± 0.3 microseconds when changing the equivalent memory cells from a value of “1” to a value of “0” in noise amplification memory **113a**. Whereas memory core interface **109m** operating at 1 microsecond pulses would effectively change the memory state of all or essentially all selected memory cells in non-volatile memory

109j, noise memory interface 109p using the shorter voltage pulses of 0.7 microseconds may change only a portion of the selected memory cells from a value of “1” to a value of “0”, thereby introducing noise or random bit errors into noise amplification memory 113a.

In this manner, in exemplary embodiments the duration of voltage pulses used by a noise memory interface 109p when operating on a noise amplifying memory 113a can be different or less than the duration of voltage pulses used by a memory core interface 109m when operating on nonvolatile memory 101j. The above values of voltage pulses of 1 microsecond for 109 m and 0.7 microseconds for 109p are exemplary, and other pulse durations or and related values may be suitable for different types of flash NAND, NOR, or similar non-volatile memory technologies, without departing from the scope of the present invention. In exemplary embodiments, the rise time, fall time, or hold time for applying voltages and voltage pulses in order to set or program memory cells in a noise amplifying memory 113a can be different or lower than nonvolatile memory 101j.

Further, as flash memory such as NAND and related mass storage technologies continue to evolve to support different configurations and higher densities, including multi-bit cells, a noise memory interface 109p could be specified to operate with parameters outside the specified or normal operating range of memory core interface 109m in a manner that (i) introduces noise or bit errors into noise amplification memory 113a, while (ii) continuing to minimize permanent damage to memory cells (such as an exemplary memory cell 240 illustrated in FIG. 2a below) or keep permanent damage to memory cells below a specified tolerance level. Noise memory interface 109p can support read operations to noise amplifying memory 113a by processor 113b similar to read operations supported by memory core interface 109m, such that CU 113 can read the randomly or pseudo-randomly generated bit errors or memory noise 194 in noise amplifying memory 113a. In general, noise memory interface 109p can introduce noise or bit errors into noise amplification memory 113a most frequently through write operations that are out of specification as described above, although read operations could also introduce some or a lower level of bit errors over time.

As contemplated herein, a noise memory interface 109p can also be identified separately from a regular memory core interface 109m in exemplary embodiments due to a significantly reduced or eliminated number of error correction code operations performed on noise amplification memory 113a, after read and write functions of a noise memory interface 109p. In other words, memory core interface 109m can use a significantly higher number of error correction code operations to rectify bit errors recorded in a non-volatile memory 109j, but a noise memory interface 109p can use a significantly lower or no error correction code operations on noise amplification memory 109p.

In an exemplary embodiment, the same physical memory can be used for noise amplification memory 113a and non-volatile memory 109j (with a separate section of memory blocks from the physical memory assigned to noise amplification memory 113a), and noise memory interface 109p can function equivalently to memory core interface 109m with the exception that memory core interface 109m uses error correction code operations while noise memory interface 109p occasionally, frequently, or entirely omits the error correction code operations. Other possibilities exist as well for a noise memory interface 109p to introduce and

retain bit errors at a higher rate than memory core interface 109m without departing from the scope of the present invention.

EEPROM 113c in CU 113 can include a CU certificate 122b, CU boot firmware 181, CU boot configuration 183, certificate authority public key 131, certificate authority public key parameters 126b, a cryptographic unit private key 112, and a symmetric key 127. CU private key 112 and symmetric key 127 can be recorded in a protected memory 185 in EEPROM 113c, similar to CU only accessible memory 109g, such that (i) only CU 113 can read CU private key 112 using instructions in CU boot firmware 181 or CU firmware 113x, and (ii) CU private key 112 may not be read by module 101 or transferred out of storage unit 109 in exemplary embodiments. In exemplary embodiments, CU boot firmware 181 or CU firmware 113x can omit instructions that would allow CU private key 112 to be transferred to electrical pins 109a.

Data 186 within EEPROM 113c can comprise CU boot firmware 181, CU boot configuration 183, certificate authority public key 131, and certificate authority public key parameters 126b. Data 186 can be written to EEPROM 113c by a CU configuration unit 104. The data 186 in EEPROM 113c can be written into EEPROM 113c in storage unit 109 before storage unit 109 is distributed to a module provider 122, such as during a step 304 depicted and described in connection with FIG. 3a below. CU certificate 122b can be written to EEPROM 113c by a CU configuration unit 104 (i) after the generation of CU private key 173, and (ii) during a step 311 to load CU certificate 122b depicted and described in connection with FIG. 3a.

CU certificate 122b can include the CU identity 109e, CU public key 111, certificate parameters 126b, and a certificate authority digital signature 184. CU certificate 122b can be formatted according to the X.509 v3 specifications, among other possible formats, and stored as a plain text file, *.pem file, or *.crt file or similar file formats. CU certificate 122b can be used by CU 113 in order to (i) verify identity of CU 113 to module 101, or (iii) generate a digital signature for an internally generated or derived module public key 172. In exemplary embodiments, parameters 126b in CU certificate 122b can include an expiration time of CU certificate 122b longer than the expected operational lifetime of storage unit 109, and in this manner CU certificate 122b can remain valid whenever storage unit 109 is utilized. An exemplary expiration time of CU certificate 122b could be 20 years, although other possibilities exist as well.

CU boot firmware 181 in EEPROM 113c can provide machine executable code for processor 113b to initiate operations when electrical power is provided to CU 113 and storage unit 109 via the electrical pins 109a. Although not illustrated in FIG. 1e, processor 113b may also include a ROM memory with CPU 113b instructions for CPU 113b to fetch CU boot firmware 181 upon startup when power is provided to CPU 113b. CU boot firmware 181 can include a set of cryptographic algorithms 141, such as depicted and described in connection with FIG. 1d above, and memory control libraries 182. CU boot firmware 181 in EEPROM 113c could also include instructions for CU 113 to load CU firmware 113x recorded in non volatile memory 109j, if present, as depicted in FIG. 1e.

In exemplary embodiments, CU firmware 113x could be decrypted with a symmetric key 127 recorded in EEPROM 113c. Authorized providers of CU firmware 113x, such as CA 118 or module provider 122, could have access to symmetric key 127 for CU 113 with CU ID 109e, and consequently only the authorized providers could properly

encrypt CU firmware **113x** using the symmetric key **127**. CU firmware **113x** could be transmitted to a module **101** over network **107** in the encrypted format. In exemplary embodiments, a symmetric key **127** for CU **113** will be unique for each different storage unit **109**, and each symmetric key **127** can be uniquely associated with a CU ID **109e**. Symmetric key **127** within CU **113** can comprise a shared secret key. Symmetric key **127** in module **101** can comprise a different key for other purposes than decrypting CU firmware **113x**. In exemplary embodiments, CU firmware **113x** is not required for CU **113** to operate, and CU **113** could operate using CU boot firmware **181**, and CU firmware **113x** can be loaded into storage unit **109** for embodiments where the firmware for CU **113** is desired to be updated.

In this manner and in exemplary embodiments, the operating firmware for CU **113** could be updated after distribution of storage unit **109**, where CU boot firmware **181** can be loaded into EEPROM **113c** upon manufacturing of storage unit **109**, such as during a step **304** described below. For example, CU firmware **113x** depicted in FIG. **1e** could include a new set of cryptographic algorithms **141**, which could comprise an updated set of cryptographic algorithms **141** that were included in CU boot firmware **181**. An exemplary new set of cryptographic algorithms **141** different than an initial set of cryptographic algorithms **141** for CU **113** can be designated as a set of cryptographic algorithms **141'**, as depicted with firmware **113x** in FIG. **1e**. In this manner, the cryptographic algorithms used by CU **113** could be updated, such as supporting the use of longer key length, the addition of new or updated asymmetric ciphering algorithms **141a**, new or updated symmetric ciphering algorithms **141b**, new or updated secure hash algorithms **141c**, etc.

CU boot firmware **181** could use a symmetric ciphering algorithm **141b** and parameters **126** and the symmetric key **127** also recorded in EEPROM **113c** to decrypt CU firmware **113x**. A certificate authority **118** or module provider **122** could encrypt the CU firmware **113x** with the symmetric key **127** in EEPROM **113** in order to ensure that only authorized and approved CU **113x** firmware is loaded into CU **113**. If CU **113** cannot properly decrypt CU firmware **113x** loaded into non volatile memory **109j** by module **101**, then CU **113** could return an error or "unauthorized" code. Note that CU firmware **113x** is not required for the operation of CU **113**, and CU **113** can operate entirely based on CU boot firmware **181** in exemplary embodiments. The use of symmetric key **127** in EEPROM **113c** and CU firmware **113x** encrypted with symmetric key **127** can be required if firmware on CU **113** is to be updated after the installation of storage unit **109** in module **101**.

Memory control libraries **182** could include software or firmware to manage and schedule the operation of CU **113**, such as machine code for (i) instructing processor **113b** to write data to bus **109d** for memory controller **109k** when data is recorded in memory **109g**, (ii) read data from interface controller **109c** when data from module **101** is passed to CU **113**, and (iii) reading CU private key **112** from protected memory **109g** or protected memory **185** when cryptographic algorithms **141** for CU **113** need the private key **112** for operations such as performing a digital signature **141d**. For embodiments where interface controller **109c** and CU **113** are combined, memory control libraries **182** can include the software libraries and firmware for processor **113b** to manage all input and output of storage unit **109**. Other possibilities exist as well for memory control libraries **182** to support the operation of CU **113** and storage unit **109**

via program instructions provided to processor **113b** without departing from the scope of the present invention.

Memory control libraries **182** can also include CU read instructions **191a** and CU write instructions **191b**. CU read instructions **191a** can provide machine executable code for processor **113b** to read data from module **101** using shared memory **109h**. The data read from shared memory **109h** could be used with cryptographic algorithms **141** by CU **113**. In this manner, CU read instructions **191a** could provide the logical software or firmware interface for CU **113** to receive data from module **101**. CU read instructions **191a** could specify memory addresses or file locations in a file system for non-volatile memory **109j** where module **101** can write data in order to be read by CU **113**. In an exemplary embodiment, (i) module **101** could write a file with a name "digital_signature_input.txt" (such as digital signature input **204** in FIG. **2c** below) to a specified location in shared memory **109h**, such as the depicted memory **191** for CU read and module write operations in FIG. **2c** below, and then (ii) CU read instructions **191a** could instruct processor **113b** to read the data in **191** and subsequently use data **191** (which could comprise digital signature input **204**) for input into a digital signature algorithm **141d**. Other possibilities exist as well for a processor **113b** to read data input from module **101** into storage unit **109** without departing from the scope of the present invention.

CU write instructions **192a** can provide machine executable code for processor **113b** to write data output from processor **113b** to memory **109h** in order for module **101** subsequent read for data input into module **101**. In this manner, CU write instructions **192a** could provide the logical software or firmware interface for CU **113** to send data to module **101**, and other possibilities exist as well for the transfer of data from CU **113** to module **101** without departing from the scope of the present invention. CU write instructions **192a** could specify memory addresses or file locations in a file system for non-volatile memory **109j** where CU **113** using processor **113b** can write data in order to be read by module **101**. In an exemplary embodiment, (i) CU **113** could write a file with a name "digital_signature_output.txt" (such as digital signature output **210** in FIG. **2c** below) to a specified location in memory **109h**, such as the depicted memory **192** for CU **113** write and module read operations, and then (ii) module **101** could subsequently read the data in **192** in order to obtain the data in digital signature output **210**.

In this exemplary embodiment described in the previous two paragraphs, CU **113**, using CU read instructions **191a** and CU write instructions **191b**, can (i) read data from module **101** using shared memory **109h** and (ii) write data to memory **109h**, where module **101** can subsequently read data from memory **109h**. In another embodiment, CU write instructions **192a** could provide instructions for CU **113** to write data directly to RAM **101e** or processor **101b**, but in this case a closely coupled software and firmware interface between CU **113** and module **101** through electrical pins **109a** would be required. For example an SPI bus mode, a one-bit SD bus mode, or a four-bit SD bus mode for the interface through electrical pins **109a** would not normally be able to support CU **113** writing data directly to RAM **101e** or processor **101b**, so alternative bus technology connecting storage unit **109** and module **101** would be required for CU **113** to write data directly to RAM **101e** or processor **101b**.

EEPROM **113c** in CU **113** for storage unit **109** can also include a CU boot configuration **183**, a certificate authority public key **131**, certificate authority public key parameters **126b**, a cryptographic unit private key **112** and a symmetric

key 127. CU boot configuration 183 can provide values for the configuration or operation of CU 113 when operating with the CU boot firmware 181, such as specifying (i) the frequency to poll shared memory 109h for data input from module 101, (ii) the frequency to operate a clock 160b, (iii) a firmware version number, (iv) the memory capacity of noise collecting memory 113a, (v) the memory addresses, cells, or file sectors to utilize for shared memory 109h or noise collecting memory 113a, (vi) the processor 113b version number, and (vii) parameters specifying values for hardware within CU 113. Certificate authority (CA) public key 131 can be utilized by CU 113 to verify digital signatures received where the digital signature was generated and signed with a CU private key 132. CA public key parameters 126b can specify the parameters for using the CA public key 131, where parameters 126b can be a subset of the parameters 126 supported by cryptographic algorithms 141. Exemplary parameters 126b for a CA public key 131 can be similar or equivalent to parameters 126b for a CU public key 172 depicted and described in connection with FIG. 7b below, such as specifying a key length, digital signature algorithm 141d and secure hash algorithm 141c to utilize, etc. Note that parameters 126b for CA public key 131 and parameters 126b for CU public key 172 can be different.

Although a single CA public key 131, CU private key 112, symmetric key 127, and CU certificate 122b is depicted in FIG. 1e, an EEPROM 113c or storage unit 109 could record a plurality of each of these and associated elements. For example CU 113 could record two different private keys 112 in EEPROM 113c, where a first private key 112 is used with asymmetric ciphering algorithms 141a and a second private key 112 is used with digital signature algorithms 141d. Each of the first and second private keys could have a corresponding public key 111, and consequently two different CU certificates 122b (each with a different public key 111) could be recorded in an EEPROM 113c. CA public key 131 could also be used with asymmetric ciphering algorithms 141a, such that CU 113 could encrypt data using the CA public key 131 and CA 118 could subsequently decrypt the encrypted data using the CA private key 132.

Cryptographic unit only accessible memory 109g within nonvolatile memory 109j could be accessed by CU 113 via an internal bus 109q and memory controller 109k. As contemplated herein, Cryptographic unit only accessible memory 109g can also be referred to as protected memory 109g. Internal bus 109q and memory controller 109k can be utilized to physically or logically separate protected memory 109g from memory 109f and memory 109i in FIG. 1c, in order to prevent module 101 or external parties with physical access to storage unit 109 from reading the data or writing data in protected memory 109g. In other words and as illustrated in FIG. 1e, internal bus 109q can limit (A) the ability to read and write data to protected memory 109g and noise amplification memory 113a only to (B) CU 113 in exemplary embodiments. In contrast, access by module 101 to memory 109f could be accomplished through the separate data bus 109d and interface controller 109c.

In exemplary embodiments, interface controller 109c can provide the functionality to module 101 for storage unit 109 to operate as a standard removable flash memory storage unit via data bus 109d. Internal bus 109q and memory controller 109k can provide memory resources to CU 113 in a manner that prevents module 101 from accessing protected memory 109g and noise amplification memory 113a, including the description of memory controller 109k above. Internal bus 109q is not required in some exemplary embodiments, and memory controller 109k could be connected to

data bus 109d, but limit access to physical memory cells comprising memory 109g and 113a to processor 113b. Other possibilities for (i) limiting access to memory 109g and memory 113a, while (ii) supporting shared access to memory 109h are possible as well without departing from the scope of the present invention.

Crypto unit only accessible memory 109g in nonvolatile memory 109j can include data for the operation of CU 113. Crypto unit only accessible memory 109g can include data such as (i) an externally derived or loaded module private key 151, (ii) an internally derived module private key 173, (iii) CU firmware 113x including cryptographic algorithms 141', (iv) a symmetric key 127 for symmetric ciphering algorithms 141b used by module 101, and (v) a module provider public key 120. Crypto unit only accessible memory 109g could also record a table 188, which can record memory state and memory address information for use by CU 113, such as the use of table 188 depicted and described in connection with FIG. 3b below. Other data could be recorded in protected memory 109g as well, including an updated CU boot configuration 183, which could include parameters for the operation of CU 113 that are different than initially stored CU boot configuration 183 in EEPROM 113c.

In exemplary embodiments crypto unit only accessible memory 109g, or protected memory 109g, can be encrypted using a symmetric key 127 recorded in CU 113 as depicted in FIG. 1e. In this manner, module 101 or external parties cannot feasibly read data from this protected memory 109g without symmetric key 127, and consequently data within protected memory 109 can only be feasibly written and read by CU 113. Additional protection or isolation of protected memory 109g can be provided via memory controller 109k.

Many of the logical steps for operation of CU 113 and storage unit 109 can be performed in software and hardware by various combinations of processor 113b, firmware 113x or boot firmware 181, data bus 109d, interface driver 109b, and interface controller 109c. When CU 113 or storage unit 109 is described herein as performing various actions such reading a file, writing a file, verifying a digital signature, generating a private key, encrypting or decrypting data, specifying herein that CU 113 or storage unit 109 performs an action can refer to software, hardware, and/or firmware operating within module 101 illustrated in FIG. 1e performing the action.

FIG. 1f

FIG. 1f is a graphical illustration of the operation of a noise collecting memory over time, in accordance with exemplary embodiments. Noise amplifying memory 113a can comprise a plurality flash NAND or NOR memory cells, such as the exemplary noise amplification memory cell 240 depicted and described in connection with FIG. 2a below using NAND technology. Noise amplification memory 113a can be organized into blocks 195 and pages 199, such that a memory core interface 109m or a noise memory interface 109p can read data from and write data to the noise amplification memory 113a. The exemplary page size of 4 bits in FIG. 1f is for illustration purposes to highlight the potential organization of nonvolatile memory, and current commercial flash technology can have page sizes typically ranging from around 512 bytes to 16 KB or more, and block sizes may typically range from ~2 MB to ~16 MB or more. Other possibilities for page sizes and block sizes within a nonvolatile memory 101j or a noise amplification memory 113a are possible as well without departing from the scope of the present invention.

At an exemplary start point or time zero $t(0)$ for noise amplification memory **113a**, which could represent an initial state for noise amplification memory **113a**, the individual bits could be set to an initial state comprising a level “1”. Although not illustrated in FIG. 1f, some cells in the initial state could alternatively have a level “0”. After time $t(0)$ and before time $t(1)$ in FIG. 1f, the cells shown for page **2 199** can be written and then reset or erased, where the erasure operation intends to return the cell to the state of “1”. However, as illustrated in FIG. 1f, an individual cell within page **2 199** could retain an “error” comprising the cell remaining in the “0” state and not returning to the state of “1”, and this exemplary “error” or “bit error” could comprise a single instance of memory noise **104**.

Alternatively (and not shown in FIG. 10, all of the cells shown for page **2 199** could be intended to be written or set at a state of “0”, and in this alternative case the three cells in page **2 199** that retain a value of “1” could comprise “bit errors” or memory noise **194**. Thus, although memory noise **194** is depicted as a cell remaining in the “0” state when the cell is intended to be in the “1” state, the converse can also be true, such that memory noise **194** could occur when a cell records the level “1” when a write operation on the cell intends to change the cell to a level “0”. Between time $t(1)$ and time $t(2)$ in FIG. 1f, the cells in page **3** could also be written and then reset to the level “1”. However, at time $t(2)$ an additional exemplary bit error in noise amplification memory **113a** could occur, as depicted in FIG. 1f, comprising a second instance of memory noise **194**.

The cause of the exemplary bit errors with a relatively high level of frequency (at least compared to an expected or specified tolerance level of error frequency in nonvolatile memory **109j**) can be preferred in exemplary embodiments for a noise amplifying memory **113a**. The memory noise **194** can be enhanced or amplified for a noise amplifying memory **113a** by any or all of (i) the physical characteristics of noise amplification memory **113a** discussed below for a cell **240**, (ii) the operation of a noise memory controller **109p** discussed above in connection with FIG. 1e, (iii) the result of omitting the application of error correction codes on noise amplifying memory **113a**, and/or (iv) the combination of any or all of (i), (ii), and/or (iii). Note that the errors recorded in noise amplification memory **113a** also remain relatively non-volatile, such that individual cells have a sufficiently high probability of remaining in the set state over a period of time, including the time required to read a page **199** or series of memory cells **240**. In an exemplary embodiment, a series of cells with memory noise **194** or without memory noise **194** could have a 90% probability of retaining their state for a period of two years or longer. In this manner, a noise amplification memory **113** can retain and accumulate additional noise over time and the information entropy recorded can continue to increase. However, with tens of millions of cells or more typically included in a noise amplification memory **113a** and the stated exemplary specification for data retention in a noise amplifying memory **113a**, after a period of several months thousands of cells or more can be in an error or noise state due to the nature of cells gradually draining voltage over time.

Between time $t(2)$ and $t(3)$, CU **113** can also perform a noise-inducing operation **193**, which can further increase the probability of bit errors or memory noise **194** being recorded in noise amplification memory **113a**. The noise-inducing operation **193** could comprise multiple writes and erasures to the same cells, groups of cells, or nearby targeted cells where memory noise **194** or bit errors are desired to be generated. In exemplary embodiments, noise-inducing

operation **193** could be conducted without the traditional “wear leveling” common for an interface controller **109c** to utilize with commercial flash technology, and “wear leveling” attempts to minimize the number of bit errors with traditional nonvolatile memory **109j**. In other words, “wear leveling” can be omitted in the operation of noise amplifying memory **113a**. Note that noise-inducing operations **193** could be combined with the function of a memory controller **109p** described above in connection with FIG. 1e in order to enhance the level of memory noise **194** induced into noise amplifying memory **113a**. Other possibilities exist as well for a noise-inducing operation **193** on noise amplifying memory **113a**, such as programming pages within a block in a random manner, instead of a sequential manner (where a sequential manner is used to minimize errors) recommended by memory manufacturers.

After several iterations and time increasing to time (x) , a noise amplifying memory **113a** can record a significant level of individual instances of memory noise **194** and a high level of information entropy. As discussed above, another desirable source of bit errors that can accumulate over time for noise amplification memory **113** are data retention errors **190**, such that an intended bit stored in a quantitatively significant number of cells is naturally and gradually flipped due to the tendency of a voltage in a cell to drain slowly over time. Data retention errors **190** can also be enhanced by the manufacturing process and specification for a cell **240** in a noise amplification memory **113a** discussed below in FIG. 2a. The physical differences from manufacturing a cell **240** in a noise amplifying memory **113a** compared to a standard memory cell **230** can result in a higher level of desired data retention errors **190**. Data retention errors **190** have the desirable property for noise amplifying memory **113a** such at the information entropy or the random distribution of bit errors or memory noise **194** within memory **113a** can increase naturally and gradually over time, even for the instance where storage unit **109** is not powered. In exemplary embodiments, neither CU **113** nor storage unit **109** performs error correcting code operations upon noise amplification memory **113a** upon restoration of power after a period where power is removed to storage unit **109**, such that data retention errors can be retained in noise amplification memory **113a**.

As illustrated in FIG. 1f, a sample or all of memory **113a** can be input into a secure hash algorithm **141c** in order to calculate a noise amplifying memory hash value **198**. Hash value **198** can be useful to further increase the apparent information entropy from memory **113a**. In an exemplary embodiment, a single instance of memory noise **194** at time $t(1)$ completely changes the output of hash value **198** in a seemingly random way (at least when viewing only or comparing only the outputs of the secure hash algorithm **141**). Consequently, in preferred embodiments, data read from a noise amplifying memory **113a** can be input into a hash algorithm **141c**, where the resulting hash value **198** can be used in the generation of a private key **173**, a shared secret key **127**, a derived shared secret key **129b**, or a random number, such as a random number or value for the parameter R transmitted with digital signatures according to the ECDSA **158** algorithm. Although only a small sample of data is depicted in FIG. 1f, a sample of the data from memory **113a** input into secure hash algorithms **141c** for the generation of private keys or similar random values in exemplary embodiments can comprise selecting a sample of hundreds of thousands of bits or more from memory **113a** in order to calculate the hash value **198**, and other possibilities

exist as well for the size of a sample without departing from the scope of the present invention.

Note that if CU 113 uses a sample of memory 113a for input into a secure hash algorithm 141d, a data table 188 (depicted in FIG. 1e in protected memory 109g) may be useful in exemplary embodiments, such that CU 113 can track which sample of memory 113a has been utilized in a sequence, and a sample of memory 113a not reused for a period of time or next in a sequence in order for the count and distribution of errors to change from one sample of data in memory 113a to the next sample of data in memory 113a. In an exemplary embodiment, noise amplification memory 113a could comprise a gigabit or more of cells similar to cells 240 depicted and described in FIG. 2a below. A sample of memory 113a could comprise an exemplary 16 megabits of data. Embedded processor 113b could operate at 100 Mhz and hash approximately 2 MB/s, and consequently calculating the first hash value 198 could require less than a second. Table 188 could increment a pointer to memory 113a, such that the next time a second hash value 198 is required for cryptographic operations that require a random number, the next or a different 16 megabits of physical memory in memory 113a could be accessed to calculate the second hash value 198.

In this manner, CU 113 could support the generation of ~1000/16 hash values 198, or approximately 62, before table 188 rolls over to including data again from the initial 16 megabits of memory used for the first hash value. Table 188 could also include an estimate of time or cycles since the last time a block of 16 megabits was used, in order to confirm noise amplification memory 113a has recorded sufficient additional memory noise 104 to be cryptographically secure. Other possibilities exist as well for the size of a noise amplification memory 113b and the size of a sample for input into a hash algorithm 141d, including larger or smaller values for each, without departing from the scope of the present invention. Assuming even a low level of bit errors or memory noise 194 in noise amplification memory, such as an exemplary 1 part per thousand of bit errors, the number of permutations resulting from the example above, assuming a random distribution of could be $2^{16,000,000!} / 2^{1584000!}$, which can provide a sufficiently large number of permutations for the reasonably secure use of a cryptographic system.

Even for cases where the memory noise 194 is not randomly distributed, such as reducing the number of possible permutations by several orders of magnitude, or more, the number of permutations can be reasonably large. Since the number of possible permutations is so high, even a smaller sized sample or total pool of memory cells 240 in a noise amplification memory 113a can be suitable for the generation of random numbers, such as an exemplary megabit or less for noise amplification memory 113a and samples of ten thousand bits or less, the numbers of permutations can remain sufficient for reasonably secure cryptographic operations such as generating a random number. In exemplary embodiments, noise amplification memory 113a and noise memory controller 109p can be included within a processor 113b, and other possibilities exist as well for combining a noise amplification memory 113a and/or noise memory controller 109p with other components in a cryptographic unit 113 or storage unit 109 without departing from the scope of the present invention.

As discussed below with connection to FIG. 2a, a memory core interface 109m could be used with a noise amplification memory 113a in embodiments where the individual cells such a plurality of cells 240 below in noise

amplification memory 113a are manufactured with different specifications and tolerances than nonvolatile memory 109j, which could comprise memory cells 230 below in FIG. 2a, since the physical nature of the cells 240 would normally introduce desired additional bit errors. In this manner and in exemplary embodiments, noise memory controller 109p can be optionally omitted. Alternatively, if a plurality of cells 240 comprising a noise amplification memory 113a is manufactured consistently or within the specification of cells 230 in non-volatile memory 109j, then a noise memory controller 109p can be helpful to increase the bit error rate and resulting "noise" residing in noise amplification memory 113a. In exemplary embodiments (i) a noise memory controller 109p and (ii) a plurality of cells 240 in memory 113a (manufactured with different specifications and tolerances to enhance memory noise 194) can be combined in order to increase the level of noise, bit errors, or information entropy retained in noise amplification memory 113a.

Although only a small sample of exemplary bits, values, or data stored is illustrated in noise amplification memory 113a in FIG. 1f, noise amplification memory 113f can comprise thousands or more of bits recorded in memory cells 240. A single bit could correspond to a single cell, although manufacturing and memory technology used to create noise amplification memory 113a could also record multiple bits per cell without departing from the scope of the present invention.

FIG. 2a

FIG. 2a is a graphical illustration of a nonvolatile memory cell and a noise collection memory cell, in accordance with exemplary embodiments. Nonvolatile memory 109j and noise collection memory 113a can comprise a plurality of memory cells in order to record data. Nonvolatile memory 109j can comprise a plurality of standard memory cells 230, organized into blocks 195 and pages 199, where memory core interface 109m can select groups of cells for blocks 195 and pages 199 using addresses specified by interface controller 109c or processor 113b, where a single memory cell 230 is depicted in FIG. 2a. Noise amplifying memory 113a can comprise a plurality of modified cells 240, organized into blocks 195 and pages 199, where noise memory controller 109p can select groups of cells for blocks 195 and pages 199 using addresses specified by processor 113b, where a single memory cell 240 is depicted in FIG. 2a. As depicted in FIG. 2a, memory cells 230 or 240 can comprise layers in sequence from bottom to top of a P substrate layer, tunnel oxide layer, polysilicon floating gate layer, oxide-nitride-oxide (ONO) dielectric layer, polysilicon control gate layer, and a charge transfer lead layer.

Noise amplification memory 113a could comprise a plurality of memory cells 240 such as, but not limited to NAND flash technology with NAND-based gates and transistors, manufactured with the same technology as non-volatile memory 109j, thus reducing the number of manufacturing steps and manufacturing costs associated with producing storage unit 109. In this case, noise and bit errors in noise amplification memory 113a can be introduced and retained via noise memory interface 109p, or possibly a memory core interface 109m for the case where a noise memory interface 109p is optionally omitted. Noise memory interface 109p can be omitted in embodiments where memory core interface 109m allows a sufficient level of bit errors or memory noise 194 to be recorded in noise amplification memory 113a. Or, noise memory interface 109p could be combined with a memory core interface 109m. Other flash memory technologies could be used for noise amplification memory 113a and non-volatile memory 109j as well, such as NOR

technology. In exemplary embodiments, a first type of flash memory technology could be used for non-volatile memory 109j and a second type of flash memory technology could be used for noise amplifying memory 113a.

In exemplary embodiments, noise amplification memory 113a could comprise memory cells 240 manufactured to different specifications than non-volatile memory 109j, such as less or more thickness of (i) a semiconductor base such as a P substrate 241 layer below the tunnel oxide layer 244, when compared to the P substrate 231 layer in a nonvolatile memory cell 230, (ii) a tunnel oxide 244 layer above the P substrate 241 layer, when compared to the tunnel oxide 234 layer in a nonvolatile memory cell 230, (iii) a polysilicon floating gate 245 layer above a tunnel oxide 244 layer, when compared to the polysilicon floating gate 235 layer in a nonvolatile memory cell 230, (iv) an oxide-nitride-oxide (ONO) dielectric 246 layer when compared to the ONO dielectric 236 layer in a nonvolatile memory cell 230, (v) a polysilicon control gate 247 layer, when compared to the polysilicon control gate 237 layer in a nonvolatile memory cell 230, and/or (vi) a charge transfer lead 248 layer, when compared to the charge transfer lead 238 layer in a nonvolatile memory cell 230. In addition, combinations of two or more of any of the differences in thickness for the layers identified above could be utilized for a plurality of memory cells 240 in a noise amplification memory 113a

Likewise either the N+ source 242 layer or N+ drain 243 layer could have a specified thickness or tolerance different than the N+ source 232 or N+ drain 233 layer for nonvolatile memory cells 230. Noise amplification memory 113a could also support a higher specified variability for the above-mentioned thickness levels in a plurality of memory cells 240 when compared to memory cells 230 for a nonvolatile memory 109j. In addition, noise amplification memory 113 could specify an offset distance for N+ source 242 or N+ drain 243, thereby reducing or increasing the contact area between (i) the source and/or drain and (ii) the tunnel oxide 244 layer, for memory cells 240 compared to memory cells 230. In addition, a collection of cells 240 could be organized in a physical layout within noise amplification memory 113a that is different than the physical layout of cells 230 for a nonvolatile memory 109j, such as being spaced or organized in a manner that enhances the introduction of bit errors or memory noise 194 in a noise amplifying memory 113a, including spacing cells 240 closer together when compared to the spacing between cells 230.

Further, noise amplification memory 113a could support either (i) a higher tolerance of impurities or (ii) the intentional introduction of impurities in any or all of the layers comprising N+ source, N+ drain, P substrate, tunnel oxide, polysilicon floating gate, ONO dielectric, and polysilicon control gate layers. In an exemplary embodiment, a specified level of impurities could be added to any or all of the N+ source, N+ drain, P substrate, tunnel oxide, polysilicon floating gate, ONO dielectric, and polysilicon control gate materials during manufacturing of noise amplification memory 113a. In these manners, noise amplification memory 113a can preferably record and retain a higher number of bit errors than non-volatile memory 101j. Other possibilities exist as well for noise amplification memory 113a to be manufactured in a manner to enhance or promote the random or pseudo-random generation of bit errors or memory noise 194 without departing from the scope of the present invention.

Although noise memory interface 109p is depicted in FIG. 1e, in an exemplary embodiment, noise memory interface 109p could optionally be omitted and a noise amplifi-

cation memory 113a could operate with memory core interface 109m. In other words, a specified range of memory pages, memory cells, blocks or memory addresses comprising a plurality of memory cells 240 could be designated by CU 113 or interface controller 109c as memory with a higher probability of incurring bit errors due to the presence of a noise amplification memory 113a for the specified range of memory pages, memory cells, blocks, or memory addresses. In this case where noise memory interface 109p is omitted, noise amplification memory 113a could be manufactured to a different level of specifications such as any of the exemplary specifications in the previous three paragraphs. Error correcting code operations could also be intentionally omitted for the specified range of memory pages, memory cells, blocks, or memory addresses comprising the noise amplification memory 113a with a plurality of memory cells 240. In exemplary embodiments, noise memory interface 109p and noise amplification memory 113a could be combined in a storage unit 109 in order to provide an enhanced level of random or pseudo-random bit errors within noise amplification memory 113a.

Although the use of memory cells 230 and 240 in FIG. 2a supports the use of NAND flash memory for nonvolatile memory 109j and noise amplification memory 113a, other nonvolatile memory technology could be utilized as well without departing from the scope of the present invention. In other words, with different memory technology, the types of materials and layers for a memory cell could change from those depicted in FIG. 2a, but memory cells 240 for noise amplification memory 113a could have different manufacturing specifications or tolerances from memory cells 230 for a nonvolatile memory 109j in order to enhance the random nature and increase the probability of bit errors or memory noise 194 occurring in noise amplification memory 113a.

FIG. 2b

FIG. 2b is a flow chart illustrating exemplary steps for using data output from a noise amplifying memory in order to generate a private key and a public key, in accordance with exemplary embodiments. The processes and operations, described below with respect to all of the logic flow diagrams may include the manipulation of signals by a processor and the maintenance of these signals within data structures resident in one or more memory storage devices. For the purposes of this discussion, a process can be generally conceived to be a sequence of computer-executed steps leading to a desired result.

These steps usually require physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical, magnetic, or optical signals capable of being stored, transferred, combined, compared, or otherwise manipulated. It is convention for those skilled in the art to refer to representations of these signals as bits, bytes, words, information, elements, symbols, characters, numbers, points, data, entries, objects, images, files, or the like. It should be kept in mind, however, that these and similar terms are associated with appropriate physical quantities for computer operations, and that these terms are merely conventional labels applied to physical quantities that exist within and during operation of the computer.

It should also be understood that manipulations within the computer are often referred to in terms such as listing, creating, adding, calculating, comparing, moving, receiving, determining, configuring, identifying, populating, loading, performing, executing, storing etc. that are often associated with manual operations performed by a human operator. The operations described herein can be machine operations per-

formed in conjunction with various input provided by a human operator or user that interacts with the computer.

In addition, it should be understood that the programs, processes, methods, etc. described herein are not related or limited to any particular computer or apparatus. Rather, various types of general purpose machines may be used with the following process in accordance with the teachings described herein.

The present invention may comprise a computer program or hardware or a combination thereof which embodies the functions described herein and illustrated in the appended flow charts. However, it should be apparent that there could be many different ways of implementing the invention in computer programming or hardware design, and the invention should not be construed as limited to any one set of computer program instructions.

Further, a skilled programmer would be able to write such a computer program or identify the appropriate hardware circuits to implement the disclosed invention without difficulty based on the flow charts and associated description in the application text, for example. Therefore, disclosure of a particular set of program code instructions or detailed hardware devices is not considered necessary for an adequate understanding of how to make and use the invention. The inventive functionality of the claimed computer implemented processes will be explained in more detail in the following description in conjunction with the remaining Figures illustrating other process flows.

Further, certain steps in the processes or process flow described in all of the logic flow diagrams below must naturally precede others for the present invention to function as described. However, the present invention is not limited to the order of the steps described if such order or sequence does not alter the functionality of the present invention. That is, it is recognized that some steps may be performed before, after, or in parallel other steps without departing from the scope and spirit of the present invention.

The processes, operations, and steps performed by the hardware and software described in this document usually include the manipulation of signals by a CPU or remote server and the maintenance of these signals within data structures resident in one or more of the local or remote memory storage devices. Such data structures impose a physical organization upon the collection of data stored within a memory storage device and represent specific electrical or magnetic elements. These symbolic representations are the means used by those skilled in the art of computer programming and computer construction to most effectively convey teachings and discoveries to others skilled in the art.

A noise amplifying memory **113a** can include a plurality of cells **240** with memory noise **194**. Before CU **113** selects a sample of memory **113a** on which to process a hash **198**, CU **113** can conduct a series of noise-inducing operations **193**, as depicted and described in connection with Figure **1f** above. CU **113** can use a memory controller **109p** in order to enhance the level of memory noise **194** generated by noise-inducing operations **193**. After a series of noise-inducing operations **193**, CU **113** can select a sample of noise amplifying memory **113a** using a table **188**, such that the sample of memory **113a** is incremented, or different than a previous selection of a sample of memory **113a**. The resulting data from the sample of memory **113a** can be input into a secure hash algorithm **141c** in order to record a noise amplifying memory hash **198**. Note that the use of a secure hash algorithm **141c** and noise amplifying memory hash **198** can be optionally omitted or substituted with other process-

ing logic such that a pseudo-random number can be input into a random number seed **128b**. In exemplary embodiments and as depicted in FIG. **2b**, additional pseudo-random data can be input into random number seed **128b**, such as a noise value **197** from a sensor **113f** in CU **113** or also a random number **252** received from module **101** via bus **109d**.

Although not illustrated in FIG. **2b**, the multiple values of hash **198**, noise value **197**, and random number **252** from module **101** could also be input into a secure hash algorithm **141c**, where the output from the secure hash algorithm **141c** could comprise random number seed **128b**. In this manner, noise or a high level of information entropy from multiple sources including memory **113a**, sensor **113f**, and module **101** could be combined together in order to increase the randomness of a number used to generate module private key **173**. Input into random number seed **128b** could also include a plurality of noise values **197** available to CU **113**, such as various machine and hardware states that could be measured or determined by CU **113**. The machine and hardware states could include combinations of clock cycle counts or increments, values from RAM **113e** memory, values from memory **109f**, and/or internal register or accumulator values for processor **113b**, and each of these values could comprise an additional noise value **197** combined into random number seed **128b**. In addition, noise values **197** and random number **252** from module **101** could optionally be omitted, and in this case the single source of information entropy or randomness could be the noise amplifying memory **113a**.

After recording random number seed **128b** with the various described inputs, CU **113** could utilize a random number generator **128** with the random number seed **128b** in order to calculate and record a random number. The random number could be input into a key pair generation algorithm **141e** along with a set of cryptographic parameters **126a**, where parameters **126a** could be a selected subset of parameters **126** from FIG. **1d** in order to generate a set of PKI keys **174** with the desired length, format, and algorithm supported (such as RSA vs. ECC and also a specified ECC curve in parameters **126a** if ECC is utilized). The output of key pair generation algorithm **141e** could be recorded by CU **113** as a derived module private key **173** and corresponding derived module public key **172**. Although not illustrated in FIG. **2b**, the derived module private key **173** can subsequently (i) be recorded in protected memory **109g** depicted and described in connection with FIG. **1e** and **1c** above, and (ii) not be transferred outside storage unit **109**. In this manner, CU **113** can obtain a PKI key pair **174** with a sufficient level of security in order to support the desired operation of module **101** and authentication of module **101** with various networks and servers, such as a wireless network **102** and a server **105**. The generation or derivation of a CU private key **112** and CU public key **111** can also utilize the steps illustrated in FIG. **2b**, with the primary difference being a potentially different set of cryptographic parameters **126b** for the CU private key **112** and CU public key **111** could be utilized, as discussed in connection with the description of a step **306** in FIG. **3a** below.

FIG. **2c**

FIG. **2c** is a graphical illustration of an exemplary system, where a module and a cryptographic unit communicate through a shared nonvolatile memory interface, in accordance with exemplary embodiments. Module **101** and CU **113** can preferably communicate through mutually supported protocols, in order to transfer data between the two elements. An exemplary embodiment for a system support-

ing communication through a shared nonvolatile memory interface **220** is illustrated in FIG. **2c**. Module **101** and CU **113** can both mutually access a shared memory **109h**, which could comprise a selected portion of non-volatile memory **109j**, where shared memory **109h** is also depicted and described in connection with FIG. **1c** and FIG. **1e**. A shared nonvolatile memory interface **220** can comprise a shared memory **109h**, CU polling **221** and module polling **222**, where shared memory **109h** can include a module write and crypto unit read memory **191** and module read and crypto unit write memory **192**.

The use of shared memory **109h** can be desirable when CU **113** resides on a storage unit **109** operating with established standards for removable media, such as using generic removable media drivers for device driver **101g**. The generic or pre-existing device driver **101g** installed on a wide variety of modules **101** may not include specific interfaces for communication with CU **113**, but communication between module **101** and CU **113** can be desirable in exemplary embodiments. For example, electrical pins **109a** and device driver **101g** could support a one-bit SD bus for removable media such as a micro SD card and resulting file or memory operations within the micro SD card, but device driver **101g** included in module **101** may not have specific support to send data directly to CU **113**. Other possibilities exist as well, where a wide variety of manufactured modules **101** can (A) support standards-based removable storage media such as SD cards, but (B) lack pre-installed drivers **101g** with protocols for communicating directly with CU **113**. Storage unit **109** and CU **113** could subsequently utilize system **200** in order to communicate with module **101**, where support for a module **101** to read and write to non-volatile memory **109j** could be widely supported by existing modules **101**.

By using shared memory **109h**, a generic or existing removable storage media device driver **101g** can allow module **101** to (i) write data to memory **191** or files in storage unit **109**, and (ii) read data from memory **192** or files in storage unit **109**. Using system **200**, CU **113** and module **101** can subsequently utilize this standard capability to communicate. In other words, for module **101** to send data to CU **113**, device driver **101g** can write the data to memory **191** in shared memory **109h**, where CU **113** can subsequently read data in the memory **191** in shared memory **109h** using CU read libraries **191a** within memory control libraries **182**. CU **113** can use periodic CU polling **221** of memory **191** in shared memory **109h** to determine that module **101** has written data for CU **113** to subsequently read. Further, in order for module **101** to read data from CU **113**, CU **113** could write the data to memory **192** in shared memory **109h** using CU write libraries **192a** within memory control libraries **182**, and module **101** could subsequently read the data from memory **192** in shared memory **109h** using device driver **101g**. Module **101** can use periodic module polling **222** of memory **192** in shared memory **109h** to determine that CU **113** has written data for module **101** to subsequently read. As contemplated herein, CU polling **221** or module polling **222** could comprise a logical loop operating with processor **113b** or processor **101b**, respectively, where the loop determines that a file or value recorded in memory has been updated or changed by the other node (where module **101** and CU **113** can comprise the two nodes). The loop timing for CU polling **221** or module polling **222** could operate at specified frequencies, such as an exemplary every 10 or 20 milliseconds, although other possibilities exist as well without departing from the scope of the present invention.

Before recording shared data in shared memory **109h**, module **101** or module provider **122** could perform a shared memory formatting and configuration process **201**. The process **201** could comprise the standard steps for formatting removable media such as an SD card, where a file system is applied to the available memory. Process **201** could include formatting memory **109h** to standards supported by module **101** such as exemplary file systems of FAT16, FAT 32, NTFS, ext3, ext4, UDF. Other file systems for memory **109f** and memory **109h** are possible as well without departing from the scope of the present invention. Process **201** could also format all of non-volatile memory **109j** (which can include share memory **109h**). At the conclusion of a process **201** while storage unit **109** is powered, CU **113** memory control libraries **182** could include a detection of the file system selected by module **101** or module provider **122** for memory **109j** or memory **109h**, such that CU **113** can subsequently support reading and writing to the selected file system using a compatible versions of memory control libraries **182**.

In other words, module **101** or module provider **122** can normally be responsible for selecting the format of a file system during configuration **201**, where the first portion of configuration **201** can comprise writing a regular file system format for standard removable media, where the regular file system format can support existing SD cards that don't include a CU **113**. A second portion of configuration **201** can comprise CU **113** subsequently detecting and utilizing the selected file system. In this manner CU **113** within a storage unit **109** can support the use of existing device drivers **101g** in modules **101**. Communication between module **101** and CU **113** using a system **200** can utilize an module program **101i** depicted and described in connection with FIG. **1b** for a module **101** (i) to write data to memory **191** in shared memory **109h**, (ii) read data from memory **192** in shared memory **109h**, and (iii) conduct a periodic module polling **222**.

After a configuration **201** step, either module **101** or CU **113** can load shared memory **109h** with an initial set of values supporting the operation of CU **113**. In exemplary embodiments, the initial set of values could be included in a CU boot configuration **183**. Module **101** could write data into module write and crypto unit read memory **191** in the format of either (i) multiple different files, or (ii) a single file with multiple values recorded in the file. The file or files in memory **191** could include the depicted values of a subset of crypto parameters **126a**, digital signature input **204**, external random input **252**, asymmetric cipher input **206**, external private key **207**, signaling data **208**, and control data **209**. CU **113** could write data into crypto unit write and module read memory **192** in the format of either (i) multiple different files, or (ii) a single file with multiple values recorded in the file. The file or files in memory **192** could include the depicted values of crypto parameters **126**, digital signature output **210**, random number output **211**, asymmetric cipher output **212**, internally generated pub key **172**, signaling **208**, and control data **214**. Other possibilities exist as well for the values or data recorded in shared memory **109h** without departing from the scope of the present invention, and the exemplary data above is illustrative as opposed to limiting.

As an example of the data flow supported by a shared nonvolatile memory interface **220** in a system **200**, after configuration **201**, CU **113** could write the set of cryptographic parameters **126** as shown in FIG. **2c**, where parameters **126** could specify all the parameters supported by a set of cryptographic algorithms **141** in CU **113**. Module **101** could read parameters **126** and (i) select a subset of cryp-

tographic parameters **126a** for CU **113** to utilize in generation of a derived module private key **173** as depicted in FIG. **2b**, and (ii) write the selected subset of parameters **126a** to a file in memory **191**. CU **113** could utilize periodic polling **221** for changes in memory **191** in order to detect that module **101** has written the subset of parameters **126a** in memory **191** and subsequently read the data. Other possibilities exist as well for both (i) the values in shared memory **109h** and (ii) the steps of transferring the data between module **101** and CU **113** without departing from the scope of the present invention.

FIG. **3a**

FIG. **3a** is a flow chart illustrating exemplary steps for configuring a cryptographic unit and generating a certificate for the cryptographic unit, in accordance with exemplary embodiments. Before a storage unit **109** with an embedded cryptographic unit **113** is distributed to a module provider **122**, the manufacturer, certificate authority **118**, or provider of storage unit **109** can perform a series of steps **300** in order to both (i) internally generate a CU public key **111** and CU private key **112** with a sufficient level of security for the desired operation of module **101**, and (ii) generate a certificate **122b** for the CU **113**. Note that PKI key pair for CU **113** is different than a module private key **173** and module public key **172**, which can subsequently be derived at later steps depicted in FIG. **3b** below. In other words and as described below, CU private key **112** and CU public key **111** can be used by a certificate authority **118** in order to verify that a subsequently derived module public key **173** (with a corresponding but secret module private key **172**) belong to CU **113** with CU **109e** operating in a module **101** with a module identity **110**. In this manner, using the steps in FIG. **3a** and FIG. **3b**, a certificate authority **118** can subsequently issue a certificate **122a** for module **101** with module identity **110** using module public key **172** with a high level of certainty and authority, such that the certificate **122a** used by module **101** in communication with a server **105** or a wireless network **102** can be trusted. In other words, a CU private key **112** can be used to digitally sign a subsequently derived module public **172**, where the CU private key **111** can be used to verify the signature. Additional details regarding exemplary embodiments using this feature for CU **113** will be described below in this FIG. **3a** and next FIG. **3b**.

At step **302**, cryptographic unit **113** can be manufactured, and a cryptographic unit identity **109e** can be recorded in CU **113**. In exemplary embodiments, CU **113** can be manufactured in step **301** with the components depicted and described in connection with FIG. **1c**, FIG. **1e**, and FIG. **2a**. CU identity **109e** can be recorded in a protected memory **109g** or also recorded in a physical location within CU **113** that can be directly read by a bus **109d** or internal bus **109q**. In this manner, CU identity **109e** can be permanently recorded in CU **113** and in exemplary embodiments CU identity **109e** cannot be readily or feasibly altered or tampered with. At step **303**, CU **113** can be merged with storage unit **109**, such as assembling the components depicted in FIG. **1e** into a housing or enclosure for both CU **113** or storage unit **109**.

A CU configuration unit **104** used in a step **303** in FIG. **3a** can comprise a server **105** or a computer designed to configure CU **113** such as loading firmware, generating keys, etc. CU configuration unit **104** can utilize a plurality of interfaces supporting electrical pins **109a**, such that a plurality of CU **113** units can be connected to CU configuration unit **104** at one time, in order to speed the subsequent configuration steps for CU **113**. Additional exemplary descriptions of CU configuration unit **104** are also above in

FIG. **1a**. Note that CU **113** discussed below can internally derive its private key **112** in a step **306**. Since CU **113** below can internally derive its private key **112** in a step **306**, the security requirements for the location and operation of CU configuration unit **104** can be reduced. For example CU configuration unit **104** could be located in a manufacturing facility or at the end of a manufacturing line producing either CU **113** or storage unit **109**. In comparison, alternative systems where private keys or shared secret keys are (i) externally generated and (ii) subsequently loaded into removable storage media require that a unit similar to CU configuration unit **104** be kept in a secure area and generally offline, such that copies of the private keys or shared secret keys in the removable storage media be kept secure, such as with traditional SIM or UICC cards. In exemplary embodiments of the present invention, the CU private key **112** or module private key **173** can preferably reside only in CU **113**, thus reducing the procedural and process overhead of the steps required when CU private key **112** has been externally generated and then loaded into CU **113**.

At step **304**, CU configuration unit **104** can load EEPROM **113c** for CU **113** with data **186**, where data **186** was depicted and described in connection with FIG. **1e** above. Although not depicted in FIG. **3a**, CU configuration unit **104** could initially read CU identity **109e** and subsequently lookup the correct or desired data **186**, such as one group of CU identities **109e** can utilize a first CU boot firmware **181**, while a second group of CU identities **109e** can utilize a second CU boot firmware **181**. After loading EEPROM **113c** with data **186**, CU configuration unit **104** can perform a series of reboots and quality assurance checks and tests to assure that CU **113** in storage unit **109** boots properly and operates to within specifications.

At step **305**, CU configuration unit **104** can conduct a series of noise-inducing operations **193** on a noise collecting memory **113a** in CU **113**, such that information entropy in memory **113a** or randomness is increased from the initial manufactured state from step **302**. In an exemplary embodiment, CU configuration unit **104** can utilize its own random number generator **128** in order to structure and organize the series of noise-inducing operations **193** differently from one CU **113** to the next. In other words, CU configuration unit **104** should perform the first sentence in a step **305** differently from one CU **113** to the next, in order to enhance randomness across different individual units of CU **113**. After the series of operations **193**, CU configuration unit **104** can instruct CU **113** to generate CU private key **112** and CU public key **111**, where the derivation or generation of the keys can be conducted in a step **306** below.

A step **305** could also include CU configuration unit **104** performing a quality assurance (QA) verification or check on a noise collecting memory **113a** and noise memory controller **109p**. During this exemplary QA step within step **305**, that a manufacturer or the operator of CU configuration unit **104** can verify that a desirable number of bit errors or memory noise **194** are introduced into noise amplifying memory **113a**. For example, if the instances of memory noise **194** are below a threshold, such as less than an exemplary **1** part per hundred, then noise amplifying memory **113a** along with CU **113** may be considered defective and not suitable for use as a storage unit **109**. Other values for a threshold could be applicable as well, depending on (i) the number of noise-inducing operations **193** performed during the QA check within a step **305**, and (ii) the specifications of the noise amplifying memory for recording bit errors or memory noise **194**.

In exemplary embodiments, although not depicted in FIG. 3a, CU configuration unit 104 and CU 113 can also optionally support a “cryptographic audit” mode 104a at the conclusion of a step 305 where random bit errors have been introduced into noise amplifying memory 113a. A cryptographic audit mode 104a is depicted in FIG. 1a. Noise inducing operations 193 can cease in cryptographic audit mode 104a and noise memory controller 109p can also preferably operate as a regular memory core interface 109m in order to minimize the introduction of new bit errors during cryptographic audit mode 104a. A potential benefit of the embodiments for generating a random number using the noise amplifying memory 113a is the complete state (in terms of a sequence of bits in noise amplifying memory 113a) at a point in time can be read, recorded, and subsequently analyzed.

In other words for exemplary embodiments, during a cryptographic audit mode 104a only, the state of all memory cells 240 for the relevant sample in a noise amplifying memory 113a used to generate a random number can be output by a CU 113 to shared memory 109h. During cryptographic audit mode 104a, CU 113 can (A) write a copy of every bit read from noise amplifying memory 113a into shared memory 109h as (B) CU 113 reads the individual bits in noise amplifying memory 113a for input into random number generator 128. In exemplary embodiments, mode 104a can thus obtain and read an accurate and non-volatile record of the state of noise amplifying memory 113a and subsequent random number generated, even for the case that noise amplifying memory 113a may incur subsequent bit errors when operating in cryptographic audit mode 104a.

Analysis of the series of a series of bits comprising the state of all memory cells can support both (i) outside verification of both “randomness” of the system, and (ii) demonstration of sufficiently low levels of potential bias. In this manner and by providing an open and complete record of the relevant state at the time of random number generation, users or third parties can gain confidence in the system and thereby support market adoption. Random number generation from transient systems, such as using thermal noise to generate a random number, often encounters problems where users do not have ready access to the complete state of thermal noise, even for auditing or verification purposes. Such alternative transient systems often remains a completely closed “black box”, where “random” numbers are extracted, but internal states at the time the “random” numbers are extracted can remain unknown and thus subject to doubt or concern by users. Without a complete and accurate record of the state of thermal noise during evaluation of random number generation, users or third parties can thus be concerned by biases or “back doors” into the system. In contrast, by using a cryptographic audit mode 104a, a complete record of the internal state of memory cells 240 in noise amplifying memory 113a for a random number can be read by authorized users of CU configuration unit 104.

The audit command and analysis can preferably only be supported when CU 113 is inserted into CU configuration unit 104 and only for the generation of new keys after a series of noise inducing operations. CU 113 can be programmed to erase a private key generated in cryptographic audit mode 104a before exiting the cryptographic audit mode 104a, such that keys generated during cryptographic audit mode 104a cannot be used for subsequent commercial operations of a storage unit 109. Cryptographic audit mode 104a can include a series of noise inducing operations 193 for noise amplifying memory 113a after the internal state

from the above two paragraphs has been read, such that internal state resulting for a cryptographic audit mode 104a would not be subsequently feasibly determined by subsequent holders of storage unit 109.

At step 306, CU 113 can generate CU private key 112 and CU public key 111. CU 113 can use the steps and procedures depicted and described in connection with FIG. 2b above, with difference that CU PKI keys are generated in a step 306 as opposed to the module PKI keys generated in a step 250. Additional differences between a step 306 and step 250 can be (i) external noise 252 can be provided by CU configuration unit 104 instead of a module 101, and (ii) parameters 126b instead of parameters 126a can be input into the key pair generation algorithm 141e. In other words, parameters 126b can be applicable for CU PKI keys, as illustrated in FIG. 7b below, and parameters 126a can be applicable for module PKI keys, as illustrated in FIG. 7a below. At the conclusion of step 306, CU 113 can internally record the internally generated CU private key 112 and CU public key 111. CU 113 can record CU private key 112 either (i) in protected memory 185 within EEPROM 113c as depicted in FIG. 1e, or (ii) within protected memory 109g, and other possibilities exist as well for CU 113 to securely record CU private key 112 within storage unit 109. In an exemplary embodiment, a processor 113b could include protected memory, and CU private key 112 could be recorded within the protected memory of processor 113b. Other possibilities exist as well for the physical memory or storage location for recording CU private key 112 within storage unit 109 without departing from the scope of the present invention.

At step 307, CU 113 operating in CU configuration unit 104 can send the CU public key 111 to CU configuration unit 104. Communication between CU 113 and CU configuration unit 104 can continue to be through electrical pins 109a. Other information can be sent by CU 113 at a step 307 as well, such as (i) CU identity 109e, and/or (ii) an identity or sequence number for the CU public key, such as a sequence number 702 depicted in FIG. 7b below.

At step 308, CU configuration unit 104 can combine the received CU public key 111 from step 307 with the CU identity 109e and the parameters 126b to generate a digital signature 309 using a private key associated with CU configuration unit 104 and a digital signature algorithm 141d. The exemplary operation of a digital signature algorithm 141d is depicted and described below in connection with FIG. 4a. CU configuration unit could record a private key similar to server private key 105c depicted in FIG. 1a. Continuing at step 308, CU configuration unit 104 can transmit or send to certificate authority 118 via a network 107 depicted in FIG. 1a the values of CU identity 109e, CU public key 111, parameters 126b, and digital signature 309 (along with an identity for CU configuration unit 104).

At a step 310, the certificate authority 118 can receive the data transmitted in step 308, and verify the digital signature 309 using the operation of a digital signature algorithm 141d depicted and described in connection with FIG. 4b below. Certificate authority 118 could record a public key for the CU configuration unit 104. In this manner, certificate authority 118 can be reasonably assured that CU public key 111 has been generated by CU 113 with CU identity 109e and transmitted by CU configuration unit 104. In other words, since CA 118 can trust CA configuration unit 104 and the operator of a CA configuration unit 104, CA 118 can (i) verify that CU public key 111 has been transmitted by CA configuration unit 104 and also (ii) subsequently trust that CU public key 111 is associated with CU identity 109e. After recording the data in a step 310 and verifying the

digital signature 309, certificate authority 118 can issue a certificate 122b, such as the exemplary certificate 122b depicted and described in connection with FIG. 7b. In order to generate certificate 7b, certificate authority 118 can also perform a digital signature algorithm 141d operation with input of values for CU identity 109e, CU public key 111, parameters 126b, and a certificate authority private key 132. The use of a digital signature algorithm 141d for a signing operation can be similar to the signing operation illustrated in FIG. 4a below, where the output can be a digital signature 184 for certificate 122b, which is also depicted below in connection with FIG. 7b below. At the conclusion of step 310, CA 118 can send the generated certificate 122b back to CU configuration unit 104 via the network 107.

At step 311, CU configuration unit 104 can receive the data transmitted by certificate authority 118 in step 310 above, and CU configuration unit 104 can load EEPROM 113c in CU 113 with certificate 122b. A step 311 could also include a verification of the signature 184 in certificate 122b by CU configuration unit 104 in order to confirm the certificate 122b from CA 118 is correct. By loading certificate 122b in EEPROM 113e, CU 113 can subsequently have ready access to certificate 122b for future operations, such as authoritatively sending CU public key 111 to third parties, such as a module provider 122. The use of certificate 122b in EEPROM 113e can be useful for authoritatively identifying CU 113. At the conclusion of a step 311, storage unit 109 with CU 113 can be removed from CU configuration unit 104. At step 312 storage unit 109 with CU 113 can be shipped to a module provider 122, or possibly directly to end users, and other possibilities exist as well without departing from the scope of the present invention.

FIG. 3b

FIG. 3b is a flow chart illustrating exemplary steps for deriving a private key for a module using a cryptographic unit, and receiving a certificate for the corresponding public key, in accordance with exemplary embodiments. Step 300 in FIG. 3b can comprise the steps depicted and described in FIG. 3a. Not all the sub-steps shown for a step 300 in FIG. 3a are required, and some may be omitted or substituted with equivalent or similar sub-steps in order to conclude a step 300 such that a cryptographic unit 113 can record a CU private key 112 and CU public key 111. For example, in an exemplary embodiment different than that depicted in FIG. 3a, CU private key 112 could be derived externally from CU 113 or storage unit 109 and consequently loaded into CU 113 using a CU configuration unit 104. At the conclusion of steps 300 in FIG. 3a, cryptographic unit 113 can record a CU private key 112 and a certificate 122b for the cryptographic unit 113 (as illustrated in FIG. 7b). Certificate 122b can support communication between module 101 and module provider 122 and certificate authority 118, and CU 113 and certificate authority 118 can use the exemplary steps in FIG. 3b such that CU 113 can (i) derive a module private key 173, (ii) send the corresponding public key 172 to a certificate authority 118 in an authenticated manner (using CA private key 112 and CA public key 111), and (iii) receive a certificate 122a for the module public key 172.

In exemplary embodiments, a module provider 122 or end user of module 101 can prefer for module 101 to utilize a different PKI key pair, which could comprise a module public key 172 and a module private key 173. Reasons for using different PKI key pair for the module could be many, including, (i) different parameters 126a than 126b could be associated with module 101, (ii) module provider or end users may prefer to rotate the use of a module private key 173 over time to increase security, (iii) module 101 may

need a plurality of PKI keys 174 at any point in time (such as a first key for digital signatures, a second key for asymmetric ciphering, etc.), and other reasons for module 101 or storage unit 109 to derive a PKI key pair 174 could exist as well.

At step 313, module provider 122 can load storage unit 109 with cryptographic unit 113 inside into either (i) module 101 or (ii) a server similar to CU configuration unit 104 depicted and described in connection with FIG. 3a above. If module provider 122 loads storage unit 109 into a server similar to CU configuration unit 104, then module provider 122 or an end user could subsequently load storage unit 109 into a module 101 at a subsequent step such as step 322 below.

At step 314, after receiving electrical power due to the previous step 313, CU 113 can conduct initialization steps such as running boot firmware 181 and then conducting a series of noise-inducing operations 193 on noise amplification memory 113a. The noise inducing operations 193 can utilize a table 188 recorded in memory 109g in order to focus the generation of memory noise 194. In other words, table 188 could record the next physical addresses in noise amplification memory 113a where CU 113 would access to collect data comprising noise, and noise inducing operations 193 upon boot of CU 113 can start in a range specified by table 188. Table 188 could also record parameters regarding noise inducing operations 193 such as a minimum target bit error rate desired (such as an exemplary rates of 2 parts per hundred, 2 parts per thousand, etc.), and CU 113 could continue noise inducing operations 193 until the specified minimum level of bit errors in a table 188 were achieved. Note that an initial table 188 could also be included in EEPROM 113c, while an operating or updated table 188 could be recorded in protected memory 109g. In exemplary embodiments, a step 314 can be included in CU boot firmware 181, such that a boot or startup process for CU 113 can include a series of noise inducing operations 193. In exemplary embodiments, a step 314 could also be performed by CU 113 either (i) during periods of idle time, or (ii) at specified periodic intervals such as every X hours, such that CU 113 continues to periodically induce errors in noise amplification memory 113a over time.

In addition, steps 314 through 321 in FIG. 3b could comprise module provider 122 accessing module 101 remotely, such as via a wireless network 102. Thus, many of the steps depicted in FIG. 3b could be conducted remotely and “over the air” instead of module provider 122 requiring physical access to module 101. In other words, module provider 122 could physically access storage unit 109 for an initial configuration comprising steps 313 through 322 in FIG. 3b, but module provider 122 could also repeat exemplary steps 314 through 321 in FIG. 3b at a later time remotely and without the physical presence of storage unit 109 with module provider 122 at the later time. For the cases where module provider 122 utilizes the steps in FIG. 3b where module 101 with storage unit 109 operate remotely, additional steps could be performed in order to establish a secure link between module 101 and module provider 122, such as setting up a data session comprising TLS, IPSec, etc over the network 107 between module 101 and module provider 122 depicted in FIG. 1a.

At step 315, module provider 122 can send a signal 208 for CU 113 to generate PKI keys 174. A set of parameters 126a could be (i) included with the signal 208, such that CU 113 would know the proper or desired subset of cryptographic parameters 126 to utilize for processing or creating the PKI keys 174, or (ii) communicated in a separate

signaling 208 message either before or after a step 315. The signal 208 could be sent to CU 113 via the system 200 depicted and described in connection with FIG. 2c. If module 101 operates with storage unit 109 remotely from module provider 122, then module provider 122 could send the signal 208 first to module 101 via a secure connection over network 107 and wireless network 102 depicted in FIG. 1a, and then module 101 could send the command to CU 113 using an exemplary system 200 in FIG. 2c. If module provider 122 has installed storage unit 109 in a CU configuration unit 104 in a step 313, the signal 208 could still utilize a system 200, but in this case the CU configuration unit 104 would write the signal 208 to shared memory 109h in a system 200 instead of the module 101. In other words, the present invention contemplates many possible multiple hardware and network configurations and combinations, and the exemplary steps depicted in FIG. 3b could be conducted over the different hardware and network combinations, including the use of a CU configuration unit 104.

In a step 250, CU 113 can generate PKI keys 174 for module 101 using parameters 126a. Exemplary individual steps and components within a step 250 are depicted and described in FIG. 2b. Although a noise amplification memory 113a is illustrated in FIG. 2b, a noise amplification memory 113a can also be optionally omitted and noise or random numbers from other sources could be utilized for deriving PKI keys 174, such as from (i) random number 252 generated externally to CU 113, or (ii) data from a sensor 113f or sensor 101i f. Other possibilities exist as well for the source of random numbers input into a key pair generation algorithm 141e in a step 250 without departing from the scope of the present invention. At the conclusion of a step 250, CU 113 could record module private key 173 in a protected, non volatile memory such as memory 109g, so that CU 113 could have access to module private key 173 at later times. CU 113 in a step 250 could also include a module public key identity 170, such that module public key 172 in a step 250 could be properly identified from a previous or subsequent module public key 172 for module 101 with module identity 110. CU 113 could receive module public key identity 170 in a signal 208 in a step 315 above, and other possibilities exist as well. The use of a module public key identity 170 for a module public key 172 is depicted and described in connection with FIG. 7b below. Module

At step 316, after processing or deriving module PKI keys 174, CU 113 can write module public key 172 to shared memory 109h, such that a component external to storage unit 109 could subsequently read the module public key 172 derived in a step 250. CU 113 could also write the module public key identity 170 with module public key 172 in a step 316. As contemplated herein, module public key identity 170 could be combined with module public key 172, such that referring to module public key 172 includes both a number for the public key and an identity of the public key. If storage unit 109 is loaded into a module 101 at a step 316, then module 101 could subsequently read the key 172 using system 200 and subsequently send the key 172 to module provider 122. If storage unit 109 is loaded into a CU configuration unit 104 at a step 316, then CU configuration unit 104 could subsequently read the key 172 after a step 316.

As step 317, module provider 122 can receive the module public key 172 derived in step 315 and recorded in step 316. If module 101 with storage unit 109 operates remotely from module provider 122 in a step 317, then module 101 could send the module public key 172 using network 107, and in this case additional steps for authentication for module 101

with module provider 122 could take place before a step 317. If storage unit 109 is in a physically secured environment with module provider 122 at a step 317, such as storage unit 109 being inserted into a CU configuration unit 104 at a step 317, then a module provider 122 may not need a module 101 to operate or conduct the step 317. After receiving the module public key 172, module provider 122 can associate the public key 172 with a module identity 110. The module identity 110 in a step 317 can be for the module 101 where storage unit 109 with private key 173 will operate.

In other words, module public key 172 could belong to a module 101 that utilizes module identity 110, where external elements or nodes communicating the module 101 through network 107 depicted in FIG. 1a could identify module 101 using the module identity 110 and also subsequently use module public key 172 to authenticate or secure communication with module 101. In exemplary embodiments, module 101 and module provider 122 can use module identity 110 instead of a cryptographic unit ID 109e for identifying module 101, since module provider 122 can control and specify the module identity 110, whereas the module provider 122 may not normally be able to specify the CU ID 109e since that identity can be recorded when CU 113 in storage unit 109 is manufactured. Note that the module public key 172 could also optionally be associated with module public key identity 170 at a step 317. In other words, in exemplary embodiments, module public key 172 can be associated with both a module public key identity 170 and a module identity 110 at a step 317.

At step 318, module provider 122 can combine the received module public key 172 from step 317 with the module identity 110 and the parameters 126a to generate a digital signature 319 using a module provider private key 121 and a digital signature algorithm 141d. The exemplary operation of a digital signature algorithm 141d is depicted and described below in connection with FIG. 4a. Note that module provider 122 could have multiple module provider private keys 121, and a selected key 121 could be utilized for the digital signature process in a step 318. Continuing at step 318, module provider 122 can transmit or send to certificate authority 118 via a network 107 depicted in FIG. 1a the values of module identity 110, module public key 172, parameters 126a, and digital signature 319.

At a step 320, the certificate authority 118 can receive the data transmitted in step 318, and verify the digital signature 319 using the operation of a digital signature algorithm 141d depicted and described in connection with FIG. 4b below. In this manner, certificate authority 118 can be reasonably assured that module public key 172 has been transmitted by module provider 122. In other words, certificate authority 118 may have a trusted relationship with module provider 122, such that certificate authority 118 can trust that module public key 172 has been properly received and recorded by module provider 122. Note that certificate authority 118 could take additional steps to those depicted in FIG. 3b if certificate authority does not have a trusted relationship with module provider 122, but in that case as well the steps in FIG. 3b can be useful. After recording the data in a step 320 and verifying the digital signature 319, certificate authority 118 can issue a certificate 122a, such as the exemplary certificate 122a depicted and described in connection with FIG. 7a.

In order to generate certificate 7a, certificate authority 118 can also perform a digital signature algorithm 141d operation with input of values for module identity 110, module public key 172, parameters 126a, and a certificate authority

private key 132, where the output of the signing operation similar to the signing operation illustrated in FIG. 4a below can be a digital signature 125 for certificate 122a, which is also depicted below in connection with FIG. 7a. At the conclusion of step 320, CA 118 can send the generated certificate 122a back to module provider 122 via the network 107.

At step 321, module provider 122 can receive the data transmitted by certificate authority 118 in step 320 above, and module provider 122 can load storage unit 109 with certificate 122a. Certificate 122a could be recorded in memory 109f in storage unit 109. A step 321 could also include a verification of the signature 125 in certificate 122a by module provider 122 in order to confirm the certificate 122a from CA 118 is correct. By loading certificate 122a in nonvolatile memory 109f, module 101 can subsequently have ready access to certificate 122a for future operations, such as authoritatively sending module public key 172 to third parties, such as a server 105 or other nodes operating on network 107. In other words, the use of certificate 122a obtained in this manner outlined in FIG. 3b can be useful for authoritatively identifying module 101 using module identity 110 by third parties, where the third parties trust CA 118.

If module 101 with storage unit 109 operates remotely from module provider 122 during steps 300 through 320 in FIG. 3b, then the sequence of steps for distributing the certificate 122a can conclude at a step 321. If storage unit 109 operates within a CU configuration unit 104 during steps 300 through 320 in FIG. 3b, then the additional step 322 can be performed. In other words, module provider 122 could use CU configuration unit 104 for an initial configuration of storage unit 109 and module 101, and module provider 122 could communicate with module 101 over a network 107 after module 101 has been distributed and deployed. For the case where module provider initially configures storage unit 109 and module 101 (such as the case where storage unit 109 has not been inserted into module 101), then module provider 122 could subsequently perform a step 322 in FIG. 3b, where module provider 122 distributes module 101 loaded with certificate 122a to end users.

Other possibilities for a CU 113 to derive PKI keys 174 for a module 101 using the steps and procedures outlined in FIG. 3b without departing from the scope of the present invention. In one embodiment, a module 101 could send a derived module public key 172 with module identity 110 and/or CU ID 109e directly to CA 118, along with a digital signature using CA private key 122 for the data. The digital signature for the data could be generated using the process depicted and described in connection with FIG. 4a and the CU private key 112. CA 118 could verify the digital signature and subsequently issue a new certificate 122a to module 101. The communication between module 101 and CA 118 could be via network 107 depicted in FIG. 1a. In this case, module provider 122 could send a signal 208 to module 101 using CU 113 to create the new PKI key pair 174. Other potentially trusted entities such as wireless network 102 or M2M service provider network 108 communicating with module 101 could originate a signal 208 for module 101 with CU 113 to derive a new PKI key pair 174.

In exemplary embodiments where CU 113 derives new PKI keys 174 while module 101 is operating remotely from module provider 122, module 101 could perform step 317 and step 318 in FIG. 3b instead of module provider 122 performing the actions. In this case, digital signature 319 in step 318 could comprise a digital signature generated using the CU private key 112. CA 118 would record a table matching module identities 110 with CU IDs 109e for CU

113 associated with the module identities 110. CA 118 could verify the digital signature 319 using the CU public key 111, using an exemplary verifying step similar to that depicted in FIG. 4b below. After successful verification, CA 118 could send module 101 via the network 107 a certificate 122a for the module identity with the module public key 172. FIG. 4a

FIG. 4a is a flow chart illustrating exemplary steps for creating a digital signature using a private key, parameters, and data input, in accordance with exemplary embodiments. As discussed above, digital signatures can be useful for verifying the identity of a node communicating over a network, such as network 107 in FIG. 1a. Step 318 in FIG. 3b includes creating a digital signature 319, and FIG. 4a illustrates an exemplary embodiment of the portion of step 318 for creating digital signature 319, which can comprise signing process 318a. In a signing process 318a, a digital signature 319 can be output from a digital signature algorithm 141d, which could comprise an RSA based DSA 167 or an ECC based ECDSA 158, and other possibilities exist as well. When using a DSA 167 or ECDSA 158 algorithm in non-deterministic mode for a signing process 318a, a value of "k" or "r", which could comprise a random number 251a, can be associated with the digital signature 319.

When using a DSA 167 or ECDSA 158 in deterministic mode, such as specified in IETF RFC 6979 and titled "Deterministic Usage of the Digital Signature Algorithm (DSA) and Elliptic Curve Digital Signature Algorithm (ECDSA)", which are hereby incorporated by reference, then the requirement for a random number 251a (such as value "k" or "r") can be optionally omitted. In exemplary embodiments, module 101 and CU 113 can utilize deterministic ECDSA 158, such that the requirement for random number 251a derived and subsequently transmitted along with the digital signature 319 can be omitted. However, due to interoperability and standards supported by remote hosts and nodes, such as potentially server 105, the use of a random number 251a can be required. Random number 251a can be generated by CU 113 using steps 251 depicted and described in connection with FIG. 2b above, where a CU 113 can utilize a noise amplification memory 113a.

In order to output a digital signature 319, a signing process 318a can input module public key 172, cryptographic parameters 126a, and module provider private key 121 into digital signature algorithm 141d. Note that module public key 172 comprises the data input in signing process 318, such that the module public key 172 a signature for module public key 172 can be created using a private key and the signature can be subsequently verified using a public key. If a non-deterministic version of the signature algorithm is being used, then a random number 251a can also be input into digital signature algorithm 141d, as depicted in FIG. 4a. Although the signing process 318a is depicted for the signature portion of step 318, the signing process 318a could be utilized for other processes or steps requiring a digital signature in the present invention. For example, a CU configuration unit 104 can create a digital signature 309 in a step 308 of FIG. 3a, and in this case a private key for unit 104 (instead of module private key 121) and the CU public key 111 (instead of module public key 172) would be input into the digital signature algorithm 141d. Other possibilities for generating a digital signature exist as well without departing from the scope of the present invention.

For embodiments where a digital signature algorithm 141d is utilized by a CU 113 in a non-deterministic mode, similar to the exemplary signing process 318a in FIG. 4a, then a record of every value of "k" or "r" utilized by CU 113

could preferably be recorded in table **188** (shown in FIG. **1e**) when used with a given module private key **173** or CU private key **112**. In other words, before every signature operation, CU **118** could first verify that an associated input value of “k” or “r” has not been previously utilized with private key by querying table **188**. If the value of “k” or “r” has been utilized previously with the private key, the CU **113** can reject performing a signature operation and request a different input value of “k” or “r”. If the value of “k” or “r” has not been utilized previously with the private key, the CU **113** can record the value of “k” or “r” in table **188** and subsequently generate a digital signature using exemplary inputs such as those shown in FIG. **4a**. If table **188** is flushed or contains errors for operating digital signature algorithm **141d** in non-deterministic mode, then CU **113** can expire module private key **173** and process a new module private key **173** using the steps in FIG. **3b** and receive a new certificate **122a** using a new module public key identity **170**. FIG. **4b**

FIG. **4b** is a flow chart illustrating exemplary steps for verifying a digital signature using a public key, parameters, and data input, in accordance with exemplary embodiments. As discussed above, digital signatures can be useful for verifying the identity of a node communicating over a network, such as network **107** in FIG. **1a**. Step **320** in FIG. **3b** includes verifying a digital signature **319**, and FIG. **4b** illustrates an exemplary embodiment of the portion of step **320** for verifying digital signature **319**, which can comprise verifying process **320a**. In a verifying process **320a**, a digital signature **319** can be output from a digital signature algorithm **141d**, which could comprise an RSA based DSA **167** or an ECC based ECDSA **158**, and other possibilities exist as well. When using a DSA **167** or ECDSA **158** algorithm in non-deterministic mode for a verifying process **318a**, a value of “k” or “r”, which could comprise a random number **251a**, can also be associated with the digital signature **319** and used in generating the digital signature **319** in a prior signing process **318a** above.

When using a DSA **167** or ECDSA **158** in deterministic mode, such as specified in IETF RFC 6979, then the requirement for a random number **251a** (such as value “k” or “r”) can be optionally omitted. In exemplary embodiments, module **101** and CU **113**, plus other elements in FIG. **1a** such as module provider **122**, CA **118**, and M2M service provider network **108** can support deterministic ECDSA **158** for both signing processes **318a** and verifying processes **320a**, such that the requirement for random number **251a** can be omitted. However, due to interoperability and standards supported by remote hosts and nodes, such as potentially server **105**, the use of a random number **251a** can be required.

In order to output a digital signature **319**, a verifying process **320a** can input module public key **172** (which can comprise the data input for step **320**, but other data besides a public key can be verified in the verifying process **320a**), cryptographic parameters **126a**, and module provider public key **120** into digital signature algorithm **141d**. If a non-deterministic version of the signature algorithm is being used, then the random number **251a** can also be input into digital signature algorithm **141d**, as depicted in FIG. **4b**. The random number **251a** along with the module public key **172** (which can comprise the data input) could be received via network **107**. The output of digital signature **319** calculated in a verifying process **320a** can subsequently be compared with a digital signature **319** received via network **107**. If the received digital signature **319** and the calculated digital signature **319** in a verifying process **320a** do not match, then

an error can be return to the party submitting the data input and the data input also rejected from being used in subsequent steps.

Although the verifying process **320a** is depicted for the verifying portion of step **320**, the verifying process **320** could be utilized for other processes or steps requiring a digital signature in the present invention. For example, a CA **118** could receive a digital signature **309** in a step **310** in FIG. **3a**, and CA **118** could verify the CU public key **111** was submitted by the CU configuration unit **104** by using the verifying process **320a**. In this case, CA **118** would use the CU configuration unit public key in order to verify the CA public key **111** was submitted by CU configuration unit **104** and not an imposter. Other possibilities for verifying a digital signature exist as well without departing from the scope of the present invention.

FIG. **5**

FIG. **5** is a graphical illustration of hardware, firmware, and software components for a module, where a cryptographic unit can be integrated with a processor, in accordance with exemplary embodiments. Although CU **113** and noise amplifying memory **113a** are illustrated in FIG. **1c** and FIG. **1e** as being located in a removable storage unit **109**, CU **113** and noise amplifying memory **113a** could be combined with other hardware on a module **101** such that a removable storage unit **109** would not be required. FIG. **5** illustrates an embodiment where the methods and systems contemplated in the present invention can also be utilized by a module without using a storage unit **109**. In other words, a module **101** can omit removable components such as a storage unit **109** while using a cryptographic unit **113** and noise amplifying memory **113a** in order to internally generate and utilize PKI keys. Applications without storage unit **109** may be desirable for (i) industrial uses where module **101** preferably remains hermetically sealed, (ii) high-security uses where potential tampering via eliminating removable components such as a storage unit **109** may be preferred, and other possible applications of the configuration depicted in FIG. **5** are possible as well without departing from the scope of the present invention.

Many of the components for a module **101** in FIG. **5** can comprise the components for a module **101** depicted and described in connection with FIG. **1b**, with the additional elements shown in FIG. **5** and described herein. For example, a data bus **101d** in FIG. **5** can comprise the data bus **101d** described in FIG. **1b**, ROM **101c** in FIG. **5** can comprise ROM **101c** from FIG. **1b** with the additional elements depicted as inserted within ROM **101c** in FIG. **5** of module provider public key **120**, certificate authority public key **131**, certificate **122a**. ROM **101c** in FIG. **5** could operate as a nonvolatile flash memory. Shared memory **109h** could operate in RAM **101e**, such that the shared memory configuration process **201** in FIG. **2c** could be performed each time module **101** boots from an unpowered state. A module **101** can include a processor **101b**, and the processor can include cryptographic unit **113**, a cryptographic unit private key **112**, cryptographic algorithms **141**, a module private key **173**, protected memory **109g**, and a table **188**. Other descriptions for processor **101b** from FIG. **1b** can be applicable for processor **101b** in FIG. **5** as well.

Cryptographic unit **113** within processor **101b** can include the components and functions for a cryptographic unit **113** depicted and described in connection with FIG. **1c**, with the primary difference being cryptographic unit **113** can operate within processor **101b** instead of storage unit **109**. Cryptographic unit **113** within processor **101b** could omit an interface controller **109c**, for example. Further, the bus

65

elements depicted in FIG. 1e such as bus 109d can be replaced by an internal bus within processor 101b. Note that RAM 113e within CU 113 in FIG. 1e can also be utilized when CU 113 operates in processor 101b. CU 113 may normally require internal RAM 113e for securely using cryptographic algorithms 141 inside processor 101b, where the internal RAM 113e can be separate from RAM 101e for processor 101b to prevent general applications and software operating on module 101 from accessing the RAM 113e in CU 113 in processor 101b in FIG. 5. Although not depicted in FIG. 5, processor 101b can also include a cryptographic unit identity 109e such that external parties like module provider 122 and certificate authority 118 can identify the cryptographic unit 113 operating in processor 101b. CU 113 in processor 101b can also be referred to as a “trusted environment” or “protected area” within processor 101b, such that access to CU 113 by software, applications, or firmware on module 101 can be restricted.

As illustrated in FIG. 5, processor 101b can also include protected memory 109g. Exemplary data recorded in non-volatile protected memory 109g depicted in FIG. 1e can be suitable for a processor 101b since the amount of nonvolatile memory required to hold the data can be readily available within current and future processors 101b for a module 101. In an exemplary embodiment, protected memory 109g can require less than 500 KB of memory, which can be readily available on many models of processors for 101b. Processor 101b can record a cryptographic unit private key 112, which can either be derived by CU 113 or loaded by the manufacturer of processor 101b. CU private key 112 in FIG. 5 can be associated with CU public key 111 recorded in a certificate 122b. CU private key 112 can be used by CU 113 in processor 101b for asymmetric ciphering algorithms 141a and digital signature algorithms 141d.

Processor 101b in FIG. 5 can record a module private key 173, where the module private key 173 was derived using steps from FIG. 3b, including a step 250 depicted and described in connection with FIG. 2b. In other words, processor 101b can record and utilize module private key 173 without the module private key 173 (i) being transferred into module 101 or (ii) ever recorded by another entity, thereby increasing the security of module private key 173. Processor 101b can also include table 188, which can be utilized for accessing noise amplifying memory 113a, such as tracking (i) the location and frequency of noise amplifying operations 193, and (ii) samples of noise amplifying memory 113a to utilize for input into hash algorithm 141c in order to generate a noise amplifying memory hash value 198, and (iii) a record of values “k” or “r” used with digital signature algorithms 141d.

As depicted in FIG. 5, a module 101 can include a noise amplifying memory 113a, and the noise amplifying memory 113a could be connected to bus 101d via a noise memory interface 109p. Noise memory interface 109p in FIG. 5 could operate as described above for a noise memory interface 109p in FIG. 1e, with the difference that noise memory interface can access bus 101d. In other words, noise memory interface 109p in FIG. 5 can operate in a manner to intentionally increase memory noise 194 and bit errors recorded in noise amplifying memory 113a. Noise memory interface 109p in FIG. 5 could translate memory addresses received on bus 101d to physical addresses within memory 113a. Although not depicted in FIG. 5, module 101 and processor 101b could utilize a separate bus such as an internal bus 109q to connect noise memory interface 109p to processor 101b, such that other elements in module 101 could not access noise amplifying memory 113a.

66

Other possibilities and configurations are possible as well, without departing from the scope of the present invention, for integrating or configuring a cryptographic unit 113, noise amplifying memory 113a, and/or noise memory interface 109p with a module 101 and without a storage unit 109. In another exemplary embodiment, noise amplifying memory 113a and noise memory interface 109p could be integrated into processor 101b and connected to CU 113 with in internal bus 109q. Although not depicted in FIG. 5, in another embodiment CU 113, noise amplifying memory 113a, noise memory interface 109p, and protected memory 109g could be integrated into a single unit connected to bus 109d, such that CU 113 operates outside of processor 101b but does not operate inside a storage unit 109. In this case, the single unit could be a separate integrated circuit that is soldered onto a motherboard of module 101 during manufacturing of module 101. In another embodiment, CU 113, noise amplifying memory 113a, and noise memory interface 109p could be integrated with ROM 101c in module 101, where ROM 101c can operate as a “flash RAM” (allowing multiple reads and writes through bus 109d). In this case, a memory interface such as system 200 could operate within ROM 101c, such that module 101 and CU 113 could communicate through a shared memory 109h operating in ROM 101c.

FIG. 6

FIG. 6 is a graphical illustration of hardware, firmware, and software components for a module, where a cryptographic unit can be integrated a universal integrated circuit card (UICC), in accordance with exemplary embodiments. For embodiments where module 101 connects with a wireless network 102 including wireless WAN networks such as a public land mobile network operated by a mobile network operator, then module 101 may include a UICC, which is often commonly referred to as a SIM card. Primary features of a UICC or SIM card is that it can record the network access credentials for a module 101 to access a wireless network 102, where the wireless network 102 has provided the credentials. As of 2015 the base credentials commonly in a SIM card are often referred to as an identity comprising an International Mobile Network Identity (IMSI) and a shared secret key K or Ki.

The use of a UICC 109u in the present invention could be in any of a mini, micro, nano, or embedded form format, where the embedded format is typically not removable and soldered onto a circuit board inside module 101. A module 101 could also include a UICC or equivalent functionality when connected to other networks besides a wireless network 102 as well, including wired networks. Module 101 could be manufactured with a slot for which to insert a UICC, such as the equivalent of a first set of electrical pins 109a (not shown) within module 101 to interface with a second set of electrical pins 109a (not shown) for a physical interface 101z within UICC 109u. In another embodiments, a UICC 109u that includes an eUICC 113u can comprise an embedded format that is soldered onto a circuit board in module 101. Module 101 in FIG. 6 could also include a storage unit 109y, which could comprise a regular, removable nonvolatile flash memory storage unit without a CU 113 operating inside the storage unit 109y. Storage unit 109y could comprise an SD card or a micro SD card such as commonly available at electronics retailers in 2015, and other possibilities exist as well for a storage unit 109 without departing from the scope of the present invention. Storage unit 109y could also comprise a solid state drive (SSD) intended to provide functionality equivalent to traditional spinning hard disk drive.

FIG. 6 illustrates an embodiment where the methods and systems contemplated in the present invention can also be utilized by a module 101 that includes a UICC. In other words, a module 101 a UICC 109u can operate as a storage unit 109 (with exemplary components for a storage unit 109 depicted in FIG. 1e), and a separate storage unit 109y without a CU 113 operating inside separate storage unit 109y could also be utilized by module 101. A UICC 109u can include components such as a cryptographic unit 113. Cryptographic unit 113 operating inside UICC 109u can include exemplary components such as an eUICC 113u, a noise amplifying memory 113a, and a noise memory controller 109p in order to internally generate PKI keys in a reasonably secure manner. For embodiments where a UICC 109u is utilized, then the physical interface and electrical pins 109a between UICC 109u and module 101 could comprise an ISO 7816 compatible interface 101z. The interface 101z could be an ISO/IEC 7816-2 interface supporting the transfer of data between UICC 109u and module 101. In exemplary embodiments, UICC 109u could also include an Embedded Universal Integrated Circuit Card (eUICC) 113u, where the function of eUICC 113u could support (A) operations outlined by the GSMA in "Remote Provisioning Architecture for Embedded UICC, Technical Specification, Version 1.0" dated Dec. 17, 2013, which is hereby incorporated by reference in its entirety, and addition to (B) the functionality of an eUICC 113u contemplated herein. However, the inclusion of an eUICC 113u functionality within UICC 109u is not required and eUICC 113u could optionally be omitted from operating within a UICC 109u.

Applications where an eUICC 113u can be included in cryptographic unit 113 can include deployments or installations where a module provider 122 can prefer to change a wireless network 102 that a module 101 connects with, as illustrated in FIG. 1a, without physically changing the SIM card or UICC. Wireless networks 102 over licensed radio spectrum and supporting applications such as mobile phones has historically required the distribution and installation of SIM cards in devices in order to connect with the wireless network. An eUICC 113u can allow a device to connect "natively" (i.e. not in a roaming configuration) with a wireless network 102, such that costs can be minimized and the UICC 109u in which the eUICC 113u operates does not need to be changed in order to connect natively with a new wireless network 102. In other words, during the operational lifetime of an eUICC 113u in UICC 109u, an eUICC 113u could record multiple different keys K, where different keys K could be associated with different wireless networks 102. A module provider 122 could have thousands of modules 101 or more deployed with monitored units 119, and manually changing out a SIM card may not be economical. But, with an eUICC 113u as specified by the GSMA standard cited above and related standards, a module provider 122 can change the credentials used by a UICC 109u operating in a module 101 for connecting with a wireless network 102 remotely and without manually changing a SIM card or UICC.

Applications with a UICC 109u may be desirable for (i) industrial uses where module 101 preferably remains hermetically sealed, (ii) high-security uses where potential tampering via eliminating removable components such as a storage unit 109 may be preferred, or (iii) module provider 122 may not know which wireless network 102 may be best suited for a module 101 before deployment or distribution to an end-user, and other possible applications of the configuration depicted in FIG. 6 are possible as well without departing from the scope of the present invention. In an

exemplary embodiment illustrated in FIG. 6, UICC 109u can also include a cryptographic unit 113 and a differential fault protection unit 601, in addition to the physical interface 101z discussed above. In addition, although a differential fault protection unit 601 is depicted with a UICC 109u in FIG. 6, a differential fault protection unit 601 could be used within other embodiments depicted above, such as with a storage unit 109 in FIG. 1e, a module 101 in FIG. 1b and FIG. 5, and other possibilities exist as well.

Cryptographic unit 113 operating in a UICC 109u can include an eUICC 113u, a noise amplifying memory 113a, protected memory 109g, a read only memory 113c, a noise memory controller 109p, an internal bus 109d, a processor 113b, and RAM 113e. As contemplated herein, UICC 109u can comprise an embodiment of storage unit 109, and consequently the various exemplary components within UICC 109u can operate in a manner described in previous figures above, such as in connection with FIG. 1c and FIG. 1e, etc. Although not depicted in FIG. 6, a UICC 109u or CU 113 could also include a cryptographic unit identity 109e, such that CU 113 or UICC 109u could be uniquely identified separately from module 101 operating with a module identity 110. Although depicted as a separate element within UICC 109u, CU 113 could optionally be combined with a UICC 109u such that exemplary components within CU 113 could operate within UICC 109u and in this case the UICC 109u can also perform the functions of CU 113. Other possibilities exist as well for the location of components within an exemplary UICC 109u depicted in FIG. 6, such as (i) noise amplification memory 113a being located inside UICC 109u but outside CU 113, (ii) eUICC 113u also being located outside of CU 113 but elsewhere within UICC 109u, and/or (iii) differential fault protection unit 601 being located in CU 113.

Processor 113b within UICC 109u can comprise an embedded processor with capabilities similar to processor 131b depicted and described in connection with FIG. 1e, where processor 131b could internally manage the function and operation of UICC 109u by the execution of program instructions such as machine code. CU 113 operating inside UICC 109u could also include an internal data bus 109d, thereby allowing the internal components of CU 113 within UICC 109u as depicted to communicate with each other. Although internal data bus 109d is depicted within CU 113, internal data bus 109d could also connect components in UICC 109u such as physical interface 101v and differential fault protection unit 601. CU 113 operating within UICC 109u can include other elements depicted and described in previous figures, without departing from the scope of the present invention. For example, CU 113 could include a clock 160b which could be driven by a clock 160 (shown in FIG. 1c) within module 101, where physical interface 101v includes a clock input electrical connection. In addition UICC 109u could include an interface driver 109b to manage the communication with module 101 through physical interface 101v.

UICC 109u can include an eUICC 113u. An eUICC 113u can provide the equivalent functionality as a physical UICC, with the exception that over time an eUICC 113u can record data and provide functionality such that UICC 109u can operate a different physical UICC cards without a user or module provider 122 physically changing the UICC 109u. Definitions for a physical UICC are included in ETSI TR 102 216 and ETSI TS 102 221 V11.0.0, and other examples for the use of a physical UICC in mobile phones and M2M modules exist as well. An eUICC 113u in FIG. 6 can support exemplary requirements for an eUICC outlined in ETSI TS

103 383 v12.1, entitled “Smart Cards; Embedded UICC; Requirements Specification,” which is herein incorporated by reference in its entirety. In other words, an eUICC 113u can operate as a “virtualized” UICC in a reasonably secure manner, such that data operations and input/output to UICC 109u related to authentication and ciphering of data between module 101 and wireless network 102 can be provided by an eUICC 113u.

An eUICC 113u can include an eUICC profile 113g, a set of cryptographic algorithms 141, a key K, a random number 251a, and a derived key 129b. Derived key 129b can operate as a symmetric key 127 as described above in FIG. 1c, or a derived key 129b in eUICC 113u could be optionally omitted. The combination of cryptographic algorithms 141, module private key 173, and a random number 251a can be used in several possible ways to (i) securely receive various encrypted eUICC profiles 113g over time, and (ii) decrypt the profiles and read different keys K in plaintext form. Exemplary embodiments include (A) module private key 173 recorded in ROM 113c could be input into the cryptographic algorithms 141 operating in eUICC 113u, such as using module private key 173 for the process of decrypting eUICC profile 113g. Or, (B) module private key 173 could be input into a key derivation function 141e along with other data to generate derived key 129b. Derived key 129b can be used to decrypt eUICC profile 113g, where eUICC profile 113g was received from an eUICC subscription manager (not shown) and also encrypted with the same value for derived key 129b.

In an exemplary embodiment, eUICC 113u can use a CU private key 112 instead of a module private key 173 in order to read a key K from an eUICC profile 113g, but in either case the private keys can be internally derived with a high level of security using a noise amplifying memory 113a and the steps depicted for using the noise amplifying memory in FIGS. 3a and 3b, including the option of using a noise memory interface 101p. Note that industry standards for an eUICC 113u can require access to a random number 251a for using cryptographic algorithms 141 in eUICC 113u, and embodiments in the present invention support the generation of random number 251a such as through the exemplary steps 251 in FIG. 2b above.

As contemplated herein, an eUICC profile, such as the exemplary eUICC profile 113g can be similar to profiles for an eUICC contemplated in ETSI specification TS 103 383 v12.2.0 and related standards. The profile 113g could be received by module 101 in an encrypted format, such as ciphered with a symmetric ciphering algorithm 141b and a symmetric key 127, where the symmetric key 127 could comprise a derived key 129b. Or, the symmetric key 127 could be sent to eUICC 113u as data ciphered with (i) an asymmetric ciphering algorithm 141a and (ii) either module public key 172 or CU public key 111. eUICC profile 113g could be subsequently decrypted and recorded within an eUICC 113u operating in a UICC 109u. Profile 113g could include network access credentials for module 101 to access wireless network 102, such as an IMSI value and a key K. eUICC 113u can decrypt profile 113g using cryptographic algorithms 141 and key 173 or key 112 in order to read key K, and module 101 can subsequently access wireless network 102 using key K.

Further, the secure operation of an eUICC 113u can require any of (i) securely recording private key 112, (ii) internally deriving private keys such as the exemplary module private key 173, (iii) creating symmetric keys 127 such as the exemplary derived key 129b, and (iv) the ability to generate a random number 251a. In an exemplary

embodiment, private key 112 within eUICC 109u can be securely internally derived using steps 300. In another embodiment, private key 173 could be subsequently changed after UICC 113u receives a signal 208 by using steps 250, 316, and 317 in FIG. 3b, where CU 113 derives a new private key 173 for use by an eUICC 113u after receiving the signal 208. Derived keys 129b can depend on private keys such as key 112 and key 173. Random number 251a can be calculated or derived using a step 251 in FIG. 2b.

Other possibilities exist as well for the operation and function of an eUICC 113u operating within a UICC 109u. Although the various industry standards for an eUICC 113u continue to evolve, a standard eUICC 113u for the foreseeable future is expected to continue relying on the use of private keys for receiving and decrypting profiles 113g. An eUICC 113u operating within CU 113 can use either a module private key 173 or a CU private key 112 in order to decrypt a profile 113g, where exemplary uses and sources of module private key 173 and CU private key 112 are depicted and described in connection with FIGS. 1a, 1c, 1e, 2b, 3a, and 3b in the present invention.

Differential fault protection unit 601 can include components and logic for increasing the resistance of UICC 109u or storage unit 109 to attack by fault analysis or differential fault analysis, as well as increasing resistance to side channel attacks. A potential attacker of the cryptographic system within CU 113 could attempt several different means, which can vary depending on if (i) the attacker has physical access to CU 113 in the form of holding storage unit 109 or UICC 109u, (ii) the attacker has physical access to a module 101 which contains CU 113, or (iii) the attacker accesses module 101 remotely over a network such as network 107 illustrated in FIG. 1a. A differential fault protection unit 601 can assist in resisting attacks in multiple ways.

Differential fault protection unit 601 can intentionally add both (i) a fixed delay in transmitting responses from CU 113 to module 101, such as an exemplary 500 milliseconds, plus (ii) a random delay of approximately +/-300 milliseconds. The random component could be distributed according to a normal distribution, a uniform distribution, or a pareto distribution, and other distributions are possible as well. In exemplary embodiments, differential fault protection unit (DFPU) 601 would change both the fixed delay and random delay components frequently over time, such as with every output from CU 113. A fixed component can intentionally reduce the frequency that CU 113 would respond to input such as signal 208 in FIG. 2c, in the case that CU 113 receives multiple requests in a relatively short period of time or within a relatively short count of clock cycles from a clock 160b. In other words, DFPU 601 can slow or temporarily halt input requests if the frequency of the requests exceeds a threshold value, and in this manner the speed of potential side-channel attacks could be slowed. In this manner, a DFPU 601 can also increase the fixed delay if the frequency of input is higher than a specified tolerance level. Other possibilities exist as well for the values of a fixed and random delay to add for a CU 113 to respond to input in a DFPU 601 without departing from the scope of the present invention.

Differential fault protection unit 601 can also include an error check on data output from CU 113. In an exemplary embodiment, differential fault protection unit 601 can control CU 113 such that all input and output with CU 113 from external sources, such as via electrical pins 109a, first passes through DFPU 601. In an exemplary embodiment, DFPU 601 can request CU 113 to perform all operations twice,

whenever input from module **101** is received. For example, if module **101** requests a digital signature **319** from CU **113** using CU private key **112** recorded in CU **113**, DFPU **601** can (i) submit the request to CU **113** a first time and record a first result in memory such as memory **113e** or memory **109g**, then (ii) submit the request to CU **113** a second time and record the second result in memory, and then (iii) compare the first result with the second result, and then (iv) output the first result through electrical pins **109a** only if the first result and the second result are equal. In this manner, DFPU **601** can make storage unit **109** or CU **113** resistant to attacks via the intentional introduction of errors from changing the physical operating environment of CU **113** outside of normal operating specifications for CU **113**. Various potential attacks resisted in this manner through DFPU **601** include exposing CU **113** to (i) an input voltage with higher, lower, or higher variability than specified, (ii) temperature or cycles of temperature higher or lower than specified, and/or (iii) ionizing radiation or similar exposure to high levels of radio-frequency interference.

FIG. **7a**

FIG. **7a** is an illustration of a certificate for a module public key, in accordance with exemplary embodiments. Public and private keys in system **100** can utilize PKI techniques other than RSA, such as a module public key **172** based on elliptic curve cryptography (ECC) illustrated in FIG. **7a**. One benefit of using ECC is that an equivalent level of security can be obtained for a much smaller key length. Also, energy may be conserved using ECC algorithms **154** compared to RSA algorithms **153**. Smaller key lengths save bandwidth, memory, processing resources, and power, which are all valuable for a module **101** to conserve a battery **101k** and usage of radio-frequency spectrum. For example, an ECC key length of 283 bits can provide security similar to an RSA key length of approximately 2048 bits. Module public key **172** can comprise an ECC key in an X.509 certificate, as illustrated in FIG. **7a**. The values to determine an elliptic curve defining equation could be stored in parameters **126a**, and the defining equation could also optionally be disclosed.

Certificate **122a** could include a signature **125**, where signature **125** can be signed using ECC signature techniques, such as the Elliptic Curve Digital Signature Algorithm (ECDSA) **158** with a secure hash such as SHA256 **156**. In order to generate signature **125**, the private key associated with either CA **118** or module provider **122** may also be an ECC-based private key. Note that the public key **172** in a certificate **122a** could use a different asymmetric ciphering algorithm **141a** than the algorithm used for signing, such that the public key **172** can be an ECC key, while the signature **125** could be generated with RSA algorithm **153** and/or key. Certificate **122a** may also include parameters **126a**, where parameters **126a** can specify an elliptic curve utilized with the module public key **172**. Parameters **126a** could also include the start and end times **133** for the validity of either public key **172** or certificate **122a**. Other parameters **126a** can be utilized in a certificate **122a** as well, and parameters **126a** may specify values that are not included or external to a certificate **122a**.

Certificate **122a** illustrated in FIG. **7a** also illustrates an exemplary embodiment of the present invention. Over the lifetime of a module **101**, which could be a decade or longer, multiple module public keys **172** may be utilized. The potential use of multiple different module public keys **172** include (i) the expiration of a certificate **122a** (including expiration of a public key associated with a certificate authority used in signature **125**), (ii) a need to change an

elliptic curve specified in a parameters **126a**, (iii) adding a new public/private key pair for connection with a different wireless network **102**, (iv) as increasing a key length utilized in a public/private key pair, (v) the transfer of ownership or control of module **101**, and/or (vi) module **101** connecting to a new server that utilizes a different asymmetric ciphering algorithm (i.e. RSA instead of ECC). Other possibilities exist as well for reasons a module to derive a new module public key **172**. Note that the multiple module public keys **172** may also be utilized concurrently, such that (i) a first module public key **172** in a first certificate **122a** can be utilized with a first server **105**, and (ii) a second module public key **172** (possibly derived using a different set of parameters **126a** including using a different elliptic curve) can be utilized with a second server **105** and/or wireless network **102**.

In either case of (i) module **101** using multiple module public keys **172** concurrently, or (ii) module **101** using different module public keys **172** in sequence, a certificate **122a** can preferably include a module public key identity **170** to specify the module public key **172** utilized in a certificate **122a**. As illustrated in FIG. **7a**, the module public key identity **170** could be included in the "Common Name" (CN) field, and the module identity **110** can be included in the "Organizational Unit" (OU) field. Alternatively, the module public key identity **170** and module identity **110** can be appended together and used in the CN field. In this manner and according to preferred exemplary embodiments, a module public key identity **170** is utilized with both a module identity **110** and a module public key **172** within a certificate **122a**. Also, as noted previously herein, the use of a certificate **122a** may optionally be omitted, such that module **101** and server **105** share public keys without using certificates **122a**. The module identity **110**, or a value associated with the module identity **110** can also be included in certificate **122a**, such as the "Common Name" (CN) field of a X.509 certificate **122a**, as illustrated in FIG. **7a**. A signature portion of a certificate **122a** or **122b** below can also include a value for "r" or "k" used with a non-deterministic use of a digital signature algorithm **141d**, such as depicted and described in connection with FIGS. **4a** and **4b**.

Note that the use of a certificate **122a** is not required for the format of a public or shared key, and the public keys could optionally omit a signature from a certificate authority **118**. In this case, the public keys such as module public key **172** could be recorded in the format of a string, without the additional fields illustrated in FIG. **7a**. Other possibilities exist as well without departing from the scope of the present invention.

FIG. **7b**

FIG. **7b** is an illustration of a certificate for cryptographic unit public key, in accordance with exemplary embodiments. A cryptographic unit **113** using a CU identity **109e** can include a CU private key **112**, where the CU private key **112** can be associated with a CU public key **111**. Various entities within system **100** can utilize a certificate for a CU **113** with CU public key **111**, such as module provider **122**. For example, module provider **122** or an end user for module **101** may receive a shipment of a storage unit **109**, with CU **113** inside the storage units. Module provider **122** or end user could verify the CU identity **109e** of CU **113** using a CU certificate **122b**. Module provider **122** or an end user could (i) create a challenge or nonce for the CU **113** operating in storage unit **109** to sign, (ii) receive a digital signature from the CU **113**, where the CU **113** used the CU private key **112** and a digital signature algorithm **141d** such as shown in FIG.

4a, and (iii) subsequently verify the digital signature using a CU public key **111** recorded in a certificate **122b**. In this manner, module provider **122**, and end user, or other nodes in a system **100** could verify the identity of CU **113** by trusting the certificate authority **118** which signed the certificate **122b**.

Other examples exist as well for the benefits and applications of a CU certificate **122b** without departing from the scope of the present invention. In other exemplary embodiments, CU **113** can derive module PKI keys **174** and subsequently send the module public key **172** and module identity **110** along with a digital signature **319**, where the digital signature **319** was processed using the CU private key. Parties receiving the module public key **172** could verify the module public key **172** is authentic by verifying the digital signature **319** using the CU public key **111** recorded in a CU certificate **122b**. In other words, a CU certificate **122b** can also be used for the cases where (A) a module certificate **122a** does not yet exist or may not be accessible and (B) a party receiving the module public key **172** with a module identity **110** needs to verify the module public key **172** is authentic.

A cryptographic unit certificate **122b** can include an expiration time **133**. In exemplary embodiments, the expiration time **133** for CU certificate **122b** can be longer than the expiration time **133** for a module public key **172**. A reason is the CU private key **112** may “underpin” or support the subsequent derivation of multiple module public keys **172** over time, and thus a longer expiration time for CU certificate **122b** can be preferred in some exemplary embodiments. As depicted in FIG. **7a** and FIG. **7b**, a CU public key **111** can have a longer key length than module public key **172** since the expiration time **133** of CU public key **111** can be longer than module public key **172**. As depicted in FIG. **7b**, the CU identity **109e** can be used in the Organizational Unit field (OU) of a certificate, and a sequence number **702** can be used for the common name (CN) field. The sequence number **702** can track different keys used by CU **113** with CU ID **109e**, such as a first public key used for a first asymmetric algorithm **141a** (such as RSA 153) could have a first sequence number, a second public key used for a second asymmetric algorithm **141a** (such as ECC 154) could have a second sequence number, a third public key used for a first digital signature algorithm **141d** could have a third sequence number, etc. Other possibilities exist as well for the use of CN, ON, CU ID **109e**, and sequence numbers fields or data within a certificate without departing from the scope of the invention.

As depicted in FIG. **7b**, CU certificate **122b** can include (i) CU public key **111** and (ii) a set of parameters **126b**. CU certificated **122b** can also include a digital signature **184** from CA **118**, where CA **118** used a CA private key **132** to create the digital signature **184**. In this manner, parties reading the CU certificate **122b** could verify the data by comparing digital signature **184** in the certificate **122b** with an independently calculated value for digital signature **184** and verifying the two values match. For the cases where a non-deterministic use of digital signature algorithms **141d** is utilized, then CU certificate **122b** could also include values of “k” or “r”, and these values are not reused for a given private key in exemplary embodiments.

CONCLUSION

Various exemplary embodiments have been described above. Those skilled in the art will understand, however, that

changes and modifications may be made to those examples without departing from the scope of the claims.

The invention claimed is:

1. A method for an embedded universal integrated circuit card (eUICC) in a module to receive and decrypt an encrypted profile, the method comprising:

recording, by the eUICC in the module, (i) a first private key, wherein the first private key is associated with a first public key, and (ii) a plurality of second private keys, and (iii) a corresponding plurality of second public keys, wherein the module comprises at least one of a mobile phone, a computing device with a radio and a user interface, a laptop computer, and a tracking device, and wherein the eUICC comprises a cryptographic unit within the module connected via a data bus;

receiving, at the module, a challenge from a server; processing, by the eUICC in the module, a first digital signature for the challenge using the first private key; sending, by the module, the first digital signature to the server;

receiving, at the module and from the server, a signal to identify a second public key from the plurality of second public keys, wherein the signal is received over a secure connection via a wireless network;

selecting, by the eUICC, the second public key, wherein the selected second public key is associated with a corresponding second private key;

receiving by the eUICC in the module, a nonce as a user input;

processing, by the eUICC in the module, a second digital signature for at least the selected second public key and the nonce, wherein the second digital signature is processed using the first private key;

sending, by the module, the second digital signature and the second public key to the server;

receiving, by the module and from the server, a set of cryptographic parameters;

receiving, at the module and from the server, the encrypted profile for the eUICC and the set of cryptographic parameters, wherein the encrypted profile is ciphered with a symmetric ciphering key;

deriving, by the eUICC in the module, the symmetric ciphering key from (i) an elliptic curve Diffie Hellman (ECDH) key exchange, using at least, in part, the second private key, and (ii) a key derivation function comprising an American National Standards Institute (ANSI) standard X-9.63, wherein the eUICC derives the symmetric ciphering key for the received set of cryptographic parameters, and wherein the symmetric ciphering key comprises a 128 bit length key for an Advanced Encryption Standard (AES) symmetric ciphering algorithm; and,

decrypting, by the eUICC in the module, the encrypted profile using the derived symmetric ciphering key in order to record a set of network access credentials.

2. The method of claim 1, wherein the nonce comprises at least one of a pseudo random string of characters and pseudo random string of numbers.

3. The method of claim 1, wherein, recording, by the eUICC, comprises the eUICC writing a memory address for a nonvolatile memory to a memory interface, wherein the eUICC can read from the memory address.

4. The method of claim 1, wherein the second public key has an associated identity for the second public key, wherein the signal includes the identity for the second public key, and

wherein the second public key and the corresponding second private key are selected by the eUICC using the identity.

5. The method of claim 1, wherein the secure connection comprises a Transport Layer Security session between the module and a network associated with the server, and wherein the secure connection is established before the module receives the challenge from the server.

6. The method of claim 1, wherein the module uses a device driver for the eUICC in order to communicate with the eUICC via the data bus.

7. The method of claim 1, wherein a configuration unit (i) derives the first private key externally from the eUICC, and (ii) loads the first private key into the eUICC, and wherein the corresponding first public key is recorded by the eUICC with a certificate.

8. The method of claim 1, wherein the cryptographic unit operates within a trusted execution environment (TEE) within a processor for the module.

9. A module for receiving and decrypting an encrypted profile, the module comprising:

an embedded universal integrated circuit card (eUICC) in the module that decrypts the encrypted profile using a symmetric ciphering key, and that records a set of network access credentials from the decrypted profile;

a first processor in the module that operates a module program to communicate with the eUICC in the module, and that sends an identity to a server via a wireless network;

a radio that receives a challenge from the server through the wireless network, wherein the first processor (i) sends a first digital signature and a second digital signature through the radio to a server, in order to authenticate the eUICC with the server, and (ii) receives a signal, a set of cryptographic parameters, and the encrypted profile from the server via the radio;

a memory in the module that records the first digital signature for the received challenge;

a protected memory in the eUICC that records (i) a first private key, (ii) a plurality of second public keys, and (iii) a corresponding plurality of second private keys, and (iii) the identity;

an interface of the eUICC that receives (i) the encrypted profile, and (ii) the signal for selecting a second public key from the plurality of second public keys, wherein the selected second public key is associated with a corresponding second private key, and wherein the first processor operates the module program to communicate with the eUICC using the interface;

a second processor in the eUICC that:

(i) processes at least, in part, the first private key to calculate:

(a) the first digital signature, and,
 (b) the second digital signature for at least, in part, the selected second public key, and

(ii) derives the symmetric ciphering key with:

(c) an elliptic curve Diffie Hellman (ECDH) key exchange, using at least, in part, the second private key,

(d) a key derivation function comprising an American National Standards Institute (ANSI) standard X-9.63,

(e) the set of cryptographic parameters, wherein the symmetric ciphering key comprises a 128 bit length key for an Advanced Encryption Standard (AES) symmetric ciphering algorithm; and,

a user interface that receives a nonce as a user input, wherein the second processor processes the second digital signature for at least the selected second public key and the nonce.

10. The module of claim 9, wherein the nonce comprises at least one of a pseudo random string of characters and pseudo random string of numbers.

11. The module of claim 9, further comprising a memory interface for the protected memory, wherein the eUICC records by writing a memory address for the protected memory to the memory interface, and wherein the eUICC can read from the memory address for the protected memory.

12. The module of claim 9, wherein the protected memory in the eUICC records a public key identity for the second public key, wherein the received signal includes the public key identity for the second public key, and wherein the second public key and the corresponding second private key are selected by the eUICC using the received signal with the received public key identity for the second public key.

13. The module of claim 9, wherein, recording in the memory of the module, comprises the first processor writing a memory address for the memory to a memory interface, wherein the second processor receives data from the memory address.

14. The module of claim 9, wherein a configuration unit for the eUICC (i) derives the first private key externally from the eUICC, and (ii) loads the first private key into the eUICC, and wherein a corresponding first public key is recorded by the eUICC with a certificate.

15. The module of claim 9, wherein the module comprises at least one of a mobile phone, a computing device with a radio and a user interface, a laptop computer, and a tracking device, and wherein the eUICC comprises a cryptographic unit within the module connected via a data bus.

16. The module of claim 9, wherein the first processor includes the second processor in a trusted execution environment (TEE) within the first processor.

* * * * *