



US 20160091769A1

(19) **United States**(12) **Patent Application Publication**  
**Rozbicki**(10) **Pub. No.: US 2016/0091769 A1**(43) **Pub. Date: Mar. 31, 2016**(54) **WIRELESS POWERED ELECTROCHROMIC WINDOWS****Publication Classification**(71) Applicant: **View, Inc.**, Milpitas, CA (US)(72) Inventor: **Robert T. Rozbicki**, Germantown, TN (US)(21) Appl. No.: **14/962,975**(22) Filed: **Dec. 8, 2015**(51) **Int. Cl.****G02F 1/163** (2006.01)**E06B 9/24** (2006.01)**H02J 5/00** (2006.01)(52) **U.S. Cl.**CPC ..... **G02F 1/163** (2013.01); **H02J 5/005** (2013.01); **E06B 9/24** (2013.01); **E06B 2009/2464** (2013.01)**Related U.S. Application Data**


(63) Continuation of application No. 14/735,016, filed on Jun. 9, 2015, which is a continuation of application No. 12/971,576, filed on Dec. 17, 2010, now Pat. No. 9,081,246.

(60) Provisional application No. 61/289,319, filed on Dec. 22, 2009.

(57)

**ABSTRACT**

Electrochromic windows powered by wireless power transmission are described, particularly, the combination of low-defectivity, highly-reliable solid state electrochromic windows with wireless power transmission. Wireless power transmission networks which incorporate electrochromic windows are described.






FIGURE 1




FIGURE 2A




FIGURE 2B




FIGURE 2C




FIGURE 2D




FIGURE 2E

## WIRELESS POWERED ELECTROCHROMIC WINDOWS

### CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation application of U.S. patent application Ser. No. 14/735,016, filed on Jun. 9, 2015 and titled "WIRELESS POWERED ELECTROCHROMIC WINDOWS," which is a continuation application of U.S. patent application Ser. No. 12/971,576, filed on Dec. 17, 2010 and titled "WIRELESS POWERED ELECTROCHROMIC WINDOWS," which is a non-provisional application of and claims priority to U.S. Provisional Application Ser. No. 61/289,319, filed on Dec. 22, 2009 and titled "WIRELESS POWERED ELECTROCHROMIC WINDOWS;" all of which are hereby incorporated by reference in their entirety and for all purposes.

### FIELD OF THE INVENTION

[0002] The invention relates generally to the field of electrochromic (EC) devices coupled with wireless power transmission technology. More specifically the invention relates to EC windows powered by wireless power transmission technology.

### BACKGROUND

[0003] Electrochromism is a phenomenon in which a material exhibits a reversible electrochemically-mediated change in an optical property when placed in a different electronic state, typically by being subjected to a voltage change. The optical property is typically one or more of color, transmittance, absorbance, and reflectance. One well known EC material, for example, is tungsten oxide ( $\text{WO}_3$ ). Tungsten oxide is a cathodic EC material in which a coloration transition, transparent to blue, occurs by electrochemical reduction. While electrochromism was discovered in the 1960's, EC devices and apparatus and systems containing EC devices have not begun to realize their full commercial potential.

[0004] Electrochromic materials may be incorporated into, for example, windows. One drawback of conventional EC windows is that the power used, although small in amount, requires a hard wired connection to a power source of a building. This creates problems when builders are installing, for example, a large number of windows in an office building. Having to deal with hard wiring required for windows is just another impediment that a builder must deal with in the long list of items necessary to build a modern structure. Also, although EC windows offer an elegant solution in the management of heat zones in a modern building, for example, when controlled by an automated heat and/or energy management system, EC windows that require hard wired power sources create impediments to integration into automated energy management systems. Thus the additional installation costs and risks associated with wires will slow down the adoption of EC windows in new construction and may prevent retrofit applications in many cases because retrofit requires additional installation of wiring infrastructure for the new EC windows.

### SUMMARY OF INVENTION

[0005] Electrochromic devices, particularly EC windows, powered by wireless power transmission are described. The

combination of low-defectivity, highly-reliable EC windows with wireless power transmission is an aspect of the invention.

[0006] Scalable EC window technology that integrates wireless power transmission technology to create a wirelessly-powered EC window is described. Such technology may optionally include environmental sensors, wireless control and/or in some aspects photovoltaic power. The invention enables full benefits of EC window technology to be realized at national level savings of quads of energy and hundreds of tons of carbon annually. New construction will benefit greatly from wirelessly powered EC windows, and there is particular advantage in retrofit applications, where installing wires for replacement windows is problematic.

[0007] One embodiment is an EC device powered by wireless power transmission. In one embodiment, the EC device is an EC window. Wireless power transmission is utilized to provide power to one or more EC device's in an EC window. Wireless power can be used to directly power an EC device in the window or, in an alternative embodiment, charge an internal battery which powers the EC transitions and/or EC states of the EC device(s) in the window. In one embodiment, wireless power transmission is received by a receiver that powers more than one EC window. Wireless power can also be used to power other active devices which are part of, or directly support, the EC window: for example, motion sensors, light sensors, heat sensors, moisture sensors, wireless communication sensors and the like. Wireless communication technology can also be used to control the wirelessly powered EC window.

[0008] Wireless power transmission of any suitable type can be used in conjunction with EC windows. Wireless power transmission includes, for example but not limited to, induction, resonance induction, radio frequency power transfer, microwave power transfer and laser power transfer. In one embodiment, power is transmitted to a receiver via radio frequency, and the receiver converts the power into electrical current utilizing polarized waves, for example circularly polarized, elliptically polarized and/or dual polarized waves, and/or various frequencies and vectors. In another embodiment, power is wirelessly transferred via inductive coupling of magnetic fields. In a specific embodiment, power is wirelessly transferred via a first resonator (a coil that converts electrical energy, e.g. AC, running through the coil into a magnetic field), which receives power from an external supply hard wired to the first resonator, and a second resonator (a coil that is coupled to the magnetic field and thereby produces electrical energy via induction), which acts as the receiver by producing an electric current or potential via coupling of the magnetic resonance fields of the first and second resonators. Although embodiments utilizing magnetic induction need not necessarily use resonance coupled magnetic fields, in those that do, near-field resonance from localized evanescent magnetic field patterns is a relatively efficient method of wireless power transfer.

[0009] In one embodiment, the window receiver is an RF antenna. In another embodiment the RF antenna converts RF power into an electrical potential used to function the EC device. In another embodiment the receiver is a second resonator which is resonance coupled to a first resonator, configured so that power is transmitted wirelessly from the first resonator to the second resonator. The second resonator converts the wirelessly transferred power into electricity to power the EC window.

[0010] Typically the receiver, whether RF antenna or secondary resonance coil, is located in the frame of the EC window, e.g., near the outer seal of the IGU and/or somewhere in the window frame so as not to obscure the viewable area through the glass of the IGU. Thus, in particular embodiments, the receiver is of relatively small dimensions. In one embodiment, the receiver is of sufficiently small dimensions that the user of the window may not recognize the receiver as being part of the window, but rather the receiver is hidden from the view of the user.

[0011] In one embodiment, the wireless power transmission is carried out via a wireless power transmission network which includes one or more power nodes for transmitting power to window receivers in particular areas. Depending on the building or need, one or more, sometimes several nodes are used to form a network of power nodes which feed power to their respective window receivers. In one embodiment, where radio frequency is used to transmit power and there are more than one power node, there are more than one frequency and/or polarization vector used in the power nodes, so that different levels or types of power are transferred from the various nodes to windows having different power needs. In another embodiment, where magnetic induction is used for wireless power transfer, there also are one or more power nodes, but in this embodiment, the power nodes are themselves resonators. For example, in one embodiment, a first resonator, which receives power via a power supply, is resonance coupled to a second resonator, and the second resonator is resonance coupled to a third resonator, for example that delivers power to an EC window. In this way, the second resonator acts as a power node in a power transfer network from the first resonator, to the second resonator, to the third resonator, the third resonator acting as the receiver and transmitting power to the EC window via conversion of magnetic field to electrical power.

[0012] Another aspect of the invention is a method of powering an EC device, the method including: i) generating and/or transmitting a wireless power to a receiver, said receiver configured to convert the wireless power to electrical energy (e.g., electrical current or potential) used to power the EC device; and ii) delivering the electrical energy to the EC device. In one embodiment, the EC device is an EC window as described above. In another embodiment, i) is performed via RF; in another embodiment, i) is performed via magnetic induction. In one embodiment, the electrical energy from the receiver is used to charge a battery, which in turn is used to power to the EC device(s) of the EC window. In one embodiment, a single window has a wireless power receiver, and the electrical energy created by the receiver is used to power more than one EC window, directly and/or by charging a battery or system of batteries associated with the windows.

[0013] Another aspect of the invention is a wireless power transmission network including: i) a wireless power transmitter configured to transmit a wireless power; ii) a power node, configured to receive the wireless power and relay the wireless power; iii) a receiver configured to receive the relayed wireless power and convert the wireless power to an electrical energy; and, iv) an EC device configured to receive the electrical energy to power a transition between optical states and/or maintain an optical state. The electrical energy can be received by the EC device either directly or indirectly. In one embodiment, the electrical energy is received directly from the receiver, in another embodiment, the electrical energy is

directed from the receiver to a battery, and then to the EC device. In one embodiment, the EC device is part of an EC window.

[0014] In certain embodiments, the EC device receives some of its electrical energy from a wireless power source as described above and additional electrical energy from a photovoltaic source that may optionally be integrated with the EC device (e.g., in or near an IGU, for example in a window frame). Such systems may require no wiring to power the EC device and associated controller, sensors and the like.

[0015] These and other features and advantages will be described in further detail below, with reference to the associated drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The following detailed description can be more fully understood when considered in conjunction with the drawings in which:

[0017] FIG. 1 depicts EC window fabrication including a wireless power receiver.

[0018] FIGS. 2A-2E are schematic representations of wireless power transmission networks as described herein.

#### DETAILED DESCRIPTION

[0019] In the broadest sense, the invention describes an EC device powered by a wireless power transmission source. In more specific embodiments, EC windows are powered by wireless power sources. Wireless power transmission is particularly well suited for supplying EC windows, because EC windows typically function using low potentials, on the order of a few volts to transition an EC device and/or maintain the device's optical state. Typically, EC windows are transitioned only a few times per day. Also, wireless power transmission can be used to charge an associated battery, so that indirect powering of one or more EC windows via wireless power transmission is achieved.

[0020] Installing windows with wires entails further considerations for the architect and builder, and in retrofit applications wires are particularly problematic due to the need for additional wiring infrastructure that was not previously installed in the building. The combination of these advanced technologies, wireless power transmission and EC windows, solves these problems and provides a synergy that saves energy, as well as time and money that would be spent integrating hard wire electrical connections of EC windows.

[0021] Dynamic, EC, insulated glass units (IGU's) for commercial and residential windows change light transmission properties in response to a small voltage, allowing control of the amount of light and heat passing through the windows. The EC device changes between a transparent "clear or bleached" state and a darkened (light and/or heat blocking) state using small potentials and can maintain optical states with even less power. Dynamic EC windows can filter the amount of light passing through the window, in one aspect providing visibility even in its darkened state and thus preserving visual contact with the outside environment while saving energy by, for example, blocking out heat generating solar rays during hot weather or keeping valuable heat in a building due to their insulating properties during cold weather.

[0022] One example of such dynamic windows are low-defectivity, highly-reliable EC windows which include solid-state EC stack materials. Such all solid-state and inorganic

EC devices, methods of fabricating them, and defectivity criterion are described in more detail in U.S. patent application, Ser. No. 12/645,111, entitled, "Fabrication of Low-Defectivity Electrochromic Devices," filed on Dec. 22, 2009 and naming Mark Kozlowski et al. as inventors; and in U.S. patent application, Ser. No. 12/645,159, entitled, "Electrochromic Devices," filed on Dec. 22, 2009 and naming Zhongchun Wang et al. as inventors; and in U.S. patent applications, Ser. Nos. 12/772,055 and 12/772,075, each filed on Apr. 30, 2010, and in U.S. patent applications, Ser. Nos. 12/814,277 and 12/814,279, each filed on Jun. 11, 2010—each of the four applications is entitled "Electrochromic Devices," each names Zhongchun Wang et al. as inventors, each of these six patent applications is incorporated by reference herein for all purposes. One aspect of the invention is a combination of an EC window, for example, but not limited to, an EC window described in any of these six U.S. patent applications, powered by wireless power transmission technology. The window may be powered directly via wireless power transmission, after conversion by a receiver to electrical energy, and/or the electrical energy may be used to charge a battery that is used to power the window.

**[0023]** Wireless power transmission is the process that takes place where electrical energy is transmitted from a power source to an electrical load, without interconnecting wires. In the broadest sense, electrical current can pass through the environment, be it air, water or solid objects without the need for wires. But more useful (controlled) forms of wireless power transmission exist, for example transmitting power via RF, magnetic induction, lasers or microwave energy. Wireless transmission finds particular use in applications where instantaneous or continuous energy transfer is needed, but interconnecting wires are inconvenient, problematic, hazardous, or impossible. Wireless power transfer may be inductive, including electrodynamic induction, or based upon other known energy transfer mediums such as radio frequency (RF), microwaves and lasers.

**[0024]** In some embodiments, power is transferred via RF, and transformed into electrical potential or current by a receiver in electrical communication with an EC device, particularly an EC window. One particularly useful method of transferring power via RF is described in US Patent Publication 2007/0191074, from application Ser. No. 11/699,148 filed Jan. 29, 2007, entitled "Power Transmission Network and Method," by Daniel W. Harist, et al., which is herein incorporated by reference for all purposes.

**[0025]** In other embodiments, power is transferred via magnetic induction using a first resonator powered by an external power supply and a second resonator which converts the magnetic field energy created by the first resonator into power that supplies the EC device of the EC window. One particularly useful method of transferring power via magnetic induction is described in US Patent Publication 2007/0222542, from application Ser. No. 11/481,077 filed Jul. 5, 2006, entitled "Wireless Non-radiative Energy Transfer," by John Joannopoulos, et al., which is herein incorporated by reference for all purposes. Another useful method of controlling wireless inductive power is described in U.S. Pat. No. 7,382,636, filed Oct. 14, 2005, entitled "System and Method for Powering a Load," by David Baarman, et al., which is herein incorporated by reference for all purposes. EC windows described herein can incorporate such methods of controlling wireless power transmission.

**[0026]** Certain embodiments include more than one wireless power transmission source, that is, the invention is not limited to embodiments where a single wireless power transmission source is used. For example, in embodiments where a wireless power transmission network is used, one wireless power transmission method, for example RF power transmission, is used in part of the network, while another method, for example, magnetic induction, is used in another part of the network.

**[0027]** One aspect of the invention is an EC window powered by a wireless power transmission source. In one embodiment, the EC window can be of any useful size, e.g., in automotive use, such as in a sunroof or a rear view mirror where wiring is inconvenient, for example having to pass through a windshield of a car. In one embodiment, the EC window uses architectural scale glass as a substrate for the EC device of the window. Architectural glass is glass that is used as a building material. Architectural glass is typically used in commercial buildings, but may also be used in residential buildings and typically, but not necessarily, separates an indoor environment from an outdoor environment. Architectural glass is at least 20 inches by 20 inches, and can be as large as about 80 inches by 80 inches. In some embodiments, the EC device is all solid state and inorganic. The window will have a receiver, for example an RF receiver or resonator, as part of a window assembly.

**[0028]** FIG. 1 depicts an EC window fabrication, **100**, where the window assembly includes a receiver, **135**, for receiving wireless power transmissions, converting the transmissions to an electrical energy and powering an EC device of the window with the electrical energy, either directly or indirectly, for example, via powering the EC device directly or charging a battery that is used to power the EC window. An EC pane, **105**, having an EC device (not shown, but for example on surface A) and bus bars, **110**, which power the EC device, is matched with another glass pane, **115**. During fabrication of IGU, **125**, a separator, **120**, is sandwiched in between and registered with substrates **105** and **115**. IGU **125** has an associated interior space defined by the faces of the substrates in contact with separator **120** and the surfaces of the interior perimeter of separator **120**. Separator **120** is typically a sealing separator, that is, includes a spacer and sealing between the spacer and each substrate where they adjoin in order to hermetically seal the interior region and thus protect the interior from moisture and the like. Typically, once the glass panes are sealed to the separator, secondary sealing may be applied around the outer perimeter edges separator **120** of the IGU in order to impart not only further sealing from the ambient, but also further structural rigidity to the IGU. The IGU is supported by a frame to create a window assembly, **130**. A cut out of the window frame is shown to reveal wireless power receiver **135** which includes an antennae in this example. Receiver **135** is proximate the IGU, in this example, inside the frame of window assembly **130**. The wireless power transmission receiver may be a component of a window controller.

**[0029]** In one embodiment, the wireless power transmission source transmits power via a radio frequency. In such embodiments, the EC window includes a radio frequency receiver, where the radio frequency receiver configured to convert the radio frequency to electrical energy (e.g., an electrical current or potential) used to power an EC device in the EC window. Powering the EC device includes at least one of powering an optical transition or an optical state of the EC

device. In one embodiment, the radio frequency receiver resides in or near the IGU of the EC window. For example, the receiver can be in the window frame that supports the IGU, in an area near the spacer that separates the glass panes of the IGU, or both. Preferably, but not necessarily, the receiver does not obscure the viewable area of the IGU, for example, as depicted in FIG. 1.

**[0030]** In another embodiment, power is wirelessly transferred via inductive coupling of magnetic fields. In general terms, a primary coil (that converts electrical energy, e.g. AC, running through the coil into a magnetic field) supplied by a power source generates a magnetic field and a secondary coil is coupled to the magnetic field and thereby produces electrical energy via induction. The electrical energy produced by the secondary coil is used to power the EC device, in particular embodiments an EC device of an EC window. In a specific embodiment where resonance coupled magnetic energy is utilized, power is wirelessly transferred via a first resonator, which receives power from an external supply hard wired to the first resonator, and a second resonator, which acts as the receiver by producing an electric current via coupling of the magnetic resonance fields of the first and second resonators. Although embodiments utilizing magnetic induction need not necessarily use resonance coupled magnetic fields, in those that do, near-field resonance from localized evanescent magnetic field patterns is a relatively efficient method of wireless power transfer.

**[0031]** In one embodiment, the receiver, whether RF antenna or resonance coil, is located proximate the IGU of the EC window, e.g., near the IGU seal or the window frame so as not to obscure the viewable area through the glass of the IGU. Thus, in particular embodiments, the receiver is of relatively small dimensions. "Small dimensions" means, for example, that the receiver occupies not more than about 5% of the viewable area of the EC window. In one embodiment, the receiver occupies none of the viewable area of the EC window, that is, the receiver is of sufficiently small dimensions that the user of the window may not recognize the receiver as being part of the window, but rather the receiver is hidden from the view of the user, e.g. housed in the frame of the window. In one embodiment, where the receiver is housed in seal area of the IGU, the frame of the window can have one or more access ports for servicing the receiver or the receiver can be sealed permanently in the window frame. There may also be ports and/or materials transparent to the wireless power transmission, so that the receiver can properly receive the wireless power transmissions without interference from the window frame material.

**[0032]** In particular embodiments, there is a controller, for example a microprocessor, that regulates the potential applied to the EC device and may optionally control other functions (alone or combined with other microprocessors) such as recharging a battery used to function the window, wirelessly communicating with a remote control, such as a hand held, an automated heat and/or energy management system that communicates wirelessly with the window controller.

**[0033]** In one embodiment, the wireless power transmission is carried out via a network which includes one or more power nodes for transmitting power to window receivers in particular areas. Wireless power transmission networks described herein can use RF, magnetic induction or both, depending on the need. Depending on the building, one or more, sometimes several nodes are used to form a network of power nodes which feed power to their respective window

receivers. In one embodiment, where radio frequency is used to transmit power and there are more than one power node, there are more than one frequency and/or polarization vector used in the power nodes, so that different levels or types of power are transferred from the various nodes to windows having different power needs.

**[0034]** In one embodiment, where magnetic induction is used for wireless power transfer, there also are one or more power nodes, but in this embodiment, the power nodes are themselves resonators. For example, in one embodiment, a first resonator, which receives power via a power supply, is resonance coupled to a second resonator, and the second resonator is resonance coupled to a third resonator, for example that delivers power to an EC window. In this way, the second resonator acts as a power node in a power transfer network from the first resonator, to the second resonator, to the third resonator, the third resonator acting as the receiver and transmitting power to the EC window via conversion of magnetic field to electrical power. In this way, near field magnetic energy can span longer distances in order to suit the needs of the particular building's EC windows.

**[0035]** Another embodiment is a method of powering an EC device, the method comprising: i) generating a wireless power; ii) transmitting the wireless power to a receiver; said receiver configured to convert the wireless power to an electrical energy used to power the EC device; and iii) delivering the electrical energy (e.g., current or potential) to the EC device and/or a battery used to power the EC device. In one embodiment, the EC device is an EC window. In other embodiments, generating the wireless power is performed via a wireless power transmitter that transmits power via a radio frequency and the electrical energy is a voltage potential. In another embodiment, generating the wireless power is performed via a wireless power transmitter that transmits power via magnetic induction, in a more particular embodiment, resonance coupled magnetic induction. In other particular embodiments, ii) and iii) are accomplished via at least one of the wireless power transmission networks as described above. In one particular embodiment of the above described embodiments, the EC device is part of an EC pane of an EC window. In an even more particular embodiment, the EC pane is of architectural glass scale. In another embodiment, at least one of i), ii) and iii) are performed via wireless communication. One embodiment includes using the electrical energy created by the receiver's conversion of wireless power transmission for charging a battery that is used to power the EC device.

**[0036]** FIG. 2A is a schematic representation of a wireless power transmission network, 200. The wireless power transmission network has a wireless power transmitter, 202, that transmits wireless power, for example via RF power or magnetic induction as described herein, to an EC window 204. The invention is not limited to EC windows, any EC device powered by wireless power transmission is within the scope of the invention. Electrochromic window 204 is configured with a receiver that converts the wirelessly transmitted power to electrical energy that is used to operate the EC device in the EC window and/or window controllers, sensors and the like. In one embodiment, the electrical energy is a voltage potential used to power the EC device's transitions and/or maintain optical states. Typically, the EC device will have an associated controller, e.g. a microprocessor that controls and manages the device depending on the input. Additionally, the EC device can be controlled and managed by an external control-

ler which communicates with the device via a network. The input can be manually input by a user, either directly or via wireless communication, or the input can be from an automated heat and/or energy management system of a building of which the EC window is a component.

**[0037]** The wireless power transmission network is generally defined by area, **206**, that is, transmission of power generally is localized to area **206**, but not necessarily so. Area **206** can define an area where one or more windows reside and where wireless power will be transmitted. Transmitter **202** can be outside area **206** in some embodiments (and transmit power into the area) or inside area **206** as depicted in FIG. 2. In one embodiment, the wireless power receiver resides proximate the IGU of the EC window. Preferably the receiver does not obstruct the view through the EC window. One of ordinary skill in the art would appreciate that a wireless power network as described can contain a plurality of EC windows to which power is supplied wirelessly via one or more transmitters. Also, the electrical energy produced via the wireless power can be used to augment a battery supply or a photovoltaic power supply in the EC window. In one embodiment, the photovoltaic power supply is used to augment battery charging performed via wireless power transmission.

**[0038]** FIG. 2B is a schematic representation of another wireless power transmission network, **201**. Network **201** is much like network **200** as described above in relation to FIG. 2A, except that the wireless power transmitted from transmitter **202** that is received by a receiver in EC window **204** is used to power not only window **204** but also windows **205**. That is, the receiver in a single window is configured to convert wireless power transmissions into electrical energy in order to power more than one EC window, either directly or via a battery or batteries that are charged by the receiver. In this example, a receiver associated with window **204** converts the wireless power transmissions into electrical energy and transfers the energy via wires to windows **205**. This has the advantage of not relying on a receiver for each window, and, although some wiring is used, it is localized to the window installation area, providing electrical communication between the windows, rather than having to be run throughout a building. Also, since EC windows do not have high power requirements, this configuration is practical.

**[0039]** FIG. 2C is a schematic representation of another wireless power transmission network, **208**. Network **208** is much like network **200** as described above in relation to FIG. 2A, except that the wireless power transmitted from transmitter **202** is not received directly by a receiver in EC window **204**, but rather relayed via a power node **210**. Power node **210** can either relay the power in the same form as that which it received (e.g. via an RF antenna or induction coil) or be configured to change the wireless power and transmit it to the receiver in a form more suited to the (ultimate) requirements of window **204**. In one example, the power node receives the wireless power transmission in one form, either RF or magnetic induction, and transmits wireless power to window **204** in the other of the other of the aforementioned forms. One embodiment is power node including: a wireless power transmission receiver; configured to receive wireless power transmissions in one or more forms and convert the transmissions to electrical energy; and a wireless power transmitter configured to convert the electrical energy into wireless power transmissions in said one or more forms. In one embodiment, the wireless power transmitter is configured to convert the electrical energy into the same form of wireless power trans-

mission than the wireless power receiver is configured to receive. Although the form is the same, there may be, for example, different frequency or polarity used so that the receiver of the power node can distinguish between the wireless transmissions from transmitter **202** and the transmitter of the power node **210**. In one embodiment, the wireless power transmitter is configured to convert the electrical energy into a different form of wireless power transmission than the wireless power receiver is configured to receive.

**[0040]** FIG. 2D is a schematic representation of another wireless power transmission network, **212**. Network **212** is much like network **208** as described above in relation to FIG. 2C, except that the wireless power transmitted from transmitter **202** is relayed via a power node **210** to a plurality of windows **204**. Again, power node **210** can either relay the power in the same form as that which it received (e.g. via an RF antenna or induction coil) or be configured to change the wireless power and transmit it to the receiver in a form more suited to the (ultimate) requirements of windows **204**. In this example, transmitter **202** is outside of area **206**. In this example, the power requirements of windows **204** are the same, however the invention is not so limited. That is, the wireless power transmitted from node **210** can be of a sufficient level so as to satisfy the power requirements of EC windows having different power needs, for example, where components for appropriately converting the wireless power transmissions from power node **210** to electrical energy are part of each window **204**'s receiver.

**[0041]** In one embodiment fulfilling the varying power requirements of different windows within a wireless power transmission network is accomplished using different power nodes for windows with different power needs. The power relayed from each node can be, for example, of different power level and/or transmitted in a different way. FIG. 2E is a schematic representation of one such wireless power transmission network, **214**. Network **214** is much like network **212** as described above in relation to FIG. 2D, except that the wireless power transmitted from transmitter **202** is relayed via two power nodes, **210** and **216**. Power node **210** can either relay the power in the same form as that which it received (e.g. via an RF antenna or induction coil) or be configured to change the wireless power and transmit it to the receiver (in window **204**) in a form more suited to the (ultimate) requirements of window **204**. Power node **216** relays the wireless power in a manner different than power node **210**, that is power node **216** is configured to change the wireless power and transmit it to the receiver in window **218** in a form more suited to the (ultimate) requirements of window **218**. In this example, window **218** is configured to supply power to itself and to windows **220** through wiring. Window **218** receives wireless power transmissions from node **216** and the receiver of window **218** converts the wireless power transmission into sufficient power to operate window **218** and windows **220**. Thus, in embodiments described herein, different power nodes can receive the same form of wireless energy, for example from a single transmitter, but relay the wireless energy in different formats for different EC devices (via associated receivers), in this example EC windows having different power requirements. In this example, transmitter **202** is outside of area **206**. In a specific embodiment, a single wireless power transmitter transmits a wireless power and each of a plurality of EC windows includes a receiver specifically configured to convert the wireless power to an electrical energy suited for the particular needs of that window. In

another embodiment, each window has an equivalent receiver that converts the wireless power into the same electrical energy, but the electrical energy is converted to the particular needs of the window by one or more electronic components, in communication with the receiver, for example a rectifier, voltage converter, frequency changer, transformer, or inverter.

**[0042]** One embodiment is a wireless power transmission network including: i) a wireless power transmitter configured to transmit a wireless power; ii) a power node, configured to receive the wireless power and relay the wireless power; iii) a receiver configured to receive the relayed wireless power and convert the wireless power to an electrical energy; and iv) an EC device configured to receive the electrical energy. In one embodiment, the EC device is an EC window. In another embodiment the power node comprises an RF antenna. In one embodiment, the power node comprises an induction coil. In another embodiment the receiver is an RF receiver. In another embodiment, the receiver is an induction coil. In other embodiments, the power node is configured to change the wireless power prior to relaying the wireless power to the EC window, depending on the requirements of the EC window. In some embodiments, the wireless power network includes a plurality of power nodes wherein each power node is configured to relay power to one or more EC windows, each of the plurality of power nodes configured to relay wireless power according to the requirements of the EC windows comprising receivers corresponding to said each of the plurality of power nodes.

**[0043]** Although the foregoing invention has been described in some detail to facilitate understanding, the described embodiments are to be considered illustrative and not limiting. It will be apparent to one of ordinary skill in the art that certain changes and modifications can be practiced within the scope of the appended claims.

1-20. (canceled)

21. A system comprising:

an electrochromic window including an electrochromic device; and

a photovoltaic power supply configured to generate power for the electrochromic window;

wherein the electrochromic device is controlled by a window controller via wireless communication, and wherein the window controller communicates with the electrochromic device via a network.

22. The system of claim 21, further comprising a battery configured to deliver power to the electrochromic device.

23. The system of claim 22, wherein the photovoltaic power supply is configured to charge the battery.

24. The system of claim 23, wherein the window controller is further configured to control charging of the battery.

25. The system of claim 21, wherein the electrochromic window is in the form of an insulated glass unit.

26. The system of claim 23, wherein the photovoltaic power supply is in or near the insulated glass unit.

27. The system of claim 21, wherein the photovoltaic power supply is in the electrochromic window.

28. The system of claim 21, further comprising a receiver configured to convert wireless power transmissions received from a wirelessly transmitted power supply to electrical energy.

29. The system of claim 28, further comprising a battery configured to deliver power to the electrochromic device,

wherein both the photovoltaic power supply and the wirelessly transmitted power supply are configured to deliver power to the battery.

30. The system of claim 28, wherein the system has no external wiring for supplying power to the system.

31. The system of claim 28, wherein the wirelessly transmitted power supply transmits power via magnetic induction, radio frequency, microwave energy or laser.

32. The system of claim 21, further comprising one or more sensors.

33. The system of claim 32, wherein the one or more sensors comprise one or more of a motion sensor, a light sensor, a heat sensor and a moisture sensor.

34. The system of claim 21, wherein the electrochromic device comprising a solid state and inorganic stack materials disposed on a glass substrate, wherein the electrochromic device is configured to change between a transparent state and a darkened state.

35. The system of claim 28, wherein wirelessly transmitted power supply transmits power via a power transmission network.

36. The system of claim 21, wherein the electrochromic window is a component of an automated heat and/or energy management system of a building.

37. The system of claim 28, wherein the window controller comprises the wireless power transmission receiver.

38. The system of claim 21, wherein the window controller comprises a microprocessor configured to regulate a potential applied to the electrochromic device.

39. The system of claim 38, wherein the microprocessor, alone or combined with other microprocessors, controls recharging the battery or wirelessly communicating with a remote control.

40. The system of claim 39, wherein the remote control is a hand held device or an automated heat and/or energy management system.

41. The system of claim 21, wherein the window controller controls the electrochromic device depending on input received via wireless communication.

42. The system of claim 41, wherein the input is from an automated energy management system of the building.

43. The system of claim 42, wherein the electrochromic window is a component of the automated energy management system.

44. A method of powering an electrochromic window, the method comprising:

generating power for the electrochromic window using a photovoltaic power supply; and

controlling an optical transition in the electrochromic device via wireless communication from a window controller, wherein the window controller communicates with the electrochromic device via a network.

45. The method of claim 44, wherein the optical transition is controlled based on input from an automated energy management system of the building with the electrochromic window.

46. The method of claim 44, further comprising delivering power to the electrochromic device from a battery in the electrochromic window.

47. The method of claim 46, further comprising charging the battery using power generated by the photovoltaic power supply.

**48.** The method of claim **46**, further comprising controlling the charging of the battery using power generated by the photovoltaic power supply.

**49.** The method of claim **44**, wherein the electrochromic window is in the form of an insulated glass unit.

**50.** The method of claim **44**, further comprising receiving wireless power transmissions at a receiver from a wirelessly transmitted power supply and converting the wireless power transmissions into an electrical energy used to power the optical transition in the electrochromic device.

**51.** The method of claim **50**, further comprising charging the battery using power from both the photovoltaic power supply and the wirelessly transmitted power supply.

**52.** The method of claim **50**, wherein the wireless power transmissions are transmitted from the wirelessly transmitted power supply via magnetic induction, radio frequency, microwave energy or laser.

**54.** The method of claim **44**, wherein the electrochromic device comprises a solid-state electrochromic stack materials disposed on a glass substrate.

\* \* \* \* \*