



(22) Date de dépôt/Filing Date: 1998/12/16
(41) Mise à la disp. pub./Open to Public Insp.: 1999/06/18
(45) Date de délivrance/Issue Date: 2003/10/07
(30) Priorité/Priority: 1997/12/18 (08/993,354) US

(51) Cl.Int.⁶/Int.Cl.⁶ G07B 17/02, G06F 17/60, G06F 3/12, G06K 15/02


(72) Inventeurs/Inventors:
GRAVELL, LINDA V., US;
LEE, DAVID K., US;
PIERCE, PERRY A., US;
RILEY, DAVID W., US;
RYAN, FREDERICK W., JR., US

(73) Propriétaire/Owner:
PITNEY BOWES INC., US

(74) Agent: SIM & MCBURNEY

(54) Titre : SYSTEME ET TECHNIQUE D'AFFRANCHISSEMENT POUR AFFRANCHISSEUSE AUTONOME DE SERVEUR EN RESEAU

(54) Title: POSTAGE METERING SYSTEM AND METHOD FOR A STAND-ALONE METER OPERATING AS A METER SERVER ON A NETWORK



(57) Abrégé/Abstract:

A postage metering system includes a plurality of printer modules operatively connected as part of a network and operating as client printer modules on the network. A postal security device (PSD) is coupled directly to a local one of the client printer modules. The PSD includes unique identification, postal value storage and a digital signature generator. The client printer



(57) Abrégé(suite)/Abstract(continued):

modules function as a postage metering network wherein a one of the client printer modules remote to the PSD requests evidence of postage payment from the PSD through the local client printer module for concluding postage metering transactions. The local client printer module function as a stand-alone meter when requests for evidence of postage payment from the PSD are initiated at the local client printer module. The local client printer module initiates local requests for evidence of postage payment to be printed at the local client printer modules and receives remote requests for evidence of postage payment from the remote client printer modules. The remote requests include identification of the remote client printer modules. The local client printer module sends each request for evidence of postage payment to the PSD and receives from the PSD the evidence of postage payment including a digital signature corresponding to each request for evidence of postage payment;. The local client printer module sends the evidence of postage payment to the remote client printer modules in response to the remote request, and prints the evidence of postage payment in response to the local request.

**POSTAGE METERING SYSTEM AND METHOD FOR A STAND-
ALONE METER OPERATING AS A METER SERVER ON A NETWORK**

Abstract of the Invention

A postage metering system includes a plurality of printer modules
5 operatively connected as part of a network and operating as client printer
modules on the network. A postal security device (PSD) is coupled directly to
a local one of the client printer modules. The PSD includes unique
identification, postal value storage and a digital signature generator. The
client printer modules function as a postage metering network wherein a one
10 of the client printer modules remote to the PSD requests evidence of postage
payment from the PSD through the local client printer module for concluding
postage metering transactions. The local client printer module function as a
stand-alone meter when requests for evidence of postage payment from the
PSD are initiated at the local client printer module. The local client printer
15 module initiates local requests for evidence of postage payment to be printed
at the local client printer modules and receives remote requests for evidence
of postage payment from the remote client printer modules. The remote
requests include identification of the remote client printer modules. The local
client printer module sends each request for evidence of postage payment to
20 the PSD and receives from the PSD the evidence of postage payment
including a digital signature corresponding to each request for evidence of
postage payment;. The local client printer module sends the evidence of
postage payment to the remote client printer modules in response to the
remote request, and prints the evidence of postage payment in response to
25 the local request.

POSTAGE METERING SYSTEM AND METHOD FOR A STAND-ALONE METER OPERATING AS A METER SERVER ON A NETWORK

Field of the Invention

The present invention relates generally to a postage metering system
5 and method for printing postage indicia using a personal computer and, more particularly, to a postage metering system and method for printing postage indicia in a network of personal computers.

Related Applications

The present application is related to the following Canadian Patent
10 Application Nos. 2,256,115; 2,255,998; 2,256,273; 2,256,275; 2,256,671 and 2,256,167, all filed concurrently herewith and assigned to the assignee of the present invention.

Background of the Invention

The Information-Based Indicia Program ("IBIP") is a distributed trusted
15 system proposed by the United States Postal Service ("USPS") to retrofit and augment existing postage meters using new technology known as information-based indicia. The program relies on digital signature techniques to produce for each envelope an indicium whose origin cannot be repudiated and content cannot be modified. IBIP is expected to support new methods of
20 applying postage in addition to the current approach, which typically relies on a postage meter to mechanically print indicia on mailpieces. IBIP requires printing a large, high density, two-dimensional ("2-D") bar code on a mailpiece. The 2-D bar code encodes information and is signed with a digital signature.

25 The USPS has published draft specifications for IBIP. The INFORMATION BASED INDICIA PROGRAM (IBIP) INDICIUM SPECIFICATION, dated June 13, 1996, and revised July 23, 1997, ("IBIP Indicium Specification") defines the proposed requirements for a new indicium that will be applied to mail being processed using IBIP. The INFORMATION
30 BASED INDICIA PROGRAM POSTAL SECURITY DEVICE SPECIFICATION, dated June 13, 1996, and revised July 23, 1997, ("IBIP PSD Specification")

defines the proposed requirements for a Postal Security Device ("PSD") that will provide security services to support the creation of a new "information based" postage postmark or indicium that will be applied to mail being processed using IBIP. The INFORMATION BASED INDICIA PROGRAM
5 HOST SYSTEM SPECIFICATION, dated October 9, 1996, defines the proposed requirements for a host system element of IBIP ("IBIP Host Specification"). The specifications are collectively referred to herein as the "IBIP Specifications". IBIP includes interfacing user (user), postal and vendor infrastructures which are the system elements of the program. The
10 INFORMATION BASED INDICIA PROGRAM KEY MANAGEMENT PLAN SPECIFICATION, dated April 25, 1997, defines the generation, distribution, use and replacement of the cryptographic keys used by the USPS product/service provider and PSDs ("IBIP KMS Specification").

The user infrastructure, which resides at the user's site, comprises a
15 PSD coupled to a host system ("Host") with printer. The PSD is a secure processor-based accounting device that dispenses and accounts for postal value stored therein.

The IBIP Indicium Specification provides requirements for the indicium that consists of both human-readable data and PDF417 bar code data. The
20 human-readable information includes an originating address, including the 5-digit ZIP Code of the licensing post office, PSD ID/Type number, date of mailing and amount of the applied postage. The bar code region of the indicium elements includes postage amount, PSD ID, user ID, date of mailing, originating address, destination delivery point identification, ascending and
25 descending registers and a digital signature.

An integrated mailing system is subject to open system requirements if it includes a computer interfaced to the meter and it prepares mailpiece fronts or labels that include both the destination address and the indicium. The integrated system is an open system even if different printers apply the
30 address and the indicium. If the mailing system satisfies such criteria, the USPS considers the "meter" to be an open system peripheral device that performs the dual functions of printing the indicia and interfacing the PSD to the Host. The integrated mailing system must be approved by the USPS according to open system criteria.

The IBIP Host Specification sets forth the requirements for a Host in an open system. The Host produces the mailpiece front including the return address (optional), the delivery address (required), the Facing Identification Mark ("FIM"), and the indicium as an integral unit. The Host may print this unit
5 on the actual mailpiece stock or label(s) for later attachment to the mailpiece. The Host provides the user with an option to omit the FIM (e.g., when the FIM is preprinted on envelopes). The Host produces standardized addresses, including standard POSTNET delivery point bar code, for use on the mailpiece. The Host verifies each address at the time of mailpiece creation.
10 The Host then creates the indicium and transmits it to the printer.

The IBIP Specifications define a stand-alone open metering system, referred to herein as a PC Meter or Stand-alone PC Meter. The Stand-alone PC meter has one personal computer ("PC") which operates as the Host ("Host PC"). The Host PC runs the metering application software and
15 associated libraries (collectively referred to herein as "Host Applications" and "PC Meter Toolkit") and communicates with one or more attached PSDs. The Stand-alone PC Meter can only access PSDs coupled to the Host PC. There is no remote PSD access for the Stand-alone PC Meter.

The Stand-alone PC Meter processes transactions for dispensing
20 postage, registration, and refill on the Host PC. Processing is performed locally between the Host and the PSD coupled thereto. Connections to a Data Center, for example for registration and refill transactions, are made locally from the Host through a local or network modem/internet connection. Accounting for debits and credits to the PSD are also performed locally,
25 logging the transactions on the Host PC, which is the PC where the transactions are processed on and to which the PSD is attached. Thus, the accounting of funds and transaction processing are centralized on a single PC. The Host PC may accommodate more than one PSD, for example supporting one PSD per serial port. Several applications programs running
30 on the Host PC, such as a word processor or an envelope designer, may access the Host Applications.

The IBIP Specifications do not address an IBIP open metering system on a network environment. However, the specifications do not prohibit such a network-based system. Generally, in a network environment a network

Server PC controls remote printing requested by a Client PC on the network. Of course, the Client PC controls any local printing.

One version of a network metering system, referred to herein as a "Virtual Meter", has many Host PCs without any PSDs coupled thereto. The Host PCs run client applications, but all PSD functions are performed on Server PCs located at a Data Center. The Host PCs must connect with the Data Center to process transactions such as postage dispensing, meter registration, or meter refills. Transactions are requested by the Host PC and sent to the Data Center for remote processing. The transactions are processed centrally at the Data Center and the results are returned to the Host PC. Accounting for funds and transaction processing are centralized at the Data Center. See, for example, U.S. Patent No. 5,454,038, which is assigned to the assignee of the present invention. The Virtual Meter does not conform to all the current requirements of the IBIP Specifications. In particular, the IBIP Specifications do not permit PSD functions to be performed at the Data Center.

Summary of the Invention

It has been found that an open metering system, which conforms to the IBIP Specifications, can be implemented on a conventional local area, or wide area, network to form a "Network PC Metering System". The Network PC Metering System includes a plurality of Client PCs operatively coupled to a Network Server PC as part of a conventional network. The Network PC Metering System is configured with at least one PSD coupled to at least one of the Client PCs, whereby authorized ones of the other Client PCs on the network can obtain postage value from a PSD that is remote from the requesting Client PC. Any Client PC may have one or more PSDs attached thereto. Each Client PC has access, if authorized, to both its own local PSD(s), if any, and any other Client PC's PSD(s) ("remote PSDs") in the network.

Each Client PC runs its own client metering application to dispense postage and to perform registration and refill operations. For each PSD in the Network PC Metering System, the Client PC to which the PSD is coupled controls processing transactions for dispensing postage and registration and

refill of the PSD. When performing such operations, the Client PC functions as a server for the metering transaction, and is referred to herein as a "Meter Server PC". In a preferred embodiment of the Network PC Metering System the accounting for debits and credits to the PSD and the logging of transactions are performed on the Meter Server PC. Thus, the transaction processing is performed remotely when a Client PC is accessing a remote PSD. In alternate embodiments, the logging of transactions is performed on a network server to which the Client PCs are connected ("Network Server PC").

In the preferred embodiment, modems or internet connections for accessing the Data Center are located in the Meter Server PC. In alternate embodiments, the modem may be located in the PSD or the Client PC and the Internet connection may be in the Client PC.

It has also been found that the Network PC Metering System can be configured such that each Client PC dynamically knows which remote PSDs are available for use by such Client PC, and that each Meter Server PC, i.e., each Client PC with a PSD coupled thereto, dynamically knows which Client PCs are on-line that are authorized to use the PSD coupled to the Meter Server PC.

There are several benefits that are realized from the present invention. One such benefit relates to the postal regulations requiring that the postage printed on a metered mailpiece must be obtained from a meter licensed from the local post office at which the mailpiece is deposited for mailing, commonly referred to as "origin of deposit" or "domain". With a plurality of PSDs accessible over a computer network a user at a Client PC is not limited to a single PSD having a single origin of deposit or domain. For example, while most users of a network metering system located in Shelton, Connecticut may be willing to deposit their mailpieces in the Post Office in Shelton, Connecticut, other users may intend to deposit their mailpieces at different origins of deposit, such as Stamford, Connecticut. Furthermore, some of the users may be at a Client PC that is physically located in Stamford, Connecticut but is connected to a network server physically located in Shelton Connecticut. The present invention provides each user of a Client PC on the network with access to several PSDs having different origins of deposit.

Another benefit of the present invention is that mailpiece generation does not have to be interrupted because of PSD funds limitation. For example, when a large mail run requires more postal value than is stored on a single PSD, the user can access another PSD on the network to complete the
5 mail run without having to interrupt the mail run to refill the PSD that is low on funds.

The present invention proves a postage metering system that includes a plurality of printer modules operatively connected as part of a network and operating as client printer modules on the network. A postal
10 security device (PSD) is coupled directly to a local one of the client printer modules. The PSD includes unique identification, postal value storage and a digital signature generator. The client printer modules function as a postage metering network wherein a one of the client printer modules remote to the PSD requests evidence of postage payment from the PSD through the local
15 client printer module for concluding postage metering transactions. The local client printer module function as a stand-alone meter when requests for evidence of postage payment from the PSD are initiated at the local client printer module. The local client printer module initiates local requests for evidence of postage payment to be printed at the local client printer modules
20 and receives remote requests for evidence of postage payment from the remote client printer modules. The remote requests include identification of the remote client printer modules. The local client printer module sends each request for evidence of postage payment to the PSD and receives from the PSD the evidence of postage payment including a digital signature
25 corresponding to each request for evidence of postage payment. The local client printer module sends the evidence of postage payment to the remote client printer modules in response to the remote request, and prints the evidence of postage payment in response to the local request.

According to an aspect of the present invention, there is provided a
30 postage metering system comprising:

a plurality of printing means operatively connected as part of a network and operating as client printing means on the network, the client printing means including processor, memory and storage means;

a postal security device (PSD) coupled directly to a first one of the client printing means (local client printing means); the PSD including unique identification, postal value storage means and digital signature means;

means in the client printing means for functioning as a postage
5 metering network wherein one of the client printing means remote to the PSD requests first evidence of postage payment from the PSD through the local client printing means for concluding postage metering transactions; and

means in the local client printing means for functioning as a stand-alone meter when requests for second evidence of postage payment from the
10 PSD are initiated at the local client printing means.

According to another aspect of the present invention, there is provided a postage metering system comprising:

a plurality of general purpose computers (computers) operatively connected as part of a computer network and operating as a client computers
15 on the computer network;

a postal security device (PSD) coupled directly to a first one of the client computers (local client computer); the PSD including unique identification, postal value storage means and digital signature means;

means in the client computers for functioning as a postage metering
20 network wherein one of the client computers remote to the PSD requests first evidence of postage payment from the PSD through the local client computer for concluding postage metering transactions; and

means in the local client computer for functioning as a stand-alone meter when requests for second evidence of postage payment from the PSD
25 are initiated at the local client computer.

According to another aspect of the present invention, there is provided a transaction evidencing system comprising:

a plurality of general purpose computers (computers) operatively connected as part of a computer network and operating as client computers
30 on the computer network, at least some of the client computers including transaction evidencing software that selectively runs on the client computers;

a transaction security device (TSD) coupled directly to a first one of the client computers (local client computer); the TSD including unique

identification, transaction evidencing storage means, digital signature means, and transaction accounting means;

means in the client computers for functioning as a transaction evidencing network wherein one of the client computers remote to the TSD requests and obtains first transaction evidencing from the TSD through the local client computer for concluding transaction evidencing transactions; and

means in the local client computer for functioning as a stand-alone transaction evidencing device when requests for second transaction evidencing from the TSD are initiated at the local client computer.

According to another aspect of the present invention, there is provided a method for postage metering wherein a postage meter has dual modes of operation as a stand-alone meter and as a meter server on a network, the method comprising the steps of:

providing a plurality of client modules on a network;

coupling a local postage security device (PSD) to a first one of said client modules and a remote PSD to a second one of said client modules, the PSDs each including unique identification, postal value storage means and digital signature means;

providing means in said first client module for requesting and obtaining first postage evidencing from the local PSD;

providing means in said second client module for requesting and obtaining second postage evidencing from the local PSD; and

providing means in said first client module for receiving and responding to said request from said second client module.

25

Description of the Drawings

The above and other objects and advantages of the present invention will be apparent upon consideration of the following detailed description, taken in conjunction with accompanying drawings, in which like reference characters refer to like parts throughout, and in which:

Fig. 1 is a block diagram of a preferred embodiment of a Network PC Metering System with PSDs couple to Client PCs in accordance with the preferred embodiment of the present invention;

Fig. 2 (2A and 2B) are block diagrams of alternate embodiments of a Network PC Metering System with PSDs couple to Client PCs with a centralized transaction log;

Fig. 3 is a Client PC operating in stand-alone mode;

Fig. 4 is a block diagram of the preferred embodiment of a Network PC Metering System of Fig. 1 with a Client PC in Meter Server mode;

Fig. 5 is a flow chart of a Client PC accessing a remote PSD; and

Fig. 6 is a flow chart of a Client PC operating as a Meter Server and a Stand-alone PC Meter;

Fig. 7 is a block diagram of a closed system metering network in accordance with the present invention.

Detailed Description of the Present Invention

In describing the present invention, reference is made to the drawings, wherein there is seen in Figs. 1-2, alternate embodiments of a Network PC Metering System. Fig. 1 shows the preferred embodiment of the present invention. A Network PC Metering System, generally designated 10, includes a plurality (five are shown) of Client PCs 20 conventionally coupled to a Network Server 30. Each PSD 40 (two are shown) of Network PC Metering System 10 is coupled to one of Client PCs 20. Each Client PC includes a conventional personal computer system with display, keyboard, and an unsecured printer 22. (Optionally, each Client PC may access a network printer 23 connected directly to the network.) Preferably, a plurality of PSDs exists in Network PC Metering System 10, with at least one PSD 40 being coupled to several Client PCs 20. When a specific PSD 40 is accessed for a metering transaction, Client PC 20, to which the PSD 40 is attached, becomes a Meter Server PC 21 (shown within parenthesis) for the remainder of the transaction. When the PSD 40 is being accessed by the Client PC 20 to which the PSD is coupled the Client PC 20 is functioning as a stand-alone PC meter. An example of a stand-alone PC metering system is described in Canadian Patent Application No. 2193434, filed December 19, 1996.

In the preferred embodiment, the postal funds accounting and the transaction processing occur in the Meter Server PC 21. It will be understood that this is a decentralized approach concerning funds accounting and transaction accounting because each Client PC 20 having a PSD 40 attached thereto maintains accounting information (departmental accounting registers 42) and transaction information (transaction logs 44) relating to transactions occurring only at its PSD 40.

Figs. 2A and 2B show alternate embodiments of the present invention. Network PC Metering System, generally designated 10', includes a plurality (five are shown) of Client PCs 20 conventionally coupled to a network server 30. Each PSD 40 (two are shown) of Network PC Metering System 10' is coupled to one of Client PCs 20. Each Client PC includes a conventional personal computer system with display, keyboard, and an unsecured printer 22 (and/or optional network printer 23). As in the preferred embodiment, a plurality of PSDs exists in Network PC Metering System 10', with at least one PSD 40 being coupled to several Client PCs 20. When the specific PSD is accessed for a metering transaction, the Client PC 20, to which the PSD 40 is attached, becomes a Meter Server PC 21 for the remainder of the transaction (Fig. 4). In this embodiment the postal funds accounting occurs in Meter Server PC 21 when the transaction has been concluded. However, the transaction processing occurs at Network Server 30. It will be understood that this is a decentralized approach concerning funds accounting because each Client PC 20 that has a PSD 40 attached thereto maintains accounting information (accounting registers 42) relating to transactions occurring only at its PSD. However, this embodiment provides a centralized approach concerning transaction accounting because one of the Meter Servers 21 (Fig. 2A) or Network Server 30 (Fig. 2B) maintains transaction information (transaction logs 44) relating to transactions occurring at any PSD.

Referring again to Figs. 1 and 2, Network PC Metering Systems 10 and 10' are configured with one or more PSDs 40 coupled to one or more Client PCs 20. In such configurations, the Client PC 20 becomes a Stand-alone PC Meter when a metering transaction is processed locally on its coupled PSD 40. When operating as a Stand-alone PC Meter, such Client PC 20 performs the previously described metering transaction, acting as both the requesting

Client PC and the Meter Server PC. As a Stand-alone PC Meter, Client PC 20 can only access the PSD 40 coupled to it. There is no remote vault access when a Client PC is processing a metering transaction on the local PSD.

Referring now to Fig. 3, a Client PC 20 is shown in Stand-alone PC Meter mode, generally designated 100. Stand-alone PC Meter 100 includes Host PC 102, PSD 104 and printer 106. Stand-alone PC Meter 100 processes the functions for PSD registration, PSD refill, and postage dispensing as transactions for PSD 104. Processing is performed locally by metering software component 110 (referred to herein as "PC Meter Toolkit") running in Host PC 102. In the preferred embodiment, PC Meter Toolkit is a Component Object Model/Distributed Component object Model (COM/DCOM) object (typically implemented as a dynamic link library (DLL) or OLE control) with interfaces to perform metering operations. One such interface maintains a list of local and remote PSDs on the network. This interface maintains a current list of all known and attached PSDs at the time it is instantiated. There is also a refresh method that Host and Client applications may use to update the list. A method for creating and maintaining the list of PSDs is described in detail in previously noted related Canadian Patent Application No. [E-645]. An example of a PC metering system using a DLL with interfaces to perform metering operations is described in previously noted Canadian Patent Application No. 2193434, filed December 19, 1996.

This Toolkit implementation allows Meter Servers to be local or remote without any changes in the Client PC interface. The PC Meter Toolkit and Meter Server could be within the same computer, computers connected via a local area network or the internet. Network protocol negotiation is handled, for example, by the Windows operating system. For additional information on COM/DCOM see technical white papers for Microsoft Windows NT® Server, including: DCOM Architecture; DCOM Technical Overview; and DCOM The Distributed Component Object Model, A Business Overview.

PC Meter Toolkit 110 includes the following components: a transaction handler, a vault interface, and a transaction log handler. Connections to the Data Center 5 can be made locally from the Stand-alone PC Meter 100 via modem 130. Accounting for debits and credits to the PSD are also performed locally, logging the transactions on the hard drive of Stand-alone PC Meter

100. In this manner, the transaction processing and funds accounting are centralized on the Client PC operating as Stand-alone PC Meter 100.

Stand-alone PC Meter 100 may accommodate more than one PSD per PC, for example, supporting one vault per serial port. Several Host or client applications programs 140, such as a word processor or an envelope designer, may access the PC Meter Toolkit 110 concurrently.

The PC Meter Toolkit 110 provides standard metering functions, such as dispensing postage, PSD refills, and PSD registration. The PC Meter Toolkit 110 resides in all Meter Servers and remote Client PCs capable of printing postage. The user of Stand-alone PC Meter 100 can access local or remote PSDs using PC Meter Toolkit 110. The PC Meter Toolkit 110 provides a list of the available PSDs from which the user selects a desired PSD for a particular transaction.

The COM/DCOM network concept provides mechanisms for a remote Client PC to gain access rights to the PC Meter Toolkit component in a PC Meter Server. Optionally, every Client PC can be given access rights to the PC Meter Server, whereby the PC Meter Server's PSD PIN (password) can be used to authorize access to postage functions in the PC Meter Server and its PSD. By default, all PSDs are considered remotely accessible by all Client PCs unless configured differently by the user. Alternatively, the list of available PSDs can be customized based on user or system filters. For example, only sharing vaults whose origin zip matches the return address of the mail piece. In the preferred embodiment, the PSD is not active during access for authorization because PIN validation is performed by the PC Meter Server. The PC Meter Server obtains the PSD PIN from the PSD to perform validation. In an alternate embodiment, the PIN validation could occur within the PSD. This is a secure process because the PIN is stored in the PSD.

During the creation of a mailpiece, the user performs the following functions whether the PC meter is operated in stand-alone mode or network mode. The user can select CD-ROM addressing or dialup addressing (at the Data Center 5) to obtain correct addressee information. The user can choose the class of mail service (rate category) for the mailpiece. The user can select from a list of rate categories that are authorized by the Post Office. The user can view an indicium on the monitor while designing the mailpiece and print

preview the mailpiece with an indicium image. PC Meter Toolkit 110 provides a method to draw the indicium image and 2D bar code before printing. The indicium may be marked as visible or invisible for display purposes. See U.S. Patent No. 5,988,897 entitled METHOD FOR PREVENTING FRAUDULENT PRINTING OF A POSTAGE INDICIUM DISPLAYED ON A PERSONAL COMPUTER filed September 3, 1997 and assigned to the assignee of the present invention, which discloses a method for preventing fraudulent printing of a postage indicium displayed on a personal computer. The user can change the postage amount, class of service and date of mailing. These changes are reflected in the indicium image.

PC Meter Toolkit 110 provides postal funds security because the user can not print an indicium without accounting for a debit to the PSD. Furthermore, there is no direct access to the indicium image, except through the PC Meter Toolkit transactions. The PC Meter Toolkit uses atomic transactions to tie the debit to PSD with the enabling of printing of the indicium image. The atomic transaction ensures that the debit to the PSD is complete before printing the indicium.

The transaction log stores funds transactions for PSD dispensing and refills. For Network PC Metering System 10, each Client PC stores the daily transaction log file for its local PSD(s). The user may select the local drive and directory path for the log file. For Network PC Metering System 10', each Client PC forwards transaction information for its local PSD(s) to Network Server 30 which stores the daily transaction log file. Once the accounting for a mailpiece transaction is completed, the client application requesting the transaction spools the mail piece corresponding to the transaction to the PC print manager for printing the indicium.

Network PC Metering System (10 or 10') has many Client PC's with or without PSD(s) attached. Each Client PC has access to both its own local PSD(s) and remote PSDs in the network. Each Client PC can run its client application to dispense postage and initiate registration and refills.

As previously stated, Network PC Metering System (10 or 10') processes transactions for dispensing postage, PSD registration, and PSD refill on the Client PC 20 where the specific PSD 40 is located. This requires

the transaction processing to be performed remotely if the user is accessing a remote PSD. Modems for accessing Data Center 5 are preferably located on each Client PC 20 having a PSD 40 coupled thereto. However, a single modem may be located on the Network Server 30 instead of several modems on each Client PC 20 having a PSD 40 coupled thereto. In this manner, PSD registrations, and PSD refills are processed through Network Server 30.

The software components for the Network PC Metering System (10 or 10') include the software components for the Stand-alone PC Meter along with two additional components, listed below.

Referring now to Fig. 4, a Client PC 20 enters Meter Server PC 21 mode when another Client PC 20 on the network initiates remote access of PSD 41 through its PC Meter Toolkit 110. Meter Server PC 21 processes the functions for PSD registration, PSD refill, and postage dispensing as transactions for PSD 41. Processing is performed at Meter Server PC 21 by the previously described PC Meter Toolkit 110 residing in Meter Server 21 and at Client PC 20 by the PC Meter Toolkit 110 residing in Client PC 20.

Using a DCOM implementation, the PC Meter Toolkits 110 residing in the Client PC 20 and the Meter Server 21 operate in conjunction with each other such that the remote requesting Client PC 20 and Meter Server PC 21 operate collectively as a PC meter regardless of PSD/Toolkit location. The PC Meter Toolkit 110 residing in Meter Server 21 handles messages from and to the requesting Client PC 20, and handles standard metering functions, such as dispensing postage, PSD refills, and PSD registration, for PSD 41 in the same manner as when in stand-alone mode.

Referring now to Fig. 5, at step 200, Client PC 20 sends a request through its PC Meter Toolkit 110 to remote PSD 41 for postal value for a mailpiece. At step 205, Meter Server 21 determines whether the Client PC 20 is authorized to make the request. If not authorized, then at 210, Meter Server 21 responds to Client PC 20 that it is not authorized to access PSD 41. If authorized, then at step 215, Meter Server 21 processes the request through its PC Meter Toolkit 110 sends the request to PSD 41 with information received from remote Client PC 20. At step 220, PSD 41 dispenses the requested postal value including a digital signature based on the request. At step 230, Meter Server 21 through its PC Meter Toolkit 110

records the transaction information in a transaction log on its hard drive. At step 235, Meter Server 21 sends the digital signature and at least some of the transaction information to remote Client PC 20. At step 240, Client PC 20 receives the digital signature and transaction information and, at step 245, Client PC 20 generates an indicium bitmap and prints the indicium including digital signature on mailpiece.

Referring now to Fig. 6, the steps of the preferred embodiment of the present invention are shown. At step 300, a user at one of the Client PCs requests a list of available PSDs on the network. At step 305, the user selects a PSD from the list. If, at step 310, the selected PSD is a PSD local to the user's Client PC, then, at step 330, PC Meter Toolkit 110 in the user's Client PC requests a postal amount for a mailpiece from the local PSD, sending information to the PSD including addressee information and the process continues at step 335 below. If the user selected a remote PSD, then at step 315, PC Meter Toolkit 110 in the user's Client PC requests access to the selected remote PSD at one of the other Client PCs. If, at step 320, access to the remote PSD is granted, then at step 330, the PC Meter Toolkit 110 at the other Client PC requests a postal amount for a mailpiece from the remote PSD, sending information to the remote PSD including addressee information. If access is not granted then, at step 325, an error is reported.

At step 335, the accessed PSD (local or remote) deducts the requested postal amount from a total postal value stored in the PSD and generates a signature using information supplied with the request including the addressee information. At step 340, the PSD sends transaction information including the signature to the requesting Client PC. At step 345, the PC Meter Toolkit 110 of the requesting Client PC generates and prints indicium including the signature.

It will be understood that the process of selecting a local or remote PSD may be done automatically by the PC Meter Toolkit 110 of the requesting Client PC. For example, the automatic PSD selection may be based on matching the origin zip code of the PSD to the zip code of the return address of the mailpiece.

Networked Operations

Microsoft's Windows 95™ and Windows NT™ operating systems provide facilities through DCOM and other mechanisms to implement network communications. Through the use of DCOM, objects can communicate via a mechanism referred to as connection points, which can be used to implement direct communication, multi-casting (more than one client receives messages), or broadcasting (all clients receive messages). This can be done between processes on the same computer or multiple computers on a network or on the internet. Mailslots is another Windows mechanism that permits the same communications facilities. The PC Meter Toolkit 110 uses these facilities to exchange information about the location and disposition of PSDs on the network.

When a Client PC logs into the network, the PC Meter Toolkit 110 running on the Client PC registers the necessary connection points; one common to all PC Meter Toolkits on the network, and one specific to the Client PC itself. The common connection point is used to send and receive multi-casted messages from all Clients. The specific connection point is for messages intended solely for one particular Client PC Meter Toolkit, such as a request or response for evidence of postage payment.

Upon initialization, the Client PC's PC Meter Toolkit 110 uses the common connection point to send a message for all other PC Meter Toolkits to respond with available PSDs. PC Meter Toolkits running on PC Meter Servers 21 then respond to the Client PC's specific connection point with information about the location and identities of any attached PSDs. Referring to figure 2A, the list of available PSDs is consolidated and presented to applications that require postage metering functions. Referring to Figure 2B, the list of available PSDs is consolidated along with locally attached PSDs and the complete list presented to applications that require postage metering functions. In this case, the PC Meter Toolkit 110 also sends messages to the common PC Meter Toolkit connection points indicating that another PSD is available for use by other PC Meter Toolkits.

When a remote Client PC 20 selects a PSD 40 to use, the PC Meter Toolkit 110 uses the information collected at initialization to know where the particular PSD is located, and how to communicate with it.

In operation, the PC Meter Toolkit 110 also handles messages regarding the status of PC Meter Toolkits 110 on the network. Should new PC Meter Toolkits be started on other Client PCs 20, the local PC Meter Toolkit responds with information regarding any attached PSDs 40. Should
 5 messages be received indicating that a new PC Meter Client 20 has come on-line with its own PSD(s) 40, the PC Meter Toolkit updates its list of available PSDs. Similarly, if a Client PC 20 is shutting down, messages are sent to all Client PCs indicating that any local PSDs will no longer be available. It is noted that all messages between PC Meter Toolkits 110 can be encrypted for
 10 added security.

The effect of the Client PC Startup and Shutdown multi-casts is that all Client PCs 20 dynamically know exactly which PSDs 40 are available. Clients also have the ability to ask explicitly for a refreshed list of available PSDs 40 since it is possible that a machine can go off-line without proper notification.
 15 DCOM also provides mechanisms for this with continual pinging to catch computers improperly notifying clients/servers.

Centralized vs. Distributed Processing On the Network

A PC Metering system must account for funds for all mail pieces and
 20 refills. This requires saving transaction records in a sequential transaction log file. Both postage dispensing and refills should be kept in the same sequential file such that meter discrepancies, such as discrepancies due to meter movement between Client PCs on the network, can be reconciled. The following paragraphs summarize the impact of using centralized vs.
 25 decentralized accounting for the transaction log on a network metering system.

In a network metering configuration, if accounting for funds is summarized by a user, transactions could be logged where the user is located. This would require consolidating log files only if the user has more
 30 than one PC at which transactions can be initiated, i.e., the user moves between PCs). This method uses decentralized accounting, logging transactions on the user's PC.

If accounting for funds is summarized by a meter, transactions should be logged where the meter, i.e. the PSD, is located. This would require

consolidating log files only if the PSD could be attached to any PC (PSD moves between PCs). This method uses decentralized accounting, logging transactions on the PSD's PC.

5 If accounting for funds is summarized by department (i.e. departments have several users that can access several PSDs), transactions must be consolidated if the logging of transactions was performed where the user is located or where the PSD is located.

10 An alternative to such consolidation of log files from PCs is a centralized accounting and logging of all transactions on same PC or a centralized server. Transactions would have to be sent to the Network Server PC for every mail piece, producing heavy network traffic. If the centralized server is down, or otherwise not available, then no postage dispensing or refills can occur, disabling metering capabilities over the entire network. A centralized server for Network PC Metering System is not the preferred
15 embodiment of the present invention.

Network PC Metering Systems 10 and 10' are representative of distributed processing of the metering transaction. Network PC Metering System 10 involves local transaction processing requested by a requesting Client PC 20, and remote accounting and logging at the Meter Server PC 21,
20 i.e., where the PSD 40 and transaction log file 44 are located. Network PC Metering System 10' involves local transaction processing by the requesting Client PC 20, remote accounting at the Meter Server PC 21, i.e., where the PSD 40 is located, and remote logging at the Network Server 30, i.e. where transaction log file 44 is located. Thus, the transaction processing is split from
25 the accounting functionality in distributed processing. The steps of the transaction are split between different PCs of the network.

There is an advantage to configuring network metering for distributed processing, such as In Network PC Metering Systems 10 and 10'. If Network Server 30 is down, metering transactions may still be performed when Client
30 PCs having PSDs coupled thereto operate in stand-alone mode. Furthermore, network-metering transactions may be performed even when a Client PC 20 with a PSD attached thereto is not logged on the network. For example, the Client PC not logged on the network can operate in stand-alone

mode, and the Client PCs logged on the network can access other Client PCs having PSDs coupled thereto.

When a Client PC is attempting to access remote PSDs on the network, an optional prioritized list of available PSDs can be displayed to the user for selection. The prioritized ordering of the available PSDs may use the following heuristics:

1. PSDs sharing the same ZIP as the originating address of the mailpiece
2. Local PSDs (same location as the Client PC)
- 10 3. Remote PSDs sharing the same origin ZIP as the local PSDs
4. PSDs having the same three digit ZIP as items 1-3
5. Remaining PSDs

The preferred embodiment of the present invention has been described based on a Windows operating system for the Client computers. It will be understood that the present invention is suitable for use with any computer operating system. It will further be understood that although the embodiments of the present invention are described as postage metering systems, the present invention is applicable to any value metering system that includes transaction evidencing, such as monetary transactions, item transactions and information transactions.

The preferred embodiment has been described for an open system metering network. It will be understood that the present invention applies also to a closed system metering network wherein digital postage meters are used in place of the Client PCs described in the preferred embodiment. Such a closed system metering network is shown in Fig. 8. A Network Metering System, generally designated 510, includes a plurality (five are shown) of Client modules 520 conventionally coupled to a Network Server 530, such as a personal computer. The Client modules are digital printers that are dedicated to printing postage indicium. Each Client module resembles a conventional digital metering system with optional display, keyboard, and printer 522, however, some of the Client modules do not have an accounting module or PSD attached thereto. Preferably, a plurality of PSDs 540 (two are shown) exists in Network Metering System 510, with at least one PSD 40 being coupled to several Client modules 20. The PSDs 540 are accounting

modules similar to accounting units in conventional electronic postage meters. When a specific PSD 540 is accessed for a metering transaction, the Client module 520, to which the PSD 40 is attached, becomes a Meter Server 521 (shown within parenthesis) for the remainder of the transaction. When the PSD 540 is being accessed by the Client module 520 to which the PSD is coupled the Client module 520 is functioning as a conventional meter. A more detailed description of a closed system metering network is provided in previously noted related Canadian Patent Application No. 2,256,275.

While the present invention has been disclosed and described with reference to the embodiments thereof, it will be apparent, as noted above, that variations and modifications may be made therein. It is, thus, intended in the following claims to cover each variation and modification that falls within the true spirit and scope of the present invention.

Windows 95 and Windows NY are trademarks of Microsoft Corporation.

What is Claimed is:

1. A postage metering system comprising:

a plurality of printing means operatively connected as part of a network and operating as client printing means on the network, the client printing means including processor, memory and storage means;

a postal security device (PSD) coupled directly to a first one of the client printing means (local client printing means); the PSD including unique identification, postal value storage means and digital signature means;

means in the client printing means for functioning as a postage metering network wherein one of the client printing means remote to the PSD requests first evidence of postage payment from the PSD through the local client printing means for concluding postage metering transactions; and

means in the local client printing means for functioning as a stand-alone meter when requests for second evidence of postage payment from the PSD are initiated at the local client printing means.

2. The postage metering system of claim 1 wherein the local client printing means comprise:

means for initiating a local request for second evidence of postage payment to be printed at the local client printing means;

means for receiving a first remote request for the first evidence of postage payment from one of the remote the client printing means, the first remote request including identification of the remote client printing means;

means for sending the requests for first and second evidence of postage payment to the PSD;

means for receiving from the PSD the first and second evidence of postage payment including a digital signature corresponding to said each of the first and second evidence of postage payment;

means for sending the first evidence of postage payment to the remote client printing means in response to the remote request; and

means for printing the second evidence of postage payment in response to the local request.

3. The postage metering system of claim 2 wherein the local client printing means further comprises:

means for storing transactional information for requests for the first and second evidence of postage payment.

4. The postage metering system of claim 3 wherein the local client printing means determines whether the remote client printing means is authorized to request evidence of postage payment from the PSD.

5. The postage metering system of claim 3 wherein the PSD determines whether the client printing means is authorized to request evidence of postage payment from the PSD.

6. The postage metering system of claim 2 wherein the client printing means includes general purpose computers.

7. The postage metering system of claim 2 wherein the client printing means are meter printers.

8. The postage metering system of claim 2 wherein the local client printing means further comprise:

means for initiating a second remote request to one of the remote client printing means for third evidence of postage payment to be printed at the local client printing means; and

means for receiving the third evidence of postage payment from the remote client printing means wherein said local client printing means prints the third evidence of postage payment in response to the second remote request.

9. The postage metering system of claim 8 wherein said one of the remote client printing means is coupled to a remote PSD which provides said third evidence of postage payment in response to said second remote request.

10. A postage metering system comprising:

a plurality of general purpose computers (computers) operatively connected as part of a computer network and operating as client computers on the computer network;

a postal security device (PSD) coupled directly to a first one of the client computers (local client computer); the PSD including unique identification, postal value storage means and digital signature means;

means in the client computers for functioning as a postage metering network wherein one of the client computers remote to the PSD requests first evidence of postage payment from the PSD through the local client computer for concluding postage metering transactions; and

means in the local client computer for functioning as a stand-alone meter when requests for second evidence of postage payment from the PSD are initiated at the local client computer.

11. The postage metering system of claim 10 wherein the local client computer comprises:

means for initiating a local request for second evidence of postage payment to be printed at the local client computer;

means for receiving a first remote request for the first evidence of postage payment from one of the remote the client computers, the first remote request including identification of the remote client computers;

means for sending the requests for first and second evidence of postage payment to the PSD;

means for receiving from the PSD the first and second evidence of postage payment including a digital signature corresponding to said each of the first and second evidence of postage payment;

means for sending the first evidence of postage payment to the remote client computers in response to the remote request; and

means for printing the second evidence of postage payment in response to the local request.

12. The postage metering system of claim 11 wherein the local client computer further comprises:

means for storing transactional information for requests for the first and second evidence of postage payment.

13. The postage metering system of claim 10 wherein the local client computer determines whether the remote client computers are authorized to request evidence of postage payment from the PSD.

14. The postage metering system of claim 10 wherein the PSD determines whether the remote client computers are authorized to request evidence of postage payment from the PSD.

15. A transaction evidencing system comprising:

a plurality of general purpose computers (computers) operatively connected as part of a computer network and operating as client computers on the computer network, at least some of the client computers including transaction evidencing software that selectively runs on the client computers;

a transaction security device (TSD) coupled directly to a first one of the client computers (local client computer); the TSD including unique identification, transaction evidencing storage means, digital signature means, and transaction accounting means;

means in the client computers for functioning as a transaction evidencing network wherein one of the client computers remote to the TSD requests and obtains first transaction evidencing from the TSD through the local client computer for concluding transaction evidencing transactions; and

means in the local client computer for functioning as a stand-alone transaction evidencing device when requests for second transaction evidencing from the TSD are initiated at the local client computer.

16. The system of claim 15 wherein the local client computer comprises:

means for initiating a local request for second transaction evidencing to be printed at the local client computer;

means for receiving a first remote request for transaction evidencing from one of the remote the client computers, the first remote request including identification of the remote client computer;

means for sending the requests for first and second transaction evidencing to the TSD;

means for receiving from the TSD the transaction evidencing including a digital signature corresponding to said each of the first and second transaction evidencing;

means for sending the first transaction evidencing to the remote client computers in response to the remote request; and

means for printing the second transaction evidencing in response to the local request.

17. The system of claim 16 wherein the local client computer further comprises:

means for storing transactional information for requests for the first and second transaction evidencing processed by the TSD.

18. The system of claim 15 wherein the local client computer determines whether the remote client computers are authorized to request evidence of postage payment from the TSD.

19. The system of claim 15 wherein the TSD determines whether the remote client computers are authorized to request transaction evidencing from the TSD.

20 A method for postage metering wherein a postage meter has dual modes of operation as a stand-alone meter and as a meter server on a network, the method comprising the steps of:

providing a plurality of client modules on a network;

coupling a local postage security device (PSD) to a first one of said client modules and a remote PSD to a second one of said client modules, the PSDs each including unique identification, postal value storage means and digital signature means;

providing means in said first client module for requesting and obtaining first postage evidencing from the local PSD;

providing means in said second client module for requesting and obtaining second postage evidencing from the local PSD; and

providing means in said first client module for receiving and responding to said request from said second client module.

21. The method of claim 20 further including the steps of:

providing means in said first client module for requesting and obtaining third postage evidencing from the remote PSD;

providing means in said second client module for printing on a mailpiece said second postage evidencing using second printing means coupled to said second client module; and

providing means in said first client module for printing on a mailpiece said first postage evidencing or said third postage evidencing using first printing means coupled to said first client module.

22. The method of claim 21 further including the steps of:

providing means in said first client module for selecting one of said local PSD and said remote PSD for obtaining postage evidencing; and

providing means in said second client module for receiving said request for said second postage evidencing and means for sending said request for said second postage evidencing to said remote PSD.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

