



US010194530B2

(12) **United States Patent**  
**Chang et al.**

(10) **Patent No.:** **US 10,194,530 B2**

(45) **Date of Patent:** **\*Jan. 29, 2019**

(54) **MICROELECTRONIC SYSTEM INCLUDING PRINTED CIRCUIT BOARD HAVING IMPROVED POWER/GROUND BALL PAD ARRAY**

(58) **Field of Classification Search**  
CPC ..... H05K 1/111; H05K 1/0298; H05K 1/115; H05K 1/0262; H05K 2201/10734  
(Continued)

(71) Applicant: **MEDIATEK INC.**, Hsin-Chu (TW)  
(72) Inventors: **Sheng-Ming Chang**, New Taipei (TW);  
**Chia-Hui Liu**, Taichung (TW);  
**Shih-Chieh Lin**, Taipei (TW);  
**Chun-Ping Chen**, New Taipei (TW)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,371,407 A \* 12/1994 Goldman ..... H01L 21/4803  
257/675

6,198,635 B1 3/2001 Shenoy  
(Continued)

(73) Assignee: **MEDIATEK INC.**, Hsin-Chu (TW)

FOREIGN PATENT DOCUMENTS

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

CN 101801154 A 8/2010  
TW 348366 12/1998  
(Continued)

This patent is subject to a terminal disclaimer.

*Primary Examiner* — Timothy Thompson

*Assistant Examiner* — Charles Pizzuto

(74) *Attorney, Agent, or Firm* — Winston Hsu

(21) Appl. No.: **15/847,852**

(22) Filed: **Dec. 19, 2017**

(65) **Prior Publication Data**

US 2018/0116051 A1 Apr. 26, 2018

**Related U.S. Application Data**

(63) Continuation of application No. 15/431,781, filed on Feb. 14, 2017, now Pat. No. 9,883,591, which is a  
(Continued)


(57) **ABSTRACT**

A microelectronic system includes a base and a semiconductor package mounted on the base. The base includes an internal conductive layer and a build-up layer on the internal conductive layer. The build-up layer includes a top conductive layer. A plurality of microvias is disposed in the build-up layer to electrically connect the top conductive layer with the internal conductive layer. A power/ground ball pad array is disposed in the top conductive layer. The power/ground ball pad array includes power ball pads and ground ball pads arranged in an array with a fixed ball pad pitch P, and the power/ground ball pad array includes a 4-ball pad unit area comprised of only one ground ball pad and three power ball pads, or comprised of only one power ball pad and three ground ball pads. The 4-ball pad unit area has a rectangular shape and a dimension of about 2P×2P.

(51) **Int. Cl.**  
**H05K 1/11** (2006.01)  
**H05K 1/02** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **H05K 1/115** (2013.01); **H01L 23/49816**  
(2013.01); **H01L 23/49822** (2013.01);  
(Continued)

**22 Claims, 7 Drawing Sheets**



**Related U.S. Application Data**

(56)

**References Cited**

- continuation of application No. 14/860,718, filed on Sep. 22, 2015, now Pat. No. 9,609,749.
- (60) Provisional application No. 62/080,019, filed on Nov. 14, 2014.
- (51) **Int. Cl.**  
*H01L 23/498* (2006.01)  
*H01L 23/50* (2006.01)  
*H01L 23/00* (2006.01)  
*H05K 1/05* (2006.01)  
*H05K 1/18* (2006.01)
- (52) **U.S. Cl.**  
 CPC ..... *H01L 23/49827* (2013.01); *H01L 23/50* (2013.01); *H01L 24/16* (2013.01); *H05K 1/0262* (2013.01); *H05K 1/0298* (2013.01); *H05K 1/05* (2013.01); *H05K 1/111* (2013.01); *H05K 1/114* (2013.01); *H05K 1/181* (2013.01); *H01L 23/49838* (2013.01); *H01L 2224/16225* (2013.01); *H01L 2224/32225* (2013.01); *H01L 2224/73204* (2013.01); *H01L 2924/15311* (2013.01); *H01L 2924/181* (2013.01); *H05K 2201/095* (2013.01); *H05K 2201/09227* (2013.01); *H05K 2201/09509* (2013.01); *H05K 2201/10378* (2013.01); *H05K 2201/10674* (2013.01); *H05K 2201/10734* (2013.01)
- (58) **Field of Classification Search**  
 USPC ..... 174/262  
 See application file for complete search history.

U.S. PATENT DOCUMENTS

7,888,803	B2	2/2011	Kariya	
8,119,931	B1	2/2012	Liu	
8,284,564	B2	10/2012	Mizuno	
8,872,350	B2	10/2014	Sawachi	
2001/0035746	A1*	11/2001	Burstein	H01L 23/5386 323/283
2002/0084107	A1*	7/2002	Chang	H01L 23/49838 174/262
2003/0045083	A1	3/2003	Towle	
2004/0183213	A1	9/2004	Hsu	
2004/0227163	A1	11/2004	Sakamoto	
2005/0098882	A1*	5/2005	Kusagaya	H05K 3/4602 257/734
2009/0188707	A1*	7/2009	van den Hoek	H05K 3/4038 174/257
2010/0202123	A1	8/2010	Mizuno	
2011/0019379	A1	1/2011	Shibuya	
2014/0116765	A1	5/2014	Hossain	
2014/0334121	A1	11/2014	Ito	
2015/0054159	A1*	2/2015	Hoegerl	H01L 23/3735 257/762
2015/0083602	A1	3/2015	Nichols	
2015/0124419	A1	5/2015	Wong	
2015/0187966	A1*	7/2015	Asthana	H01L 31/02245 438/64

FOREIGN PATENT DOCUMENTS

TW	200616505	5/2006
TW	200806107	1/2008

\* cited by examiner




FIG. 1




FIG. 2






FIG. 4




FIG. 5




FIG. 6




FIG. 7

**MICROELECTRONIC SYSTEM INCLUDING  
PRINTED CIRCUIT BOARD HAVING  
IMPROVED POWER/GROUND BALL PAD  
ARRAY**

CROSS REFERENCE TO RELATED  
APPLICATION

This application is a continuation of U.S. application Ser. No. 15/431,781 filed Feb. 14, 2017, which itself is a continuation of U.S. application Ser. No. 14/860,718 filed Sep. 22, 2015. U.S. application Ser. No. 14/860,718 claims the benefit of U.S. provisional application No. 62/080,019 filed Nov. 14, 2014. The above-mentioned applications are included in their entirety herein by reference.

BACKGROUND

The present invention relates to semiconductor technology fields. More particularly, the present invention relates to a microelectronic system involving an improved power/ground ball pad array on a printed circuit board (PCB) that is capable of reducing board-level IR drop.

An integrated circuit (IC) device typically includes an IC chip that is housed in a package. The IC chip typically includes a circuit fabricated by lithographically patterning conductive and insulating materials on a thin wafer of semiconductor using known fabrication techniques. The package supports and protects the IC chip and provides electrical connections between the circuit and an external circuit board. Several known package types are used to house IC chips, such as ball grid arrays (BGAs), pin grid arrays (PGAs), plastic leaded chip carriers, plastic quad flat packs and others, for example.

A ball grid array (BGA) package for higher performance applications is known in the art. A BGA package is typically joined to a mounting board by use of conductive balls (bumps) arranged in an array on its back as external terminals, instead of using a lead frame. Because the entire back surface of the semiconductor package can be used for connection to the board, the number of input/output pads can be markedly increased. To support higher functionality, the number of pins has remarkably increased.

As system complexity and operational speeds increase, the power consumption of integrated circuits increases dramatically. Additionally, the IC supply voltage continues to drop with the inevitable scaling of VLSI technology. Reducing the nominal supply voltage is accompanied by a reduction in device noise margins, making components more vulnerable to power supply noise. This noise consists of the dynamic AC voltage fluctuation due to the frequency dependent distributed parasitics inherent in today's power distribution systems, and the DC voltage drop (i.e., "IR" drop).

In a microelectronic system, the system's IR drop may be budgeted into three portions: on-chip, package and board. On-chip IR drop has been extensively studied because the resistive loss is severe due to the fine feature-size of the on-die power grid. On the other hand, package and board-level IR drop have not been given much attention. Due to increased current requirements and reduced supply voltage noise margins, package and board IR drop now can have a significant impact on the operation of high-speed devices.

Several factors contribute to increased off-chip path resistances. In multilayer IC packages such as BGAs, for example, the power distribution usually traverses multiple layers from the balls to the chip connect bumps. These paths are much shorter than those on the board; however, package

power and ground planes usually require much more irregular shapes to accommodate the chip I/O breakout and usually are not allowed to fill an entire plane. Many packages also contain a number of power domains, but a very limited number of layers are available for their distribution.

Therefore, it is common for power distributions to contain complex shapes and other non-ideal routing. Printed circuit boards have their own share of issues as well. In large and complex PCBs, the power distribution system may have to traverse several feet of planes and traces to reach the far-end devices. Therefore, far-end devices will see a larger voltage drop. Because of the long distribution paths, it is possible for designs to deliver insufficient voltage to some devices. Therefore, for high-current and low-voltage designs, it is becoming critically important to include package and board IR drop into the total noise budget of the system.

SUMMARY

It is an objective of the claimed invention to provide a microelectronic system involving an improved printed circuit board (PCB) having a novel power/ground ball pad array that is capable of reducing board-level IR drop.

According to one aspect of the invention, a microelectronic system includes a base and a semiconductor package mounted on the base. The base includes an internal conductive layer and a build-up layer on the internal conductive layer. The build-up layer comprises a top conductive layer. A plurality of microvias is disposed in the build-up layer to electrically connect the top conductive layer with the internal conductive layer. A power/ground ball pad array is disposed in the top conductive layer. The power/ground ball pad array comprises power ball pads and ground ball pads arranged in an array with a fixed ball pad pitch P, and the power/ground ball pad array comprises a 4-ball pad unit area comprised of only one ground ball pad and three power ball pads, or comprised of only one power ball pad and three ground ball pads. The 4-ball pad unit area has a rectangular shape and a dimension of about  $2P \times 2P$ .

According to another aspect of the invention, a microelectronic system includes a base and a semiconductor package mounted on the base. The base includes an internal conductive layer and a build-up layer on the internal conductive layer. The build-up layer comprises a top conductive layer. A plurality of microvias is disposed in the build-up layer to electrically connect the top conductive layer with the internal conductive layer. A power net is disposed in the top conductive layer. The power net comprises a plurality of power ball pads arranged and interconnected in a comb-shaped pattern. A ground net is disposed in close proximity to the power net and coupled to the power net in an interdigitated fashion. The ground net comprises a plurality of ground ball pads arranged and interconnected in an inverted comb-shaped pattern so that said ground net is interdigitated with the power net.

According to still another aspect of the invention, a microelectronic system includes a base and a semiconductor package mounted on the base. The base includes an internal conductive layer and a build-up layer on the internal conductive layer. The build-up layer comprises a top conductive layer. A plurality of microvias is disposed in the build-up layer to electrically connect the top conductive layer with the internal conductive layer. A power net is disposed in the top conductive layer. The power net comprises a plurality of power ball pads arranged in cascade. A ground net is disposed in close proximity to the power net and coupled to

the power net in an interdigitated fashion. The ground net comprises a plurality of ground ball pads arranged in cascade.

These and other objectives of the present invention will no doubt become obvious to those of ordinary skill in the art after reading the following detailed description of the preferred embodiment that is illustrated in the various figures and drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings are included to provide a further understanding of the invention, and are incorporated in and constitute a part of this specification. The drawings illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention. In the drawings:

FIG. 1 illustrates a cross-sectional representation of a microelectronic system according to one embodiment of the invention;

FIG. 2 illustrates an exemplary cross-sectional diagram showing a portion of a high-density multi-layer PCB according to one embodiment of the invention;

FIG. 3 is a top schematic plan view showing a portion of the power/ground ball pad array in the first layer ( $L_1$ ) of the exemplary high-density multi-layer PCB as depicted in FIG. 2;

FIG. 4 is a schematic plan view showing a portion of the via arrangement in the second layer ( $L_2$ ) of the exemplary high-density multi-layer PCB, wherein the illustrated area portion in FIG. 3 is approximately aligned with the area portion shown in FIG. 4;

FIG. 5 is an enlarged view showing two adjacent ball pad units of FIG. 3;

FIG. 6 is a top schematic plan view showing a portion of the power/ground ball pad array in the first layer ( $L_1$ ) of the exemplary high-density multi-layer PCB; and

FIG. 7 is a schematic plan view showing a portion of the via arrangement in the second layer ( $L_2$ ) of the exemplary high-density multi-layer PCB, wherein the illustrated area portion in FIG. 6 is approximately aligned with the area portion shown in FIG. 7.

#### DETAILED DESCRIPTION

In the following detailed description of embodiments of the invention, reference is made to the accompanying drawings, which form a part hereof, and in which is shown by way of illustration specific preferred embodiments in which the disclosure may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice them, and it is to be understood that other embodiments may be utilized and that mechanical, chemical, electrical, and procedural changes may be made without departing from the spirit and scope of the present disclosure. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of embodiments of the present invention is defined only by the appended claims.

BGA packages such as Flip-chip BGA packages, wire-bond BGA, or Fan-Out WLPs (Fan-Out Wafer Level Packages), continue to evolve in terms of complexity, and on-die voltages continue to decrease with advances in deep sub-micron technology. Because the signals and voltages in package planes are large in comparison to the proximity of the IC components and the package planes, proximity effects take on more and more importance to the operation of the integrated circuit.

A high IR drop results in increased power consumption and reduced signal timing speed. Therefore, there is a need in this industry to provide an improved power/ground ball pad array on a printed circuit board (PCB) that is capable of reducing board-level IR drop in a microelectronic system. The present invention addresses this issue.

FIG. 1 illustrates a cross-sectional representation of a microelectronic system **1** comprising a semiconductor package **10** such as a BGA package mounted on a top surface of a high-density multi-layer printed circuit board (PCB) **20**. For example, the semiconductor package **10** may be a flip-chip BGA, but not limited thereto. It is to be understood that other types of BGA packages such as wire-bond BGA, Fan-Out packages, etc. may be employed. According to the illustrative embodiment, for example, the semiconductor package **10** comprises a flip chip **110** mounted on a first side (chip side) of a packaging substrate **120**. For example, the flip chip **110** may be a CPU or an SOC (System-On-a-Chip) of a mobile phone platform according to the illustrative embodiment.

It is to be understood that the semiconductor package **10** may further comprise other chips or chip packages to thereby form a System-In-a-Package (SiP), a Package-on-Package (PoP), etc.

Generally, in a flip-chip BGA, the electrically conductive terminals on the inverted "upper" surface of the flip chip **110** are soldered directly to corresponding lands of a die bond area on the surface of the packaging substrate **120** using reflowable solder bumps **112**. The semiconductor package **10** is then couple to the PCB **20** using solder bumps or balls **122**.

The semiconductor package **10** may further comprise an underfill **114** interposed between the flip chip **110** and the packaging substrate **120**. The underfill **114** may be a specially engineered epoxy that fills the gap between the flip chip **110** and the packaging substrate **120**, surrounding the bumps **112**. It is designed to control the stress in the solder joints caused by the difference in thermal expansion between the flip chip **110** and the packaging substrate **120**. Once cured, the underfill **114** absorbs the stress, reducing the strain on the bumps **114**, greatly increasing the life of the finished package. It is to be understood that in some cases, the underfill **114** may be omitted. The semiconductor package **10** may further comprise a molding cap **116** that at least encapsulates the flip chip **110** for protection purposes.

The solder balls **122** may comprise an array of power balls and ground balls (not explicitly shown), which are typically disposed in an approximately central area of the bottom surface of the semiconductor package **10**. Further, it is understood that multiple power nets and ground nets may be provided. These power balls and ground balls are aligned and joined to corresponding ball pads **200** on the package-mounting surface **20a** of the PCB **20**.

FIG. 2 illustrates an exemplary cross-sectional diagram showing a portion of the high-density multi-layer PCB **20**. For example, the high-density multi-layer PCB **20** may be a high-density interconnect (HDI) circuit board having 4 to 10 layers, for example, HDI-1, HDI-2, HDI-3, HDI-4, or ELIC (every layer inter-connection) PCB. For illustration purposes only, FIG. 2 depicts a 6-layer (1+4+1) PCB. However, it is understood that the present invention may be applicable to other types of PCBs.

As shown in FIG. 2, the high-density multi-layer PCB **20** comprises a laminated core **210** and build-up layers **212** and **214** sandwiching about the laminated core **210**. The build-up layers **212** and **214** may be formed on the laminated core **210** using any resin build-up method and metallization process

known in the art. For example, the build-up layers **212** and **214** may comprise BT resin and plated copper layer. A plurality of microvias **220a** may be formed in the build-up layer **212** to electrically connect the top conductive layer ( $L_1$  or the 1st layer) with the internal conductive layer ( $L_2$  or the 2nd layer) of the laminated core **210**. A plurality of microvias **220b** may be formed in the build-up layer **214** to electrically connect the bottom conductive layer ( $L_6$  or the 6th layer) with the internal conductive layer ( $L_5$  or the 5th layer) of the laminated core **210**. The microvias **220a** and **220b** may be formed using laser-drilling techniques and may have a via diameter size ranging between 0.05-0.2 mm, for example.

An exemplary buried through via **230a** may be provided to penetrate through an entire thickness of the laminated core **210** for interconnection. For example, the buried through via **230a** may be filled with epoxy resin. An exemplary plated through hole (PTH) **230b** may be provided to penetrate through an entire thickness of the 6-layer PCB for component pins. The buried through via **230a** and the PTH **230b** may be formed by using mechanical drilling techniques and may have a larger hole diameter ranging between 0.25-0.5 mm, for example. According to the embodiment of the invention, the bottom ( $L_6$ ) conductive layer may be used as a ground plane, but not limited thereto.

Normally, a solder mask **252** may be coated on the build-up layer **212** to protect the top conductive layer ( $L_1$ ) and a solder mask **254** may be coated on the build-up layer **214** to protect the bottom conductive layer ( $L_6$ ). Solder mask openings **252a** and **254a** may be formed in the solder masks **252** and **254**, respectively, to expose the corresponding ball pads **200**.

It is to be understood that various PCB standard parameters (e.g. layers, stack-up and via type, etc.) may be employed depending upon design requirements. For example, the PCB standard parameters may comprise a layer count (e.g. 6, 8 or 10 layers), a stack-up setting (e.g. high density interconnect HDI-1 or HDI-2; and a via type: stagger via or stacked via), wherein HDI-1 stands for 1+4+1 6-layer PCB and HDI-2 stands for 1+1+2+1+1 6-layer PCB, for example. Moreover, the PCB standard parameters may comprise a component placement parameter indicating that the components such as capacitors or resistors may be mounted on a single-sided or double-sided PCB.

Please refer to FIG. 3 and FIG. 4. FIG. 3 is a top schematic plan view showing a portion of the power/ground ball pad array in the top layer ( $L_1$ ) of the exemplary high-density multi-layer PCB as depicted in FIG. 2. FIG. 4 is a schematic plan view showing a portion of the via arrangement in the second layer ( $L_2$ ) of the exemplary high-density multi-layer PCB, wherein the illustrated area portion in FIG. 3 is approximately aligned with the area portion shown in FIG. 4. According to the illustrative embodiment, the power/ground ball pad array is situated directed under the chip package **10** within a chip package mounting area.

As shown in FIG. 3, a power net **30** and a ground net **40** are provided in the first layer ( $L_1$ ) within the chip package mounting area of the exemplary high-density multi-layer PCB. The power net **30** comprises a plurality of power ball pads **302** arranged and interconnected in a comb-shaped pattern. The power ball pads **302** are interconnected together by power traces **310** and power traces **320**. For example, the power traces **310** may extend along a first direction and the power traces **320** may extend along a second direction. The first direction may be perpendicular to the second direction.

The power balls on a chip package (not shown in this figure) may be aligned and joined to corresponding power

ball pads **302**. According to the illustrative embodiment, four to six power ball pads **302** may be interconnected together along the first direction by a single power trace **310**, and each power trace **320** may interconnect three power ball pads, for example, ball pads **302b**, **302c**, and **302d**, along the second direction.

The ground net **40** is disposed in close proximity to the power net **30** and is coupled to the power net **30** in an interdigitated fashion. The ground net **40** comprises a plurality of ground ball pads **402** arranged and interconnected in an inverted comb-shaped pattern so that the comb-shaped ground net **40** is interdigitated with the comb-shaped power net **30**. The interdigitated configuration of the power net **30** and ground net **40** is beneficial because such arrangement makes power/ground inductive loop get smaller, and thus smaller AC IR drop.

Likewise, the ground ball pads **402** are interconnected together by ground traces **410** and ground traces **420**. The ground traces **410** may extend along the first direction and the ground traces **420** may extend along the second direction. The ground balls on a chip package may be aligned and joined to corresponding ground ball pads **402**. According to the illustrative embodiment, four to six ground ball pads **402** may be interconnected together along the first direction by a single ground trace **410**, and each ground trace **420** may interconnect three ground ball pads, for example, pads **402b**, **402c**, and **402d**, along the second direction.

According to the illustrative embodiment, the power ball pads **302** and the ground ball pads **402** may be arranged in an array with a fixed ball pad pitch. The ball pad pitch is defined as the distance between two center points of two adjacent ball pads. The ball pad pitch may range between 0.2 mm and 0.6 mm, for example, 0.4 mm, but not limited thereto.

In FIG. 3, a 2x4 ball pad unit matrix is indicated by dashed lines. The 2x4 ball pad unit matrix includes a plurality of 4-ball pad unit areas **2a** and a plurality of 4-ball pad unit areas **2b**. Two adjacent ball pad unit areas **2a** and **2b** are shown in FIG. 5. According to the illustrative embodiment, each of the 4-ball pad unit areas **2a** and **2b** has a rectangular shape and a dimension of about  $2P \times 2P$ , wherein  $P$  is the ball pad pitch. According to the illustrative embodiment, each 4-ball pad unit area **2a** includes one distal ground ball pad, for example, ground ball pad **402d**, and three power ball pads, for example, power ball pads **302a**, **302b**, and **302c**.

In the 4-ball pad unit area **2a**, according to the illustrative embodiment, only two of the three power ball pads, for example, power ball pads **302b**, and **302c**, are interconnected to the underlying power plane **610** through respective laser-drilled microvias **330a** and **330b**. Please refer briefly to FIG. 4, the region **2a'** corresponding to the 4-ball pad unit area **2a** in FIG. 3 accommodates only two laser-drilled microvias **330a** and **330b** and only one mechanically-drilled buried through via **630a** that interconnects the power plane **610** in the second layer ( $L_2$ ) with the underlying layers of the exemplary high-density multi-layer PCB.

According to the illustrative embodiment, each 4-ball pad unit area **2b** includes one distal power ball pad, for example, power ball pad **302d**, and three ground ball pads, for example, ground ball pads **402a**, **402b**, and **402c**. In the 4-ball pad unit area **2b**, according to the illustrative embodiment, only two of the three ground ball pads, for example, ground ball pads **402b**, and **402c**, are interconnected to the underlying ground plane **710** through respective laser-drilled microvias **430a** and **430b**. Please refer briefly to FIG. 4, the region **2b'** corresponding to the 4-ball pad unit area **2b** in

FIG. 3 accommodates only two laser-drilled microvias **430a** and **430b** and only one mechanically-drilled buried through via **730a** that interconnects the ground plane **710** in the second layer ( $L_2$ ) with the underlying layers of the exemplary high-density multi-layer PCB.

Please refer to FIG. 6 and FIG. 7. FIG. 6 is a top schematic plan view showing a portion of the power/ground ball pad array in the first layer ( $L_1$ ) of the exemplary high-density multi-layer PCB according to another embodiment of the invention, wherein like regions, layers, or elements are designated with like numeral numbers. FIG. 7 is a schematic plan view showing a portion of the via arrangement in the second layer ( $L_2$ ) of the exemplary high-density multi-layer PCB, wherein the illustrated area portion in FIG. 6 is approximately aligned with the area portion shown in FIG. 7. According to the illustrative embodiment, the power/ground ball pad array is situated directed under the chip package **10** within a chip package mounting area.

As shown in FIG. 6, likewise, at least one power net **30** and at least one ground net **40** are provided in the first layer ( $L_1$ ) within the chip package mounting area of the exemplary high-density multi-layer PCB. The power net **30** comprises a plurality of power ball pads **302** arranged and interconnected in cascade in a ladder form. The power ball pads **302** are interconnected together by power traces **310** and power traces **320**.

According to the illustrative embodiment, for example, each power trace **310** may extend along a first direction and each power trace **320** may extend along a second direction. The first direction may be perpendicular to the second direction. According to the illustrative embodiment, each power trace **310** may interconnect two to three power ball pads **302**, for example, power ball pads **302b**, **302c**, **302d** along the first direction, while each power trace **310** may interconnect two power ball pads **302**, for example, power ball pads **302d** and **302e** along the second direction.

According to the illustrative embodiment, the ground net **40** is disposed in close proximity to the power net **30**. The ground net **40** comprises a plurality of ground ball pads **402** arranged and interconnected in cascade in a ladder form. According to the illustrative embodiment, the power net **30** and the ground net **40** are basically arranged in a one-power one-ground (1P1G) interleaving power/ground trace routing configuration.

Likewise, the ground ball pads **402** are interconnected together by ground traces **410** and ground traces **420**. The ground traces **410** may extend along the first direction and the ground traces **420** may extend along the second direction. The ground balls on a chip package may be aligned and joined to corresponding ground ball pads **402**. According to the illustrative embodiment, three ground ball pads **402**, for example, pads **402b**, **402c**, and **402d**, may be interconnected together along the first direction by a single ground trace **410**, and each ground trace **420** may interconnect two ground ball pads, for example, pads **402a** and **402b**, along the second direction.

According to the illustrative embodiment, the power ball pads **302** and the ground ball pads **402** may be arranged in an array with a fixed ball pad pitch. The ball pad pitch is defined as the distance between two center points of two adjacent ball pads. The ball pad pitch may range between 0.2 mm and 0.6 mm, for example, 0.4 mm, but not limited thereto.

In FIG. 6, a 2x2 ball pad unit matrix is indicated by dashed lines. The 2x2 ball pad unit matrix includes a 4-ball pad unit area **3a**, a 4-ball pad unit area **3b**, and a 4-ball pad unit area **3c**. According to the illustrative embodiment, each

of the 4-ball pad unit areas **3a-3c** has a rectangular shape and a dimension of about  $2P \times 2P$ , wherein P is the ball pad pitch as previously mentioned. According to the illustrative embodiment, the 2x2 ball pad unit matrix includes sixteen ball pads **302** and **402** including 9 power ball pads **302b-302j** and 7 ground ball pads **402a-402g**.

According to the illustrative embodiment, each 4-ball pad unit area **3a** includes only one power ball pad **302**, for example, power ball pad **302b**, and three ground ball pads **402**, for example, ground ball pads **402a**, **402b**, and **402c**. In the 4-ball pad unit area **3a**, according to the illustrative embodiment, only one of the three ground ball pads **402**, for example, ground ball pad **402a**, is interconnected to the underlying ground plane **710** through the laser-drilled microvia **430a**. The power ball pad **302b** in the 4-ball pad unit area **3a** is interconnected to the underlying power plane **610** through the laser-drilled microvia **330a**.

Please refer briefly to FIG. 7, the region **3a'** corresponding to the 4-ball pad unit area **3a** in FIG. 6 accommodates only two laser-drilled microvias **330a** and **430a** and only one mechanically-drilled buried through via **630a** that interconnects the power plane **610** in the second layer ( $L_2$ ) with the underlying layers of the exemplary high-density multi-layer PCB.

According to the illustrative embodiment, each 4-ball pad unit area **3b** includes only one ground ball pad **402**, for example, ground ball pad **402g**, and three power ball pads **302**, for example, power ball pads **302f**, **302g**, and **302h**. In the 4-ball pad unit area **3b**, according to the illustrative embodiment, only two of the three power ball pads **302**, for example, power ball pads **302f** and **302g**, are interconnected to the underlying ground plane **710** through respective laser-drilled microvias **330b** and **330c**. Please refer briefly to FIG. 7, the region **3b'** corresponding to the 4-ball pad unit area **3b** in FIG. 6 accommodates only two laser-drilled microvias **330b** and **330c** and only one mechanically-drilled buried through via **630b** that interconnects the power plane **610** in the second layer ( $L_2$ ) with the underlying layers of the exemplary high-density multi-layer PCB.

According to the illustrative embodiment, each 4-ball pad unit area **3c** includes two power ball pads **302**, for example, power ball pads **302i** and **302j**, and two ground ball pads **402**, for example, ground ball pads **402e** and **402f**. In the 4-ball pad unit area **3c**, according to the illustrative embodiment, only one of the two ground ball pads **402**, for example, ground ball pad **402e**, may be interconnected to the underlying ground plane **710** through the laser-drilled microvia **430b**. In FIG. 7, the region **3c'** corresponding to the 4-ball pad unit area **3c** in FIG. 6 accommodates only one laser-drilled microvia **430b** and only one mechanically-drilled buried through via **730a** that interconnects the ground plane **710** in the second layer ( $L_2$ ) with the underlying layers of the exemplary high-density multi-layer PCB.

Those skilled in the art will readily observe that numerous modifications and alterations of the device and method may be made while retaining the teachings of the invention. Accordingly, the above disclosure should be construed as limited only by the metes and bounds of the appended claims.

What is claimed is:

1. A microelectronic system, comprising:  
a base, comprising:

- an internal conductive layer;
- a build-up layer on the internal conductive layer, said build-up layer comprising a top conductive layer;

- a plurality of microvias in the build-up layer to electrically connect the top conductive layer with the internal conductive layer; and
- a power/ground ball pad array in the top conductive layer, said power/ground ball pad array comprising power ball pads and ground ball pads arranged in an array with a fixed ball pad pitch P, and said power/ground ball pad array comprising a 4-ball pad unit area comprised of only one ground ball pad and three power ball pads, or comprised of only one power ball pad and three ground ball pads; and
- a semiconductor device mounted on the base.
2. The microelectronic system according to claim 1, wherein said 4-ball pad unit area has a rectangular shape and a dimension of about  $2P \times 2P$ .
3. The microelectronic system according to claim 1 further comprising a solder mask on said build-up layer.
4. The microelectronic system according to claim 3, wherein said solder mask comprises a plurality of solder mask openings for exposing said power ball pads and said ground ball pads, respectively.
5. The microelectronic system according to claim 1, wherein said base comprises 2 to 8 internal conductive layers.
6. The microelectronic system according to claim 1, wherein said microvias are laser-drilled microvias and each of said microvias has a via diameter size ranging between 0.05-0.2 mm.
7. The microelectronic system according to claim 1, wherein said only one ground ball pad is a distal ground ball pad of a ground net.
8. The microelectronic system according to claim 1, wherein said only one power ball pad is a distal power ball pad of a power net.
9. A microelectronic system, comprising:  
a base, comprising:  
an internal conductive layer;  
a build-up layer on the internal conductive layer, said build-up layer comprising a top conductive layer;  
a plurality of microvias in the build-up layer to electrically connect the top conductive layer with the internal conductive layer;  
a power net in the top conductive layer, said power net comprising a plurality of power ball pads arranged and interconnected in a comb-shaped pattern; and  
a ground net disposed being in close proximity to said power net and coupled to said power net in an interdigitated fashion, wherein said ground net comprises a plurality of ground ball pads arranged and interconnected in an inverted comb-shaped pattern so that said ground net is interdigitated with said power net; and  
a semiconductor device mounted on the base.
10. The microelectronic system according to claim 9, wherein said plurality of power ball pads and said plurality of ground ball pads are arranged in an array with a fixed ball pad pitch.
11. The microelectronic system according to claim 9, wherein said power ball pads are interconnected together by a first power trace and a second power trace.
12. The microelectronic system according to claim 11, wherein said first power trace extends along a first direction and said second power trace extends along a second direction, wherein said first direction is perpendicular to said second direction.

13. The microelectronic system according to claim 12, wherein four to six of said power ball pads are interconnected together along said first direction by said first power trace, and three of said power ball pads are interconnected together along said second direction by said second power trace.
14. The microelectronic system according to claim 12, wherein said ground ball pads are interconnected together by a first ground trace and a second ground trace.
15. The microelectronic system according to claim 14, wherein said first ground trace extends along said first direction and said second ground trace extends along said second direction.
16. The microelectronic system according to claim 15, wherein four to six of said ground ball pads are interconnected together along said first direction by said first ground trace, and three of said ground ball pads are interconnected together along said second direction by said second ground trace.
17. The microelectronic system according to claim 9, wherein said microvias are laser-drilled microvias and each of said microvias has a via diameter size ranging between 0.05-0.2 mm.
18. The microelectronic system according to claim 17, wherein said plurality of power ball pads and said plurality of ground ball pads are arranged in an array with a fixed ball pad pitch, and wherein said array comprises a 4-ball pad unit area that is comprised of only one ground ball pad and three power ball pads, or comprised of only one power ball pad and three ground ball pads.
19. The microelectronic system according to claim 18, wherein in said 4-ball pad unit area, only two of the three power ball pads are interconnected to an underlying power plane in said internal conductive layer through respective two of said microvias.
20. The microelectronic system according to claim 18, wherein in said 4-ball pad unit area, only two of the three ground ball pads are interconnected to an underlying ground plane in said internal conductive layer through respective two of said microvias.
21. A microelectronic system, comprising:  
a base, comprising  
an internal conductive layer;  
a build-up layer on the internal conductive layer, said build-up layer comprising a top conductive layer;  
a plurality of microvias in the build-up layer to electrically connect the top conductive layer with the internal conductive layer;  
a power net in the top conductive layer, said power net comprising a plurality of power ball pads arranged in cascade; and  
a ground net disposed being in close proximity to said power net and coupled to said power net in an interdigitated fashion, wherein said ground net comprises a plurality of ground ball pads arranged in cascade; and  
a semiconductor device mounted on the base.
22. The microelectronic system according to claim 21, wherein said plurality of power ball pads and said plurality of ground ball pads are arranged in an array with a fixed ball pad pitch.