(19) Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) EP 0 824 146 B1

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention of the grant of the patent:
04.06.2003 Bulletin 2003/23

(51) Int Cl.[7]: **C11D 3/395**, C11D 3/37

(21) Application number: **97870040.9**

(22) Date of filing: **27.03.1997**

(54) **Bleaching compositions**

Bleichmittelzusammensetzungen

Compositions de blanchiment

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB GR IE IT LI LU NL PT SE

(30) Priority: **12.08.1996 EP 96870105**

(43) Date of publication of application:
18.02.1998 Bulletin 1998/08

(73) Proprietor: **THE PROCTER & GAMBLE COMPANY**
Cincinnati, Ohio 45202 (US)

(72) Inventors:
- **Scialla, Stefano**
  00128 Rome (IT)
- **Briatore, Andrea**
  17040 Savona (IT)
- **Capua, Gloria Di**
  00040 Ardea (IT)

(74) Representative: **Engisch, Gautier et al**
Procter & Gamble
European Technical Center N.V.
Temselaan 100
1853 Strombeek-Bever (BE)

(56) References cited:
EP-A- 0 429 108
EP-A- 0 442 191
EP-A- 0 606 707
EP-A- 0 636 689
EP-A- 0 653 483
EP-A- 0 668 345
DE-A- 2 501 529
GB-A- 2 271 119
US-A- 5 135 675

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 824 146 B1

Description

Field of the invention

[0001] The present invention relates to bleaching compositions, in particular to hypochlorite bleaching compositions, suitable for use in laundry applications such as hand and machine laundry methods.

Background of the invention

[0002] Bleaching compositions are well-known in the art. Amongst the different bleaching compositions available, those relying on bleaching by hypohalite bleaches such as hypochlorite are often preferred, mainly for performance reasons, especially at lower temperature.

[0003] However, a problem encountered with the use of hypochlorite based-compositions is the resulting damage and/or yellowing of the fabrics being bleached.

[0004] It is therefore an object of the invention to provide a hypohalite-containing composition, suitable for use in laundry applications, which provides improved fabric whiteness to fabrics treated therewith.

[0005] It is another object of the invention to provide a hypohalite-containing composition, suitable for use in laundry applications, which provides improved fabric safety to fabrics treated therewith.

[0006] To fulfill such needs, pH buffering components such as silicates have been incorporated in hypochlorite compositions. A typical disclosure can be found in EP-A-0,653,483.

[0007] The Applicant has thus now surprisingly found that this problem is solved by the use, in a hypohalite bleaching composition containing a pH buffering component, of an ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water. Indeed, it has been found that improved fabric whiteness and/or safety were obtained with the composition of the invention compared to hypohalite compositions containing a pH buffering component but no ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water.

[0008] Another advantage of the compositions of the invention is that they are chemically stable. By "chemically stable", it is meant that the hypohalite bleaching compositions of the present invention should not undergo more than 15% loss of available chlorine after 5 days of storage at $50°C \pm 0.5°C$. The % loss of available chlorine may be measured using the method described, for instance, in "Analyses des Eaux et Extraits de Javel" by "La chambre syndicale nationale de L'eau de Javel et des produits connexes", pages 9-10 (1984). Said method consists in measuring the available chlorine in the fresh compositions, i.e. just after they are made, and in the same compositions after 5 days at 50°C.

[0009] A further advantage of the compositions of the invention is that they are suitable for the bleaching of different types of fabrics including natural fabrics (e.g., fabrics made of cotton, viscose, linen, silk and wool), synthetic fabrics such as those made of polymeric fibers of synthetic origin as well as those made of both natural and synthetic fibers. Indeed, the compositions of the present invention may be used on synthetic fibers despite a standing prejudice against the use of hypohalite bleaches, especially hypochlorite bleaches, on synthetic fibers, as evidenced by warning on labels of commercially available hypochlorite bleaches and clothes.

Summary of the invention

[0010] The present invention is a liquid bleaching composition comprising

a)- a hypohalite bleach,
b)- a pH buffering component in an amount of 0.5% to 9% by weight, and
c)- an ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water; with the proviso that where said ingredient is a polyacrylate polymer, the polymer is present in an amount of less than 0.5% by weight; wherein said ingredient having the ability to prevent the precipitation of the salts of said buffering compound upon dilution of the composition in water is a polymer selected from the group consisting of: polyacrylate polymers; co-polymers of acrylic acid and maleic acid ; co-polymers of sytrene sulphonic acid and maleic acid; and mixtures thereof; and wherein said polymer is modified with aminophosphonic and/or phosphonic groups.

[0011] In another aspect of the invention, a solid bleaching composition is provided comprising:

a)- a hypohalite bleach,
b)- a pH buffering component, and
c)- an ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution

of the composition in water; wherein said ingredient having the ability to prevent the precipitation of the salts of said buffering compound upon dilution of the composition in water is a polymer selected from the group consisting of: polyacrylate polymers; co-polymers of acrylic acid and maleic acid ; co-polymers of sytrene sulphonic acid and maleic acid; and mixtures thereof; and wherein said polymer is modified with aminophosphonic and/or phosphonic groups.

[0012] The present invention also encompasses a process of bleaching fabrics with a composition comprising:

a)- a hypohalite bleach,
b)- a pH buffering component in an amount of 0.5% to 9% by weight, and
c)- an ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water;

where said fabrics are immersed in a bleaching solution formed by diluting said composition in water, and wherein said ingredient having the ability to prevent the precipitation of the salts of said buffering compound upon dilution of the composition in water is a polymer selected from the group consisting of: polyacrylate polymers; co-polymers of acrylic acid and maleic acid ; co-polymers of sytrene sulphonic acid and maleic acid; and mixtures thereof; and wherein said polymer is modified with aminophosphonic and/or phosphonic groups.

[0013] The present invention also encompasses the use, in a hypohalite bleaching composition comprising a pH buffering component, of an ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water, as described herein, for providing improved fabric whiteness and/or safety to the fabrics treated therewith.

Detailed description of the invention

Hypohalite bleach

[0014] An essential component of the invention is a hypohalite bleach. Hypohalite bleaches may be provided by a variety of sources, including bleaches that are oxidative bleaches and subsequently lead to the formation of positive halide ions as well as bleaches that are organic based sources of halides such as chloroisocyanurates.

[0015] Suitable hypohalite bleaches for use herein include the alkali metal and alkaline earth metal hypochlorites, hypobromites, hypoiodites, chlorinated trisodium phosphate dodecahydrates, potassium and sodium dichloroisocyanurates, potassium and sodium trichlorocyanurates, N-chloroimides, N-chloroamides, N-chloroamines and chlorohydantoins.

[0016] For liquid compositions, the preferred hypohalite bleaches among the above described are the alkali metal and/or alkaline earth metal hypochlorites selected from the group consisting of sodium, potassium, magnesium, lithium and calcium hypochlorites, and mixtures thereof, more preferably the alkali metal sodium hypochlorite.

[0017] For solid compositions, the preferred hypohalite bleaches among the above described are the alkali metal and/or alkaline earth metal hypochlorites selected from the group consisting of lithium hypochlorites, calcium hypochlorites, chlorinated trisodium phosphate dodecahydrates, potassium dichloroisocyanurates, sodium dichloroisocyanurates, potassium trichlorocyanurates, sodium trichlorocyanurates, and mixtures thereof, more preferably sodium dichloroisocyanurates and/or calcium hypochlorite.

[0018] Preferably, the liquid compositions according to the present invention comprise said hypohalite bleach such that the content of active halide in the composition is of from 0.1% to 20% by weight, more preferably from 2% to 8% by weight, most preferably from 3% to 6% by weight of the composition.

[0019] Preferably, the solid compositions according to the present invention comprise said hypohalite bleach such that the content of active halide in the composition is of from 20% to 95% by weight, more preferably from 25% to 60% by weight of the composition.

pH buffering component

[0020] A pH buffering component is another essential component for the compositions of the invention. The pH buffering component ensures that the pH of the composition is buffered to a pH value ranging from 7.5 to 13, preferably from 8 to 12, more preferably from 8.5 to 11.5 after the composition has been diluted into 1 to 500 times its weight of water.

[0021] Suitable pH buffering components for use herein are selected from the group consisting of alkali metal salts of carbonates, polycarbonates, sesquicarbonates, silicates, polysilicates, borates, metaborates, phosphates, stannates, alluminates and mixtures thereof, and preferably are selected from the group consisting of sodium carbonate,

sodium silicate, sodium borate, and mixtures thereof.

[0022] The raw materials involved in the preparation of hypohalite bleaches usually contain by-products, e.g calcium carbonate resulting in an amount of up to 0.4% by weight of by-product within the hypohalite composition. However, at such amount, the by-product will not have the buffering action defined above.

[0023] Liquid bleaching compositions herein will contain an amount of pH buffering component of from 0.5% to 9% by weight, preferably from 0.5% to 5% by weight, and more preferably in an amount of from 0.6% to 3% by weight of the composition.

[0024] Solid bleaching compositions herein will preferably contain an amount of pH buffering component of from 3% to 30% by weight, more preferably from 5% to 25% by weight, and most preferably in an amount of from 10% to 20% by weight of the composition.

Ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water

[0025] The other essential component of the invention is an ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water. That ingredient, by preventing the precipitation of the salts of said buffering component upon dilution of the composition in water, has surprisingly been found to provide a reduction of the yellowing of the fabrics treated therewith, i.e. improved whiteness, as well as providing improved fabric safety. Naturally, for the purpose of the invention, the ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water has to be stable to the hypohalite bleach.

[0026] The ability of an ingredient to prevent the precipitation of the salts of the buffering component upon dilution of the composition in water may be measured by the following comparative test:

[0027] A composition containing 5%wt. sodium hypochlorite, 1.4%wt. sodium hydroxide, 1.5%wt, calcium carbonate and water (between 10°F (French Degree) 40°F) and to balance to 100%wt is prepared. 10 ml of this composition is added to 1 litre of tap water (30°F). The solution is maintained at 40°C for 30 min. The precipitates formed are separated from said solution and then dried and weighted. By "separating the precipitates formed", it is meant to filter said solution with an apparatus comprising a peristaltic pump, a vacuum flask and a filter with 0.45 microns porosity.

[0028] The above test is repeated with the same composition formulation but with the exception that 0.05%wt. of the ingredient to be tested is added to the composition. Ingredients having the ability to prevent the precipitation of the salts of the buffering component upon dilution of the composition in water will reduce the amount of precipitates formed, as measured according to this method, by more than 50% compared to the same compositions which do not contain the ingredient having the ability to prevent the precipitation of the salts of the buffering component upon dilution of the composition in water.

[0029] Preferred ingredients, for the purpose of the invention, are those substantially maintaining their ability to prevent the precipitation of the salts of said buffering component, as defined above, upon dilution of the composition in water after storage in an oven as defined by the oven test method below:

[0030] The two compositions defined in the test method above are stored in an oven (Memmert®) at 50°C for 7 days. After storage, the above test method is repeated, i.e. for each composition 10 ml of the composition is taken and added to 1 litre of tap water (30°F(French Degree)). The solution is maintained at 40°C for 30 min. The precipitates formed are separated from said solution and then dried and weighted.

[0031] The compositions may also be assessed for their whitening effect and/or safety on the treated fabrics.

[0032] The whitening effect, i.e. the yellowing-prevention effect, and /or safety effect of the present invention can be evaluated by comparing the composition according to the present invention to the same composition without the ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water.

[0033] The degree of yellowing can be determined by both visual and instumental grading. Visually, the difference in yellowing between items treated with different compositions can be determined by a team of expert panellists. Instrumentally, the assessment can be determined with the help of Colorimeters such as Ganz Griesser® instruments (e.g., Datacolor® Spectraflash® SF 500, Machbet White-eye® 500) or a ZEISS ELREPHO® or others which are available for instance from Hunterlab® or Gardner®.

[0034] Fabric safety may be evaluated by different test methods including the degree of polymerisation test method according to UNI (Ente Nazionale Italiano di Unificazione) official method UNI 8282-Determinazione della viscosità intrinseca in soluzione di cuprietilendiammina (CED).

[0035] Preferred ingredients which prevent the precipitation of the salts of the buffering component upon dilution of the composition in water are of the polymeric type.

[0036] Polymers which prevent the precipitation of the salts of the buffering component upon dilution of the composition in water are selected from the group consisting of polyacrylate polymers, co-polymers of acrylic and maleic acid,

co-polymers of styrene sulphonic acid and maleic acid, and mixtures thereof, modified with aminophosphonic and/or phosphonic groups.

[0037] The molecular weight for these polymers and co-polymers is preferably below 100,000, most preferably between 500 and 50,000. Most suitable polymers and co-polymers for use herein will be soluble in an amount up to 0.1% by weight, in an aqueous composition comprising 5% by weight of sodium hypochlorite with its pH adjusted to 13 with sodium hydroxide.

[0038] Commercially available polymers, suitable for use herein, which prevent the precipitation of the salts of the buffering component upon dilution of the composition in water are polyacrylate polymers sold under the tradename Norasol® from Norso Haas.

[0039] Preferred commercially available polymers are the polyacrvlate polymer modified with phosphonic groups Norasol®440N (MW 4000) and its corresponding acid form Norasol®QR 784 (MW 4000).

[0040] A preferred polymer for use herein still maintaining its ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water after storage in an oven as defined in the above oven test method are the polyacrylate polymer modified with phosphonic groups commercially available under the tradename Norasol® 440N (MW 4000) and its corresponding acid form Norasol® QR 784 (MW 4000) from Norso-Haas.

[0041] Mixtures of polymers as herein described may also be used in the present invention.

[0042] The ingredient having the ability to prevent the precipitation of the salts of the buffering component upon dilution of the composition in water is preferably present at a low amount, i.e. in an amount of up to 0.5% by weight, more preferably from 0.001% to 0.3% by weight, most preferably from 0.005% to 0.2% by weight of the liquid composition.

[0043] Solid compositions of the invention will preferably comprise an amount of said ingredient of from 0.01% to 3% by weight, preferably from 0.05% to 2% by weight of the composition.

[0044] The compositions according to the present invention are either in liquid or solid form. Solid forms include forms such as powders, tablets and granules. Preferably, the compositions of the invention are in liquid aqueous form. More preferably, they comprise water in an amount of from 60% to 98% by weight, more preferably of from 80% to 97% and most preferably of from 85% to 97% by weight of the total aqueous liquid bleaching composition.

pH

[0045] The pH of the liquid compositions according to the present invention, as is, is typically from 12 to 14 measured at 25°C. Solid compositions or liquid compositions of the invention have a pH of from 7.5 to 13, preferably from 8 to 12, more preferably from 8.5 to 11.5, when diluted into 1 to 500 times its weight of water. It is in this alkaline range that the optimum stability and performance of the hypohalite as well as fabric whiteness and/or safety are obtained. The pH range is suitably provided by the pH buffering component and the hypohalite bleach mentioned hereinbefore, which are alkalis. However, in addition to these components, a strong source of alkalinity may also optionally be used.

[0046] Suitable sources of alkalinity are the caustic alkalis such as sodium hydroxide, potassium hydroxide and/or lithium hydroxide, and/or the alkali metal oxides such as sodium and/or potassium oxide. A preferred strong source of alkalinity is a caustic alkali, more preferably sodium hydroxide and/or potassium hydroxide. Typical levels of such caustic alkalis, when present, are of from 0.1% to 1.5% by weight, preferably from 0.5% to 1.5% by weight of the composition.

[0047] The composition according to the invention may also comprise further optional components such as perfumes, bleach-stable surfactants, organic or inorganic alkalis, pigments, dyes, optical brighteners, solvents, chelating agents, radical scavengers and mixtures thereof.

[0048] Preferably, the compositions of the invention are used in diluted form in laundry applications. The expression "used in diluted form" herein includes dilution by the user, which occurs for instance in hand laundry applications, as well as dilution by other means, such as in a washing machine. Preferably, the composition is diluted into 5 to 500 times its weight of water for hand laundry application and 10 to 500 times its weight of water in a washing machine. Thus, in another aspect of the invention there is provided a process for washing fabrics with a composition as disclosed herein, where said fabrics are immersed in a bleaching solution formed by diluting said composition in water.

[0049] In another aspect of the invention, there is provided the use, in a hypohalite bleaching composition comprising a pH buffering component, of an ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water for providing improved whiteness and/or safety to the fabrics treated therewith. Accordingly, the present invention also encompasses the use, in a hypohalite bleaching composition comprising a pH buffering component, of an ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water, for providing improved whiteness and/or safety to the fabrics treated therewith. By "improved whiteness and/or safety", it is meant that hypohalite bleaching compositions, comprising a pH buffering component and an ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water, provide better whiteness, i.e. less yellowing, and/

or fabric safety compared to hypohalite bleaching compositions which do not comprise said ingredient.

[0050] The invention is illustrated in the following non-limiting example, in which all percentages are on a weight basis unless otherwise stated.

Example 1

[0051] The following compositions, according to the invention, were prepared:

Composition (weight %)	1	2	3	4	5	6	7	8
Sodium hypochlorite	5.0	5.0	5.0	2.5	2.5	2.5	5.0	5.0
Sodium hydroxide	0.9	0.7	0.7	0.9	0.7	0.7	0.5	-
Sodium carbonate	1.2	1.2	1.2	1.2	1.2	1.2	-	1.5
Sodium silicate	-	0.5	-	-	0.5	-	-	-
Sodium metaborate	-	-	1.0	-	-	1.0	1.0	-
Norasol QR 784	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Water and minors to balance to 100								

Claims

1. A liquid bleaching composition comprising

a)- a hypohalite bleach,
b)- a pH buffering component in an amount of 0.5% to 9% by weight, and
c)- an ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water; with the proviso that where said ingredient is a polyacrylate polymer, the polymer is present in an amount of less than 0.5% by weight; wherein said ingredient having the ability to prevent the precipitation of the salts of said buffering compound upon dilution of the composition in water is a polymer selected from the group consisting of: polyacrylate polymers; co-polymers of acrylic acid and maleic acid ; co-polymers of styrene sulphonic acid and maleic acid; and mixtures thereof; and wherein said polymer is modified with aminophosphonic and/or phosphonic groups.

2. A solid bleaching composition comprising:

a)- a hypohalite bleach,
b)- a pH buffering component, and
c)- an ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water wherein said ingredient having the ability to prevent the precipitation of the salts of said buffering compound upon dilution of the composition in water is a polymer selected from the group consisting of: polyacrylate polymers; co-polymers of acrylic acid and maleic acid ; co-polymers of styrene sulphonic acid and maleic acid; and mixtures thereof; and wherein said polymer is modified with aminophosphonic and/or phosphonic groups.

3. The use, in a hypohalite bleaching composition comprising a pH buffering component, of an ingredient having the ability to prevent the precipitation of the salt of said buffering component upon dilution of the composition in water wherein said ingredient having the ability to prevent the precipitation of the salts of said buffering compound upon dilution of the composition in water is a polymer selected from the group consisting of: polyacrylate polymers; co-polymers of acrylic acid and maleic acid ; co-polymers of styrene sulphonic acid and maleic acid; and mixtures thereof; and wherein said polymer is modified with aminophosphonic and/or phosphonic groups, for providing improved whiteness and/or safety to the fabrics treated therewith.

4. A process of bleaching fabrics with a composition comprising :

a)- a hypohalite bleach,
b)- a pH buffering component in an amount of 0.5% to 9% by weight, and

c)- an ingredient having the ability to prevent the precipitation of the salts of said buffering component upon dilution of the composition in water;

where said fabrics are immersed in a beaching solution formed by diluting said composition in water; and wherein said ingredient having the ability to prevent the precipitation of the salts of said buffering compound upon dilution of the composition in water is a polymer selected from the group consisting of: polyacrylate polymers; co-polymers of acrylic acid and maleic acid ; co-polymers of styrene sulphonic acid and maleic acid; and mixtures thereof; and wherein said polymer is modified with aminophosphonic and/or phosphonic groups.

5. A bleaching composition according to claims 1 or 2, use according to claim 3, or process according to claim 4, wherein said ingredient is present in an amount of from 0.001% to 0.5% by weight, preferably from 0.001% to 0.3%.

6. A bleaching composition, use or process according to either one of claim 1 to 5, wherein said polymer has a molecular weight below 100.000.

7. A bleaching composition, use or process according to any one of claims 1-6, wherein said pH buffering component is selected from the group consisting of alkali metal salts of carbonates, polycarbonates, sesquicarbonates, silicates, polysilicates, borates, metaborates, phosphates, stannates, alluminates, and mixtures thereof.

8. A bleaching composition, use or process according to claim 7, wherein said pH uffering component is selected from the group consisting of sodium carbonate, sodium silicates, sodium borate, and mixtures thereof.

9. A bleaching composition, use or process according to any one of claims 1 - 8, wherein said pH buffering component is in an amount of from 0.5% to 9% by weight, preferably 0.5% to 5% by weight of the liquid composition or in an amount of from 3% to 30% by weight, preferably from 5% to 25% by weight of the solid composition.

10. A bleaching composition, use or process according to any one of claims 1 - 9, wherein said hypohalite bleach is, for liquid bleaching compositions, an alkali metal sodium hypochlorite or, for solid compositions, sodium dichloroisocyanurate and/or calcium hypochlorite.

11. A bleaching composition, use or process according to any one of claims 1-10 wherein said hypohalite, based on active halide, is present in an amount of from 0.1% to 20% by weight, preferably from 2% to 8% by weight of the liquid composition or in an amount of from 20% to 95% by weight, preferably from 25% to 60% by weight of the solid composition.

12. A bleaching composition, use or process according to any one of claims 1-11, wherein said composition further comprises a strong source of alkalinity.

Patentansprüche

1. Flüssige Bleichmittelzusammensetzung, umfassend:

a) ein Hypohalogenit-Bleichmittel,
b) eine pH-Pufferkomponente in einer Menge von 0.5 bis 9 Gew.-%, und
c) einen Bestandteil mit der Fähigkeit, die Ausfällung der Salze der Pufferkomponente beim Verdünnen der Zusammensetzung in Wasser zu verhindern; mit der Maßgabe, daß, wenn der Bestandteil ein Polyacrylatpolymer Ist, das Polymer in einer Menge von weniger als 0,5 Gew.-% vorliegt; wobei der Bestandteil mit der Fähigkeit, die Ausfällung der Salze der Pufferkomponente beim Verdünnen der Zusammensetzung in Wasser zu verhindern ein Polymer ist, gewählt aus der Gruppe, bestehend aus: Polyacrylatpolymere; Copolymere von Acryl- und Maleinsäure; Copolymere von Styrolsulfonsäure und Maleinsäure; und Mischungen hiervon; und wobei das Polymer mit Aminophosphonsäure- und/oder Phosphonsäuregruppen modifiziert ist.

2. Feste Bleichmittelzusammensetzung, umfassend:

a) ein Hypohalogenit-Bleichmittel,
b) eine pH-Pufferkomponente, und
c) einen Bestandteil mit der Fähigkeit, die Ausfällung der Salze der Pufferkomponente beim Verdünnen der

Zusammensetzung in Wasser zu verhindern, wobei der Bestandteil mit der Fähigkeit, die Ausfällung der Salze der Pufferkomponente beim Verdünnen der Zusammensetzung in Wasser zu verhindern ein Polymer ist, gewählt aus der Gruppe, bestehend aus: Polyacrylatpolymere; Copolymere von Acryl- und Maleinsäure; Copolymere von Styrolsulfonsäure und Maleinsäure; und Mischungen hiervon; und wobei das Polymer mit Aminophosphonsäure- und/oder Phosphonsäuregruppen modifiziert ist.

3. Verwendung, in einer Hypohalogenit-Bleichmittelzusammensetzung, die eine pH-Pufferkomponente umfaßt, eines Bestandteils mit der Fähigkeit, die Ausfällung der Salze der Pufferkomponente beim Verdünnen der Zusammensetzung in Wasser zu verhindern, wobei der Bestandteil mit der Fähigkeit die Ausfällung der Salze der Pufferkomponente beim Verdünnen der Zusammensetzung in Wasser zu verhindern ein Polymer ist, gewählt aus der Gruppe, bestehend aus: Polyacrylatpolymere; Copolymere von Acryl- und Maleinsäure; Copolymere von Styrolsulfonsäure und Maleinsäure; und Mischungen hiervon; und wobei das Polymer mit Aminophosphonsäure- und/oder Phosphonsäuregruppen modifiziert ist, um verbesserten Weißgrad und/oder Sicherheit für die damit behandelten Textilien vorzusehen.

4. Verfahren zum Bleichen von Textilien mit einer Zusammensetzung, umfassend:

a) ein Hypohalogenit-Bleichmittel,
b) eine pH-Pufferkomponente in einer Menge von 0.5 bis 9 Gew.-%, und
c) einen Bestandteil mit der Fähigkeit, die Ausfällung der Salze der Pufferkomponente beim Verdünnen der Zusammensetzung in Wasser zu verhindern;

wobei die Textilien in eine durch Verdünnung der Zusammensetzung in Wasser gebildete Bleichlösung eingetaucht werden; und wobei der Bestandteil mit der Fähigkeit die Ausfällung der Salze der Pufferkomponente beim Verdünnen der Zusammensetzung In Wasser zu verhindern ein Polymer ist, gewählt aus der Gruppe, bestehend aus: Polyacrylatpolymere; Copolymere von Acryl- und Maleinsäure; Copolymere von Styrolsulfonsäure und Maleinsäure: und Mischungen hiervon; und wobei das Polymer mit Aminophosphonsäure- und/oder Phosphonsäuregruppen modifiziert ist.

5. Bleichmittelzusammensetzung nach den Ansprüchen 1 oder 2, Verwendung nach Anspruch 3 oder Verfahren nach Anspruch 4. wobei der Bestandteil in einer Menge von 0.001 bis 0,5 Gew.-%, vorzugsweise 0,001 bis 0,3 Gew.-%, vorliegt.

6. Bleichmittelzusammensetzung, Verwendung oder Verfahren gemäß mindestens einem der Ansprüche 1-5, wobei das Polymer ein Molekulargewicht unterhalb 100.000 besitzt.

7. Bleichmittelzusammensetzung, Verwendung oder Verfahren gemäß mindestens einem der Ansprüche 1-6, wobei die pH-Pufferkomponente aus der Gruppe gewählt ist, bestehend aus Alkallmetallsalzen von Carbonaten, Polycarbonaten, Sesquicarbonaten, Silikaten, Polysilikaten, Boraten, Metaboraten, Phosphaten, Stannaten, Allumina-ten und Mischungen hiervon.

8. Bleichmittelzusammensetzung. Verwendung oder Verfahren nach Anspruch 7, wobei die pH-Pufferkomponente aus der Gruppe gewählt ist, bestehend aus Natriumcarbonat, Natriumsilikaten. Natriumborat und Mischungen hiervon.

9. Bleichmittelzusammensetzung, Verwendung oder Verfahren nach mindestens einem der Ansprüche 1-8, wobei die pH-Pufferkomponente in einer Menge von 0,5 bis 9 Gew.-%, vorzugsweise 0,5 bis 5 Gew.-% der flüssigen Zusammensetzung oder in einer Menge von 3 bis 30 Gew.-%, vorzugsweise 5 bis 25 Gew.-% der festen Zusammensetzung, vorliegt.

10. Bleichmittelzusammensetzung, Verwendung oder Verfahren nach mindestens einem der Ansprüche 1-9, wobei das Hypohalogenit-Bleichmittel für flüssige Bleichmittelzusammensetzungen ein Alkalimetall-Natriumhypochlorit oder, für feste Zusammensetzungen, Natriumdichlorisocyanurat und/oder Calciumhypochlorit ist.

11. Bleichmittelzusammensetzung, Verwendung oder Verfahren nach mindestens einem der Ansprüche 1-10, wobei das Hypohalogenit, bezogen auf aktives Halogenid, in einer Menge von 0,1 bis 20 Gew.-%, vorzugsweise 2 bis 8 Gew.-% der flüssigen Zusammensetzung oder in einer Menge von 20 bis 95 Gew.-%, vorzugsweise 25 bis 60 Gew.-% der festen Zusammensetzung vorliegt.

12. Bleichmittelzusammensetzung, Verwendung oder Verfahren nach mindestens einem der Ansprüche 1-11, wobei die Zusammensetzung weiterhin eine starke Alkallnitätsquelle umfaßt.

Revendications

1. Composition d'agent de blanchiment liquide comprenant :

a) un agent de blanchiment hypohalogéneux,
b) un agent tampon du pH selon une quantité de 0,5 % à 9 % en poids et
c) un ingrédient ayant l'aptitude à empêcher la précipitation des sels dudit agent tampon lors de la dilution de la composition dans l'eau à condition que lorsque ledit ingrédient est un polymère de polyacrylate, le polymère soit présent selon une quantité inférieure à 0,5 % en poids, dans laquelle ledit ingrédient ayant l'aptitude à empêcher la précipitation des sels dudit agent tampon lors de la dilution de la composition dans l'eau est un polymère choisi parmi le groupe comprenant les polymères de polyacrylate, les copolymères d'acide acrylique et d'acide maléique, les copolymères d'acide styrène sulfonique et d'acide maléique et leurs mélanges et dans laquelle ledit polymère est modifié avec des groupes amino phosphoniques et/ou phosphoniques.

2. Composition d'agent de blanchiment solide comprenant:

a) un agent de blanchiment hypohalogéneux,
b) un agent tampon du pH et
c) un ingrédient ayant l'aptitude à empêcher la précipitation des sels dudit agent tampon lors de la dilution de la composition dans l'eau, dans laquelle ledit ingrédient ayant l'aptitude à empêcher la précipitation des sels dudit agent tampon lors de la dilution de la composition dans l'eau est un polymère choisi parmi le groupe comprenant les polymères de polyacrylate, les copolymères d'acide acrylique et d'acide maléique, les copolymères d'acide styrène sulfonique et d'acide maléique et leurs mélanges et dans laquelle ledit polymère est modifié avec des groupes amino phosphoniques et/ou phosphoniques.

3. Utilisation dans une composition d'agent de blanchiment hypohalogéneux comprenant un agent tampon du pH d'un ingrédient ayant l'aptitude à empêcher la précipitation des sels dudit agent tampon lors de la dilution de la composition dans l'eau, dans laquelle ledit ingrédient ayant l'aptitude à empêcher la précipitation des sels dudit agent tampon lors de la dilution de la composition dans l'eau est un polymère choisi parmi le groupe comprenant les polymères de polyacrylate, les copolymères d'acide acrylique et d'acide maléique, les copolymères d'acide styrène sulfonique et d'acide maléique et leurs mélanges et dans laquelle ledit polymère est modifié avec des groupes amino phosphoniques et/ou phosphoniques pour obtenir une blancheur et/ou un avivage amélioré aux tissus traités avec celle-ci.

4. Procédé de blanchiment de tissus avec une composition comprenant :

a) un agent de blanchiment hypohalogéneux,
b) un agent tampon du pH selon une quantité de 0,5 % à 9 % en poids et
c) un ingrédient ayant l'aptitude à empêcher la précipitation des sels dudit agent tampon lors de la dilution de la composition dans l'eau,

dans lequel lesdits tissus sont immergés dans une solution de blanchiment formée par la dilution de ladite composition dans l'eau et dans laquelle ledit ingrédient ayant l'aptitude à empêcher la précipitation des sels dudit agent tampon lors de là dilution de la composition dans l'eau est un . polymère choisi parmi le groupe comprenant les polymères de polyacrylate, les copolymères d'acide acrylique et d'acide maléique, les copolymères d'acide styrène sulfonique et d'acide maléique et leurs mélanges et dans laquelle ledit polymère est modifié avec des groupes amino phosphoniques et/ou phosphoniques.

5. Composition d'agent de blanchiment selon la revendication 1 ou 2, utilisation selon la revendication 3 ou procédé selon la revendication 4, dans lequel (dans laquelle) ledit ingrédient est présent à raison de 0,001 % à 0,5 % en poids, de préférence de 0,001 % à 0,3 %.

6. Composition d'agent de blanchiment, utilisation ou procédé selon l'une quelconque des revendications 1 à 5, dans lequel (dans laquelle) ledit polymère a un poids moléculaire en-dessous de 100 000.

7. Composition d'agent de blanchiment, utilisation ou procédé selon l'une quelconque des revendications 1 à 6, dans lequel (dans laquelle) ledit agent tampon du pH est choisi parmi le groupe comprenant les sels de métaux alcalins des carbonates, polycarbonates, sesquicarbonates, silicates, polysilicates, borates, métaborates, phosphates, stannates, alluminates et leurs mélanges.

8. Composition d'agent de blanchiment, utilisation ou procédé selon la revendication 7, dans lequel (dans laquelle) ledit agent tampon du pH est choisi parmi le groupe comprenant le carbonate de sodium, les silicates de sodium, le borate de sodium et leurs mélanges.

9. Composition d'agent de blanchiment, utilisation ou procédé selon l'une quelconque des revendications 1 à 8, dans lequel (dans laquelle) ledit agent tampon du pH est présent à raison de 0,5 % à 9 % en poids, de préférence de 0,5 % à 5 % en poids de la composition liquide ou à raison de 3 % à 30 % en poids, de préférence de 5 % à 25 % en poids de la composition solide.

10. Composition d'agent de blanchiment, utilisation ou procédé selon l'une quelconque des revendications 1 à 9, dans lequel (dans laquelle) ledit agent de blanchiment hypohalogéneux est, pour les compositions d'agent de blanchiment liquides, un hypochlorite de métal alcalin sodique ou, pour les compositions solides, du dichloroisocyanurate de sodium et/ou de l'hypochlorite de calcium.

11. Composition d'agent de blanchiment, utilisation ou procédé selon l'une quelconque des revendications 1 à 10, dans lequel (dans laquelle) ledit composé hypohalogéneux, sur la base de l'halogénure actif, est présent à raison de 0,1 % à 20 % en poids, de préférence de 2 % à 8 % en poids de la composition liquide ou à raison de 20 % à 95 % en poids, de préférence de 25 % à 60 % en poids de la composition solide.

12. Composition d'agent de blanchiment, utilisation ou procédé selon l'une quelconque des revendications 1 à 11, dans lequel (dans laquelle) ladite composition renferme, en outre, une forte source d'alcalinité.