



US008029498B2

(12) **United States Patent**
Johnson et al.

(10) **Patent No.:** **US 8,029,498 B2**
(45) **Date of Patent:** **Oct. 4, 2011**

(54) **SYSTEM FOR PERCUTANEOUSLY
ADMINISTERING REDUCED PRESSURE
TREATMENT USING BALLOON
DISSECTION**

(75) Inventors: **Royce W. Johnson**, Universal City, TX
(US); **Larry D. Swain**, San Antonio, TX
(US); **Douglas A. Cornet**, San Antonio,
TX (US); **Michael Manwaring**, San
Antonio, TX (US); **Jonathan Kagan**,
Hopkins, MN (US)

(73) Assignee: **KCI Licensing Inc.**, San Antonio, TX
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 802 days.

(21) Appl. No.: **11/717,892**

(22) Filed: **Mar. 13, 2007**

(65) **Prior Publication Data**

US 2007/0219471 A1 Sep. 20, 2007

Related U.S. Application Data

(60) Provisional application No. 60/782,171, filed on Mar.
14, 2006.

(51) **Int. Cl.**

A61M 27/00 (2006.01)
A61M 1/00 (2006.01)
A61M 3/00 (2006.01)
A61M 31/00 (2006.01)

(52) **U.S. Cl.** **604/543**; 604/27; 604/44; 604/48;
604/57; 604/73

(58) **Field of Classification Search** 604/28,
604/93, 175, 176, 164, 30, 246, 502, 506,
604/543, 27, 44, 48, 57, 73, 540

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,355,846	A	10/1920	Rannells
2,547,758	A	4/1951	Keeling
2,632,443	A	3/1953	Leshner
2,682,873	A	7/1954	Evans et al.
2,910,763	A	11/1959	Lauterbach
2,969,057	A	1/1961	Simmons

(Continued)

FOREIGN PATENT DOCUMENTS

AU 550575 A1 8/1982

(Continued)

OTHER PUBLICATIONS

N.A. Bagautdinov, "Variant of External Vacuum Aspiration in the
Treatment of Purulent Diseases of the Soft Tissues," *Current Prob-
lems in Modern Clinical Surgery: Interdepartmental Collection*,
edited by V. Ye Volkov et al. (Chuvashia State University,
Cheboksary, U.S.S.R. 1986);pp. 94-96 (certified translation).

(Continued)

Primary Examiner — Leslie Deak


Assistant Examiner — Adam Marcetich

(57)

ABSTRACT

A reduced pressure delivery system for applying a reduced
pressure to a tissue site includes a manifold delivery tube
having at least two lumens and a manifold having a plurality
of flow channels. The manifold is disposed within a first of the
lumens of the manifold delivery tube. A balloon having an
inner space and being capable of assuming collapsed and
expanded positions is provided. The inner space of the bal-
loon is fluidly connected to a second of the lumens of the
manifold delivery tube.

45 Claims, 20 Drawing Sheets



US 8,029,498 B2

Page 2

U.S. PATENT DOCUMENTS									
3,066,672	A	12/1962	Crosby, Jr. et al.	5,116,310	A	5/1992	Seder et al.		
3,367,332	A	2/1968	Groves	5,134,994	A	8/1992	Say		
3,382,867	A	5/1968	Reaves	5,149,331	A	9/1992	Ferdman et al.		
3,520,300	A	7/1970	Flower, Jr.	5,163,905	A	11/1992	Don Michael		
3,568,675	A	3/1971	Harvey	5,167,613	A	12/1992	Karami et al.		
3,648,692	A	3/1972	Wheeler	5,176,663	A	1/1993	Svedman et al.		
3,682,180	A	8/1972	McFarlane	5,215,522	A	6/1993	Page et al.		
3,826,254	A	7/1974	Mellor	5,232,453	A	8/1993	Plass et al.		
3,867,319	A	2/1975	Lundberg	5,254,084	A	10/1993	Geary		
3,993,080	A	* 11/1976	Loseff	5,259,399	A	11/1993	Brown		
4,029,104	A	6/1977	Kerber	5,261,893	A	11/1993	Zamierowski		
4,080,970	A	3/1978	Miller	5,266,071	A	11/1993	Elftman		
4,096,853	A	6/1978	Weigand	5,278,100	A	1/1994	Doan et al.		
4,139,004	A	2/1979	Gonzalez, Jr.	5,279,550	A	1/1994	Habib et al.		
4,165,748	A	8/1979	Johnson	5,298,015	A	3/1994	Komatsuzaki et al.		
4,184,510	A	1/1980	Murry et al.	5,324,306	A	6/1994	Makower et al.		
4,233,969	A	11/1980	Lock et al.	5,342,376	A	8/1994	Ruff		
4,245,630	A	1/1981	Lloyd et al.	5,344,415	A	9/1994	DeBusk et al.		
4,256,109	A	3/1981	Nichols	5,358,494	A	10/1994	Svedman		
4,261,363	A	4/1981	Russo	5,405,322	A	4/1995	Lennox et al.		
4,275,721	A	6/1981	Olson	5,437,622	A	8/1995	Carion		
4,284,079	A	8/1981	Adair	5,437,651	A	8/1995	Todd et al.		
4,297,995	A	11/1981	Golub	5,443,481	A	8/1995	Lee		
4,324,262	A	* 4/1982	Hall	5,527,293	A	6/1996	Zamierowski		
4,329,743	A	5/1982	Alexander et al.	5,549,579	A	8/1996	Batdorf et al.		
4,333,468	A	6/1982	Geist	5,549,584	A	8/1996	Gross		
4,373,519	A	2/1983	Errede et al.	5,556,375	A	9/1996	Ewall		
4,382,441	A	5/1983	Svedman	5,569,184	A	10/1996	Crocker et al.		
4,392,853	A	7/1983	Muto	5,591,183	A	1/1997	Chin		
4,392,858	A	7/1983	George et al.	5,607,388	A	3/1997	Ewall		
4,419,097	A	12/1983	Rowland	5,634,935	A	6/1997	Taheri		
4,465,485	A	8/1984	Kashmer et al.	5,636,643	A	6/1997	Argenta et al.		
4,475,909	A	10/1984	Eisenberg	5,645,081	A	7/1997	Argenta et al.		
4,479,792	A	10/1984	Lazarus et al.	5,676,634	A	10/1997	Khoury		
4,480,638	A	11/1984	Schmid	5,820,581	A	10/1998	Wolfenbarger, Jr.		
4,525,166	A	6/1985	Leclerc	5,885,508	A	3/1999	Ishida		
4,525,374	A	6/1985	Vaillancourt	5,888,544	A	3/1999	Gergely et al.		
4,540,412	A	9/1985	Van Overloop	5,914,264	A	6/1999	Korman		
4,543,100	A	9/1985	Brodsky	5,948,020	A	9/1999	Yoon et al.		
4,548,202	A	10/1985	Duncan	5,984,942	A	11/1999	Alden et al.		
4,551,139	A	11/1985	Plaas et al.	6,013,054	A	1/2000	Jium Yan		
4,569,348	A	2/1986	Hasslinger	6,042,537	A	3/2000	Kaiser		
4,572,906	A	2/1986	Sparkes et al.	6,071,267	A	6/2000	Zamierowski		
4,579,555	A	4/1986	Russo	6,086,587	A	7/2000	Hawk		
4,605,399	A	8/1986	Weston et al.	6,132,415	A	* 10/2000	Finch et al.	604/502	
4,608,041	A	8/1986	Nielson	6,135,116	A	10/2000	Vogel et al.		
4,640,688	A	2/1987	Hauser	6,142,982	A	* 11/2000	Hunt et al.	604/313	
4,655,754	A	4/1987	Richmond et al.	6,174,306	B1	1/2001	Fleischmann		
4,664,662	A	5/1987	Webster	6,241,747	B1	6/2001	Ruff		
4,681,570	A	7/1987	Dalton	6,285,903	B1	* 9/2001	Rosenthal et al.	600/433	
4,710,165	A	12/1987	McNeil et al.	6,287,316	B1	9/2001	Agarwal et al.		
4,733,659	A	3/1988	Edenbaum et al.	6,345,623	B1	2/2002	Heaton et al.		
4,743,232	A	5/1988	Kruger	6,394,948	B1	5/2002	Borst et al.		
4,758,220	A	7/1988	Sundblom et al.	6,398,767	B1	6/2002	Fleischmann		
4,787,888	A	11/1988	Fox	6,458,109	B1	10/2002	Henley et al.		
4,826,494	A	5/1989	Richmond et al.	6,478,960	B1	11/2002	Saruhashi et al.		
4,830,856	A	5/1989	Peppers	6,488,643	B1	12/2002	Tumey et al.		
4,838,883	A	6/1989	Matsuura	6,493,568	B1	12/2002	Bell et al.		
4,840,187	A	6/1989	Brazier	6,500,112	B1	12/2002	Khoury		
4,863,449	A	9/1989	Therriault et al.	6,551,280	B1	4/2003	Knighton et al.		
4,872,450	A	10/1989	Austad	6,553,998	B2	4/2003	Heaton et al.		
4,878,901	A	11/1989	Sachse	6,613,026	B1	9/2003	Palasis et al.		
4,897,081	A	1/1990	Poirier et al.	6,641,575	B1	11/2003	Lonky		
4,906,233	A	3/1990	Moriuchi et al.	6,685,681	B2	2/2004	Lockwood et al.		
4,906,240	A	3/1990	Reed et al.	6,695,823	B1	2/2004	Lina et al.		
4,919,654	A	4/1990	Kalt et al.	6,752,794	B2	6/2004	Lockwood et al.		
4,936,834	A	6/1990	Beck et al.	6,755,796	B2	6/2004	Spector		
4,941,882	A	7/1990	Ward et al.	6,755,807	B2	6/2004	Risk, Jr. et al.		
4,953,565	A	9/1990	Tachibana et al.	6,758,836	B2	7/2004	Zawacki		
4,969,880	A	11/1990	Zamierowski	6,764,497	B2	7/2004	Fogarty et al.		
4,985,019	A	1/1991	Michelson	6,800,074	B2	10/2004	Henley et al.		
5,034,006	A	7/1991	Hosoda et al.	6,814,079	B2	11/2004	Heaton et al.		
5,037,397	A	8/1991	Kalt et al.	6,824,533	B2	11/2004	Risk, Jr. et al.		
5,045,056	A	* 9/1991	Behl	6,840,960	B2	1/2005	Bubb		
5,086,170	A	2/1992	Luheshi et al.	6,855,135	B2	2/2005	Lockwood et al.		
5,092,858	A	3/1992	Benson et al.	6,866,805	B2	3/2005	Hong et al.		
5,100,396	A	3/1992	Zamierowski	6,871,740	B1	3/2005	Cao		
5,108,364	A	* 4/1992	Takezawa et al.	6,979,324	B2	12/2005	Bybordi et al.		
				7,322,971	B2	* 1/2008	Shehada	604/540	

7,753,902	B1 *	7/2010	Mansour et al.	604/541
2002/0028243	A1	3/2002	Masters	
2002/0077661	A1	6/2002	Saadat	
2002/0115951	A1	8/2002	Norstrom et al.	
2002/0120185	A1	8/2002	Johnson	
2002/0143286	A1	10/2002	Tumey	
2002/0161346	A1	10/2002	Lockwood et al.	
2002/0198503	A1	12/2002	Risk, Jr. et al.	
2003/0033017	A1	2/2003	Lotz et al.	
2003/0057070	A1	3/2003	Wang et al.	
2003/0088209	A1	5/2003	Chiu et al.	
2003/0167031	A1	9/2003	Odland	
2003/0216672	A1	11/2003	Rastegar et al.	
2004/0006319	A1	1/2004	Lina et al.	
2004/0064111	A1	4/2004	Lockwood et al.	
2004/0071949	A1	4/2004	Glatkowski et al.	
2004/0093026	A1	5/2004	Weidenhagen et al.	
2004/0093080	A1	5/2004	Helmus et al.	
2004/0098017	A1 *	5/2004	Saab et al.	606/192
2004/0122434	A1	6/2004	Argenta et al.	
2004/0243167	A1	12/2004	Tanaka et al.	
2005/0065484	A1	3/2005	Watson, Jr.	
2005/0131327	A1	6/2005	Lockwood et al.	
2005/0192532	A1	9/2005	Kucklick et al.	
2005/0267577	A1	12/2005	Trieu	
2006/0024266	A1	2/2006	Brandom et al.	
2006/0142685	A1	6/2006	Addison et al.	
2006/0200003	A1	9/2006	Youssef	
2007/0156251	A1	7/2007	Karmon	
2007/0237811	A1	10/2007	Scherr	
2008/0033333	A1	2/2008	Macphee et al.	
2008/0114277	A1	5/2008	Ambrosio et al.	
2008/0206308	A1	8/2008	Jabbari et al.	
2008/0275409	A1	11/2008	Kane et al.	
2008/0319268	A1	12/2008	Michaeli et al.	

FOREIGN PATENT DOCUMENTS

AU	745271	4/1999
AU	755496	2/2002
CA	2005436	6/1990
DE	26 40 413 A1	3/1978
DE	43 06 478 A1	9/1994
DE	295 04 378 U1	10/1995
EP	0100148 A1	2/1984
EP	0117632 A2	9/1984
EP	0161865 A2	11/1985
EP	0358302 A2	3/1990
EP	1018967 B1	8/2004
GB	692578	6/1953
GB	2 195 255 A	4/1988
GB	2 197 789 A	6/1988
GB	2 220 357 A	1/1990
GB	2 235 877 A	3/1991
GB	2 333 965 A	8/1999
GB	2 329 127 B	8/2000
JP	4129536	4/1992
KR	10-2002-0000580 A	1/2002
SG	71559	4/2002
TW	512066	12/2002
TW	558444	10/2003
TW	200612877	5/2006
WO	WO 80/02182	10/1980
WO	WO 87/04626	8/1987
WO	WO 90/10424	9/1990
WO	WO 93/09727	5/1993
WO	WO 94/20041	9/1994
WO	WO 96/05873	2/1996
WO	WO 96/30073 A1	10/1996
WO	WO 97/18007	5/1997
WO	WO 99/13793	3/1999
WO	WO 03/057070	7/2003
WO	WO 2004/071949 A2	8/2004
WO	WO 2005/105180	11/2005

OTHER PUBLICATIONS

Chariker, Mark E., M.D., et al; "Effective Management of incisional and cutaneous fistulae with closed suction wound drainage"; *Con-temporary Surgery*, vol. 34, Jun. 1989, pp. 59-63.

Egnell Minor, Instruction Book, First Edition, 300 7502, Feb. 1975, pp. 24.

Egnell Minor: Addition to the Users Manual Concerning Overflow Protection—Concerns all Egnell Pumps, Feb. 3, 1983, pp. 2.

Svedman, P.: "Irrigation Treatment of Leg Ulcers", *The Lancet*, Sep. 3, 1983, pp. 532-534.

Chinn, Steven D. et al.: "Closed Wound Suction Drainage", *The Journal of Foot Surgery*, vol. 24, No. 1, 1985, pp. 76-81.

Arnljots, Björn et al.: "Irrigation Treatment in Split-Thickness Skin Grafting of Intractable Leg Ulcers", *Scand J. Plast Reconstr. Surg.*, No. 19, 1985, pp. 211-213.

Svedman, P.: "A Dressing Allowing Continuous Treatment of a Biosurface", *IRCS Medical Science: Biomedical Technology, Clinical Medicine, Surgery and Transplantation*, vol. 7, 1979, p. 221.

Svedman, P. et al.: "A Dressing System Providing Fluid Supply and Suction Drainage Used for Continuous or Intermittent Irrigation", *Annals of Plastic Surgery*, vol. 17, No. 2, Aug. 1986, pp. 125-133.

K.F. Jeter, T.E. Tittle, and M. Chariker, "Managing Draining Wounds and Fistulae: New and Established Methods," *Chronic Wound Care*, edited by D. Krasner (Health Management Publications, Inc., King of Prussia, PA 1990), pp. 240-246.

G. Živadinović, V. Đukić, Ž. Maksimović, Đ. Radak, and P. Peška, "Vacuum Therapy in the Treatment of Peripheral Blood Vessels," *Timok Medical Journal* 11 (1986), pp. 161-164 (certified translation). F.E. Johnson, "An Improved Technique for Skin Graft Placement Using a Suction Drain," *Surgery, Gynecology, and Obstetrics* 159 (1984), pp. 584-585.

A.A. Safronov, Dissertation Abstract, *Vacuum Therapy of Trophic Ulcers of the Lower Leg with Simultaneous Autoplasty of the Skin* (Central Scientific Research Institute of Traumatology and Orthopedics, Moscow, U.S.S.R. 1967) (certified translation).

M. Schein, R. Saadia, J.R. Jamieson, and G.A.G. Decker, "The 'Sandwich Technique' in the Management of the Open Abdomen," *British Journal of Surgery* 73 (1986), pp. 369-370.

D.E. Tribble, An Improved Sump Drain-Irrigation Device of Simple Construction, *Archives of Surgery* 105 (1972) pp. 511-513.

M.J. Morykwas, L.C. Argenta, E.I. Shelton-Brown, and W. McGuirt, "Vacuum-Assisted Closure: A New Method for Wound Control and Treatment: Animal Studies and Basic Foundation," *Annals of Plastic Surgery* 38 (1997), pp. 553-562 (Morykwas I).

C.E. Tennants, "The Use of Hypermia in the Postoperative Treatment of Lesions of the Extremities and Thorax," *Journal of the American Medical Association* 64 (1915), pp. 1548-1549.

Selections from W. Meyer and V. Schmieden, *Bier's Hyperemic Treatment in Surgery, Medicine, and the Specialties: A Manual of Its Practical Application*, (W.B. Saunders Co., Philadelphia, PA 1909), pp. 17-25, 44-64, 90-96, 167-170, and 210-211.

Non-Final Office Action date mailed May 28, 2008 for U.S. Appl. No. 11/717,854.

Response filed Aug. 13, 2008 to Non-Final Office Action date mailed May 28, 2008 for U.S. Appl. No. 11/717,854.

Non-Final Office Action date mailed Nov. 13, 2008 for U.S. Appl. No. 11/717,854.

Response filed Dec. 12, 2008 to Non-Final Office Action date mailed Nov. 13, 2008 for U.S. Appl. No. 11/717,854.

Louis C. Argenta, MD and Michael J. Morykwas, PhD; "Vacuum-Assisted Closure: A New Method for Wound Control and Treatment: Clinical Experience"; *Annals of Plastic Surgery*, vol. 38, No. 6, Jun. 1997; pp. 563-576.

Susan Mendez-Eastmen, RN; "When Wounds Won't Heal" *RN Jan.* 1998, vol. 61 (1); Medical Economics Company, Inc., Montvale, NJ, USA; pp. 20-24.

James H. Blackburn, II, MD, et al; "Negative-Pressure Dressings as a Bolster for Skin Grafts"; *Annals of Plastic Surgery*, vol. 40, No. 5, May 1998, pp. 453-457.

John Masters; "Reliable, Inexpensive and Simple Suction Dressings"; Letter to the Editor, *British Journal of Plastic Surgery*, 1998, vol. 51 (3), p. 267; Elsevier Science/The British Association of Plastic Surgeons, UK.

S.E. Greer, et al "The Use of Subatmospheric Pressure Dressing Therapy to Close Lymphocutaneous Fistulas of the Groin" *British Journal of Plastic Surgery* (2000), 53, pp. 484-487.

- George V. Letsou, MD., et al; "Stimulation of Adenylate Cyclase Activity in Cultured Endothelial Cells Subjected to Cyclic Stretch"; *Journal of Cardiovascular Surgery*, 31, 1990, pp. 634-639.
- Orringer, Jay, et al; "Management of Wounds in Patients with Complex Enterocutaneous Fistulas"; *Surgery, Gynecology & Obstetrics*, Jul. 1987, vol. 165, pp. 79-80.
- International Search Report for PCT International Application PCT/GB95/01983; Nov. 23, 1995.
- PCT International Search Report for PCT International Application PCT/GB98/02713; Jan. 8, 1999.
- PCT Written Opinion; PCT International Application PCT/GB98/02713; Jun. 8, 1999.
- PCT International Examination and Search Report, PCT International Application PCT/GB96/02802; Jan. 15, 1998 & Apr. 29, 1997.
- PCT Written Opinion, PCT International Application PCT/GB96/02802; Sep. 3, 1997.
- Dattilo, Philip P., Jr., et al; "Medical Textiles: Application of an Absorbable Barbed Bi-directional Surgical Suture"; *Journal of Textile and Apparel, Technology and Management*, vol. 2, Issue 2, Spring 2002, pp. 1-5.
- Kostyuchenok, B.M., et al; "Vacuum Treatment in the Surgical Management of Purulent Wounds"; *Vestnik Khirurgi*, Sep. 1986, pp. 18-21 and 6 page English translation thereof.
- Davydov, Yu. A., et al; "Vacuum Therapy in the Treatment of Purulent Lactation Mastitis"; *Vestnik Khirurgi*, May 14, 1986, pp. 66-70, and 9 page English translation thereof.
- Yusupov, Yu. N., et al; "Active Wound Drainage"; *Vestnik Khirurgi*, vol. 138, Issue 4, 1987, and 7 page English translation thereof.
- Davydov, Yu. A., et al; "Bacteriological and Cytological Assessment of Vacuum Therapy for Purulent Wounds"; *Vestnik Khirurgi*, May 2, 1986, pp. 42-46, and 7 page English translation thereof.
- Davydov, Yu. A., et al; "Concepts for the Clinical-Biological Management of the Wound Process in the Treatment of Purulent Wounds by Means of Vacuum Therapy"; *Vestnik Khirurgi*, Jul. 7, 1980, pp. 132-136, and 8 page English translation thereof.
- Marc G. Jeschke, MD, et al; "Development of New Reconstructive Techniques: Use of Integra in Combination with Fibrin Glue and Negative-Pressure Therapy for Reconstruction of Acute and Chronic Wounds"; *Plastic and Reconstructive Surgery*, Feb. 2004, vol. 113, No. 2, pp. 525-530.
- C. Daniel Medical, Inc.; All Silicone Jackson Pratt® Style Round Drain; www.cdanielmedical.com; Mar. 2007, 2 pgs.
- C. Daniel Medical, Inc.; All Silicone Jackson Pratt® Style Flat Drain; www.cdanielmedical.com; Mar. 2007, 2 pgs.
- V.A. Solovev et al., Guidelines, The Method of Treatment of Immature External Fistulas in the Upper Gastrointestinal Tract, editor-in-chief Prov. V.I. Parahonyak (S.M. Kirov Gorky State Medical Institute, Gorky, U.S.S.R. 1987) ("Solovev Guidelines").
- V.A. Kuznetsov & N.a. Bagautdinov, "Vacuum and Vacuum-Sorption Treatment of Open Septic Wounds," in II All-Union Conference on Wounds and Wound Infections: Presentation Abstracts, edited by B.M. Kostyuchenok et al. (Moscow, U.S.S.R. Oct. 28-29, 1986) pp. 91-92 ("Bagautdinov II").
- V.A. Solovev, Dissertation Abstract, Treatment and Prevention of Suture Failures after Gastric Resection (S.M. Kirov Gorky State Medical Institute, Gorky, U.S.S.R. 1988) ("Solovev Abstract").
- Non-Final Office Action date mailed Mar. 5, 2009 for U.S. Appl. No. 11/717,854.
- Response filed Jun. 25, 2009 to Non-Final Office Action date mailed Mar. 5, 2009 for U.S. Appl. No. 11/717,854.
- Non-Final Office Action date mailed Jun. 18, 2009 for U.S. Appl. No. 11/807,834.
- Non-Final Office Action date mailed Oct. 1, 2009 in U.S. Appl. No. 11/717,854.
- Examiner Interview Summary date mailed Dec. 11, 2009 in U.S. Appl. No. 11/717,854.
- Response filed Dec. 23, 2009 to Non-Final Action dated Oct. 1, 2009 in U.S. Appl. No. 11/717,854.
- Response to Non-Final Action filed Aug. 19, 2009 in U.S. Appl. No. 11/807,834.
- Final Office Action date mailed Oct. 2, 2009 in U.S. Appl. No. 11/807,834.
- RCE/Amendment filed Jan. 27, 2010 in U.S. Appl. No. 11/807,834.
- V.A.C.® Therapy Clinical Guidelines: A Reference Source for Clinicians (Jul. 2007).
- Non-Final Rejection date mailed Mar. 18, 2010 in U.S. Appl. No. 11/717,854.
- Non-Final Action date mailed Mar. 11, 2010 in U.S. Appl. No. 11/807,834.
- Kilbride, et al. "Vacuum-assisted closure: a new method for treating patients with giant omphalocele", *J Pediatr Surg*; Jan. 2006; vol. 41, iss 1, pp. 212-215 (Abstract only).
- Davydov et al, "Vacuum-therapy of Wounds and Wound Process," Moscow, Meditsina, 1999, pp. 66-69 (English translation).
- Express Abandonment filed Apr. 22, 2010 in U.S. Appl. No. 12/540,934.
- Decision on Petition for Express Abandonment and Notice of Abandonment date mailed May 3, 2010 in U.S. Appl. No. 12/540,934.
- Non-Final Office Action date mailed Sep. 15, 2010 for U.S. Appl. No. 11/717,854.
- Final Office Action date mailed Aug. 31, 2010 for U.S. Appl. No. 11/807,834.
- Response filed Jul. 1, 2010 for U.S. Appl. No. 11/717,854.
- Interview Summary date mailed Jul. 6, 2010 for U.S. Appl. No. 11/717,854.
- Interview Summary date mailed Jun. 11, 2010 for U.S. Appl. No. 11/807,834.
- Response filed Jun. 14, 2010 for U.S. Appl. No. 11/807,834.
- Restriction Requirement date mailed Oct. 6, 2010 for U.S. Appl. No. 11/724,073.
- Response filed Nov. 2, 2010 for U.S. Appl. No. 11/724,073.
- Restriction Requirement date mailed Oct. 7, 2010 for U.S. Appl. No. 11/724,072.
- Response filed Nov. 8, 2010 for U.S. Appl. No. 11/724,072.
- Response filed Oct. 26, 2010 for U.S. Appl. No. 11/807,834.
- International Search Report and Written Opinion date mailed Sep. 13, 2010 for PCT Application No. PCT/US2009/069495.
- Response filed Apr. 18, 2011 for U.S. Appl. No. 11/724,073.
- Interview Summary date mailed Apr. 20, 2011 for U.S. Appl. No. 11/724,073.
- Advisory Action date mailed Nov. 10, 2010 for U.S. Appl. No. 11/807,834.
- RCE/Response filed Nov. 24, 2010 for U.S. Appl. No. 11/807,834.
- Non-Final Office Action date mailed Feb. 18, 2011 for U.S. Appl. No. 11/807,834.
- Response filed Dec. 15, 2010 for U.S. Appl. No. 11/717,854.
- Interview Summary date mailed Dec. 19, 2010 for U.S. Appl. No. 11/717,854.
- Non-Final Office Action date mailed Jan. 21, 2011 for U.S. Appl. No. 11/724,073.
- Non-Final Office Action date mailed Feb. 14, 2011 for U.S. Appl. No. 11/724,072.

* cited by examiner





FIG. 2




FIG. 3




FIG. 4A




FIG. 4B










FIG. 5

4/20








FIG. 10




FIG. 11




FIG. 12










FIG. 13

*FIG. 14**FIG. 15**FIG. 16**FIG. 17**FIG. 18**FIG. 19*




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24













FIG. 25



*FIG. 27**FIG. 27A**FIG. 28*

*FIG. 29**FIG. 30*

*FIG. 31*




FIG. 32




FIG. 33




FIG. 34




FIG. 35



















FIG. 36











1

SYSTEM FOR PERCUTANEOUSLY ADMINISTERING REDUCED PRESSURE TREATMENT USING BALLOON DISSECTION

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application No. 60/782,171, filed Mar. 14, 2006, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates generally to a system or method of promoting tissue growth and more specifically a system for applying reduced pressure tissue treatment to a tissue site.

2. Description of Related Art

Reduced pressure therapy is increasingly used to promote wound healing in soft tissue wounds that are slow to heal or non-healing without reduced pressure therapy. Typically, reduced pressure is applied to the wound site through an open-cell foam that serves as a manifold to distribute the reduced pressure. The open-cell foam is sized to fit the existing wound, placed into contact with the wound, and then periodically replaced with smaller pieces of foam as the wound begins to heal and become smaller. Frequent replacement of the open-cell foam is necessary to minimize the amount of tissue that grows into the cells of the foam. Significant tissue in-growth can cause pain to patients during removal of the foam.

Reduced pressure therapy is typically applied to non-healing, open wounds. In some cases, the tissues being healed are subcutaneous, and in other cases, the tissues are located within or on dermal tissue. Traditionally, reduced pressure therapy has primarily been applied to soft tissues. Reduced pressure therapy has not typically been used to treat closed, deep-tissue wounds because of the difficulty of access presented by such wounds. Additionally, reduced pressure therapy has not been used in connection with healing bone defects or promoting bone growth, primarily due to access problems. Surgically exposing a bone to apply reduced pressure therapy may create more problems than it solves. Finally, devices and systems for applying reduced pressure therapy have advanced little beyond the open-cell foam pieces that are manually shaped to fit a wound site and then removed following a period of reduced pressure therapy.

BRIEF SUMMARY OF THE INVENTION

The problems presented by existing wound-healing system and methods are solved by the systems and methods of the present invention. A reduced pressure delivery system is provided in accordance with one embodiment of the present invention to apply a reduced pressure to a tissue site. The reduced pressure delivery system includes a manifold delivery tube having at least two lumens and a manifold having a plurality of flow channels. The manifold is disposed within a first of the lumens of the manifold delivery tube. A balloon having an inner space and being capable of assuming collapsed and expanded positions is provided. The inner space of the balloon is fluidly connected to a second of the lumens of the manifold delivery tube.

In accordance with another embodiment of the present invention, a reduced pressure delivery system is provided and includes an impermeable membrane having an inner space.

2

The impermeable membrane is capable of assuming compressed and relaxed conditions. A manifold having a plurality of flow channels is positioned within the inner space of the impermeable membrane. A reduced pressure within the inner space of the impermeable membrane is less than the pressure outside the impermeable membrane to reduce a volume of space occupied by the manifold within the impermeable membrane.

In accordance with still another embodiment of the present invention, a reduced pressure delivery system is provided and includes a manifold delivery tube having at least one passageway and a distal end, the distal end capable of being placed adjacent the tissue site. A manifold having a plurality of flow channels is configured to be delivered through the passageway of the manifold delivery tube to the tissue site. An impermeable membrane is provided and is positionable at the distal end of the manifold delivery tube. The impermeable membrane includes an inner space and is capable of assuming at least one of an expanded position and a collapsed position.

Other objects, features, and advantages of the present invention will become apparent with reference to the drawings and detailed description that follow.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 depicts a perspective view of a reduced pressure delivery apparatus according to an embodiment of the present invention, the reduced pressure delivery apparatus having a plurality of projections extending from a flexible barrier to create a plurality of flow channels;

FIG. 2 illustrates a front view of the reduced pressure delivery apparatus of FIG. 1;

FIG. 3 depicts a top view of the reduced pressure delivery apparatus of FIG. 1;

FIG. 4A illustrates a side view of the reduced pressure delivery apparatus of FIG. 1, the reduced pressure delivery apparatus having a single lumen, reduced-pressure delivery tube;

FIG. 4B depicts a side view of an alternative embodiment of the reduced pressure delivery apparatus of FIG. 1, the reduced pressure delivery apparatus having a dual lumen, reduced-pressure delivery tube;

FIG. 5 illustrates an enlarged perspective view of the reduced pressure delivery apparatus of FIG. 1;

FIG. 6 depicts a perspective view of a reduced pressure delivery apparatus according to an embodiment of the present invention, the reduced pressure delivery apparatus having a cellular material attached to a flexible barrier having a spine portion and a pair of wing portions, the cellular material having a plurality of flow channels;

FIG. 7 illustrates a front view of the reduced pressure delivery apparatus of FIG. 6;

FIG. 8 depicts a cross-sectional side view of the reduced pressure delivery apparatus of FIG. 7 taken at XVII-XVII;

FIG. 8A illustrates a cross-sectional front view of a reduced pressure delivery apparatus according to an embodiment of the present invention;

FIG. 8B depicts a side view of the reduced pressure delivery apparatus of FIG. 8A;

FIG. 9 illustrates a front view of a reduced pressure delivery apparatus according to an embodiment of the present invention being used to apply a reduced pressure tissue treatment to a bone of a patient;

FIG. 10 depicts a color histological section of a rabbit cranium showing naive, undamaged bone;

3

FIG. 11 illustrates a color histological section of a rabbit cranium showing induction of granulation tissue after application of reduced pressure tissue treatment;

FIG. 12 depicts a color histological section of a rabbit cranium showing deposition of new bone following application of reduced pressure tissue treatment;

FIG. 13 illustrates a color histological section of a rabbit cranium showing deposition of new bone following application of reduced pressure tissue treatment;

FIG. 14 depicts a color photograph of a rabbit cranium having two critical size defects formed in the cranium;

FIG. 15 illustrates a color photograph of the rabbit cranium of FIG. 14 showing a calcium phosphate scaffold inserted within one of the critical size defects and a stainless steel screen overlaying the second of the critical size defects;

FIG. 16 depicts a color photograph of the rabbit cranium of FIG. 14 showing the application of reduced pressure tissue treatment to the critical size defects;

FIG. 17 illustrates a color histological section of a rabbit cranium following reduced pressure tissue treatment, the histological section showing deposition of new bone within the calcium phosphate scaffold;

FIG. 18 depicts a radiograph of the scaffold-filled, critical size defect of FIG. 15 following six days of reduced pressure tissue treatment and two weeks post surgery;

FIG. 19 illustrates a radiograph of the scaffold-filled, critical size defect of FIG. 15 following six days of reduced pressure tissue treatment and twelve weeks post surgery;

FIG. 20 depicts a front view of a reduced pressure delivery system according to an embodiment of the present invention, the reduced pressure delivery system having a manifold delivery tube that is used to percutaneously insert a reduced pressure delivery apparatus to a tissue site;

FIG. 21 illustrates an enlarged front view of the manifold delivery tube of FIG. 20, the manifold delivery tube containing a reduced pressure delivery apparatus having a flexible barrier and/or a cellular material in a compressed position;

FIG. 22 depicts an enlarged front view of the manifold delivery tube of FIG. 21, the flexible barrier and/or cellular material of the reduced pressure delivery apparatus being shown in an expanded position after having been pushed from the manifold delivery tube;

FIG. 23 illustrates a front view of a reduced pressure delivery system according to an embodiment of the present invention, the reduced pressure delivery system having a manifold delivery tube that is used to percutaneously insert a reduced pressure delivery apparatus to a tissue site, the reduced pressure delivery apparatus being shown outside of the manifold delivery tube but constrained by an impermeable membrane in a compressed position;

FIG. 24 depicts a front view of the reduced pressure delivery system of FIG. 23, the reduced pressure delivery apparatus being shown outside of the manifold delivery tube but constrained by an impermeable membrane in a relaxed position;

FIG. 25 illustrates a front view of the reduced pressure delivery system of FIG. 23, the reduced pressure delivery apparatus being shown outside of the manifold delivery tube but constrained by an impermeable membrane in an expanded position;

FIG. 25A illustrates a front view of the reduced pressure delivery system of FIG. 23, the reduced pressure delivery apparatus being shown outside of the manifold delivery tube but surrounded by an impermeable membrane in an expanded position

FIG. 26 depicts a front view of a reduced pressure delivery system according to an embodiment of the present invention,

4

the reduced pressure delivery system having a manifold delivery tube that is used to percutaneously insert a reduced pressure delivery apparatus to a tissue site, the reduced pressure delivery apparatus being shown outside of the manifold delivery tube but constrained by an impermeable membrane having a glue seal;

FIG. 26A depicts a front view of a reduced pressure delivery system according to an embodiment of the present invention;

FIG. 27 illustrates a front view of a reduced pressure delivery system according to an embodiment of the present invention, the reduced pressure delivery system having a manifold delivery tube that is used to percutaneously inject a reduced pressure delivery apparatus to a tissue site;

FIG. 27A illustrates a front view of a reduced pressure delivery system according to an embodiment of the present invention, the reduced pressure delivery system having a manifold delivery tube that is used to percutaneously deliver a reduced pressure delivery apparatus to an impermeable membrane positioned at a tissue site;

FIG. 28 depicts a flow chart of a method of administering a reduced pressure tissue treatment to a tissue site according to an embodiment of the present invention;

FIG. 29 illustrates a flow chart of a method of administering a reduced pressure tissue treatment to a tissue site according to an embodiment of the present invention;

FIG. 30 depicts a flow chart of a method of administering a reduced pressure tissue treatment to a tissue site according to an embodiment of the present invention;

FIG. 31 illustrates a flow chart of a method of administering a reduced pressure tissue treatment to a tissue site according to an embodiment of the present invention;

FIG. 32 depicts a cross-sectional front view of a reduced pressure delivery apparatus according to an embodiment of the present invention, the reduced pressure delivery apparatus including a hip prosthesis having a plurality of flow channels for applying a reduced pressure to an area of bone surrounding the hip prosthesis;

FIG. 33 illustrates a cross-sectional front view of the hip prosthesis of FIG. 32 having a second plurality of flow channels for delivering a fluid to the area of bone surrounding the hip prosthesis;

FIG. 34 depicts a flow chart of a method for repairing a joint of a patient using reduced pressure tissue treatment according to an embodiment of the present invention;

FIG. 35 illustrates a cross-sectional front view of a reduced pressure delivery apparatus according to an embodiment of the present invention, the reduced pressure delivery apparatus including an orthopedic fixation device having a plurality of flow channels for applying a reduced pressure to an area of bone adjacent the orthopedic fixation device;

FIG. 36 depicts a cross-sectional front view of the orthopedic fixation device of FIG. 35 having a second plurality of flow channels for delivering a fluid to the area of bone adjacent the orthopedic fixation device;

FIG. 37 illustrates a flow chart of a method for healing a bone defect of a bone using reduced pressure tissue treatment according to an embodiment of the present invention;

FIG. 38 depicts a flow chart of a method of administering a reduced pressure tissue treatment to a tissue site according to an embodiment of the present invention; and

FIG. 39 illustrates a flow chart of a method of administering a reduced pressure tissue treatment to a tissue site according to an embodiment of the present invention.

FIGS. 40-48 depict various views of a reduced pressure delivery system according to an embodiment of the present invention, the reduced pressure delivery system having a pri-

5

mary manifold that includes a flexible wall surrounding a primary flow passage and a plurality of apertures in the flexible wall;

FIGS. 49-50 illustrate perspective and top cross-sectional views of a reduced pressure delivery system according to an embodiment of the present invention, the reduced pressure delivery system having a primary manifold that is integrally connected to a reduced pressure delivery tube;

FIG. 51 depicts a perspective view of the primary manifolds of FIGS. 40-50 being applied with a secondary manifold to a bone tissue site; and

FIG. 52 illustrates a schematic view of a reduced pressure delivery system having a valve fluidly connected to a second conduit according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In the following detailed description of the preferred embodiments, reference is made to the accompanying drawings that form a part hereof, and in which is shown by way of illustration specific preferred embodiments in which the invention may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention, and it is understood that other embodiments may be utilized and that logical structural, mechanical, electrical, and chemical changes may be made without departing from the spirit or scope of the invention. To avoid detail not necessary to enable those skilled in the art to practice the invention, the description may omit certain information known to those skilled in the art. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is defined only by the appended claims.

As used herein, the term “elastomeric” means having the properties of an elastomer. The term “elastomer” refers generally to a polymeric material that has rubber-like properties. More specifically, most elastomers have elongation rates greater than 100% and a significant amount of resilience. The resilience of a material refers to the material's ability to recover from an elastic deformation. Examples of elastomers may include, but are not limited to, natural rubbers, polyisoprene, styrene butadiene rubber, chloroprene rubber, polybutadiene, nitrile rubber, butyl rubber, ethylene propylene rubber, ethylene propylene diene monomer, chlorosulfonated polyethylene, polysulfide rubber, polyurethane, and silicones.

As used herein, the term “flexible” refers to an object or material that is able to be bent or flexed. Elastomeric materials are typically flexible, but reference to flexible materials herein does not necessarily limit material selection to only elastomers. The use of the term “flexible” in connection with a material or reduced pressure delivery apparatus of the present invention generally refers to the material's ability to conform to or closely match the shape of a tissue site. For example, the flexible nature of a reduced pressure delivery apparatus used to treat a bone defect may allow the apparatus to be wrapped or folded around the portion of the bone having the defect.

The term “fluid” as used herein generally refers to a gas or liquid, but may also include any other flowable material, including but not limited to gels, colloids, and foams.

The term “impermeable” as used herein generally refers to the ability of a membrane, cover, sheet, or other substance to block or slow the transmission of either liquids or gas. Impermeability may be used to refer to covers, sheets, or other membranes that are resistant to the transmission of liquids,

6

while allowing gases to transmit through the membrane. While an impermeable membrane may be liquid tight, the membrane may simply reduce the transmission rate of all or only certain liquids. The use of the term “impermeable” is not meant to imply that an impermeable membrane is above or below any particular industry standard measurement for impermeability, such as a particular value of water vapor transfer rate (WVTR).

The term “manifold” as used herein generally refers to a substance or structure that is provided to assist in applying reduced pressure to, delivering fluids to, or removing fluids from a tissue site. A manifold typically includes a plurality of flow channels or pathways that are interconnected to improve distribution of fluids provided to and removed from the area of tissue around the manifold. Examples of manifolds may include without limitation devices that have structural elements arranged to form flow channels, cellular foam such as open-cell foam, porous tissue collections, and liquids, gels and foams that include or cure to include flow channels.

The term “reduced pressure” as used herein generally refers to a pressure less than the ambient pressure at a tissue site that is being subjected to treatment. In most cases, this reduced pressure will be less than the atmospheric pressure at which the patient is located. Alternatively, the reduced pressure may be less than a hydrostatic pressure of tissue at the tissue site. Although the terms “vacuum” and “negative pressure” may be used to describe the pressure applied to the tissue site, the actual pressure applied to the tissue site may be significantly less than the pressure normally associated with a complete vacuum. Reduced pressure may initially generate fluid flow in the tube and the area of the tissue site. As the hydrostatic pressure around the tissue site approaches the desired reduced pressure, the flow may subside, and the reduced pressure is then maintained. Unless otherwise indicated, values of pressure stated herein are gage pressures.

The term “scaffold” as used herein refers to a substance or structure used to enhance or promote the growth of cells and/or the formation of tissue. A scaffold is typically a three dimensional porous structure that provides a template for cell growth. The scaffold may be infused with, coated with, or comprised of cells, growth factors, or other nutrients to promote cell growth. A scaffold may be used as a manifold in accordance with the embodiments described herein to administer reduced pressure tissue treatment to a tissue site.

The term “tissue site” as used herein refers to a wound or defect located on or within any tissue, including but not limited to, bone tissue, adipose tissue, muscle tissue, neural tissue, dermal tissue, vascular tissue, connective tissue, cartilage, tendons, or ligaments. The term “tissue site” may further refer to areas of any tissue that are not necessarily wounded or defective, but are instead areas in which it is desired to add or promote the growth of additional tissue. For example, reduced pressure tissue treatment may be used in certain tissue areas to grow additional tissue that may be harvested and transplanted to another tissue location.

Referring to FIGS. 1-5, a reduced pressure delivery apparatus, or wing manifold 211 according to the principles of the present invention includes a flexible barrier 213 having a spine portion 215 and a pair of wing portions 219. Each wing portion 219 is positioned along opposite sides of the spine portion 215. The spine portion 215 forms an arcuate channel 223 that may or may not extend the entire length of the wing manifold 211. Although the spine portion 215 may be centrally located on the wing manifold 211 such that the width of the wing portions 219 is equal, the spine portion 215 may also be offset as illustrated in FIGS. 1-5, resulting in one of the wing portions 219 being wider than the other wing portion

219. The extra width of one of the wing portions **219** may be particularly useful if the wing manifold **211** is being used in connection with bone regeneration or healing and the wider wing manifold **211** is to be wrapped around fixation hardware attached to the bone.

The flexible barrier **213** is preferably formed by an elastomeric material such as a silicone polymer. An example of a suitable silicone polymer includes MED-6015 manufactured by Nusil Technologies of Carpinteria, Calif. It should be noted, however, that the flexible barrier **213** could be made from any other biocompatible, flexible material. The flexible barrier **213** encases a flexible backing **227** that adds strength and durability to the flexible barrier **213**. The thickness of the flexible barrier **213** encasing the flexible backing **227** may be less in the arcuate channel **223** than that in the wing portions **219**. If a silicone polymer is used to form the flexible barrier **213**, a silicone adhesive may also be used to aid bonding with the flexible backing **227**. An example of a silicone adhesive could include MED-1011, also sold by Nusil Technologies. The flexible backing **227** is preferably made from a polyester knit fabric such as Bard 6013 manufactured by C.R. Bard of Tempe, Ariz. However, the flexible backing **227** could be made from any biocompatible, flexible material that is capable of adding strength and durability to the flexible barrier **213**. Under certain circumstances, if the flexible barrier **213** is made from a suitably strong material, the flexible backing **227** could be omitted.

It is preferred that either the flexible barrier **213** or the flexible backing **227** be impermeable to liquids, air, and other gases, or alternatively, both the flexible backing **227** and the flexible barrier **213** may be impermeable to liquids, air, and other gases.

The flexible barrier **213** and flexible backing **227** may also be constructed from bioresorbable materials that do not have to be removed from a patient's body following use of the reduced pressure delivery apparatus **211**. Suitable bioresorbable materials may include, without limitation, a polymeric blend of polylactic acid (PLA) and polyglycolic acid (PGA). The polymeric blend may also include without limitation polycarbonates, polyfumarates, and caprolactones. The flexible barrier **213** and the flexible backing **227** may further serve as a scaffold for new cell-growth, or a scaffold material may be used in conjunction with the flexible barrier **213** and flexible backing **227** to promote cell-growth. Suitable scaffold material may include, without limitation, calcium phosphate, collagen, PLA/PGA, coral hydroxy apatites, carbonates, or processed allograft materials. Preferably, the scaffold material will have a high void-fraction (i.e. a high content of air).

In one embodiment the flexible backing **227** may be adhesively attached to a surface of the flexible barrier **213**. If a silicone polymer is used to form the flexible barrier **213**, a silicone adhesive may also be used to attach the flexible backing **227** to the flexible barrier **213**. While an adhesive is the preferred method of attachment when the flexible backing **227** is surface bonded to the flexible barrier **213**, any suitable attachment may be used.

The flexible barrier **213** includes a plurality of projections **231** extending from the wing portions **219** on a surface of the flexible barrier **213**. The projections **231** may be cylindrical, spherical, hemispherical, cubed, or any other shape, as long as at least some portion of each projection **231** is in a plane different than the plane associated with the side of the flexible backing **213** to which the projections **231** are attached. In this regard, a particular projection **231** is not even required to have the same shape or size as other projections **231**; in fact, the projections **231** may include a random mix of different shapes

and sizes. Consequently, the distance by which each projection **231** extends from the flexible barrier **213** could vary, but may also be uniform among the plurality of projections **231**.

The placement of projections **231** on the flexible barrier **213** creates a plurality of flow channels **233** between the projections. When the projections **231** are of uniform shape and size and are spaced uniformly on the flexible barrier **213**, the flow channels **233** created between the projections **231** are similarly uniform. Variations in the size, shape, and spacing of the projections **231** may be used to alter the size and flow characteristics of the flow channels **233**.

A reduced-pressure delivery tube **241** is positioned within the arcuate channel **223** and is attached to the flexible barrier **213** as illustrated in FIG. 5. The reduced-pressure delivery tube **241** may be attached solely to the flexible barrier **213** or the flexible backing **227**, or the tube **241** could be attached to both the flexible barrier **213** and the flexible backing **227**. The reduced-pressure delivery tube **241** includes a distal orifice **243** at a distal end of the tube **241**. The tube **241** may be positioned such that the distal orifice **243** is located at any point along the arcuate channel **223**, but the tube **241** is preferably positioned such that the distal orifice **243** is located approximately midway along the longitudinal length of the arcuate channel **223**. The distal orifice **243** is preferably made elliptical or oval in shape by cutting the tube **241** along a plane that is oriented less than ninety (90) degrees to the longitudinal axis of the tube **241**. While the orifice **243** may also be round, the elliptical shape of the orifice **243** increases fluid communication with the flow channels **233** formed between the projections **231**.

The reduced-pressure delivery tube **241** is preferably made from paralyne-coated silicone or urethane. However, any medical-grade tubing material may be used to construct the reduced-pressure delivery tube **241**. Other coatings that may coat the tube include heparin, anti-coagulants, anti-fibrinogens, anti-adherents, anti-thrombinogens, and hydrophilic coatings.

In one embodiment, the reduced-pressure delivery tube **241** may also include vent openings, or vent orifices **251** positioned along the reduced-pressure delivery tube **241** as either an alternative to the distal orifice **243** or in addition to the distal orifice **243** to further increase fluid communication between the reduced-pressure delivery tube **241** and the flow channels **233**. The reduced-pressure delivery tube **241** may be positioned along only a portion of the longitudinal length of the arcuate channel **223** as shown in FIGS. 1-5, or alternatively may be positioned along the entire longitudinal length of the arcuate channel **223**. If positioned such that the reduced-pressure delivery tube **241** occupies the entire length of the arcuate channel **223**, the distal orifice **243** may be capped such that all fluid communication between the tube **241** and the flow channels **233** occurs through the vent openings **251**.

The reduced-pressure delivery tube **241** further includes a proximal orifice **255** at a proximal end of the tube **241**. The proximal orifice **255** is configured to mate with a reduced-pressure source, which is described in more detail below with reference to FIG. 9. The reduced-pressure delivery tube **241** illustrated in FIGS. 1-3, 4A, and 5 includes only a single lumen, or passageway **259**. It is possible, however, for the reduced-pressure delivery tube **241** to include multiple lumens such as a dual lumen tube **261** illustrated in FIG. 4B. The dual lumen tube **261** includes a first lumen **263** and a second lumen **265**. The use of a dual lumen tube provides separate paths of fluid communication between the proximal end of the reduced-pressure delivery tube **241** and the flow channels **233**. For example, the use of the dual lumen tube **261**

may be used to allow communication between the reduced pressure source and the flow channels 233 along the first lumen 263. The second lumen 265 may be used to introduce a fluid to the flow channels 233. The fluid may be filtered air or other gases, antibacterial agents, antiviral agents, cell-growth promotion agents, irrigation fluids, chemically active fluids, or any other fluid. If it is desired to introduce multiple fluids to the flow channels 233 through separate fluid communication paths, a reduced-pressure delivery tube may be provided with more than two lumens.

Referring still to FIG. 4B, a horizontal divider 271 separates the first and second lumens 263, 265 of the reduced-pressure delivery tube 261, resulting in the first lumen 263 being positioned above the second lumen 265. The relative position of the first and second lumens 263, 265 may vary, depending on how fluid communication is provided between the lumens 263, 265 and the flow channels 233. For example, when the first lumen 263 is positioned as illustrated in FIG. 4B, vent openings similar to vent openings 251 may be provided to allow communication with the flow channels 233. When the second lumen 263 is positioned as illustrated in FIG. 4B, the second lumen 263 may communicate with the flow channels 233 through a distal orifice similar to distal orifice 243. Alternatively, the multiple lumens of a reduced-pressure delivery tube could be positioned side by side with a vertical divider separating the lumens, or the lumens could be arranged concentrically or coaxially.

It should be apparent to a person having ordinary skill in the art that the provision of independent paths of fluid communication could be accomplished in a number of different ways, including that of providing a multi-lumen tube as described above. Alternatively, independent paths of fluid communication may be provided by attaching a single lumen tube to another single lumen tube, or by using separate, unattached tubes with single or multiple lumens.

If separate tubes are used to provide separate paths of fluid communication to the flow channels 233, the spine portion 215 may include multiple arcuate channels 223, one for each tube. Alternatively the arcuate channel 223 may be enlarged to accommodate multiple tubes. An example of a reduced-pressure delivery apparatus having a reduced-pressure delivery tube separate from a fluid delivery tube is discussed in more detail below with reference to FIG. 9.

Referring to FIGS. 6-8, a reduced pressure delivery apparatus, or wing manifold 311 according to the principles of the present invention includes a flexible barrier 313 having a spine portion 315 and a pair of wing portions 319. Each wing portion 319 is positioned along opposite sides of the spine portion 315. The spine portion 315 forms an arcuate channel 323 that may or may not extend the entire length of the wing manifold 311. Although the spine portion 315 may be centrally located on the wing manifold 311 such that the size of the wing portions 319 is equal, the spine portion 315 may also be offset as illustrated in FIGS. 6-8, resulting in one of the wing portions 319 being wider than the other wing portion 319. The extra width of one of the wing portions 319 may be particularly useful if the wing manifold 311 is being used in connection with bone regeneration or healing and the wider wing manifold 311 is to be wrapped around fixation hardware attached to the bone.

A cellular material 327 is attached to the flexible barrier 313 and may be provided as a single piece of material that covers the entire surface of the flexible barrier 313, extending across the spine portion 315 and both wing portions 319. The cellular material 327 includes an attachment surface (not visible in FIG. 6) that is disposed adjacent to the flexible

barrier 313, a main distribution surface 329 opposite the attachment surface, and a plurality of perimeter surfaces 330.

In one embodiment the flexible barrier 313 may be similar to flexible barrier 213 and include a flexible backing. While an adhesive is a preferred method of attaching the cellular material 327 to the flexible barrier 313, the flexible barrier 313 and cellular material 327 could be attached by any other suitable attachment method or left for the user to assemble at the site of treatment. The flexible barrier 313 and/or flexible backing serve as an impermeable barrier to transmission of fluids such as liquids, air, and other gases.

In one embodiment, a flexible barrier and flexible backing may not be separately provided to back the cellular material 327. Rather, the cellular material 327 may have an integral barrier layer that is an impermeable portion of the cellular material 327. The barrier layer could be formed from closed-cell material to prevent transmission of fluids, thereby substituting for the flexible barrier 313. If an integral barrier layer is used with the cellular material 327, the barrier layer may include a spine portion and wing portions as described previously with reference to the flexible barrier 313.

The flexible barrier 313 is preferably made from an elastomeric material such as a silicone polymer. An example of a suitable silicone polymer includes MED-6015 manufactured by Nusil Technologies of Carpinteria, Calif. It should be noted, however, that the flexible barrier 313 could be made from any other biocompatible, flexible material. If the flexible barrier encases or otherwise incorporates a flexible backing, the flexible backing is preferably made from a polyester knit fabric such as Bard 6013 manufactured by C.R. Bard of Tempe, Ariz. However, the flexible backing 227 could be made from any biocompatible, flexible material that is capable of adding strength and durability to the flexible barrier 313.

In one embodiment, the cellular material 327 is an open-cell, reticulated polyetherurethane foam with pore sizes ranging from about 400-600 microns. An example of this foam may include GranuFoam manufactured by Kinetic Concepts, Inc. of San Antonio, Tex. The cellular material 327 may also be gauze, felted mats, or any other biocompatible material that provides fluid communication through a plurality of channels in three dimensions.

The cellular material 327 is primarily an "open cell" material that includes a plurality of cells fluidly connected to adjacent cells. A plurality of flow channels is formed by and between the "open cells" of the cellular material 327. The flow channels allow fluid communication throughout that portion of the cellular material 327 having open cells. The cells and flow channels may be uniform in shape and size, or may include patterned or random variations in shape and size. Variations in shape and size of the cells of the cellular material 327 result in variations in the flow channels, and such characteristics can be used to alter the flow characteristics of fluid through the cellular material 327. The cellular material 327 may further include portions that include "closed cells." These closed-cell portions of the cellular material 327 contain a plurality of cells, the majority of which are not fluidly connected to adjacent cells. An example of a closed-cell portion is described above as a barrier layer that may be substituted for the flexible barrier 313. Similarly, closed-cell portions could be selectively disposed in the cellular material 327 to prevent transmission of fluids through the perimeter surfaces 330 of the cellular material 327.

The flexible barrier 313 and cellular material 327 may also be constructed from bioresorbable materials that do not have to be removed from a patient's body following use of the reduced pressure delivery apparatus 311. Suitable bioresorb-

11

able materials may include, without limitation, a polymeric blend of polylactic acid (PLA) and polyglycolic acid (PGA). The polymeric blend may also include without limitation polycarbonates, polyfumarates, and caprolactones. The flexible barrier 313 and the cellular material 327 may further serve as a scaffold for new cell-growth, or a scaffold material may be used in conjunction with the flexible barrier 313, flexible backing 327, and/or cellular material 327 to promote cell-growth. Suitable scaffold materials may include, without limitation, calcium phosphate, collagen, PLA/PGA, coral hydroxy apatites, carbonates, or processed allograft materials. Preferably, the scaffold material will have a high void-fraction (i.e. a high content of air).

A reduced-pressure delivery tube 341 is positioned within the arcuate channel 323 and is attached to the flexible barrier 313. The reduced-pressure delivery tube 341 may also be attached to the cellular material 327, or in the case of only a cellular material 327 being present, the reduced-pressure delivery tube 341 may be attached to only the cellular material 327. The reduced-pressure delivery tube 341 includes a distal orifice 343 at a distal end of the tube 341 similar to the distal orifice 243 of FIG. 5. The reduced-pressure delivery tube 341 may be positioned such that the distal orifice 343 is located at any point along the arcuate channel 323, but is preferably located approximately midway along the longitudinal length of the arcuate channel 323. The distal orifice 343 is preferably made elliptical or oval in shape by cutting the tube 341 along a plane that is oriented less than ninety (90) degrees to the longitudinal axis of the tube 341. While the orifice may also be round, the elliptical shape of the orifice increases fluid communication with the flow channels in the cellular material 327.

In one embodiment, the reduced-pressure delivery tube 341 may also include vent openings, or vent orifices (not shown) similar to vent openings 251 of FIG. 5. The vent openings are positioned along the tube 341 as either an alternative to the distal orifice 343 or in addition to the distal orifice 343 to further increase fluid communication between the reduced-pressure delivery tube 341 and the flow channels. As previously described, the reduced-pressure delivery tube 341 may be positioned along only a portion of the longitudinal length of the arcuate channel 323, or alternatively may be positioned along the entire longitudinal length of the arcuate channel 323. If positioned such that the reduced-pressure delivery tube 341 occupies the entire arcuate channel 323, the distal orifice 343 may be capped such that all fluid communication between the tube 341 and the flow channels occurs through the vent openings.

Preferably, the cellular material 327 overlays and directly contacts the reduced-pressure delivery tube 341. The cellular material 327 may be connected to the reduced-pressure delivery tube 341, or the cellular material 327 may simply be attached to the flexible barrier 313. If the reduced-pressure delivery tube 341 is positioned such that it only extends to a midpoint of the arcuate channel 323, the cellular material 327 may also be connected to the spine portion 315 of the flexible barrier 313 in that area of the arcuate channel 323 that does not contain the reduced-pressure delivery tube 341.

The reduced-pressure delivery tube 341 further includes a proximal orifice 355 at a proximal end of the tube 341. The proximal orifice 355 is configured to mate with a reduced-pressure source, which is described in more detail below with reference to FIG. 9. The reduced-pressure delivery tube 341 illustrated in FIGS. 6-8 includes only a single lumen, or passageway 359. It is possible, however, for the reduced-pressure delivery tube 341 to include multiple lumens such as those described previously with reference to FIG. 4B. The use

12

of a multiple lumen tube provides separate paths of fluid communication between the proximal end of the reduced-pressure delivery tube 341 and the flow channels as previously described. These separate paths of fluid communication may also be provided by separate tubes having single or multiple lumens that communicate with the flow channels.

Referring to FIGS. 8A and 8B, a reduced pressure delivery apparatus 371 according to the principles of the present invention includes a reduced pressure delivery tube 373 having an extension portion 375 at a distal end 377 of the reduced pressure delivery tube 373. The extension portion 375 is preferably arcuately shaped to match the curvature of the reduced pressure delivery tube 373. The extension portion 375 may be formed by removing a portion of the reduced pressure delivery tube 373 at the distal end 377, thereby forming a cut-out 381 having a shoulder 383. A plurality of projections 385 is disposed on an inner surface 387 of the reduced pressure delivery tube 373 to form a plurality of flow channels 391 between the projections 385. The projections 385 may be similar in size, shape, and spacing as the projections described with reference to FIGS. 1-5. The reduced pressure delivery apparatus 371 is particularly suited for applying reduced pressure to and regenerating tissue on connective tissues that are capable of being received within the cut-out 381. Ligaments, tendons, and cartilage are non-limiting examples of the tissues that may be treated by reduced pressure delivery apparatus 371.

Referring to FIG. 9, a reduced pressure delivery apparatus 411 similar to the other reduced pressure delivery apparatuses described herein is used to apply a reduced pressure tissue treatment to a tissue site 413, such as a human bone 415 of a patient. When used to promote bone tissue growth, reduced pressure tissue treatment can increase the rate of healing associated with a fracture, a non-union, a void, or other bone defects. It is further believed that reduced pressure tissue treatment may be used to improve recovery from osteomyelitis. The therapy may further be used to increase localized bone densities in patients suffering from osteoporosis. Finally, reduced pressure tissue treatment may be used to speed and improve osseointegration of orthopedic implants such as hip implants, knee implants, and fixation devices.

Referring still to FIG. 9, the reduced pressure delivery apparatus 411 includes a reduced-pressure delivery tube 419 having a proximal end 421 fluidly connected to a reduced pressure source 427. The reduced pressure source 427 is a pump or any other device that is capable of applying a reduced pressure to the tissue site 413 through the reduced pressure delivery tube 419 and a plurality of flow channels associated with the reduced pressure delivery apparatus 411. Applying reduced pressure to the tissue site 413 is accomplished by placing the wing portions of the reduced pressure delivery apparatus 411 adjacent the tissue site 413, which in this particular example involves wrapping the wing portions around a void defect 429 in the bone 415. The reduced pressure delivery apparatus 411 may be surgically or percutaneously inserted. When percutaneously inserted, the reduced-pressure delivery tube 419 is preferably inserted through a sterile insertion sheath that penetrates the skin tissue of the patient.

The application of reduced pressure tissue treatment typically generates granulation tissue in the area surrounding the tissue site 413. Granulation tissue is a common tissue that often forms prior to tissue repair in the body. Under normal circumstances, granulation tissue may form in response to a foreign body or during wound healing. Granulation tissue typically serves as a scaffold for healthy replacement tissue and further results in the development of some scar tissue.

13

Granulation tissue is highly vascularized, and the increased growth and growth rate of the highly vascularized tissue in the presence of reduced pressure promotes new tissue growth at the tissue site **413**.

Referring still to FIG. 9, a fluid delivery tube **431** may be fluidly connected at a distal end to the flow channels of the reduced pressure delivery apparatus **411**. The fluid delivery tube **431** includes a proximal end **432** that is fluidly connected to a fluid delivery source **433**. If the fluid being delivered to the tissue site is air, the air is preferably filtered by a filter **434** capable of filtering particles at least as small as 0.22 μm in order to clean and sterilize the air. The introduction of air to the tissue site **413**, especially when the tissue site **413** is located beneath the surface of the skin, is important to facilitate good drainage of the tissue site **413**, thereby reducing or preventing obstruction of the reduced pressure delivery tube **419**. The fluid delivery tube **431** and fluid delivery source **433** could also be used to introduce other fluids to the tissue site **413**, including without limitation an antibacterial agent, an antiviral agent, a cell-growth promotion agent, an irrigation fluid, or other chemically active agents. When percutaneously inserted, the fluid delivery tube **431** is preferably inserted through a sterile insertion sheath that penetrates the skin tissue of the patient.

14

described previously with reference to FIG. 4B. A person of ordinary skill in the art will recognize that the sensors, valves, and other components associated with the fluid delivery tube **431** could also be similarly associated with a particular lumen in the reduced pressure delivery tube **419** if a multi-lumen tube is used. It is preferred that any lumen or tube that fluidly communicates with the tissue site be coated with an anti-coagulant to prevent a build-up of bodily fluids or blood within the lumen or tube. Other coatings that may coat the lumens or tubes include without limitation heparin, anti-coagulants, anti-fibrinogens, anti-adherents, anti-thrombinogens, and hydrophilic coatings.

Referring to FIGS. 10-19, testing has shown the positive effects of reduced pressure tissue treatment when applied to bone tissue. In one particular test, reduced pressure tissue treatment was applied to the cranium of several rabbits to determine its effect on bone growth and regeneration. The specific goals of the test were to discover the effect of reduced pressure tissue treatment on rabbits having no defect on or injury to the cranium, the effect of reduced pressure tissue treatment on rabbits having critical-size defects on the cranium, and the effect of using a scaffold material with reduced pressure tissue treatment to treat critical-size defects on the cranium. The specific testing protocol and number of rabbits are listed below in Table 1.

TABLE 1

Testing Protocol	
No. of Rabbits	Protocol
4	No defect on cranium; reduced pressure tissue treatment (RPTT) applied through cellular foam (GranuFoam) on top of intact periosteum for 6 days followed by immediate tissue harvest
4	No defect on cranium; cellular foam (GranuFoam) placed on top of intact periosteum without RPTT (control) for 6 days followed by immediate tissue harvest
4	One critical-size defect with stainless-steel screen placed on defect; one critical-size defect with calcium phosphate scaffold placed in defect; 24 hours RPTT applied to both defects; tissue harvest 2 weeks post-surgery
4	One critical-size defect with stainless-steel screen placed on defect; one critical-size defect with calcium phosphate scaffold placed in defect; 24 hours RPTT applied to both defects; tissue harvest 12 weeks post-surgery
4	One critical-size defect with stainless-steel screen placed on defect; one critical-size defect with calcium phosphate scaffold placed in defect; 6 days RPTT applied to both defects; tissue harvest 2 weeks post-surgery
4	One critical-size defect with stainless-steel screen placed on defect; one critical-size defect with calcium phosphate scaffold placed in defect; 6 days RPTT applied to both defects; tissue harvest 12 weeks post-surgery
4	One critical-size defect with stainless-steel screen placed on defect; one critical-size defect with calcium phosphate scaffold placed in defect; no RPTT applied (control); tissue harvest 2 weeks post-surgery
4	One critical-size defect with stainless-steel screen placed on defect; one critical-size defect with calcium phosphate scaffold placed in defect; no RPTT applied (control); tissue harvest 12 weeks post-surgery
4	Native control (no surgery; no RPTT)
4	Sham surgery (no defects, no RPTT); tissue harvest 6 days post-surgery

A pressure sensor **435** may be operably connected to the fluid delivery tube **431** to indicate whether the fluid delivery tube **431** is occluded with blood or other bodily fluids. The pressure sensor **435** may be operably connected to the fluid delivery source **433** to provide feedback so that the amount of fluid introduced to the tissue site **413** is controlled. A check valve (not shown) may also be operably connected near the distal end of the fluid delivery tube **431** to prevent blood or other bodily fluids from entering the fluid delivery tube **431**.

The independent paths of fluid communication provided by reduced pressure delivery tube **419** and fluid delivery tube **431** may be accomplished in a number of different ways, including that of providing a single, multi-lumen tube as

Critical-size defects are defects in a tissue (e.g. the cranium), the size of which is large enough that the defect will not heal solely by in-life recovery. For rabbits, boring a full-thickness hole through the cranium that is approximately 15 mm in diameter creates a critical-size defect of the cranium.

Referring more specifically to FIG. 10, a histological section of a rabbit cranium having naïve, undamaged bone is illustrated. The bone tissue of the cranium is colored magenta, the surrounding soft tissue white, and the layer of periosteum is highlighted by yellow asterisks. In FIG. 11, the rabbit cranium is illustrated following the application of reduced pressure tissue treatment for 6 days followed by immediate tissue harvest. The bone and periosteum are visible, and a

15

layer of granulation tissue has developed. In FIG. 12, the rabbit cranium is illustrated following the application of reduced pressure tissue treatment for 6 days and followed by immediate tissue harvest. The histological section of FIG. 12 is characterized by the development of new bone tissue underlying the granulation tissue. The bone tissue is highlighted by yellow asterisks. In FIG. 13, the rabbit cranium is illustrated following the application of reduced pressure tissue treatment for 6 days followed by immediate tissue harvest. The new bone and periosteum are visible. This histological appearance of bone tissue development in response to reduced pressure tissue treatment is very similar to the histological appearance of bone development in a very young animal that is undergoing very rapid growth and deposition of new bone.

Referring more specifically to FIGS. 14-19, several photographs and histological sections are illustrated showing the procedures and results of reduced pressure tissue treatment on a rabbit cranium having critical-size defects. In FIG. 14, a rabbit cranium is illustrated on which two critical-size defects have been created. The full-thickness critical-size defects are approximately 15 mm in diameter. In FIG. 15, a stainless-steel screen has been placed over one of the critical-size defects, and a calcium phosphate scaffold has been placed within the second critical-size defect. In FIG. 16, a reduced pressure tissue treatment apparatus similar to those described herein is used to apply reduced pressure to the critical-size defects. The amount of pressure applied to each defect was -125 mm Hg gauge pressure. The reduced pressure was applied according to one of the protocols listed in Table 1. In FIG. 17, a histological section of cranium following six-day reduced pressure tissue treatment and twelve week post-surgery harvest is illustrated. The section illustrated includes calcium phosphate scaffold, which is indicated by red arrows. The application of reduced pressure tissue treatment resulted in the significant growth of new bone tissue, which is highlighted in FIG. 17 by yellow asterisks. The amount of bone growth is significantly greater than in critical-size defects containing identical calcium phosphate scaffolds but which were not treated with reduced pressure tissue treatment. This observation suggests there may be a threshold level or duration of therapy required to elicit a prolific new-bone response. Effects of reduced pressure tissue treatment are most pronounced in the specimens collected 12 weeks post-surgery, indicating the reduced pressure tissue treatment initiates a cascade of biological events leading to enhanced formation of new bone tissue.

Critical-size defects covered with stainless steel screens (FIG. 15) but without scaffold material in the defect served as intra-animal controls with minimal new-bone growth. These data highlight the advantage of an appropriate scaffold material and the positive effect of reduced pressure tissue treatment on scaffold integration and biological performance. In FIGS. 18 and 19, radiographs of scaffold-filled, critical-size defects are illustrated following six days of reduced pressure tissue treatment. FIG. 18 illustrates the defect two weeks post-surgery and indicates some new bone deposition within the scaffold. The primary structure of the scaffold is still evident. FIG. 19 illustrates the defect twelve weeks post surgery and shows almost complete healing of the critical-size defect and a near complete loss of the primary scaffold architecture due to tissue integration, i.e. new bone formation within the scaffold matrix.

Referring to FIG. 20, a reduced pressure delivery system 711 according to an embodiment of the present invention delivers reduced pressure tissue treatment to a tissue site 713 of a patient. The reduced pressure delivery system 711 includes a manifold delivery tube 721. The manifold delivery

16

tube 721 may be a catheter or cannula and may include features such as a steering unit 725 and a guide wire 727 that allow the manifold delivery tube 721 to be guided to the tissue site 713. Placement and direction of the guide wire 727 and the manifold delivery tube 721 may be accomplished by using endoscopy, ultrasound, fluoroscopy, auscultation, palpation, or any other suitable localization technique. The manifold delivery tube 721 is provided to percutaneously insert a reduced pressure delivery apparatus to the tissue site 713 of the patient. When percutaneously inserted, the manifold delivery tube 721 is preferably inserted through a sterile insertion sheath that penetrates the skin tissue of the patient.

In FIG. 20, the tissue site 713 includes bone tissue adjacent a fracture 731 on a bone 733 of the patient. The manifold delivery tube 721 is inserted through the patient's skin 735 and any soft tissue 739 surrounding the bone 733. As previously discussed, the tissue site 713 may also include any other type of tissue, including without limitation adipose tissue, muscle tissue, neural tissue, dermal tissue, vascular tissue, connective tissue, cartilage, tendons, or ligaments.

Referring to FIGS. 21 and 22, the reduced pressure delivery system 711 is further illustrated. The manifold delivery tube 721 may include a tapered distal end 743 to ease insertion through the patient's skin 735 and soft tissue 739. The tapered distal end 743 may further be configured to flex radially outward to an open position such that the inner diameter of the distal end 743 would be substantially the same as or greater than the inner diameter at other portions of the tube 721. The open position of the distal end 743 is schematically illustrated in FIG. 21 by broken lines 737.

The manifold delivery tube 721 further includes a passageway 751 in which a reduced pressure delivery apparatus 761, or any other reduced pressure delivery apparatus, is contained. The reduced pressure delivery apparatus 761 includes a flexible barrier 765 and/or cellular material 767 similar to that described with reference to FIGS. 6-8. The flexible barrier 765 and/or cellular material 767 is preferably rolled, folded, or otherwise compressed around a reduced pressure delivery tube 769 to reduce the cross-sectional area of the reduced pressure delivery apparatus 761 within the passageway 751.

The reduced pressure delivery apparatus 761 may be placed within the passageway 751 and guided to the tissue site 713 following the placement of the distal end 743 manifold delivery tube 721 at the tissue site 713. Alternatively, the reduced pressure delivery apparatus 761 may be pre-positioned within the passageway 751 prior to the manifold delivery tube 721 being inserted into the patient. If the reduced pressure delivery apparatus 761 is to be pushed through the passageway 751, a biocompatible lubricant may be used to reduce friction between the reduced pressure delivery apparatus 761 and the manifold delivery tube 721. When the distal end 743 has been positioned at the tissue site 713 and the reduced pressure delivery apparatus 761 has been delivered to the distal end 743, the reduced pressure delivery apparatus 761 is then pushed toward the distal end 743, causing the distal end 743 to expand radially outward into the open position. The reduced pressure delivery apparatus 761 is pushed out of the manifold delivery tube 721, preferably into a void or space adjacent the tissue site 713. The void or space is typically formed by dissection of soft tissue, which may be accomplished by percutaneous means. In some cases, the tissue site 713 may be located at a wound site, and a void may be naturally present due to the anatomy of the wound. In other instances, the void may be created by balloon dissection, sharp dissection, blunt dissection, hydrodissection, pneumatic dissection, ultrasonic dissection, electrocautery dissec-

17

tion, laser dissection, or any other suitable dissection technique. When the reduced pressure delivery apparatus **761** enters the void adjacent the tissue site **713**, the flexible barrier **765** and/or cellular material **767** of the reduced pressure delivery apparatus **761** either unrolls, unfolds, or decompresses (see FIG. 22) such that the reduced pressure delivery apparatus **761** can be placed in contact with the tissue site **713**. Although not required, the flexible barrier **765** and/or cellular material **767** may be subjected to a vacuum or reduced pressure supplied through the reduced pressure delivery tube **769** to compress the flexible barrier **765** and/or cellular material **767**. The unfolding of the flexible barrier **765** and/or cellular material **767** may be accomplished by either relaxing the reduced pressure supplied through the reduced pressure delivery tube **769** or by supplying a positive pressure through the reduced pressure delivery tube **769** to assist the unrolling process. Final placement and manipulation of the reduced pressure delivery apparatus **761** may be accomplished by using endoscopy, ultrasound, fluoroscopy, auscultation, palpation, or any other suitable localization technique. Following placement of the reduced pressure delivery apparatus **761**, the manifold delivery tube **721** is preferably removed from the patient, but the reduced pressure delivery tube associated with reduced pressure delivery apparatus **761** remains in situ to allow percutaneous application of reduced pressure to the tissue site **713**.

Referring to FIGS. 23-25, a reduced pressure delivery system **811** according to an embodiment of the present invention includes a manifold delivery tube **821** having a tapered distal end **843** that is configured to flex radially outward to an open position such that the inner diameter of the distal end **843** would be substantially the same as or greater than the inner diameter at other portions of the tube **821**. The open position of the distal end **843** is schematically illustrated in FIGS. 23-25 by broken lines **837**.

The manifold delivery tube **821** further includes a passageway in which a reduced pressure delivery apparatus **861** similar to the other reduced pressure delivery apparatuses described herein is contained. The reduced pressure delivery apparatus **861** includes a flexible barrier **865** and/or a cellular material **867** that is preferably rolled, folded, or otherwise compressed around a reduced pressure delivery tube **869** to reduce the cross-sectional area of the reduced pressure delivery apparatus **861** within the passageway.

An impermeable membrane **871** having an inner space **873** is disposed around the reduced pressure delivery apparatus **861** such that the reduced pressure delivery apparatus **861** is contained within the inner space **873** of the impermeable membrane **871**. The impermeable membrane **871** may be a balloon, a sheath, or any other type of membrane that is capable of preventing fluid transmission such that the impermeable membrane **871** can assume at least one of a compressed position (see FIG. 23), a relaxed position (see FIG. 24), and an expanded position (see FIGS. 25 and 25A). The impermeable membrane **871** may be sealingly connected to the manifold delivery tube **821** such that the inner space **873** of the impermeable membrane **871** is in fluid communication with the passageway of the manifold delivery tube **821**. The impermeable membrane **871** may alternatively be attached to the reduced pressure delivery tube **869** such that the inner space **873** of the impermeable membrane **871** is in fluid communication with the passageway of the reduced pressure delivery tube **869**. The impermeable membrane **871** instead may be attached to a separate control tube or control lumen (see for example FIG. 25A) that fluidly communicates with the inner space **873**.

18

In one embodiment, the impermeable membrane **871** may be provided to further reduce the cross-sectional area of the reduced pressure delivery apparatus **861** within the passageway. To accomplish this, a pressure is applied to the inner space **873** of the impermeable membrane **871** that is less than the ambient pressure surrounding the impermeable membrane **871**. A significant portion of the air or other fluid within the inner space **873** is thereby evacuated, placing the impermeable membrane **871** in the compressed position illustrated in FIG. 23. In the compressed position, the impermeable membrane **871** is drawn inward such that a compressive force is applied to the reduced pressure delivery apparatus **861** to further reduce the cross-sectional area of the reduced pressure delivery apparatus **861**. As previously described with reference to FIGS. 21 and 22, the reduced pressure delivery apparatus **861** may be delivered to the tissue site following the placement of the distal end **843** of the manifold delivery tube **821** at the tissue site. Placement and manipulation of the impermeable membrane **871** and the reduced pressure delivery apparatus **861** may be accomplished by using endoscopy, ultrasound, fluoroscopy, auscultation, palpation, or any other suitable localization technique. The impermeable membrane **871** may include radio-opaque markers **881** that improve visualization of the impermeable membrane **871** under fluoroscopy prior to its removal.

After pushing the reduced pressure delivery apparatus **861** through the distal end **843**, the reduced pressure applied to the inner space **873** may be eased to place the impermeable membrane **871** in the relaxed position (see FIG. 24), thereby facilitating easier removal of the reduced pressure delivery apparatus **861** from the impermeable membrane **871**. A removal instrument **885** such as a trocar, stylet, or other sharp instrument may be provided to rupture the impermeable membrane **871**. Preferably, the removal instrument **885** is inserted through the reduced pressure delivery tube **869** and is capable of being advanced into contact with the impermeable membrane **871**. After rupture of the impermeable membrane **871**, the removal instrument **885** and the impermeable membrane **871** may be withdrawn through the manifold delivery tube **821**, allowing the flexible barrier **865** and/or cellular material **867** of the reduced pressure delivery apparatus **861** to unroll, unfold, or decompress such that the reduced pressure delivery apparatus **861** can be placed in contact with the tissue site. The unrolling of the flexible barrier **865** and/or cellular material **867** may occur automatically following the relaxation of reduced pressure to the inner space **873** and the removal of the impermeable membrane **871**. In some cases, a positive pressure may be delivered through the reduced pressure delivery tube **869** to assist in unrolling or decompressing the flexible barrier **865** and/or cellular material **867**. Following final placement of the reduced pressure delivery apparatus **861**, the manifold delivery tube **821** is preferably removed from the patient, but the reduced pressure delivery tube **869** associated with the reduced pressure delivery apparatus **861** remains in situ to allow percutaneous application of reduced pressure to the tissue site.

The impermeable membrane **871** may also be used to dissect tissue adjacent the tissue site prior to placing the reduced pressure delivery apparatus **861** against the tissue site. After pushing the reduced pressure delivery apparatus **861** and intact impermeable membrane **871** through the distal end **843** of the manifold delivery tube **821**, air or another fluid may be injected or pumped into the inner space **873** of the impermeable membrane **871**. A liquid is preferably used to inflate the impermeable membrane **871** since the incompressibility of liquids allow the impermeable membrane **871** to expand more evenly and consistently. The impermeable membrane **871**

may expand radially as illustrated in FIG. 25 or directionally depending on its method of manufacture and attachment to the manifold delivery tube 821. As the impermeable membrane 871 expands outward into the expanded position (see FIG. 25) due to the pressure of the air or fluid, a void is dissected adjacent the tissue site. When the void is large enough, the liquid, air or other fluid may be released from the inner space 873 to allow the impermeable membrane 871 to assume the relaxed position. The impermeable membrane 871 may then be ruptured as previously explained and the reduced pressure delivery apparatus 861 inserted adjacent the tissue site.

Referring to FIG. 25A, if the impermeable membrane 871 is used primarily to dissect tissue adjacent the tissue site, the impermeable membrane 871 may be sealingly attached to the manifold delivery tube 821 such that the inner space 873 fluidly communicates with a secondary lumen or tube 891 associated with or attached to the manifold delivery tube 821. The secondary lumen 891 may be used to deliver a liquid, air, or other fluid to the inner space 873 to place the impermeable membrane 871 in the expanded position. Following dissection, the impermeable membrane 871 may be relaxed and ruptured as previously described with reference to FIG. 24.

Referring to FIG. 26, a reduced pressure delivery system 911 according to an embodiment of the present invention includes a manifold delivery tube 921 having a tapered distal end 943 that is configured to flex radially outward to an open position such that the inner diameter of the distal end 943 would be substantially the same as or greater than the inner diameter at other portions of the tube 921. The open position of the distal end 943 is schematically illustrated in FIG. 26 by broken lines 937.

The manifold delivery tube 921 further includes a passageway in which a reduced pressure delivery apparatus 961 similar to the other reduced pressure delivery apparatuses described herein is contained. The reduced pressure delivery apparatus 961 includes a flexible barrier 965 and/or a cellular material 967 that is preferably rolled, folded, or otherwise compressed around a reduced pressure delivery tube 969 to reduce the cross-sectional area of the reduced pressure delivery apparatus 961 within the passageway of the manifold delivery tube 921.

An impermeable membrane 971 having an inner space 973 is disposed around the reduced pressure delivery apparatus 961 such that the reduced pressure delivery apparatus 961 is contained within the inner space 973 of the impermeable membrane 971. The impermeable membrane 971 includes a glue seal 977 on one end of the impermeable membrane 971 to provide an alternative method of removing the reduced pressure delivery apparatus 961 from the impermeable membrane 971. The impermeable membrane 971 may be sealingly connected at another end to the manifold delivery tube 921 such that the inner space 973 of the impermeable membrane 971 is in fluid communication with the passageway of the manifold delivery tube 921. Alternatively, the impermeable membrane 971 may be attached to a separate control tube (not shown) that fluidly communicates with the inner space 973.

Similar to the impermeable membrane 871 of FIG. 23, impermeable membrane 971 may be capable of preventing fluid transmission such that the impermeable membrane 971 can assume at least one of a compressed position, a relaxed position, and an expanded position. Since the procedures for placing the impermeable membrane 971 in a compressed position and an expanded position are similar to those for impermeable membrane 871, only the differing process of removing the reduced pressure delivery apparatus 961 is described.

The reduced pressure delivery apparatus 961 is delivered to the tissue site within the impermeable membrane 971 and then properly positioned using endoscopy, ultrasound, fluoroscopy, auscultation, palpation, or any other suitable localization technique. The impermeable membrane 971 may include radio-opaque markers 981 that improve visualization of the impermeable membrane 971 under fluoroscopy prior to its removal. The reduced pressure delivery apparatus 961 is then pushed through the distal end 943 of the manifold delivery tube 921. The reduced pressure applied to the inner space 973 may be eased to place the impermeable membrane 971 in the relaxed position. The reduced pressure delivery apparatus 961 is then pushed through the glue seal 977 to exit the impermeable membrane 971.

Referring to FIG. 26A, a reduced pressure delivery system 985 according to an embodiment of the present invention may not include a manifold delivery tube similar to manifold delivery tube 921 of FIG. 26. Instead, the reduced pressure delivery system 985 may include a guide wire 987, a reduced pressure delivery tube 989, and a reduced pressure delivery apparatus 991. The reduced pressure delivery apparatus 991 includes a plurality of flow channels that is fluidly connected to the reduced pressure delivery tube 989. Instead of using an independent manifold delivery tube to deliver the reduced pressure delivery apparatus 991, the reduced pressure delivery apparatus 991 and reduced pressure delivery tube 989 are placed on the guide wire 987, which is percutaneously guided to a tissue site 993. Preferably, the guide wire 987 and reduced pressure delivery tube 989 penetrate the skin of the patient through a sterile sheath. By guiding the reduced pressure delivery tube 989 and reduced pressure delivery apparatus 991 along the guide wire 987, the reduced pressure delivery apparatus 991 may be placed at the tissue site 993 to allow percutaneous application of reduced pressure tissue treatment.

Since the reduced pressure delivery apparatus 991 is not constrained within a manifold delivery tube during delivery to the tissue site 993, it is preferable to hold the reduced pressure delivery apparatus 991 in a compressed position during delivery. If an elastic foam is used as the reduced pressure delivery apparatus 991, a biocompatible, soluble adhesive may be applied to the foam and the foam compressed. Upon arrival at the tissue site, bodily fluids or other fluids delivered through the reduced pressure delivery tube 989 dissolve the adhesive, allowing the foam to expand into contact with the tissue site. Alternatively, the reduced pressure delivery apparatus 991 may be formed from a compressed, dry hydrogel. The hydrogel absorbs moisture following delivery to the tissue site 993 allowing expansion of the reduced pressure delivery apparatus 991. Still another reduced pressure delivery apparatus 991 may be made from a thermoactive material (e.g. polyethylene glycol) that expands at the tissue site 993 when exposed to the body heat of the patient. In still another embodiment, a compressed reduced pressure delivery apparatus 991 may be delivered to the tissue site 993 in a dissolvable membrane.

Referring to FIG. 27, a reduced pressure delivery system 1011 according to an embodiment of the present invention includes a manifold delivery tube 1021 having a distal end 1043 that is inserted through a tissue of a patient to access a tissue site 1025. The tissue site 1025 may include a void 1029 that is associated with a wound or other defect, or alternatively a void may be created by dissection, including the dissection techniques described herein.

Following placement of the distal end 1043 within the void 1029 adjacent the tissue site 1025, an injectable, pourable, or flowable reduced pressure delivery apparatus 1035 is delivered through the manifold delivery tube 1021 to the tissue site

1025. The reduced pressure delivery apparatus **1035** preferably exists in a flowable state during delivery to the tissue site, and then, after arrival forms a plurality of flow channels for distribution of reduced pressure or fluids. In some cases, the flowable material may harden into a solid state after arrival at the tissue site, either through a drying process, a curing process, or other chemical or physical reaction. In other cases, the flowable material may form a foam in-situ following delivery to the tissue site. Still other materials may exist in a gel-like state at the tissue site **1025** but still have a plurality of flow channels for delivering reduced pressure. The amount of reduced pressure delivery apparatus **1035** delivered to the tissue site **1025** may be enough to partially or completely fill the void **1029**. The reduced pressure delivery apparatus **1035** may include aspects of both a manifold and a scaffold. As a manifold, the reduced pressure delivery apparatus **1035** includes a plurality of pores or open cells that may be formed in the material after delivery to the void **1029**. The pores or open cells communicate with one another, thereby creating a plurality of flow channels. The flow channels are used to apply and distribute reduced pressure to the tissue site **1025**. As a scaffold, the reduced pressure delivery apparatus **1035** is bioresorbable and serves as a substrate upon and within which new tissue may grow.

In one embodiment, the reduced pressure delivery apparatus **1035** may include poragens such as NaCl or other salts that are distributed throughout a liquid or viscous gel. After the liquid or viscous gel is delivered to the tissue site **1025**, the material conforms to the void **1029** and then cures into a solid mass. The water-soluble NaCl poragens dissolve in the presence of bodily fluids leaving a structure with interconnected pores, or flow channels. Reduced pressure and/or fluid is delivered to the flow channels. As new tissue develops, the tissue grows into the pores of the reduced pressure delivery apparatus **1035**, and then ultimately replaces the reduced pressure delivery apparatus **1035** as it degrades. In this particular example, the reduced pressure delivery apparatus **1035** serves not only as a manifold, but also as a scaffold for new tissue growth.

In another embodiment, the reduced pressure delivery apparatus **1035** is an alginate mixed with 400 μ m mannose beads. The poragens or beads may be dissolved by local body fluids or by irrigational or other fluids delivered to the reduced pressure delivery apparatus **1035** at the tissue site. Following dissolution of the poragens or beads, the spaces previously occupied by the poragens or beads become voids that are interconnected with other voids to form the flow channels within the reduced pressure delivery apparatus **1035**.

The use of poragens to create flow channels in a material is effective, but it also forms pores and flow channels that are limited in size to approximately the particle size of the selected poragen. Instead of poragens, a chemical reaction may be used to create larger pores due to the formation of gaseous by-products. For example, in one embodiment, a flowable material may be delivered to the tissue site **1025** that contains sodium bicarbonate and citric acid particles (non-stoichiometric amounts may be used). As the flowable material forms a foam or solid in-situ, bodily fluids will initiate an acid-base reaction between the sodium bicarbonate and the citric acid. The resulting carbon dioxide gas particles that are produced create larger pore and flow channels throughout the reduced pressure delivery apparatus **1035** than techniques relying on poragen dissolution.

The transformation of the reduced pressure delivery apparatus **1035** from a liquid or viscous gel into a solid or a foam can be triggered by pH, temperature, light, or a reaction with bodily fluids, chemicals or other substances delivered to the

tissue site. The transformation may also occur by mixing multiple reactive components. In one embodiment, the reduced pressure delivery apparatus **1035** is prepared by selecting bioresorbable microspheres made from any bioresorbable polymer. The microspheres are dispersed in a solution containing a photoinitiator and a hydrogel-forming material such as hyaluronic acid, collagen, or polyethylene glycol with photoreactive groups. The microsphere-gel mixture is exposed to light for a brief period of time to partially crosslink the hydrogel and immobilize the hydrogel on the microspheres. The excess solution is drained, and the microspheres are then dried. The microspheres are delivered to the tissue site by injection or pouring, and following delivery, the mixture absorbs moisture, and the hydrogel coating becomes hydrated. The mixture is then again exposed to light, which crosslinks the microspheres, creating a plurality of flow channels. The crosslinked microspheres then serve as a manifold to deliver reduced pressure to the tissue site and as a porous scaffold to promote new tissue growth.

In addition to the preceding embodiments described herein, the reduced pressure delivery apparatus **1035** may be made from a variety of materials, including without limitation calcium phosphate, collagen, alginate, cellulose, or any other equivalent material that is capable of being delivered to the tissue site as a gas, liquid, gel, paste, putty, slurry, suspension, or other flowable material and is capable of forming multiple flow paths in fluid communication with the tissue site. The flowable material may further include particulate solids, such as beads, that are capable of flowing through the manifold delivery tube **1021** if the particulate solids are sufficiently small in size. Materials that are delivered to the tissue site in a flowable state may polymerize or gel in-situ.

As previously described, the reduced pressure delivery apparatus **1035** may be injected or poured directly into the void **1029** adjacent the tissue site **1025**. Referring to FIG. 27A, the manifold delivery tube **1021** may include an impermeable or semi-permeable membrane **1051** at the distal end **1043** of the manifold delivery tube **1021**. The membrane **1051** includes an inner space **1055** that fluidly communicates with a secondary lumen **1057** attached to the manifold delivery tube **1021**. The manifold delivery tube **1021** is guided to the tissue site **1025** over a guide wire **1061**.

The reduced pressure delivery apparatus **1035** may be injected or poured through the secondary lumen **1057** to fill the inner space **1055** of the membrane **1051**. As the fluid or gel fills the membrane **1051**, the membrane **1051** expands to fill the void **1029** such that the membrane is in contact with the tissue site **1025**. As the membrane **1051** expands, the membrane **1051** may be used to dissect additional tissue adjacent or near the tissue site **1025**. The membrane **1051**, if impermeable, may be physically ruptured and removed, leaving behind the reduced pressure delivery apparatus **1035** in contact with the tissue site **1025**. Alternatively, the membrane **1051** may be made from a dissolvable material that dissolves in the presence of bodily fluids or biocompatible solvents that may be delivered to the membrane **1051**. If the membrane **1051** is semi-permeable, the membrane **1051** may remain in situ. The semi-permeable membrane **1051** allows communication of reduced pressure and possibly other fluids to the tissue site **1025**.

Referring to FIG. 28, a method **1111** of administering a reduced pressure tissue treatment to a tissue site includes at **1115** surgically inserting a manifold adjacent the tissue site, the manifold having a plurality of projections extending from a flexible barrier to create a plurality of flow channels between the projections. The manifold is positioned at **1119** such that at least a portion of the projections are in contact

23

with the tissue site. At **1123**, a reduced pressure is applied through the manifold to the tissue site.

Referring to FIG. **29**, a method **1211** of administering a reduced pressure tissue treatment to a tissue site includes at **1215** percutaneously inserting a manifold adjacent the tissue site. The manifold may include a plurality of projections extending from a flexible barrier to create a plurality of flow channels between the projections. Alternatively, the manifold may include cellular material having a plurality of flow channels within the cellular material. Alternatively, the manifold may be formed from an injectable or pourable material that is delivered to the tissue site and forms a plurality of flow channels after arriving at the tissue site. At **1219**, the manifold is positioned such that at least a portion of the flow channels are in fluid communication with the tissue site. A reduced pressure is applied to the tissue site through the manifold at **1223**.

Referring to FIG. **30**, a method **1311** of administering a reduced pressure tissue treatment to a tissue site includes at **1315** percutaneously inserting a tube having a passageway through a tissue of a patient to place a distal end of the tube adjacent the tissue site. At **1319**, a balloon associated with the tube may be inflated to dissect tissue adjacent the tissue site, thereby creating a void. At **1323**, a manifold is delivered through the passageway. The manifold may include a plurality of projections extending from a flexible barrier to create a plurality of flow channels between the projections. Alternatively, the manifold may include cellular material having a plurality of flow channels within the cellular material. Alternatively, the manifold may be formed from an injectable or pourable material that is delivered to the tissue site as described previously with reference to FIG. **27**. The manifold is positioned in the void at **1327** such that at least a portion of the flow channels are in fluid communication with the tissue site. At **1331**, a reduced pressure is applied to the tissue site through the manifold via a reduced pressure delivery tube or any other delivery means.

Referring to FIG. **31**, a method **1411** of administering a reduced pressure tissue treatment to a tissue site includes at **1415** percutaneously inserting a tube having a passageway through a tissue of a patient to place a distal end of the tube adjacent the tissue site. At **1423**, a manifold is delivered through the passageway to the tissue site within an impermeable sheath, the impermeable sheath at **1419** having been subjected to a first reduced pressure less than an ambient pressure of the sheath. At **1427**, the sheath is ruptured to place the manifold in contact with the tissue site. At **1431**, a second reduced pressure is applied through the manifold to the tissue site.

Referring to FIGS. **32** and **33**, a reduced pressure delivery apparatus **1511** according to an embodiment of the present invention includes an orthopedic hip prosthesis **1515** for replacing the existing femoral head of a femur **1517** of a patient. The hip prosthesis **1515** includes a stem portion **1521** and a head portion **1525**. The stem portion **1521** is elongated for insertion within a passage **1529** reamed in a shaft of the femur **1517**. A porous coating **1535** is disposed around the stem portion and preferably is constructed from sintered or vitrified ceramics or metal. Alternatively, a cellular material having porous characteristic could be disposed around the stem portion. A plurality of flow channels **1541** is disposed within the stem portion **1521** of the hip prosthesis **1515** such that the flow channels **1541** are in fluid communication with the porous coating **1535**. A connection port **1545** is fluidly connected to the flow channels **1541**, the port being configured for releasable connection to a reduced pressure delivery tube **1551** and a reduced pressure delivery source **1553**. The

24

flow channels **1541** are used to deliver a reduced pressure to the porous coating **1535** and/or the bone surrounding the hip prosthesis **1515** following implantation. The flow channels **1541** may include a main feeder line **1543** that fluidly communicates with several lateral branch lines **1547**, which communicate with the porous coating **1535**. The lateral branch lines **1545** may be oriented normal to the main feeder line **1543** as illustrated in FIG. **32**, or may be oriented at angles to the main feeder line **1543**. An alternative method for distributing the reduced pressure includes providing a hollow hip prosthesis, and filling the inner space of the prosthesis with a cellular (preferably open-cell) material that is capable of fluidly communicating with the porous coating **1535**.

Referring more specifically to FIG. **33**, hip prosthesis **1515** may further include a second plurality of flow channels **1561** within the stem portion **1521** to provide a fluid to the porous coating **1535** and/or the bone surrounding the hip prosthesis **1515**. The fluid could include filtered air or other gases, antibacterial agents, antiviral agents, cell-growth promotion agents, irrigation fluids, chemically active fluids, or any other fluid. If it is desired to introduce multiple fluids to the bone surrounding the hip prosthesis **1515**, additional paths of fluid communication may be provided. A connection port **1565** is fluidly connected to the flow channels **1561**, the port **1565** being configured for releasable connection to a fluid delivery tube **1571** and a fluid delivery source **1573**. The flow channels **1561** may include a main feeder line **1583** that fluidly communicates with several lateral branch lines **1585**, which communicate with the porous coating **1535**. The lateral branch lines **1585** may be oriented normal to the main feeder line **1583** as illustrated in FIG. **33**, or may be oriented at angles to the main feeder line **1583**.

The delivery of reduced pressure to the first plurality of flow channels **1541** and the delivery of the fluid to the second plurality of flow channels **1561** may be accomplished by separate tubes such as reduced pressure delivery tube **1551** and fluid delivery tube **1571**. Alternatively, a tube having multiple lumens as described previously herein may be used to separate the communication paths for delivering the reduced pressure and the fluid. It should further be noted that while it is preferred to provide separate paths of fluid communication within the hip prosthesis **1515**, the first plurality of flow channels **1541** could be used to deliver both the reduced pressure and the fluid to the bone surrounding the hip prosthesis **1515**.

As previously described, application of reduced pressure to bone tissue promotes and speeds the growth of new bone tissue. By using the hip prosthesis **1515** as a manifold to deliver reduced pressure to the area of bone surrounding the hip prosthesis, recovery of the femur **1517** is faster, and the hip prosthesis **1515** integrates more successfully with the bone. Providing the second plurality of flow channels **1561** to vent the bone surrounding the hip prosthesis **1515** improves the successful generation of new bone around the prosthesis.

Following the application of reduced pressure through the hip prosthesis **1515** for a selected amount of time, the reduced pressure delivery tube **1551** and fluid delivery tube **1571** may be disconnected from the connection ports **1545**, **1565** and removed from the patient's body, preferably without a surgically-invasive procedure. The connection between the connection ports **1545**, **1565** and the tubes **1551**, **1571** may be a manually-releasable connection that is effectuated by applying an axially-oriented tensile force to the tubes **1551**, **1571** on the outside of the patient's body. Alternatively, the connection ports **1545**, **1565** may be bioresorbable or dissolvable in the presence of selected fluids or chemicals such that release of the tubes **1551**, **1571** may be obtained by exposing

25

the connection ports **1545**, **1565** to the fluid or chemical. The tubes **1551**, **1571** may also be made from a bioresorbable material that dissolves over a period of time or an activated material that dissolves in the presence of a particular chemical or other substance.

The reduced pressure delivery source **1553** may be provided outside the patient's body and connected to the reduced pressure delivery tube **1551** to deliver reduced pressure to the hip prosthesis **1515**. Alternatively, the reduced pressure delivery source **1553** may be implanted within the patient's body, either on-board or near the hip prosthesis **1515**. Placement of the reduced pressure delivery source **1553** within the patient's body eliminates the need for a percutaneous fluid connection. The implanted reduced pressure delivery source **1553** may be a traditional pump that is operably connected to the flow channels **1541**. The pump may be powered by a battery that is implanted within the patient, or may be powered by an external battery that is electrically and percutaneously connected to the pump. The pump may also be driven directly by a chemical reaction that delivers a reduced pressure and circulates fluids through the flow channels **1541**, **1561**.

While only the stem portion **1521** and head portion **1525** of the hip prosthesis **1515** are illustrated in FIGS. **32** and **33**, it should be noted that the flow channels and means for applying reduced pressure tissue treatment described herein could be applied to any component of the hip prosthesis **1515** that contacts bone or other tissue, including for example the acetabular cup.

Referring to FIG. **34**, a method **1611** for repairing a joint of a patient includes at **1615** implanting a prosthesis within a bone adjacent the joint. The prosthesis could be a hip prosthesis as described above or any other prosthesis that assists in restoring mobility to the joint of the patient. The prosthesis includes a plurality of flow channels configured to fluidly communicate with the bone. At **1619**, a reduced pressure is applied to the bone through the plurality of flow channels to improve osseointegration of the prosthesis.

Referring to FIGS. **35** and **36**, a reduced pressure delivery apparatus **1711** according to an embodiment of the present invention includes an orthopedic fixation device **1715** for securing a bone **1717** of a patient that includes a fracture **1719** or other defect. The orthopedic fixation device **1715** illustrated in FIGS. **35** and **36** is a plate having a plurality of passages **1721** for anchoring the orthopedic fixation device **1715** to the bone **1717** with screws **1725**, pins, bolts, or other fasteners. A porous coating **1735** may be disposed on a surface of the orthopedic fixation device **1715** that is to contact the bone **1717**. The porous coating is preferably constructed from sintered or vitrified ceramics or metal. Alternatively, a cellular material having porous characteristic could be disposed between the bone **1717** and the orthopedic fixation device **1715**. A plurality of flow channels **1741** is disposed within the orthopedic fixation device **1715** such that the flow channels **1741** are in fluid communication with the porous coating **1735**. A connection port **1745** is fluidly connected to the flow channels **1741**, the port being configured for connection to a reduced pressure delivery tube **1751** and a reduced pressure delivery source **1753**. The flow channels **1741** are used to deliver a reduced pressure to the porous coating **1735** and/or the bone surrounding the orthopedic fixation device **1715** following fixation of the orthopedic fixation device **1715** to the bone **1717**. The flow channels **1741** may include a main feeder line **1743** that fluidly communicates with several lateral branch lines **1747**, which communicate with the porous coating **1735**. The lateral branch lines **1747** may be oriented normal to the main feeder line **1743** as illustrated in FIG. **35**, or may be oriented at angles to the main feeder line

26

1743. An alternative method for distributing the reduced pressure includes providing a hollow orthopedic fixation device, and filling the inner space of the orthopedic fixation device with a cellular (preferably open-cell) material that is capable of fluidly communicating with the porous coating **1735**.

The orthopedic fixation device **1715** may be a plate as shown in FIG. **35**, or alternatively may be a fixation device such as a sleeve, a brace, a strut, or any other device that is used to stabilize a portion of the bone. The orthopedic fixation device **1715** may further be fasteners used to attach prosthetic or other orthopedic devices or implanted tissues (e.g. bone tissues or cartilage), provided that the fasteners include flow channels for delivering reduced pressure to tissue adjacent to or surrounding the fasteners. Examples of these fasteners may include pins, bolts, screws, or any other suitable fastener.

Referring more specifically to FIG. **36**, the orthopedic fixation device **1715** may further include a second plurality of flow channels **1761** within the orthopedic fixation device **1715** to provide a fluid to the porous coating **1735** and/or the bone surrounding the orthopedic fixation device **1715**. The fluid could include filtered air or other gases, antibacterial agents, antiviral agents, cell-growth promotion agents, irrigation fluids, chemically active agents, or any other fluid. If it is desired to introduce multiple fluids to the bone surrounding the orthopedic fixation device **1715**, additional paths of fluid communication may be provided. A connection port **1765** is fluidly connected to the flow channels **1761**, the port **1765** being configured for connection to a fluid delivery tube **1771** and a fluid delivery source **1773**. The flow channels **1761** may include a main feeder line **1783** that fluidly communicates with several lateral branch lines **1785**, which communicate with the porous coating **1735**. The lateral branch lines **1785** may be oriented normal to the main feeder line **1783** as illustrated in FIG. **33**, or may be oriented at angles to the main feeder line **1783**.

The delivery of reduced pressure to the first plurality of flow channels **1741** and the delivery of the fluid to the second plurality of flow channels **1761** may be accomplished by separate tubes such as reduced pressure delivery tube **1751** and fluid delivery tube **1771**. Alternatively, a tube having multiple lumens as described previously herein may be used to separate the communication paths for delivering the reduced pressure and the fluid. It should further be noted that while it is preferred to provide separate paths of fluid communication within the orthopedic fixation device **1715**, the first plurality of flow channels **1741** could be used to deliver both the reduced pressure and the fluid to the bone adjacent the orthopedic fixation device **1715**.

The use of orthopedic fixation device **1715** as a manifold to deliver reduced pressure to the area of bone adjacent the orthopedic fixation device **1715** speeds and improves recovery of the defect **1719** of the bone **1717**. Providing the second plurality of flow channels **1761** to communicate fluids to the bone surrounding the orthopedic fixation device **1715** improves the successful generation of new bone near the orthopedic fixation device.

Referring to FIG. **37**, a method **1811** for healing a bone defect of a bone includes at **1815** fixating the bone using an orthopedic fixation device. The orthopedic fixation device includes a plurality of flow channels disposed within the orthopedic fixation device. At **1819**, a reduced pressure is applied to the bone defect through the plurality of flow channels.

Referring to FIG. **38**, a method **1911** for administering reduced pressure tissue treatment to a tissue site includes at **1915** positioning a manifold having a plurality of flow channels such that at least a portion of the flow channels are in fluid

27

communication with the tissue site. A reduced pressure is applied at **1919** to the tissue site through the flow channels, and a fluid is delivered at **1923** to the tissue site through the flow channels

Referring to FIG. **39**, a method **2011** for administering reduced pressure tissue treatment to a tissue site includes at **2015** positioning a distal end of a manifold delivery tube adjacent the tissue site. At **2019** a fluid is delivered through the manifold delivery tube to the tissue site. The fluid is capable of filling a void adjacent the tissue site and becoming a solid manifold having a plurality of flow channels in fluid communication with the tissue site. A reduced pressure is applied at **2023** to the tissue site through the flow channels of the solid manifold.

Referring to FIGS. **40-48**, a reduced pressure delivery system **2111** includes a primary manifold **2115** having a flexible wall **2117** surrounding a primary flow passage **2121**. The flexible wall **2117** is connected at a proximal end **2123** to a reduced pressure delivery tube **2125**. Since the shape of the reduced pressure delivery tube **2125** will typically be round in cross-section, and since the shape of the primary manifold **2115** in cross-section may be other than round (i.e. rectangular in FIGS. **40-45** and triangular in FIGS. **46-48**), a transition region **2129** is provided between the reduced pressure delivery tube **2125** and the primary manifold **2115**. The primary manifold **2115** may be adhesively connected to the reduced pressure delivery tube **2125**, connected using other means such as fusing or insert molding, or alternatively may be integrally connected by co-extrusion. The reduced pressure delivery tube **2125** delivers reduced pressure to the primary manifold **2115** for distribution at or near the tissue site.

A blockage prevention member **2135** is positioned within the primary manifold to prevent collapse of the manifold **2115**, and thus blockage of the primary flow passage **2121** during application of reduced pressure. In one embodiment, the blockage prevention member **2135** may be a plurality of projections **2137** (see FIG. **44**) disposed on an inner surface **2141** of the flexible wall **2117** and extending into the primary flow passage **2121**. In another embodiment, the blockage prevention member **2135** may be a single or multiple ridges **2145** disposed on the inner surface **2141** (see FIGS. **40** and **41**). In yet another embodiment, the blockage prevention member **2135** may include a cellular material **2149** disposed within the primary flow passage such as that illustrated in FIG. **47**. The blockage prevention member **2135** may be any material or structure that is capable of being inserted within the flow passage or that is capable of being integrally or otherwise attached to the flexible wall **2117**. The blockage prevention member **2135** is able to prevent total collapse of the flexible wall **2117**, while still allowing the flow of fluids through the primary flow passage **2121**.

The flexible wall **2117** further includes a plurality of apertures **2155** through the flexible wall **2117** that communicate with the primary flow passage **2121**. The apertures **2155** allow reduced pressure delivered to the primary flow passage **2121** to be distributed to the tissue site. Apertures **2155** may be selectively positioned around the circumference of the manifold **2115** to preferentially direct the delivery of vacuum. For example, in FIG. **51**, apertures may be placed facing the bone, facing the overlying tissue, or both.

The reduced pressure delivery tube **2125** preferably includes a first conduit **2161** having at least one outlet fluidly connected to the primary flow passage **2121** to deliver reduced pressure to the primary flow passage **2121**. A second conduit **2163** may also be provided to purge the primary flow passage **2121** and the first conduit **2161** with a fluid to prevent or resolve blockages caused by wound exudate and other

28

fluids drawn from the tissue site. The second conduit **2163** preferably includes at least one outlet positioned proximate to at least one of the primary flow passage **2121** and the at least one outlet of the first conduit **2161**.

Referring more specifically to FIGS. **40** and **41**, the reduced pressure delivery system **2111** the second conduit **2163** may include multiple conduits for purging the primary flow passage **2121** and the first conduit **2161**. While the end of the flexible wall **2117** opposite the end attached to reduced pressure delivery tube **2125** may be open as illustrated in FIG. **40**, it has been found that capping the end of the flexible wall **2117** may improve the performance and reliability of the purging function. Preferably, a head space **2171** is provided for between the capped end of the flexible wall and the end of the second conduits **2163**. The head space **2171** allows for a buildup of purge fluid during the purging process, which helps drive the purge fluid through the primary flow passage **2121** and into the first conduit **2161**.

Also illustrated in FIG. **41** is the divider that serves as the blockage prevention member **2135**. The centrally-located divider bifurcates the primary flow passage **2121** into two chambers, which allows continued operation of the primary manifold **2115** if one of the chambers becomes blocked and purging is unable to resolve the blockage.

Referring to FIGS. **49** and **50**, a reduced pressure delivery system **2211** includes a primary manifold **2215** that is integral to a reduced pressure delivery tube **2217**. The reduced pressure delivery tube **2217** includes a central lumen **2223** and a plurality of ancillary lumens **2225**. While the ancillary lumens **2225** may be used to measure pressure at or near the tissue site, the ancillary lumens **2225** may further be used to purge the central lumen **2223** to prevent or resolve blockages. A plurality of apertures **2231** communicate with the central lumen **2223** to distribute the reduced pressure delivered by the central lumen **2223**. As illustrated in FIG. **50**, it is preferred that the apertures **2231** not penetrate the ancillary lumens **2225**. Also illustrated in FIG. **50** is the countersunk end of the reduced pressure delivery tube, which creates a head space **2241** beyond the end of the ancillary lumens **2225**. If tissue, scaffolds, or other materials were to engage the end of the reduced pressure delivery tube **2217** during application of reduced pressure, the head space **2241** would continue to allow purging fluid to be delivered to the central lumen **2223**.

In operation, the reduced pressure delivery systems **2111**, **2211** of FIGS. **40-50** may be applied directly to a tissue site for distributing reduced pressure to the tissue site. The low-profile shape of the primary manifolds is highly desirable for the percutaneous installation and removal techniques described herein. Similarly, the primary manifolds may also be inserted surgically.

Referring to FIG. **51**, the primary manifolds **2115**, **2215** may be used in conjunction with a secondary manifold **2321**. In FIG. **51**, the secondary manifold **2321** includes a two-layered felted mat. The first layer of the secondary manifold **2321** is placed in contact with a bone tissue site that includes a bone fracture. The primary manifold **2115** is placed in contact with the first layer, and the second layer of the secondary manifold **2321** is placed on top of the primary manifold **2115** and first layer. The secondary manifold **2321** allows fluid communication between the primary manifold **2115** and the tissue site, yet prevents direct contact between the tissue site and the primary manifold **2115**.

Preferably, the secondary manifold **2321** is bioabsorbable, which allows the secondary manifold **2321** to remain in situ following completion of reduced pressure treatment. Upon completion of reduced pressure treatment, the primary manifold **2115** may be removed from between the layers of the

secondary manifold with little or no disturbance to the tissue site. In one embodiment, the primary manifold may be coated with a lubricious material or a hydrogel-forming material to ease removal from between the layers.

The secondary manifold preferably serves as a scaffold for new tissue growth. As a scaffold, the secondary manifold may be comprised of at least one material selected from the group of polylactic acid, polyglycolic acid, polycaprolactone, polyhydroxybutyrate, polyhydroxyvalerate, polydioxanone, polyorthoesters, polyphosphazenes, polyurethanes, collagen, hyaluronic acid, chitosan, hydroxyapatite, calcium phosphate, calcium sulfate, calcium carbonate, bioglass, stainless steel, titanium, tantalum, allografts, and autografts.

The purging function of the reduced pressure delivery systems **2111**, **2211** described above may be employed with any of the manifolds described herein. The ability to purge a manifold or a conduit delivering reduced pressure prevents blockages from forming that hinder the administration of reduced pressure. These blockages typically form as the pressure near the tissue site reaches equilibrium and egress of fluids around the tissue site slows. It has been found that purging the manifold and reduced pressure conduit with air for a selected amount of time at a selected interval assists in preventing or resolving blockages.

More specifically, air is delivered through a second conduit separate from a first conduit that delivers reduced pressure. An outlet of the second conduit is preferably proximate to the manifold or an outlet of the first conduit. While the air may be pressurized and "pushed" to the outlet of the second conduit, the air is preferably drawn through the second conduit by the reduced pressure at the tissue site. It has been found that delivery of air for two (2) seconds at intervals of sixty (60) seconds during the application of reduced pressure is sufficient to prevent blockages from forming in many instances. This purging schedule provides enough air to sufficiently move fluids within the manifold and first conduit, while preventing the introduction of too much air. Introducing too much air, or introducing air at too high of an interval frequency will result in the reduced pressure system not being able to return to the target reduced pressure between purge cycles. The selected amount of time for delivering a purging fluid and the selected interval at which the purging fluid is delivered will typically vary based on the design and size of system components (e.g. the pump, tubing, etc.). However, air should be delivered in a quantity and at a frequency that is high enough to sufficiently clear blockages while allowing the full target pressure to recover between purging cycles.

Referring to FIG. **52**, in one illustrative embodiment, a reduced pressure delivery system **2411** includes a manifold **2415** fluidly connected to a first conduit **2419** and a second conduit **2423**. The first conduit **2419** is connected to a reduced pressure source **2429** to provide reduced pressure to the manifold **2415**. The second conduit **2423** includes an outlet **2435** positioned in fluid communication with the manifold **2415** and proximate an outlet of the first conduit **2419**. The second conduit **2423** is fluidly connected to a valve **2439**, which is capable of allowing communication between the second conduit **2423** and the ambient air when the valve is placed in an open position. The valve **2439** is operably connected to a controller **2453** that is capable of controlling the opening and closing of the valve **2439** to regulate purging of the second conduit with ambient air to prevent blockages within the manifold **2415** and the first conduit **2419**.

It should be noted that any fluid, including liquids or gases, could be used to accomplish the purging techniques described herein. While the driving force for the purging fluid is preferably the draw of reduced pressure at the tissue site, the fluid

similarly could be delivered by a fluid delivery means similar to that discussed with reference to FIG. **9**.

The administration of reduced pressure tissue treatment to a tissue site in accordance with the systems and methods described herein may be accomplished by applying a sufficient reduced pressure to the tissue site and then maintaining that sufficient reduced pressure over a selected period of time. Alternatively, the reduced pressure that is applied to the tissue site may be cyclic in nature. More specifically, the amount of reduced pressure applied may be varied according to a selected temporal cycle. Still another method of applying the reduced pressure may vary the amount of reduced pressure randomly. Similarly, the rate or volume of fluid delivered to the tissue site may be constant, cyclic, or random in nature. Fluid delivery, if cyclic, may occur during application of reduced pressure, or may occur during cyclic periods in which reduced pressure is not being applied. While the amount of reduced pressure applied to a tissue site will typically vary according to the pathology of the tissue site and the circumstances under which reduced pressure tissue treatment is administered, the reduced pressure will typically be between about -5 mm Hg and -500 mm Hg, but more preferably between about -5 mm Hg and -300 mm Hg.

While the systems and methods of the present invention have been described with reference to tissue growth and healing in human patients, it should be recognized that these systems and methods for applying reduced pressure tissue treatment can be used in any living organism in which it is desired to promote tissue growth or healing. Similarly, the systems and methods of the present invention may be applied to any tissue, including without limitation bone tissue, adipose tissue, muscle tissue, neural tissue, dermal tissue, vascular tissue, connective tissue, cartilage, tendons, or ligaments. While the healing of tissue may be one focus of applying reduced pressure tissue treatment as described herein, the application of reduced pressure tissue treatment, especially to tissues located beneath a patient's skin, may also be used to generate tissue growth in tissues that are not diseased, defective, or damaged. For example, it may be desired to use the percutaneous implantation techniques to apply reduced pressure tissue treatment to grow additional tissue at a tissue site that can then be harvested. The harvested tissue may be transplanted to another tissue site to replace diseased or damaged tissue, or alternatively the harvested tissue may be transplanted to another patient.

It is also important to note that the reduced pressure delivery apparatuses described herein may be used in conjunction with scaffold material to increase the growth and growth rate of new tissue. The scaffold material could be placed between the tissue site and the reduced pressure delivery apparatus, or the reduced pressure delivery apparatus could itself be made from bioresorbable material that serves as a scaffold to new tissue growth.

It should be apparent from the foregoing that an invention having significant advantages has been provided. While the invention is shown in only a few of its forms, it is not just limited but is susceptible to various changes and modifications without departing from the spirit thereof.

We claim:

1. A reduced pressure delivery system for applying reduced pressure tissue treatment to a tissue site comprising:

- a manifold delivery tube having at least two lumens;
- a manifold having a plurality of flow channels, the manifold disposed within a first of the lumens of the manifold delivery tube;
- a balloon having an inner space and being capable of assuming collapsed and expanded positions, the inner

31

space being fluidly connected to a second of the lumens of the manifold delivery tube; and
a sharp tip configured to slide within the manifold delivery tube for selectively puncturing the balloon.

2. The reduced pressure delivery system according to claim 1, wherein the first and second lumens are substantially coaxial.

3. The reduced pressure delivery system according to claim 1 further comprising a reduced pressure delivery tube fluidly connected to at least one of the plurality of flow channels.

4. The reduced pressure delivery system according to claim 3, wherein the reduced-pressure delivery tube is capable of being disconnected from the at least one flow channel.

5. The reduced pressure delivery system according to claim 4, wherein the manifold is bioresorbable.

6. The reduced pressure delivery system according to claim 3, further comprising a reduced pressure source fluidly connected to the reduced-pressure delivery tube.

7. The reduced pressure delivery system according to claim 3, wherein a reduced pressure is applied through the reduced-pressure delivery tube to the at least one flow channel.

8. The reduced pressure delivery system according to claim 7, wherein the reduced pressure is applied cyclically.

9. The reduced pressure delivery system according to claim 1, wherein the manifold delivery tube is a catheter.

10. The reduced pressure delivery system according to claim 1, wherein the manifold delivery tube is a cannula.

11. The reduced pressure delivery system according to claim 1 further comprising markers operably attached to at least one of the manifold delivery tube and the manifold to visualize a location of the manifold delivery tube or the manifold relative to the tissue site.

12. The reduced pressure delivery system according to claim 11, wherein the markers are radio-opaque markers.

13. The reduced pressure delivery system according to claim wherein the manifold further comprises:

a flexible wall surrounding a primary flow passage and adapted to be placed in proximity to the tissue site, the flexible wall including a plurality of apertures through the flexible wall and communicating with the primary flow passage;

a blockage prevention member positioned within the primary flow passage;

a first conduit having at least one outlet fluidly connected to the primary flow passage to deliver reduced pressure to the primary flow passage; and

a second conduit having at least one outlet proximate the primary flow passage or the at least one outlet of the first conduit to purge at least one of the primary flow passage and the outlet of the first conduit with a gaseous fluid during the application of reduced pressure.

14. The reduced pressure delivery system according to claim 13, wherein the blockage prevention member is a plurality of projections disposed on an inner surface of the flexible wall and extending into the primary flow passage.

15. The reduced pressure delivery system according to claim 13, wherein the blockage prevention member is a cellular material positioned within the primary flow passage.

16. The reduced pressure delivery system according to claim 1, wherein the manifold further comprises:

a flexible barrier;
a cellular material disposed adjacent to the flexible barrier, the cellular material including the plurality of flow channels; and

a reduced-pressure delivery tube fluidly connected to at least one of the plurality of flow channels.

32

17. The reduced pressure delivery system according to claim 1, wherein the balloon is expanded by injecting a fluid into the inner space.

18. The reduced pressure delivery system according to claim 1, wherein the tissue site includes a hard tissue.

19. The reduced pressure delivery system according to claim 1, wherein the tissue site includes a soft tissue.

20. A reduced pressure delivery system for applying reduced pressure tissue treatment to a tissue site comprising: an impermeable membrane having an inner space, the impermeable membrane being capable of assuming compressed and relaxed conditions;

a manifold having a plurality of flow channels, the manifold positioned within the inner space of the impermeable membrane; and

wherein a pressure within the inner space of the impermeable membrane is less than the pressure outside the impermeable membrane to reduce a volume of space occupied by the manifold within the impermeable membrane.

21. The reduced pressure delivery system according to claim 20, wherein the impermeable membrane is sealed to maintain the pressure within the impermeable membrane.

22. The reduced pressure delivery system according to claim 20 further comprising a reduced pressure source fluidly connected to the inner space of the impermeable membrane to maintain the pressure within the inner space.

23. The reduced pressure delivery system according to claim 20, wherein the impermeable membrane is dissolvable when placed in contact with bodily fluids or bodily tissue.

24. The reduced pressure delivery system according to claim 20, wherein the impermeable membrane is capable of assuming an expanded position to dissect tissue adjacent the tissue site.

25. The reduced pressure delivery system according to claim 24, wherein the impermeable membrane is expanded by injecting a fluid into the inner space.

26. The reduced pressure delivery system according to claim 20 further comprising an instrument having a sharp tip to selectively rupture the impermeable membrane.

27. The reduced pressure delivery system according to claim 20 further comprising:

a seal disposed on the impermeable membrane; and
an instrument to push the manifold through the seal.

28. The reduced pressure delivery system according to claim 20 further comprising markers operably attached to at least one of the impermeable membrane and the manifold to visualize a location of the impermeable membrane or the manifold relative to the tissue site.

29. The reduced pressure delivery system according to claim 28, wherein the markers are radio-opaque markers.

30. The reduced pressure delivery system according to claim 20 further comprising a reduced-pressure delivery tube having a distal end fluidly connected to at least one of the flow channels of the manifold.

31. The reduced pressure delivery system according to claim 30 further comprising a reduced pressure source fluidly connected to a proximal end of the reduced-pressure delivery tube to deliver a second reduced pressure to the at least one flow channel.

32. The reduced pressure delivery system according to claim 31, wherein the second reduced pressure is applied cyclically.

33. The reduced pressure delivery system according to claim 30, wherein the reduced-pressure delivery tube is capable of being disconnected from the at least one flow channel.

33

34. The reduced pressure delivery system according to claim 33, wherein the manifold is bioresorbable.

35. The reduced pressure delivery system according to claim 20, wherein the manifold further comprises:

- a flexible wall surrounding a primary flow passage and adapted to be placed in proximity to the tissue site, the flexible wall including a plurality of apertures through the flexible wall and communicating with the primary flow passage;
- a blockage prevention member positioned within the primary flow passage;
- a first conduit having at least one outlet fluidly connected to the primary flow passage to deliver reduced pressure to the primary flow passage; and
- a second conduit having at least one outlet proximate the primary flow passage or the at least one outlet of the first conduit to purge at least one of the primary flow passage and the outlet of the first conduit with a fluid during the application of reduced pressure.

36. The reduced pressure delivery system according to claim 35, wherein the blockage prevention member is a plurality of projections disposed on an inner surface of the flexible wall and extending into the primary flow passage.

37. The reduced pressure delivery system according to claim 35, wherein the blockage prevention member is a cellular material positioned within the primary flow passage.

38. The reduced pressure delivery system according to claim 35, wherein the fluid is a gas.

39. The reduced pressure delivery system according to claim 35, wherein the fluid is a liquid.

40. The reduced pressure delivery system according to claim 20, wherein the manifold further comprises:

- a flexible barrier;
- a cellular material attached to the flexible barrier, the cellular material including the plurality of flow channels; and
- a reduced-pressure delivery tube fluidly connected to at least one of the plurality of flow channels.

34

41. The reduced pressure delivery system according to claim 20, wherein the tissue site includes hard tissue.

42. The reduced pressure delivery system according to claim 20, wherein the tissue site includes soft tissue.

43. A reduced pressure delivery system for applying reduced pressure tissue treatment to a tissue site comprising:

- a manifold delivery tube having at least two lumens;
- a manifold having a plurality of flow channels, the manifold disposed within a first of the lumens of the manifold delivery tube, the manifold comprising:
 - a flexible wall surrounding a primary flow passage and adapted to be placed in proximity to the tissue site, the flexible wall including a plurality of apertures through the flexible wall and communicating with the primary flow passage;
 - a blockage prevention member positioned within the primary flow passage;
 - a first conduit having at least one outlet fluidly connected to the primary flow passage to deliver reduced pressure to the primary flow passage; and
 - a second conduit having at least one outlet proximate the primary flow passage or the at least one outlet of the first conduit to purge at least one of the primary flow passage and the outlet of the first conduit with a gaseous fluid during the application of reduced pressure; and
- a balloon having an inner space and being capable of assuming collapsed and expanded positions, the inner space being fluidly connected to a second of the lumens of the manifold delivery tube.

44. The reduced pressure delivery system according to claim 43, wherein the blockage prevention member is a plurality of projections disposed on an inner surface of the flexible wall and extending into the primary flow passage.

45. The reduced pressure delivery system according to claim 43, wherein the blockage prevention member is a cellular material positioned within the primary flow passage.

* * * * *