

12 **EUROPEAN PATENT SPECIFICATION**

45 Date of publication of patent specification: **12.07.89**

51 Int. Cl.⁴: **B 01 F 3/00**

21 Application number: **85901454.0**

22 Date of filing: **28.03.85**

86 International application number:
PCT/FI85/00030

87 International publication number:
WO 85/04344 10.10.85 Gazette 85/22

54 **PROCEDURE FOR DISPERSING TALC.**

30 Priority: **30.03.84 FI 841298**

43 Date of publication of application:
09.07.86 Bulletin 86/28

45 Publication of the grant of the patent:
12.07.89 Bulletin 89/28

84 Designated Contracting States:
AT BE CH DE FR GB LI NL SE

56 References cited:
FI-B- 64 674
GB-A-1 449 129
US-A-4 187 192
US-A-4 430 249

**The file contains technical information
submitted after the application was filed and
not included in this specification**

73 Proprietor: **Oy Partek AB**
SF-73670 Luikonlahti (FI)

72 Inventor: **KAILA, Mikko**
Merenneidontie 28
SF-02320 Espoo (FI)
Inventor: **ESKELINEN, Eelis**
SF-73670 Luikonlahti (FI)
Inventor: **TYNI, Matti**
SF-73670 Luikonlahti (FI)

74 Representative: **Whalley, Kevin et al**
MARKS & CLERK 57/60 Lincoln's Inn Fields
London WC2A 3LS (GB)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European patent convention).

Description

The present invention concerns a procedure for dispersing talc. In particular, the present invention concerns a procedure with which granulated, finely divided talc can be advantageously dispersed to become a suspension which fulfills the requirements of paper coating paste, at the same time retaining the advantages of granulated talc regarding its handling, and in which standard blunging apparatus can be used.

Granulating finely ground talc is a method commonly used in order to improve the processability of a bulk-type talc product. In the granulation process, the moistened talc is compressed with fairly great force into small non-dusting briquettes. However, the talc particles which have been pressed too close to each other and are mutually suitably oriented become combined by action of a van der Waals force like those in the original talc crystal. The energy threshold of talc is 4.1 kcal/mol (17.2 kJ/mol) and the critical distance, 3 Å (R. F. Giese, Jr: Interlayer Bonding in Talc and Pyrophyllite, 1974). In conventional granulation, and in storage silos, these values are often exceeded, with the consequence that upon granulation the particle size distribution of the suspended talc is coarser than before granulation.

In paper coating paste, the pigment must be completely dispersed. Success in this respect implies that the aggregated particles are separated. It is in fact necessary, in suspending finely divided talc, to use especially powerful dispersing agents. The energy requirements in the coating talc suspending process are twice those in suspending coating kaolin (J—E, TEIRFOLK, INSKO p. 82—80 VI).

The viscosity and rheological properties of the suspension to be used in paper coating paste must be stable. No agglomeration or sedimentation must take place, not even during prolonged storage.

The object of the invention is to provide a procedure in which the use of expensive, high-power special mixers can be avoided.

The aim of the invention is achieved by a method which is mainly characterized in that the talc is suspended in the presence of at least one hydrophilic mineral substance, the quantity of talc being between 10—60% by weight of the quantity of the suspension, and the quantity of said hydrophilic mineral being between 5—55% by weight of the quantity of suspension.

The other characteristic features of the procedure of the invention are stated in claims 2—8.

In the procedure of the invention, the talc may be either finely divided powdery talc or granulated talc. The original grain size of the granulated finely divided talc is 1—5 µm on the average. To the granulating water have been added 0.5—1.5% by weight, of the talc dry weight, e.g. of pH-regulating hydrophilizing and defoaming auxiliary substances, such as e.g. NaOH, polyalkylene glycol and/or its derivatives, and appropriate tensides. To the aqueous suspension prepared of hydrophilic mineral material(s) or of mixtures of such, the above-mentioned auxiliary substances are added at 0.1—0.5% by weight, referred to the total quantity of pigments. In view of maintaining the effectivity of the additives, the temperature must not rise above 50°C in the suspending operation.

The hydrophilicity of a mineral is caused by the difference between the surface energy of said mineral and that of the water surface; the smaller this difference, the higher the hydrophilicity of the mineral.

40	The surface energy of normal water is	72 mJ/m ²
	The surface energy of kaoline is	65 kJ/m ²
	The surface energy of calcium carbonate is	70 mJ/m ²
	The surface energy of gypsum is abt.	70 mJ/m ²
45	The surface energy of talc is	45 mJ/m ²

The differences between the surface energies of the minerals are due to different crystal structures and chemical composition. Talc is by nature strongly hydrophobic. The other minerals mentioned are easily wettable. A talc/water suspension prepared without auxiliary substances is thixotropic, but it becomes dilatant later as the air escapes from the suspension. The stability of viscosity is poor, and the rheological properties change with the slow wetting of the talc. The viscosity of a suspension with more than 60% dry matter content produced without additives is far too high in view of its use.

For hydrophilic mineral substance, the contents of which in the suspension should be 5—55% of the weight of the ultimate suspension, one may use for instance kaolin, calcium carbonate or gypsum suited for paper coating. The effect of the mineral substance in dispersing finely divided, granulated talc is based on the following:

the refining effect with which the particles in the suspension scatter the talc agglomerates; different surface energy: by interposing themselves in the interstices of talc particles, they decrease the hydrophobicity of the pigment and inhibit the reagglomeration of talc particles under pressure.

In a suspension prepared as described, one obtains the original particle size distribution and a high dry matter content: 60—70%, advantageously 65—68%. Complete wetting of the pigments is achieved, and the handling properties of the suspension are good. The auxiliary substances that are used are suited for making a coating paste, and the suspension is stable also in prolonged storage. Dispersing as taught by the invention can be carried out in standard blungers, and the processability advantages afforded by the talc granulation can be preserved.

EP 0 186 665 B1

Example 1

Finely divided, granulated talc, with average grain size 2.2 μm , and to the granulating water of which was added polyalkylene glycol (Pluriol[®] PE 6400) at 0.8% of the dry weight of talc, was dispersed in a suspension made of SPS kaolin to the suspension water of which had been added 0.3 parts by weight of a dispersing agent (Polysalz[®] S), 0.02 parts by weight of sodium hydroxide and 0.02 parts by weight of defoaming agent (Nopco[®] 8034), (all percentages referring to the total pigment weight). The ultimate dry matter content of the suspension was 65%, thereof 50% talc and 50% kaolin. The suspension process took place in a Kady Mill apparatus. On dilution to 63% by weight, the suspension had a viscosity of 100 mPas/50 r/min. The viscosity and rheological properties did not change during storage for 24 hours. The suspension was used to coat LWC paper, with good results.

Example 2

Finely divided, granulated talc with average grain size 2.2 μm , and to the granulating water of which was added polyalkylene glycol (Pluriol[®] PE 6400) at 1.2% of the dry weight of talc, was dispersed in a suspension prepared on SPS kaolin and to the suspension water of which had been added 0.3 parts by weight of a dispersing agent (Polysalz[®] S), 0.02 parts by weight of sodium hydroxide (all these referred to the total pigment weight). The ultimate dry matter content of the suspension was 60.0%, thereof 50% talc and 50% kaolin. The suspension process took place in the laboratory with a Diaf apparatus. The viscosity of the suspension was 75 mPas/20 r/min. The viscosity and rheological properties did not change in 24-hr storage.

When merely finely divided talc was suspended to 60% suspension density, the required suspending time was doubled. The suspension had viscosity 80 mPas/20 r/min. The viscosity and the rheological properties changed substantially during storage for 24 hrs. The suspension was unstable.

Example 3

Fine-grained granulated talc with 2.5 μm average grain size was dispersed in a suspension prepared of calcium carbonate with 1.7 μm average grain size, to the suspension water of which had been added, among others, 1.2% polyalkylene glycol (Pluriol[®] PE 6400) at 1.2% by weight, and sodium hydroxide at 0.02% by weight of the talc dry weight. Dispersion was carried out in the laboratory with a Diaf apparatus. The ultimate dry matter content of the suspension was 60%.

The grain size of the dry matter of the suspension with different carbonate/talc proportions was as follows:

	Talc	Carbonate	Average grain size		Difference
			Calculated	Measured	
	95%	5%	2.47	2.30	7.4%
	90%	10%	2.42	2.20	10%
	70%	30%	2.26	2.10	7.6%
	50%	50%	2.10	1.90	10.5%

The grain sizes were measured with a Sedigraph apparatus. In the experiments, nearly 10% smaller grain sizes were achieved than might be expected, calculating from the original grain size of the pigments. This is believed to be due to the scattering of the talc agglomerates.

Example 4

Fine-grained granulated talc with average grain size 2.2 μm was dispersed with a Diaf apparatus in a suspension prepared of gypsum (CoCoat[®]) meant for paper coating, to the suspension water of which was added polyethylene glycol (Pluriol[®] 6400) 0.8% by weight and sodium hydroxide 0.02% by weight, of the weight of talc. The ultimate solid matter content of the suspension was about 60%. With mixing proportions 5—30% gypsum 95—70% talc, it was easy to obtain a well dispersed stable suspension in which no sedimentation took place, nor any substantial change of viscosity, during storage for two days.

Example 5

Finely divided granulated talc with average grain size 2.2 μm and to the granulating water of which was added polyalkylene glycol (Pluriol[®] PE 6400) at 0.8% of the talc dry weight, was dispersed in a suspension prepared of SPS kaolin, to the suspension water of which had been added 0.3 parts by weight of dispersing agent (Polysalz[®] S), 0.02 parts by weight of sodium hydroxide (all referred to the total pigment weight). The ultimate dry matter content of the suspension was about 64% and it contained 70—95% talc and 30—5% kaolin. Suspension was carried out in the laboratory with a Diaf apparatus. The viscosity and rheological properties did not change at storage for 24 hrs. The viscosity at different mixing proportions was:

EP 0 186 665 B1

	Talc	Kaolin	Dry matter, %	Viscosity, mPas/20 r/min
5	95	5	63.9	450
	90	10	64.1	550
	70	30	63.9	420

- 10 When only finely divided talc was suspended to 64% dry matter content, the viscosity of the suspension was about double the above-mentioned values.

Claims

- 15 1. A procedure for dispersing talc, characterized in that the talc is suspended in the presence of at least one hydrophilic mineral substance, the quantity of talc being between 10—60% by weight of the quantity of the suspension, and the quantity of said hydrophilic mineral being between 5—55% by weight of the quantity of suspension.
- 20 2. A procedure as claimed in claim 1, characterized in that the hydrophilic mineral substance is kaolin.
3. A procedure as claimed in claim 1, characterized in that the hydrophilic mineral substance is calcium carbonate.
4. A procedure as claimed in claim 1, characterized in that the hydrophilic mineral substance is gypsum.
- 25 5. A procedure as claimed in any of claims 1—4, characterized in that the talc is finely divided, powdery talc.
6. A procedure as claimed in any of claims 1—4, characterized in that the talc is granulated talc.
7. A procedure as claimed in any of claims 1—6, characterized in that the average grain size of the talc is 5 μm at maximum.
- 30 8. A procedure as claimed in any of claims 1—7, characterized in that to the suspension and/or to the granulating water have been added pH-regulating, hydrophilizing and defoaming auxiliary substances, such as NaOH, polyalkylene glycol and/or its derivatives and tensides.

Patentansprüche

- 35 1. Verfahren zum Dispergieren von Talk, dadurch gekennzeichnet, dass man den Talk in Gegenwart von mindestens einem hydrophilen anorganischen Stoff suspendiert, wobei die Menge Talk zwischen 10—60 Gew.-% der Menge Suspension liegt und die Menge dieses hydrophilen Minerals zwischen 5—55 Gew.-% der Menge Suspension liegt.
- 40 2. Verfahren nach Anspruch 1, dadurch gekennzeichnet, dass der hydrophile anorganische Stoff Kaolin ist.
3. Verfahren nach Anspruch 1, dadurch gekennzeichnet, dass der hydrophile anorganische Stoff Calciumcarbonat ist.
4. Verfahren nach Anspruch 1, dadurch gekennzeichnet, dass der hydrophile anorganische Stoff Gips ist.
- 45 5. Verfahren nach einem der Ansprüche 1—4, dadurch gekennzeichnet, dass der Talk feinzerteilter pulveriger Talk ist.
6. Verfahren nach einem der Ansprüche 1—4, dadurch gekennzeichnet, dass der Talk granulierter Talk ist.
- 50 7. Verfahren nach einem der Ansprüche 1—6, dadurch gekennzeichnet, dass die durchschnittliche Korngrösse des Talks höchstens 5 μm beträgt.
8. Verfahren nach einem der Ansprüche 1—7, dadurch gekennzeichnet, dass man der Suspension und/oder dem Granulierwasser pH-einstellende, hydrophilisierende und schaumhemmende Hilfsstoffe wie NaOH, Polyalkylenglykol und/oder dessen Derivate und Tenside beigegeben hat.

Revendications

1. Procédé pour disperser du talc, caractérisé en ce que le talc est mis en suspension en présence d'au moins une substance minérale hydrophile, la quantité de talc étant entre 10 et 60% en poids de la quantité de la suspension, et la quantité de ladite substance minérale hydrophile étant entre 5 et 55% en poids de la quantité de suspension.
- 60 2. Procédé selon la revendication 1, caractérisé en ce que la substance minérale hydrophile est le kaolin.
3. Procédé selon la revendication 1, caractérisé en ce que la substance minérale hydrophile est le carbonate de calcium.
- 65

EP 0 186 665 B1

4. Procédé selon la revendication 1, caractérisé en ce que la substance minérale hydrophile est le gypse.

5. Procédé selon l'une quelconque des revendications 1 à 4, caractérisé en ce que le talc est du talc en poudre finement divisé.

5 6. Procédé selon l'une quelconque des revendications 1 à 4, caractérisé en ce que le talc est du talc granulé.

7. Procédé selon l'une quelconque des revendications 1 à 6, caractérisé en ce que la granulométrie moyenne du talc est au maximum de 5 μm .

10 8. Procédé selon l'une quelconque des revendications 1 à 7, caractérisé en ce que l'on a ajouté, à la suspension et/ou à l'eau de granulation, des substances auxiliaires de régulation du pH, d'hydrophilie et antimousses telles que NaOH, un polyalcoylèneglycol et/ou un dérivé de celui-ci et des agents tensio-actifs.

15

20

25

30

35

40

45

50

55

60

65