



US009804691B1

(12) **United States Patent**  
**Strahle et al.**

(10) **Patent No.:** **US 9,804,691 B1**  
(45) **Date of Patent:** **\*Oct. 31, 2017**

(54) **INTERCHANGEABLE INPUT MECHANISMS FOR CONTROL DEVICES**

G06F 1/1662; G06F 3/03; A63F 13/24;  
A63F 13/22; A63F 9/24; A63F  
2009/2407; G05G 9/047

(71) Applicant: **Performance Designed Products LLC**,  
Burbank, CA (US)

See application file for complete search history.

(72) Inventors: **Bradley M. Strahle**, Crestline, CA  
(US); **Eric B. Fulghum**, South  
Pasadena, CA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **Performance Designed Products LLC**,  
Burbank, CA (US)

5,883,690 A *	3/1999	Meyers .....	A63F 13/02 345/157
2004/0155862 A1 *	8/2004	Higginson .....	G05G 1/06 345/156
2005/0255915 A1 *	11/2005	Riggs .....	A63F 13/06 463/37

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

\* cited by examiner

This patent is subject to a terminal dis-  
claimer.

*Primary Examiner* — Lun-yi Lao

*Assistant Examiner* — Jarurat Suteerawongsa

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson  
& Bear LLP

(21) Appl. No.: **15/605,797**

(57) **ABSTRACT**

(22) Filed: **May 25, 2017**

Various embodiments described herein are directed toward  
input mechanisms, for input devices, configured to receive  
and removably couple to interchangeable elements. Hand-  
held input devices applicable to some embodiments may  
include, without limitation, computer controllers, video  
game console controllers, and handheld video gaming  
devices. Input mechanisms applicable to various embodi-  
ments may include, for example, control sticks (e.g., joy-  
sticks or analog sticks operable by a user's finger, such as a  
thumbstick), buttons, switches, and directional pads.  
According to some embodiments, an input mechanism is  
provided comprising a base component. Depending on the  
embodiment, coupling different interchangeable elements to  
the base component may cause the input mechanism to vary  
in size, appearance, contour, material, or features provided  
by the input mechanism.

**Related U.S. Application Data**

(63) Continuation of application No. 13/848,660, filed on  
Mar. 21, 2013, now Pat. No. 9,710,072.



(60) Provisional application No. 61/621,907, filed on Apr.  
9, 2012.

(51) **Int. Cl.**  
**G06F 3/033** (2013.01)

(52) **U.S. Cl.**  
CPC ..... **G06F 3/033** (2013.01)

(58) **Field of Classification Search**  
CPC ..... G06F 1/169; G06F 1/3259; G06F 3/0213;  
G06F 3/033; G06F 3/0338; G06F 1/1624;

**20 Claims, 11 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12







FIG. 13



1

## INTERCHANGEABLE INPUT MECHANISMS FOR CONTROL DEVICES

### CROSS-REFERENCE TO RELATED APPLICATION

Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57 and should be considered a part of this specification. This application is a continuation of U.S. application Ser. No. 13/848,660, filed Mar. 21, 2013, which claims the benefit of U.S. Provisional Application Ser. No. 61/621,907, entitled "INTERCHANGEABLE INPUT MECHANISMS FOR HANDHELD CONTROL DEVICES," filed Apr. 9, 2012, which is hereby incorporated herein by reference.

### FIELD

The systems and methods described herein relate to input devices and, more particularly, some embodiments relate to customizable input devices having interchangeable components.

### DESCRIPTION OF THE RELATED ART

The use of specially configured and customized human input devices, such as video game controllers, keyboards, mice, and trackpads, have a history of use in controlling various devices in many industries. Generally, human input devices (hereafter, simply referred to as "input devices") are configured or customized to meet the needs or preferences of an individual user, often with respect to particular context, application or environment of use. Input devices typically include one or more input mechanisms adapted to receive an input (e.g., physical input) from a user and to translate the input into a corresponding output that may be electrical or mechanical in nature. For instance, an electronic input device, such as a digital handheld controller that is coupled to a processor-based system may receive a physical input from a user (e.g., via an input mechanism) and translate the physical input into a corresponding electrical signal readable by the digital input device.

In the realm of video game consoles (e.g., handheld or other video game consoles) and other video game processor-based systems (e.g., PDAs, laptops, smartphones, etc.), specially configured or customized input devices may include handheld game controllers (e.g., motion-enabled and otherwise), joysticks, analog sticks, digital sticks, directional pads, steering wheels, musical instrument controllers, pads (e.g., dance pads), and the like. Typically, the special configuration or customization of input devices include user preferences relating to ergonomics of the input device, aesthetics of the input device, assignment of buttons or input mechanisms, and the specific application (e.g., first-person shooter video game) with which the input device is being used.

### SUMMARY

Various embodiments of the invention(s) described herein are directed toward input mechanisms for input devices and, more specifically, toward input mechanisms comprising interchangeable elements that enable the input mechanism to be customized/reconfigured according to a user's preferences and/or based on the input mechanism's context of use.

2

Input devices applicable to some embodiments may include, without limitation, computer controllers, video game console controllers, and handheld video gaming devices (e.g., handheld video game consoles, or video game-enabled mobile devices). Other input devices application may include those used in commercial or industrial contexts/environments, such as input devices used to control for heavy machinery (e.g., tractors, cranes, etc.). Depending on the embodiment, input mechanisms may take various forms including, for example, control sticks (e.g., joysticks, digital sticks, or analog sticks such as thumbsticks, which are operable by a user's finger), buttons, switches, and directional pads. For some embodiments, a button may be an electronic button, a mechanical button, a trigger, a shoulder button, or a bumper button; a switch may be a rocker switch, a flit switch, or a slide switch; and a directional pad may be a round directional pad or a plus-shaped directional pad. Additionally, the input mechanisms may be digital or analog in nature, and may vary in size, appearance, contour, and material based on the embodiment.

According to various embodiments, an input mechanism (e.g., directional pad input mechanism, or thumbstick input mechanism) is provided, configured to be integrated into an input device (e.g., input device embedded in a handheld video gaming console, or a video game controller), and having an interchangeable element (e.g., directional pad button, or thumbstick element) removably coupled to a base component of the input mechanism (e.g., at designated coupling point disposed on the base component, such as a socket). The interchangeable element may be coupled to the base component such that the interchangeable element can be decoupled from the input mechanism and optionally replaced by another interchangeable element, which may be similar or different in nature (e.g., possibly an element that is differs in certain aspect in comparison to the element being replaced). Certain embodiment may include an input device incorporating such input mechanisms as those disclosed herein.

According to one embodiment, an input mechanism may comprise: a base component configured to couple to the input device and comprising a coupling mechanism; and a first interchangeable element configured to releasably attach to the coupling mechanism. The first interchangeable element may be configured to receive, or assist the input mechanism in receiving, an input from a user, ideally, when the first interchangeable element is coupled to the base component. Additionally, the coupling mechanism may be configured to couple the first interchangeable element to the base component such that the first interchangeable element can be decoupled from the base component and a second interchangeable element can be coupled to the base component in place of the first interchangeable element.

Depending on the embodiment, the first interchangeable element and the second interchangeable element differ in appearance, material, physical dimension, shape, or input feature provided. For example, the first interchangeable element may comprise a concave top surface or a convex top contact surface (e.g., adapted to the contour of a user's fingertip). In another example, the first interchangeable element may have spherical or semi-spherical shape, which may increase accessibility of the input mechanism.

For some embodiments, the base component may be configured to translate the input to a corresponding input instruction provided to the input device. For instance, the base component of an input mechanism may include electrical components (e.g., potentiometers, switches, etc.) operable in translating a physical input (e.g., receive a control

stick of the input mechanism) into a corresponding electrical signal (e.g., digital or analog signal that is provided to the input device to which the input mechanism is coupled).

For various embodiments, the input mechanism may comprise a joystick, an analog stick, a digital stick or a directional pad. The input mechanism of some embodiments may comprise a button or a switch. Additionally, for some embodiments, the first interchangeable element may comprise a control stick optimized for use by an appendage of the user's hand (e.g., thumbstick optimized for control by a user's thumb). For example, the control stick may comprise a cradle configured to receive and support the appendage of the user's hand (e.g., thumb or index finger).

For some embodiments, the coupling mechanism may comprise a socket configured to receive a plug disposed on the first interchangeable element. Alternatively, the coupling mechanism may comprise a plug configured to be received by a socket disposed on the first interchangeable element. Further, for some embodiments, the coupling mechanism may comprise an opening configured to reduce or prevent the likelihood of a vacuum forming between the first interchangeable element and the base component as the two are decoupled. By this feature, various embodiments can make it easier for a user to decouple the first interchangeable element from the base component when the user chooses to swap the first interchangeable element for another interchangeable element. The coupling mechanism, for various embodiments, may comprise a fastener or the coupling mechanism is friction-based. For example, beads may be disclosed on a coupling portion of the first interchangeable element such that the beads contribute to the adhesion between the coupling portion and the base component to which it is coupled.

In certain embodiments, the coupling mechanism may comprise a guide configured to align the first interchangeable element with the base component during coupling (e.g., as the first interchangeable element is being coupled to the base component). Further, for some embodiments, the guide may be further configured to align the first interchangeable element in a first orientation with respect to the base component. For example, once the first interchangeable element has been coupled to the base component, the guide may cause the first interchangeable element to align in certain direction with respect to the base component.

Other features and aspects of the systems, methods and apparatuses described herein will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, which illustrate, by way of example, features in accordance with various embodiments. The summary is not intended to limit the scope of the invention(s), which is defined solely by the claims attached hereto.

### BRIEF DESCRIPTION OF THE DRAWINGS

One or more various embodiments described herein are done so in detail with reference to the following figures. The drawings are provided for purposes of illustration only and merely depict typical or embodiments. These drawings are provided to facilitate the reader's understanding of various embodiments and shall not be considered limiting of the breadth, scope, or applicability of embodiments. It should be noted that for clarity and ease of illustration these drawings are not necessarily made to scale.

Some of the figures included herein illustrate various embodiments of the invention(s) from different viewing angles. Although the accompanying descriptive text may

refer to such views as "top," "bottom" or "side" views, such references are merely descriptive and do not imply or require that the invention(s) be implemented or used in a particular spatial orientation unless explicitly stated otherwise.

FIG. 1 is a block diagram illustrating a generalized version of a gaming system as one example of an environment with which various embodiments can be implemented.

FIG. 2 is a diagram providing a cross-sectional view of an example input mechanism comprising an interchangeable thumbstick element decoupled from a base component in accordance with various embodiments.

FIG. 3 is a diagram providing a cross-sectional view of an example input mechanism comprising an interchangeable thumbstick element coupled to a base component in accordance with various embodiments.

FIG. 4 is a diagram providing a top-perspective view of an example input mechanism comprising an interchangeable thumb stick element decoupled from a base component in accordance with various embodiments.

FIG. 5 is a diagram providing a cross-sectional view of an example input mechanism comprising an interchangeable thumbstick element coupled to a base component in accordance with various embodiments.

FIGS. 6A and 6B are diagrams providing a side view of an example input mechanism comprising an interchangeable thumbstick element coupled a base component in accordance with various embodiments, and a cutaway view of the base component.

FIG. 7 is a diagram providing a bottom-perspective view of an example input mechanism comprising an interchangeable thumbstick element coupled to a base component in accordance with various embodiments.

FIG. 8 is a diagram providing a bottom-perspective view of an example thumbstick interchangeable element in accordance with some embodiments.

FIG. 9 is a diagram providing a cross-sectional view of an example input mechanism comprising an interchangeable thumbstick element coupled to a base component in accordance with various embodiments.

FIG. 10 depicts example configurations for an input mechanism comprising a common base component coupled to different interchangeable thumbstick elements in accordance with various embodiments.

FIG. 11 depicts an example video game controller comprising at least one input mechanism that comprises an interchangeable thumbstick element coupled to a base component in accordance with various embodiments.

FIG. 12 depicts an example video game controller comprising an input mechanism that includes a base component configured to receive an interchangeable element in accordance with various embodiments.

FIG. 13 depicts example configurations for an input mechanism, coupled to a video game controller, comprising a common base component coupled to different interchangeable thumbstick elements in accordance with various embodiments.

FIGS. 14-16 depict example video game controllers comprising input mechanisms that comprise base components coupled to different interchangeable thumbstick elements in accordance with various embodiments.

The figures are not intended to be exhaustive or to limit various embodiments to the precise form disclosed. It should be understood that various embodiments can be practiced

with modification and alteration, and that embodiments may be limited only by the claims and the equivalents thereof.

#### DETAILED DESCRIPTION

Various embodiments described herein are directed toward input mechanisms for input devices (e.g., handheld input devices), configured to receive and removably couple to interchangeable elements. Input devices, including handheld input devices, applicable to some embodiments may include, without limitation, computer controllers, video game controllers, and handheld video gaming devices. Input mechanisms applicable to various embodiments may include, for example, control sticks (e.g., joysticks or analog sticks operable by a user's finger, such as a thumbstick), buttons, switches, and directional pads. According to some embodiments, an input mechanism is provided comprising a base component, and an interchangeable element configured to removably couple to the base component. Depending on the embodiment, coupling different interchangeable elements to the base component may cause the input mechanism to vary in size, appearance, contour, shape, texture, or material, and may vary or alter the features provided by the input mechanism.

According to various embodiments, an input mechanism, such as directional pad input mechanism, or thumbstick input mechanism, is provided. The input mechanism may be configured to be integrated into a handheld control device, such as handheld video gaming console or a video game or computer controller. Additionally, the input mechanism may have an interchangeable input element, such as a directional pad button or a thumbstick element, that is removably coupled to the input mechanism, possibly at designated coupling point disposed on the input mechanism (e.g., at a socket). The interchangeable element may be coupled to the input mechanism such that the interchangeable element can be decoupled from the input mechanism and optionally replaced by another interchangeable element similar or different in nature. For example, in some embodiments, the interchangeable element can be an element that differs in one or more aspects in comparison to the element being replaced. Certain embodiments may include a handheld control device incorporating such input mechanisms as those disclosed herein.

The base component may comprise mechanical and/or electronic components that facilitate generation of or affect control instructions or signals from the input mechanism to the input device to which it the input mechanism is coupled. The base component can include, for example, a potentiometer or encoder for a thumbstick or joystick, a switch for a button, a series of switches for a D-pad, or other base component.

The interchangeable element may couple to the base component at a coupling point, which may be disposed on or extend through an exterior surface of the base component. Depending on the embodiment, the base component may be an integrated component of an input device. As part of the coupling mechanism, the coupling point may comprise an attachment/retention mechanism utilizing one or more different methodologies to attach the interchangeable element to, and allow detachment of the interchangeable element from, the base component. There are a number of mechanisms that can be used to allow releasable attachment. Examples of attachment/retention mechanisms may include, for instance, friction based mechanisms, socket and plug mechanisms, or fasteners (e.g., screws, clasps, tabs, clips, etc.).

Through the use of certain embodiments, an input device, such as a video game controller, may be reconfigured or customized for various purposes. One such purpose is to suit a user's (e.g., gamer's) preferences with respect to use, feel, appearance, features or performance of the input device. A user may, for instance, interchange an element of an input mechanism to adjust the shape/contour, dimensions, look, feel, material, or performance of one or more the input mechanism elements. Take for instance a thumbstick element coupled to a thumbstick input mechanisms of a video game console controller. A user may change the contour/shape of the thumbstick element of the thumbstick input mechanism by interchanging/replacing a concave thumbstick element with a convex thumbstick element; change the dimensions by interchanging/replacing a thumbstick element of given length with a taller or shorter thumbstick element; change the look of the thumbstick element by interchanging/replacing an opaque thumbstick element of one color (e.g., red) with a semi-translucent thumbstick element of another color (e.g., green); or change the feel by interchanging/replacing a smooth, plastic thumbstick element for a thumbstick element including a surface that has an enhanced grip for finger (e.g., covered by an elastomer, neoprene, or textured material).

Before describing various embodiments in detail, it is useful to describe a few example environments with which certain embodiments can be implemented. One such example is that of a computing system, such as a gaming system, used by one or more participants, such as video game players (gamers), to participate in a group activity, such as playing a computer game or video game.

FIG. 1 illustrates a generalized version of a gaming system **100** as one example of an environment with which various embodiments can be utilized or implemented. Referring now to FIG. 1, the example gaming system includes a gaming console **201**, a monitor **106**, a dance pad game controller **110**, and a musical-instrument game controller **112**. Both dance pad game controller **110** and musical-instrument game controller **112** are provided in this example in addition to handheld game controller **104**. The illustrated example also includes an interface to a communication medium or communication network **108** such as, for example, the Internet or other communication channel. Both the handheld game controller **104** and the musical-instrument game controller **112** are example of handheld control device with which various embodiments described herein may be utilized.

In one environment, gaming console **102** might be implemented as a PlayStation®, Xbox360®, Wii® or other like gaming console. In another implementation, gaming console **102** might be implemented as a personal computer or other like computing device. A gaming console **102** would typically include a processor or other computing device providing the ability to allow gaming applications, which are typically software applications, to be run thereon. A gaming application might be installed, for example, through the use of CD ROM drives, DVD drives, Ethernet or WiFi download, or other storage medium or communications interfaces. Typically a gaming console **102** can be analogized to a computer system used to run the gaming software. In another environment, the gaming console **102** might be implemented as a personal computer, laptop, tablet, or other computing device.

A monitor **106** or other display is typically provided to allow the gaming environment to be displayed to the game during game play. Monitor **106** can also be used to display menus and other features to the gamer to enhance the game

play environment. Various interfaces might be provided between gaming console **102** and monitor **106** to provide the proper video signal to drive monitor **106**. For example, RGB, NTSC, VGA, and other signal types or specifications can be used to provide communications between gaming console **102** and monitor **106**. In the alternative, a video projector or other viewing mechanism (not shown) can be utilized in place of the monitor **106** to provide similarity display functionality.

As illustrated, speakers can also be provided, separately or with monitor **106**, to provide audible information to the gamer during game play and during set up. For example, in one embodiment, monitor **106** might be implemented as a television with built in speakers that is connected to the gaming console via a coaxial or other audio and video input.

Also illustrated in the example environment is handheld gaming controller **104** that can be used to allow gamers to provide input to the console and to the game software as well as to receive feedback from the console and game software during set up and game play. As described in the background section, handheld gaming controller **104** can include, for example, X, Y, A, B buttons, triggers, analog joysticks, key pads, and other devices to allow the user to provide input to the game. Thus by actuating the various buttons, switches or joysticks, the gamer can control the operation of the game or control characters or vehicles in the game. The interface between gaming console **102** and handheld gaming controller **104**, dance pad game controller **110**, and musical-instrument game controller **112** might be either a wired and/or wireless interface, as may be desired. Likewise, throughout this document, references to communication or signal interfaces can be implemented using wired or wireless interfaces, unless otherwise specified.

Also illustrated in the example of FIG. **1** is a communications connection to a network **108**. For example, a user may wish to connect the gaming console **102** to the Internet or other network or communication medium whereby game information can be downloaded from or uploaded to various websites, online services such as Xbox Live™, or other entities or services. In addition, through a communication medium **108**, gamers might compete amongst other gamers at their gaming systems **100**, even if such other gamers at remote or distant locations. Note that depending on the gaming environment, remote gaming systems **100** might or might not have similar configurations to one another.

Although not depicted, game system **100** can have feedback devices, or stimulus, that can be used to provide sensory feedback from the gaming console to the user. The game system **100** can also have biosensors allowing for biological information (e.g., biometrics) regarding the user to be provided to the console. Both the biosensors and feedback devices can communicate to the gaming console **102** via a separate communication path from the controllers **104**, **110**, and **112**. For example, feedback devices can communicate through the USB ports or like communication ports as those found on gaming consoles such as the XBOX 360®, PlayStation® and personal computing system. Biosensors and feedback devices can also be configured to connect through ports of handheld gaming consoles **102**, often referred to as expansion ports. As a further example, biosensors and feedback devices can communicate with gaming consoles **102** via wireless communication interfaces.

In yet another embodiment, feedback devices and biosensors can communicate with the gaming console via a communication path through the handheld gaming controller **104**. For example, the communication controller can be equipped with another communication interface and the

biosensors, feedback devices, or both are communicatively coupled (whether hard wired or wirelessly) to the handheld gaming controller **104**. As one specific example of this case, a biosensor and feedback device can be configured for communicative coupling to a Nintendo® Wii® controller via the Wii controller's Wii Nunchuck pass-through port. As these examples serve to illustrate, there are a number of mechanisms by which a biosensor or feedback device can be interfaced to a controller or to the gaming console.

Those of ordinary skill in the art will appreciate that various embodiments described herein may be used in conjunction with video game controllers, such as controllers **104** and **112**, and with handheld video gaming device that share features similar to those of the game system **100** and its various devices (e.g., handheld gaming controller **104**).

FIG. **2** provides a cross-sectional view of an example input mechanism **200** in accordance with one embodiment of the systems and methods described herein. Referring now to FIG. **2**, this example includes an interchangeable thumbstick element **202** decoupled from a base component **204**. As shown, the interchangeable element **202** of FIG. **2** is a thumbstick element having a concave surface **206** (e.g., button head), which is generally configured to come in contact with a user's finger (e.g., thumb tip) when in use by the user. For some embodiments, the interchangeable thumbstick element **202** is considered to have a short shaft in comparison to other interchangeable thumbstick elements.

To facilitate removable coupling between the interchangeable thumbstick element **202** and the base component **204**, the interchangeable thumbstick element **202** includes a socket **208** configured to receive a plug **210** embedded in the base component **204**. Those skilled in the art will appreciate that for some embodiments, the socket **208** may be embedded in the base component **205** while the thumbstick element **202** includes the plug **210**. The dimensions of the socket and the plug are chosen such that element **202** can be releasably attached to base **204**. For example, in one embodiment, the cross-sectional diameter of plug **210** and the diameter of socket **208** are sized such that plug **210** fits snugly into socket **208**. In other embodiments, the sidewalls of socket **208** are dimensioned such that they provide a snug fit with the gap around plug **210**. Preferably, the dimensions are such that the device fits snugly enough to not fall off or otherwise become easily dislodged by normal game play. On the other hand, the dimensions are also chosen so that element **202** can be separated from base **204** with the application of a pulling force applied by the user so as to allow for interchangeability. Ideally, the force required to separate the components is no greater than the amount of force that would result in breakage or destruction of either or both components.

A user may couple the interchangeable thumbstick element **202** with the base component **204** by inserting the plug **210** into the socket **208** using reasonable force. For example, the user may push the interchangeable thumbstick element **202** and the base component **204** together until they are seated. The components may also be decoupled using reasonable force. For example, the user pulls the element **202** from base **104** to remove the element **202** from the base **204**, in one embodiment, the force required to separate element **202** from base **104** is the force that can be exerted by an average teenager, or by an average adult. In another embodiment, the force required to separate element **202** from base **104** is the force that can be exerted by a typical five-year old. In other embodiments, to avoid choking hazards, the force required to remove the element **202** from the base **204** is

greater than that force that a young child is able to apply (such as, for example, the force that can be applied by an average 3 or 4 year old). As would be apparent to one of ordinary skill in the art after reading this description, the components can be dimensioned or otherwise configured to require other levels of force to separate the components.

FIG. 3 provides a cross-sectional view of the example input mechanism 200 with the interchangeable thumbstick element 202 and the base component 204 in a coupled configuration.

Those skilled in the art will appreciate that attachment mechanisms other than sockets and plugs may be utilized to removably couple the interchangeable element 202 to the base component 204. Additionally, those skilled in the art will understand that for some embodiments, the attachment mechanism employed may utilize or require one or more tools to facilitate attachment or detachment of the interchangeable element 202 and the base component 204.

FIG. 4 provides a top-perspective view of an example input mechanism 400 in accordance with one embodiment of the systems and methods described herein. The example illustrated in FIG. 4 comprises an interchangeable thumbstick 402 element decoupled from a base component 404. As shown, in this example the interchangeable element 402 is a thumbstick element having a convex contact surface 406, which is generally configured to come in contact with a user's finger (e.g., thumb tip) when in use by the user. For some embodiments, the interchangeable thumbstick element 402 is considered to have a tall shaft in comparison to other interchangeable thumbstick elements. To facilitate removable coupling between the interchangeable element 402 and the base component 404, the interchangeable element 402 includes socket 408 configured to receive a plug 412 embedded into the base component 404. A user may couple the interchangeable thumbstick element 402 with the base component 404 by inserting the plug 412 into the socket 408 using reasonable force (e.g., pushing the interchangeable thumbstick element 402 and the base component 404 until they snap together). FIG. 5 provides a cross-sectional view of the example thumbstick input mechanism 400 once the interchangeable thumbstick element 402 and the base component 404 are coupled together. To further secure the coupling between the socket 408 and the plug 412, the socket walls may further include friction beads 410, configured to increase adhesion between the socket 408 walls and the plug 412 walls.

In the illustrated example, friction beads 410 are longitudinal bars or ridges projecting from the surface of the outer wall of socket 408. These friction beads 410 provide additional friction to maintain the releasable connection between base 404 and element 402. Although friction beads 410 in this example are illustrated as longitudinal bars extending substantially axially along the surface, friction heads 410 can be provided in other shapes and configurations. For example, friction beads 410 can be bars or protuberances aligned in other directions such as diagonally along the surface, helically around the surface or as latitudinal rings about the circumference of the outer surface of the socket wall. As another example, friction beads 410, can be provided in patterns such as sinusoidal, circular, or any other pattern. Additionally, friction beads 410 can be other than the linear examples described above. For example, friction beads 410 can be any pattern of shapes or protuberances about the surface to provide the desired amount of friction to allow releasable attachment with a desired level of force. For example, a pattern of protruding hemispheres, pyramids, cubics, or various polyhedral or other shapes. Additionally,

although illustrated on outer surface of socket 408 wall, friction beads 410 can be provided on any or all of the various mating surfaces of the plug and socket.

In addition to or in place of friction beads 410, various surface materials, surface treatments or other imparted surface properties can be used to affect the amount of friction presented by the coupling. For example, high coefficient-of-friction materials can be used for any or all of the various mating surfaces of the plug and socket. Such surfaces can be provided, for example, by using rough or abraded surfaces, by using polymeric or rubber-like surface materials or other materials providing a desired coefficient of friction.

Those skilled in the art will appreciate that, in addition to friction beads or friction surfaces, other methods of adhesion may be utilized to secure the socket 408 to the plug 412. Likewise, other attachment mechanisms other than sockets and plugs may be utilized in removably coupling the interchangeable element to the base component. For example, barbs, snap-tabs, click lock or other 'snap-fit' components could be used to provide a releasable coupling. As further examples, threaded connectors can be used for screw on/off releasable connection, as can twist & lock fastening mechanisms of various configurations.

Decoupling the interchangeable element from the base may involve using reasonable force to detach the components (e.g., in the example of FIG. 4, pulling the interchangeable thumbstick element 402 and the base component 404 away from each other). As described above, the coupling mechanism can be chosen and implemented to provide the requisite level of force for decoupling. For example, in some embodiments it would be undesirable to have the element decouple with the application of such small forces that the element detaches during normal use or in unwanted circumstances. As a further example, in a gaming application it would be undesirable for the interchangeable element to detach from the base component as a result of forces imparted on the assembly during normal game play. Likewise, it may be undesirable for the interchangeable element to be capable of being detached from the base component by a small child especially in applications where the detachable element presents a choking hazard.

For some embodiments, the base component 404 and the plug 412 are similar to that of base 204, such that the base component 404 can compatibly receive and couple to either the convex thumbstick element 402 of FIG. 4 or the concave thumbstick element 202 of FIG. 2 (based on user preference). More importantly, in various embodiments one or more base components on a device or controller use a common coupling interface with each other. Likewise, multiple interchangeable elements use a common coupling interface complementary to the coupling interface on the base(s). In this manner, each of these base components can accept each of the compatible interchangeable elements, allowing flexibility of customization.

FIG. 6A provides a side view of an example input mechanism 600, in accordance with one embodiment of the systems and methods described herein. In the illustrated example, input mechanism 600 includes an interchangeable element 602 and a base component 604. In this example, interchangeable element 602 is a thumbstick, although other elements could be used. A coupling mechanism may be included with the base component 604 to enable the thumbstick interchangeable element 602 to couple to the base component 604. For some embodiments, the coupling mechanism may comprise a socket configured to receive a plug disposed on the thumbstick interchangeable element 602, or the coupling mechanism may comprise a plug

11

configured to be received by a socket disposed on the thumbstick interchangeable element **602**. FIG. 6B provides a cutaway view of what the base component **604** may look like after a plug **606** is joined to a socket **608**, thereby coupling the thumbstick interchangeable element **602** to the base component **604**.

According to some embodiments, the socket **608** may be disposed on the thumbstick interchangeable element **602** while the plug **606** may be disposed on the base component **604**. As shown in FIG. 6A, the plug **606** may be embedded into the outer surface of the base component **604**. Alternatively, the socket **608** may be disposed on the base component **604** while the plug **606** may be disposed on the thumbstick interchangeable element **602**. Though FIG. 6B illustrates the use of plug and socket elements in coupling the interchangeable element **602** to the base component **604**, some embodiments may utilize alternative elements in facilitate the coupling between the interchangeable element **602** to the base component **604**.

As depicted in FIG. 6B, the base component **604** in some embodiments may include one or more openings **610** configured to allow the passage of air as the thumbstick interchangeable element **602** is coupled to and decoupled from the base component **604**. The openings **610** may be disposed at a coupling point where the base component **604** joins with the thumbstick interchangeable element **602**, as shown in FIG. 6, or may be disposed at other locations that can facilitate passage of air between the thumbstick interchangeable element **602** and the base component **604**.

For some embodiments, the openings **610** prevent or reduce the likelihood of a vacuum forming between the thumbstick interchangeable element **602** and the base component **604** as the two are decoupled. This could be helpful for some embodiments where the formation of a vacuum between the thumbstick interchangeable element **602** and the base component **604** would otherwise make decoupling of the two more difficult. In some embodiments, where a vacuum is utilized to couple the thumbstick interchangeable element **602** to the base component **604**, such opening may be absent from the base component **604** and/or the thumbstick interchangeable element.

FIG. 7 provides a bottom-perspective view of an example input mechanism **700** comprising an interchangeable element **706** coupled to a base component **702** in accordance with one embodiment of the systems and methods described herein. FIG. 7 depicts an input mechanism **700** from the perspective of the underside of the base component **702**. In the illustrated example, element **706** is a thumbstick element, however other interchangeable elements could also be used. As shown in the illustrated example, the base component **702** for some embodiments may include one or more openings **704**, which like the openings **610** of FIG. 6, may be configured to allow the passage of air as the interchangeable element **706** is coupled to and decoupled from the base component **702**. As noted above, such openings may prevent the buildup of pressure between interchangeable element **706** and the base component **702** during coupling. Likewise, one or more openings can help to avoid or reduce the likelihood of a vacuum forming between the interchangeable element **706** and the base component **702** as the two are decoupled.

The openings **704** may be further configured to engage an attachment mechanism to secure the interchangeable element **706** and the base component **702**. For example, the openings **704** may be adapted to receive and engage structural features disposed on a coupling member of the interchangeable element **706** to facilitate releasable attachment

12

of the components. By way of further example, spring tabs extending from interchangeable element **706** can be configured to engage with a surface of openings **704** to retain the components in a connected configuration. Likewise, in a twist-lock configuration, slots can be provided in the base **702** to engage posts on interchangeable element **706**.

In various embodiments, complementary elements of a locking mechanism can be disposed on the interchangeable element **706** and the base component **702**. For instance, one or more tabs may be disposed on the interchangeable element **706**, and the tabs may be configured to engage and be received by the openings **704** disposed on the base component **702**. Alternatively, in various embodiments, the openings **704** may be disposed on the interchangeable element **706** and the tabs may be disposed on the on the base component **702**.

FIG. 8 providing a bottom-perspective view of an example thumbstick interchangeable element **800** in accordance with one embodiment of the systems and methods described herein. In this example, thumbstick interchangeable element **800** comprises a thumbstick contact surface **806** and a shaft including a socket **810**. The socket **810** includes structural protrusions **802** (e.g., tabs) disposed along the outer rim at one end of the socket **810**, and beads **804** disposed along the shaft of the socket **810**. As described herein, the structural protrusions **802** may be utilized by an attachment mechanism configured to secure the example thumbstick interchangeable element **800** to a compatible base component (not shown). To receive and releasably secure the structural protrusions **802** to a compatible base component, the base component may be configured to include openings/receptors that complement the structural protrusions, possible in the form of through holes. As also described herein, the beads **804** may be disposed on the socket **810** of the first interchangeable element, such that the beads **804** contribute to the adhesion between the socket **810** and the plug of the base component to which it is coupled. Though FIG. 8 depicts an interchangeable element **800** as a thumbstick, the interchangeable element **800** may comprise other forms of input elements including, without limitation, joysticks, buttons, switches, and the like.

For example, FIG. 9 provides a cross-sectional view of an example thumbstick input mechanism **900**, in accordance with some embodiments, comprising a based component **902**, the plug **904**, and the thumbstick interchangeable element **800** of FIG. 8, coupled to the base component **902**. As shown in FIG. 9, the structural protrusions **802** disposed on the thumbstick interchangeable element **800** allow the thumbstick interchangeable element **800** to secure itself to the base component **902**. For example, the base component **902** may include one or more openings/receptors **906** configured to receive and engage the structural protrusions **802** of the thumbstick interchangeable element **800**, thereby allowing the thumbstick interchangeable element **800** to be releasably coupled and secured to the base component **902**. The openings/receptors **906** may be disposed in outer walls **908** of the opening where the base component **902** receives the socket **810** and structural protrusions **802** of element **800**.

According to the some embodiments, the base component **902**, in turn, may be coupled to mechanical and/or electronic components that translate the movement of the thumbstick input mechanism to input control information for a handheld control device.

FIG. 10 provides example configurations **1000** of various input mechanisms in accordance with one embodiment of the systems and methods described herein. In the examples

illustrated, each of the configurations **1000** may comprise a common base component **1002** coupled to a different interchangeable thumbstick element (**1004a-j**) in accordance with various embodiments. As shown in FIG. **10**, the interchangeable thumbstick elements **1004a-j** may vary in size, shape, or dimensions. Those skilled in the art will appreciate that elements **1004a-j** do not necessarily have to be thumbsticks but, rather, could function as other forms of input elements including, without limitation, joysticks, buttons, switches and the like. Those skilled in the art will also appreciate that the interchangeable thumbstick elements **1004a-j** may vary in their outer materials, color, or transparency.

For instance, one or more of the interchangeable thumbstick elements **1004a-j** may include an exterior surface comprising an elastomer, neoprene, or textured material, which can enhance grip for a user's finger. Using one or more of the input mechanism configurations **1000** with an input device may enable or otherwise enhance a particular user's ability to provide physical input to the input device. Those skilled in the art will appreciate that for some embodiments, the interchangeable thumbstick elements may comprise mechanical components that enable the input mechanism to provide additional features (e.g., input features or comfort-related features) to the user. For instance, a given interchangeable thumbstick element may include a button the thumbstick, or the thumbstick to be multi-jointed (e.g., easier accessibility or greater range of motion). Those skilled in the art will also appreciate that for various embodiments, an interchangeable element may comprise one or more coupling features that enable the interchangeable element to couple to input mechanisms of different input devices. For example, the interchangeable element may be configured to couple with an input mechanism of a Sony® Playstation® input device and be configured to couple with an input mechanism of a Microsoft® XBOX 360° input device.

FIG. **11** provides an example video game controller **1100**, in accordance with various embodiments, comprising at least one input mechanism **1102**, **1104** or **1106** that comprises an interchangeable thumbstick element coupled to a base component. For example, as shown in FIG. **12**, an example video game controller **1200** comprises an input mechanism **1202** that includes a base component **1204** configured and ready to receive a compatible interchangeable element. As also shown, the base component **1204** may comprise a plug component configured to couple with a socket of the compatible interchangeable element.

FIG. **13** depicts different configurations of the input mechanism **1202** comprising the base component **1204** and different interchangeable elements **1300a-h**. As shown in FIG. **13**, for some embodiments, an interchangeable element may include structural features that cause the interchangeable element to resemble objects that aesthetically please the user. For instance, the interchangeable thumbstick element **1300h** is configured to resemble a skull and once coupled to the base component **1204**, causes the video game controller **1100** to appear as if the skull is mounted to the controller.

FIGS. **14-16** provide example video game controllers **1400**, **1500**, and **1600**, in accordance with various embodiments, comprising input mechanisms that comprise base components coupled to different interchangeable thumbstick elements. In particular, each of the video game controllers **1400**, **1500**, and **1600** as shown comprises two input mechanisms having different interchangeable elements in accordance with some embodiments. By using such embodiments, users can customize different input mechanisms of a

given video game controllers **1400**, **1500**, or **1600** with dissimilar interchangeable elements that provide comfort, ergonomics, or enhanced controllability to a given user.

While various embodiments have been described above with respect to handheld video gaming device, it should be understood that they have been presented by way of example only, and not of limitation. Those of ordinary skill in the art would appreciate that some embodiments may include other handheld control device comprising having input mechanisms, and may include handheld control devices used in non-gaming contexts/environments (e.g., control of unmanned aerial vehicles [UAVs], unmanned ground vehicles, or remote control [R/C] vehicles).

Likewise, the various diagrams may depict an example architectural or other configuration for the invention(s), which is done to aid in understanding the features and functionality that can be included in the invention(s). The invention(s) are not restricted to the illustrated example architectures or configurations, but the desired features can be implemented using a variety of alternative architectures and configurations. Indeed, it will be apparent to one of skill in the art how alternative functional, logical or physical partitioning and configurations can be implemented to implement the desired features of the present invention(s). In addition, a multitude of different constituent module names other than those depicted herein can be applied to the various partitions. Additionally, with regard to flow diagrams, operational descriptions and method claims, the order in which the steps are presented herein shall not mandate that various embodiments be implemented to perform the recited functionality in the same order unless the context dictates otherwise.

Although the inventions are described above in terms of various example embodiments and implementations, it should be understood that the various features, aspects and functionality described in one or more of the individual embodiments are not limited in their applicability to the particular embodiment with which they are described, but instead can be applied, alone or in various combinations, to one or more of the other embodiments of the inventions(s), whether or not such embodiments are described and whether or not such features are presented as being a part of a described embodiment. Thus, the breadth and scope of the present invention(s) should not be limited by any of the above-described example embodiments.

Terms and phrases used in this document, and variations thereof, unless otherwise expressly stated, should be construed as open ended as opposed to limiting. As examples of the foregoing: the term "including" should be read as meaning "including, without limitation" or the like; the term "example" is used to provide example instances of the item in discussion, not an exhaustive or limiting list thereof; the terms "a" or "an" should be read as meaning "at least one," "one or more" or the like; and adjectives such as "conventional," "traditional," "normal," "standard," "known" and terms of similar meaning should not be construed as limiting the item described to a given time period or to an item available as of a given time, but instead should be read to encompass conventional, traditional, normal, or standard technologies that may be available or known now or at any time in the future. Likewise, where this document refers to technologies that would be apparent or known to one of ordinary skill in the art, such technologies encompass those apparent or known to the skilled artisan now or at any time in the future.

The presence of broadening words and phrases such as "one or more," "at least," "but not limited to" or other like

15

phrases in some instances shall not be read to mean that the narrower care is intended or required in instances where such broadening phrases may be absent.

What is claimed is:

1. A handheld video game controller, comprising:
  - an interchangeable cross-shaped directional pad;
  - a plurality of input buttons; and a pair of thumbsticks, each of the pair of thumbsticks comprising
    - an interchangeable thumbstick element comprising a proximal contact surface configured to contact a user's finger and a distal socket extending from the contact surface to a distal end of the thumbstick element, the socket having at least one protrusion that extends to the distal end of the socket and protrudes inward from a wall of the socket, and
    - a base component comprising a convex surface disposed at least partially below a casing of the video game controller and configured to pivot in a multi-directional manner about a center point below the housing, the base component further comprising a plug that extends outward from the convex surface to a proximal end and define a single piece with the convex surface, the base component defining a recessed circumferential wall space about the plug to define an annular channel between the plug and the circumferential wall so that a distal end of the plug is disposed below at least a portion of the convex surface, the plug having at least one recessed groove on an outer surface that receives the at least one protrusion of the socket to align the thumbstick element relative to the base component,

wherein the socket of the interchangeable thumbstick element is configured to releasably couple to the plug of the base component such that a distal end of the socket is positioned in the recessed annular channel and extends below at least a portion of the convex surface.
2. The video game controller of claim 1, wherein the recessed groove of the plug extends to the distal end of the plug in the recessed annular channel of the base component.
3. The video game controller of claim 1, wherein the interchangeable thumbstick element comprises a plurality of interchangeable thumbstick elements of varying size.
4. The video game controller of claim 3, wherein at least two of the plurality of thumbstick elements vary in height.
5. The video game controller of claim 1, wherein the interchangeable thumbstick element comprises a plurality of thumbstick elements, the contact surface of at least two of the plurality of thumbstick elements having a different shape.
6. The video game controller of claim 5, wherein said at least two of the plurality of interchangeable thumbstick elements have a contact surface having a convex or concave shape.
7. The video game controller of claim 1, wherein the plurality of input buttons includes at least four buttons.
8. The video game controller of claim 1, wherein the directional pad is disposed at least partially between the pair of thumbsticks.
9. The video game controller of claim 1, wherein one of the pair of thumbsticks is at least partially disposed laterally between the plurality of input buttons and the directional pad.
10. The video game controller of claim 1, wherein the casing defines a pair of handles of the video game controller.
11. A handheld video game controller, comprising:
  - a plurality of input buttons; and
  - at least one thumbstick comprising

16

- an interchangeable thumbstick element comprising a proximal contact surface configured to contact a user's finger and a distal socket extending from the contact surface to a distal end of the thumbstick element, the socket having at least one protrusion that extends to the distal end of the socket and protrudes inward from a wall of the socket, and
  - a base component comprising a convex surface disposed at least partially below a casing of the video game controller and configured to pivot in a multi-directional manner about a center point below the housing, the base component further comprising a plug that extends outward from the convex surface to a proximal end and define a single piece with the convex surface, the base component defining a recessed circumferential wall space about the plug to define an annular channel between the plug and the circumferential wall so that a distal end of the plug is disposed below at least a portion of the convex surface, the plug having at least one recessed groove on an outer surface that receives the at least one protrusion of the socket to align the thumbstick element relative to the base component,
- wherein the socket of the interchangeable thumbstick element is configured to releasably couple to the plug of the base component such that a distal end of the socket is positioned in the recessed annular channel and extends below at least a portion of the convex surface.

12. The video game controller of claim 11, wherein the interchangeable thumbstick element comprises a plurality of interchangeable thumbstick elements of varying size.

13. A handheld video game controller kit, comprising:
  - a video game controller unit comprising
    - an interchangeable cross-shaped directional pad,
    - a plurality of input buttons,
    - a pair of thumbsticks, each of the pair of thumbsticks comprising
  - a removable thumbstick element comprising a proximal contact surface configured to contact a user's finger and a distal socket extending from the contact surface to a distal end of the removable thumbstick element, the socket having at least one protrusion that extends to the distal end of the socket and protrudes inward from a wall of the socket, and
  - a base component comprising a convex surface disposed at least partially below a casing of the video game controller and configured to pivot in a multi-directional manner about a center point below the housing, the base component further comprising a plug that extends outward from the convex surface to a proximal end and define a single piece with the convex surface, the base component defining a recessed circumferential wall space about the plug to define an annular channel between the plug and the circumferential wall so that a distal end of the plug is disposed below at least a portion of the convex surface; the plug having at least one recessed groove on an outer surface that receives the at least one protrusion of the socket to align the removable thumbstick element relative to the base component, the socket of the thumbstick element being configured to releasably couple to the plug of the base component such that a distal end of the socket is positioned in the recessed annular channel and extends below at least a portion of the convex surface; and

a plurality of interchangeable thumbstick elements configured to replace the removable thumbstick element, at least two of the plurality of interchangeable thumbstick elements having a different size or shape.

14. The kit of claim 13, wherein said at least two of the plurality of interchangeable thumbstick elements vary in height. 5

15. The kit of claim 13, wherein said at least two of the plurality of interchangeable thumbstick elements have a contact surface of different shape, the contact surface configured to contact a user's finger in use. 10

16. The kit of claim 15, wherein said at least two of the plurality of interchangeable thumbstick elements have a contact surface having a convex or concave shape.

17. The kit of claim 13, wherein the plurality of input buttons includes at least four buttons. 15

18. The kit of claim 13, wherein the directional pad is disposed between the pair of thumbsticks.

19. The kit of claim 13, wherein one of the pair of thumbsticks is laterally disposed between the plurality of input buttons and the directional pad. 20

20. The kit of claim 13, wherein the casing defines a pair of handles of the video game controller.

\* \* \* \* \*