



US008295876B1

(12) **United States Patent**
Fujisaki

(10) **Patent No.:** **US 8,295,876 B1**
(45) **Date of Patent:** ***Oct. 23, 2012**

(54) **COMMUNICATION DEVICE**

(76) Inventor: **Iwao Fujisaki**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/026,208**

(22) Filed: **Feb. 12, 2011**

Related U.S. Application Data

(63) Continuation of application No. 12/344,306, filed on Dec. 26, 2008, now Pat. No. 7,917,167, which is a continuation of application No. 10/905,836, filed on Jan. 22, 2005, now abandoned, which is a continuation of application No. 10/711,265, filed on Sep. 7, 2004, now abandoned.

(60) Provisional application No. 60/481,695, filed on Nov. 22, 2003.

(51) **Int. Cl.**
H04M 1/00 (2006.01)

(52) **U.S. Cl.** **455/550.1**; 455/556.1; 455/557; 455/419; 455/420; 455/41.2

(58) **Field of Classification Search** 455/418–420, 455/566, 550.1, 575.1, 90.3, 41.2, 556.1–557
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,934,773 A 6/1990 Becker
4,937,570 A 6/1990 Matsukawa et al.
5,113,427 A 5/1992 Ryoichi et al.
5,272,638 A 12/1993 Martin et al.

5,345,272 A 9/1994 Ersoz et al.
5,353,376 A 10/1994 Oh et al.
5,388,147 A 2/1995 Grimes
5,404,579 A 4/1995 Obayashi et al.
5,405,152 A 4/1995 Katanics et al.
5,414,461 A 5/1995 Kishi et al.
5,418,837 A * 5/1995 Johansson et al. 455/558
5,438,357 A 8/1995 McNelley
5,446,904 A 8/1995 Belt et al.
5,479,476 A 12/1995 Finke-Anlauff
5,530,472 A 6/1996 Bregman et al.
5,532,741 A 7/1996 Tsutsumi
5,542,557 A 8/1996 Koyama et al.
5,543,789 A 8/1996 Behr et al.
5,550,754 A 8/1996 McNelley et al.
5,559,554 A 9/1996 Uekane et al.
5,625,675 A 4/1997 Katsumaru et al.
5,629,741 A 5/1997 Hopper
5,648,768 A 7/1997 Bouve
5,675,630 A 10/1997 Beatty
5,687,331 A 11/1997 Volk et al.
5,732,383 A 3/1998 Foldare et al.

(Continued)

FOREIGN PATENT DOCUMENTS

JP H11/195137 A1 7/1999

(Continued)

OTHER PUBLICATIONS

Audiovox, "POCKET PC Phone User Manual", published on Mar. 19, 2004.


(Continued)

Primary Examiner — Sharad Rampuria

(57) **ABSTRACT**

The mobile phone comprising a CPU which updates battery controller, CCD unit controller, microphone controller, speaker controller, or vibrator controller by utilizing the mobile phone updating data received via antenna.

18 Claims, 1 Drawing Sheet



U.S. PATENT DOCUMENTS

5,758,280 A	5/1998	Kimura	6,567,984 B1	5/2003	Allport
5,772,586 A	6/1998	Heinonen et al.	6,600,975 B2	7/2003	Moriguchi et al.
5,778,304 A	7/1998	Grube et al.	6,606,504 B1	8/2003	Mooney et al.
5,786,846 A	7/1998	Hiroaki	6,611,753 B1	8/2003	Millington
5,802,460 A	9/1998	Parvulescu et al.	6,615,186 B1	9/2003	Kolls
5,805,672 A	9/1998	Barkat et al.	6,618,704 B2	9/2003	Kanevsky et al.
5,812,930 A	9/1998	Zavrel	6,622,018 B1	9/2003	Erekson
5,825,408 A	10/1998	Yuyama et al.	6,630,958 B2	10/2003	Tanaka et al.
5,844,824 A	12/1998	Newman et al.	6,631,271 B1	10/2003	Logan
5,902,349 A	5/1999	Endo et al.	6,647,251 B1	11/2003	Siegle et al.
5,916,024 A	6/1999	Von Kohorn	6,650,877 B1	11/2003	Tarbouriech et al.
5,918,180 A	6/1999	Dimino	6,650,894 B1	11/2003	Berstis et al.
5,959,661 A	9/1999	Isono	6,658,272 B1	12/2003	Lenchik et al.
6,009,336 A	12/1999	Harris et al.	6,658,461 B1	12/2003	Mazo
6,011,973 A	1/2000	Valentine et al.	6,662,023 B1	12/2003	Helle
6,034,715 A	3/2000	Ishida et al.	6,681,120 B1	1/2004	Kim
6,043,752 A	3/2000	Hisada et al.	6,690,932 B1	2/2004	Barnier et al.
6,073,034 A	6/2000	Jacobsen et al.	6,701,148 B1	3/2004	Wilson et al.
6,081,265 A	6/2000	Nakayama et al.	6,707,942 B1	3/2004	Cortopassi et al.
6,115,597 A	9/2000	Kroll et al.	6,711,399 B1	3/2004	Granier
6,128,594 A	10/2000	Gulli et al.	6,725,022 B1	4/2004	Clayton et al.
6,144,848 A	11/2000	Walsh et al.	6,728,531 B1	4/2004	Lee et al.
6,148,212 A	11/2000	Park et al.	6,738,643 B1	5/2004	Harris
6,161,134 A	12/2000	Wang et al.	6,738,711 B2	5/2004	Ohmura et al.
6,167,283 A	12/2000	Korpela et al.	6,763,226 B1	7/2004	McZeal, Jr.
6,192,343 B1	2/2001	Morgan et al.	6,772,174 B1	8/2004	Pettersson
6,198,942 B1	3/2001	Hayashi et al.	6,775,361 B1	8/2004	Arai et al.
6,202,060 B1	3/2001	Tran	6,779,030 B1	8/2004	Dugan et al.
6,216,013 B1	4/2001	Moore et al.	6,788,928 B2	9/2004	Kohinata et al.
6,216,158 B1	4/2001	Luo et al.	6,795,715 B1	9/2004	Kubo et al.
6,222,482 B1	4/2001	Guezic	6,812,954 B1	11/2004	Priestman et al.
6,223,029 B1	4/2001	Stenman et al.	6,819,939 B2	11/2004	Masamura
6,225,944 B1	5/2001	Hayes	6,820,055 B2	11/2004	Saindon et al.
6,236,832 B1	5/2001	Ito	6,836,654 B2	12/2004	Decotignie
6,243,039 B1	6/2001	Elliot	6,850,209 B2	2/2005	Mankins et al.
6,249,720 B1	6/2001	Kubota et al.	6,865,372 B2	3/2005	Mauney et al.
6,253,075 B1	6/2001	Beghtol et al.	6,870,828 B1	3/2005	Giordano, III
6,265,988 B1	7/2001	LeMense et al.	6,883,000 B1	4/2005	Gropper
6,285,317 B1	9/2001	Ong	6,891,525 B2	5/2005	Ogoro
6,285,757 B1	9/2001	Carroll et al.	6,895,084 B1	5/2005	Saylor et al.
6,292,666 B1	9/2001	Siddiqui et al.	6,895,256 B2	5/2005	Harma
6,292,747 B1	9/2001	Amro et al.	6,895,259 B1	5/2005	Blank nee Keller et al.
6,311,011 B1	10/2001	Kuroda	6,898,321 B1	5/2005	Knee et al.
6,311,077 B1	10/2001	Bien	6,898,765 B2	5/2005	Matthews, III et al.
6,332,122 B1	12/2001	Ortega et al.	6,901,383 B1	5/2005	Ricketts et al.
6,333,684 B1	12/2001	Kang	6,904,298 B2	6/2005	Arai et al.
6,363,320 B1	3/2002	Chou	6,912,544 B1	6/2005	Weiner
6,366,651 B1	4/2002	Griffith et al.	6,922,630 B2	7/2005	Maruyama et al.
6,366,782 B1	4/2002	Fumarolo et al.	6,937,868 B2	8/2005	Himmel et al.
6,374,221 B1	4/2002	Haimi-Cohen	6,947,728 B2	9/2005	Tagawa et al.
6,385,466 B1	5/2002	Hirai et al.	6,954,645 B2	10/2005	Tsai et al.
6,385,541 B1	5/2002	Blumberg et al.	6,958,675 B2	10/2005	Maeda et al.
6,385,654 B1	5/2002	Tanaka	6,961,559 B1	11/2005	Chow et al.
6,405,033 B1	6/2002	Kennedy, III et al.	6,968,184 B2	11/2005	Criss et al.
6,411,198 B1	6/2002	Hirai et al.	6,968,206 B1	11/2005	Whitsey-Anderson
6,411,822 B1	6/2002	Kraft	6,970,178 B2	11/2005	Tanioka et al.
6,415,138 B2	7/2002	Sirola et al.	6,970,703 B2	11/2005	Fuchs et al.
6,421,470 B1	7/2002	Nozaki et al.	6,992,699 B1	1/2006	Vance et al.
6,421,602 B1	7/2002	Bullock et al.	6,999,757 B2	2/2006	Bates et al.
6,430,498 B1	8/2002	Maruyama et al.	6,999,802 B2	2/2006	Kim
6,438,380 B1	8/2002	Bi et al.	7,003,598 B2	2/2006	Kavanagh
6,442,404 B1	8/2002	Sakajiri	7,007,239 B1	2/2006	Hawkins et al.
6,445,802 B1	9/2002	Dan	7,012,999 B2	3/2006	Ruckart
6,477,387 B1	11/2002	Jackson et al.	7,019,770 B1	3/2006	Katz
6,486,867 B1	11/2002	Kopp et al.	7,028,077 B2	4/2006	Toshimitsu et al.
6,487,422 B1	11/2002	Lee	7,030,880 B2	4/2006	Tanioka et al.
6,512,919 B2	1/2003	Ogasawara	7,035,666 B2	4/2006	Silberfening
6,518,956 B1	2/2003	Sato	7,058,356 B2	6/2006	Slotznick
6,519,566 B1	2/2003	Boyer et al.	7,076,052 B2	7/2006	Yoshimura
6,526,293 B1	2/2003	Matsuo	7,081,832 B2	7/2006	Nelson et al.
6,529,742 B1	3/2003	Yang	7,085,578 B2	8/2006	Barclay et al.
6,532,035 B1	3/2003	Saari et al.	7,085,739 B1	8/2006	Winter et al.
6,538,558 B2	3/2003	Sakazume et al.	7,089,298 B2	8/2006	Nyman et al.
6,542,750 B2	4/2003	Hendrey et al.	7,106,846 B2	9/2006	Nguyen et al.
6,542,814 B2	4/2003	Polidi et al.	7,107,081 B1	9/2006	Fujisaki
6,553,309 B2 *	4/2003	Uchida et al. 701/409	7,117,152 B1	10/2006	Mukherji et al.
6,553,310 B1	4/2003	Lopke	7,117,504 B2	10/2006	Smith et al.
6,567,745 B2	5/2003	Fuchs et al.	7,126,951 B2	10/2006	Belcea et al.
			7,127,238 B2	10/2006	Vandermeijden et al.

7,127,271	B1	10/2006	Fujisaki	2002/0085700	A1	7/2002	Metcalf
7,130,630	B1	10/2006	Enzmann et al.	2002/0094806	A1	7/2002	Kamimura
7,142,810	B2	11/2006	Oesterling	2002/0097984	A1	7/2002	Abecassis
7,142,890	B2	11/2006	Irimajiri et al.	2002/0098857	A1	7/2002	Ishii
7,190,880	B2	3/2007	Cookson et al.	2002/0102960	A1	8/2002	Lechner
7,218,916	B2	5/2007	Nonami	2002/0103872	A1	8/2002	Watanabe
7,224,851	B2	5/2007	Kinjo	2002/0110246	A1	8/2002	Gosior et al.
7,224,987	B1	5/2007	Bhela et al.	2002/0115469	A1	8/2002	Rekimoto et al.
7,233,781	B2	6/2007	Hunter et al.	2002/0120589	A1	8/2002	Aoki
7,233,795	B1	6/2007	Ryden	2002/0120718	A1	8/2002	Lee
7,239,742	B2	7/2007	Ohtani et al.	2002/0123336	A1	9/2002	Kamada
7,251,255	B1	7/2007	Young	2002/0127997	A1	9/2002	Karlstedt et al.
7,254,408	B2	8/2007	Kim	2002/0133342	A1	9/2002	McKenna
7,260,416	B2	8/2007	Shippee	2002/0137470	A1	9/2002	Baron et al.
7,266,186	B1	9/2007	Henderson	2002/0137503	A1	9/2002	Roderique
7,274,952	B2	9/2007	Hayashi	2002/0137526	A1	9/2002	Shinohara
7,277,711	B2	10/2007	Nyu	2002/0142763	A1	10/2002	Kolsky
7,321,783	B2	1/2008	Kim et al.	2002/0147645	A1	10/2002	Alao et al.
7,346,373	B2	3/2008	Kim	2002/0151326	A1	10/2002	Awada et al.
7,372,447	B1	5/2008	Jacobsen et al.	2002/0151327	A1	10/2002	Levitt
7,383,067	B2	6/2008	Phillips et al.	2002/0154632	A1	10/2002	Wang et al.
7,426,264	B1	9/2008	Henderson	2002/0157101	A1	10/2002	Schrader et al.
7,433,845	B1	10/2008	Flitcroft et al.	2002/0164996	A1	11/2002	Dorenbosch
7,444,168	B2 *	10/2008	Nakagawa et al.	2002/0165850	A1	11/2002	Roberts et al.
7,450,709	B2	11/2008	Gonzalez et al.	2002/0168959	A1	11/2002	Noguchi et al.
7,489,768	B1	2/2009	Strietzel	2002/0173344	A1	11/2002	Cupps et al.
7,532,879	B1	5/2009	Fujisaki	2002/0177407	A1	11/2002	Mitsumoto
7,551,899	B1	6/2009	Nicolas et al.	2002/0178009	A1	11/2002	Firman
7,657,252	B2	2/2010	Futami	2002/0178225	A1	11/2002	Madenberg et al.
7,707,592	B2	4/2010	Wesslen et al.	2002/0183045	A1	12/2002	Emmerson et al.
7,707,602	B2	4/2010	Cragun et al.	2002/0191951	A1	12/2002	Sodeyama et al.
7,769,364	B2	8/2010	Logan et al.	2002/0196378	A1	12/2002	Slobodin et al.
7,787,857	B2	8/2010	Peterman	2002/0198813	A1	12/2002	Patterson et al.
7,787,887	B2	8/2010	Gupta et al.	2002/0198936	A1	12/2002	McIntyre et al.
7,853,295	B1	12/2010	Fujisaki	2003/0003967	A1	1/2003	Ito
7,853,297	B1	12/2010	Fujisaki	2003/0006879	A1	1/2003	Kang et al.
7,873,349	B1	1/2011	Smith et al.	2003/0007556	A1	1/2003	Oura et al.
7,899,410	B2	3/2011	Rakshani et al.	2003/0013483	A1	1/2003	Ausems et al.
7,917,167	B1 *	3/2011	Fujisaki	2003/0014286	A1	1/2003	Cappellini
7,941,141	B2	5/2011	Shoykhet et al.	2003/0016189	A1	1/2003	Abe et al.
7,953,439	B2	5/2011	Rofougaran	2003/0017857	A1	1/2003	Kitson et al.
2001/0000249	A1	4/2001	Oba et al.	2003/0018744	A1	1/2003	Johanson et al.
2001/0005826	A1	6/2001	Shibuya	2003/0018748	A1	1/2003	McKenna, Jr.
2001/0011293	A1	8/2001	Murakami et al.	2003/0032389	A1	2/2003	Kim et al.
2001/0029425	A1	10/2001	Myr	2003/0032406	A1	2/2003	Miner et al.
2001/0035829	A1	11/2001	Yu et al.	2003/0033214	A1	2/2003	Mikkelsen et al.
2001/0037191	A1	11/2001	Furuta et al.	2003/0038800	A1	2/2003	Kawahara
2001/0041590	A1	11/2001	Silberfenig et al.	2003/0045301	A1	3/2003	Wollrab
2001/0049470	A1	12/2001	Mault et al.	2003/0045311	A1	3/2003	Larikka et al.
2002/0002044	A1	1/2002	Naruse et al.	2003/0045329	A1	3/2003	Kinoshita
2002/0002705	A1	1/2002	Byrnes et al.	2003/0045996	A1	3/2003	Yamazaki et al.
2002/0004701	A1	1/2002	Nakano	2003/0050776	A1	3/2003	Blair
2002/0006804	A1	1/2002	Mukai et al.	2003/0052964	A1	3/2003	Priestman et al.
2002/0009978	A1	1/2002	Dukach et al.	2003/0054830	A1	3/2003	Williams et al.
2002/0016724	A1	2/2002	Yang et al.	2003/0055994	A1	3/2003	Herrmann et al.
2002/0019225	A1	2/2002	Miyashita	2003/0061606	A1	3/2003	Hartwig et al.
2002/0026348	A1	2/2002	Fowler et al.	2003/0063732	A1	4/2003	McKnight
2002/0028690	A1	3/2002	McKenna et al.	2003/0065784	A1	4/2003	Herrod
2002/0031120	A1	3/2002	Rakib	2003/0065805	A1	4/2003	Barnes, Jr.
2002/0034292	A1	3/2002	Tuoriniemi	2003/0069693	A1	4/2003	Snapp et al.
2002/0036231	A1	3/2002	Monaghan et al.	2003/0073432	A1	4/2003	Meade, II
2002/0036642	A1	3/2002	Kwon et al.	2003/0083055	A1	5/2003	Riordan et al.
2002/0038219	A1	3/2002	Yanay et al.	2003/0083873	A1	5/2003	Ross et al.
2002/0039914	A1	4/2002	Hama et al.	2003/0084121	A1	5/2003	De Boer et al.
2002/0041262	A1	4/2002	Mukai et al.	2003/0093503	A1	5/2003	Yamaki et al.
2002/0047787	A1	4/2002	Mikkola et al.	2003/0093790	A1	5/2003	Logan et al.
2002/0049742	A1	4/2002	Chan et al.	2003/0099367	A1	5/2003	Okamura
2002/0054068	A1	5/2002	Ellis et al.	2003/0100326	A1	5/2003	Grube et al.
2002/0055350	A1	5/2002	Gupte et al.	2003/0107580	A1	6/2003	Egawa et al.
2002/0058497	A1	5/2002	Jeong	2003/0109251	A1	6/2003	Fujito et al.
2002/0058531	A1	5/2002	Terasaki et al.	2003/0114191	A1	6/2003	Nishimura
2002/0065037	A1	5/2002	Messina et al.	2003/0115240	A1	6/2003	Cho
2002/0065604	A1	5/2002	Sekiyama	2003/0117316	A1	6/2003	Tischer
2002/0066115	A1	5/2002	Wendelrup	2003/0119479	A1	6/2003	Arima et al.
2002/0068558	A1	6/2002	Janik	2003/0119485	A1	6/2003	Ogasawara
2002/0068585	A1	6/2002	Chan et al.	2003/0119562	A1	6/2003	Kokubo
2002/0068599	A1	6/2002	Rodriguez et al.	2003/0120784	A1	6/2003	Johnson et al.
2002/0072395	A1	6/2002	Miramontes	2003/0122779	A1	7/2003	Martin et al.
2002/0082059	A1	6/2002	Nariai et al.	2003/0125008	A1	7/2003	Shimamura


2003/0132928	A1	7/2003	Kori	2005/0120225	A1	6/2005	Kirsch et al.
2003/0135563	A1	7/2003	Bodin et al.	2005/0136949	A1	6/2005	Barnes et al.
2003/0137970	A1	7/2003	Odman	2005/0153681	A1	7/2005	Hanson
2003/0142957	A1	7/2003	Young et al.	2005/0153745	A1	7/2005	Smethers
2003/0144024	A1	7/2003	Luo	2005/0159189	A1	7/2005	Iyer
2003/0148772	A1	8/2003	Ben-Ari	2005/0164684	A1	7/2005	Chen et al.
2003/0153364	A1	8/2003	Osann, Jr.	2005/0165871	A1	7/2005	Barrs et al.
2003/0155413	A1	8/2003	Kovesdi et al.	2005/0166242	A1	7/2005	Matsumoto et al.
2003/0157929	A1	8/2003	Janssen et al.	2005/0186954	A1	8/2005	Kenney
2003/0166399	A1	9/2003	Tokkonen et al.	2005/0191969	A1	9/2005	Mousseau
2003/0169329	A1	9/2003	Parker et al.	2005/0235312	A1	10/2005	Karaoguz et al.
2003/0171113	A1	9/2003	Choi	2005/0257149	A1	11/2005	Kamiya et al.
2003/0174685	A1	9/2003	Hasebe	2005/0261945	A1	11/2005	Mougin et al.
2003/0181201	A1	9/2003	Bomze et al.	2005/0272504	A1	12/2005	Eguchi et al.
2003/0204562	A1	10/2003	Hwang	2005/0282582	A1	12/2005	Slotznick et al.
2003/0208541	A1	11/2003	Musa	2006/0003813	A1	1/2006	Seligmann et al.
2003/0220835	A1	11/2003	Barnes, Jr.	2006/0015819	A1	1/2006	Hawkins et al.
2003/0222762	A1	12/2003	Beigl et al.	2006/0031407	A1	2/2006	Dispensa et al.
2003/0222982	A1	12/2003	Hamdan et al.	2006/0033809	A1	2/2006	Farley
2003/0224760	A1	12/2003	Day	2006/0041923	A1	2/2006	McQuaide, Jr.
2003/0227570	A1	12/2003	Kim et al.	2006/0052100	A1	3/2006	Almgren
2003/0229900	A1	12/2003	Reisman	2006/0059038	A1	3/2006	Iuchi et al.
2003/0236866	A1	12/2003	Light	2006/0073820	A1	4/2006	Craswell et al.
2004/0003307	A1	1/2004	Tsuji	2006/0114100	A1	6/2006	Ghabra et al.
2004/0029640	A1	2/2004	Masuyama et al.	2006/0133590	A1	6/2006	Jiang
2004/0033795	A1	2/2004	Walsh et al.	2006/0140173	A1	6/2006	Hoover
2004/0034692	A1	2/2004	Eguchi et al.	2006/0140387	A1	6/2006	Boldt
2004/0072595	A1	4/2004	Anson et al.	2006/0143655	A1	6/2006	Ellis et al.
2004/0082321	A1	4/2004	Kontianinen	2006/0166650	A1	7/2006	Berger et al.
2004/0092255	A1 *	5/2004	Ji et al. 455/419	2006/0199571	A1	9/2006	Chin et al.
2004/0103303	A1	5/2004	Yamauchi et al.	2006/0206913	A1	9/2006	Jerding et al.
2004/0107072	A1	6/2004	Dietrich et al.	2006/0229114	A2	10/2006	Kim
2004/0114732	A1	6/2004	Choe et al.	2006/0234693	A1	10/2006	Isidore et al.
2004/0117108	A1	6/2004	Nemeth	2006/0234758	A1	10/2006	Parupudi et al.
2004/0128359	A1	7/2004	Horvitz et al.	2006/0284732	A1	12/2006	Brock-Fisher
2004/0132445	A1	7/2004	Rogalski et al.	2007/0015550	A1	1/2007	Kayanuma
2004/0137893	A1	7/2004	Muthuswamy et al.	2007/0050832	A1	3/2007	Wright et al.
2004/0137983	A1	7/2004	Kerr et al.	2007/0061845	A1	3/2007	Barnes, Jr.
2004/0139208	A1	7/2004	Tuli	2007/0109262	A1	5/2007	Oshima et al.
2004/0142678	A1	7/2004	Krasner	2007/0121596	A1	5/2007	Kurapati et al.
2004/0157664	A1	8/2004	Link	2007/0135145	A1	6/2007	Lee et al.
2004/0166832	A1	8/2004	Portman et al.	2007/0135150	A1	6/2007	Ushiki et al.
2004/0166879	A1	8/2004	Meadows et al.	2007/0142047	A1	6/2007	Heeschen
2004/0174863	A1	9/2004	Caspi et al.	2007/0190944	A1	8/2007	Doan et al.
2004/0183937	A1	9/2004	Viinikanoja et al.	2007/0204014	A1	8/2007	Greer et al.
2004/0198374	A1	10/2004	Bajikar	2007/0216760	A1	9/2007	Kondo et al.
2004/0203490	A1	10/2004	Kaplan	2007/0218891	A1	9/2007	Cox
2004/0203520	A1	10/2004	Schirtzinger et al.	2007/0260456	A1	11/2007	Proux et al.
2004/0203577	A1	10/2004	Forman et al.	2007/0262848	A1	11/2007	Berstis et al.
2004/0203904	A1	10/2004	Gwon et al.	2007/0293240	A1	12/2007	Drennan et al.
2004/0203909	A1	10/2004	Koster	2008/0014917	A1	1/2008	Rhoads et al.
2004/0204035	A1	10/2004	Raghuram et al.	2008/0016526	A1	1/2008	Asmussen
2004/0204126	A1	10/2004	Reyes et al.	2008/0016534	A1	1/2008	Ortiz et al.
2004/0204821	A1	10/2004	Tu	2008/0058005	A1	3/2008	Zicker et al.
2004/0204848	A1	10/2004	Matsuo et al.	2008/0194273	A1	8/2008	Kansal et al.
2004/0209649	A1	10/2004	Lord	2008/0242271	A1	10/2008	Schmidt et al.
2004/0216037	A1	10/2004	Hishida et al.	2008/0242283	A1	10/2008	Ruckart
2004/0218738	A1	11/2004	Arai et al.	2008/0250459	A1	10/2008	Roman
2004/0219951	A1	11/2004	Holder	2008/0299989	A1	12/2008	King et al.
2004/0222988	A1	11/2004	Donnelly	2009/0047972	A1	2/2009	Neeraj
2004/0235513	A1	11/2004	O'Connell	2009/0153490	A1	6/2009	Nymark et al.
2004/0235520	A1	11/2004	Cadiz et al.	2009/0186628	A1	7/2009	Yonker et al.
2004/0242240	A1	12/2004	Lin	2009/0197641	A1	8/2009	Rofougaran et al.
2004/0242269	A1	12/2004	Fadell	2009/0290369	A1	11/2009	Schofield et al.
2004/0248586	A1	12/2004	Patel et al.	2010/0030557	A1	2/2010	Molloy et al.
2004/0252197	A1	12/2004	Fraley et al.	2010/0062740	A1	3/2010	Ellis et al.
2004/0257208	A1	12/2004	Huang et al.	2010/0099457	A1	4/2010	Kim
2004/0267628	A1	12/2004	Stillman	2010/0145700	A1	6/2010	Kennewick et al.
2005/0004749	A1	1/2005	Park				
2005/0020301	A1	1/2005	Lee				
2005/0026629	A1	2/2005	Contractor				
2005/0036509	A1	2/2005	Acharya et al.				
2005/0046584	A1	3/2005	Breed				
2005/0048987	A1	3/2005	Glass				
2005/0070257	A1	3/2005	Saarinan et al.				
2005/0090768	A1	4/2005	Brattesani et al.				
2005/0097038	A1	5/2005	Yu et al.				
2005/0107119	A1	5/2005	Lee et al.				
2005/0113080	A1	5/2005	Nishimura				

FOREIGN PATENT DOCUMENTS

JP 2005/216149 A1 8/2005
 WO WO03001457 A1 1/2003

OTHER PUBLICATIONS

Gamespot, "Super Mario Bros. 3", Feb 12, 1990, <<http://www.gamespot.com/nes/action/supermariobros3/index.html?tag=tabs%3Bsummary>>
 HI Corporation's company history (<http://www.hicorp.co.jp/english/corporate/history.html>).
 * cited by examiner .



1

COMMUNICATION DEVICE

CROSS REFERENCE TO RELATED
APPLICATIONS

This application is a continuation of U.S. Ser. No. 12/344, 306, filed Dec. 26, 2008, which is a continuation of U.S. Ser. No. 10/905,836, filed Jan. 22, 2005, which is a continuation of U.S. Ser. No. 10/711,265, filed Sep. 7, 2004, which claims the benefit of U.S. Provisional Application Ser. No. 60/481,695, filed Nov. 22, 2003, all of which are hereby incorporated herein by reference in their entirety.

BACKGROUND OF INVENTION

The invention relates to communication device and more particularly to the communication device which is capable to communicate with another communication device in a wireless fashion.

U.S. Patent Publication No. 20030013483 is introduced as prior art of the present invention of which the summary is the following: "A user interface includes a main screen segregated into various screen areas. At least one of the screen areas is devoted to a system application for displaying status icons, and another of the screen areas is devoted to an interface page which may or may not link to other interface pages which are used for displaying current or recent application information for respective user applications, which user applications may be accessed through interaction with the interface page. The application information may be application status information, recent communication messages (such as e-mail messages, SMS messages, or instant messaging messages) and/or one or more upcoming events or to do items for a user. The user interaction may occur through selection with a pointing device such as a stylus, a fingertip stylus, a finger, or one or more buttons, or even through voice commands. The user interface may also include an area reserved for displaying advertisements." However, this prior art does not disclose the mobile phone comprising a CPU which updates battery controller, CCD unit controller, microphone controller, speaker controller, or vibrator controller by utilizing the mobile phone updating data received via antenna.

For the avoidance of doubt, the number of the prior arts introduced herein (and/or in IDS) may be of a large one, however, applicant has no intent to hide the more relevant prior art(s) in the less relevant ones.

SUMMARY OF INVENTION

It is an object of the present invention to provide a device capable to implement a plurality of functions.

It is another object of the present invention to provide merchandise to merchants attractive to the customers in the U.S.

It is another object of the present invention to provide mobility to the users of communication device.

It is another object of the present invention to provide more convenience to the customers in the U.S.

It is another object of the present invention to provide more convenience to the users of communication device or any tangible thing in which the communication device is fixedly or detachably (i.e., removably) installed.

It is another object of the present invention to overcome the shortcomings associated with the foregoing prior art.

The present invention introduces the mobile phone comprising a CPU which updates battery controller, CCD unit

2

controller, microphone controller, speaker controller, or vibrator controller by utilizing the mobile phone updating data received via antenna.

BRIEF DESCRIPTION OF DRAWINGS

The above and other aspects, features, and advantages of the invention will be better understood by reading the following more particular description of the invention, presented in conjunction with the following drawing, wherein:

FIG. 1 is a block diagram illustrating an exemplary embodiment of the present invention.

DETAILED DESCRIPTION

Paragraph [0020]—The following description is of the best presently contemplated mode of carrying out the present invention. This description is not to be taken in a limiting sense but is made merely for the purpose of describing the general principles of the invention. For example, each description of random access memory in this specification illustrate(s) only one function or mode in order to avoid complexity in its explanation, however, such description does not mean that only one function or mode can be implemented at a time. In other words, more than one function or mode can be implemented simultaneously by way of utilizing the same random access memory. In addition, the figure number is cited after the elements in parenthesis in a manner for example 'RAM 206 (FIG. 1)'. It is done so merely to assist the readers to have a better understanding of this specification, and must not be used to limit the scope of the claims in any manner since the figure numbers cited are not exclusive. There are only few data stored in each storage area described in this specification. This is done so merely to simplify the explanation and, thereby, to enable the reader of this specification to understand the content of each function with less confusion. Therefore, more than few data (hundreds and thousands of data, if necessary) of the same kind, not to mention, are preferred to be stored in each storage area to fully implement each function described herein. The scope of the invention should be determined by referencing the appended claims.

Paragraph [0021]—FIG. 1 is a simplified block diagram of the Communication Device 200 utilized in the present invention. Referring to FIG. 1, Communication Device 200 includes CPU 211 which controls and administers the overall function and operation of Communication Device 200. CPU 211 uses RAM 206 to temporarily store data and/or to perform calculation to perform its function, and to implement the present invention, modes, functions, and systems explained hereinafter. Video Processor 202 generates analog and/or digital video signals which are displayed on LCD 201. ROM 207 stores the data and programs which are essential to operate Communication Device 200. Wireless signals are received by Antenna 218 and processed by Signal Processor 208. Input signals are input by Input Device 210, such as a dial pad, a joystick, and/or a keypad, and the signals are transferred via Input Interface 209 and Data Bus 203 to CPU 211. Indicator 212 is an LED lamp which is designed to output different colors (e.g., red, blue, green, etc). Analog audio data is input to Microphone 215. A/D 213 converts the analog audio data into a digital format. Speaker 216 outputs analog audio data which is converted into an analog format from digital format by D/A 204. Sound Processor 205 produces digital audio signals that are transferred to D/A 204 and also processes the digital audio signals transferred from A/D 213. CCD Unit 214

captures video image which is stored in RAM 206 in a digital format. Vibrator 217 vibrates the entire device by the command from CPU 211.

Paragraph [0022]—As another embodiment, LCD 201 or LCD 201/Video Processor 202 may be separated from the other elements described in FIG. 1, and be connected in a wireless fashion to be wearable and/or head-mountable.

Paragraph [0023]—When Communication Device 200 is in the voice communication mode, the analog audio data input to Microphone 215 is converted to a digital format by A/D 213 and transmitted to another device via Antenna 218 in a wireless fashion after being processed by Signal Processor 208, and the wireless signal representing audio data which is received via Antenna 218 is output from Speaker 216 after being processed by Signal Processor 208 and converted to analog signal by D/A 204. For the avoidance of doubt, the definition of Communication Device 200 in this specification includes so-called 'PDA'. The definition of Communication Device 200 also includes in this specification any device which is mobile and/or portable and which is capable to send and/or receive audio data, text data, image data, video data, and/or other types of data in a wireless fashion via Antenna 218. The definition of Communication Device 200 further includes any micro device embedded or installed into devices and equipments (e.g., VCR, TV, tape recorder, heater, air conditioner, fan, clock, micro wave oven, dish washer, refrigerator, oven, washing machine, dryer, door, window, automobile, motorcycle, and modem) to remotely control these devices and equipments. The size of Communication Device 200 is irrelevant. Communication Device 200 may be installed in houses, buildings, bridges, boats, ships, submarines, airplanes, and spaceships, and firmly fixed therein.

Paragraph [0024]—This Paragraph [0024] illustrate(s) the elements of Communication Device 200. The elements of Communication Device 200 described in this Paragraph [0024] is identical to the ones described in FIG. 1, except Communication Device 200 has new element, i.e., LED 219. Here, LED 219 receives infra red signals from other wireless devices, which are transferred to CPU 211 via Data Bus 203. LED 219 also sends infra red signals in a wireless fashion which are composed by CPU 211 and transferred via Data Bus 203. As the second embodiment, LED 219 may be connected to Signal Processor 208. Here, LED 219 transfers the received infra red signals to Signal Processor 208, and Signal Processor 208 processes and converts the signals to a CPU readable format which are transferred to CPU 211 via Data Bus 203. The data produced by CPU 211 are processed by Signal Processor 208 and transferred to another device via LED 219 in a wireless fashion. The task of LED 219 is as same as that of Antenna 218 described in FIG. 1 except that LED 219 utilizes infra red signals for implementing wireless communication in the second embodiment. For the avoidance of doubt, the reference to FIG. 1 (e.g., referring to FIG. 1 in parenthesis) automatically refers to this Paragraph [0024] in this specification.

Paragraph [0025]—This Paragraph [0025] illustrate(s) the data stored in Host H. In the present embodiment, Host H includes Host Information Storage Area H00a which stores various types of data to assist and/or co-operate with Communication Device 200 to implement all modes, functions, and systems described in this specification. As another embodiment, Host H may be composed of a plurality of computers, i.e., one master computer and a plurality of slave computers, wherein the master computer is connected to the plurality of slave computers. As another embodiment, Host H may also be composed of a plurality of master computers by way of utilizing peer-to-peer connection.

Paragraph [0026]—<<Multiple Language Displaying Function>>

Paragraph [0027]—Paragraph [0028] through Paragraph [0076] illustrate the multiple language displaying function wherein a language is selected from a plurality of languages, such as English, Japanese, French, and German, which is utilized to operate Communication Device 200.

Paragraph [0028]—This Paragraph [0028] illustrates the storage area included in RAM 206 (FIG. 1). In the present embodiment, RAM 206 includes Multiple Language Displaying Info Storage Area 20654a of which the data and the software programs stored therein are described in Paragraph [0030].

Paragraph [0029]—The data and/or the software programs stored in Multiple Language Displaying Info Storage Area 20654a (Paragraph [0028]) may be downloaded from Host H (Paragraph [0025]).

Paragraph [0030]—This Paragraph [0030] illustrates the storage areas included in Multiple Language Displaying Info Storage Area 20654a (Paragraph [0028]). In the present embodiment, Multiple Language Displaying Info Storage Area 20654a includes Multiple Language Displaying Data Storage Area 20654b and Multiple Language Displaying Software Storage Area 20654c. Multiple Language Displaying Data Storage Area 20654b stores the data necessary to implement the present function, such as the ones described in Paragraph [0031] through Paragraph [0039]. Multiple Language Displaying Software Storage Area 20654c stores the software programs necessary to implement the present function, such as the ones described in Paragraph [0040].

Paragraph [0031]—This Paragraph [0031] illustrates the storage areas included in Multiple Language Displaying Data Storage Area 20654b (Paragraph [0030]). In the present embodiment, Multiple Language Displaying Data Storage Area 20654b includes Language Tables Storage Area 20654b1, Language Type Data Storage Area 20654b2, Language Item Data Storage Area 20654b3, and Selected Language Table ID Storage Area 20654b4. Language Tables Storage Area 20654b1 stores the data described in Paragraph [0032]. Language Type Data Storage Area 20654b2 stores the data described in Paragraph [0038]. Language Item Data Storage Area 20654b3 stores the data described in Paragraph [0039]. Selected Language Table ID Storage Area 20654b4 stores the language table ID selected in S4s of Paragraph [0042], Paragraph [0051], Paragraph [0060], and Paragraph [0069].

Paragraph [0032]—This Paragraph [0032] illustrates the storage areas included in Language Tables Storage Area 20654b1 (Paragraph [0031]). In the present embodiment, Language Tables Storage Area 20654b1 includes Language Table#1 Storage Area 20654b1a, Language Table#2 Storage Area 20654b1b, Language Table#3 Storage Area 20654b1c, and Language Table#4 Storage Area 20654b1d. Language Table#1 Storage Area 20654b1a stores the data described in Paragraph [0033]. Language Table#2 Storage Area 20654b1b stores the data described in Paragraph [0035]. Language Table#3 Storage Area 20654b1c stores the data described in Paragraph [0036]. Language Table#4 Storage Area 20654b1d stores the data described in Paragraph [0037].

Paragraph [0033]—This Paragraph [0033] illustrates the data stored in Language Table#1 Storage Area 20654b1a (Paragraph [0032]). In the present embodiment, Language Table#1 Storage Area 20654b1a comprises two columns, i.e., 'Language Item ID' and 'Language Text Data'. Column 'Language Item ID' stores the language item IDs, and each language item ID represents the identification of the corresponding language text data.

5

Paragraph [0034]—Column ‘Language Text Data’ stores the language text data, and each language text data represents the English text data displayed on LCD 201 (FIG. 1). In the present embodiment, Language Table#1 Storage Area 20654b1a stores the following data: the language item ID ‘Language Item#1’ and the corresponding language text data ‘Open file’; the language item ID ‘Language Item#2’ and the corresponding language text data ‘Close file’; the language item ID ‘Language Item#3’ and the corresponding language text data ‘Delete’; the language item ID ‘Language Item#4’ and the corresponding language text data ‘Copy’; the language item ID ‘Language Item#5’ and the corresponding language text data ‘Cut’; the language item ID ‘Language Item#6’ and the corresponding language text data ‘Paste’; the language item ID ‘Language Item#7’ and the corresponding language text data ‘Insert’; the language item ID ‘Language Item#8’ and the corresponding language text data ‘File’; the language item ID ‘Language Item#9’ and the corresponding language text data ‘Edit’; the language item ID ‘Language Item#10’ and the corresponding language text data ‘View’; the language item ID ‘Language Item#11’ and the corresponding language text data ‘Format’; the language item ID ‘Language Item#12’ and the corresponding language text data ‘Tools’; the language item ID ‘Language Item#13’ and the corresponding language text data ‘Window’; the language item ID ‘Language Item#14’ and the corresponding language text data ‘Help’; the language item ID ‘Language Item#15’ and the corresponding language text data ‘My Network’; the language item ID ‘Language Item#16’ and the corresponding language text data ‘Trash’; the language item ID ‘Language Item#17’ and the corresponding language text data ‘Local Disk’; the language item ID ‘Language Item#18’ and the corresponding language text data ‘Save’; the language item ID ‘Language Item#19’ and the corresponding language text data ‘Yes’; the language item ID ‘Language Item#20’ and the corresponding language text data ‘No’; and the language item ID ‘Language Item#21’ and the corresponding language text data ‘Cancel’.

Paragraph [0035]—This Paragraph [0035] illustrates the data stored in Language Table#1 Storage Area 20654b1b (Paragraph [0032]). In the present embodiment, Language Table#1 Storage Area 20654b1b comprises two columns, i.e., ‘Language Item ID’ and ‘Language Text Data’. Column ‘Language Item ID’ stores the language item IDs, and each language item ID represents the identification of the corresponding language text data. Column ‘Language Text Data’ stores the language text data, and each language text data represents the Japanese text data displayed on LCD 201 (FIG. 1). In the present embodiment, Language Table#1 Storage Area 20654b1b stores the following data: the language item ID ‘Language Item#1’ and the corresponding language text data meaning ‘Open file’ in Japanese; the language item ID ‘Language Item#2’ and the corresponding language text data meaning ‘Close file’ in Japanese; the language item ID ‘Language Item#3’ and the corresponding language text data meaning ‘Delete’ in Japanese; the language item ID ‘Language Item#4’ and the corresponding language text data meaning ‘Copy’ in Japanese; the language item ID ‘Language Item#5’ and the corresponding language text data meaning ‘Cut’ in Japanese; the language item ID ‘Language Item#6’ and the corresponding language text data meaning ‘Paste’ in Japanese; the language item ID ‘Language Item#7’ and the corresponding language text data meaning ‘Insert’ in Japanese; the language item ID ‘Language Item#8’ and the corresponding language text data meaning ‘File’ in Japanese; the language item ID ‘Language Item#9’ and the corresponding language text data meaning ‘Edit’ in Japanese; the language

6

item ID ‘Language Item#10’ and the corresponding language text data meaning ‘View’ in Japanese; the language item ID ‘Language Item#11’ and the corresponding language text data meaning ‘Format’ in Japanese; the language item ID ‘Language Item#12’ and the corresponding language text data meaning ‘Tools’ in Japanese; the language item ID ‘Language Item#13’ and the corresponding language text data meaning ‘Window’ in Japanese; the language item ID ‘Language Item#14’ and the corresponding language text data meaning ‘Help’ in Japanese; the language item ID ‘Language Item#15’ and the corresponding language text data meaning ‘My Network’ in Japanese; the language item ID ‘Language Item#16’ and the corresponding language text data meaning ‘Trash’ in Japanese; the language item ID ‘Language Item#17’ and the corresponding language text data meaning ‘Local Disk’ in Japanese; the language item ID ‘Language Item#18’ and the corresponding language text data meaning ‘Save’ in Japanese; the language item ID ‘Language Item#19’ and the corresponding language text data meaning ‘Yes’ in Japanese; the language item ID ‘Language Item#20’ and the corresponding language text data meaning ‘No’ in Japanese; and the language item ID ‘Language Item#21’ and the corresponding language text data meaning ‘Cancel’ in Japanese.

Paragraph [0036]—This Paragraph [0036] illustrates the data stored in Language Table#1 Storage Area 20654b1c (Paragraph [0032]). In the present embodiment, Language Table#1 Storage Area 20654b1c comprises two columns, i.e., ‘Language Item ID’ and ‘Language Text Data’. Column ‘Language Item ID’ stores the language item IDs, and each language item ID represents the identification of the corresponding language text data. Column ‘Language Text Data’ stores the language text data, and each language text data represents the French text data displayed on LCD 201 (FIG. 1). In the present embodiment, Language Table#1 Storage Area 20654b1c stores the following data: the language item ID ‘Language Item#1’ and the corresponding language text data ‘French#1’ meaning ‘Open file’ in French; the language item ID ‘Language Item#2’ and the corresponding language text data ‘French#2’ meaning ‘Close file’ in French; the language item ID ‘Language Item#3’ and the corresponding language text data ‘French#3’ meaning ‘Delete’ in French; the language item ID ‘Language Item#4’ and the corresponding language text data ‘French#4’ meaning ‘Copy’ in French; the language item ID ‘Language Item#5’ and the corresponding language text data ‘French#5’ meaning ‘Cut’ in French; the language item ID ‘Language Item#6’ and the corresponding language text data ‘French#6’ meaning ‘Paste’ in French; the language item ID ‘Language Item#7’ and the corresponding language text data ‘French#7’ meaning ‘Insert’ in French; the language item ID ‘Language Item#8’ and the corresponding language text data ‘French#8’ meaning ‘File’ in French; the language item ID ‘Language Item#9’ and the corresponding language text data ‘French#9’ meaning ‘Edit’ in French; the language item ID ‘Language Item#10’ and the corresponding language text data ‘French#10’ meaning ‘View’ in French; the language item ID ‘Language Item#11’ and the corresponding language text data ‘French#11’ meaning ‘Format’ in French; the language item ID ‘Language Item#12’ and the corresponding language text data ‘French#12’ meaning ‘Tools’ in French; the language item ID ‘Language Item#13’ and the corresponding language text data ‘French#13’ meaning ‘Window’ in French; the language item ID ‘Language Item#14’ and the corresponding language text data ‘French#14’ meaning ‘Help’ in French; the language item ID ‘Language Item#15’ and the corresponding language text data ‘French#15’ meaning ‘My Network’ in French; the language item ID ‘Language Item#16’ and the corresponding

language text data 'French#16' meaning 'Trash' in French; the language item ID 'Language Item#17' and the corresponding language text data 'French#17' meaning 'Local Disk' in French; the language item ID 'Language Item#18' and the corresponding language text data 'French#18' meaning 'Save' in French; the language item ID 'Language Item#19' and the corresponding language text data 'French#19' meaning 'Yes' in French; the language item ID 'Language Item#20' and the corresponding language text data 'French#20' meaning 'No' in French; and the language item ID 'Language Item#21' and the corresponding language text data 'French#21' meaning 'Cancel' in French.

Paragraph [0037]—This Paragraph [0037] illustrates the data stored in Language Table#1 Storage Area **20654b1d** (Paragraph [0032]). In the present embodiment, Language Table#1 Storage Area **20654b1d** comprises two columns, i.e., 'Language Item ID' and 'Language Text Data'. Column 'Language Item ID' stores the language item IDs, and each language item ID represents the identification of the corresponding language text data. Column 'Language Text Data' stores the language text data, and each language text data represents the German text data displayed on LCD **201** (FIG. 1). In the present embodiment, Language Table#1 Storage Area **20654b1d** stores the following data: the language item ID 'Language Item#1' and the corresponding language text data 'German#1' meaning 'Open file' in German; the language item ID 'Language Item#2' and the corresponding language text data 'German#2' meaning 'Close file' in German; the language item ID 'Language Item#3' and the corresponding language text data 'German#3' meaning 'Delete' in German; the language item ID 'Language Item#4' and the corresponding language text data 'German#4' meaning 'Copy' in German; the language item ID 'Language Item#5' and the corresponding language text data 'German#5' meaning 'Cut' in German; the language item ID 'Language Item#6' and the corresponding language text data 'German#6' meaning 'Paste' in German; the language item ID 'Language Item#7' and the corresponding language text data 'German#7' meaning 'Insert' in German; the language item ID 'Language Item#8' and the corresponding language text data 'German#8' meaning 'File' in German; the language item ID 'Language Item#9' and the corresponding language text data 'German#9' meaning 'Edit' in German; the language item ID 'Language Item#10' and the corresponding language text data 'German#10' meaning 'View' in German; the language item ID 'Language Item#11' and the corresponding language text data 'German#11' meaning 'Format' in German; the language item ID 'Language Item#12' and the corresponding language text data 'German#12' meaning 'Tools' in German; the language item ID 'Language Item#13' and the corresponding language text data 'German#13' meaning 'Window' in German; the language item ID 'Language Item#14' and the corresponding language text data 'German#14' meaning 'Help' in German; the language item ID 'Language Item#15' and the corresponding language text data 'German#15' meaning 'My Network' in German; the language item ID 'Language Item#16' and the corresponding language text data 'German#16' meaning 'Trash' in German; the language item ID 'Language Item#17' and the corresponding language text data 'German#17' meaning 'Local Disk' in German; the language item ID 'Language Item#18' and the corresponding language text data 'German#18' meaning 'Save' in German; the language item ID 'Language Item#19' and the corresponding language text data 'German#19' meaning 'Yes' in German; the language item ID 'Language Item#20' and the corresponding language text data 'German#20' meaning 'No' in German; and the language

item ID 'Language Item#21' and the corresponding language text data 'German#21' meaning 'Cancel' in German.

Paragraph [0038]—This Paragraph [0038] illustrates data stored in Language Type Data Storage Area **20654b2** (Paragraph [0031]). In the present embodiment, Language Type Data Storage Area **20654b2** comprises two columns, i.e., 'Language Table ID' and 'Language Type Data'. Column 'Language Table ID' stores the language table ID, and each language table ID represents the identification of the storage areas included in Language Tables Storage Area **20654b1** (Paragraph [0032]). Column 'Language Type Data' stores the language type data, and each language type data represents the type of the language utilized in the language table of the corresponding language table ID. In the present embodiment, Language Type Data Storage Area **20654b2** stores the following data: the language table ID 'Language Table#1' and the corresponding language type data 'English'; the language table ID 'Language Table#2' and the corresponding language type data 'Japanese'; the language table ID 'Language Table#3' and the corresponding language type data 'French'; and the language table ID 'Language Table#4' and the corresponding language type data 'German'. Here, the language table ID 'Language Table#1' is an identification of Language Table#1 Storage Area **20654b1a** (Paragraph [0033]); the language table ID 'Language Table#2' is an identification of Language Table#2 Storage Area **20654b1b** (Paragraph [0035]); the language table ID 'Language Table#3' is an identification of Language Table#3 Storage Area **20654b1c** (Paragraph [0036]); and the language table ID 'Language Table#4' is an identification of Language Table#4 Storage Area **20654b1d** (Paragraph [0037]).

Paragraph [0039]—This Paragraph [0039] illustrates the data stored in Language Item Data Storage Area **20654b3** (Paragraph [0031]). In the present embodiment, Language Item Data Storage Area **20654b3** comprises two columns, i.e., 'Language Item ID' and 'Language Item Data'. Column 'Language Item ID' stores the language item IDs, and each language item ID represents the identification of the corresponding language item data. Column 'Language Item Data' stores the language item data, and each language item data represents the content and/or the meaning of the language text data displayed on LCD **201** (FIG. 1). In the present embodiment, Language Item Data Storage Area **20654b3** stores the following data: the language item ID 'Language Item#1' and the corresponding language item data 'Open file'; the language item ID 'Language Item#2' and the corresponding language item data 'Close file'; the language item ID 'Language Item#3' and the corresponding language item data 'Delete'; the language item ID 'Language Item#4' and the corresponding language item data 'Copy'; the language item ID 'Language Item#5' and the corresponding language item data 'Cut'; the language item ID 'Language Item#6' and the corresponding language item data 'Paste'; the language item ID 'Language Item#7' and the corresponding language item data 'Insert'; the language item ID 'Language Item#8' and the corresponding language item data 'File'; the language item ID 'Language Item#9' and the corresponding language item data 'Edit'; the language item ID 'Language Item#10' and the corresponding language item data 'View'; the language item ID 'Language Item#11' and the corresponding language item data 'Format'; the language item ID 'Language Item#12' and the corresponding language item data 'Tools'; the language item ID 'Language Item#13' and the corresponding language item data 'Window'; the language item ID 'Language Item#14' and the corresponding language item data 'Help'; the language item ID 'Language Item#15' and the corresponding language item data 'My Network'; the language

item ID 'Language Item#16' and the corresponding language item data 'Trash'; the language item ID 'Language Item#17' and the corresponding language item data 'Local Disk'; the language item ID 'Language Item#18' and the corresponding language item data 'Save'; the language item ID 'Language Item#19' and the corresponding language item data 'Yes'; the language item ID 'Language Item#20' and the corresponding language item data 'No'; and the language item ID 'Language Item#21' and the corresponding language item data 'Cancel'. Primarily, the data stored in column 'Language Item Data' are same as the ones stored in column 'Language Text Data' of Language Table#1 Storage Area **20654b1a** (Paragraph [0033]).

Paragraph [0040]—This Paragraph [0040] illustrates the software program stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0030]). In the present embodiment, Multiple Language Displaying Software Storage Area **20654c** stores Language Selecting Software **20654c1**, Selected Language Displaying Software **20654c2**, Language Text Data Displaying Software For Word Processor **20654c3a**, Language Text Data Displaying Software For Word Processor **20654c3b**, and Language Text Data Displaying Software For Explorer **20654c4**. Language Selecting Software **20654c1** is the software program described in Paragraph [0042], Paragraph [0051], Paragraph [0060], and Paragraph [0069]. Selected Language Displaying Software **20654c2** is the software program described in Paragraph [0043], Paragraph [0052], Paragraph [0061], and Paragraph [0070]. Language Text Data Displaying Software For Word Processor **20654c3a** is the software program described in Paragraph [0044], Paragraph [0053], Paragraph [0062], and Paragraph [0071]. Language Text Data Displaying Software For Word Processor **20654c3b** is the software program described in Paragraph [0046], Paragraph [0055], Paragraph [0064], and Paragraph [0073]. Language Text Data Displaying Software For Explorer **20654c4** is the software program described in Paragraph [0048], Paragraph [0057], Paragraph [0066], and Paragraph [0075].

Paragraph [0041]—<<Multiple Language Displaying Function—Utilizing English>>

Paragraph [0042]—This Paragraph [0042] illustrates Language Selecting Software **20654c1** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which selects the language utilized to operate Communication Device **200** from a plurality of languages. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves the language type data from Language Type Data Storage Area **20654b2** (Paragraph [0038]) (S1), and Displays a list of available languages on LCD **201** (FIG. 1) (S2). In the present example, the following languages are displayed on LCD **201**: English, Japanese, French, and German. A certain language is selected therefrom by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S3). Assume that 'English' is selected in S3. CPU **211** then identifies the language table ID corresponding to the language type data in Language Type Data Storage Area **20654b2** (Paragraph [0038]), and stores the language table ID (Language Table#1) in Selected Language Table ID Storage Area **20654b4** (Paragraph [0031]) (S4).

Paragraph [0043]—This Paragraph [0043] illustrates Selected Language Displaying Software **20654c2** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays and operates with the language selected in S3 of Paragraph [0042] (i.e., English). In the present embodiment, when Communication Device **200** is powered on (S1), CPU **211** (FIG. 1) of Communication Device **200** retrieves the selected language table

ID (Language Table#1) from Selected Language Table ID Storage Area **20654b4** (Paragraph [0031]) (S2). CPU **211** then identifies the storage area corresponding to the language table ID selected in S2 (Language Table#1 Storage Area **20654b1a** (Paragraph [0033])) in Language Tables Storage Area **20654b1** (Paragraph [0032]) (S3). Language text data displaying process is initiated thereafter of which the details are described hereinafter (S4).

Paragraph [0044]—This Paragraph [0044] illustrates Language Text Data Displaying Software For Word Processor **20654c3a** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays the language text data at the time a word processor, such as MS Word and WordPerfect is executed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** executes a word processor in response to the signal input by the user of Communication Device **200** indicating to activate and execute the word processor (S1). In the process of displaying the word processor on LCD **201** (FIG. 1), the following steps of S2 through S8 are implemented. Namely, CPU **211** identifies the language item ID 'Language Item#8' in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data 'File' at the predetermined location in the word processor (S2). CPU **211** identifies the language item ID 'Language Item#9' in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data 'Edit' at the predetermined location in the word processor (S3). CPU **211** identifies the language item ID 'Language Item#10' in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data 'View' at the predetermined location in the word processor (S4). CPU **211** identifies the language item ID 'Language Item#11' in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data 'Format' at the predetermined location in the word processor (S5). CPU **211** identifies the language item ID 'Language Item#12' in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data 'Tools' at the predetermined location in the word processor (S6). CPU **211** identifies the language item ID 'Language Item#13' in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data 'Window' at the predetermined location in the word processor (S7). CPU **211** identifies the language item ID 'Language Item#14' in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data 'Help' at the predetermined location in the word processor (S8). Alphanumeric data is input to the word processor by utilizing Input Device **210** (FIG. 1) or via voice recognition system thereafter (S9).

Paragraph [0045]—This Paragraph [0045] illustrates the data displayed on LCD **201** (FIG. 1) of Communication Device **200** at the time Language Text Data Displaying Software For Word Processor **20654c3a** (Paragraph [0044]) is implemented. In the present embodiment, the word processor described in Paragraph [0044] is primarily composed of Menu Bar **20154MB** and Alphanumeric Data Input Area **20154ADIA** wherein the language text data described in S2 through S8 of Paragraph [0044] are displayed on Menu Bar **20154MB** and alphanumeric data are input in Alphanumeric Data Input Area **20154ADIA**. In the present embodiment, **20154MBF** is the language text data processed in S2 of the previous paragraph; **20154MBE** is the language text data processed in S3 of the previous paragraph; **20154MBV** is the language text data processed in S4 of the previous paragraph; **20154MBF** is the language text data processed in S5 of the

11

previous paragraph; **20154MBT** is the language text data processed in **S6** of the previous paragraph; **20154MBW** is the language text data processed in **S7** of the previous paragraph; and **20154MBH** is the language text data processed in **S8** of the previous paragraph.

Paragraph [0046]—This Paragraph [0046] illustrates Language Text Data Displaying Software For Word Processor **20654c3b** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays a prompt on LCD **201** (FIG. 1) at the time a word processor is closed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** initiates the closing process of the word processor in response to the signal input by the user of Communication Device **200** indicating to close the word processor (**S1**). In the process of closing the word processor, the following steps of **S2** through **S5** are implemented. Namely, CPU **211** identifies the language item ID ‘Language Item#18’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘Save’ at the predetermined location in the word processor (**S2**). CPU **211** identifies the language item ID ‘Language Item#19’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘Yes’ at the predetermined location in the word processor (**S3**). CPU **211** identifies the language item ID ‘Language Item#20’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘No’ at the predetermined location in the word processor (**S4**). CPU **211** identifies the language item ID ‘Language Item#21’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘Cancel’ at the predetermined location in the word processor (**S5**). The save signal indicating to save the alphanumeric data input in **S9** of Paragraph [0044] is input by utilizing Input Device **210** (FIG. 1) or via voice recognition system, assuming that the user of Communication Device **200** intends to save the data (**S6**), and the data are saved in a predetermined location in RAM **206** (FIG. 1) (**S7**). The word processor is closed thereafter (**S8**).

Paragraph [0047]—This Paragraph [0047] illustrates the data displayed on LCD **201** (FIG. 1) of Communication Device **200** at the time Language Text Data Displaying Software For Word Processor **20654c3b** (Paragraph [0046]) is implemented. In the present embodiment, Prompt **20154Pr** is displayed on LCD **201** (FIG. 1) at the time Language Text Data Displaying Software For Word Processor **20654c3a** (Paragraph [0044]) is closed. In the present embodiment, Prompt **20154Pr** is primarily composed of **20154PrS**, **20154PrY**, **20154PrN**, and **20154PrC**. In the present embodiment, **20154PrS** is the language text data processed in **S2** of the previous paragraph; **20154PrY** is the language text data processed in **S3** of the previous paragraph; **20154PrN** is the language text data processed in **S4** of the previous paragraph; and **20154PrC** is the language text data processed in **S5** of the previous paragraph.

Paragraph [0048]—This Paragraph [0048] illustrates Language Text Data Displaying Software For Explorer **20654c4** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays the language text data at the time a Windows Explorer like software program which displays folders and/or directories and the structures thereof is executed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** executes Windows Explorer like software program in response to the signal input by the user of Communication Device **200** indicating to activate and execute the software program (**S1**). In the process of displaying the Windows Explorer like software program on

12

LCD **201** (FIG. 1), the steps of **S2** through **S4** are implemented. Namely, CPU **211** identifies the language item ID ‘Language Item#15’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘My Network’ at the predetermined location in the Windows Explorer like software program (**S2**). CPU **211** identifies the language item ID ‘Language Item#16’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘Trash’ at the predetermined location in the Windows Explorer like software program (**S3**). CPU **211** identifies the language item ID ‘Language Item#17’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘Local Disk’ at the predetermined location in the Windows Explorer like software program (**S4**).

Paragraph [0049]—This Paragraph [0049] illustrates the data displayed on LCD **201** (FIG. 1) of Communication Device **200** at the time Language Text Data Displaying Software For Explorer **20654c4** (Paragraph [0048]) is executed. In the present embodiment, **20154LD**, **20154MN**, and **20154Tr** are displayed on LCD **201** (FIG. 1) at the time Language Text Data Displaying Software For Explorer **20654c4** is executed. In the present embodiment, **20154LD** is the language text data processed in **S4** of the previous paragraph; **20154MN** is the language text data processed in **S2** of the previous paragraph; and **20154Tr** is the language text data processed in **S3** of the previous paragraph.

Paragraph [0050]—<<Multiple Language Displaying Function—Utilizing Japanese>>

Paragraph [0051]—This Paragraph [0051] illustrates Language Selecting Software **20654c1** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which selects the language utilized to operate Communication Device **200** from a plurality of languages. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves the language type data from Language Type Data Storage Area **20654b2** (Paragraph [0038]) (**S1**), and Displays a list of available languages on LCD **201** (FIG. 1) (**S2**). In the present example, the following languages are displayed on LCD **201**: English, Japanese, French, and German. A certain language is selected therefrom by utilizing Input Device **210** (FIG. 1) or via voice recognition system (**S3**). Assume that ‘Japanese’ is selected in **S3**. CPU **211** then identifies the language table ID corresponding to the language type data in Language Type Data Storage Area **20654b2** (Paragraph [0038]), and stores the language table ID (Language Table#2) in Selected Language Table ID Storage Area **20654b4** (Paragraph [0031]) (**S4**).

Paragraph [0052]—This Paragraph [0052] illustrates Selected Language Displaying Software **20654c2** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays and operates with the language selected in **S3** of Paragraph [0051] (i.e., Japanese). In the present embodiment, when Communication Device **200** is powered on (**S1**), CPU **211** (FIG. 1) of Communication Device **200** retrieves the selected language table ID (Language Table#2) from Selected Language Table ID Storage Area **20654b4** (Paragraph [0031]) (**S2**). CPU **211** then identifies the storage area corresponding to the language table ID selected in **S2** (Language Table#2 Storage Area **20654b1b** (Paragraph [0035])) in Language Tables Storage Area **20654b1** (Paragraph [0032]) (**S3**). Language text data displaying process is initiated thereafter of which the details are described hereinafter (**S4**).

Paragraph [0053]—This Paragraph [0053] illustrates Language Text Data Displaying Software For Word Processor

13

20654c3a stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays the language text data at the time a word processor, such as MS Word and WordPerfect is executed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** executes a word processor in response to the signal input by the user of Communication Device **200** indicating to activate and execute the word processor (S1). In the process of displaying the word processor on LCD **201** (FIG. 1), the following steps of S2 through S8 are implemented. Namely, CPU **211** identifies the language item ID 'Language Item#8' in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating 'File' in Japanese at the predetermined location in the word processor (S2). CPU **211** identifies the language item ID 'Language Item#9' in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating 'Edit' in Japanese at the predetermined location in the word processor (S3). CPU **211** identifies the language item ID 'Language Item#10' in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating 'View' in Japanese at the predetermined location in the word processor (S4). CPU **211** identifies the language item ID 'Language Item#11' in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating 'Format' in Japanese at the predetermined location in the word processor (S5). CPU **211** identifies the language item ID 'Language Item#12' in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating 'Tools' in Japanese at the predetermined location in the word processor (S6). CPU **211** identifies the language item ID 'Language Item#13' in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating 'Window' in Japanese at the predetermined location in the word processor (S7). CPU **211** identifies the language item ID 'Language Item#14' in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating 'Help' in Japanese at the predetermined location in the word processor (S8). Alphanumeric data is input to the word processor by utilizing Input Device **210** (FIG. 1) or via voice recognition system thereafter (S9).

Paragraph [0054]—This Paragraph [0054] illustrates the data displayed on LCD **201** (FIG. 1) of Communication Device **200** at the time Language Text Data Displaying Software For Word Processor **20654c3a** (Paragraph [0053]) is implemented. In the present embodiment, the word processor described in Paragraph [0053] is primarily composed of Menu Bar **20154MB** and Alphanumeric Data Input Area **20154ADIA** wherein the language text data described in S2 through S8 of Paragraph [0053] are displayed on Menu Bar **20154MB** and alphanumeric data are input in Alphanumeric Data Input Area **20154ADIA**. In the present embodiment, **20154MBF** is the language text data processed in S2 of the previous paragraph; **20154MBE** is the language text data processed in S3 of the previous paragraph; **20154MBV** is the language text data processed in S4 of the previous paragraph; **20154MBF** is the language text data processed in S5 of the previous paragraph; **20154MBT** is the language text data processed in S6 of the previous paragraph; **20154MBW** is the language text data processed in S7 of the previous paragraph; and **20154MBH** is the language text data processed in S8 of the previous paragraph.

Paragraph [0055]—This Paragraph [0055] illustrates Language Text Data Displaying Software For Word Processor

14

20654c3b stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays a prompt on LCD **201** (FIG. 1) at the time a word processor is closed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** initiates the closing process of the word processor in response to the signal input by the user of Communication Device **200** indicating to close the word processor (S1). In the process of closing the word processor, the following steps of S2 through S5 are implemented. Namely, CPU **211** identifies the language item ID 'Language Item#18' in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating 'Save' in Japanese at the predetermined location in the word processor (S2). CPU **211** identifies the language item ID 'Language Item#19' in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating 'Yes' in Japanese at the predetermined location in the word processor (S3). CPU **211** identifies the language item ID 'Language Item#20' in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating 'No' in Japanese at the predetermined location in the word processor (S4). CPU **211** identifies the language item ID 'Language Item#21' in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating 'Cancel' in Japanese at the predetermined location in the word processor (S5). The save signal indicating to save the alphanumeric data input in S9 of Paragraph [0053] is input by utilizing Input Device **210** (FIG. 1) or via voice recognition system, assuming that the user of Communication Device **200** intends to save the data (S6), and the data are saved in a predetermined location in RAM **206** (FIG. 1) (S7). The word processor is closed thereafter (S8).

Paragraph [0056]—This Paragraph [0056] illustrates the data displayed on LCD **201** (FIG. 1) of Communication Device **200** at the time Language Text Data Displaying Software For Word Processor **20654c3b** (Paragraph [0055]) is implemented. In the present embodiment, Prompt **20154Pr** is displayed on LCD **201** (FIG. 1) at the time Language Text Data Displaying Software For Word Processor **20654c3a** (Paragraph [0053]) is closed. In the present embodiment, Prompt **20154Pr** is primarily composed of **20154PrS**, **20154PrY**, **20154PrN**, and **20154PrC**. In the present embodiment, **20154PrS** is the language text data processed in S2 of the previous paragraph; **20154PrY** is the language text data processed in S3 of the previous paragraph; **20154PrN** is the language text data processed in S4 of the previous paragraph; and **20154PrC** is the language text data processed in S5 of the previous paragraph.

Paragraph [0057]—This Paragraph [0057] illustrates Language Text Data Displaying Software For Explorer **20654c4** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays the language text data at the time a Windows Explorer like software program which displays folders and/or directories and the structures thereof is executed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** executes Windows Explorer like software program in response to the signal input by the user of Communication Device **200** indicating to activate and execute the software program (S1). In the process of displaying the Windows Explorer like software program on LCD **201** (FIG. 1), the following steps of S2 through S4 are implemented. Namely, CPU **211** identifies the language item ID 'Language Item#15' in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating 'My Network' in Japanese at the

15

predetermined location in the Windows Explorer like software program (S2). CPU 211 identifies the language item ID 'Language Item#16' in Language Table#2 Storage Area 20654b1b (Paragraph [0035]) and displays the corresponding language text data indicating 'Trash' in Japanese at the predetermined location in the Windows Explorer like software program (S3). CPU 211 identifies the language item ID 'Language Item#17' in Language Table#2 Storage Area 20654b1b (Paragraph [0035]) and displays the corresponding language text data indicating 'Local Disk' in Japanese at the predetermined location in the Windows Explorer like software program (S4).

Paragraph [0058]—This Paragraph [0058] illustrates the data displayed on LCD 201 (FIG. 1) of Communication Device 200 at the time Language Text Data Displaying Software For Explorer 20654c4 (Paragraph [0057]) is executed. In the present embodiment, 20154LD, 20154MN, and 20154Tr are displayed on LCD 201 (FIG. 1) at the time Language Text Data Displaying Software For Explorer 20654c4 is executed. In the present embodiment, 20154LD is the language text data processed in S4 of the previous paragraph; 20154MN is the language text data processed in S2 of the previous paragraph; and 20154Tr is the language text data processed in S3 of the previous paragraph.

Paragraph [0059]—<<Multiple Language Displaying Function—Utilizing French>>

Paragraph [0060]—This Paragraph [0060] illustrates Language Selecting Software 20654c1 stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which selects the language utilized to operate Communication Device 200 from a plurality of languages. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves the language type data from Language Type Data Storage Area 20654b2 (Paragraph [0038]) (S1), and Displays a list of available languages on LCD 201 (FIG. 1) (S2). In the present example, the following languages are displayed on LCD 201: English, Japanese, French, and German. A certain language is selected therefrom by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S3). Assume that 'French' is selected in S3. CPU 211 then identifies the language table ID corresponding to the language type data in Language Type Data Storage Area 20654b2 (Paragraph [0038]), and stores the language table ID (Language Table#3) in Selected Language Table ID Storage Area 20654b4 (Paragraph [0031]) (S4).

Paragraph [0061]—This Paragraph [0061] illustrates Selected Language Displaying Software 20654c2 stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays and operates with the language selected in S3 of Paragraph [0060] (i.e., French). In the present embodiment, when Communication Device 200 is powered on (S1), CPU 211 (FIG. 1) of Communication Device 200 retrieves the selected language table ID (Language Table#3) from Selected Language Table ID Storage Area 20654b4 (Paragraph [0031]) (S2). CPU 211 then identifies the storage area corresponding to the language table ID selected in S2 (Language Table#3 Storage Area 20654b1c (Paragraph [0036])) in Language Tables Storage Area 20654b1 (Paragraph [0032]) (S3). Language text data displaying process is initiated thereafter of which the details are described hereinafter (S4).

Paragraph [0062]—This Paragraph [0062] illustrates Language Text Data Displaying Software For Word Processor 20654c3a stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays the language text data at the time a word processor, such as MS Word and WordPerfect is executed. In the present embodi-

16

ment, CPU 211 (FIG. 1) of Communication Device 200 executes a word processor in response to the signal input by the user of Communication Device 200 indicating to activate and execute the word processor (S1). In the process of displaying the word processor on LCD 201 (FIG. 1), the following steps of S2 through S8 are implemented. Namely, CPU 211 identifies the language item ID 'Language Item#8' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#8' indicating 'File' in French at the predetermined location in the word processor (S2). CPU 211 identifies the language item ID 'Language Item#9' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#9' indicating 'Edit' in French at the predetermined location in the word processor (S3). CPU 211 identifies the language item ID 'Language Item#10' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#10' indicating 'View' in French at the predetermined location in the word processor (S4). CPU 211 identifies the language item ID 'Language Item#11' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#11' indicating 'Format' in French at the predetermined location in the word processor (S5). CPU 211 identifies the language item ID 'Language Item#12' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#12' indicating 'Tools' in French at the predetermined location in the word processor (S6). CPU 211 identifies the language item ID 'Language Item#13' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#13' indicating 'Window' in French at the predetermined location in the word processor (S7). CPU 211 identifies the language item ID 'Language Item#14' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#14' indicating 'Help' in French at the predetermined location in the word processor (S8). Alphanumeric data is input to the word processor by utilizing Input Device 210 (FIG. 1) or via voice recognition system thereafter (S9).

Paragraph [0063]—This Paragraph [0063] illustrates the data displayed on LCD 201 (FIG. 1) of Communication Device 200 at the time Language Text Data Displaying Software For Word Processor 20654c3a (Paragraph [0062]) is implemented. In the present embodiment, the word processor described in Paragraph [0062] is primarily composed of Menu Bar 20154MB and Alphanumeric Data Input Area 20154ADIA wherein the language text data described in S2 through S8 of Paragraph [0062] are displayed on Menu Bar 20154MB and alphanumeric data are input in Alphanumeric Data Input Area 20154ADIA. In the present embodiment, 20154MBF is the language text data processed in S2 of the previous paragraph; 20154MBE is the language text data processed in S3 of the previous paragraph; 20154MBV is the language text data processed in S4 of the previous paragraph; 20154MBF is the language text data processed in S5 of the previous paragraph; 20154MBT is the language text data processed in S6 of the previous paragraph; 20154MBW is the language text data processed in S7 of the previous paragraph; and 20154MBH is the language text data processed in S8 of the previous paragraph.

Paragraph [0064]—This Paragraph [0064] illustrates Language Text Data Displaying Software For Word Processor 20654c3b stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays a prompt on LCD 201 (FIG. 1) at the time a word processor is

17

closed. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 initiates the closing process of the word processor in response to the signal input by the user of Communication Device 200 indicating to close the word processor (S1). In the process of closing the word processor, the following steps of S2 through S5 are implemented. Namely, CPU 211 identifies the language item ID 'Language Item#18' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#18' indicating 'Save' in French at the predetermined location in the word processor (S2). CPU 211 identifies the language item ID 'Language Item#19' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#19' indicating 'Yes' in French at the predetermined location in the word processor (S3). CPU 211 identifies the language item ID 'Language Item#20' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#20' indicating 'No' in French at the predetermined location in the word processor (S4). CPU 211 identifies the language item ID 'Language Item#21' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#21' indicating 'Cancel' in French at the predetermined location in the word processor (S5). The save signal indicating to save the alphanumeric data input in S9 of Paragraph [0062] is input by utilizing Input Device 210 (FIG. 1) or via voice recognition system, assuming that the user of Communication Device 200 intends to save the data (S6), and the data are saved in a predetermined location in RAM 206 (FIG. 1) (S7). The word processor is closed thereafter (S8).

Paragraph [0065]—This Paragraph [0065] illustrates the data displayed on LCD 201 (FIG. 1) of Communication Device 200 at the time Language Text Data Displaying Software For Word Processor 20654c3b (Paragraph [0064]) is implemented. In the present embodiment, Prompt 20154Pr is displayed on LCD 201 (FIG. 1) at the time Language Text Data Displaying Software For Word Processor 20654c3a (Paragraph [0062]) is closed. In the present embodiment, Prompt 20154Pr is primarily composed of 20154PrS, 20154PrY, 20154PrN, and 20154PrC. In the present embodiment, 20154PrS is the language text data processed in S2 of the previous paragraph; 20154PrY is the language text data processed in S3 of the previous paragraph; 20154PrN is the language text data processed in S4 of the previous paragraph; and 20154PrC is the language text data processed in S5 of the previous paragraph.

Paragraph [0066]—This Paragraph [0066] illustrates Language Text Data Displaying Software For Explorer 20654c4 stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays the language text data at the time a Windows Explorer like software program which displays folders and/or directories and the structures thereof is executed. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 executes Windows Explorer like software program in response to the signal input by the user of Communication Device 200 indicating to activate and execute the software program (S1). In the process of displaying the Windows Explorer like software program on LCD 201 (FIG. 1), the following steps of S2 through S4 are implemented. Namely, CPU 211 identifies the language item ID 'Language Item#15' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#15' indicating 'My Network' in French at the predetermined location in the Windows Explorer like software program (S2). CPU 211 identifies the language item ID 'Language Item#16' in Language Table#3

18

Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#16' indicating 'Trash' in French at the predetermined location in the Windows Explorer like software program (S3). CPU 211 identifies the language item ID 'Language Item#17' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#17' indicating 'Local Disk' in French at the predetermined location in the Windows Explorer like software program (S4).

Paragraph [0067]—This Paragraph [0067] illustrates the data displayed on LCD 201 (FIG. 1) of Communication Device 200 at the time Language Text Data Displaying Software For Explorer 20654c4 (Paragraph [0066]) is executed. In the present embodiment, 20154LD, 20154MN, and 20154Tr are displayed on LCD 201 (FIG. 1) at the time Language Text Data Displaying Software For Explorer 20654c4 is executed. In the present embodiment, 20154LD is the language text data processed in S4 of the previous paragraph; 20154MN is the language text data processed in S2 of the previous paragraph; and 20154Tr is the language text data processed in S3 of the previous paragraph.

Paragraph [0068]—<<Multiple Language Displaying Function—Utilizing German>>

Paragraph [0069]—This Paragraph [0069] illustrates Language Selecting Software 20654c1 stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which selects the language utilized to operate Communication Device 200 from a plurality of languages. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves the language type data from Language Type Data Storage Area 20654b2 (Paragraph [0038]) (S1), and Displays a list of available languages on LCD 201 (FIG. 1) (S2). In the present example, the following languages are displayed on LCD 201: English, Japanese, French, and German. A certain language is selected therefrom by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S3). Assume that 'German' is selected in S3. CPU 211 then identifies the language table ID corresponding to the language type data in Language Type Data Storage Area 20654b2 (Paragraph [0038]), and stores the language table ID (Language Table#4) in Selected Language Table ID Storage Area 20654b4 (Paragraph [0031]) (S4).

Paragraph [0070]—This Paragraph [0070] illustrates Selected Language Displaying Software 20654c2 stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays and operates with the language selected in S3 of Paragraph [0069] (i.e., German) In the present embodiment, when Communication Device 200 is powered on (S1), CPU 211 (FIG. 1) of Communication Device 200 retrieves the selected language table ID (Language Table#4) from Selected Language Table ID Storage Area 20654b4 (Paragraph [0031]) (S2). CPU 211 then identifies the storage area corresponding to the language table ID selected in S2 (Language Table#4 Storage Area 20654b1d (Paragraph [0037])) in Language Tables Storage Area 20654b1 (Paragraph [0032]) (S3). Language text data displaying process is initiated thereafter of which the details are described hereinafter (S4).

Paragraph [0071]—This Paragraph [0071] illustrates Language Text Data Displaying Software For Word Processor 20654c3a stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays the language text data at the time a word processor, such as MS Word and WordPerfect is executed. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 executes a word processor in response to the signal input by the user of Communication Device 200 indicating to activate

19

and execute the word processor (S1). In the process of displaying the word processor on LCD 201 (FIG. 1), the following steps of S2 through S8 are implemented. Namely, CPU 211 identifies the language item ID 'Language Item#8' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#8' indicating 'File' in German at the predetermined location in the word processor (S2). CPU 211 identifies the language item ID 'Language Item#9' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#9' indicating 'Edit' in German at the predetermined location in the word processor (S3). CPU 211 identifies the language item ID 'Language Item#10' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#10' indicating 'View' in German at the predetermined location in the word processor (S4). CPU 211 identifies the language item ID 'Language Item#11' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#11' indicating 'Format' in German at the predetermined location in the word processor (S5). CPU 211 identifies the language item ID 'Language Item#12' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#12' indicating 'Tools' in German at the predetermined location in the word processor (S6). CPU 211 identifies the language item ID 'Language Item#13' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#13' indicating 'Window' in German at the predetermined location in the word processor (S7). CPU 211 identifies the language item ID 'Language Item#14' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#14' indicating 'Help' in German at the predetermined location in the word processor (S8). Alphanumeric data is input to the word processor by utilizing Input Device 210 (FIG. 1) or via voice recognition system thereafter (S9).

Paragraph [0072]—This Paragraph [0072] illustrates the data displayed on LCD 201 (FIG. 1) of Communication Device 200 at the time Language Text Data Displaying Software For Word Processor 20654c3a (Paragraph [0071]) is implemented. In the present embodiment, the word processor described in Paragraph [0071] is primarily composed of Menu Bar 20154MB and Alphanumeric Data Input Area 20154ADIA wherein the language text data described in S2 through S8 of Paragraph [0071] are displayed on Menu Bar 20154MB and alphanumeric data are input in Alphanumeric Data Input Area 20154ADIA. In the present embodiment, 20154MBF is the language text data processed in S2 of the previous paragraph; 20154MBE is the language text data processed in S3 of the previous paragraph; 20154MBV is the language text data processed in S4 of the previous paragraph; 20154MBF is the language text data processed in S5 of the previous paragraph; 20154MBT is the language text data processed in S6 of the previous paragraph; 20154MBW is the language text data processed in S7 of the previous paragraph; and 20154MBH is the language text data processed in S8 of the previous paragraph.

Paragraph [0073]—This Paragraph [0073] illustrates Language Text Data Displaying Software For Word Processor 20654c3b stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays a prompt on LCD 201 (FIG. 1) at the time a word processor is closed. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 initiates the closing process of the word processor in response to the signal input by the user

20

of Communication Device 200 indicating to close the word processor (S1). In the process of closing the word processor, the following steps of S2 through S5 are implemented. Namely, CPU 211 identifies the language item ID 'Language Item#18' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#18' indicating 'Save' in German at the predetermined location in the word processor (S2). CPU 211 identifies the language item ID 'Language Item#19' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#19' indicating 'Yes' in German at the predetermined location in the word processor (S3). CPU 211 identifies the language item ID 'Language Item#20' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#20' indicating 'No' in German at the predetermined location in the word processor (S4). CPU 211 identifies the language item ID 'Language Item#21' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#21' indicating 'Cancel' in German at the predetermined location in the word processor (S5). The save signal indicating to save the alphanumeric data input in S9 of Paragraph [0071] is input by utilizing Input Device 210 (FIG. 1) or via voice recognition system, assuming that the user of Communication Device 200 intends to save the data (S6), and the data are saved in a predetermined location in RAM 206 (FIG. 1) (S7). The word processor is closed thereafter (S8).

Paragraph [0074]—This Paragraph [0074] illustrates the data displayed on LCD 201 (FIG. 1) of Communication Device 200 at the time Language Text Data Displaying Software For Word Processor 20654c3b (Paragraph [0073]) is implemented. In the present embodiment, Prompt 20154Pr is displayed on LCD 201 (FIG. 1) at the time Language Text Data Displaying Software For Word Processor 20654c3a (Paragraph [0071]) is closed. In the present embodiment, Prompt 20154Pr is primarily composed of 20154PrS, 20154PrY, 20154PrN, and 20154PrC. In the present embodiment, 20154PrS is the language text data processed in S2 of the previous paragraph; 20154PrY is the language text data processed in S3 of the previous paragraph; 20154PrN is the language text data processed in S4 of the previous paragraph; and 20154PrC is the language text data processed in S5 of the previous paragraph.

Paragraph [0075]—This Paragraph [0075] illustrates Language Text Data Displaying Software For Explorer 20654c4 stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays the language text data at the time a Windows Explorer like software program which displays folders and/or directories and the structures thereof is executed. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 executes Windows Explorer like software program in response to the signal input by the user of Communication Device 200 indicating to activate and execute the software program (S1). In the process of displaying the Windows Explorer like software program on LCD 201 (FIG. 1), the following steps of S2 through S4 are implemented. Namely, CPU 211 identifies the language item ID 'Language Item#15' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#15' indicating 'My Network' in German at the predetermined location in the Windows Explorer like software program (S2). CPU 211 identifies the language item ID 'Language Item#16' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#16' indicating 'Trash' in German at the predetermined location in the Win-

dows Explorer like software program (S3). CPU 211 identifies the language item ID 'Language Item#17' in Language Table#4 Storage Area 20654b1d (Paragraph [0037]) and displays the corresponding language text data 'German#17' indicating 'Local Disk' in German at the predetermined location in the Windows Explorer like software program (S4).

Paragraph [0076]—This Paragraph [0076] illustrates the data displayed on LCD 201 (FIG. 1) of Communication Device 200 at the time Language Text Data Displaying Software For Explorer 20654c4 (Paragraph [0075]) is executed. In the present embodiment, 20154LD, 20154MN, and 20154Tr are displayed on LCD 201 (FIG. 1) at the time Language Text Data Displaying Software For Explorer 20654c4 is executed. In the present embodiment, 20154LD is the language text data processed in S4 of the previous paragraph; 20154MN is the language text data processed in S2 of the previous paragraph; and 20154Tr is the language text data processed in S3 of the previous paragraph.

Paragraph [0077]—<<Multiple Language Displaying Function—Utilizing Other Languages>>

Paragraph [0078]—For the avoidance of doubt, the present function is not limited to select a language, to operate Communication Device 200, only from the foregoing four languages of English, Japanese, French, and German. The present function is also capable to select a language from Dutch, Chinese, Arabic, Korean, Spanish, Italian, and any other languages existing in this world, in addition to the foregoing four languages.

Paragraph [0079]—<<Caller's Information Displaying Function>>

Paragraph [0080]—Paragraph [0084] through Paragraph [0129] illustrate the Caller's Information displaying function which displays the Information regarding the caller (e.g., name, phone number, email address, and home address, etc.) on LCD 201 (FIG. 1) when Communication Device 200 is utilized as a 'TV phone'.

Paragraph [0081]—Paragraph [0084] through Paragraph [0091] illustrate the data and software programs stored in RAM 206 (FIG. 1) of Caller's Device, a Communication Device 200, utilized by the caller.

Paragraph [0082]—Paragraph [0092] through Paragraph [0099] illustrate the data and software programs stored in RAM 206 (FIG. 1) of Callee's Device, a Communication Device 200, utilized by the callee.

Paragraph [0083]—Paragraph [0100] through Paragraph [0103] illustrate the data and software programs stored in Host H (Paragraph [0025]).

Paragraph [0084]—This Paragraph [0084] illustrates the storage area included in RAM 206 (FIG. 1) of Caller's Device. In the present embodiment, RAM 206 of Caller's Device includes Caller's Information Displaying Information Storage Area 20655a of which the data and the software programs stored therein are described in Paragraph [0085].

Paragraph [0085]—This Paragraph [0085] illustrates the storage areas included in Caller's Information Displaying Information Storage Area 20655a (Paragraph [0084]). In the present embodiment, Caller's Information Displaying Information Storage Area 20655a includes Caller's Information Displaying Data Storage Area 20655b and Caller's Information Displaying Software Storage Area 20655c. Caller's Information Displaying Data Storage Area 20655b stores the data necessary to implement the present function on the side of Caller's Device, such as the ones described in Paragraph [0086] through Paragraph [0090]. Caller's Information Displaying Software Storage Area 20655c stores the software

programs necessary to implement the present function on the side of Caller's Device, such as the ones described in Paragraph [0091].

Paragraph [0086]—This Paragraph [0086] illustrates the storage areas included in Caller's Information Displaying Data Storage Area 20655b. In the present embodiment, Caller's Information Displaying Data Storage Area 20655b includes Caller's Audiovisual Data Storage Area 20655b1, Callee's Audiovisual Data Storage Area 20655b2, Caller's Personal Data Storage Area 20655b3, Callee's Personal Data Storage Area 20655b4, Caller's Calculated GPS Data Storage Area 20655b5, Callee's Calculated GPS Data Storage Area 20655b6, Caller's Map Data Storage Area 20655b7, Callee's Map Data Storage Area 20655b8, and Work Area 20655b9. Caller's Audiovisual Data Storage Area 20655b1 stores the data described in Paragraph [0087]. Callee's Audiovisual Data Storage Area 20655b2 stores the data described in Paragraph [0088]. Caller's Personal Data Storage Area 20655b3 stores the data described in Paragraph [0089]. Callee's Personal Data Storage Area 20655b4 stores the data described in Paragraph [0090]. Caller's Calculated GPS Data Storage Area 20655b5 stores the caller's calculated GPS data which represents the current geographic location of Caller's Device in (x, y, z) format. Callee's Calculated GPS Data Storage Area 20655b6 stores the callee's calculated GPS data which represents the current geographic location of Callee's Device in (x, y, z) format. Caller's Map Data Storage Area 20655b7 stores the map data representing the surrounding area of the location indicated by the caller's calculated GPS data. Callee's Map Data Storage Area 20655b8 stores the map data representing the surrounding area of the location indicated by the callee's calculated GPS data. Work Area 20655b9 is a storage area utilized to perform calculation and to temporarily store data.

Paragraph [0087]—This Paragraph [0087] illustrates the storage areas included in Caller's Audiovisual Data Storage Area 20655b1 (Paragraph [0086]). In the present embodiment, Caller's Audiovisual Data Storage Area 20655b1 includes Caller's Audio Data Storage Area 20655b1a and Caller's Visual Data Storage Area 20655b1b. Caller's Audio Data Storage Area 20655b1a stores the caller's audio data which represents the audio data input via Microphone 215 (FIG. 1) of Caller's Device. Caller's Visual Data Storage Area 20655b1b stores the caller's visual data which represents the visual data input via CCD Unit 214 (FIG. 1) of Caller's Device.

Paragraph [0088]—This Paragraph [0088] illustrates the storage areas included in Callee's Audiovisual Data Storage Area 20655b2 (Paragraph [0086]). In the present embodiment, Callee's Audiovisual Data Storage Area 20655b2 includes Callee's Audio Data Storage Area 20655b2a and Callee's Visual Data Storage Area 20655b2b. Callee's Audio Data Storage Area 20655b2a stores the callee's audio data which represents the audio data sent from Callee's Device. Callee's Visual Data Storage Area 20655b2b stores the callee's visual data which represents the visual data sent from Callee's Device.

Paragraph [0089]—This Paragraph [0089] illustrates the data stored in Caller's Personal Data Storage Area 20655b3 (Paragraph [0086]). In the present embodiment, Caller's Personal Data Storage Area 20655b3 comprises two columns, i.e., 'Caller's Personal Data' and 'Permitted Caller's Personal Data Flag'. Column 'Caller's Personal Data' stores the caller's personal data which represent the personal data of the caller. Column 'Permitted Caller's Personal Data Flag' stores the permitted caller's personal data flag and each permitted caller's personal data flag represents whether the correspond-

23

ing caller's personal data is permitted to be displayed on Callee's Device. The permitted caller's personal data flag is represented by either '1' or '0' wherein '1' indicates that the corresponding caller's personal data is permitted to be displayed on Callee's Device, and '0' indicates that the corresponding caller's personal data is not permitted to be displayed on Callee's Device. In the present embodiment, Caller's Personal Data Storage Area **20655b3** stores the following data: the caller's name and the corresponding permitted caller's personal data flag '1'; the caller's phone number and the corresponding permitted caller's personal data flag '1'; the caller's email address and the corresponding permitted caller's personal data flag '1'; the caller's home address and the corresponding permitted caller's personal data flag '1'; the caller's business address and the corresponding permitted caller's personal data flag '0'; the caller's title and the corresponding permitted caller's personal data flag '0'; the caller's hobby and the corresponding permitted caller's personal data flag '0'; the caller's blood type and the corresponding permitted caller's personal data flag '0'; the caller's gender and the corresponding permitted caller's personal data flag '0'; the caller's age and the corresponding permitted caller's personal data flag '0'; and caller's date of birth and the corresponding permitted caller's personal data flag '0'.

Paragraph [0090]—This Paragraph [0090] illustrates the data stored in Callee's Personal Data Storage Area **20655b4** (Paragraph [0086]). In the present embodiment, Callee's Personal Data Storage Area **20655b4** stores the callee's personal data which represent the personal data of the callee which are displayed on LCD **201** (FIG. 1) of Caller's Device. In the present embodiment, Callee's Personal Data Storage Area **20655b4** stores the callee's name and phone number.

Paragraph [0091]—This Paragraph [0091] illustrates the software programs stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0085]). In the present embodiment, Caller's Information Displaying Software Storage Area **20655c** stores Permitted Caller's Personal Data Selecting Software **20655c1**, Dialing Software **20655c2**, Caller's Device Pin-pointing Software **20655c3**, Map Data Sending/Receiving Software **20655c4**, Caller's Audiovisual Data Collecting Software **20655c5**, Caller's Information Sending/Receiving Software **20655c6**, Callee's Information Sending/Receiving Software **20655c6a**, Permitted Callee's Personal Data Displaying Software **20655c7**, Map Displaying Software **20655c8**, Callee's Audio Data Outputting Software **20655c9**, and Callee's Visual Data Displaying Software **20655c10**. Permitted Caller's Personal Data Selecting Software **20655c1** is the software program described in Paragraph [0105]. Dialing Software **20655c2** is the software program described in Paragraph [0106]. Caller's Device Pin-pointing Software **20655c3** is the software program described in Paragraph [0107] and Paragraph [0108]. Map Data Sending/Receiving Software **20655c4** is the software program described in Paragraph [0109]. Caller's Audiovisual Data Collecting Software **20655c5** is the software program described in Paragraph [0110]. Caller's Information Sending/Receiving Software **20655c6** is the software program described in Paragraph [0111]. Callee's Information Sending/Receiving Software **20655c6a** is the software program described in Paragraph [0125]. Permitted Callee's Personal Data Displaying Software **20655c7** is the software program described in Paragraph [0126]. Map Displaying Software **20655c8** is the software program described in Paragraph [0127]. Callee's Audio Data Outputting Software **20655c9** is the software program described in Paragraph [0128]. Callee's Visual Data Displaying Software **20655c10** is the software program described in Paragraph [0129].

24

Paragraph [0092]—This Paragraph [0092] illustrates the storage area included in RAM **206A** (FIG. 1) of Callee's Device. In the present embodiment, RAM **206A** of Callee's Device includes Callee's Information Displaying Information Storage Area **20655aA** of which the data and the software programs stored therein are described in Paragraph [0093].

Paragraph [0093]—This Paragraph [0093] illustrates the storage areas included in Callee's Information Displaying Information Storage Area **20655aA** (Paragraph [0092]). In the present embodiment, Callee's Information Displaying Information Storage Area **20655aA** includes Callee's Information Displaying Data Storage Area **20655bA** and Callee's Information Displaying Software Storage Area **20655cA**. Callee's Information Displaying Data Storage Area **20655bA** stores the data necessary to implement the present function on the side of Callee's Device, such as the ones described in Paragraph [0094] through Paragraph [0098]. Callee's Information Displaying Software Storage Area **20655cA** stores the software programs necessary to implement the present function on the side of Callee's Device, such as the ones described in Paragraph [0099].

Paragraph [0094]—This Paragraph [0094] illustrates the storage areas included in Callee's Information Displaying Data Storage Area **20655bA**. In the present embodiment, Callee's Information Displaying Data Storage Area **20655bA** includes Caller's Audiovisual Data Storage Area **20655b1A**, Callee's Audiovisual Data Storage Area **20655b2A**, Caller's Personal Data Storage Area **20655b3A**, Callee's Personal Data Storage Area **20655b4A**, Caller's Calculated GPS Data Storage Area **20655b5A**, Callee's Calculated GPS Data Storage Area **20655b6A**, Caller's Map Data Storage Area **20655b7A**, Callee's Map Data Storage Area **20655b8A**, and Work Area **20655b9A**. Caller's Audiovisual Data Storage Area **20655b1A** stores the data described in Paragraph [0095]. Callee's Audiovisual Data Storage Area **20655b2A** stores the data described in Paragraph [0096]. Caller's Personal Data Storage Area **20655b3A** stores the data described in Paragraph [0097]. Callee's Personal Data Storage Area **20655b4A** stores the data described in Paragraph [0098]. Caller's Calculated GPS Data Storage Area **20655b5A** stores the caller's calculated GPS data which represents the current geographic location of Caller's Device in (x, y, z) format. Callee's Calculated GPS Data Storage Area **20655b6A** stores the callee's calculated GPS data which represents the current geographic location of Callee's Device in (x, y, z) format. Caller's Map Data Storage Area **20655b7A** stores the map data representing the surrounding area of the location indicated by the caller's calculated GPS data. Callee's Map Data Storage Area **20655b8A** stores the map data representing the surrounding area of the location indicated by the callee's calculated GPS data. Work Area **20655b9A** is a storage area utilized to perform calculation and to temporarily store data.

Paragraph [0095]—This Paragraph [0095] illustrates the storage areas included in Caller's Audiovisual Data Storage Area **20655b1A** (Paragraph [0094]). In the present embodiment, Caller's Audiovisual Data Storage Area **20655b1A** includes Caller's Audio Data Storage Area **20655b1aA** and Caller's Visual Data Storage Area **20655b1bA**. Caller's Audio Data Storage Area **20655b1aA** stores the caller's audio data which represents the audio data sent from Caller's Device in a wireless fashion. Caller's Visual Data Storage Area **20655b1bA** stores the caller's visual data which represents the visual data input sent from Caller's Device in a wireless fashion.

Paragraph [0096]—This Paragraph [0096] illustrates the storage areas included in Callee's Audiovisual Data Storage Area **20655b2A** (Paragraph [0094]). In the present embodi-

25

ment, Callee's Audiovisual Data Storage Area **20655b2A** includes Callee's Audio Data Storage Area **20655b2aA** and Callee's Visual Data Storage Area **20655b2bA**. Callee's Audio Data Storage Area **20655b2aA** stores the callee's audio data which represents the audio data input via Microphone **215** (FIG. 1) of Callee's Device. Callee's Visual Data Storage Area **20655b2bA** stores the callee's visual data which represents the visual data input via CCD Unit **214** (FIG. 1) of Callee's Device.

Paragraph [0097]—This Paragraph [0097] illustrates the data stored in Caller's Personal Data Storage Area **20655b3A** (Paragraph [0094]). In the present embodiment, Caller's Personal Data Storage Area **20655b3A** stores the caller's personal data which represent the personal data of the caller which are displayed on LCD **201** (FIG. 1) of Caller's Device. In the present embodiment, Caller's Personal Data Storage Area **20655b3A** stores the caller's name, phone number, email address, and home address.

Paragraph [0098]—This Paragraph [0098] illustrates the data stored in Callee's Personal Data Storage Area **20655b4A** (Paragraph [0094]). In the present embodiment, Callee's Personal Data Storage Area **20655b4A** comprises two columns, i.e., 'Callee's Personal Data' and 'Permitted Callee's Personal Data Flag'. Column 'Callee's Personal Data' stores the callee's personal data which represent the personal data of the callee. Column 'Permitted Callee's Personal Data Flag' stores the permitted callee's personal data flag and each permitted callee's personal data flag represents whether the corresponding callee's personal data is permitted to be displayed on Caller's Device. The permitted callee's personal data flag is represented by either '1' or '0' wherein '1' indicates that the corresponding callee's personal data is permitted to be displayed on Caller's Device, and '0' indicates that the corresponding callee's personal data is not permitted to be displayed on Caller's Device. In the present embodiment, Callee's Personal Data Storage Area **20655b4A** stores the following data: callee's name and the corresponding permitted callee's personal data flag '1'; the callee's phone number and the corresponding permitted callee's personal data flag '1'; the callee's email address and the corresponding permitted caller's personal data flag '0'; the callee's home address and the corresponding permitted callee's personal data flag '0'; the callee's business address and the corresponding permitted callee's personal data flag '0'; the callee's title and the corresponding permitted callee's personal data flag '0'; the callee's hobby and the corresponding permitted callee's personal data flag '0'; the callee's blood type and the corresponding permitted callee's personal data flag '0'; the callee's gender and the corresponding permitted callee's personal data flag '0'; the callee's age and the corresponding permitted callee's personal data flag '0'; and callee's date of birth and the corresponding permitted callee's personal data flag '0'.

Paragraph [0099]—This Paragraph [0099] illustrates the software programs stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0093]). In the present embodiment, Callee's Information Displaying Software Storage Area **20655cA** stores Permitted Callee's Personal Data Selecting Software **20655c1A**, Dialing Software **20655c2A**, Callee's Device Pin-pointing Software **20655c3A**, Map Data Sending/Receiving Software **20655c4A**, Callee's Audiovisual Data Collecting Software **20655c5A**, Callee's Information Sending/Receiving Software **20655c6A**, Caller's Information Sending/Receiving Software **20655c6aA**, Permitted Caller's Personal Data Displaying Software **20655c7A**, Map Displaying Software **20655c8A**, Caller's Audio Data Outputting Software **20655c9A**, and Caller's Visual Data Displaying Software

26

20655c10A. Permitted Callee's Personal Data Selecting Software **20655c1A** is the software program described in Paragraph [0118]. Dialing Software **20655c2A** is the software program described in Paragraph [0119]. Callee's Device Pin-pointing Software **20655c3A** is the software program described in Paragraph [0120] and Paragraph [0121]. Map Data Sending/Receiving Software **20655c4A** is the software program described in Paragraph [0122]. Callee's Audiovisual Data Collecting Software **20655c5A** is the software program described in Paragraph [0123]. Callee's Information Sending/Receiving Software **20655c6A** is the software program described in Paragraph [0124]. Caller's Information Sending/Receiving Software **20655c6aA** is the software program described in Paragraph [0112]. Permitted Caller's Personal Data Displaying Software **20655c7A** is the software program described in Paragraph [0113]. Map Displaying Software **20655c8A** is the software program described in Paragraph [0114]. Caller's Audio Data Outputting Software **20655c9A** is the software program described in Paragraph [0115]. Caller's Visual Data Displaying Software **20655c10A** is the software program described in Paragraph [0116].

Paragraph [0100]—This Paragraph [0100] illustrates the storage area included in Host H (Paragraph [0025]). In the present embodiment, Host H includes Caller/Callee Information Storage Area **H55a** of which the data and the software programs stored therein are described in Paragraph [0101].

Paragraph [0101]—This Paragraph [0101] illustrates the storage areas included in Caller/Callee Information Storage Area **H55a**. In the present embodiment, Caller/Callee Information Storage Area **H55a** includes Caller/Callee Data Storage Area **H55b** and Caller/Callee Software Storage Area **H55c**. Caller/Callee Data Storage Area **H55b** stores the data necessary to implement the present function on the side of Host H (Paragraph [0025]), such as the ones described in Paragraph [0102]. Caller/Callee Software Storage Area **H55c** stores the software programs necessary to implement the present function on the side of Host H, such as the ones described in Paragraph [0103].

Paragraph [0102]—This Paragraph [0102] illustrates the storage areas included in Caller/Callee Data Storage Area **H55b**. In the present embodiment, Caller/Callee Data Storage Area **H55b** includes Caller's Information Storage Area **H55b1**, Callee's Information Storage Area **H55b2**, Map Data Storage Area **H55b3**, Work Area **H55b4**, Caller's Calculated GPS Data Storage Area **H55b5**, and Callee's Calculated GPS Data Storage Area **H55b6**. Caller's Information Storage Area **H55b1** stores the Caller's Information received Caller's Device. Callee's Information Storage Area **H55b2** stores the Callee's Information received Callee's Device. Map Data Storage Area **H55b3** stores the map data received from Caller's Device and Callee's Device. Work Area **H55b4** is a storage area utilized to perform calculation and to temporarily store data. Caller's Calculated GPS Data Storage Area **H55b5** stores the caller's calculated GPS data. Callee's Calculated GPS Data Storage Area **H55b6** stores the callee's calculated GPS data.

Paragraph [0103]—This Paragraph [0103] illustrates the software programs stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]). In the present embodiment, Caller/Callee Software Storage Area **H55c** stores Dialing Software **H55c2**, Caller's Device Pin-pointing Software **H55c3**, Callee's Device Pin-pointing Software **H55c3a**, Map Data Sending/Receiving Software **H55c4**, Caller's Information Sending/Receiving Software **H55c6**, and Callee's Information Sending/Receiving Software **H55c6a**. Dialing Software **H55c2** is the software program described in Paragraph

[0106] and Paragraph [0119]. Caller's Device Pin-pointing Software **H55c3** is the software program described in Paragraph [0107]. Callee's Device Pin-pointing Software **H55c3a** is the software program described in Paragraph [0120]. Map Data Sending/Receiving Software **H55c4** is the software program described in Paragraph [0109] and Paragraph [0122]. Caller's Information Sending/Receiving Software **H55c6** is the software program described in Paragraph [0111]. Callee's Information Sending/Receiving Software **H55c6a** is the software program described in Paragraph [0124] and Paragraph [0125].

Paragraph [0104]—Paragraph [0105] through Paragraph [0116] primarily illustrate the sequence to output the Caller's Information (which is defined hereinafter) from Callee's Device.

Paragraph [0105]—This Paragraph [0105] illustrates Permitted Caller's Personal Data Selecting Software **20655c1** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which selects the permitted caller's personal data to be displayed on LCD **201** (FIG. 1) of Callee's Device. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves all of the caller's personal data from Caller's Personal Data Storage Area **20655b3** (Paragraph [0089]) (S1). CPU **211** then displays a list of caller's personal data on LCD **201** (FIG. 1) (S2). The caller selects, by utilizing Input Device **210** (FIG. 1) or via voice recognition system, the caller's personal data permitted to be displayed on Callee's Device (S3). The permitted caller's personal data flag of the data selected in S3 is registered as '1' (S4).

Paragraph [0106]—This Paragraph [0106] illustrates Dialing Software **H55c2** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]), Dialing Software **20655c2** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, and Dialing Software **20655c2A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which enables to connect between Caller's Device and Callee's Device via Host H (Paragraph [0025]) in a wireless fashion. In the present embodiment, a connection is established between Caller's Device and Host H (S1). Next, a connection is established between Host H and Callee's Device (S2). As a result, Caller's Device and Callee's Device are able to exchange audiovisual data, text data, and various types of data with each other. The connection is maintained until Caller's Device, Host H, or Callee's Device terminates the connection.

Paragraph [0107]—This Paragraph [0107] illustrates Caller's Device Pin-pointing Software **H55c3** (Paragraph [0103]) stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Caller's Device Pin-pointing Software **20655c3** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which identifies the current geographic location of Caller's Device. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device collects the GPS raw data from the near base stations (S1). CPU **211** sends the raw GPS data to Host H (S2). Upon receiving the raw GPS data (S3), Host H produces the caller's calculated GPS data by referring to the raw GPS data (S4). Host H stores the caller's calculated GPS data in Caller's Calculated GPS Data Storage Area **H55b5** (Paragraph [0102]) (S5). Host H then retrieves the caller's calculated GPS data from Caller's Calculated GPS Data Storage Area **H55b5** (Paragraph [0102]) (S6), and sends the data to Caller's Device (S7). Upon receiving the caller's calculated GPS data from Host H (S8),

CPU **211** stores the data in Caller's Calculated GPS Data Storage Area **20655b5** (Paragraph [0086]) (S9). Here, the GPS raw data are the primitive data utilized to produce the caller's calculated GPS data, and the caller's calculated GPS data is the data representing the location of Caller's Device in (x, y, z) format. The sequence described in the present paragraph is repeated periodically.

Paragraph [0108]—This Paragraph [0108] illustrates another embodiment of the sequence described in Paragraph [0107] in which the entire process is performed solely by Caller's Device Pin-pointing Software **20655c3** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device collects the raw GPS data from the near base stations (S1). CPU **211** then produces the caller's calculated GPS data by referring to the raw GPS data (S2), and stores the caller's calculated GPS data in Caller's Calculated GPS Data Storage Area **20655b5** (Paragraph [0086]) (S3). The sequence described in the present paragraph is repeated periodically.

Paragraph [0109]—This Paragraph [0109] illustrates Map Data Sending/Receiving Software **H55c4** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Map Data Sending/Receiving Software **20655c4** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which sends and receives the map data. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves the caller's calculated GPS data from Caller's Calculated GPS Data Storage Area **20655b5** (Paragraph [0086]) (S1), and sends the data to Host H (S2). Upon receiving the calculated GPS data from Caller's Device (S3), Host H identifies the map data in Map Data Storage Area **H55b3** (Paragraph [0102]) (S4). Here, the map data represents the surrounding area of the location indicated by the caller's calculated GPS data. Host H retrieves the map data from Map Data Storage Area **H55b3** (Paragraph [0102]) (S5), and sends the data to Caller's Device (S6). Upon receiving the map data from Host H (S7), Caller's Device stores the data in Caller's Map Data Storage Area **20655b7** (Paragraph [0086]) (S8). The sequence described in the present paragraph is repeated periodically.

Paragraph [0110]—This Paragraph [0110] illustrates Caller's Audiovisual Data Collecting Software **20655c5** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which collects the audiovisual data of the caller to be sent to Callee's Device via Antenna **218** (FIG. 1) thereof. CPU **211** (FIG. 1) of Caller's Device retrieves the caller's audiovisual data from CCD Unit **214** and Microphone **215** (S1). CPU **211** then stores the caller's audio data in Caller's Audio Data Storage Area **20655b1a** (Paragraph [0087]) (S2), and the caller's visual data in Caller's Visual Data Storage Area **20655b1b** (Paragraph [0087]) (S3). The sequence described in the present paragraph is repeated periodically.

Paragraph [0111]—This Paragraph [0111] illustrates Caller's Information Sending/Receiving Software **H55c6** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Caller's Information Sending/Receiving Software **20655c6** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which sends and receives the Caller's Information (which is defined hereinafter) between Caller's Device and Host H. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves the permitted caller's personal data from Caller's Personal Data Storage Area **20655b3** (Paragraph [0089]) (S1). CPU **211**

retrieves the caller's calculated GPS data from Caller's Calculated GPS Data Storage Area **20655b5** (Paragraph [0086]) (S2). CPU **211** retrieves the map data from Caller's Map Data Storage Area **20655b7** (Paragraph [0086]) (S3). CPU **211** retrieves the caller's audio data from Caller's Audio Data Storage Area **20655b1a** (Paragraph [0087]) (S4). CPU **211** retrieves the caller's visual data from Caller's Visual Data Storage Area **20655b1b** (Paragraph [0087]) (S5). CPU **211** then sends the data retrieved in S1 through S5 (collectively defined as the 'Caller's Information' hereinafter) to Host H (S6). Upon receiving the Caller's Information from Caller's Device (S7), Host H stores the Caller's Information in Caller's Information Storage Area **H55b1** (Paragraph [0102]) (S8). The sequence described in the present paragraph is repeated periodically.

Paragraph [0112]—This Paragraph [0112] illustrates Caller's Information Sending/Receiving Software **H55c6** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Caller's Information Sending/Receiving Software **20655c6aA** (Paragraph [0099]) stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Callee's Device, which sends and receives the Caller's Information between Host H and Callee's Device. In the present embodiment, Host H retrieves the Caller's Information from Caller's Information Storage Area **H55b1** (Paragraph [0102]) (S1), and sends the Caller's Information to Callee's Device (S2). CPU **211** (FIG. 1) of Callee's Device receives the Caller's Information from Host H (S3). CPU **211** stores the permitted caller's personal data in Caller's Personal Data Storage Area **20655b3A** (Paragraph [0097]) (S4). CPU **211** stores the caller's calculated GPS data in Caller's Calculated GPS Data Storage Area **20655b5A** (Paragraph [0094]) (S5). CPU **211** stores the map data in Caller's Map Data Storage Area **20655b7A** (Paragraph [0094]) (S6). CPU **211** stores the caller's audio data in Caller's Audio Data Storage Area **20655b1aA** (Paragraph [0095]) (S7). CPU **211** stores the caller's visual data in Caller's Visual Data Storage Area **20655b1bA** (Paragraph [0095]) (S8). The sequence described in the present paragraph is repeated periodically.

Paragraph [0113]—This Paragraph [0113] illustrates Permitted Caller's Personal Data Displaying Software **20655c7A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which displays the permitted caller's personal data on LCD **201** (FIG. 1) of Callee's Device. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves the permitted caller's personal data from Caller's Personal Data Storage Area **20655b3A** (Paragraph [0097]) (S1). CPU **211** then displays the permitted caller's personal data on LCD **201** (FIG. 1) (S2). The sequence described in the present paragraph is repeated periodically.

Paragraph [0114]—This Paragraph [0114] illustrates Map Displaying Software **20655c8A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which displays the map representing the surrounding area of the location indicated by the caller's calculated GPS data. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves the caller's calculated GPS data from Caller's Calculated GPS Data Storage Area **20655b5A** (Paragraph [0094]) (S1). CPU **211** then retrieves the map data from Caller's Map Data Storage Area **20655b7A** (Paragraph [0094]) (S2), and arranges on the map data the caller's current location icon in accordance with the caller's calculated GPS data (S3). Here, the caller's current location icon is an icon which represents the location of Caller's Device in the map data. The map with the caller's

current location icon is displayed on LCD **201** (FIG. 1) (S4). The sequence described in the present paragraph is repeated periodically.

Paragraph [0115]—This Paragraph [0115] illustrates Caller's Audio Data Outputting Software **20655c9A** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which outputs the caller's audio data from Speaker **216** (FIG. 1) of Callee's Device. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves the caller's audio data from Caller's Audio Data Storage Area **20655b1aA** (Paragraph [0095]) (S1). CPU **211** then outputs the caller's audio data from Speaker **216** (FIG. 1) (S2). The sequence described in the present paragraph is repeated periodically.

Paragraph [0116]—This Paragraph [0116] illustrates Caller's Visual Data Displaying Software **20655c10A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which displays the caller's visual data on LCD **201** (FIG. 1) of Callee's Device. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves the caller's visual data from Caller's Visual Data Storage Area **20655b1bA** (Paragraph [0095]) (S1). CPU **211** then displays the caller's visual data on LCD **201** (FIG. 1) (S2). The sequence described in the present paragraph is repeated periodically.

Paragraph [0117]—Paragraph [0118] through Paragraph [0129] primarily illustrate the sequence to output the Callee's Information (which is defined hereinafter) from Caller's Device.

Paragraph [0118]—This Paragraph [0118] illustrates Permitted Callee's Personal Data Selecting Software **20655c1A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which selects the permitted callee's personal data to be displayed on LCD **201** (FIG. 1) of Caller's Device. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves all of the callee's personal data from Callee's Personal Data Storage Area **20655b4A** (Paragraph [0098]) (S1). CPU **211** then displays a list of callee's personal data on LCD **201** (FIG. 1) (S2). The callee selects, by utilizing Input Device **210** (FIG. 1) or via voice recognition system, the callee's personal data permitted to be displayed on Caller's Device (S3). The permitted callee's personal data flag of the data selected in S3 is registered as '1' (S4).

Paragraph [0119]—This Paragraph [0119] illustrates Dialing Software **H55c2** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]), Dialing Software **20655c2A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, and Dialing Software **20655c2** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which enables to connect between Callee's Device and Caller's Device via Host H (Paragraph [0025]) in a wireless fashion. In the present embodiment, a connection is established between Callee's Device and Host H (S1). Next, a connection is established between Host H and Caller's Device (S2). As a result, Callee's Device and Caller's Device are able to exchange audiovisual data, text data, and various types of data with each other. The sequence described in the present paragraph is not necessarily implemented if the connection between Caller's Device and Callee's Device is established as described in Paragraph [0106]. The sequence described in the present paragraph may be implemented if the connection is accidentally terminated by Callee's Device and the connection process is initiated by Callee's Device.

31

Paragraph [0120]—This Paragraph [0120] illustrates Callee's Device Pin-pointing Software **H55c3a** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Callee's Device Pin-pointing Software **20655c3A** stored in Callee's Information Displaying Software Storage Area **20655cA** of Callee's Device, which identifies the current geographic location of Callee's Device. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device collects the GPS raw data from the near base stations (S1). CPU **211** sends the raw GPS data to Host H (S2). Upon receiving the raw GPS data (S3), Host H produces the callee's calculated GPS data by referring to the raw GPS data (S4). Host H stores the callee's calculated GPS data in Callee's Calculated GPS Data Storage Area **H55b6** (Paragraph [0102]) (S5). Host H then retrieves the callee's calculated GPS data from Callee's Calculated GPS Data Storage Area **H55b6** (Paragraph [0102]) (S6), and sends the data to Callee's Device (S7). Upon receiving the callee's calculated GPS data from Host H (S8), CPU **211** stores the data in Callee's Calculated GPS Data Storage Area **20655b6A** (Paragraph [0094]) (S9). Here, the GPS raw data are the primitive data utilized to produce the callee's calculated GPS data, and the callee's calculated GPS data is the data representing the location of Callee's Device in (x, y, z) format. The sequence described in the present paragraph is repeated periodically.

Paragraph [0121]—This Paragraph [0121] illustrates another embodiment of the sequence described in Paragraph [0120] in which the entire process is performed solely by Callee's Device Pin-pointing Software **20655c3A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device collects the raw GPS data from the near base stations (S1). CPU **211** then produces the callee's calculated GPS data by referring to the raw GPS data (S2), and stores the callee's calculated GPS data in Callee's Calculated GPS Data Storage Area **20655b6A** (Paragraph [0094]) (S3). The sequence described in the present paragraph is repeated periodically.

Paragraph [0122]—This Paragraph [0122] illustrates Map Data Sending/Receiving Software **H55c4** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Map Data Sending/Receiving Software **20655c4A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which sends and receives the map data. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves the callee's calculated GPS data from Callee's Calculated GPS Data Storage Area **20655b6A** (Paragraph [0094]) (S1), and sends the data to Host H (S2). Upon receiving the calculated GPS data from Callee's Device (S3), Host H identifies the map data in Map Data Storage Area **H55b3** (Paragraph [0102]) (S4). Here, the map data represents the surrounding area of the location indicated by the callee's calculated GPS data. Host H retrieves the map data from Map Data Storage Area **H55b3** (Paragraph [0102]) (S5), and sends the data to Callee's Device (S6). Upon receiving the map data from Host H (S7), Callee's Device stores the data in Callee's Map Data Storage Area **20655b8A** (Paragraph [0094]) (S8). The sequence described in the present paragraph is repeated periodically.

Paragraph [0123]—This Paragraph [0123] illustrates Callee's Audiovisual Data Collecting Software **20655c5A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which collects the audiovisual data of the callee to be sent to Caller's Device via Antenna **218** (FIG. 1) thereof. CPU **211** (FIG. 1) of Callee's Device retrieves the callee's audiovisual data from

32

CCD Unit **214** and Microphone **215** (S1). CPU **211** then stores the callee's audio data in Callee's Audio Data Storage Area **20655b2aA** (Paragraph [0096]) (S2), and the callee's visual data in Callee's Visual Data Storage Area **20655b2bA** (Paragraph [0096]) (S3). The sequence described in the present paragraph is repeated periodically.

Paragraph [0124]—This Paragraph [0124] illustrates Callee's Information Sending/Receiving Software **H55c6a** (Paragraph [0103]) stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Callee's Information Sending/Receiving Software **20655c6A** (Paragraph [0099]) stored in Callee's Information Displaying Software Storage Area **20655cA** of Callee's Device, which sends and receives the Callee's Information (which is defined hereinafter) between Callee's Device and Host H. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves the permitted callee's personal data from Callee's Personal Data Storage Area **20655b4A** (Paragraph [0098]) (S1). CPU **211** retrieves the callee's calculated GPS data from Callee's Calculated GPS Data Storage Area **20655b6A** (Paragraph [0094]) (S2). CPU **211** retrieves the map data from Callee's Map Data Storage Area **20655b8A** (Paragraph [0094]) (S3). CPU **211** retrieves the callee's audio data from Callee's Audio Data Storage Area **20655b2aA** (Paragraph [0096]) (S4). CPU **211** retrieves the callee's visual data from Callee's Visual Data Storage Area **20655b2bA** (Paragraph [0096]) (S5). CPU **211** then sends the data retrieved in S1 through S5 (collectively defined as the 'Callee's Information' hereinafter) to Host H (S6). Upon receiving the Callee's Information from Callee's Device (S7), Host H stores the Callee's Information in Callee's Information Storage Area **H55b2** (Paragraph [0102]) (S8). The sequence described in the present paragraph is repeated periodically.

Paragraph [0125]—This Paragraph [0125] illustrates Callee's Information Sending/Receiving Software **H55c6a** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Callee's Information Sending/Receiving Software **20655c6a** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which sends and receives the Callee's Information between Host H and Caller's Device. In the present embodiment, Host H retrieves the Callee's Information from Callee's Information Storage Area **H55b2** (Paragraph [0102]) (S1), and sends the Callee's Information to Caller's Device (S2). CPU **211** (FIG. 1) of Caller's Device receives the Callee's Information from Host H (S3). CPU **211** stores the permitted callee's personal data in Callee's Personal Data Storage Area **20655b4** (Paragraph [0090]) (S4). CPU **211** stores the callee's calculated GPS data in Callee's Calculated GPS Data Storage Area **20655b6** (Paragraph [0086]) (S5). CPU **211** stores the map data in Callee's Map Data Storage Area **20655b8** (Paragraph [0086]) (S6). CPU **211** stores the callee's audio data in Callee's Audio Data Storage Area **20655b2a** (Paragraph [0088]) (S7). CPU **211** stores the callee's visual data in Callee's Visual Data Storage Area **20655b2b** (Paragraph [0088]) (S8). The sequence described in the present paragraph is repeated periodically.

Paragraph [0126]—This Paragraph [0126] illustrates Permitted Callee's Personal Data Displaying Software **20655c7** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which displays the permitted callee's personal data on LCD **201** (FIG. 1) of Caller's Device. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves the permitted callee's personal data from Callee's Personal Data Storage

Area **20655b4** (Paragraph [0090]) (S1). CPU **211** then displays the permitted callee's personal data on LCD **201** (FIG. 1) (S2). The sequence described in the present paragraph is repeated periodically.

Paragraph [0127]—This Paragraph [0127] illustrates Map Displaying Software **20655c8** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which displays the map representing the surrounding area of the location indicated by the callee's calculated GPS data. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves the callee's calculated GPS data from Callee's Calculated GPS Data Storage Area **20655b6** (Paragraph [0086]) (S1). CPU **211** then retrieves the map data from Callee's Map Data Storage Area **20655b8** (Paragraph [0086]) (S2), and arranges on the map data the callee's current location icon in accordance with the callee's calculated GPS data (S3). Here, the callee's current location icon is an icon which represents the location of Callee's Device in the map data. The map with the callee's current location icon is displayed on LCD **201** (FIG. 1) (S4). The sequence described in the present paragraph is repeated periodically.

Paragraph [0128]—This Paragraph [0128] illustrates Callee's Audio Data Outputting Software **20655c9** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which outputs the callee's audio data from Speaker **216** (FIG. 1) of Caller's Device. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves the callee's audio data from Callee's Audio Data Storage Area **20655b2a** (Paragraph [0088]) (S1). CPU **211** then outputs the caller's audio data from Speaker **216** (FIG. 1) (S2). The sequence described in the present paragraph is repeated periodically.

Paragraph [0129]—This Paragraph [0129] illustrates Callee's Visual Data Displaying Software **20655c10** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which displays the callee's visual data on LCD **201** (FIG. 1) of Caller's Device. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves the callee's visual data from Callee's Visual Data Storage Area **20655b2b** (Paragraph [0088]) (S1). CPU **211** then displays the callee's visual data on LCD **201** (FIG. 1) (S2). The sequence described in the present paragraph is repeated periodically.

Paragraph [0130]—<<Communication Device Remote Controlling Function (By Phone)>>

Paragraph [0131]—Paragraph [0132] through Paragraph [0155] illustrate the communication device remote controlling function (by phone) which enables the user of Communication Device **200** to remotely control Communication Device **200** via conventional telephone Phone PH (not shown).

Paragraph [0132]—This Paragraph [0132] illustrates the storage areas included in Host H (Paragraph [0025]). In the present embodiment, Host H includes Communication Device Controlling Information Storage Area **H57a** of which the data and the software programs stored therein are described in Paragraph [0133].

Paragraph [0133]—This Paragraph [0133] illustrates the storage areas included in Communication Device Controlling Information Storage Area **H57a** (Paragraph [0132]). In the present embodiment, Communication Device Controlling Information Storage Area **H57a** includes Communication Device Controlling Data Storage Area **H57b** and Communication Device Controlling Software Storage Area **H57c**. Communication Device Controlling Data Storage Area **H57b** stores the data necessary to implement the present function on

the side of Host H (Paragraph [0025]), such as the ones described in Paragraph [0134] through Paragraph [0137]. Communication Device Controlling Software Storage Area **H57c** stores the software programs necessary to implement the present function on the side of Host H, such as the ones described in Paragraph [0138].

Paragraph [0134]—This Paragraph [0134] illustrates the storage areas included in Communication Device Controlling Data Storage Area **H57b** (Paragraph [0133]). In the present embodiment, Communication Device Controlling Data Storage Area **H57b** includes Password Data Storage Area **H57b1**, Phone Number Data Storage Area **H57b2**, Audio Data Storage Area **H57b3**, and Work Area **H57b4**. Password Data Storage Area **H57b1** stores the data described in Paragraph [0135]. Phone Number Data Storage Area **H57b2** stores the data described in Paragraph [0136]. Audio Data Storage Area **H57b3** stores the data described in Paragraph [0137]. Work Area **H57b4** is utilized as a work area to perform calculation and to temporarily store data.

Paragraph [0135]—This Paragraph [0135] illustrates the data stored in Password Data Storage Area **H57b1** (Paragraph [0134]). In the present embodiment, Password Data Storage Area **H57b1** comprises two columns, i.e., 'User ID' and 'Password Data'. Column 'User ID' stores the user IDs, and each user ID represents the identification of the user of Communication Device **200**. Column 'Password Data' stores the password data, and each password data represents the password set by the user of the corresponding user ID. Here, each password data is composed of alphanumeric data. In the present embodiment, Password Data Storage Area **H57b1** stores the following data: the user ID 'User#1' and the corresponding password data 'Password Data#1'; the user ID 'User#2' and the corresponding password data 'Password Data#2'; the user ID 'User#3' and the corresponding password data 'Password Data#3'; the user ID 'User#4' and the corresponding password data 'Password Data#4'; and the user ID 'User#5' and the corresponding password data 'Password Data#5'.

Paragraph [0136]—This Paragraph [0136] illustrates the data stored in Phone Number Data Storage Area **H57b2** (Paragraph [0134]). In the present embodiment, Phone Number Data Storage Area **H57b2** comprises two columns, i.e., 'User ID' and 'Phone Number Data'. Column 'User ID' stores the user IDs, and each user ID represents the identification of the user of Communication Device **200**. Column 'Phone Number Data' stores the phone number data, and each phone number data represents the phone number of the user of the corresponding user ID. Here, each phone number data is composed of numeric data. In the present embodiment, Phone Number Data Storage Area **H57b2** stores the following data: the user ID 'User#1' and the corresponding phone number data 'Phone Number Data#1'; the user ID 'User#2' and the corresponding phone number data 'Phone Number Data#2'; the user ID 'User#3' and the corresponding phone number data 'Phone Number Data#3'; the user ID 'User#4' and the corresponding phone number data 'Phone Number Data#4'; and the user ID 'User#5' and the corresponding phone number data 'Phone Number Data#5'.

Paragraph [0137]—This Paragraph [0137] illustrates the data stored in Audio Data Storage Area **H57b3** (Paragraph [0134]). In the present embodiment, Audio Data Storage Area **H57b3** comprises two columns, i.e., 'Audio ID' and 'Audio Data'. Column 'Audio ID' stores the audio IDs, and each audio ID represents the identification of the audio data stored in column 'Audio Data'. Column 'Audio Data' stores the audio data, and each audio data represents a message output from a conventional telephone Phone PH. In the present

35

embodiment, Audio Data Storage Area **H57b3** stores the following data: the audio ID 'Audio#0' and the corresponding audio data 'Audio Data#0'; the audio ID 'Audio#1' and the corresponding audio data 'Audio Data#1'; the audio ID 'Audio#2' and the corresponding audio data 'Audio Data#2'; the audio ID 'Audio#3' and the corresponding audio data 'Audio Data#3'; the audio ID 'Audio#4' and the corresponding audio data 'Audio Data#4'; the audio ID 'Audio#5' and the corresponding audio data 'Audio Data#5'; and the audio ID 'Audio#6' and the corresponding audio data 'Audio Data#6'. 'Audio Data#0' represents the message: 'To deactivate manner mode, press 1. To deactivate manner mode and ring your mobile phone, press 2. To ring your mobile phone, press 3. To change password of your mobile phone, press 4. To lock your mobile phone, press 5. To power off your mobile phone, press 6.' 'Audio Data#1' represents the message: 'The manner mode has been deactivated.' 'Audio Data#2' represents the message: 'The manner mode has been deactivated and your mobile phone has been rung.' 'Audio Data#3' represents the message: 'Your mobile phone has been rung.' 'Audio Data#4' represents the message: 'The password of your mobile phone has been changed.' 'Audio Data#5' represents the message: 'Your mobile phone has been changed.' 'Audio Data#6' represents the message: 'Your mobile phone has been power-offed.' The foregoing audio data may be recorded in either male's voice or female's voice.

Paragraph [0138]—This Paragraph [0138] illustrates the software programs stored in Communication Device Controlling Software Storage Area **H57c** (Paragraph [0133]). In the present embodiment, Communication Device Controlling Software Storage Area **H57c** stores User Authenticating Software **H57c1**, Menu Introducing Software **H57c2**, Line Connecting Software **H57c3**, Manner Mode Deactivating Software **H57c4**, Manner Mode Deactivating & Ringing Software **H57c5**, Ringing Software **H57c6**, Password Changing Software **H57c7**, Device Locking Software **H57c8**, and Power Off Software **H57c9**. User Authenticating Software **H57c1** is the software program described in Paragraph [0147]. Menu Introducing Software **H57c2** is the software program described in Paragraph [0148]. Line Connecting Software **H57c3** is the software program described in Paragraph [0149]. Manner Mode Deactivating Software **H57c4** is the software program described in Paragraph [0150]. Manner Mode Deactivating & Ringing Software **H57c5** is the software program described in Paragraph [0151]. Ringing Software **H57c6** is the software program described in Paragraph [0152]. Password Changing Software **H57c7** is the software program described in Paragraph [0153]. Device Locking Software **H57c8** is the software program described in Paragraph [0154]. Power Off Software **H57c9** is the software program described in Paragraph [0155].

Paragraph [0139]—This Paragraph [0139] illustrates the storage area included in RAM **206** (FIG. 1). In the present embodiment, RAM **206** includes Communication Device Controlling Information Storage Area **20657a** of which the data and the software programs stored therein are described in Paragraph [0140].

Paragraph [0140]—This Paragraph [0140] illustrates the storage areas included in Communication Device Controlling Information Storage Area **20657a** (Paragraph [0139]). In the present embodiment, Communication Device Controlling Information Storage Area **20657a** includes Communication Device Controlling Data Storage Area **20657b** and Communication Device Controlling Software Storage Area **20657c**. Communication Device Controlling Data Storage Area **20657b** stores the data necessary to implement the present function on the side of Communication Device **200**, such as

36

the ones described in Paragraph [0142] through Paragraph [0144]. Communication Device Controlling Software Storage Area **20657c** stores the software programs necessary to implement the present function on the side of Communication Device **200**, such as the ones described in Paragraph [0145].

Paragraph [0141]—The data and/or the software programs stored in Communication Device Controlling Information Storage Area **20657a** (Paragraph [0140]) may be downloaded from Host **H** (Paragraph [0025]).

Paragraph [0142]—This Paragraph [0142] illustrates the storage areas included in Communication Device Controlling Data Storage Area **20657b** (Paragraph [0140]). In the present embodiment, Communication Device Controlling Data Storage Area **20657b** includes Password Data Storage Area **20657b1** and Work Area **20657b4**. Password Data Storage Area **20657b1** stores the data described in Paragraph [0143]. Work Area **20657b4** is utilized as a work area to perform calculation and to temporarily store data.

Paragraph [0143]—This Paragraph [0143] illustrates the data stored in Password Data Storage Area **20657b1** (Paragraph [0142]). In the present embodiment, Password Data Storage Area **20657b1** comprises two columns, i.e., 'User ID' and 'Password Data'. Column 'User ID' stores the user ID which represents the identification of the user of Communication Device **200**. Column 'Password Data' stores the password data set by the user of Communication Device **200**. Here, the password data is composed of alphanumeric data. Assuming that the user ID of Communication Device **200** is 'User#1'. In the present embodiment, Password Data Storage Area **H57b1** stores the following data: the user ID 'User#1' and the corresponding password data 'Password Data#1'.

Paragraph [0144]—This Paragraph [0144] illustrates the data stored in Phone Number Data Storage Area **20657b2** (Paragraph [0142]). In the present embodiment, Phone Number Data Storage Area **20657b2** comprises two columns, i.e., 'User ID' and 'Phone Number Data'. Column 'User ID' stores the user ID of the user of Communication Device **200**. Column 'Phone Number Data' stores the phone number data which represents the phone number of Communication Device **200**. Here, the phone number data is composed of numeric data. In the present embodiment, Phone Number Data Storage Area **H57b2** stores the following data: the user ID 'User#1' and the corresponding phone number data 'Phone Number Data#1'.

Paragraph [0145]—This Paragraph [0145] illustrates the software programs stored in Communication Device Controlling Software Storage Area **20657c** (Paragraph [0140]). In the present embodiment, Communication Device Controlling Software Storage Area **20657c** stores Line Connecting Software **20657c3**, Manner Mode Deactivating Software **20657c4**, Manner Mode Deactivating & Ringing Software **20657c5**, Ringing Software **20657c6**, Password Changing Software **20657c7**, Device Locking Software **20657c8**, and Power Off Software **20657c9**. Line Connecting Software **20657c3** is the software program described in Paragraph [0149]. Manner Mode Deactivating Software **20657c4** is the software program described in Paragraph [0150]. Manner Mode Deactivating & Ringing Software **20657c5** is the software program described in Paragraph [0151]. Ringing Software **20657c6** is the software program described in Paragraph [0152]. Password Changing Software **20657c7** is the software program described in Paragraph [0153]. Device Locking Software **20657c8** is the software program described in Paragraph [0154]. Power Off Software **20657c9** is the software program described in Paragraph [0155].

Paragraph [0146]—Paragraph [0147] through Paragraph [0155] illustrate the software programs which enables the user of Communication Device 200 to remotely control Communication Device 200 via conventional telephone Phone PH.

Paragraph [0147]—This Paragraph [0147] illustrates User Authenticating Software H57c1 (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area H57c of Host H (Paragraph [0025]), which authenticates the user of Communication Device 200 to implement the present function via Phone PH. In the present embodiment, Phone PH calls Host H by dialing the predetermined phone number of Host H (S1). Upon receiving the call from Phone PH (S2) and the line is connected therebetween (S3), the user, by utilizing Phone PH, inputs both his/her password data (S4) and the phone number data of Communication Device 200 (S5). Host H initiates the authentication process by referring to Password Data Storage Area H57b1 (Paragraph [0135]) and Phone Number Data Storage Area H57b2 (Paragraph [0136]) (S6). The authentication process is completed (and the sequences described hereafter are enabled thereafter) if the password data and the phone number data described in S4 and S5 match with the data stored in Password Data Storage Area H57b1 and Phone Number Data Storage Area H57b2.

Paragraph [0148]—This Paragraph [0148] illustrates Menu Introducing Software H57c2 (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area H57c of Host H (Paragraph [0025]), which introduces the menu via Phone PH. In the present embodiment, Host H retrieves Audio Data#0 from Audio Data Storage Area H57b3 (Paragraph [0137]) (S1), and sends the data to Phone PH (S2). Upon receiving Audio Data#0 from Host H (S3), Phone PH outputs Audio Data#0 from its speaker (S4). The user presses one of the keys of '1' through '6' wherein the sequences implemented thereafter are described in Paragraph [0149] through Paragraph [0155] (S5).

Paragraph [0149]—This Paragraph [0149] illustrates Line Connecting Software H57c3 (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area H57c of Host H (Paragraph [0025]) and Line Connecting Software 20657c3 (Paragraph [0145]) stored in Communication Device Controlling Software Storage Area 20657c of Communication Device 200, which connect line between Host H and Communication Device 200. In the present embodiment, Host H calls Communication Device 200 by retrieving the corresponding phone number data from Phone Number Data Storage Area H57b2 (Paragraph [0136]) (S1). Upon Communication Device 200 receiving the call from Host H (S2), the line is connected therebetween (S3). For the avoidance of doubt, the line is connected between Host H and Communication Device 200 merely to implement the present function, and a voice communication between human beings is not enabled thereafter.

Paragraph [0150]—This Paragraph [0150] illustrates Manner Mode Deactivating Software H57c4 (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area H57c of Host H (Paragraph [0025]) and Manner Mode Deactivating Software 20657c4 (Paragraph [0145]) stored in Communication Device Controlling Software Storage Area 20657c of Communication Device 200, which deactivate the manner mode of Communication Device 200. Here, Communication Device 200 activates Vibrator 217 (FIG. 1) when Communication Device 200 is in the manner mode and outputs a ringing sound from Speaker 216 (FIG. 1) when Communication Device 200 is not in the manner mode, upon receiving an incoming call. Assume that the user presses key '1' of Phone PH (S1). In response, Phone PH sends the cor-

responding signal to Host H (S2). Host H, upon receiving the signal described in S2, sends a manner mode deactivating command to Communication Device 200 (S3). Upon receiving the manner mode deactivating command from Host H (S4), Communication Device 200 deactivates the manner mode (S5). Host H retrieves Audio Data#1 from Audio Data Storage Area H57b3 (Paragraph [0137]) and sends the data to Phone PH (S6). Upon receiving Audio Data#1 from Host H, Phone PH outputs the data from its speaker (S7). Normally the purpose to output the ringing sound from Speaker 216 is to give a notification to the user that Communication Device 200 has received an incoming call, and a voice communication is enabled thereafter upon answering the call. In contrast, the purpose to output the ringing sound from Speaker 216 by executing Manner Mode Deactivating & Ringing Software H57c5 and Manner Mode Deactivating & Ringing Software 20657c5 is merely to let the user to identify the location of Communication Device 200. Therefore, a voice communication between human beings is not enabled thereafter.

Paragraph [0151]—This Paragraph [0151] illustrates Manner Mode Deactivating & Ringing Software H57c5 (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area H57c of Host H (Paragraph [0025]) and Manner Mode Deactivating & Ringing Software 20657c5 (Paragraph [0145]) stored in Communication Device Controlling Software Storage Area 20657c of Communication Device 200, which deactivate the manner mode of Communication Device 200 and outputs a ringing sound thereafter. Assume that the user presses key '2' of Phone PH (S1). In response, Phone PH sends the corresponding signal to Host H (S2). Host H, upon receiving the signal described in S2, sends a manner mode deactivating & device ringing command to Communication Device 200 (S3). Upon receiving the manner mode deactivating & device ringing command from Host H (S4), Communication Device 200 deactivates the manner mode (S5) and outputs a ring data from Speaker 216 (S6). Host H retrieves Audio Data#2 from Audio Data Storage Area H57b3 (Paragraph [0137]) and sends the data to Phone PH (S7). Upon receiving Audio Data#2 from Host H, Phone PH outputs the data from its speaker (S8). Normally the purpose to output the ringing sound from Speaker 216 is to give a notification to the user that Communication Device 200 has received an incoming call, and a voice communication is enabled thereafter upon answering the call. In contrast, the purpose to output the ringing sound from Speaker 216 by executing Manner Mode Deactivating & Ringing Software H57c5 and Manner Mode Deactivating & Ringing Software 20657c5 is merely to let the user to identify the location of Communication Device 200. Therefore, a voice communication between human beings is not enabled thereafter by implementing the present function.

Paragraph [0152]—This Paragraph [0152] illustrates Ringing Software H57c6 (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area H57c of Host H (Paragraph [0025]) and Ringing Software 20657c6 (Paragraph [0145]) stored in Communication Device Controlling Software Storage Area 20657c of Communication Device 200, which output a ringing sound from Speaker 216 (FIG. 1). Assume that the user presses key '3' of Phone PH (S1). In response, Phone PH sends the corresponding signal to Host H (S2). Host H, upon receiving the signal described in S2, sends a device ringing command to Communication Device 200 (S3). Upon receiving the device ringing command from Host H (S4), Communication Device 200 outputs a ring data from Speaker 216 (S5). Host H retrieves Audio Data#3 from Audio Data Storage Area H57b3 (Paragraph [0137]) and sends the data to Phone PH (S6). Upon receiving

Audio Data#3 from Host H, Phone PH outputs the data from its speaker (S7). Normally the purpose to output the ringing sound from Speaker 216 is to give a notification to the user that Communication Device 200 has received an incoming call, and a voice communication is enabled thereafter upon answering the call. In contrast, the purpose to output the ringing sound from Speaker 216 by executing Ringing Software H57c6 and Ringing Software 20657c6 is merely to let the user to identify the location of Communication Device 200. Therefore, a voice communication between human beings is not enabled thereafter by implementing the present function.

Paragraph [0153]—This Paragraph [0153] illustrates Password Changing Software H57c7 (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area H57c of Host H (Paragraph [0025]) and Password Changing Software 20657c7 (Paragraph [0145]) stored in Communication Device Controlling Software Storage Area 20657c of Communication Device 200, which change the password necessary to operate Communication Device 200. Assume that the user presses key '4' of Phone PH (S1). In response, Phone PH sends the corresponding signal to Host H (S2). The user then enters a new password data by utilizing Phone PH (S3), which is sent to Communication Device 200 by Host H (S4). Upon receiving the new password data from Host H (S5), Communication Device 200 stores the new password data in Password Data Storage Area 20657b1 (Paragraph [0143]) and the old password data is erased (S6). Host H retrieves Audio Data#4 from Audio Data Storage Area H57b3 (Paragraph [0137]) and sends the data to Phone PH (S7). Upon receiving Audio Data#4 from Host H, Phone PH outputs the data from its speaker (S8).

Paragraph [0154]—This Paragraph [0154] illustrates Device Locking Software H57c8 (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area H57c of Host H (Paragraph [0025]) and Device Locking Software 20657c8 (Paragraph [0145]) stored in Communication Device Controlling Software Storage Area 20657c of Communication Device 200, which lock Communication Device 200, i.e., nullify any input signal input via Input Device 210 (FIG. 1). Assume that the user presses key '5' of Phone PH (S1). In response, Phone PH sends the corresponding signal to Host H (S2). Host H, upon receiving the signal described in S2, sends a device locking command to Communication Device 200 (S3). Upon receiving the device locking command from Host H (S4), Communication Device 200 is locked thereafter, i.e., any input via Input Device 210 is nullified unless a password data matching to the one stored in Password Data Storage Area 20657b1 (Paragraph [0143]) is entered (S5). Host H retrieves Audio Data#5 from Audio Data Storage Area H57b3 (Paragraph [0137]) and sends the data to Phone PH (S6). Upon receiving Audio Data#5 from Host H, Phone PH outputs the data from its speaker (S7).

Paragraph [0155]—This Paragraph [0155] illustrates Power Off Software H57c9 (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area H57c of Host H (Paragraph [0025]) and Power Off Software 20657c9 (Paragraph [0145]) stored in Communication Device Controlling Software Storage Area 20657c of Communication Device 200, which turn off the power of Communication Device 200. Assume that the user presses key '6' of Phone PH (S1). In response, Phone PH sends the corresponding signal to Host H (S2). Host H, upon receiving the signal described in S2, sends a power off command to Communication Device 200 (S3). Upon receiving the power off command from Host H (S4), Communication Device 200 turns off the power of itself (S5). Host H retrieves Audio Data#6 from

Audio Data Storage Area H57b3 (Paragraph [0137]) and sends the data to Phone PH (S6). Upon receiving Audio Data#6 from Host H, Phone PH outputs the data from its speaker (S7).

Paragraph [0156]—<<Communication Device Remote Controlling Function (By Web)>>

Paragraph [0157]—Paragraph [0158] through Paragraph [0181] illustrate the communication device remote controlling function (by web) which enables the user of Communication Device 200 to remotely control Communication Device 200 by an ordinary personal computer (Personal Computer PC) via the Internet, i.e., by accessing a certain web site. Here, Personal Computer PC may be any type of personal computer, including a desktop computer, lap top computer, and PDA.

Paragraph [0158]—This Paragraph [0158] illustrates the storage areas included in Host H (Paragraph [0025]). In the present embodiment, Host H includes Communication Device Controlling Information Storage Area H58a of which the data and the software programs stored therein are described in Paragraph [0159].

Paragraph [0159]—This Paragraph [0159] illustrates the storage areas included in Communication Device Controlling Information Storage Area H58a (Paragraph [0158]). In the present embodiment, Communication Device Controlling Information Storage Area H58a includes Communication Device Controlling Data Storage Area H58b and Communication Device Controlling Software Storage Area H58c. Communication Device Controlling Data Storage Area H58b stores the data necessary to implement the present function on the side of Host H (Paragraph [0025]), such as the ones described in Paragraph [0160] through Paragraph [0163]. Communication Device Controlling Software Storage Area H58c stores the software programs necessary to implement the present function on the side of Host H, such as the ones described in Paragraph [0164].

Paragraph [0160]—This Paragraph [0160] illustrates the storage areas included in Communication Device Controlling Data Storage Area H58b (Paragraph [0159]). In the present embodiment, Communication Device Controlling Data Storage Area H58b includes Password Data Storage Area H58b1, Phone Number Data Storage Area H58b2, Web Display Data Storage Area H58b3, and Work Area H58b4. Password Data Storage Area H58b1 stores the data described in Paragraph [0161]. Phone Number Data Storage Area H58b2 stores the data described in Paragraph [0162]. Web Display Data Storage Area H58b3 stores the data described in Paragraph [0163]. Work Area H58b4 is utilized as a work area to perform calculation and to temporarily store data.

Paragraph [0161]—This Paragraph [0161] illustrates the data stored in Password Data Storage Area H58b1 (Paragraph [0160]). In the present embodiment, Password Data Storage Area H58b1 comprises two columns, i.e., 'User ID' and 'Password Data'. Column 'User ID' stores the user IDs, and each user ID represents the identification of the user of Communication Device 200. Column 'Password Data' stores the password data, and each password data represents the password set by the user of the corresponding user ID. Here, each password data is composed of alphanumeric data. In the present embodiment, Password Data Storage Area H58b1 stores the following data: the user ID 'User#1' and the corresponding password data 'Password Data#1'; the user ID 'User#2' and the corresponding password data 'Password Data#2'; the user ID 'User#3' and the corresponding password data 'Password Data#3'; the user ID 'User#4' and the

corresponding password data 'Password Data#4'; and the user ID 'User#5' and the corresponding password data 'Password Data#5'.

Paragraph [0162]—This Paragraph [0162] illustrates the data stored in Phone Number Data Storage Area **H58b2** (Paragraph [0160]). In the present embodiment, Phone Number Data Storage Area **H58b2** comprises two columns, i.e., 'User ID' and 'Phone Number Data'. Column 'User ID' stores the user IDs, and each user ID represents the identification of the user of Communication Device **200**. Column 'Phone Number Data' stores the phone number data, and each phone number data represents the phone number of the user of the corresponding user ID. Here, each phone number data is composed of numeric data. In the present embodiment, Phone Number Data Storage Area **H58b2** stores the following data: the user ID 'User#1' and the corresponding phone number data 'Phone Number Data#1'; the user ID 'User#2' and the corresponding phone number data 'Phone Number Data#2'; the user ID 'User#3' and the corresponding phone number data 'Phone Number Data#3'; the user ID 'User#4' and the corresponding phone number data 'Phone Number Data#4'; and the user ID 'User#5' and the corresponding phone number data 'Phone Number Data#5'.

Paragraph [0163]—This Paragraph [0163] illustrates the data stored in Web Display Data Storage Area **H58b3** (Paragraph [0160]). In the present embodiment, Web Display Data Storage Area **H58b3** comprises two columns, i.e., 'Web Display ID' and 'Web Display Data'. Column 'Web Display ID' stores the web display IDs, and each web display ID represents the identification of the web display data stored in column 'Web Display Data'. Column 'Web Display Data' stores the web display data, and each web display data represents a message displayed on Personal Computer PC. In the present embodiment, Web Display Data Storage Area **H58b3** stores the following data: the web display ID 'Web Display#0' and the corresponding web display data 'Web Display Data#0'; the web display ID 'Web Display#1' and the corresponding web display data 'Web Display Data#1'; the web display ID 'Web Display#2' and the corresponding web display data 'Web Display Data#2'; the web display ID 'Web Display#3' and the corresponding web display data 'Web Display Data#3'; the web display ID 'Web Display#4' and the corresponding web display data 'Web Display Data#4'; the web display ID 'Web Display#5' and the corresponding web display data 'Web Display Data#5'; and the web display ID 'Web Display#6' and the corresponding web display data 'Web Display Data#6'. 'Web Display Data#0' represents the message: 'To deactivate manner mode, press 1. To deactivate manner mode and ring your mobile phone, press 2. To ring your mobile phone, press 3. To change password of your mobile phone, press 4. To lock your mobile phone, press 5. To power off your mobile phone, press 6.' 'Web Display Data#1' represents the message: 'The manner mode has been deactivated.' 'Web Display Data#2' represents the message: 'The manner mode has been deactivated and your mobile phone has been rung.' 'Web Display Data#3' represents the message: 'Your mobile phone has been rung.' 'Web Display Data#4' represents the message: 'The password of your mobile phone has been changed.' 'Web Display Data#5' represents the message: 'Your mobile phone has been changed.' 'Web Display Data#6' represents the message: 'Your mobile phone has been power-offed.' Paragraph [0163]a illustrates the display of Personal Computer PC. In the present embodiment, Home Page **20158HP**, i.e., a home page to implement the present function is displayed on Personal Computer PC. Home Page **20158HP** is primarily composed of Web Display Data#0 (Paragraph [0163]) and six buttons, i.e., Buttons 1

through 6. Following the instruction described in Web Display Data#0, the user may select one of the buttons to implement the desired function as described hereinafter.

Paragraph [0164]—This Paragraph [0164] illustrates the software programs stored in Communication Device Controlling Software Storage Area **H58c** (Paragraph [0159]). In the present embodiment, Communication Device Controlling Software Storage Area **H58c** stores User Authenticating Software **H58c1**, Menu Introducing Software **H58c2**, Line Connecting Software **H58c3**, Manner Mode Deactivating Software **H58c4**, Manner Mode Deactivating & Ringing Software **H58c5**, Ringing Software **H58c6**, Password Changing Software **H58c7**, Device Locking Software **H58c8**, and Power Off Software **H58c9**. User Authenticating Software **H58c1** is the software program described in Paragraph [0173]. Menu Introducing Software **H58c2** is the software program described in Paragraph [0174]. Line Connecting Software **H58c3** is the software program described in Paragraph [0175]. Manner Mode Deactivating Software **H58c4** is the software program described in Paragraph [0176]. Manner Mode Deactivating & Ringing Software **H58c5** is the software program described in Paragraph [0177]. Ringing Software **H58c6** is the software program described in Paragraph [0178]. Password Changing Software **H58c7** is the software program described in Paragraph [0179]. Device Locking Software **H58c8** is the software program described in Paragraph [0180]. Power Off Software **H58c9** is the software program described in Paragraph [0181].

Paragraph [0165]—This Paragraph [0165] illustrates the storage area included in RAM **206** (FIG. 1). In the present embodiment, RAM **206** includes Communication Device Controlling Information Storage Area **20658a** of which the data and the software programs stored therein are described in Paragraph [0166].

Paragraph [0166]—This Paragraph [0166] illustrates the storage areas included in Communication Device Controlling Information Storage Area **20658a** (Paragraph [0165]). In the present embodiment, Communication Device Controlling Information Storage Area **20658a** includes Communication Device Controlling Data Storage Area **20658b** and Communication Device Controlling Software Storage Area **20658c**. Communication Device Controlling Data Storage Area **20658b** stores the data necessary to implement the present function on the side of Communication Device **200**, such as the ones described in Paragraph [0168] through Paragraph [0170]. Communication Device Controlling Software Storage Area **20658c** stores the software programs necessary to implement the present function on the side of Communication Device **200**, such as the ones described in Paragraph [0171].

Paragraph [0167]—The data and/or the software programs stored in Communication Device Controlling Information Storage Area **20658a** (Paragraph [0166]) may be downloaded from Host H (Paragraph [0025]).

Paragraph [0168]—This Paragraph [0168] illustrates the storage areas included in Communication Device Controlling Data Storage Area **20658b** (Paragraph [0166]). In the present embodiment, Communication Device Controlling Data Storage Area **20658b** includes Password Data Storage Area **20658b1** and Work Area **20658b4**. Password Data Storage Area **20658b1** stores the data described in Paragraph [0169]. Work Area **20658b4** is utilized as a work area to perform calculation and to temporarily store data.

Paragraph [0169]—This Paragraph [0169] illustrates the data stored in Password Data Storage Area **20658b1** (Paragraph [0168]). In the present embodiment, Password Data Storage Area **20658b1** comprises two columns, i.e., 'User ID'

and 'Password Data'. Column 'User ID' stores the user ID which represents the identification of the user of Communication Device **200**. Column 'Password Data' stores the password data set by the user of Communication Device **200**. Here, the password data is composed of alphanumeric data. Assuming that the user ID of Communication Device **200** is 'User#1'. In the present embodiment, Password Data Storage Area **H58b1** stores the following data: the user ID 'User#1' and the corresponding password data 'Password Data#1'.

Paragraph [0170]—This Paragraph [0170] illustrates the data stored in Phone Number Data Storage Area **20658b2** (Paragraph [0168]). In the present embodiment, Phone Number Data Storage Area **20658b2** comprises two columns, i.e., 'User ID' and 'Phone Number Data'. Column 'User ID' stores the user ID of the user of Communication Device **200**. Column 'Phone Number Data' stores the phone number data which represents the phone number of Communication Device **200**. Here, the phone number data is composed of numeric data. In the present embodiment, Phone Number Data Storage Area **H58b2** stores the following data: the user ID 'User#1' and the corresponding phone number data 'Phone Number Data#1'.

Paragraph [0171]—This Paragraph [0171] illustrates the software programs stored in Communication Device Controlling Software Storage Area **20658c** (Paragraph [0166]). In the present embodiment, Communication Device Controlling Software Storage Area **20658c** stores Line Connecting Software **20658c3**, Manner Mode Deactivating Software **20658c4**, Manner Mode Deactivating & Ringing Software **20658c5**, Ringing Software **20658c6**, Password Changing Software **20658c7**, Device Locking Software **20658c8**, and Power Off Software **20658c9**. Line Connecting Software **20658c3** is the software program described in Paragraph [0175]. Manner Mode Deactivating Software **20658c4** is the software program described in Paragraph [0176]. Manner Mode Deactivating & Ringing Software **20658c5** is the software program described in Paragraph [0177]. Ringing Software **20658c6** is the software program described in Paragraph [0178]. Password Changing Software **20658c7** is the software program described in Paragraph [0179]. Device Locking Software **20658c8** is the software program described in Paragraph [0180]. Power Off Software **20658c9** is the software program described in Paragraph [0181].

Paragraph [0172]—Paragraph [0173] through Paragraph [0181] illustrate the software programs which enables the user of Communication Device **200** to remotely control Communication Device **200** by Personal Computer PC.

Paragraph [0173]—This Paragraph [0173] illustrates User Authenticating Software **H58c1** (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area **H58c** of Host H (Paragraph [0025]), which authenticates the user of Communication Device **200** to implement the present function via Personal Computer PC. In the present embodiment, Personal Computer PC sends an access request to Host H via the Internet (S1). Upon receiving the request from Personal Computer PC (S2) and the line is connected therebetween (S3), the user, by utilizing Personal Computer PC, inputs both his/her password data (S4) and the phone number data of Communication Device **200** (S5). Host H initiates the authentication process by referring to Password Data Storage Area **H58b1** (Paragraph [0161]) and Phone Number Data Storage Area **H58b2** (Paragraph [0162])) (S6). The authentication process is completed (and the sequences described hereafter are enabled thereafter) if the password data and the phone number data described in S4 and S5 match with the data stored in Password Data Storage Area **H58b1** and Phone Number Data Storage Area **H58b2**.

Paragraph [0174]—This Paragraph [0174] illustrates Menu Introducing Software **H58c2** (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area **H58c** of Host H (Paragraph [0025]), which introduces the menu on Personal Computer PC. In the present embodiment, Host H retrieves Web Display Data#0 from Web Display Data Storage Area **H58b3** (Paragraph [0163]) (S1), and sends the data to Personal Computer PC (S2). Upon receiving Web Display Data#0 from Host H (S3), Personal Computer PC displays Web Display Data#0 on its display (S4). The user selects from one of the buttons of '1' through '6' wherein the sequences implemented thereafter are described in Paragraph [0175] through Paragraph [0181] (S5).

Paragraph [0175]—This Paragraph [0175] illustrates Line Connecting Software **H58c3** (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area **H58c** of Host H (Paragraph [0025]) and Line Connecting Software **20658c3** (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area **20658c** of Communication Device **200**, which connect line between Host H and Communication Device **200**. In the present embodiment, Host H calls Communication Device **200** by retrieving the corresponding phone number data from Phone Number Data Storage Area **H58b2** (Paragraph [0162]) (S1). Upon Communication Device **200** receiving the call from Host H (S2), the line is connected therebetween (S3). For the avoidance of doubt, the line is connected between Host H and Communication Device **200** merely to implement the present function, and a voice communication between human beings is not enabled thereafter.

Paragraph [0176]—This Paragraph [0176] illustrates Manner Mode Deactivating Software **H58c4** (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area **H58c** of Host H (Paragraph [0025]) and Manner Mode Deactivating Software **20658c4** (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area **20658c** of Communication Device **200**, which deactivate the manner mode of Communication Device **200**. Here, Communication Device **200** activates Vibrator **217** (FIG. 1) when Communication Device **200** is in the manner mode and outputs a ringing sound from Speaker **216** (FIG. 1) when Communication Device **200** is not in the manner mode, upon receiving an incoming call. Assume that the user selects button '1' displayed on Personal Computer PC (S1). In response, Personal Computer PC sends the corresponding signal to Host H via the Internet (S2). Host H, upon receiving the signal described in S2, sends a manner mode deactivating command to Communication Device **200** (S3). Upon receiving the manner mode deactivating command from Host H (S4), Communication Device **200** deactivates the manner mode (S5). Host H retrieves Web Display Data#1 from Web Display Data Storage Area **H58b3** (Paragraph [0163]) and sends the data to Personal Computer PC (S6). Upon receiving Web Display Data#1 from Host H, Personal Computer PC displays the data (S7). Normally the purpose to output the ringing sound from Speaker **216** is to give a notification to the user that Communication Device **200** has received an incoming call, and a voice communication is enabled thereafter upon answering the call. In contrast, the purpose to output the ringing sound from Speaker **216** by executing Manner Mode Deactivating & Ringing Software **H58c5** and Manner Mode Deactivating & Ringing Software **20658c5** is merely to let the user to identify the location of Communication Device **200**. Therefore, a voice communication between human beings is not enabled thereafter.

Paragraph [0177]—This Paragraph [0177] illustrates Manner Mode Deactivating & Ringing Software **H58c5** (Para-

graph [0164]) stored in Communication Device Controlling Software Storage Area H58c of Host H (Paragraph [0025]) and Manner Mode Deactivating & Ringing Software 20658c5 (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area 20658c of Communication Device 200, which deactivate the manner mode of Communication Device 200 and outputs a ringing sound thereafter. Assume that the user selects button '2' displayed on Personal Computer PC (S1). In response, Personal Computer PC sends the corresponding signal to Host H via the Internet (S2). Host H, upon receiving the signal described in S2, sends a manner mode deactivating & device ringing command to Communication Device 200 (S3). Upon receiving the manner mode deactivating & device ringing command from Host H (S4), Communication Device 200 deactivates the manner mode (S5) and outputs a ring data from Speaker 216 (S6). Host H retrieves Web Display Data#2 from Web Display Data Storage Area H58b3 (Paragraph [0163]) and sends the data to Personal Computer PC (S7). Upon receiving Web Display Data#2 from Host H, Personal Computer PC displays the data (S8). Normally the purpose to output the ringing sound from Speaker 216 is to give a notification to the user that Communication Device 200 has received an incoming call, and a voice communication is enabled thereafter upon answering the call. In contrast, the purpose to output the ringing sound from Speaker 216 by executing Manner Mode Deactivating & Ringing Software H58c5 and Manner Mode Deactivating & Ringing Software 20658c5 is merely to let the user to identify the location of Communication Device 200. Therefore, a voice communication between human beings is not enabled thereafter by implementing the present function.

Paragraph [0178]—This Paragraph [0178] illustrates Ringing Software H58c6 (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area H58c of Host H (Paragraph [0025]) and Ringing Software 20658c6 (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area 20658c of Communication Device 200, which output a ringing sound from Speaker 216 (FIG. 1). Assume that the user selects button '3' displayed on Personal Computer PC (S1). In response, Personal Computer PC sends the corresponding signal to Host H via the Internet (S2). Host H, upon receiving the signal described in S2, sends a device ringing command to Communication Device 200 (S3). Upon receiving the device ringing command from Host H (S4), Communication Device 200 outputs a ring data from Speaker 216 (S5). Host H retrieves Web Display Data#3 from Web Display Data Storage Area H58b3 (Paragraph [0163]) and sends the data to Personal Computer PC (S6). Upon receiving Web Display Data#3 from Host H, Personal Computer PC displays the data (S7). Normally the purpose to output the ringing sound from Speaker 216 is to give a notification to the user that Communication Device 200 has received an incoming call, and a voice communication is enabled thereafter upon answering the call. In contrast, the purpose to output the ringing sound from Speaker 216 by executing Ringing Software H58c6 and Ringing Software 20658c6 is merely to let the user to identify the location of Communication Device 200. Therefore, a voice communication between human beings is not enabled thereafter by implementing the present function.

Paragraph [0179]—This Paragraph [0179] illustrates Password Changing Software H58c7 (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area H58c of Host H (Paragraph [0025]) and Password Changing Software 20658c7 (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area 20658c of Communication Device 200, which change the password

necessary to operate Communication Device 200. Assume that the user selects button '4' displayed on Personal Computer PC (S1). In response, Personal Computer PC sends the corresponding signal to Host H via the Internet (S2). The user then enters a new password data by utilizing Personal Computer PC (S3), which is sent to Communication Device 200 by Host H (S4). Upon receiving the new password data from Host H (S5), Communication Device 200 stores the new password data in Password Data Storage Area 20658b1 (Paragraph [0169]) and the old password data is erased (S6). Host H retrieves Web Display Data#4 from Web Display Data Storage Area H58b3 (Paragraph [0163]) and sends the data to Personal Computer PC (S7). Upon receiving Web Display Data#4 from Host H, Personal Computer PC displays the data (S8).

Paragraph [0180]—This Paragraph [0180] illustrates Device Locking Software H58c8 (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area H58c of Host H (Paragraph [0025]) and Device Locking Software 20658c8 (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area 20658c of Communication Device 200, which lock Communication Device 200, i.e., nullify any input signal input via Input Device 210 (FIG. 1). Assume that the user selects button '5' displayed on Personal Computer PC (S1). In response, Personal Computer PC sends the corresponding signal to Host H via the Internet (S2). Host H, upon receiving the signal described in S2, sends a device locking command to Communication Device 200 (S3). Upon receiving the device locking command from Host H (S4), Communication Device 200 is locked thereafter, i.e., any input via Input Device 210 is nullified unless a password data matching to the one stored in Password Data Storage Area 20658b1 (Paragraph [0169]) is entered (S5). Host H retrieves Web Display Data#5 from Web Display Data Storage Area H58b3 (Paragraph [0163]) and sends the data to Personal Computer PC (S6). Upon receiving Web Display Data#5 from Host H, Personal Computer PC displays the data (S7).

Paragraph [0181]—This Paragraph [0181] illustrates Power Off Software H58c9 (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area H58c of Host H (Paragraph [0025]) and Power Off Software 20658c9 (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area 20658c of Communication Device 200, which turn off the power of Communication Device 200. Assume that the user selects button '6' displayed on Personal Computer PC (S1). In response, Personal Computer PC sends the corresponding signal to Host H via the Internet (S2). Host H, upon receiving the signal described in S2, sends a power off command to Communication Device 200 (S3). Upon receiving the power off command from Host H (S4), Communication Device 200 turns off the power of itself (S5). Host H retrieves Web Display Data#6 from Web Display Data Storage Area H58b3 (Paragraph [0163]) and sends the data to Personal Computer PC (S6). Upon receiving Web Display Data#6 from Host H, Personal Computer PC displays the data (S7).

Paragraph [0182]—<<OS Updating Function>>

Paragraph [0183]—Paragraph [0184] through Paragraph [0244] illustrate the OS updating function which updates the operating system of Communication Device 200 in a wireless fashion. In other words, Communication Device 200 downloads the portion of the operating system of the latest version from Host H (Paragraph [0025]) via Antenna 218 (FIG. 1).

Paragraph [0184]—This Paragraph [0184] illustrates the storage areas included in RAM 206 (FIG. 1). In the present embodiment, RAM 206 includes Operating System 20663OS

of which the data stored therein are described in Paragraph [0185], and OS Updating Information Storage Area **20663a** of which the data and the software programs stored therein are described in Paragraph [0186].

Paragraph [0185]—This Paragraph [0185] illustrates the data stored in Operating System **20663OS** (Paragraph [0184]). In the present embodiment, Operating System **20663OS** includes Battery Controller **20663OSa**, CCD Unit Controller **20663OSb**, Flash Light Unit Controller **20663OSc**, Indicator Controller **20663OSd**, Input Device Controller **20663OSe**, LCD Controller **20663OSf**, LED Controller **20663OSg**, Memory Card Interface Controller **20663OSh**, Microphone Controller **20663OSi**, Photometer Controller **20663OSj**, RAM Controller **20663OSk**, ROM Controller **20663OSl**, Signal Processor Controller **20663OSm**, Signal Processor Controller **20663OSn**, Solar Panel Controller **20663OSo**, Speaker Controller **20663OSp**, Vibrator Controller **20663OSq**, Video Processor Controller **20663OSr**, Wireless Receiver Controller **20663OSs**, Wireless Receiver Controller **20663OSu**, Wireless Receiver Controller **20663OSv**, Wireless Transmitter Controller **20663OSw**, and Wireless Transmitter Controller **20663OSx**. Battery Controller **20663OSa** is a controller which controls Battery **230** (not shown). CCD Unit Controller **20663OSb** is a controller which controls CCD Unit **214** (not shown). Flash Light Unit Controller **20663OSc** is a controller which controls Flash Light Unit **220** (not shown). Indicator Controller **20663OSd** is a controller which controls Indicator **212** (not shown). Input Device Controller **20663OSe** is a controller which controls Input Device **210** (not shown). LCD Controller **20663OSf** is a controller which controls LCD **201** (not shown). LED Controller **20663OSg** is a controller which controls LED **219** (not shown). Memory Card Interface Controller **20663OSh** is a controller which controls Memory Card Interface **221** (not shown). Microphone Controller **20663OSi** is a controller which controls Microphone **215** (not shown). Photometer Controller **20663OSj** is a controller which controls Photometer **232** (not shown). RAM Controller **20663OSk** is a controller which controls RAM **206** (not shown). ROM Controller **20663OSl** is a controller which controls ROM **207** (not shown). Signal Processor Controller **20663OSm** is a controller which controls Signal Processor **205** (not shown). Signal Processor Controller **20663OSn** is a controller which controls Signal Processor **208** (not shown). Solar Panel Controller **20663OSo** is a controller which controls Solar Panel **229** (not shown). Speaker Controller **20663OSp** is a controller which controls Speaker **216L** (not shown). Vibrator Controller **20663OSq** is a controller which controls Vibrator **217** (not shown). Video Processor Controller **20663OSr** is a controller which controls Video Processor **202** (not shown). Wireless Receiver Controller **20663OSs** is a controller which controls Wireless Receiver **224** (not shown). Wireless Receiver Controller **20663OSu** is a controller which controls Wireless Receiver **225** (not shown). Wireless Receiver Controller **20663OSv** is a controller which controls Wireless Receiver **226** (not shown). Wireless Transmitter Controller **20663OSw** is a controller which controls Wireless Transmitter **222** (not shown). Wireless Transmitter Controller **20663OSx** is a controller which controls Wireless Transmitter **227** (not shown). For the avoidance of doubt, the data stored in Operating System **20663OS** are illustrative, and other types of data, which are updated by implementing the present function, are also stored therein, such as DLLs, drivers, security implementing program.

Paragraph [0186]—This Paragraph [0186] illustrates the storage areas included in OS Updating Information Storage Area **20663a** (Paragraph [0184]). In the present embodiment, OS Updating Information Storage Area **20663a** includes OS Updating Data Storage Area **20663b** and OS Updating Software Storage Area **20663c**. OS Updating Data Storage Area **20663b** stores the data necessary to implement the present function on the side of Communication Device **200**, such as the ones described in Paragraph [0188]. OS Updating Software Storage Area **20663c** stores the software programs necessary to implement the present function on the side of Communication Device **200**, such as the ones described in Paragraph [0190].

Paragraph [0187]—The data and/or the software programs stored in OS Updating Software Storage Area **20663c** (Paragraph [0186]) may be downloaded from Host H (Paragraph [0025]).

Paragraph [0188]—This Paragraph [0188] illustrates the storage area included in OS Updating Data Storage Area **20663b** (Paragraph [0186]). In the present embodiment, OS Updating Data Storage Area **20663b** includes OS Version Data Storage Area **20663b1**. OS Version Data Storage Area **20663b1** stores the data described in Paragraph [0189].

Paragraph [0189]—This Paragraph [0189] illustrates the data stored in OS Version Data Storage Area **20663b1** (Paragraph [0188]). In the present embodiment, OS Version Data Storage Area **20663b1** includes Battery Controller Version Data **20663b1a**, CCD Unit Controller Version Data **20663b1b**, Flash Light Unit Controller Version Data **20663b1c**, Indicator Controller Version Data **20663b1d**, Input Device Controller Version Data **20663b1e**, LCD Controller Version Data **20663b1f**, LED Controller Version Data **20663b1g**, Memory Card Interface Controller Version Data **20663b1h**, Microphone Controller Version Data **20663b1i**, Photometer Controller Version Data **20663b1j**, RAM Controller Version Data **20663b1k**, ROM Controller Version Data **20663b1l**, Signal Processor Controller Version Data **20663b1m**, Signal Processor Controller Version Data **20663b1n**, Solar Panel Controller Version Data **20663b1o**, Speaker Controller Version Data **20663b1p**, Vibrator Controller Version Data **20663b1q**, Video Processor Controller Version Data **20663b1r**, Wireless Receiver Controller Version Data **20663b1s**, Wireless Receiver Controller Version Data **20663b1t**, Wireless Receiver Controller Version Data **20663b1u**, Wireless Transmitter Controller Version Data **20663b1v**, Wireless Transmitter Controller Version Data **20663b1w**, and Wireless Transmitter Controller Version Data **20663b1x**. Battery Controller Version Data **20663b1a** is the version data representing the current version of Battery Controller **20663OSa** (Paragraph [0185]). CCD Unit Controller Version Data **20663b1b** is the version data representing the current version of CCD Unit Controller **20663OSb** (Paragraph [0185]). Flash Light Unit Controller Version Data **20663b1c** is the version data representing the current version of Flash Light Unit Controller **20663OSc** (Paragraph [0185]). Indicator Controller Version Data **20663b1d** is the version data representing the current version of Indicator Controller **20663OSd** (Paragraph [0185]). Input Device Controller Version Data **20663b1e** is the version data representing the current version of Input Device Controller **20663OSe** (Paragraph [0185]). LCD Controller Version Data **20663b1f** is the version data representing the current version of LCD Controller **20663OSf** (Paragraph [0185]). LED Controller Version Data **20663b1g** is the version data representing the current version of LED Controller **20663OSg** (Paragraph [0185]). Memory Card Interface Controller Version Data **20663b1h** is the version data representing the current version of Memory Card

Interface Controller **20663OSh** (Paragraph [0185]). Microphone Controller Version Data **20663b1i** is the version data representing the current version of Microphone Controller **20663OSi** (Paragraph [0185]). Photometer Controller Version Data **20663b1j** is the version data representing the current version of Photometer Controller **20663OSj** (Paragraph [0185]). RAM Controller Version Data **20663b1k** is the version data representing the current version of RAM Controller **20663OSk** (Paragraph [0185]). ROM Controller Version Data **20663b1l** is the version data representing the current version of ROM Controller **20663OSl** (Paragraph [0185]). Signal Processor Controller Version Data **20663b1m** is the version data representing the current version of Signal Processor Controller **20663OSm** (Paragraph [0185]). Signal Processor Controller Version Data **20663b1n** is the version data representing the current version of Signal Processor Controller **20663OSn** (Paragraph [0185]). Solar Panel Controller Version Data **20663b1o** is the version data representing the current version of Solar Panel Controller **20663OSo** (Paragraph [0185]). Speaker Controller Version Data **20663b1p** is the version data representing the current version of Speaker Controller **20663OSp** (Paragraph [0185]). Vibrator Controller Version Data **20663b1q** is the version data representing the current version of Vibrator Controller **20663OSq** (Paragraph [0185]). Video Processor Controller Version Data **20663b1r** is the version data representing the current version of Video Processor Controller **20663OSr** (Paragraph [0185]). Wireless Receiver Controller Version Data **20663b1s** is the version data representing the current version of Wireless Receiver Controller **20663OSs** (Paragraph [0185]). Wireless Receiver Controller Version Data **20663b1t** is the version data representing the current version of Wireless Receiver Controller **20663OSt** (Paragraph [0185]). Wireless Receiver Controller Version Data **20663b1u** is the version data representing the current version of Wireless Receiver Controller **20663OSu** (Paragraph [0185]). Wireless Transmitter Controller Version Data **20663b1v** is the version data representing the current version of Wireless Transmitter Controller **20663OSv** (Paragraph [0185]). Wireless Transmitter Controller Version Data **20663b1w** is the version data representing the current version of Wireless Transmitter Controller **20663OSw** (Paragraph [0185]). Wireless Transmitter Controller Version Data **20663b1x** is the version data representing the current version of Wireless Transmitter Controller **20663OSx** (Paragraph [0185]). Here, the version data is composed of numeric data, such as '1', '2', and '3', wherein '1' represents version '1.0', '2' represents version '2.0', and '3' represents version '3.0'.

Paragraph [0190]—This Paragraph [0190] illustrates the software programs stored in OS Updating Software Storage Area **20663c** (Paragraph [0186]). In the present embodiment, OS Updating Software Storage Area **20663c** stores Battery Controller Updating Software **20663c1a**, CCD Unit Controller Updating Software **20663c1b**, Flash Light Unit Controller Updating Software **20663c1c**, Indicator Controller Updating Software **20663c1d**, Input Device Controller Updating Software **20663c1e**, LCD Controller Updating Software **20663c1f**, LED Controller Updating Software **20663c1g**, Memory Card Interface Controller Updating Software **20663c1h**, Microphone Controller Updating Software **20663c1i**, Photometer Controller Updating Software **20663c1j**, RAM Controller Updating Software **20663c1k**, ROM Controller Updating Software **20663c1l**, Signal Processor Controller Updating Software **20663c1m**, Signal Processor Controller Updating Software **20663c1n**, Solar Panel Controller Updating Software **20663c1o**, Speaker Controller Updating Software **20663c1p**, Vibrator Controller Updating Software **20663c1q**, Video Processor Controller Updating

Software **20663c1r**, Wireless Receiver Controller Updating Software **20663c1s**, Wireless Receiver Controller Updating Software **20663c1t**, Wireless Receiver Controller Updating Software **20663c1u**, Wireless Transmitter Controller Updating Software **20663c1v**, Wireless Transmitter Controller Updating Software **20663c1w**, and Wireless Transmitter Controller Updating Software **20663c1x**. Battery Controller Updating Software **20663c1a** is the software program described in Paragraph [0197] and Paragraph [0198]. CCD Unit Controller Updating Software **20663c1b** is the software program described in Paragraph [0199] and Paragraph [0200]. Flash Light Unit Controller Updating Software **20663c1c** is the software program described in Paragraph [0201] and Paragraph [0202]. Indicator Controller Updating Software **20663c1d** is the software program described in Paragraph [0203] and Paragraph [0204]. Input Device Controller Updating Software **20663c1e** is the software program described in Paragraph [0205] and Paragraph [0206]. LCD Controller Updating Software **20663c1f** is the software program described in Paragraph [0207] and Paragraph [0208]. LED Controller Updating Software **20663c1g** is the software program described in Paragraph [0209] and Paragraph [0210]. Memory Card Interface Controller Updating Software **20663c1h** is the software program described in Paragraph [0211] and Paragraph [0212]. Microphone Controller Updating Software **20663c1i** is the software program described in Paragraph [0213] and Paragraph [0214]. Photometer Controller Updating Software **20663c1j** is the software program described in Paragraph [0215] and Paragraph [0216]. RAM Controller Updating Software **20663c1k** is the software program described in Paragraph [0217] and Paragraph [0218]. ROM Controller Updating Software **20663c1l** is the software program described in Paragraph [0219] and Paragraph [0220]. Signal Processor Controller Updating Software **20663c1m** is the software program described in Paragraph [0221] and Paragraph [0222]. Signal Processor Controller Updating Software **20663c1n** is the software program described in Paragraph [0223] and Paragraph [0224]. Solar Panel Controller Updating Software **20663c1o** is the software program described in Paragraph [0225] and Paragraph [0226]. Speaker Controller Updating Software **20663c1p** is the software program described in Paragraph [0227] and Paragraph [0228]. Vibrator Controller Updating Software **20663c1q** is the software program described in Paragraph [0229] and Paragraph [0230]. Video Processor Controller Updating Software **20663c1r** is the software program described in Paragraph [0231] and Paragraph [0232]. Wireless Receiver Controller Updating Software **20663c1s** is the software program described in Paragraph [0233] and Paragraph [0234]. Wireless Receiver Controller Updating Software **20663c1t** is the software program described in Paragraph [0235] and Paragraph [0236]. Wireless Receiver Controller Updating Software **20663c1u** is the software program described in Paragraph [0237] and Paragraph [0238]. Wireless Transmitter Controller Updating Software **20663c1v** is the software program described in Paragraph [0239] and Paragraph [0240]. Wireless Transmitter Controller Updating Software **20663c1w** is the software program described in Paragraph [0241] and Paragraph [0242]. Wireless Transmitter Controller Updating Software **20663c1x** is the software program described in Paragraph [0243] and Paragraph [0244].

Paragraph [0191]—This Paragraph [0191] illustrates the storage areas included in Host H (Paragraph [0025]). In the present embodiment, Host H includes Operating System **H63OS** of which the data stored therein are described in Paragraph [0192], and OS Updating Information Storage

51

Area H63a of which the data and the software programs stored therein are described in Paragraph [0193].

Paragraph [0192]—This Paragraph [0192] illustrates the data stored in Operating System H63OS (Paragraph [0191]). In the present embodiment, Operating System H63OS includes Battery Controller H63OSa, CCD Unit Controller H63OSb, Flash Light Unit Controller H63OSc, Indicator Controller H63OSd, Input Device Controller H63OSe, LCD Controller H63OSf, LED Controller H63OSg, Memory Card Interface Controller H63OSH, Microphone Controller H63OSi, Photometer Controller H63OSj, RAM Controller H63OSk, ROM Controller H63OSl, Signal Processor Controller H63OSm, Signal Processor Controller H63OSn, Solar Panel Controller H63OSo, Speaker Controller H63OSp, Vibrator Controller H63OSq, Video Processor Controller H63OSr, Wireless Receiver Controller H63OSs, Wireless Receiver Controller H63OSt, Wireless Receiver Controller H63OSu, Wireless Transmitter Controller H63OSy, Wireless Transmitter Controller H63OSw, and Wireless Transmitter Controller H63OSx. Battery Controller H63OSa is the controller of the latest version which controls Battery 230 (not shown). CCD Unit Controller H63OSb is the controller of the latest version which controls CCD Unit 214 (not shown). Flash Light Unit Controller H63OSc is the controller of the latest version which controls Flash Light Unit 220 (not shown). Indicator Controller H63OSd is the controller of the latest version which controls Indicator 212 (not shown). Input Device Controller H63OSe is the controller of the latest version which controls Input Device 210 (not shown). LCD Controller H63OSf is the controller of the latest version which controls LCD 201 (not shown). LED Controller H63OSg is the controller of the latest version which controls LED 219 (not shown). Memory Card Interface Controller H63OSH is the controller of the latest version which controls Memory Card Interface 221 (not shown). Microphone Controller H63OSi is the controller of the latest version which controls Microphone 215 (not shown). Photometer Controller H63OSj is the controller of the latest version which controls Photometer 232 (not shown). RAM Controller H63OSk is the controller of the latest version which controls Host H (not shown). ROM Controller H63OSl is the controller of the latest version which controls ROM 207 (not shown). Signal Processor Controller H63OSm is the controller of the latest version which controls Signal Processor 205 (not shown). Signal Processor Controller H63OSn is the controller of the latest version which controls Signal Processor 208 (not shown). Solar Panel Controller H63OSo is the controller of the latest version which controls Solar Panel 229 (not shown). Speaker Controller H63OSp is the controller of the latest version which controls Speaker 216L (not shown). Vibrator Controller H63OSq is the controller of the latest version which controls Vibrator 217 (not shown). Video Processor Controller H63OSr is the controller of the latest version which controls Video Processor 202 (not shown). Wireless Receiver Controller H63OSs is the controller of the latest version which controls Wireless Receiver 224 (not shown). Wireless Receiver Controller H63OSt is the controller of the latest version which controls Wireless Receiver 225 (not shown). Wireless Receiver Controller H63OSu is the controller of the latest version which controls Wireless Receiver 226 (not shown). Wireless Transmitter Controller H63OSy is the controller of the latest version which controls Wireless Transmitter 222 (not shown). Wireless Transmitter Controller H63OSw is the controller of the latest version which controls Wireless Transmitter 223 (not shown). Wireless Transmitter Controller H63OSx is the controller of the latest version which controls Wireless Transmitter 227 (not shown). The

52

data stored in Operating System Storage Area H63OS are updated periodically. For the avoidance of doubt, the data stored in Operating System H63OS are illustrative, and other types of data, which are utilized to update Operating System H63OS of Communication Device 200 by implementing the present function, are also stored therein, such as DLLs, drivers, security implementing program. The data stored in Operating System H63OS are updated periodically thereby the data are always of the latest version.

Paragraph [0193]—This Paragraph [0193] illustrates the storage areas included in OS Updating Information Storage Area H63a (Paragraph [0191]). In the present embodiment, OS Updating Information Storage Area H63a includes OS Updating Data Storage Area H63b and OS Updating Software Storage Area H63c. OS Updating Data Storage Area H63b stores the data necessary to implement the present function on the side of Host H (Paragraph [0025]), such as the ones described in Paragraph [0194]. OS Updating Software Storage Area H63c stores the software programs necessary to implement the present function on the side of Host H, such as the ones described in Paragraph [0196].

Paragraph [0194]—This Paragraph [0194] illustrates the storage area included in OS Updating Data Storage Area H63b (Paragraph [0193]). In the present embodiment, OS Updating Data Storage Area H63b includes OS Version Data Storage Area H63b1. OS Version Data Storage Area H63b1 stores the data described in Paragraph [0195].

Paragraph [0195]—This Paragraph [0195] illustrates the data stored in OS Version Data Storage Area H63b1 (Paragraph [0194]). In the present embodiment, OS Version Data Storage Area H63b1 includes Battery Controller Version Data H63b1a, CCD Unit Controller Version Data H63b1b, Flash Light Unit Controller Version Data H63b1c, Indicator Controller Version Data H63b1d, Input Device Controller Version Data H63b1e, LCD Controller Version Data H63b1f, LED Controller Version Data H63b1g, Memory Card Interface Controller Version Data H63b1h, Microphone Controller Version Data H63b1i, Photometer Controller Version Data H63b1j, RAM Controller Version Data H63b1k, ROM Controller Version Data H63b1l, Signal Processor Controller Version Data H63b1m, Signal Processor Controller Version Data H63b1n, Solar Panel Controller Version Data H63b1o, Speaker Controller Version Data H63b1p, Vibrator Controller Version Data H63b1q, Video Processor Controller Version Data H63b1r, Wireless Receiver Controller Version Data H63b1s, Wireless Receiver Controller Version Data H63b1t, Wireless Receiver Controller Version Data H63b1u, Wireless Transmitter Controller Version Data H63b1y, Wireless Transmitter Controller Version Data H63b1w, and Wireless Transmitter Controller Version Data H63b1x. Battery Controller Version Data H63b1a is the version data representing the latest version of Battery Controller H63OSa (Paragraph [0192]). CCD Unit Controller Version Data H63b1b is the version data representing the latest version of CCD Unit Controller H63OSb (Paragraph [0192]). Flash Light Unit Controller Version Data H63b1c is the version data representing the latest version of Flash Light Unit Controller H63OSc (Paragraph [0192]). Indicator Controller Version Data H63b1d is the version data representing the latest version of Indicator Controller H63OSd (Paragraph [0192]). Input Device Controller Version Data H63b1e is the version data representing the latest version of Input Device Controller H63OSe (Paragraph [0192]). LCD Controller Version Data H63b1f is the version data representing the latest version of LCD Controller H63OSf (Paragraph [0192]). LED Controller Version Data H63b1g is the version data representing the latest version of LED Controller H63OSg (Paragraph

[0192]). Memory Card Interface Controller Version Data **H63b1h** is the version data representing the latest version of Memory Card Interface Controller **H63OSh** (Paragraph [0192]). Microphone Controller Version Data **H63b1i** is the version data representing the latest version of Microphone Controller **H63OSi** (Paragraph [0192]). Photometer Controller Version Data **H63b1j** is the version data representing the latest version of Photometer Controller **H63OSj** (Paragraph [0192]). RAM Controller Version Data **H63b1k** is the version data representing the latest version of RAM Controller **H63OSk** (Paragraph [0192]). ROM Controller Version Data **H63b1l** is the version data representing the latest version of ROM Controller **H63OSl** (Paragraph [0192]). Signal Processor Controller Version Data **H63b1m** is the version data representing the latest version of Signal Processor Controller **H63OSm** (Paragraph [0192]). Signal Processor Controller Version Data **H63b1n** is the version data representing the latest version of Signal Processor Controller **H63OSn** (Paragraph [0192]). Solar Panel Controller Version Data **H63b1o** is the version data representing the latest version of Solar Panel Controller **H63OSo** (Paragraph [0192]). Speaker Controller Version Data **H63b1p** is the version data representing the latest version of Speaker Controller **H63OSp** (Paragraph [0192]). Vibrator Controller Version Data **H63b1q** is the version data representing the latest version of Vibrator Controller **H63OSq** (Paragraph [0192]). Video Processor Controller Version Data **H63b1r** is the version data representing the latest version of Video Processor Controller **H63OSr** (Paragraph [0192]). Wireless Receiver Controller Version Data **H63b1s** is the version data representing the latest version of Wireless Receiver Controller **H63OSS** (Paragraph [0192]). Wireless Receiver Controller Version Data **H63b1t** is the version data representing the latest version of Wireless Receiver Controller **H63OST** (Paragraph [0192]). Wireless Receiver Controller Version Data **H63b1u** is the version data representing the latest version of Wireless Receiver Controller **H63OSu** (Paragraph [0192]). Wireless Transmitter Controller Version Data **H63b1y** is the version data representing the latest version of Wireless Transmitter Controller **H63OSy** (Paragraph [0192]). Wireless Transmitter Controller Version Data **H63b1w** is the version data representing the latest version of Wireless Transmitter Controller **H63OSw** (Paragraph [0192]). Wireless Transmitter Controller Version Data **H63b1x** is the version data representing the latest version of Wireless Transmitter Controller **H63OSx** (Paragraph [0192]). Here, the version data is composed of numeric data, such as '1', '2', and '3', wherein '1' represents version '1.0', '2' represents version '2.0', and '3' represents version '3.0'. The data stored in OS Version Data Storage Area **H63b1** are updated periodically.

Paragraph [0196]—This Paragraph [0196] illustrates the software programs stored in OS Updating Software Storage Area **H63c** (Paragraph [0193]). In the present embodiment, OS Updating Software Storage Area **H63c** stores Battery Controller Updating Software **H63c1a**, CCD Unit Controller Updating Software **H63c1b**, Flash Light Unit Controller Updating Software **H63c1c**, Indicator Controller Updating Software **H63c1d**, Input Device Controller Updating Software **H63c1e**, LCD Controller Updating Software **H63c1f**, LED Controller Updating Software **H63c1g**, Memory Card Interface Controller Updating Software **H63c1h**, Microphone Controller Updating Software **H63c1i**, Photometer Controller Updating Software **H63c1j**, RAM Controller Updating Software **H63c1k**, ROM Controller Updating Software **H63c1l**, Signal Processor Controller Updating Software **H63c1m**, Signal Processor Controller Updating Software **H63c1n**, Solar Panel Controller Updating Software **H63c1o**,

Speaker Controller Updating Software **H63c1p**, Vibrator Controller Updating Software **H63c1q**, Video Processor Controller Updating Software **H63c1r**, Wireless Receiver Controller Updating Software **H63c1s**, Wireless Receiver Controller Updating Software **H63c1t**, Wireless Receiver Controller Updating Software **H63c1u**, Wireless Transmitter Controller Updating Software **H63c1v**, Wireless Transmitter Controller Updating Software **H63c1w**, and Wireless Transmitter Controller Updating Software **H63c1x**. Battery Controller Updating Software **H63c1a** is the software program described in Paragraph [0197] and Paragraph [0198]. CCD Unit Controller Updating Software **H63c1b** is the software program described in Paragraph [0199] and Paragraph [0200]. Flash Light Unit Controller Updating Software **H63c1c** is the software program described in Paragraph [0201] and Paragraph [0202]. Indicator Controller Updating Software **H63c1d** is the software program described in Paragraph [0203] and Paragraph [0204]. Input Device Controller Updating Software **H63c1e** is the software program described in Paragraph [0205] and Paragraph [0206]. LCD Controller Updating Software **H63c1f** is the software program described in Paragraph [0207] and Paragraph [0208]. LED Controller Updating Software **H63c1g** is the software program described in Paragraph [0209] and Paragraph [0210]. Memory Card Interface Controller Updating Software **H63c1h** is the software program described in Paragraph [0211] and Paragraph [0212]. Microphone Controller Updating Software **H63c1i** is the software program described in Paragraph [0213] and Paragraph [0214]. Photometer Controller Updating Software **H63c1j** is the software program described in Paragraph [0215] and Paragraph [0216]. RAM Controller Updating Software **H63c1k** is the software program described in Paragraph [0217] and Paragraph [0218]. ROM Controller Updating Software **H63c1l** is the software program described in Paragraph [0219] and Paragraph [0220]. Signal Processor Controller Updating Software **H63c1m** is the software program described in Paragraph [0221] and Paragraph [0222]. Signal Processor Controller Updating Software **H63c1n** is the software program described in Paragraph [0223] and Paragraph [0224]. Solar Panel Controller Updating Software **H63c1o** is the software program described in Paragraph [0225] and Paragraph [0226]. Speaker Controller Updating Software **H63c1p** is the software program described in Paragraph [0227] and Paragraph [0228]. Vibrator Controller Updating Software **H63c1q** is the software program described in Paragraph [0229] and Paragraph [0230]. Video Processor Controller Updating Software **H63c1r** is the software program described in Paragraph [0231] and Paragraph [0232]. Wireless Receiver Controller Updating Software **H63c1s** is the software program described in Paragraph [0233] and Paragraph [0234]. Wireless Receiver Controller Updating Software **H63c1t** is the software program described in Paragraph [0235] and Paragraph [0236]. Wireless Receiver Controller Updating Software **H63c1u** is the software program described in Paragraph [0237] and Paragraph [0238]. Wireless Transmitter Controller Updating Software **H63c1v** is the software program described in Paragraph [0239] and Paragraph [0240]. Wireless Transmitter Controller Updating Software **H63c1w** is the software program described in Paragraph [0241] and Paragraph [0242]. Wireless Transmitter Controller Updating Software **H63c1x** is the software program described in Paragraph [0243] and Paragraph [0244]. The foregoing software programs are automatically implemented periodically or implemented manually by utilizing Input Device **210** (FIG. 1) or via voice recognition system.

55

Paragraph [0197]—This Paragraph [0197] illustrates Battery Controller Updating Software **H63c1a** (Paragraph [0196]) of Host H (Paragraph [0025]) and Battery Controller Updating Software **20663c1a** (Paragraph [0190]) of Communication Device **200**, which update Battery Controller **20663OSa** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Battery Controller Version Data **20663b1a** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Battery Controller Version Data **20663b1a** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Battery Controller Version Data **20663b1a** (Paragraph [0189]) with Battery Controller Version Data **H63b1a** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Battery Controller Version Data **20663b1a** of Communication Device **200** is of an old version. Host H retrieves Battery Controller **H63OSa**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Battery Controller **H63OSa** from Host H (S5), CPU **211** stores Battery Controller **H63OSa** as Battery Controller **20663OSa** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Battery Controller **20663OSa** (Paragraph [0185]) is deleted.

Paragraph [0198]—This Paragraph [0198] illustrates another embodiment of Battery Controller Updating Software **H63c1a** (Paragraph [0196]) of Host H (Paragraph [0025]) and Battery Controller Updating Software **20663c1a** (Paragraph [0190]) of Communication Device **200**, which update Battery Controller **20663OSa** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Battery Controller Update Request, which is received by Host H (S1). Here, the Battery Controller Update Request is a request to send Battery Controller Version Data **H63b1a** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Battery Controller Version Data **H63b1a** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Battery Controller Version Data **H63b1a** from Host H (S3), CPU **211** compares Battery Controller Version Data **H63b1a** with Battery Controller Version Data **20663b1a** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Battery Controller Version Data **20663b1a** of Communication Device **200** is of an old version. CPU **211** sends a New Battery Controller Sending Request, which is received by Host H (S5). Here, the New Battery Controller Sending Request is a request to send Battery Controller **H63OSa** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Battery Controller **H63OSa** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Battery Controller **H63OSa** from Host H (S7), CPU **211** stores Battery Controller **H63OSa** as Battery Controller **20663OSa** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Battery Controller **20663OSa** (Paragraph [0185]) is deleted.

Paragraph [0199]—This Paragraph [0199] illustrates CCD Unit Controller Updating Software **H63c1b** (Paragraph [0196]) of Host H (Paragraph [0025]) and CCD Unit Controller Updating Software **20663c1b** (Paragraph [0190]) of

56

Communication Device **200**, which update CCD Unit Controller **20663OSb** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves CCD Unit Controller Version Data **20663b1b** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving CCD Unit Controller Version Data **20663b1b** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares CCD Unit Controller Version Data **20663b1b** (Paragraph [0189]) with CCD Unit Controller Version Data **H63b1b** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that CCD Unit Controller Version Data **20663b1b** of Communication Device **200** is of an old version. Host H retrieves CCD Unit Controller **H63OSb**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving CCD Unit Controller **H63OSb** from Host H (S5), CPU **211** stores CCD Unit Controller **H63OSb** as CCD Unit Controller **20663OSb** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of CCD Unit Controller **20663OSb** (Paragraph [0185]) is deleted.

Paragraph [0200]—This Paragraph [0200] illustrates another embodiment of CCD Unit Controller Updating Software **H63c1b** (Paragraph [0196]) of Host H (Paragraph [0025]) and CCD Unit Controller Updating Software **20663c1b** (Paragraph [0190]) of Communication Device **200**, which update CCD Unit Controller **20663OSb** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a CCD Unit Controller Update Request, which is received by Host H (S1). Here, the CCD Unit Controller Update Request is a request to send CCD Unit Controller Version Data **H63b1b** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves CCD Unit Controller Version Data **H63b1b** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving CCD Unit Controller Version Data **H63b1b** from Host H (S3), CPU **211** compares CCD Unit Controller Version Data **H63b1b** with CCD Unit Controller Version Data **20663b1b** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that CCD Unit Controller Version Data **20663b1b** of Communication Device **200** is of an old version. CPU **211** sends a New CCD Unit Controller Sending Request, which is received by Host H (S5). Here, the New CCD Unit Controller Sending Request is a request to send CCD Unit Controller **H63OSb** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves CCD Unit Controller **H63OSb** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving CCD Unit Controller **H63OSb** from Host H (S7), CPU **211** stores CCD Unit Controller **H63OSb** as CCD Unit Controller **20663OSb** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of CCD Unit Controller **20663OSb** (Paragraph [0185]) is deleted.

Paragraph [0201]—This Paragraph [0201] illustrates Flash Light Unit Controller Updating Software **H63c1c** (Paragraph [0196]) of Host H (Paragraph [0025]) and Flash Light Unit Controller Updating Software **20663c1c** (Paragraph [0190]) of Communication Device **200**, which update Flash Light Unit Controller **20663OSc** stored in Operating System

57

20663OS (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Flash Light Unit Controller Version Data **20663b1c** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Flash Light Unit Controller Version Data **20663b1c** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Flash Light Unit Controller Version Data **20663b1c** (Paragraph [0189]) with Flash Light Unit Controller Version Data **H63b1c** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Flash Light Unit Controller Version Data **20663b1c** of Communication Device **200** is of an old version. Host H retrieves Flash Light Unit Controller **H63OSc**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Flash Light Unit Controller **H63OSc** from Host H (S5), CPU **211** stores Flash Light Unit Controller **H63OSc** as Flash Light Unit Controller **20663OSc** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Flash Light Unit Controller **20663OSc** (Paragraph [0185]) is deleted.

Paragraph [0202]—This Paragraph [0202] illustrates another embodiment of Flash Light Unit Controller Updating Software **H63c1c** (Paragraph [0196]) of Host H (Paragraph [0025]) and Flash Light Unit Controller Updating Software **20663c1c** (Paragraph [0190]) of Communication Device **200**, which update Flash Light Unit Controller **20663OSc** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Flash Light Unit Controller Update Request, which is received by Host H (S1). Here, the Flash Light Unit Controller Update Request is a request to send Flash Light Unit Controller Version Data **H63b1c** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Flash Light Unit Controller Version Data **H63b1c** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Flash Light Unit Controller Version Data **H63b1c** from Host H (S3), CPU **211** compares Flash Light Unit Controller Version Data **H63b1c** with Flash Light Unit Controller Version Data **20663b1c** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Flash Light Unit Controller Version Data **20663b1c** of Communication Device **200** is of an old version. CPU **211** sends a New Flash Light Unit Controller Sending Request, which is received by Host H (S5). Here, the New Flash Light Unit Controller Sending Request is a request to send Flash Light Unit Controller **H63OSc** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Flash Light Unit Controller **H63OSc** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Flash Light Unit Controller **H63OSc** from Host H (S7), CPU **211** stores Flash Light Unit Controller **H63OSc** as Flash Light Unit Controller **20663OSc** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Flash Light Unit Controller **20663OSc** (Paragraph [0185]) is deleted.

Paragraph [0203]—This Paragraph [0203] illustrates Indicator Controller Updating Software **H63c1d** (Paragraph [0196]) of Host H (Paragraph [0025]) and Indicator Controller Updating Software **20663c1d** (Paragraph [0190]) of Communication Device **200**, which update Indicator Controller

58

20663OSd stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Indicator Controller Version Data **20663b1d** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Indicator Controller Version Data **20663b1d** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Indicator Controller Version Data **20663b1d** (Paragraph [0189]) with Indicator Controller Version Data **H63b1d** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Indicator Controller Version Data **20663b1d** of Communication Device **200** is of an old version. Host H retrieves Indicator Controller **H63OSd**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Indicator Controller **H63OSd** from Host H (S5), CPU **211** stores Indicator Controller **H63OSd** as Indicator Controller **20663OSd** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Indicator Controller **20663OSd** (Paragraph [0185]) is deleted.

Paragraph [0204]—This Paragraph [0204] illustrates another embodiment of Indicator Controller Updating Software **H63c1d** (Paragraph [0196]) of Host H (Paragraph [0025]) and Indicator Controller Updating Software **20663c1d** (Paragraph [0190]) of Communication Device **200**, which update Indicator Controller **20663OSd** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Indicator Controller Update Request, which is received by Host H (S1). Here, the Indicator Controller Update Request is a request to send Indicator Controller Version Data **H63b1d** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Indicator Controller Version Data **H63b1d** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Indicator Controller Version Data **H63b1d** from Host H (S3), CPU **211** compares Indicator Controller Version Data **H63b1d** with Indicator Controller Version Data **20663b1d** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Indicator Controller Version Data **20663b1d** of Communication Device **200** is of an old version. CPU **211** sends a New Indicator Controller Sending Request, which is received by Host H (S5). Here, the New Indicator Controller Sending Request is a request to send Indicator Controller **H63OSd** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Indicator Controller **H63OSd** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Indicator Controller **H63OSd** from Host H (S7), CPU **211** stores Indicator Controller **H63OSd** as Indicator Controller **20663OSd** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Indicator Controller **20663OSd** (Paragraph [0185]) is deleted.

Paragraph [0205]—This Paragraph [0205] illustrates Input Device Controller Updating Software **H63c1e** (Paragraph [0196]) of Host H (Paragraph [0025]) and Input Device Controller Updating Software **20663c1e** (Paragraph [0190]) of Communication Device **200**, which update Input Device Controller **20663OSe** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication

Device **200** retrieves Input Device Controller Version Data **20663b1e** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Input Device Controller Version Data **20663b1e** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Input Device Controller Version Data **20663b1e** (Paragraph [0189]) with Input Device Controller Version Data **H63b1e** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Input Device Controller Version Data **20663b1e** of Communication Device **200** is of an old version. Host H retrieves Input Device Controller **H63OSe**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Input Device Controller **H63OSe** from Host H (S5), CPU **211** stores Input Device Controller **H63OSe** as Input Device Controller **20663OSe** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Input Device Controller **20663OSe** (Paragraph [0185]) is deleted.

Paragraph [0206]—This Paragraph [0206] illustrates another embodiment of Input Device Controller Updating Software **H63c1e** (Paragraph [0196]) of Host H (Paragraph [0025]) and Input Device Controller Updating Software **20663c1e** (Paragraph [0190]) of Communication Device **200**, which update Input Device Controller **20663OSe** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Input Device Controller Update Request, which is received by Host H (S1). Here, the Input Device Controller Update Request is a request to send Input Device Controller Version Data **H63b1e** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Input Device Controller Version Data **H63b1e** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Input Device Controller Version Data **H63b1e** from Host H (S3), CPU **211** compares Input Device Controller Version Data **H63b1e** with Input Device Controller Version Data **20663b1e** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Input Device Controller Version Data **20663b1e** of Communication Device **200** is of an old version. CPU **211** sends a New Input Device Controller Sending Request, which is received by Host H (S5). Here, the New Input Device Controller Sending Request is a request to send Input Device Controller **H63OSe** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Input Device Controller **H63OSe** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Input Device Controller **H63OSe** from Host H (S7), CPU **211** stores Input Device Controller **H63OSe** as Input Device Controller **20663OSe** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Input Device Controller **20663OSe** (Paragraph [0185]) is deleted.

Paragraph [0207]—This Paragraph [0207] illustrates LCD Controller Updating Software **H63c1f** (Paragraph [0196]) of Host H (Paragraph [0025]) and LCD Controller Updating Software **20663c1f** (Paragraph [0190]) of Communication Device **200**, which update LCD Controller **20663OSf** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves LCD Controller Version Data **20663b1f** from OS Version Data Storage

Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving LCD Controller Version Data **20663b1f** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares LCD Controller Version Data **20663b1f** (Paragraph [0189]) with LCD Controller Version Data **H63b1f** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that LCD Controller Version Data **20663b1f** of Communication Device **200** is of an old version. Host H retrieves LCD Controller **H63OSf**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving LCD Controller **H63OSf** from Host H (S5), CPU **211** stores LCD Controller **H63OSf** as LCD Controller **20663OSf** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of LCD Controller **20663OSf** (Paragraph [0185]) is deleted.

Paragraph [0208]—This Paragraph [0208] illustrates another embodiment of LCD Controller Updating Software **H63c1f** (Paragraph [0196]) of Host H (Paragraph [0025]) and LCD Controller Updating Software **20663c1f** (Paragraph [0190]) of Communication Device **200**, which update LCD Controller **20663OSf** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a LCD Controller Update Request, which is received by Host H (S1). Here, the LCD Controller Update Request is a request to send LCD Controller Version Data **H63b1f** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves LCD Controller Version Data **H63b1f** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving LCD Controller Version Data **H63b1f** from Host H (S3), CPU **211** compares LCD Controller Version Data **H63b1f** with LCD Controller Version Data **20663b1f** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that LCD Controller Version Data **20663b1f** of Communication Device **200** is of an old version. CPU **211** sends a New LCD Controller Sending Request, which is received by Host H (S5). Here, the New LCD Controller Sending Request is a request to send LCD Controller **H63OSf** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves LCD Controller **H63OSf** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving LCD Controller **H63OSf** from Host H (S7), CPU **211** stores LCD Controller **H63OSf** as LCD Controller **20663OSf** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of LCD Controller **20663OSf** (Paragraph [0185]) is deleted.

Paragraph [0209]—This Paragraph [0209] illustrates LED Controller Updating Software **H63c1g** (Paragraph [0196]) of Host H (Paragraph [0025]) and LED Controller Updating Software **20663c1g** (Paragraph [0190]) of Communication Device **200**, which update LED Controller **20663OSg** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves LED Controller Version Data **20663b1g** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving LED Controller Version Data **20663b1g** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares LED Controller Version Data **20663b1g** (Paragraph [0189]) with LED Controller Version Data **H63b1g** stored in OS Version Data Storage Area **H63b1**

61

(Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that LED Controller Version Data **20663b1g** of Communication Device **200** is of an old version. Host H retrieves LED Controller H63OSg, which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving LED Controller H63OSg from Host H (S5), CPU **211** stores LED Controller H63OSg as LED Controller **20663OSg** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of LED Controller **20663OSg** (Paragraph [0185]) is deleted.

Paragraph [0210]—This Paragraph [0210] illustrates another embodiment of LED Controller Updating Software H63c1g (Paragraph [0196]) of Host H (Paragraph [0025]) and LED Controller Updating Software **20663c1g** (Paragraph [0190]) of Communication Device **200**, which update LED Controller **20663OSg** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a LED Controller Update Request, which is received by Host H (S1). Here, the LED Controller Update Request is a request to send LED Controller Version Data H63b1g (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves LED Controller Version Data H63b1g from OS Version Data Storage Area H63b1 (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving LED Controller Version Data H63b1g from Host H (S3), CPU **211** compares LED Controller Version Data H63b1g with LED Controller Version Data **20663b1g** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that LED Controller Version Data **20663b1g** of Communication Device **200** is of an old version. CPU **211** sends a New LED Controller Sending Request, which is received by Host H (S5). Here, the New LED Controller Sending Request is a request to send LED Controller H63OSg (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves LED Controller H63OSg (Paragraph [0192]), which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving LED Controller H63OSg from Host H (S7), CPU **211** stores LED Controller H63OSg as LED Controller **20663OSg** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of LED Controller **20663OSg** (Paragraph [0185]) is deleted.

Paragraph [0211]—This Paragraph [0211] illustrates Memory Card Interface Controller Updating Software H63c1h (Paragraph [0196]) of Host H (Paragraph [0025]) and Memory Card Interface Controller Updating Software **20663c1h** (Paragraph [0190]) of Communication Device **200**, which update Memory Card Interface Controller **20663OSh** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Memory Card Interface Controller Version Data **20663b1h** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Memory Card Interface Controller Version Data **20663b1h** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Memory Card Interface Controller Version Data **20663b1h** (Paragraph [0189]) with Memory Card Interface Controller Version Data H63b1h stored in OS Version Data Storage Area H63b1 (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Memory Card Interface Controller Version Data **20663b1h** of Communication Device **200** is of an old version. Host H retrieves Memory

62

Card Interface Controller H63OSh, which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Memory Card Interface Controller H63OSh from Host H (S5), CPU **211** stores Memory Card Interface Controller H63OSh as Memory Card Interface Controller **20663OSh** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Memory Card Interface Controller **20663OSh** (Paragraph [0185]) is deleted.

Paragraph [0212]—This Paragraph [0212] illustrates another embodiment of Memory Card Interface Controller Updating Software H63c1h (Paragraph [0196]) of Host H (Paragraph [0025]) and Memory Card Interface Controller Updating Software **20663c1h** (Paragraph [0190]) of Communication Device **200**, which update Memory Card Interface Controller **20663OSh** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Memory Card Interface Controller Update Request, which is received by Host H (S1). Here, the Memory Card Interface Controller Update Request is a request to send Memory Card Interface Controller Version Data H63b1h (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Memory Card Interface Controller Version Data H63b1h from OS Version Data Storage Area H63b1 (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Memory Card Interface Controller Version Data H63b1h from Host H (S3), CPU **211** compares Memory Card Interface Controller Version Data H63b1h with Memory Card Interface Controller Version Data **20663b1h** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Memory Card Interface Controller Version Data **20663b1h** of Communication Device **200** is of an old version. CPU **211** sends a New Memory Card Interface Controller Sending Request, which is received by Host H (S5). Here, the New Memory Card Interface Controller Sending Request is a request to send Memory Card Interface Controller H63OSh (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Memory Card Interface Controller H63OSh (Paragraph [0192]), which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Memory Card Interface Controller H63OSh from Host H (S7), CPU **211** stores Memory Card Interface Controller H63OSh as Memory Card Interface Controller **20663OSh** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Memory Card Interface Controller **20663OSh** (Paragraph [0185]) is deleted.

Paragraph [0213]—This Paragraph [0213] illustrates Microphone Controller Updating Software H63c1i (Paragraph [0196]) of Host H (Paragraph [0025]) and Microphone Controller Updating Software **20663c1i** (Paragraph [0190]) of Communication Device **200**, which update Microphone Controller **20663OSi** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Microphone Controller Version Data **20663b1i** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Microphone Controller Version Data **20663b1i** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Microphone Controller Version Data **20663b1i** (Paragraph [0189]) with Microphone Controller Version Data

H63b1i stored in OS Version Data Storage Area H63b1 (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Microphone Controller Version Data 20663b1i of Communication Device 200 is of an old version. Host H retrieves Microphone Controller H63OSi, which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S4). Upon receiving Microphone Controller H63OSi from Host H (S5), CPU 211 stores Microphone Controller H63OSi as Microphone Controller 20663OSi in Operating System 20663OS (Paragraph [0185]) (S6). The old version of Microphone Controller 20663OSi (Paragraph [0185]) is deleted.

Paragraph [0214]—This Paragraph [0214] illustrates another embodiment of Microphone Controller Updating Software H63c1i (Paragraph [0196]) of Host H (Paragraph [0025]) and Microphone Controller Updating Software 20663c1i (Paragraph [0190]) of Communication Device 200, which update Microphone Controller 20663OSi stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 sends a Microphone Controller Update Request, which is received by Host H (S1). Here, the Microphone Controller Update Request is a request to send Microphone Controller Version Data H63b1i (Paragraph [0195]) stored in Host H to Communication Device 200. In response to the request, Host H retrieves Microphone Controller Version Data H63b1i from OS Version Data Storage Area H63b1 (Paragraph [0195]), and sends the data to Communication Device 200 (S2). Upon receiving Microphone Controller Version Data H63b1i from Host H (S3), CPU 211 compares Microphone Controller Version Data H63b1i with Microphone Controller Version Data 20663b1i stored in OS Version Data Storage Area 20663b1 (Paragraph [0189]) of Communication Device 200 (S4). Assuming that CPU211 detects in S4 that Microphone Controller Version Data 20663b1i of Communication Device 200 is of an old version. CPU 211 sends a New Microphone Controller Sending Request, which is received by Host H (S5). Here, the New Microphone Controller Sending Request is a request to send Microphone Controller H63OSi (Paragraph [0192]) stored in Host H to Communication Device 200. Host H retrieves Microphone Controller H63OSi (Paragraph [0192]), which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S6). Upon receiving Microphone Controller H63OSi from Host H (S7), CPU 211 stores Microphone Controller H63OSi as Microphone Controller 20663OSi in Operating System 20663OS (Paragraph [0185]) (S8). The old version of Microphone Controller 20663OSi (Paragraph [0185]) is deleted.

Paragraph [0215]—This Paragraph [0215] illustrates Photometer Controller Updating Software H63c1j (Paragraph [0196]) of Host H (Paragraph [0025]) and Photometer Controller Updating Software 20663c1j (Paragraph [0190]) of Communication Device 200, which update Photometer Controller 20663OSj stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves Photometer Controller Version Data 20663b1j from OS Version Data Storage Area 20663b1 (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Photometer Controller Version Data 20663b1j (Paragraph [0189]) from Communication Device 200 (S2), Host H compares Photometer Controller Version Data 20663b1j (Paragraph [0189]) with Photometer Controller Version Data H63b1j stored in OS Version Data Storage Area H63b1 (Para-

graph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Photometer Controller Version Data 20663b1j of Communication Device 200 is of an old version. Host H retrieves Photometer Controller H63OSj, which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S4). Upon receiving Photometer Controller H63OSj from Host H (S5), CPU 211 stores Photometer Controller H63OSj as Photometer Controller 20663OSj in Operating System 20663OS (Paragraph [0185]) (S6). The old version of Photometer Controller 20663OSj (Paragraph [0185]) is deleted.

Paragraph [0216]—This Paragraph [0216] illustrates another embodiment of Photometer Controller Updating Software H63c1j (Paragraph [0196]) of Host H (Paragraph [0025]) and Photometer Controller Updating Software 20663c1j (Paragraph [0190]) of Communication Device 200, which update Photometer Controller 20663OSj stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 sends a Photometer Controller Update Request, which is received by Host H (S1). Here, the Photometer Controller Update Request is a request to send Photometer Controller Version Data H63b1j (Paragraph [0195]) stored in Host H to Communication Device 200. In response to the request, Host H retrieves Photometer Controller Version Data H63b1j from OS Version Data Storage Area H63b1 (Paragraph [0195]), and sends the data to Communication Device 200 (S2). Upon receiving Photometer Controller Version Data H63b1j from Host H (S3), CPU 211 compares Photometer Controller Version Data H63b1j with Photometer Controller Version Data 20663b1j stored in OS Version Data Storage Area 20663b1 (Paragraph [0189]) of Communication Device 200 (S4). Assuming that CPU211 detects in S4 that Photometer Controller Version Data 20663b1j of Communication Device 200 is of an old version. CPU 211 sends a New Photometer Controller Sending Request, which is received by Host H (S5). Here, the New Photometer Controller Sending Request is a request to send Photometer Controller H63OSj (Paragraph [0192]) stored in Host H to Communication Device 200. Host H retrieves Photometer Controller H63OSj (Paragraph [0192]), which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S6). Upon receiving Photometer Controller H63OSj from Host H (S7), CPU 211 stores Photometer Controller H63OSj as Photometer Controller 20663OSj in Operating System 20663OS (Paragraph [0185]) (S8). The old version of Photometer Controller 20663OSj (Paragraph [0185]) is deleted.

Paragraph [0217]—This Paragraph [0217] illustrates RAM Controller Updating Software H63c1k (Paragraph [0196]) of Host H (Paragraph [0025]) and RAM Controller Updating Software 20663c1k (Paragraph [0190]) of Communication Device 200, which update RAM Controller 20663OSk stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves RAM Controller Version Data 20663b1k from OS Version Data Storage Area 20663b1 (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving RAM Controller Version Data 20663b1k (Paragraph [0189]) from Communication Device 200 (S2), Host H compares RAM Controller Version Data 20663b1k (Paragraph [0189]) with RAM Controller Version Data H63b1k stored in OS Version Data Storage Area H63b1 (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that RAM Controller

65

Version Data **20663b1k** of Communication Device **200** is of an old version. Host H retrieves RAM Controller **H63OSk**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving RAM Controller **H63OSk** from Host H (S5), CPU **211** stores RAM Controller **H63OSk** as RAM Controller **20663OSk** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of RAM Controller **20663OSk** (Paragraph [0185]) is deleted.

Paragraph [0218]—This Paragraph [0218] illustrates another embodiment of RAM Controller Updating Software **H63c1k** (Paragraph [0196]) of Host H (Paragraph [0025]) and RAM Controller Updating Software **20663c1k** (Paragraph [0190]) of Communication Device **200**, which update RAM Controller **20663OSk** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a RAM Controller Update Request, which is received by Host H (S1). Here, the RAM Controller Update Request is a request to send RAM Controller Version Data **H63b1k** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves RAM Controller Version Data **H63b1k** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving RAM Controller Version Data **H63b1k** from Host H (S3), CPU **211** compares RAM Controller Version Data **H63b1k** with RAM Controller Version Data **20663b1k** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that RAM Controller Version Data **20663b1k** of Communication Device **200** is of an old version. CPU **211** sends a New RAM Controller Sending Request, which is received by Host H (S5). Here, the New RAM Controller Sending Request is a request to send RAM Controller **H63OSk** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves RAM Controller **H63OSk** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving RAM Controller **H63OSk** from Host H (S7), CPU **211** stores RAM Controller **H63OSk** as RAM Controller **20663OSk** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of RAM Controller **20663OSk** (Paragraph [0185]) is deleted.

Paragraph [0219]—This Paragraph [0219] illustrates ROM Controller Updating Software **H63c1l** (Paragraph [0196]) of Host H (Paragraph [0025]) and ROM Controller Updating Software **20663c1l** (Paragraph [0190]) of Communication Device **200**, which update ROM Controller **20663OS1** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves ROM Controller Version Data **20663b1l** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving ROM Controller Version Data **20663b1l** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares ROM Controller Version Data **20663b1l** (Paragraph [0189]) with ROM Controller Version Data **H63b1l** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that ROM Controller Version Data **20663b1l** of Communication Device **200** is of an old version. Host H retrieves ROM Controller **H63OS1**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to

66

Communication Device **200** (S4). Upon receiving ROM Controller **H63OS1** from Host H (S5), CPU **211** stores ROM Controller **H63OS1** as ROM Controller **20663OS1** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of ROM Controller **20663OS1** (Paragraph [0185]) is deleted.

Paragraph [0220]—This Paragraph [0220] illustrates another embodiment of ROM Controller Updating Software **H63c1l** (Paragraph [0196]) of Host H (Paragraph [0025]) and ROM Controller Updating Software **20663c1l** (Paragraph [0190]) of Communication Device **200**, which update ROM Controller **20663OS1** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a ROM Controller Update Request, which is received by Host H (S1). Here, the ROM Controller Update Request is a request to send ROM Controller Version Data **H63b1l** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves ROM Controller Version Data **H63b1l** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving ROM Controller Version Data **H63b1l** from Host H (S3), CPU **211** compares ROM Controller Version Data **H63b1l** with ROM Controller Version Data **20663b1l** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that ROM Controller Version Data **20663b1l** of Communication Device **200** is of an old version. CPU **211** sends a New ROM Controller Sending Request, which is received by Host H (S5). Here, the New ROM Controller Sending Request is a request to send ROM Controller **H63OS1** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves ROM Controller **H63OS1** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving ROM Controller **H63OS1** from Host H (S7), CPU **211** stores ROM Controller **H63OS1** as ROM Controller **20663OS1** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of ROM Controller **20663OS1** (Paragraph [0185]) is deleted.

Paragraph [0221]—This Paragraph [0221] illustrates Signal Processor Controller Updating Software **H63c1m** (Paragraph [0196]) of Host H (Paragraph [0025]) and Signal Processor Controller Updating Software **20663c1m** (Paragraph [0190]) of Communication Device **200**, which update Signal Processor Controller **20663OSm** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Signal Processor Controller Version Data **20663b1m** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Signal Processor Controller Version Data **20663b1m** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Signal Processor Controller Version Data **20663b1m** (Paragraph [0189]) with Signal Processor Controller Version Data **H63b1m** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Signal Processor Controller Version Data **20663b1m** of Communication Device **200** is of an old version. Host H retrieves Signal Processor Controller **H63OSm**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Signal Processor Controller **H63OSm** from Host H (S5), CPU **211** stores Signal Processor

67

Controller **H63OSm** as Signal Processor Controller **20663OSm** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Signal Processor Controller **20663OSm** (Paragraph [0185]) is deleted.

Paragraph [0222]—This Paragraph [0222] illustrates another embodiment of Signal Processor Controller Updating Software **H63c1m** (Paragraph [0196]) of Host H (Paragraph [0025]) and Signal Processor Controller Updating Software **20663c1m** (Paragraph [0190]) of Communication Device **200**, which update Signal Processor Controller **20663OSm** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Signal Processor Controller Update Request, which is received by Host H (S1). Here, the Signal Processor Controller Update Request is a request to send Signal Processor Controller Version Data **H63b1m** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Signal Processor Controller Version Data **H63b1m** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Signal Processor Controller Version Data **H63b1m** from Host H (S3), CPU **211** compares Signal Processor Controller Version Data **H63b1m** with Signal Processor Controller Version Data **20663b1m** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Signal Processor Controller Version Data **20663b1m** of Communication Device **200** is of an old version. CPU **211** sends a New Signal Processor Controller Sending Request, which is received by Host H (S5). Here, the New Signal Processor Controller Sending Request is a request to send Signal Processor Controller **H63OSm** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Signal Processor Controller **H63OSm** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Signal Processor Controller **H63OSm** from Host H (S7), CPU **211** stores Signal Processor Controller **H63OSm** as Signal Processor Controller **20663OSm** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Signal Processor Controller **20663OSm** (Paragraph [0185]) is deleted.

Paragraph [0223]—This Paragraph [0223] illustrates Signal Processor Controller Updating Software **H63c1n** (Paragraph [0196]) of Host H (Paragraph [0025]) and Signal Processor Controller Updating Software **20663c1n** (Paragraph [0190]) of Communication Device **200**, which update Signal Processor Controller **20663OSn** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Signal Processor Controller Version Data **20663b1n** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Signal Processor Controller Version Data **20663b1n** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Signal Processor Controller Version Data **20663b1n** (Paragraph [0189]) with Signal Processor Controller Version Data **H63b1n** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Signal Processor Controller Version Data **20663b1n** of Communication Device **200** is of an old version. Host H retrieves Signal Processor Controller **H63OSn**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device

68

200 (S4). Upon receiving Signal Processor Controller **H63OSn** from Host H (S5), CPU **211** stores Signal Processor Controller **H63OSn** as Signal Processor Controller **20663OSn** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Signal Processor Controller **20663OSn** (Paragraph [0185]) is deleted.

Paragraph [0224]—This Paragraph [0224] illustrates another embodiment of Signal Processor Controller Updating Software **H63c1n** (Paragraph [0196]) of Host H (Paragraph [0025]) and Signal Processor Controller Updating Software **20663c1n** (Paragraph [0190]) of Communication Device **200**, which update Signal Processor Controller **20663OSn** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Signal Processor Controller Update Request, which is received by Host H (S1). Here, the Signal Processor Controller Update Request is a request to send Signal Processor Controller Version Data **H63b1n** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Signal Processor Controller Version Data **H63b1n** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Signal Processor Controller Version Data **H63b1n** from Host H (S3), CPU **211** compares Signal Processor Controller Version Data **H63b1n** with Signal Processor Controller Version Data **20663b1n** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Signal Processor Controller Version Data **20663b1n** of Communication Device **200** is of an old version. CPU **211** sends a New Signal Processor Controller Sending Request, which is received by Host H (S5). Here, the New Signal Processor Controller Sending Request is a request to send Signal Processor Controller **H63OSn** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Signal Processor Controller **H63OSn** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Signal Processor Controller **H63OSn** from Host H (S7), CPU **211** stores Signal Processor Controller **H63OSn** as Signal Processor Controller **20663OSn** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Signal Processor Controller **20663OSn** (Paragraph [0185]) is deleted.

Paragraph [0225]—This Paragraph [0225] illustrates Solar Panel Controller Updating Software **H63c1o** (Paragraph [0196]) of Host H (Paragraph [0025]) and Solar Panel Controller Updating Software **20663c1o** (Paragraph [0190]) of Communication Device **200**, which update Solar Panel Controller **20663OSo** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Solar Panel Controller Version Data **20663b1o** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Solar Panel Controller Version Data **20663b1o** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Solar Panel Controller Version Data **20663b1o** (Paragraph [0189]) with Solar Panel Controller Version Data **H63b1o** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Solar Panel Controller Version Data **20663b1o** of Communication Device **200** is of an old version. Host H retrieves Solar Panel Controller **H63OSo**, which is of the latest version, from Operating System Storage Area

H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S4). Upon receiving Solar Panel Controller H63OSo from Host H (S5), CPU 211 stores Solar Panel Controller H63OSo in Operating System 20663OS (Paragraph [0185]) (S6). The old version of Solar Panel Controller 20663OSo (Paragraph [0185]) is deleted.

Paragraph [0226]—This Paragraph [0226] illustrates another embodiment of Solar Panel Controller Updating Software H63c1o (Paragraph [0196]) of Host H (Paragraph [0025]) and Solar Panel Controller Updating Software 20663c1o (Paragraph [0190]) of Communication Device 200, which update Solar Panel Controller 20663OSo stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 sends a Solar Panel Controller Update Request, which is received by Host H (S1). Here, the Solar Panel Controller Update Request is a request to send Solar Panel Controller Version Data H63b1o (Paragraph [0195]) stored in Host H to Communication Device 200. In response to the request, Host H retrieves Solar Panel Controller Version Data H63b1o from OS Version Data Storage Area H63b1 (Paragraph [0195]), and sends the data to Communication Device 200 (S2). Upon receiving Solar Panel Controller Version Data H63b1o from Host H (S3), CPU 211 compares Solar Panel Controller Version Data H63b1o with Solar Panel Controller Version Data 20663b1o stored in OS Version Data Storage Area 20663b1 (Paragraph [0189]) of Communication Device 200 (S4). Assuming that CPU 211 detects in S4 that Solar Panel Controller Version Data 20663b1o of Communication Device 200 is of an old version. CPU 211 sends a New Solar Panel Controller Sending Request, which is received by Host H (S5). Here, the New Solar Panel Controller Sending Request is a request to send Solar Panel Controller H63OSo (Paragraph [0192]) stored in Host H to Communication Device 200. Host H retrieves Solar Panel Controller H63OSo (Paragraph [0192]), which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S6). Upon receiving Solar Panel Controller H63OSo from Host H (S7), CPU 211 stores Solar Panel Controller H63OSo as Solar Panel Controller 20663OSo in Operating System 20663OS (Paragraph [0185]) (S8). The old version of Solar Panel Controller 20663OSo (Paragraph [0185]) is deleted.

Paragraph [0227]—This Paragraph [0227] illustrates Speaker Controller Updating Software H63c1p (Paragraph [0196]) of Host H (Paragraph [0025]) and Speaker Controller Updating Software 20663c1p (Paragraph [0190]) of Communication Device 200, which update Speaker Controller 20663OSp stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves Speaker Controller Version Data 20663b1p from OS Version Data Storage Area 20663b1 (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Speaker Controller Version Data 20663b1p (Paragraph [0189]) from Communication Device 200 (S2), Host H compares Speaker Controller Version Data 20663b1p (Paragraph [0189]) with Speaker Controller Version Data H63b1p stored in OS Version Data Storage Area H63b1 (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Speaker Controller Version Data 20663b1p of Communication Device 200 is of an old version. Host H retrieves Speaker Controller H63OSp, which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S4).

Upon receiving Speaker Controller H63OSp from Host H (S5), CPU 211 stores Speaker Controller H63OSp as Speaker Controller 20663OSp in Operating System 20663OS (Paragraph [0185]) (S6). The old version of Speaker Controller 20663OSp (Paragraph [0185]) is deleted.

Paragraph [0228]—This Paragraph [0228] illustrates another embodiment of Speaker Controller Updating Software H63c1p (Paragraph [0196]) of Host H (Paragraph [0025]) and Speaker Controller Updating Software 20663c1p (Paragraph [0190]) of Communication Device 200, which update Speaker Controller 20663OSp stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 sends a Speaker Controller Update Request, which is received by Host H (S1). Here, the Speaker Controller Update Request is a request to send Speaker Controller Version Data H63b1p (Paragraph [0195]) stored in Host H to Communication Device 200. In response to the request, Host H retrieves Speaker Controller Version Data H63b1p from OS Version Data Storage Area H63b1 (Paragraph [0195]), and sends the data to Communication Device 200 (S2). Upon receiving Speaker Controller Version Data H63b1p from Host H (S3), CPU 211 compares Speaker Controller Version Data H63b1p with Speaker Controller Version Data 20663b1p stored in OS Version Data Storage Area 20663b1 (Paragraph [0189]) of Communication Device 200 (S4). Assuming that CPU 211 detects in S4 that Speaker Controller Version Data 20663b1p of Communication Device 200 is of an old version. CPU 211 sends a New Speaker Controller Sending Request, which is received by Host H (S5). Here, the New Speaker Controller Sending Request is a request to send Speaker Controller H63OSp (Paragraph [0192]) stored in Host H to Communication Device 200. Host H retrieves Speaker Controller H63OSp (Paragraph [0192]), which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S6). Upon receiving Speaker Controller H63OSp from Host H (S7), CPU 211 stores Speaker Controller H63OSp as Speaker Controller 20663OSp in Operating System 20663OS (Paragraph [0185]) (S8). The old version of Speaker Controller 20663OSp (Paragraph [0185]) is deleted.

Paragraph [0229]—This Paragraph [0229] illustrates Vibrator Controller Updating Software H63c1q (Paragraph [0196]) of Host H (Paragraph [0025]) and Vibrator Controller Updating Software 20663c1q (Paragraph [0190]) of Communication Device 200, which update Vibrator Controller 20663OSq stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves Vibrator Controller Version Data 20663b1q from OS Version Data Storage Area 20663b1 (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Vibrator Controller Version Data 20663b1q (Paragraph [0189]) from Communication Device 200 (S2), Host H compares Vibrator Controller Version Data 20663b1q (Paragraph [0189]) with Vibrator Controller Version Data H63b1q stored in OS Version Data Storage Area H63b1 (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Vibrator Controller Version Data 20663b1q of Communication Device 200 is of an old version. Host H retrieves Vibrator Controller H63OSq, which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S4). Upon receiving Vibrator Controller H63OSq from Host H (S5), CPU 211 stores Vibrator Controller H63OSq as Vibrator Controller 20663OSq in Operating System 20663OS (Para-

graph [0185]) (S6). The old version of Vibrator Controller **20663OSq** (Paragraph [0185]) is deleted.

Paragraph [0230]—This Paragraph [0230] illustrates another embodiment of Vibrator Controller Updating Software **H63c1q** (Paragraph [0196]) of Host H (Paragraph [0025]) and Vibrator Controller Updating Software **20663c1q** (Paragraph [0190]) of Communication Device **200**, which update Vibrator Controller **20663OSq** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Vibrator Controller Update Request, which is received by Host H (S1). Here, the Vibrator Controller Update Request is a request to send Vibrator Controller Version Data **H63b1q** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Vibrator Controller Version Data **H63b1q** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Vibrator Controller Version Data **H63b1q** from Host H (S3), CPU **211** compares Vibrator Controller Version Data **H63b1q** with Vibrator Controller Version Data **20663b1q** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Vibrator Controller Version Data **20663b1q** of Communication Device **200** is of an old version. CPU **211** sends a New Vibrator Controller Sending Request, which is received by Host H (S5). Here, the New Vibrator Controller Sending Request is a request to send Vibrator Controller **H63OSq** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Vibrator Controller **H63OSq** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Vibrator Controller **H63OSq** from Host H (S7), CPU **211** stores Vibrator Controller **H63OSq** as Vibrator Controller **20663OSq** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Vibrator Controller **20663OSq** (Paragraph [0185]) is deleted.

Paragraph [0231]—This Paragraph [0231] illustrates Video Processor Controller Updating Software **H63c1r** (Paragraph [0196]) of Host H (Paragraph [0025]) and Video Processor Controller Updating Software **20663c1r** (Paragraph [0190]) of Communication Device **200**, which update Video Processor Controller **20663OSr** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Video Processor Controller Version Data **20663b1r** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Video Processor Controller Version Data **20663b1r** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Video Processor Controller Version Data **20663b1r** (Paragraph [0189]) with Video Processor Controller Version Data **H63b1r** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Video Processor Controller Version Data **20663b1r** of Communication Device **200** is of an old version. Host H retrieves Video Processor Controller **H63OSr**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Video Processor Controller **H63OSr** from Host H (S5), CPU **211** stores Video Processor Controller **H63OSr** as Video Processor Controller **20663OSr** in Operat-

ing System **20663OS** (Paragraph [0185]) (S6). The old version of Video Processor Controller **20663OSr** (Paragraph [0185]) is deleted.

Paragraph [0232]—This Paragraph [0232] illustrates another embodiment of Video Processor Controller Updating Software **H63c1r** (Paragraph [0196]) of Host H (Paragraph [0025]) and Video Processor Controller Updating Software **20663c1r** (Paragraph [0190]) of Communication Device **200**, which update Video Processor Controller **20663OSr** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Video Processor Controller Update Request, which is received by Host H (S1). Here, the Video Processor Controller Update Request is a request to send Video Processor Controller Version Data **H63b1r** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Video Processor Controller Version Data **H63b1r** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Video Processor Controller Version Data **H63b1r** from Host H (S3), CPU **211** compares Video Processor Controller Version Data **H63b1r** with Video Processor Controller Version Data **20663b1r** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Video Processor Controller Version Data **20663b1r** of Communication Device **200** is of an old version. CPU **211** sends a New Video Processor Controller Sending Request, which is received by Host H (S5). Here, the New Video Processor Controller Sending Request is a request to send Video Processor Controller **H63OSr** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Video Processor Controller **H63OSr** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Video Processor Controller **H63OSr** from Host H (S7), CPU **211** stores Video Processor Controller **H63OSr** as Video Processor Controller **20663OSr** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Video Processor Controller **20663OSr** (Paragraph [0185]) is deleted.

Paragraph [0233]—This Paragraph [0233] illustrates Wireless Receiver Controller Updating Software **H63c1s** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Receiver Controller Updating Software **20663c1s** (Paragraph [0190]) of Communication Device **200**, which update Wireless Receiver Controller **20663OSs** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Wireless Receiver Controller Version Data **20663b1s** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Wireless Receiver Controller Version Data **20663b1s** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Wireless Receiver Controller Version Data **20663b1s** (Paragraph [0189]) with Wireless Receiver Controller Version Data **H63b1s** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Wireless Receiver Controller Version Data **20663b1s** of Communication Device **200** is of an old version. Host H retrieves Wireless Receiver Controller **H63OSs**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Wireless Receiver Controller **H63OSs** from Host H (S5), CPU **211** stores Wireless Receiver

Controller H63OSs as Wireless Receiver Controller 20663OSs in Operating System 20663OS (Paragraph [0185]) (S6). The old version of Wireless Receiver Controller 20663OSs (Paragraph [0185]) is deleted.

Paragraph [0234]—This Paragraph [0234] illustrates another embodiment of Wireless Receiver Controller Updating Software H63c1s (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Receiver Controller Updating Software 20663c1s (Paragraph [0190]) of Communication Device 200, which update Wireless Receiver Controller 20663OSs stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 sends a Wireless Receiver Controller Update Request#1, which is received by Host H (S1). Here, the Wireless Receiver Controller Update Request#1 is a request to send Wireless Receiver Controller Version Data H63b1s (Paragraph [0195]) stored in Host H to Communication Device 200. In response to the request, Host H retrieves Wireless Receiver Controller Version Data H63b1s from OS Version Data Storage Area H63b1 (Paragraph [0195]), and sends the data to Communication Device 200 (S2). Upon receiving Wireless Receiver Controller Version Data H63b1s from Host H (S3), CPU 211 compares Wireless Receiver Controller Version Data H63b1s with Wireless Receiver Controller Version Data 20663b1s stored in OS Version Data Storage Area 20663b1 (Paragraph [0189]) of Communication Device 200 (S4). Assuming that CPU211 detects in S4 that Wireless Receiver Controller Version Data 20663b1s of Communication Device 200 is of an old version. CPU 211 sends a New Wireless Receiver Controller Sending Request#1, which is received by Host H (S5). Here, the New Wireless Receiver Controller Sending Request#1 is a request to send Wireless Receiver Controller H63OSs (Paragraph [0192]) stored in Host H to Communication Device 200. Host H retrieves Wireless Receiver Controller H63OSs (Paragraph [0192]), which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S6). Upon receiving Wireless Receiver Controller H63OSs from Host H (S7), CPU 211 stores Wireless Receiver Controller H63OSs as Wireless Receiver Controller 20663OSs in Operating System 20663OS (Paragraph [0185]) (S8). The old version of Wireless Receiver Controller 20663OSs (Paragraph [0185]) is deleted.

Paragraph [0235]—This Paragraph [0235] illustrates Wireless Receiver Controller Updating Software H63c1t (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Receiver Controller Updating Software 20663c1t (Paragraph [0190]) of Communication Device 200, which update Wireless Receiver Controller 20663OSt stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves Wireless Receiver Controller Version Data 20663b1t from OS Version Data Storage Area 20663b1 (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Wireless Receiver Controller Version Data 20663b1t (Paragraph [0189]) from Communication Device 200 (S2), Host H compares Wireless Receiver Controller Version Data 20663b1t (Paragraph [0189]) with Wireless Receiver Controller Version Data H63b1t stored in OS Version Data Storage Area H63b1 (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Wireless Receiver Controller Version Data 20663b1t of Communication Device 200 is of an old version. Host H retrieves Wireless Receiver Controller H63OSt, which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device

200 (S4). Upon receiving Wireless Receiver Controller H63OSt from Host H (S5), CPU 211 stores Wireless Receiver Controller H63OSt as Wireless Receiver Controller 20663OSt in Operating System 20663OS (Paragraph [0185]) (S6). The old version of Wireless Receiver Controller 20663OSt (Paragraph [0185]) is deleted.

Paragraph [0236]—This Paragraph [0236] illustrates another embodiment of Wireless Receiver Controller Updating Software H63c1t (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Receiver Controller Updating Software 20663c1t (Paragraph [0190]) of Communication Device 200, which update Wireless Receiver Controller 20663OSt stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 sends a Wireless Receiver Controller Update Request#2, which is received by Host H (S1). Here, the Wireless Receiver Controller Update Request#2 is a request to send Wireless Receiver Controller Version Data H63b1t (Paragraph [0195]) stored in Host H to Communication Device 200. In response to the request, Host H retrieves Wireless Receiver Controller Version Data H63b1t from OS Version Data Storage Area H63b1 (Paragraph [0195]), and sends the data to Communication Device 200 (S2). Upon receiving Wireless Receiver Controller Version Data H63b1t from Host H (S3), CPU 211 compares Wireless Receiver Controller Version Data H63b1t with Wireless Receiver Controller Version Data 20663b1t stored in OS Version Data Storage Area 20663b1 (Paragraph [0189]) of Communication Device 200 (S4). Assuming that CPU211 detects in S4 that Wireless Receiver Controller Version Data 20663b1t of Communication Device 200 is of an old version. CPU 211 sends a New Wireless Receiver Controller Sending Request#2, which is received by Host H (S5). Here, the New Wireless Receiver Controller Sending Request#2 is a request to send Wireless Receiver Controller H63OSt (Paragraph [0192]) stored in Host H to Communication Device 200. Host H retrieves Wireless Receiver Controller H63OSt (Paragraph [0192]), which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S6). Upon receiving Wireless Receiver Controller H63OSt from Host H (S7), CPU 211 stores Wireless Receiver Controller H63OSt as Wireless Receiver Controller 20663OSt in Operating System 20663OS (Paragraph [0185]) (S8). The old version of Wireless Receiver Controller 20663OSt (Paragraph [0185]) is deleted.

Paragraph [0237]—This Paragraph [0237] illustrates Wireless Receiver Controller Updating Software H63c1u (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Receiver Controller Updating Software 20663c1u (Paragraph [0190]) of Communication Device 200, which update Wireless Receiver Controller 20663OSu stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves Wireless Receiver Controller Version Data 20663b1u from OS Version Data Storage Area 20663b1 (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Wireless Receiver Controller Version Data 20663b1u (Paragraph [0189]) from Communication Device 200 (S2), Host H compares Wireless Receiver Controller Version Data 20663b1u (Paragraph [0189]) with Wireless Receiver Controller Version Data H63b1u stored in OS Version Data Storage Area H63b1 (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Wireless Receiver Controller Version Data 20663b1u of Communication Device 200 is of an old version. Host H retrieves Wireless Receiver Controller H63OSu, which is of the latest version,

from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Wireless Receiver Controller **H63OSu** from Host H (S5), CPU **211** stores Wireless Receiver Controller **H63OSu** as Wireless Receiver Controller **20663OSu** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Wireless Receiver Controller **20663OSu** (Paragraph [0185]) is deleted.

Paragraph [0238]—This Paragraph [0238] illustrates another embodiment of Wireless Receiver Controller Updating Software **H63c1u** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Receiver Controller Updating Software **20663c1u** (Paragraph [0190]) of Communication Device **200**, which update Wireless Receiver Controller **20663OSu** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Wireless Receiver Controller Update Request#3, which is received by Host H (S1). Here, the Wireless Receiver Controller Update Request#3 is a request to send Wireless Receiver Controller Version Data **H63b1u** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Wireless Receiver Controller Version Data **H63b1u** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Wireless Receiver Controller Version Data **H63b1u** from Host H (S3), CPU **211** compares Wireless Receiver Controller Version Data **H63b1u** with Wireless Receiver Controller Version Data **20663b1u** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Wireless Receiver Controller Version Data **20663b1u** of Communication Device **200** is of an old version, CPU **211** sends a New Wireless Receiver Controller Sending Request#3, which is received by Host H (S5). Here, the New Wireless Receiver Controller Sending Request#3 is a request to send Wireless Receiver Controller **H63OSu** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Wireless Receiver Controller **H63OSu** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Wireless Receiver Controller **H63OSu** from Host H (S7), CPU **211** stores Wireless Receiver Controller **H63OSu** as Wireless Receiver Controller **20663OSu** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Wireless Receiver Controller **20663OSu** (Paragraph [0185]) is deleted.

Paragraph [0239]—This Paragraph [0239] illustrates Wireless Transmitter Controller Updating Software **H63c1y** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Transmitter Controller Updating Software **20663c1y** (Paragraph [0190]) of Communication Device **200**, which update Wireless Transmitter Controller **20663OSy** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Wireless Transmitter Controller Version Data **20663b1y** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Wireless Transmitter Controller Version Data **20663b1y** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Wireless Transmitter Controller Version Data **20663b1y** (Paragraph [0189]) with Wireless Transmitter Controller Version Data **H63b1y** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that

Host H detects in S3 that Wireless Transmitter Controller Version Data **20663b1y** of Communication Device **200** is of an old version, Host H retrieves Wireless Transmitter Controller **H63OSy**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Wireless Transmitter Controller **H63OSy** from Host H (S5), CPU **211** stores Wireless Transmitter Controller **H63OSy** as Wireless Transmitter Controller **20663OSy** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Wireless Transmitter Controller **20663OSy** (Paragraph [0185]) is deleted.

Paragraph [0240]—This Paragraph [0240] illustrates another embodiment of Wireless Transmitter Controller Updating Software **H63c1y** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Transmitter Controller Updating Software **20663c1y** (Paragraph [0190]) of Communication Device **200**, which update Wireless Transmitter Controller **20663OSy** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Wireless Transmitter Controller Update Request#1, which is received by Host H (S1). Here, the Wireless Transmitter Controller Update Request#1 is a request to send Wireless Transmitter Controller Version Data **H63b1y** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Wireless Transmitter Controller Version Data **H63b1y** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Wireless Transmitter Controller Version Data **H63b1y** from Host H (S3), CPU **211** compares Wireless Transmitter Controller Version Data **H63b1y** with Wireless Transmitter Controller Version Data **20663b1y** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Wireless Transmitter Controller Version Data **20663b1y** of Communication Device **200** is of an old version, CPU **211** sends a New Wireless Transmitter Controller Sending Request#1, which is received by Host H (S5). Here, the New Wireless Transmitter Controller Sending Request#1 is a request to send Wireless Transmitter Controller **H63OSy** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Wireless Transmitter Controller **H63OSy** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Wireless Transmitter Controller **H63OSy** from Host H (S7), CPU **211** stores Wireless Transmitter Controller **H63OSy** as Wireless Transmitter Controller **20663OSy** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Wireless Transmitter Controller **20663OSy** (Paragraph [0185]) is deleted.

Paragraph [0241]—This Paragraph [0241] illustrates Wireless Transmitter Controller Updating Software **H63c1w** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Transmitter Controller Updating Software **20663c1w** (Paragraph [0190]) of Communication Device **200**, which update Wireless Transmitter Controller **20663OSw** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Wireless Transmitter Controller Version Data **20663b1w** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Wireless Transmitter Controller Version Data **20663b1w** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares

Wireless Transmitter Controller Version Data **20663b1w** (Paragraph [0189]) with Wireless Transmitter Controller Version Data **H63b1w** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Wireless Transmitter Controller Version Data **20663b1w** of Communication Device **200** is of an old version. Host H retrieves Wireless Transmitter Controller **H63OSw**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Wireless Transmitter Controller **H63OSw** from Host H (S5), CPU **211** stores Wireless Transmitter Controller **H63OSw** as Wireless Transmitter Controller **20663OSw** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Wireless Transmitter Controller **20663OSw** (Paragraph [0185]) is deleted.

Paragraph [0242]—This Paragraph [0242] illustrates another embodiment of Wireless Transmitter Controller Updating Software **H63c1w** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Transmitter Controller Updating Software **20663c1w** (Paragraph [0190]) of Communication Device **200**, which update Wireless Transmitter Controller **20663OSw** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Wireless Transmitter Controller Update Request#2, which is received by Host H (S1). Here, the Wireless Transmitter Controller Update Request#2 is a request to send Wireless Transmitter Controller Version Data **H63b1w** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Wireless Transmitter Controller Version Data **H63b1w** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Wireless Transmitter Controller Version Data **H63b1w** from Host H (S3), CPU **211** compares Wireless Transmitter Controller Version Data **H63b1w** with Wireless Transmitter Controller Version Data **20663b1w** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Wireless Transmitter Controller Version Data **20663b1w** of Communication Device **200** is of an old version. CPU **211** sends a New Wireless Transmitter Controller Sending Request#2, which is received by Host H (S5). Here, the New Wireless Transmitter Controller Sending Request#2 is a request to send Wireless Transmitter Controller **H63OSw** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Wireless Transmitter Controller **H63OSw** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Wireless Transmitter Controller **H63OSw** from Host H (S7), CPU **211** stores Wireless Transmitter Controller **H63OSw** as Wireless Transmitter Controller **20663OSw** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Wireless Transmitter Controller **20663OSw** (Paragraph [0185]) is deleted.

Paragraph [0243]—This Paragraph [0243] illustrates Wireless Transmitter Controller Updating Software **H63c1x** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Transmitter Controller Updating Software **20663c1x** (Paragraph [0190]) of Communication Device **200**, which update Wireless Transmitter Controller **20663OSx** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Wireless Transmitter Controller Version Data **20663b1x** from OS Ver-

sion Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Wireless Transmitter Controller Version Data **20663b1x** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Wireless Transmitter Controller Version Data **20663b1x** (Paragraph [0189]) with Wireless Transmitter Controller Version Data **H63b1x** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Wireless Transmitter Controller Version Data **20663b1x** of Communication Device **200** is of an old version. Host H retrieves Wireless Transmitter Controller **H63OSx**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Wireless Transmitter Controller **H63OSx** from Host H (S5), CPU **211** stores Wireless Transmitter Controller **H63OSx** as Wireless Transmitter Controller **20663OSx** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Wireless Transmitter Controller **20663OSx** (Paragraph [0185]) is deleted.

Paragraph [0244]—This Paragraph [0244] illustrates another embodiment of Wireless Transmitter Controller Updating Software **H63c1x** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Transmitter Controller Updating Software **20663c1x** (Paragraph [0190]) of Communication Device **200**, which update Wireless Transmitter Controller **20663OSx** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Wireless Transmitter Controller Update Request#3, which is received by Host H (S1). Here, the Wireless Transmitter Controller Update Request#3 is a request to send Wireless Transmitter Controller Version Data **H63b1x** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Wireless Transmitter Controller Version Data **H63b1x** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Wireless Transmitter Controller Version Data **H63b1x** from Host H (S3), CPU **211** compares Wireless Transmitter Controller Version Data **H63b1x** with Wireless Transmitter Controller Version Data **20663b1x** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Wireless Transmitter Controller Version Data **20663b1x** of Communication Device **200** is of an old version. CPU **211** sends a New Wireless Transmitter Controller Sending Request#3, which is received by Host H (S5). Here, the New Wireless Transmitter Controller Sending Request#3 is a request to send Wireless Transmitter Controller **H63OSx** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Wireless Transmitter Controller **H63OSx** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Wireless Transmitter Controller **H63OSx** from Host H (S7), CPU **211** stores Wireless Transmitter Controller **H63OSx** as Wireless Transmitter Controller **20663OSx** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Wireless Transmitter Controller **20663OSx** (Paragraph [0185]) is deleted.

Paragraph [0245]—As another embodiment, each and all data and software programs described in this specification stored in Communication Device **200** may be updated in the manner described hereinbefore.

Paragraph [0246]—For the avoidance of doubt, the present function may be utilized to repair the operating system of

Communication Device **200**, i.e., Operating System **20663OS** (Paragraph [0185]) in the form of downloading updates.

Paragraph [0247]—<<Automobile Controlling Function>>

Paragraph [0248]—Paragraph [0249] through Paragraph [0290] illustrate the automobile controlling function which enables Communication Device **200** to remotely control an automobile in a wireless fashion via Antenna **218** (FIG. 1).

Paragraph [0249]—This Paragraph [0249] illustrates the storage area included in Automobile **835**, i.e., an automobile or a car. In the present embodiment, Automobile **835** includes Automobile Controlling Information Storage Area **83565a** of which the data and the software programs stored therein are described in Paragraph [0251].

Paragraph [0250]—The data and/or the software programs stored in Automobile Controlling Information Storage Area **83565a** (Paragraph [0249]) may be downloaded from Host H (Paragraph [0025]).

Paragraph [0251]—This Paragraph [0251] illustrates the storage areas included in Automobile Controlling Information Storage Area **83565a** (Paragraph [0249]). In the present embodiment, Automobile Controlling Information Storage Area **83565a** includes Automobile Controlling Data Storage Area **83565b** and Automobile Controlling Software Storage Area **83565c**. Automobile Controlling Data Storage Area **83565b** stores the data necessary to implement the present function on the side of Automobile **835** (Paragraph [0249]), such as the ones described in Paragraph [0252] through Paragraph [0258]. Automobile Controlling Software Storage Area **83565c** stores the software programs necessary to implement the present function on the side of Automobile **835**, such as the ones described in Paragraph [0259].

Paragraph [0252]—This Paragraph [0252] illustrates the storage areas included in Automobile Controlling Data Storage Area **83565b** (Paragraph [0251]). In the present embodiment, Automobile Controlling Data Storage Area **83565b** includes User Access Data Storage Area **83565b1**, Window Data Storage Area **83565b2**, Door Data Storage Area **83565b3**, Radio Channel Data Storage Area **83565b4**, TV Channel Data Storage Area **83565b5**, Blinker Data Storage Area **83565b6**, and Work Area **83565b7**. User Access Data Storage Area **83565b1** stores the data described in Paragraph [0253]. Window Data Storage Area **83565b2** stores the data described in Paragraph [0254]. Door Data Storage Area **83565b3** stores the data described in Paragraph [0255]. Radio Channel Data Storage Area **83565b4** stores the data described in Paragraph [0256]. TV Channel Data Storage Area **83565b5** stores the data described in Paragraph [0257]. Blinker Data Storage Area **83565b6** stores the data described in Paragraph [0258]. Work Area **83565b7** is utilized as a work area to perform calculation and temporarily store data. The data stored in Automobile Controlling Data Storage Area **83565b** excluding the ones stored in User Access Data Storage Area **83565b1** and Work Area **83565b7** are primarily utilized for reinstallation, i.e., to reinstall the data to Communication Device **200** as described hereinafter in case the data stored in Communication Device **200** are corrupted or lost.

Paragraph [0253]—This Paragraph [0253] illustrates the data stored in User Access Data Storage Area **83565b1** (Paragraph [0252]). In the present embodiment, User Access Data Storage Area **83565b1** comprises two columns, i.e., 'User ID' and 'Password Data'. Column 'User ID' stores the user IDs, and each user ID is an identification of the user of Communication Device **200** authorized to implement the present function. Column 'Password Data' stores the password data, and each password data represents the password set by the

user of the corresponding user ID. The password data is composed of alphanumeric data. In the present embodiment, User Access Data Storage Area **83565b1** stores the following data: the user ID 'User#1' and the corresponding password data 'Password Data#1'; the user ID 'User#2' and the corresponding password data 'Password Data#2'; the user ID 'User#3' and the corresponding password data 'Password Data#3'; and the user ID 'User#4' and the corresponding password data 'Password Data#4'. According to the present example, the users represented by User#1 through #4 are authorized to implement the present function.

Paragraph [0254]—This Paragraph [0254] illustrates the data stored in Window Data Storage Area **83565b2** (Paragraph [0252]). In the present embodiment, Window Data Storage Area **83565b2** comprises two columns, i.e., 'Window ID' and 'Window Data'. Column 'Window ID' stores the window IDs, and each window ID is an identification of the window (not shown) of Automobile **835** (Paragraph [0249]). Column 'Window Data' stores the window data, and each window data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the position of the window (not shown) of the corresponding window ID. In the present embodiment, Window Data Storage Area **83565b2** stores the following data: the window ID 'Window#1' and the corresponding window data 'Window Data#1'; the window ID 'Window#2' and the corresponding window data 'Window Data#2'; the window ID 'Window#3' and the corresponding window data 'Window Data#3'; and the window ID 'Window#4' and the corresponding window data 'Window Data#4'. Four windows of Automobile **835** which are represented by the window IDs, 'Window#1' through 'Window#4', are remotely controllable by implementing the present function.

Paragraph [0255]—This Paragraph [0255] illustrates the data stored in Door Data Storage Area **83565b3** (Paragraph [0252]). In the present embodiment, Door Data Storage Area **83565b3** comprises two columns, i.e., 'Door ID' and 'Door Data'. Column 'Door ID' stores the door IDs, and each door ID is an identification of the door (not shown) of Automobile **835** (Paragraph [0249]). Column 'Door Data' stores the door data, and each door data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the position of the door (not shown) of the corresponding door ID. In the present embodiment, Door Data Storage Area **83565b3** stores the following data: the door ID 'Door#1' and the corresponding door data 'Door Data#1'; the door ID 'Door#2' and the corresponding door data 'Door Data#2'; the door ID 'Door#3' and the corresponding door data 'Door Data#3'; and the door ID 'Door#4' and the corresponding door data 'Door Data#4'. Four doors of Automobile **835** which are represented by the door IDs, 'Door#1' through 'Door#4', are remotely controllable by implementing the present function.

Paragraph [0256]—This Paragraph [0256] illustrates the data stored in Radio Channel Data Storage Area **83565b4** (Paragraph [0252]). In the present embodiment, Radio Channel Data Storage Area **83565b4** comprises two columns, i.e., 'Radio Channel ID' and 'Radio Channel Data'. Column 'Radio Channel ID' stores the radio channel IDs, and each radio channel ID is an identification of the radio channel (not shown) playable by the radio (not shown) installed in Automobile **835** (Paragraph [0249]). Column 'Radio Channel Data' stores the radio channel data, and each radio channel data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the radio channel (not shown) of the corresponding radio channel ID. In the present embodiment, Radio Channel Data Storage Area **83565b4** stores the following data: the radio channel ID 'Radio Channel#1' and the

81

corresponding radio channel data 'Radio Channel Data#1'; the radio channel ID 'Radio Channel#2' and the corresponding radio channel data 'Radio Channel Data#2'; the radio channel ID 'Radio Channel#3' and the corresponding radio channel data 'Radio Channel Data#3'; and the radio channel ID 'Radio Channel#4' and the corresponding radio channel data 'Radio Channel Data#4'. Four radio channels which are represented by the radio channel IDs, 'Radio Channel#1' through 'Radio Channel#4', are remotely controllable by implementing the present invention.

Paragraph [0257]—This Paragraph [0257] illustrates the data stored in TV Channel Data Storage Area **83565b5** (Paragraph [0252]). In the present embodiment, TV Channel Data Storage Area **83565b5** comprises two columns, i.e., 'TV Channel ID' and 'TV Channel Data'. Column 'TV Channel ID' stores the TV channel IDs, and each TV channel ID is an identification of the TV channel (not shown) playable by the TV (not shown) installed in Automobile **835** (Paragraph [0249]). Column 'TV Channel Data' stores the TV channel data, and each TV channel data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the TV channel (not shown) of the corresponding TV channel ID. In the present embodiment, TV Channel Data Storage Area **83565b5** stores the following data: the TV channel ID 'TV Channel#1' and the corresponding TV channel data 'TV Channel Data#1'; the TV channel ID 'TV Channel#2' and the corresponding TV channel data 'TV Channel Data#2'; the TV channel ID 'TV Channel#3' and the corresponding TV channel data 'TV Channel Data#3'; and the TV channel ID 'TV Channel#4' and the corresponding TV channel data 'TV Channel Data#4'. Four TV channels which are represented by the TV channel IDs, 'TV Channel#1' through 'TV Channel#4', are remotely controllable by implementing the present invention.

Paragraph [0258]—This Paragraph [0258] illustrates the data stored in Blinker Data Storage Area **83565b6** (Paragraph [0252]). In the present embodiment, Blinker Data Storage Area **83565b6** comprises two columns, i.e., 'Blinker ID' and 'Blinker Data'. Column 'Blinker ID' stores the blinker IDs, and each blinker ID is an identification of the blinker (not shown) of Automobile **835** (Paragraph [0249]). Column 'Blinker Data' stores the blinker data, and each blinker data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the blinker (not shown) of the corresponding blinker ID. In the present embodiment, Blinker Data Storage Area **83565b6** stores the following data: the blinker ID 'Blinker#1' and the corresponding blinker data 'Blinker Data#1'; and the blinker ID 'Blinker#2' and the corresponding blinker data 'Blinker Data#2'. Two blinkers which are represented by the blinker IDs, 'Blinker#1' and 'Blinker#2', are remotely controllable by implementing the present invention. Here, the blinker (not shown) represented by 'Blinker#1' is the right blinker and the blinker (not shown) represented by 'Blinker#2' is the left blinker.

Paragraph [0259]—This Paragraph [0259] illustrates the storage areas included in Automobile Controlling Software Storage Area **83565c** (Paragraph [0251]). In the present embodiment, Automobile Controlling Software Storage Area **83565c** includes Automobile Controller Storage Area **83565c1** and Remote Controlling Software Storage Area **83565c2**. Automobile Controller Storage Area **83565c1** stores the controllers described in Paragraph [0260]. Remote Controlling Software Storage Area **83565c2** stores the software programs described in Paragraph [0261].

Paragraph [0260]—This Paragraph [0260] illustrates the controllers stored in Automobile Controller Storage Area **83565c1** (Paragraph [0259]). In the present embodiment,

82

Automobile Controller Storage Area **83565c1** stores Engine Controller **83565c1a**, Direction Controller **83565c1b**, Speed Controller **83565c1c**, Window Controller **83565c1d**, Door Controller **83565c1e**, Radio Controller **83565c1f**, TV Controller **83565c1g**, Radio Channel Selector **83565c1h**, TV Channel Selector **83565c1i**, Blinker Controller **83565c1j**, Emergency Lamp Controller **83565c1k**, Cruise Control Controller **83565c1l**, and Speaker Volume Controller **83565c1m**. Engine Controller **83565c1a** is the controller which controls the engine (not shown) of Automobile **835** (Paragraph [0249]). Direction Controller **83565c1b** is the controller which controls the steering wheel (not shown) of Automobile **835**. Speed Controller **83565c1c** is the controller which controls the accelerator (not shown) of Automobile **835**. Window Controller **83565c1d** is the controller which controls the windows (not shown) of Automobile **835**. Door Controller **83565c1e** is the controller which controls the doors (not shown) of Automobile **835**. Radio Controller **83565c1f** is the controller which controls the radio (not shown) of Automobile **835**. TV Controller **83565c1g** is the controller which controls the TV (not shown) of Automobile **835**. Radio Channel Selector **83565c1h** is the controller which controls the radio channels (not shown) of the radio (not shown) installed in Automobile **835**. TV Channel Selector **83565c1i** is the controller which controls the radio channels (not shown) of the radio (not shown) installed in Automobile **835**. Blinker Controller **83565c1j** is the controller which controls the blinkers (not shown) of Automobile **835**. Emergency Lamp Controller **83565c1k** is the controller which controls the emergency lamp (not shown) of Automobile **835**. Cruise Control Controller **83565c1l** is the controller which controls the cruise control (not shown) of Automobile **835**. Speaker Volume Controller **83565c1m** is the controller which controls the speaker (not shown) of Automobile **835**. As another embodiment, the foregoing controllers may be in the form of hardware instead of software.

Paragraph [0261]—This Paragraph [0261] illustrates the software programs stored in Remote Controlling Software Storage Area **83565c2** (Paragraph [0259]). In the present embodiment, Remote Controlling Software Storage Area **83565c2** stores Engine Controlling Software **83565c2a**, Direction Controlling Software **83565c2b**, Speed Controlling Software **83565c2c**, Window Controlling Software **83565c2d**, Door Controlling Software **83565c2e**, Radio Controlling Software **83565c2f**, TV Controlling Software **83565c2g**, Radio Channel Selecting Software **83565c2h**, TV Channel Selecting Software **83565c2i**, Blinker Controlling Software **83565c2j**, Emergency Lamp Controlling Software **83565c2k**, Cruise Control Controlling Software **83565c2l**, Speaker Volume Controlling Software **83565c2m**, Controller Reinstalling Software **83565c2n**, Data Reinstalling Software **83565c2o**, and User Access Authenticating Software **83565c2p**. Engine Controlling Software **83565c2a** is the software program described in Paragraph [0276]. Direction Controlling Software **83565c2b** is the software program described in Paragraph [0277]. Speed Controlling Software **83565c2c** is the software program described in Paragraph [0278]. Window Controlling Software **83565c2d** is the software program described in Paragraph [0279]. Door Controlling Software **83565c2e** is the software program described in Paragraph [0280]. Radio Controlling Software **83565c2f** is the software program described in Paragraph [0281]. TV Controlling Software **83565c2g** is the software program described in Paragraph [0282]. Radio Channel Selecting Software **83565c2h** is the software program described in Paragraph [0283]. TV Channel Selecting Software **83565c2i** is the software program described in Paragraph [0284].

Blinker Controlling Software **83565c2j** is the software program described in Paragraph [0285]. Emergency Lamp Controlling Software **83565c2k** is the software program described in Paragraph [0286]. Cruise Control Controlling Software **83565c2l** is the software program described in Paragraph [0287]. Speaker Volume Controlling Software **83565c2m** is the software program described in Paragraph [0288]. Controller Reinstalling Software **83565c2n** is the software program described in Paragraph [0289]. Data Reinstalling Software **83565c2o** is the software program described in Paragraph [0290]. User Access Authenticating Software **83565c2p** is the software program described in Paragraph [0275]. The controllers stored in Automobile Controller Storage Area **83565c1** primarily functions as directly controlling Automobile **835** in the manner described in Paragraph [0260], and the software programs stored in Remote Controlling Software Storage Area **83565c2** controls the controllers stored in Automobile Controller Storage Area **83565c1**, by cooperating with the software programs stored in Remote Controlling Software Storage Area **20665c2** (Paragraph [0274]) of Communication Device **200**, in a wireless fashion via Antenna **218** (FIG. 1).

Paragraph [0262]—This Paragraph [0262] illustrates the storage area included in RAM **206** (FIG. 1) of Communication Device **200**. In the present embodiment, RAM **206** includes Automobile Controlling Information Storage Area **20665a** of which the data and the software programs stored therein are described in Paragraph [0264].

Paragraph [0263]—The data and/or the software programs stored in Automobile Controlling Information Storage Area **20665a** (Paragraph [0262]) may be downloaded from Host H (Paragraph [0025]).

Paragraph [0264]—This Paragraph [0264] illustrates the storage areas included in Automobile Controlling Information Storage Area **20665a** (Paragraph [0262]). In the present embodiment, Automobile Controlling Information Storage Area **20665a** includes Automobile Controlling Data Storage Area **20665b** and Automobile Controlling Software Storage Area **20665c**. Automobile Controlling Data Storage Area **20665b** stores the data necessary to implement the present function on the side of Communication Device **200**, such as the ones described in Paragraph [0265] through Paragraph [0271]. Automobile Controlling Software Storage Area **20665c** stores the software programs necessary to implement the present function on the side of Communication Device **200**, such as the ones described in Paragraph [0272].

Paragraph [0265]—This Paragraph [0265] illustrates the storage areas included in Automobile Controlling Data Storage Area **20665b** (Paragraph [0264]). In the present embodiment, Automobile Controlling Data Storage Area **20665b** includes User Access Data Storage Area **20665b1**, Window Data Storage Area **20665b2**, Door Data Storage Area **20665b3**, Radio Channel Data Storage Area **20665b4**, TV Channel Data Storage Area **20665b5**, Blinker Data Storage Area **20665b6**, and Work Area **20665b7**. User Access Data Storage Area **20665b1** stores the data described in Paragraph [0266]. Window Data Storage Area **20665b2** stores the data described in Paragraph [0267]. Door Data Storage Area **20665b3** stores the data described in Paragraph [0268]. Radio Channel Data Storage Area **20665b4** stores the data described in Paragraph [0269]. TV Channel Data Storage Area **20665b5** stores the data described in Paragraph [0270]. Blinker Data Storage Area **20665b6** stores the data described in Paragraph [0271]. Work Area **20665b7** is utilized as a work area to perform calculation and temporarily store data.

Paragraph [0266]—This Paragraph [0266] illustrates the data stored in User Access Data Storage Area **20665b1** (Para-

graph [0265]). In the present embodiment, User Access Data Storage Area **20665b1** comprises two columns, i.e., ‘User ID’ and ‘Password Data’. Column ‘User ID’ stores the user ID which is an identification of the user of Communication Device **200**. Column ‘Password Data’ stores the password data which represents the password set by the user of Communication Device **200**. The password data is composed of alphanumeric data. In the present embodiment, User Access Data Storage Area **20665b1** stores the following data: the user ID ‘User#1’ and the corresponding password data ‘Password Data#1’.

Paragraph [0267]—This Paragraph [0267] illustrates the data stored in Window Data Storage Area **20665b2** (Paragraph [0265]). In the present embodiment, Window Data Storage Area **20665b2** comprises two columns, i.e., ‘Window ID’ and ‘Window Data’. Column ‘Window ID’ stores the window IDs, and each window ID is an identification of the window (not shown) of Automobile **835** (Paragraph [0249]). Column ‘Window Data’ stores the window data, and each window data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the position of the window (not shown) of the corresponding window ID. In the present embodiment, Window Data Storage Area **20665b2** stores the following data: the window ID ‘Window#1’ and the corresponding window data ‘Window Data#1’; the window ID ‘Window#2’ and the corresponding window data ‘Window Data#2’; the window ID ‘Window#3’ and the corresponding window data ‘Window Data#3’; and the window ID ‘Window#4’ and the corresponding window data ‘Window Data#4’. Four windows of Automobile **835** which are represented by the window IDs, ‘Window#1’ through ‘Window#4’, are remotely controllable by implementing the present function.

Paragraph [0268]—This Paragraph [0268] illustrates the data stored in Door Data Storage Area **20665b3** (Paragraph [0265]). In the present embodiment, Door Data Storage Area **20665b3** comprises two columns, i.e., ‘Door ID’ and ‘Door Data’. Column ‘Door Data’ stores the door data, and each door data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the position of the door (not shown) of the corresponding door ID. In the present embodiment, Door Data Storage Area **20665b3** stores the following data: the door ID ‘Door#1’ and the corresponding door data ‘Door Data#1’; the door ID ‘Door#2’ and the corresponding door data ‘Door Data#2’; the door ID ‘Door#3’ and the corresponding door data ‘Door Data#3’; and the door ID ‘Door#4’ and the corresponding door data ‘Door Data#4’. Four doors of Automobile **835** (Paragraph [0249]) which are represented by the door IDs, ‘Door#1’ through ‘Door#4’, are remotely controllable by implementing the present function.

Paragraph [0269]—This Paragraph [0269] illustrates the data stored in Radio Channel Data Storage Area **20665b4** (Paragraph [0265]). In the present embodiment, Radio Channel Data Storage Area **20665b4** comprises two columns, i.e., ‘Radio Channel ID’ and ‘Radio Channel Data’. Column ‘Radio Channel ID’ stores the radio channel IDs, and each radio channel ID is an identification of the radio channel (not shown) playable by the radio (not shown) installed in Automobile **835** (Paragraph [0249]). Column ‘Radio Channel Data’ stores the radio channel data, and each radio channel data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the radio channel (not shown) of the corresponding radio channel ID. In the present embodiment, Radio Channel Data Storage Area **20665b4** stores the following data: the radio channel ID ‘Radio Channel#1’ and the corresponding radio channel data ‘Radio Channel Data#1’; the radio channel ID ‘Radio Channel#2’ and the correspond-

85

ing radio channel data 'Radio Channel Data#2'; the radio channel ID 'Radio Channel#3' and the corresponding radio channel data 'Radio Channel Data#3'; and the radio channel ID 'Radio Channel#4' and the corresponding radio channel data 'Radio Channel Data#4'. Four radio channels which are represented by the radio channel IDs, 'Radio Channel#1' through 'Radio Channel#4', are remotely controllable by implementing the present invention.

Paragraph [0270]—This Paragraph [0270] illustrates the data stored in TV Channel Data Storage Area **20665b5** (Paragraph [0265]). In the present embodiment, TV Channel Data Storage Area **20665b5** comprises two columns, i.e., 'TV Channel ID' and 'TV Channel Data'. Column 'TV Channel ID' stores the TV channel IDs, and each TV channel ID is an identification of the TV channel (not shown) playable by the TV (not shown) installed in Automobile **835** (Paragraph [0249]). Column 'TV Channel Data' stores the TV channel data, and each TV channel data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the TV channel (not shown) of the corresponding TV channel ID. In the present embodiment, TV Channel Data Storage Area **20665b5** stores the following data: the TV channel ID 'TV Channel#1' and the corresponding TV channel data 'TV Channel Data#1'; the TV channel ID 'TV Channel#2' and the corresponding TV channel data 'TV Channel Data#2'; the TV channel ID 'TV Channel#3' and the corresponding TV channel data 'TV Channel Data#3'; and the TV channel ID 'TV Channel#4' and the corresponding TV channel data 'TV Channel Data#4'. Four TV channels which are represented by the TV channel IDs, 'TV Channel#1' through 'TV Channel#4', are remotely controllable by implementing the present invention.

Paragraph [0271]—This Paragraph [0271] illustrates the data stored in Blinker Data Storage Area **20665b6** (Paragraph [0265]). In the present embodiment, Blinker Data Storage Area **20665b6** comprises two columns, i.e., 'Blinker ID' and 'Blinker Data'. Column 'Blinker ID' stores the blinker IDs, and each blinker ID is an identification of the blinker (not shown) of Automobile **835** (Paragraph [0249]). Column 'Blinker Data' stores the blinker data, and each blinker data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the blinker (not shown) of the corresponding blinker ID. In the present embodiment, Blinker Data Storage Area **20665b6** stores the following data: the blinker ID 'Blinker#1' and the corresponding blinker data 'Blinker Data#1'; and the blinker ID 'Blinker#2' and the corresponding blinker data 'Blinker Data#2'. Two blinkers which are represented by the blinker IDs, 'Blinker#1' and 'Blinker#2', are remotely controllable by implementing the present invention. Here, the blinker (not shown) represented by 'Blinker#1' is the right blinker and the blinker (not shown) represented by 'Blinker#2' is the left blinker.

Paragraph [0272]—This Paragraph [0272] illustrates the storage areas included in Automobile Controlling Software Storage Area **20665c** (Paragraph [0264]). In the present embodiment, Automobile Controlling Software Storage Area **20665c** includes Automobile Controller Storage Area **20665c1** and Remote Controlling Software Storage Area **20665c2**. Automobile Controller Storage Area **20665c1** stores the controllers described in Paragraph [0273]. Remote Controlling Software Storage Area **20665c2** stores the software programs described in Paragraph [0274].

Paragraph [0273]—This Paragraph [0273] illustrates the controllers stored in Automobile Controller Storage Area **20665c1** (Paragraph [0272]). In the present embodiment, Automobile Controller Storage Area **20665c1** stores Engine Controller **20665c1a**, Direction Controller **20665c1b**, Speed

86

Controller **20665c1c**, Window Controller **20665c1d**, Door Controller **20665c1e**, Radio Controller **20665c1f**, TV Controller **20665c1g**, Radio Channel Selector **20665c1h**, TV Channel Selector **20665c1i**, Blinker Controller **20665c1j**, Emergency Lamp Controller **20665c1k**, Cruise Control Controller **20665c1l**, and Speaker Volume Controller **20665c1m**. Engine Controller **20665c1a** is the controller which controls the engine (not shown) of Automobile **206**. Direction Controller **20665c1b** is the controller which controls the steering wheel (not shown) of Automobile **206**. Speed Controller **20665c1c** is the controller which controls the accelerator (not shown) of Automobile **206**. Window Controller **20665c1d** is the controller which controls the windows (not shown) of Automobile **206**. Door Controller **20665c1e** is the controller which controls the doors (not shown) of Automobile **206**. Radio Controller **20665c1f** is the controller which controls the radio (not shown) of Automobile **206**. TV Controller **20665c1g** is the controller which controls the TV (not shown) of Automobile **206**. Radio Channel Selector **20665c1h** is the controller which controls the radio channels (not shown) of the radio (not shown) installed in Automobile **206**. TV Channel Selector **20665c1i** is the controller which controls the radio channels (not shown) of the radio (not shown) installed in Automobile **206**. Blinker Controller **20665c1j** is the controller which controls the blinkers (not shown) of Automobile **206**. Emergency Lamp Controller **20665c1k** is the controller which controls the emergency lamp (not shown) of Automobile **206**. Cruise Control Controller **20665c1l** is the controller which controls the cruise control (not shown) of Automobile **206**. Speaker Volume Controller **20665c1m** is the controller which controls the speaker (not shown) of Automobile **206**. As another embodiment, the foregoing controllers may be in the form of hardware instead of software. The data stored in Automobile Controller Storage Area **20665c1** are primarily utilized for reinstallation, i.e., to reinstall the data to Automobile **835** (Paragraph [0249]) as described hereinafter in case the data stored in Automobile **835** are corrupted or lost.

Paragraph [0274]—This Paragraph [0274] illustrates the software programs stored in Remote Controlling Software Storage Area **20665c2** (Paragraph [0264]). In the present embodiment, Remote Controlling Software Storage Area **20665c2** stores Engine Controlling Software **20665c2a**, Direction Controlling Software **20665c2b**, Speed Controlling Software **20665c2c**, Window Controlling Software **20665c2d**, Door Controlling Software **20665c2e**, Radio Controlling Software **20665c2f**, TV Controlling Software **20665c2g**, Radio Channel Selecting Software **20665c2h**, TV Channel Selecting Software **20665c2i**, Blinker Controlling Software **20665c2j**, Emergency Lamp Controlling Software **20665c2k**, Cruise Control Controlling Software **20665c2l**, Speaker Volume Controlling Software **20665c2m**, Controller Reinstalling Software **20665c2n**, Data Reinstalling Software **20665c2o**, and User Access Authenticating Software **20665c2p**. Engine Controlling Software **20665c2a** is the software program described in Paragraph [0276]. Direction Controlling Software **20665c2b** is the software program described in Paragraph [0277]. Speed Controlling Software **20665c2c** is the software program described in Paragraph [0278]. Window Controlling Software **20665c2d** is the software program described in Paragraph [0279]. Door Controlling Software **20665c2e** is the software program described in Paragraph [0280]. Radio Controlling Software **20665c2f** is the software program described in Paragraph [0281]. TV Controlling Software **20665c2g** is the software program described in Paragraph [0282]. Radio Channel Selecting Software **20665c2h** is the software program described in Paragraph [0283]. TV Channel Selecting Software **20665c2i**

is the software program described in Paragraph [0284]. Blinker Controlling Software **20665c2j** is the software program described in Paragraph [0285]. Emergency Lamp Controlling Software **20665c2k** is the software program described in Paragraph [0286]. Cruise Control Controlling Software **20665c2l** is the software program described in Paragraph [0287]. Speaker Volume Controlling Software **20665c2m** is the software program described in Paragraph [0288]. Controller Reinstalling Software **20665c2n** is the software program described in Paragraph [0289]. Data Reinstalling Software **20665c2o** is the software program described in Paragraph [0290]. User Access Authenticating Software **20665c2p** is the software program described in Paragraph [0275]. The controllers stored in Automobile Controller Storage Area **83565c1** primarily functions as directly controlling Automobile **835** in the manner described in Paragraph [0260], and the software programs stored in Remote Controlling Software Storage Area **83565c2** (Paragraph [0274]) controls the controllers stored in Automobile Controller Storage Area **83565c1** (Paragraph [0260]), by cooperating with the software programs stored in Remote Controlling Software Storage Area **83565c2** (Paragraph [0261]) of Automobile **835**, in a wireless fashion via Antenna **218** (FIG. 1).

Paragraph [0275]—This Paragraph [0275] illustrates User Access Authenticating Software **83565c2p** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and User Access Authenticating Software **20665c2p** (Paragraph [0274]) of Communication Device **200**, which determine whether Communication Device **200** in question is authorized to remotely control Automobile **835** by implementing the present function. In the present embodiment, the user of Communication Device **200** inputs the user ID and the password data by utilizing Input Device **210** (FIG. 1) or via voice recognition system. The user ID and the password data are temporarily stored in User Access Data Storage Area **20665b1** (Paragraph [0266]) from which the two data are sent to Automobile **835** (S1). Assume that the user input ‘User#1’ as the user ID and ‘Password Data#1’ as the password data. Upon receiving the user ID and the password data (in the present example, User#1 and Password Data#1) from Communication Device **200**, Automobile **835** stores the two data in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** then initiates the authentication process to determine whether Communication Device **200** in question is authorized to remotely control Automobile **835** by referring to the data stored in User Access Data Storage Area **83565b1** (Paragraph [0253]) (S3). Assume that the authenticity of Communication Device **200** in question is cleared. Automobile **835** permits Communication Device **200** in question to remotely control Automobile **835** in the manner described hereinafter (S4).

Paragraph [0276]—This Paragraph [0276] illustrates Engine Controlling Software **83565c2a** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Engine Controlling Software **20665c2a** (Paragraph [0274]) of Communication Device **200**, which ignite or turn off the engine (not shown) of Automobile **835**. In the present embodiment, the user of Communication Device **200** inputs an engine controlling signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system. The signal is sent to Automobile **835** (S1). Here, the engine controlling signal indicates either to ignite the engine or turn off the engine. Upon receiving the engine controlling signal from Communication Device **200**, Automobile **835** stores the signal in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** controls the engine

(not shown) via Engine Controller **83565c1a** (Paragraph [0260]) in accordance with the engine controlling signal (S3).

Paragraph [0277]—This Paragraph [0277] illustrates Direction Controlling Software **83565c2b** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Direction Controlling Software **20665c2b** (Paragraph [0274]) of Communication Device **200**, which control the direction of Automobile **835**. In the present embodiment, the user of Communication Device **200** inputs a direction controlling signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system. The signal is sent to Automobile **835** (S1). Here, the direction controlling signal indicates either to move forward, back, left, or right Automobile **835**. Upon receiving the direction controlling signal from Communication Device **200**, Automobile **835** stores the signal in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** controls the direction via Direction Controller **83565c1b** (Paragraph [0260]) in accordance with the direction controlling signal (S3).

Paragraph [0278]—This Paragraph [0278] illustrates Speed Controlling Software **83565c2c** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Speed Controlling Software **20665c2c** (Paragraph [0274]) of Communication Device **200**, which control the speed of Automobile **835**. In the present embodiment, the user of Communication Device **200** inputs a speed controlling signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system. The signal is sent to Automobile **835** (S1). Here, the speed controlling signal indicates either to increase speed or decrease speed of Automobile **835**. Upon receiving the speed controlling signal from Communication Device **200**, Automobile **835** stores the signal in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** controls the speed via Speed Controller **83565c1c** (Paragraph [0260]) in accordance with the speed controlling signal (S3).

Paragraph [0279]—This Paragraph [0279] illustrates Window Controlling Software **83565c2d** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Window Controlling Software **20665c2d** (Paragraph [0274]) of Communication Device **200**, which control the window (not shown) of Automobile **835**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves all window data from Window Data Storage Area **20665b2** (Paragraph [0267]) and displays the data on LCD **201** (FIG. 1) (S1). The user of Communication Device **200** selects one of the window data (for example, Window Data#1), and CPU **211** identifies the corresponding window ID (for example, Window#1) by referring to Window Data Storage Area **20665b2** (Paragraph [0267]) (S2). The user further inputs a window controlling signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S3). Here, the window controlling signal indicates either to open the window or to close the window. CPU **211** sends the window ID and the window controlling signal to Automobile **835** (S4). Upon receiving the window ID and the window controlling signal from Communication Device **200**, Automobile **835** stores both data in Work Area **83565b7** (Paragraph [0252]) (S5). Automobile **835** controls the window identified by the window ID via Window Controller **83565c1d** (Paragraph [0260]) in accordance with the window controlling signal (S6).

Paragraph [0280]—This Paragraph [0280] illustrates Door Controlling Software **83565c2e** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Door Controlling Software **20665c2e** (Paragraph [0274]) of Communication Device **200**, which control the door (not shown) of Automobile **835**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves all door data from Door Data Storage Area **20665b3** (Paragraph [0268]) and displays

the data on LCD 201 (FIG. 1) (S1). The user of Communication Device 200 selects one of the door data (for example, Door Data#1), and CPU 211 identifies the corresponding door ID (for example, Door#1) by referring to Door Data Storage Area 20665b3 (Paragraph [0268]) (S2). The user further inputs a door controlling signal by utilizing Input Device 210 (FIG. 1) or via voice recognition system. Here, the door controlling signal indicates either to open the door or to close the door (S3). CPU 211 sends the door ID and the door controlling signal to Automobile 835 (S4). Upon receiving the door ID and the door controlling signal from Communication Device 200, Automobile 835 stores both data in Work Area 83565b7 (Paragraph [0252]) (S5). Automobile 835 controls the door identified by the door ID via Door Controller 83565c1e (Paragraph [0260]) in accordance with the door controlling signal (S6).

Paragraph [0281]—This Paragraph [0281] illustrates Radio Controlling Software 83565c2f (Paragraph [0261]) of Automobile 835 (Paragraph [0249]) and Radio Controlling Software 20665c2f (Paragraph [0274]) of Communication Device 200, which turn on or turn off the radio (not shown) installed in Automobile 835. In the present embodiment, the user of Communication Device 200 inputs a radio controlling signal, and CPU 211 sends the signal to Automobile 835 (S1). Here, the radio controlling signal indicates either to turn on the radio or to turn off the radio. Upon receiving the radio controlling signal from Communication Device 200, Automobile 835 stores the signal in Work Area 83565b7 (Paragraph [0252]) (S2). Automobile 835 controls the radio via Radio Controller 83565c1f (Paragraph [0260]) in accordance with the radio controlling signal (S3).

Paragraph [0282]—This Paragraph [0282] illustrates TV Controlling Software 83565c2g (Paragraph [0261]) of Automobile 835 (Paragraph [0249]) and TV Controlling Software 20665c2g (Paragraph [0274]) of Communication Device 200, which turn on or turn off the TV (not shown) installed in Automobile 835. In the present embodiment, the user of Communication Device 200 inputs a TV controlling signal, and CPU 211 (FIG. 1) sends the signal to Automobile 835 (S1). Here, the TV controlling signal indicates either to turn on the TV or to turn off the TV. Upon receiving the TV controlling signal from Communication Device 200, Automobile 835 stores the signal in Work Area 83565b7 (Paragraph [0252]) (S2). Automobile 835 controls the TV via TV Controller 83565c1g (Paragraph [0260]) in accordance with the TV controlling signal (S3).

Paragraph [0283]—This Paragraph [0283] illustrates Radio Channel Selecting Software 83565c2h (Paragraph [0261]) of Automobile 835 (Paragraph [0249]) and Radio Channel Selecting Software 20665c2h (Paragraph [0274]) of Communication Device 200, which select the channel of the radio (not shown) installed in Automobile 835. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves all radio channel data from Radio Channel Data Storage Area 20665b4 (Paragraph [0269]) and Displays the data on LCD 201 (FIG. 1) (S1). The user of Communication Device 200 selects one of the radio channel data (for example, Radio Channel Data#1), and CPU 211 identifies the corresponding radio channel ID (for example, Radio Channel#1) by referring to Radio Channel Data Storage Area 20665b4 (Paragraph [0269]) (S2). CPU 211 sends the radio channel ID and the radio channel controlling signal to Automobile 835 (S3). Here, the radio channel controlling signal indicates to change the radio channel to the one identified by the radio channel ID. Upon receiving the radio channel ID and the radio channel controlling signal from Communication Device 200, Automobile 835 stores both data in Work Area 83565b7

(Paragraph [0252]) (S4). Automobile 835 controls the radio channel of the radio via Radio Channel Selector 83565c1h (Paragraph [0260]) in accordance with the Radio Channel Controlling Signal (S5).

Paragraph [0284]—This Paragraph [0284] illustrates TV Channel Selecting Software 83565c2i (Paragraph [0261]) of Automobile 835 (Paragraph [0249]) and TV Channel Selecting Software 20665c2i (Paragraph [0274]) of Communication Device 200, which select the channel of the TV (not shown) installed in Automobile 835. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves all TV channel data from TV Channel Data Storage Area 20665b5 (Paragraph [0270]) and displays the data on LCD 201 (FIG. 1) (S1). The user of Communication Device 200 selects one of the TV channel data, and CPU 211 identifies the corresponding TV channel ID (for example, TV Channel#1) by referring to TV Channel Data Storage Area 20665b5 (Paragraph [0270]) (S2). CPU 211 sends the TV channel ID and the TV channel controlling signal to Automobile 835 (S3). Here, the TV channel controlling signal indicates to change the TV channel to the one identified by the TV channel ID. Upon receiving the TV channel ID and the TV channel controlling signal from Communication Device 200, Automobile 835 stores both data in Work Area 83565b7 (Paragraph [0252]) (S4). Automobile 835 controls the TV Channel via TV Channel Selector 83565c1i (Paragraph [0260]) in accordance with the TV channel controlling signal (S5).

Paragraph [0285]—This Paragraph [0285] illustrates Blinker Controlling Software 83565c2j (Paragraph [0261]) of Automobile 835 (Paragraph [0249]) and Blinker Controlling Software 20665c2j (Paragraph [0274]) of Communication Device 200, which turn on or turn off the blinker (not shown) of Automobile 835. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves all blinker data from Blinker Data Storage Area 20665b6 (Paragraph [0271]) and displays the data on LCD 201 (FIG. 1) (S1). The user of Communication Device 200 selects one of the blinker data, and CPU 211 identifies the corresponding blinker ID (for example Blinker#1) by referring to Blinker Data Storage Area 20665b6 (Paragraph [0271]) (S2). CPU 211 sends the blinker ID and the blinker controlling signal to Automobile 835 (S3). Here, the blinker controlling signal indicates either to turn on or turn off the blinker identified by the blinker ID. Upon receiving the blinker ID and the blinker controlling signal from Communication Device 200, Automobile 835 stores both data in Work Area 83565b7 (Paragraph [0252]) (S4). Automobile 835 controls the blinker via Blinker Controller 20665c1j in accordance with the blinker controlling signal (S5).

Paragraph [0286]—This Paragraph [0286] illustrates Emergency Lamp Controlling Software 83565c2k (Paragraph [0261]) of Automobile 835 (Paragraph [0249]) and Emergency Lamp Controlling Software 20665c2k (Paragraph [0274]) of Communication Device 200, which turn on or turn off the emergency lamp (not shown) installed in Automobile 835. In the present embodiment, the user of Communication Device 200 inputs an emergency lamp controlling signal, and CPU 211 (FIG. 1) sends the signal to Automobile 835 (S1). Here, the emergency lamp controlling signal indicates either to turn on the emergency lamp or to turn off the emergency lamp. Upon receiving the emergency lamp controlling signal from Communication Device 200, Automobile 835 stores the signal in Work Area 83565b7 (Paragraph [0252]) (S2). Automobile 835 controls the emergency lamp

via Emergency Lamp Controller **83565c1k** (Paragraph [0260]) in accordance with the emergency lamp controlling signal (S3).

Paragraph [0287]—This Paragraph [0287] illustrates Cruise Control Controlling Software **83565c2l** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Cruise Control Controlling Software **20665c2l** (Paragraph [0274]) of Communication Device **200**, which turn on or turn off the cruise control (not shown) of Automobile **835**. In the present embodiment, the user of Communication Device **200** inputs a cruise control controlling signal, and CPU **211** (FIG. 1) sends the signal to Automobile **835** (S1). Here, the cruise control controlling signal indicates either to turn on the cruise control or turn off the cruise control. Upon receiving the cruise control controlling signal from Communication Device **200**, Automobile **835** stores the signal in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** controls the cruise control via Cruise Control Controller **83565c1l** (Paragraph [0260]) in accordance with the cruise control controlling signal (S3).

Paragraph [0288]—This Paragraph [0288] illustrates Speaker Volume Controlling Software **83565c2m** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Speaker Volume Controlling Software **20665c2m** (Paragraph [0274]) of Communication Device **200**, which raise or lower the volume of the speaker (not shown) of Automobile **835**. In the present embodiment, the user of Communication Device **200** inputs a speaker volume controlling signal, and CPU **211** (FIG. 1) sends the signal to Automobile **835** (S1). Here, the speaker volume controlling signal indicates either to raise the volume or lower the volume of the speaker. Upon receiving the speaker volume controlling signal from Communication Device **200**, Automobile **835** stores the signal in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** controls the speaker volume of the speaker via Speaker Volume Controller **83565c1m** (Paragraph [0260]) in accordance with the speaker volume controlling signal (S3).

Paragraph [0289]—This Paragraph [0289] illustrates Controller Reinstalling Software **83565c2n** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Controller Reinstalling Software **20665c2n** (Paragraph [0274]) of Communication Device **200**, which reinstalls the controllers to Automobile Controller Storage Area **83565c1**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves all controllers from Automobile Controller Storage Area **20665c1**, and sends the controllers to Automobile **835** (S1). Upon receiving the controllers from Communication Device **200**, Automobile **835** stores the controllers in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** then reinstalls the controllers in Automobile Controller Storage Area **83565c1** (S3).

Paragraph [0290]—This Paragraph [0290] illustrates Data Reinstalling Software **83565c2o** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Data Reinstalling Software **20665c2o** (Paragraph [0274]) of Communication Device **200**, which reinstall the data to Automobile Controlling Data Storage Area **20665b**. In the present embodiment, Automobile **835** retrieves all data from Automobile Controlling Data Storage Area **83565b**, and sends the data to Communication Device **200** (S1). Upon receiving the data from Automobile **835**, CPU **211** (FIG. 1) of Communication Device **200** stores the data in Work Area **20665b7** (S2). CPU **211** then reinstalls the data in Automobile Controlling Data Storage Area **20665b** (S3).

Paragraph [0291]—For the avoidance of doubt, Automobile **835** (Paragraph [0249]) is not limited to an automobile or a car; the present function may be implemented with any type

of carrier or vehicle, such as airplane, space ship, artificial satellite, space station, train, and motor cycle.

Paragraph [0292]—<<DVD Remote Controlling Function>>

Paragraph [0293]—Paragraph [0294] through Paragraph [0315] illustrate DVD remote controlling function which enables Communication Device **200** to remotely control a DVD player (not shown).

Paragraph [0294]—This Paragraph [0294] illustrates the screen displayed on DVD Monitor DVD**M69**, a monitor which displays the DVD signal received from the DVD player, after both DVD Monitor DVD**M69** and the DVD player are powered on. In the present embodiment, DVD Monitor DVD**M69** displays Main Menu MM**69** of the movie inserted in the DVD player. In the present embodiment, Main Menu MM**69** is composed of the following menu icons: Chapter Menu Icon MM**69a**, Language Menu Icon MM**69b**, Sub-title Menu Icon MM**69c**, and Start Movie Icon MM**69d**. Chapter Menu Icon MM**69a** is the icon which displays the screen described in Paragraph [0295] upon which said icon is selected by the user of Communication Device **200**. Language Menu Icon MM**69b** is the icon which displays the screen described in Paragraph [0296] upon which said icon is selected by the user of Communication Device **200**. Sub-title Menu Icon MM**69c** is the icon which displays the screen described in Paragraph [0297] upon which said icon is selected by the user of Communication Device **200**. Start Movie Icon MM**69d** is the icon which starts the movie inserted in the DVD player (not shown) upon which said icon is selected by the user of Communication Device **200**.

Paragraph [0295]—This Paragraph [0295] illustrates the screen displayed on DVD Monitor DVD**M69** when Chapter Menu Icon MM**69a** is selected from Main Menu MM**69** (Paragraph [0294]). In the present embodiment, DVD Monitor DVD**M69** displays Chapter List CL**69** of the movie inserted in the DVD player. In the present example, Chapter List CL**69** is composed of the following chapter icons: Chapter 1 Icon CL**69a**, Chapter 2 Icon CL**69b**, Chapter 3 Icon CL**69c**, Chapter 4 Icon CL**69d**, Start Movie Icon CL**69e**, and Main Menu Icon CL**69f**. Chapter 1 Icon CL**69a** represents the first chapter of the movie inserted in the DVD player. Chapter 2 Icon CL**69b** represents the second chapter of the movie inserted in the DVD player. Chapter 3 Icon CL**69c** represents the third chapter of the movie inserted in the DVD player. Chapter 4 Icon CL**69d** represents the fourth chapter of the movie inserted in the DVD player. Start Movie Icon CL**69e** is the icon which starts, upon which said icon is selected by the user, the movie inserted in the DVD player (not shown) from the chapter represented by the icon selected by the user of Communication Device **200**. Assume that the user selects Chapter 3 Icon CL**69c** from Chapter List CL**69**. The movie starts from the chapter represented by Chapter 3 Icon CL**69c** thereafter. Main Menu Icon CL**69f** is the icon which displays the screen described in Paragraph [0294] upon which said icon is selected by the user of Communication Device **200**.

Paragraph [0296]—This Paragraph [0296] illustrates the screen displayed on DVD Monitor DVD**M69** when Language Menu Icon MM**69b** is selected from Main Menu MM**69** (Paragraph [0294]). In the present embodiment, DVD Monitor DVD**M69** displays Language List LL**69** of the movie inserted in the DVD player. In the present embodiment, Language List LL**69** is composed of the following language icons: English Icon LL**69a**, Japanese Icon LL**69b**, French Icon LL**69c**, and Main Menu Icon LL**69d**. English Icon LL**69a** is the icon which plays the movie inserted in the DVD player (not shown) in English upon which said icon is selected by the user of Communication Device **200**. Japanese

Icon LL**69b** is the icon which plays the movie inserted in the DVD player (not shown) in Japanese upon which said icon is selected by the user of Communication Device **200**. French Icon LL**69c** is the icon which plays the movie inserted in the DVD player (not shown) in French upon which said icon is selected by the user of Communication Device **200**. Main Menu Icon LL**69d** is the icon which displays the screen described in Paragraph [0294] upon which said icon is selected by the user of Communication Device **200**.

Paragraph [0297]—This Paragraph [0297] illustrates the screen displayed on DVD Monitor DVDM**69** when Sub-title Menu Icon MM**69c** is selected from Main Menu MM**69** (Paragraph [0294]). In the present embodiment, DVD Monitor DVDM**69** displays Sub-title List StL**69** of the movie inserted in the DVD player. In the present embodiment, Sub-title List StL**69** is composed of the following sub-title icons: English Icon StL**69a**, Japanese Icon StL**69b**, French Icon StL**69c**, Sub-title OFF Icon StL**69d**, and Main Menu Icon StL**69e**. English Icon StL**69a** is the icon which displays the sub-titles in English while played of the movie inserted in the DVD player (not shown) upon which said icon is selected by the user of Communication Device **200**. Japanese Icon StL**69b** is the icon which displays the sub-titles in Japanese while played of the movie inserted in the DVD player (not shown) upon which said icon is selected by the user of Communication Device **200**. French Icon StL**69c** is the icon which displays the sub-titles in French while played of the movie inserted in the DVD player (not shown) upon which said icon is selected by the user of Communication Device **200**. Sub-title OFF Icon StL**69d** is the icon which displays no sub-title while played of the movie upon which said icon is selected by the user of Communication Device **200**. Main Menu Icon StL**69e** is the icon which displays the screen described in Paragraph [0294] upon which said icon is selected by the user of Communication Device **200**.

Paragraph [0298]—This Paragraph [0298] illustrates the storage area included in RAM **206** (FIG. 1) of Communication Device **200**. In the present embodiment, RAM **206** includes DVD Remote Controlling Information Storage Area **20669a** of which the data and the software programs stored therein are described in Paragraph [0300].

Paragraph [0299]—The data and/or the software programs stored in DVD Remote Controlling Information Storage Area **20669a** (Paragraph [0298]) may be downloaded from Host H (Paragraph [0025]).

Paragraph [0300]—This Paragraph [0300] illustrates the storage areas included in DVD Remote Controlling Information Storage Area **20669a** (Paragraph [0298]). In the present embodiment, DVD Remote Controlling Information Storage Area **20669a** includes DVD Remote Controlling Data Storage Area **20669b** and DVD Remote Controlling Software Storage Area **20669c**. DVD Remote Controlling Data Storage Area **20669b** stores the data necessary to implement the present function, such as the ones described in Paragraph [0301] through Paragraph [0303]. DVD Remote Controlling Software Storage Area **20669c** stores the software programs necessary to implement the present function, such as the ones described in Paragraph [0304].

Paragraph [0301]—This Paragraph [0301] illustrates the storage areas included in DVD Remote Controlling Data Storage Area **20669b** (Paragraph [0300]). In the present embodiment, DVD Remote Controlling Data Storage Area **20669b** includes DVD Player Type Data Storage Area **20669b1** and Work Area **20669b2**. DVD Player Type Data Storage Area **20669b1** stores the data described in Paragraph [0302]. Work Area **20669b2** is utilized as a work area to perform calculation and temporarily store data.

Paragraph [0302]—This Paragraph [0302] illustrates the data stored in DVD Player Type Data Storage Area **20669b1** (Paragraph [0301]). In the present embodiment, DVD Player Type Data Storage Area **20669b1** comprises two columns, i.e., 'DVD Player Type ID' and 'DVD Player Type Data'. Column 'DVD Player Type ID' stores the DVD player type IDs, and each DVD player ID is an identification of the DVD player type data stored in column 'DVD Player Type Data'. Each DVD player ID is the name of the DVD player manufacturer. Column 'DVD Player Type Data' stores the DVD player type data, and each DVD player type data is a package of signals designed to be sent to the DVD player (not shown) in a wireless fashion via Antenna **218** (FIG. 1) or LED **219** (not shown). In the present embodiment, DVD Player Type Data Storage Area **20669b1** stores the following data: DVD player type ID 'DVD Player Type#1' and the corresponding DVD player type Data 'DVD Player Type Data#1'; DVD player type ID 'DVD Player Type#2' and the corresponding DVD player type Data 'DVD Player Type Data#2'; DVD player type ID 'DVD Player Type#3' and the corresponding DVD player type Data 'DVD Player Type Data#3'; and DVD player type ID 'DVD Player Type#4' and the corresponding DVD player type Data 'DVD Player Type Data#4'. Here, DVD Player Type#1 represents Sony; DVD Player Type#2 represents Samsung; DVD Player Type#3 represents NEC; and DVD Player Type#4 represents Mitsubishi. DVD Player Type Data#1 is a package of signals designed to be sent to the DVD player manufactured by Sony in a wireless fashion via Antenna **218** (FIG. 1) or LED **219** (not shown). DVD Player Type Data#2 is a package of signals designed to be sent to the DVD player manufactured by Samsung in a wireless fashion via Antenna **218** (FIG. 1) or LED **219** (not shown). DVD Player Type Data#3 is a package of signals designed to be sent to the DVD player manufactured by NEC in a wireless fashion via Antenna **218** (FIG. 1) or LED **219** (not shown). DVD Player Type Data#4 is a package of signals designed to be sent to the DVD player manufactured by Mitsubishi in a wireless fashion via Antenna **218** (FIG. 1) or LED **219** (not shown). Each DVD player type data includes the following data: power on signal, power off signal, main menu displaying signal, main menu selecting signal, chapter menu selecting signal, chapter selecting signal, movie starting signal, sound menu selecting signal, sound selecting signal, sub-title menu selecting signal, and sub-title selecting signal. The details of each signal is described in the next paragraph.

Paragraph [0303]—This Paragraph [0303] illustrates the signals included in DVD Player Type Data#1 stored in DVD Player Type Data Storage Area **20669b1** (Paragraph [0302]), for example. As described in the present paragraph, DVD Player Type Data#1 includes Power ON Signal#1, Power OFF Signal#1, Main Menu Displaying Signal#1, Chapter Menu Selecting Signal#1, Chapter Selecting Signal#1, Movie Starting Signal#1, Language Menu Selecting Signal#1, Language Selecting Signal#1, Sub-title Menu Selecting Signal#1, and Sub-title Selecting Signal#1. Power ON Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to turn on its power. Power OFF Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to turn off its power. Main Menu Displaying Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to display Main Menu MM**69** (Paragraph [0294]). Chapter Menu Selecting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select Chapter Menu Icon MM**69a** (Paragraph [0294]) and display Chapter List CL**69** (Paragraph [0295]). Chapter

Selecting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select one of the chapter icons from Chapter List CL**69** (Paragraph [0295]). Movie Starting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to start the movie from the chapter represented by the chapter icon identified by Chapter Selecting Signal#1. Language Menu Selecting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select Language Menu Icon MM**69b** (Paragraph [0294]) and display Language List LL**69** (Paragraph [0296]). Language Selecting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select one of the sound icons from Language List LL**69** (Paragraph [0296]). Sub-title Menu Selecting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select Sub-title Menu Icon MM**69c** (Paragraph [0294]) and display Sub-title List StL**69** (Paragraph [0297]). Sub-title Selecting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select one of the sub-title icons from Sub-title List StL**69** (Paragraph [0297]).

Paragraph [0304]—This Paragraph [0304] illustrates the software programs stored in DVD Remote Controlling Software Storage Area **20669c** (Paragraph [0300]). In the present embodiment, DVD Remote Controlling Software Storage Area **20669c** stores DVD Player Type Selecting Software **20669c1**, DVD Power ON Software **20669c2**, DVD Power OFF Software **20669c3**, Main Menu Displaying Software **20669c4**, Chapter Menu Selecting Software **20669c5**, Chapter Selecting Software **20669c6**, Movie Starting Software **20669c7**, Language Menu Selecting Software **20669c8**, Language Selecting Software **20669c9**, Sub-title Menu Selecting Software **20669c10**. DVD Player Type Selecting Software **20669c1** is the software program described in Paragraph [0305]. DVD Power ON Software **20669c2** is the software program described in Paragraph [0306]. DVD Power OFF Software **20669c3** is the software program described in Paragraph [0307]. Main Menu Displaying Software **20669c4** is the software program described in Paragraph [0308]. Chapter Menu Selecting Software **20669c5** is the software program described in Paragraph [0309]. Chapter Selecting Software **20669c6** is the software program described in Paragraph [0310]. Movie Starting Software **20669c7** is the software program described in Paragraph [0311]. Language Menu Selecting Software **20669c8** is the software program described in Paragraph [0312]. Language Selecting Software **20669c9** is the software program described in Paragraph [0313]. Sub-title Menu Selecting Software **20669c10** is the software program described in Paragraph [0314]. Sub-title Selecting Software **20669c11** is the software program described in Paragraph [0315].

Paragraph [0305]—This Paragraph [0305] illustrates DVD Player Type Selecting Software **20669c1** (Paragraph [0304]) of Communication Device **200**, which selects the DVD player type of the DVD player. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves all DVD Player Type IDs from DVD Player Type Data Storage Area **20669b1** (Paragraph [0302]) (S1), and displays a list of DVD player type IDs on LCD **201** (FIG. 1) (S2). The user of Communication Device **200** selects a DVD player type ID by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S3). CPU **211** retrieves the corresponding DVD player type data, and stores the data in Work Area **20669b2** (Paragraph [0301]) (S4). Assume that the DVD player ID selected in S3 is DVD Player Type#1 (i.e., Sony) and DVD

Player Type Data#1 is stored in Work Area **20669b2** in S4 for purposes of explaining the software programs hereinafter.

Paragraph [0306]—This Paragraph [0306] illustrates DVD Power ON Software **20669c2** (Paragraph [0304]) of Communication Device **200**, which sends Power ON Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to turn on its power. In the present embodiment, the user of Communication Device **200** inputs a power ON command by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S1). CPU **211** (FIG. 1) retrieves Power ON Signal#1 from Work Area **20669b2** (Paragraph [0301]) (S2), and sends Power ON Signal#1 to the DVD player (S3).

Paragraph [0307]—This Paragraph [0307] illustrates DVD Power OFF Software **20669c3** (Paragraph [0304]) of Communication Device **200**, which sends Power OFF Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to turn off its power. In the present embodiment, the user of Communication Device **200** inputs a power OFF command by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S1). CPU **211** (FIG. 1) retrieves Power OFF Signal#1 from Work Area **20669b2** (Paragraph [0301]) (S2), and sends Power OFF Signal#1 to the DVD player (S3).

Paragraph [0308]—This Paragraph [0308] illustrates Main Menu Displaying Software **20669c4** (Paragraph [0304]) of Communication Device **200**, which sends Main Menu Displaying Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to display Main Menu MM**69** (Paragraph [0294]). In the present embodiment, the user of Communication Device **200** inputs a main menu displaying command by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S1). CPU **211** (FIG. 1) retrieves Main Menu Displaying Signal#1 from Work Area **20669b2** (Paragraph [0301]) (S2), and sends Main Menu Displaying Signal#1 to the DVD player (S3).

Paragraph [0309]—This Paragraph [0309] illustrates Chapter Menu Selecting Software **20669c5** (Paragraph [0304]) of Communication Device **200**, which sends Chapter Menu Selecting Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select Chapter Menu Icon MM**69a** (Paragraph [0294]) and display Chapter List CL**69** (Paragraph [0295]). In the present embodiment, the user of Communication Device **200** inputs a chapter menu selecting command by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S1). CPU **211** (FIG. 1) retrieves Chapter Menu Selecting Signal#1 from Work Area **20669b2** (Paragraph [0301]) (S2), and sends Chapter Menu Selecting Signal#1 to the DVD player (S3).

Paragraph [0310]—This Paragraph [0310] illustrates Chapter Selecting Software **20669c6** (Paragraph [0304]) of Communication Device **200**, which sends Chapter Selecting Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select one of the chapter icons from Chapter List LL**69** (Paragraph [0295]). In the present embodiment, the user of Communication Device **200** inputs a chapter selecting command by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S1). CPU **211** (FIG. 1) retrieves Chapter Selecting Signal#1 from Work Area **20669b2** (Paragraph [0301]) (S2), and sends Chapter Selecting Signal#1 to the DVD player (S3).

Paragraph [0311]—This Paragraph [0311] illustrates Movie Starting Software **20669c7** (Paragraph [0304]) of Communication Device **200**, which sends Movie Starting Signal#1, i.e., the wireless signal which instructs the DVD

player of the corresponding manufacturer (i.e., Sony) to start the movie from the chapter represented by the chapter icon identified by Chapter Selecting Signal#1. In the present embodiment, the user of Communication Device 200 inputs a movie starting command by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S1). CPU 211 (FIG. 1) retrieves Movie Starting Signal#1 from Work Area 20669b2 (Paragraph [0301]) (S2), and sends Movie Starting Signal#1 to the DVD player (S3).

Paragraph [0312]—This Paragraph [0312] illustrates Language Menu Selecting Software 20669c8 (Paragraph [0304]) of Communication Device 200, which sends Language Menu Selecting Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select Language Menu Icon MM69b (Paragraph [0294]) and display Language List LL69 (Paragraph [0296]). In the present embodiment, the user of Communication Device 200 inputs a language menu selecting command by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S1). CPU 211 (FIG. 1) retrieves Language Menu Selecting Signal#1 from Work Area 20669b2 (Paragraph [0301]) (S2), and sends Language Menu Selecting Signal#1 to the DVD player (S3).

Paragraph [0313]—This Paragraph [0313] illustrates Language Selecting Software 20669c9 (Paragraph [0304]) of Communication Device 200, which sends Language Selecting Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select one of the sound icons from Language List LL69 (Paragraph [0296]). In the present embodiment, the user of Communication Device 200 inputs a language selecting command by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S1). CPU 211 (FIG. 1) retrieves Language Selecting Signal#1 from Work Area 20669b2 (Paragraph [0301]) (S2), and sends Language Selecting Signal#1 to the DVD player (S3).

Paragraph [0314]—This Paragraph [0314] illustrates Sub-title Menu Selecting Software 20669c10 (Paragraph [0304]) of Communication Device 200, which sends Sub-title Menu Selecting Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select Sub-title Menu Icon MM69c (Paragraph [0294]) and display Sub-title List StL69 (Paragraph [0297]). In the present embodiment, the user of Communication Device 200 inputs a sub-title menu selecting command by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S1). CPU 211 (FIG. 1) retrieves Sub-title Menu Selecting Signal#1 from Work Area 20669b2 (Paragraph [0301]) (S2), and sends Sub-title Menu Selecting Signal#1 to the DVD player (S3).

Paragraph [0315]—This Paragraph [0315] illustrates Sub-title Selecting Software 20669c11 (Paragraph [0304]) of Communication Device 200, which sends Sub-title Selecting Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select one of the sub-title icons from Sub-title List StL69 (Paragraph [0297]). In the present embodiment, the user of Communication Device 200 inputs a sub-title selecting command by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S1). CPU 211 (FIG. 1) retrieves Sub-title Selecting Signal#1 from Work Area 20669b2 (Paragraph [0301]) (S2), and sends Sub-title Selecting Signal#1 to the DVD player (S3).

Paragraph [0316]—<<Multiple Mode Implementing Function>>

Paragraph [0317]—Paragraph [0318] through Paragraph [0323] illustrate the multiple mode implementing function of

Communication Device 200 which enables to activate and implement a plurality of modes, functions, and/or systems described in this specification simultaneously.

Paragraph [0318]—This Paragraph [0318] illustrates the software programs stored in RAM 206 (FIG. 1) to implement the multiple mode implementing function (FIG. 1). As described in Paragraph [0318], RAM 206 includes Multiple Mode Implementer Storage Area 20690a. Multiple Mode Implementer Storage Area 20690a stores Multiple Mode Implementer 20690b, Mode List Displaying Software 20690c, Mode Selecting Software 20690d, Mode Activating Software 20690e, and Mode Implementation Repeater 20690f, all of which are software programs. Multiple Mode Implementer 20690b administers the overall implementation of the present function. One of the major tasks of Multiple Mode Implementer 20690b is to administer and control the timing and sequence of Mode List Displaying Software 20690c, Mode Selecting Software 20690d, Mode Activating Software 20690e, and Mode Implementation Repeater 20690f. For example, Multiple Mode Implementer 20690b executes them in the following order: Mode List Displaying Software 20690c, Mode Selecting Software 20690d, Mode Activating Software 20690e, and Mode Implementation Repeater 20690f. Mode List Displaying Software 20690c displays on LCD 201 (FIG. 1) a list of a certain amount or all modes, functions, and/or systems explained in this specification of which the sequence is explained in Paragraph [0319]. Mode Selecting Software 20690d selects a certain amount or all modes, functions, and/or systems explained in this specification of which the sequence is explained in Paragraph [0320]. Mode Activating Software 20690e activates a certain amount or all modes, functions, and/or systems selected by the Mode Selecting Software 20690d of which the sequence is explained in Paragraph [0321]. Mode Implementation Repeater 20690f executes Multiple Mode Implementer 20690b which reactivates Mode List Displaying Software 20690c, Mode Selecting Software 20690d, Mode Activating Software 20690e of which the sequence is explained in Paragraph [0322].

Paragraph [0319]—This Paragraph [0319] illustrates the sequence of Mode List Displaying Software 20690c (Paragraph [0318]). Referring to Paragraph [0319], CPU 211 (FIG. 1), under the command of Mode List Displaying Software 20690c, displays a list of a certain amount or all modes, functions, and/or systems described in this specification on LCD 201 (FIG. 1).

Paragraph [0320]—This Paragraph [0320] illustrates the sequence of Mode Selecting Software 20690d (Paragraph [0318]). Referring to Paragraph [0320], the user of Communication Device 200 inputs an input signal by utilizing Input Device 210 (FIG. 1) or via voice recognition system identifying one of the modes, functions, and/or systems displayed on LCD 201 (FIG. 1) (S1), and CPU 211 (FIG. 1), under the command of Mode Selecting Software 20690d, interprets the input signal and selects the corresponding mode, function, or system (S2).

Paragraph [0321]—This Paragraph [0321] illustrates the sequence of Mode Activating Software 20690e (Paragraph [0318]). Referring to Paragraph [0321], CPU 211 (FIG. 1), under the command of Mode Activating Software 20690e, activates the mode, function, or system selected in S2 of Paragraph [0320]. CPU 211 thereafter implements the activated mode, function, or system as described in the relevant paragraphs in this specification.

Paragraph [0322]—This Paragraph [0322] illustrates the sequence of Mode Implementation Repeater 20690f (Paragraph [0318]). Referring to Paragraph [0322], the user of

Communication Device **200** inputs an input signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S1). Once the activation of the selected mode, function, or system described in Paragraph [0321] hereinbefore is completed, and if the input signal indicates to repeat the process to activate another mode, function, or system (S2), CPU **211** (FIG. 1), under the command of Mode Implementation Repeater **20690f**, executes Multiple Mode Implementer **20690b** (Paragraph [0318]), which reactivates Mode List Displaying Software **20690c** (Paragraph [0318]), Mode Selecting Software **20690d** (Paragraph [0318]), and Mode Activating Software **20690e** (Paragraph [0318]) to activate the second mode, function, or system while the first mode, function, or system is implemented by utilizing the method of so-called 'time sharing' (S3). Mode List Displaying Software **20690c**, Mode Selecting Software **20690d**, and Mode Activating Software **20690e** can be repeatedly executed until all modes, function, and systems displayed on LCD **201** (FIG. 1) are selected and activated. The activation of modes, functions, and/or systems is not repeated if the input signal explained in S2 so indicates.

Paragraph [0323]—As another embodiment, Multiple Mode Implementer **20690b**, Mode List Displaying Software **20690c**, Mode Selecting Software **20690d**, Mode Activating Software **20690e**, and Mode Implementation Repeater **20690f** described in Paragraph [0318] may be integrated into one software program, Multiple Mode Implementer **20690b**, as described in Paragraph [0323]. Referring to Paragraph [0323], CPU **211** (FIG. 1), first of all, displays a list of a certain amount or all modes, functions, and/or systems described in this specification on LCD **201** (FIG. 1) (S1). Next, the user of Communication Device **200** inputs an input signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system identifying one of the modes, functions, and/or systems displayed on LCD **201** (S2), and CPU **211** interprets the input signal and selects the corresponding mode, function, or system (S3). CPU **211** activates the mode, function, or system selected in S3, and thereafter implements the activated mode, function, or system as described in the relevant paragraphs in this specification (S4). Once the activation of the selected mode, function, or system described in S4 is completed, the user of Communication Device **200** inputs an input signal by utilizing Input Device **210** or via voice recognition system (S5). If the input signal indicates to repeat the process to activate another mode, function, or system (S6), CPU **211** repeats the steps S1 through S4 to activate the second mode, function, or system while the first mode, function, or system is implemented by utilizing the method so-called 'time sharing'. The steps of S1 through S4 can be repeatedly executed until all modes, function, and systems displayed on LCD **201** are selected and activated. The activation of modes, functions, and/or systems is not repeated if the input signal explained in S5 so indicates. As another embodiment, before or at the time one software program is activated, CPU **211** may, either automatically or manually (i.e., by a signal input by the user of Communication Device), terminate the other software programs already activated or prohibit other software programs to be activated while one software program is implemented in order to save the limited space of RAM **206**, thereby allowing only one software program implemented at a time. For the avoidance of doubt, the meaning of each term 'mode(s)', 'function(s)', and 'system(s)' is equivalent to the others in this specification. Namely, the meaning of 'mode(s)' includes and is equivalent to that of 'function(s)' and 'system(s)', the meaning of 'function(s)' includes and is equivalent to that of 'mode(s)' and 'system(s)', and the meaning of 'system(s)' includes and is

equivalent to that of 'mode(s)' and 'function(s)'. Therefore, even only mode(s) is expressly utilized in this specification, it impliedly includes function(s) and/or system(s) by its definition.

Paragraph [0324]—<<Incorporation By Reference>>

Paragraph [0325]—All paragraphs and drawings described in U.S. Ser. No. 10/711,265, filed Sep. 7, 2004, are incorporated to this application by reference, particularly the following: the preamble described in paragraph [2149] (no drawings); Communication Device **200** (Voice Communication Mode) described in paragraphs [2150] through [2155] (FIGS. 1 through 2c); Voice Recognition System described in paragraphs [2156] through [2188] (FIGS. 3 through 19); Positioning System described in paragraphs [2189] through [2220] (FIGS. 20a through 32e); Auto Backup System described in paragraphs [2221] through [2230] (FIGS. 33 through 37); Signal Amplifier described in paragraphs [2231] through [2236] (FIG. 38); Audio/Video Data Capturing System described in paragraphs [2237] through [2249] (FIGS. 39 through 44b); Digital Mirror Function (1) described in paragraphs [2250] through [2258] (FIGS. 44c through 44e); Caller ID System described in paragraphs [2259] through [2266] (FIGS. 45 through 47); Stock Purchasing Function described in paragraphs [2267] through [2276] (FIGS. 48 through 52); Timer Email Function described in paragraphs [2277] through [2283] (FIGS. 53a and 53b); Call Blocking Function described in paragraphs [2284] through [2297] (FIGS. 54 through 59); Online Payment Function described in paragraphs [2298] through [2307] (FIGS. 60 through 64); Navigation System described in paragraphs [2308] through [2330] (FIGS. 65 through 74a); Remote Controlling System described in paragraphs [2331] through [2349] (FIGS. 75 through 85); Auto Emergency Calling System described in paragraphs [2350] through [2358] (FIGS. 86 and 87); Cellular TV Function described in paragraphs [2359] through [2443] (FIGS. 88 through 135); 3D Video Game Function described in paragraphs [2444] through [2456] (FIGS. 136 through 144); Digital Mirror Function (2) described in paragraphs [2457] through [2466] (FIGS. 145 through 155); Voice Recognition Sys—E-mail (2) described in paragraphs [2467] through [2475] (FIGS. 156 through 160); Positioning System—GPS Search Engine described in paragraphs [2476] through [2518] (FIGS. 161 through 182); Mobile Ignition Key Function described in paragraphs [2519] through [2541] (FIGS. 183 through 201); Voice Print Authentication System described in paragraphs [2542] through [2552] (FIGS. 202 through 211); Fingerprint Authentication System described in paragraphs [2553] through [2565] (FIGS. 212 through 221); Auto Time Adjust Function described in paragraphs [2566] through [2570] (FIGS. 222 through 224); Video/Photo Mode described in paragraphs [2571] through [2599] (FIGS. 225 through 242); Call Taxi Function described in paragraphs [2600] through [2640] (FIGS. 243 through 269); Shooting Video Game Function described in paragraphs [2641] through [2657] (FIGS. 270 through 283); Driving Video Game Function described in paragraphs [2658] through [2671] (FIGS. 284 through 294); Address Book Updating Function described in paragraphs [2672] through [2692] (FIGS. 295 through 312); Batch Address Book Updating Function—With Host described in paragraphs [2693] through [2714] (FIGS. 313 through 329); Batch Address Book Updating Function—Peer-To-Peer Connection described in paragraphs [2715] through [2719] (FIGS. 329a through 329c); Batch Scheduler Updating Function—With Host described in paragraphs [2720] through [2743] (FIGS. 330 through 350); Batch Scheduler Updating Function—Peer-To-Peer Connection described in paragraphs [2744]

through [2748] (FIGS. **351** and **352**); Calculator Function described in paragraphs [2749] through [2754] (FIGS. **353** through **356**); Spreadsheet Function described in paragraphs [2755] through [2762] (FIGS. **357** through **360**); Word Processing Function described in paragraphs [2763] through [2778] (FIGS. **361** through **373**); TV Remote Controller Function described in paragraphs [2779] through [2801] (FIGS. **374** through **394**); CD/PC Inter-communicating Function described in paragraphs [2802] through [2826] (FIGS. **413** through **427**); PDWR Sound Selecting Function described in paragraphs [2827] through [2863] (FIGS. **428** through **456**); Start Up Software Function described in paragraphs [2864] through [2880] (FIGS. **457** through **466**); Another Embodiment Of Communication Device **200** described in paragraphs [2881] through [2885] (FIGS. **467a** through **467d**); Stereo Audio Data Output Function described in paragraphs [2886] through [2905] (FIGS. **468** through **479**); Stereo Visual Data Output Function described in paragraphs [2906] through [2925] (FIGS. **480** through **491**); Multiple Signal Processing Function described in paragraphs [2926] through [2998] (FIGS. **492** through **529**); Positioning System—Pin-pointing Function described in paragraphs [2999] through [3032] (FIGS. **530** through **553**); Artificial Satellite Host described in paragraphs [3033] through [3051] (FIGS. **554** through **567**); CCD Bar Code Reader Function described in paragraphs [3052] through [3073] (FIGS. **568** through **579**); Online Renting Function described in paragraphs [3074] through [3151] (FIGS. **580** through **633**); SOS Calling Function described in paragraphs [3152] through [3172] (FIGS. **634** through **645**); Input Device described in paragraphs [3173] through [3178] (FIGS. **646** through **650**); PC Remote Controlling Function described in paragraphs [3179] through [3214] (FIGS. **651** through **670**); PC Remote Downloading Function described in paragraphs [3215] through [3264] (FIGS. **671** through **701**); Audiovisual Playback Function described in paragraphs [3265] through [3290] (FIGS. **702** through **716**); Audio Playback Function described in paragraphs [3291] through [3315] (FIGS. **717** through **731**); Ticket Purchasing Function described in paragraphs [3316] through [3345] (FIGS. **732** through **753**); Remote Data Erasing Function described in paragraphs [3346] through [3375] (FIGS. **754** through **774**); Business Card Function described in paragraphs [3376] through [3392] (FIGS. **775** through **783**); Game Vibrating Function described in paragraphs [3393] through [3403] (FIGS. **784** through **786**); Part-time Job Finding Function described in paragraphs [3404] through [3424] (FIGS. **787** through **801**); Parking Lot Finding Function described in paragraphs [3425] through [3464] (FIGS. **802** through **832**); Parts Upgradable Communication Device described in paragraphs [3465] through [3490] (FIGS. **833a** through **833x**); On Demand TV Function described in paragraphs [3491] through [3521] (FIGS. **834** through **855**); Inter-communicating TV Function described in paragraphs [3522] through [3556] (FIGS. **856** through **882**); Display Controlling Function described in paragraphs [3557] through [3574] (FIGS. **883** through **894**); Multiple Party Communicating Function described in paragraphs [3575] through [3608] (FIGS. **894a** through **917**); Display Brightness Controlling Function described in paragraphs [3609] through [3618] (FIGS. **918** through **923**); Multiple Party Pin-pointing Function described in paragraphs [3619] through [3666] (FIGS. **924** through **950f**); Digital Camera Function described in paragraphs [3667] through [3694] (FIGS. **951** through **968**); Phone Number Linking Function described in paragraphs [3695] through [3718] (FIGS. **968a** through **983**); Multiple Window Displaying Function described in paragraphs [3719] through [3737]

(FIGS. **984** through **995**); Mouse Pointer Displaying Function described in paragraphs [3738] through [3775] (FIGS. **996** through **1021**); House Item Pin-pointing Function described in paragraphs [3776] through [3935] (FIGS. **1022** through **1152**); Membership Administrating Function described in paragraphs [3936] through [3978] (FIGS. **1153** through **1188**); Keyword Search Timer Recording Function described in paragraphs [3979] through [4070] (FIGS. **1189** through **1254**); Weather Forecast Displaying Function described in paragraphs [4071] through [4112] (FIGS. **1255** through **1288**); Multiple Language Displaying Function described in paragraphs [4113] through [4170] (FIGS. **1289** through **1331**); Caller's Information Displaying Function described in paragraphs [4171] through [4224] (FIGS. **1332** through **1375**); Communication Device Remote Controlling Function (By Phone) described in paragraphs [4225] through [4265] (FIGS. **1394** through **1415**); Communication Device Remote Controlling Function (By Web) described in paragraphs [4266] through [4306] (FIGS. **1416** through **1437**); Shortcut Icon Displaying Function described in paragraphs [4307] through [4334] (FIGS. **1438** through **1455**); Task Tray Icon Displaying Function described in paragraphs [4335] through [4357] (FIGS. **1456** through **1470**); Multiple Channel Processing Function described in paragraphs [4358] through [4405] (FIGS. **1471** through **1498**); Solar Battery Charging Function described in paragraphs [4406] through [4419] (FIGS. **1499** through **1509**); OS Updating Function described in paragraphs [4420] through [4487] (FIGS. **1510** through **1575**); Device Managing Function described in paragraphs [4488] through [4505] (FIGS. **1576** through **1587**); Automobile Controlling Function described in paragraphs [4506] through [4554] (FIGS. **1588** through **1627**); OCR Function described in paragraphs [4555] through [4590] (FIGS. **1628** through **1652**); Real-time GPS Function described in paragraphs [4591] through [4660] (FIGS. **1653** through **1712**); CCD Video Stabilizing Function described in paragraphs [4661] through [4692] (FIGS. **1713** through **1736**); DVD Remote Controlling Function described in paragraphs [4693] through [4731] (FIGS. **1737** through **1757**); Dual Frame Buffer Implementing Function described in paragraphs [4732] through [4748] (FIGS. **1758** through **1767**); Mouse Pointer Image Auto Changing Function described in paragraphs [4749] through [4762] (FIGS. **1768** through **1774**); Dual CCD Camera Function described in paragraphs [4763] through [4783] (FIGS. **1775a** through **1786**); Radio Tuner Function described in paragraphs [4784] through [4814] (FIGS. **1787** through **1812**); Registered Voice Recognizing Function described in paragraphs [4815] through [4854] (FIGS. **1813** through **1842**); Host's TV Resolution Converting Function described in paragraphs [4855] through [4884] (FIGS. **1843** through **1864**); Voice Shortcut Recognizing Function described in paragraphs [4885] through [4919] (FIGS. **1865** through **1889**); and Vital Sign Monitoring Function described in paragraphs [4920] through [5009] (FIGS. **1890a** through **1954**).

The invention claimed is:

1. A mobile phone comprising:

a CPU which configures said mobile phone to a mobile phone updating mode; and

an antenna;

wherein when said mobile phone updating mode is implemented, a mobile phone updating data is received via said antenna in a wireless fashion; and

wherein said CPU updates by utilizing said mobile phone updating data one or more of the following:

(1) a mobile phone battery controller which controls the mobile phone battery included in said mobile phone,

103

- (2) a mobile phone CCD unit controller which controls the mobile phone CCD unit included in said mobile phone,
- (3) a mobile phone microphone controller which controls the mobile phone microphone included in said mobile phone,
- (4) a mobile phone speaker controller which controls the mobile phone speaker included in said mobile phone, and
- (5) a mobile phone vibrator controller which controls the mobile phone vibrator included in said mobile phone.
2. A mobile phone comprising:
- a CPU which configures said mobile phone to a voice communication mode and a mobile phone updating mode; and
- an antenna;
- wherein when said voice communication mode is implemented, multiple voice data are sent and received via said antenna in a wireless fashion;
- wherein when said mobile phone updating mode is implemented, a mobile phone updating data is received via said antenna in a wireless fashion; and
- wherein said CPU updates by utilizing said mobile phone updating data one or more of the following:
- (1) a mobile phone battery controller which controls the mobile phone battery included in said mobile phone,
- (2) a mobile phone CCD unit controller which controls the mobile phone CCD unit included in said mobile phone,
- (3) a mobile phone microphone controller which controls the mobile phone microphone included in said mobile phone,
- (4) a mobile phone speaker controller which controls the mobile phone speaker included in said mobile phone, and
- (5) a mobile phone vibrator controller which controls the mobile phone vibrator included in said mobile phone.
3. A method to update a mobile phone, comprising:
- receiving a mobile phone updating data via an antenna in a wireless fashion; and
- updating said mobile phone by utilizing said mobile phone updating data;
- wherein one or more of the following is updated by a CPU by utilizing said mobile phone updating data:
- (1) a mobile phone battery controller which controls the mobile phone battery included in said mobile phone,
- (2) a mobile phone CCD unit controller which controls the mobile phone CCD unit included in said mobile phone,
- (3) a mobile phone microphone controller which controls the mobile phone microphone included in said mobile phone,
- (4) a mobile phone speaker controller which controls the mobile phone speaker included in said mobile phone, and
- (5) a mobile phone vibrator controller which controls the mobile phone vibrator included in said mobile phone.
4. The mobile phone of claim 1, wherein said mobile phone is a handheld voice communication device which is operable to implement data communication.

104

5. The mobile phone of claim 1, wherein said mobile phone is a handheld voice communication device which is operable to implement multiple functions simultaneously together with voice communication.

6. The mobile phone of claim 1, wherein said mobile phone battery controller, said mobile phone CCD unit controller, said mobile phone microphone controller, said mobile phone speaker controller, and/or said mobile phone vibrator controller is/are updated to the latest version by said mobile phone updating data.

7. The mobile phone of claim 1, wherein two or more of said mobile phone battery controller, said mobile phone CCD unit controller, said mobile phone microphone controller, said mobile phone speaker controller, and said mobile phone vibrator controller are updated simultaneously.

8. The mobile phone of claim 1, wherein said mobile phone updating data is received from a host computer.

9. The mobile phone of claim 2, wherein said mobile phone is a handheld voice communication device which is operable to implement data communication.

10. The mobile phone of claim 2, wherein said mobile phone is a handheld voice communication device which is operable to implement multiple functions simultaneously together with voice communication.

11. The mobile phone of claim 2, wherein said mobile phone battery controller, said mobile phone CCD unit controller, said mobile phone microphone controller, said mobile phone speaker controller, and/or said mobile phone vibrator controller is/are updated to the latest version by said mobile phone updating data.

12. The mobile phone of claim 2, wherein two or more of said mobile phone battery controller, said mobile phone CCD unit controller, said mobile phone microphone controller, said mobile phone speaker controller, and said mobile phone vibrator controller are updated simultaneously.

13. The mobile phone of claim 2, wherein said mobile phone updating data is received from a host computer.

14. The method of claim 3, wherein said mobile phone is a handheld voice communication device which is operable to implement data communication.

15. The method of claim 3, wherein said mobile phone is a handheld voice communication device which is operable to implement multiple functions simultaneously together with voice communication.

16. The method of claim 3, wherein said mobile phone battery controller, said mobile phone CCD unit controller, said mobile phone microphone controller, said mobile phone speaker controller, and/or said mobile phone vibrator controller is/are updated to the latest version by said mobile phone updating data.

17. The method of claim 3, wherein two or more of said mobile phone battery controller, said mobile phone CCD unit controller, said mobile phone microphone controller, said mobile phone speaker controller, and said mobile phone vibrator controller are updated simultaneously.

18. The method of claim 3, wherein said mobile phone updating data is received from a host computer.

* * * * *