



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
16.09.2020 Bulletin 2020/38

(51) Int Cl.:
A45C 13/00 ^(2006.01) **A45C 3/08** ^(2006.01)
A45C 13/02 ^(2006.01)

(21) Application number: **20163113.2**

(22) Date of filing: **13.03.2020**

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

Designated Extension States:
BA ME

Designated Validation States:
KH MA MD TN

(72) Inventors:
• **YEATES, Eric M.**
Virginia Beach, VA 23451 (US)
• **STORMS, Jr., Frederick W.**
Virginia Beach, VA 23456 (US)

(74) Representative: **J A Kemp LLP**
14 South Square
Gray's Inn
London WC1R 5JJ (GB)

(30) Priority: **14.03.2019 US 201962818511 P**

(71) Applicant: **Sentry Solutions Products Group LLC**
Virginia Beach, VA 23452 (US)

(54) **MODULAR ATTACHMENT APERTURE ARRAY**

(57) A modular attachment aperture array having an aperture array layer, wherein the aperture array layer comprises a plurality of spaced apart array apertures, wherein each array aperture is formed of two substantially equal length, substantially parallel sides and an arcuate side joining respective upper terminal ends and respective lower terminal ends of each of the arcuate

sides, wherein each of the array apertures is formed through the aperture array layer, and wherein the array apertures are arranged in a repeating sequence of spaced rows and spaced columns, and wherein the aperture array layer is at least partially attached or coupled to at least a portion of the carrier material.




FIG. 3

Description

[0001] The present disclosure relates generally to the field of modular attachment systems. More specifically, the presently disclosed systems, methods, and/or apparatuses relates to a modular attachment system having an aperture array.

[0002] It is advantageous be able to configure and/or reconfigure various pouches, pockets, holsters, holders, and other accessories on items such as, for example, articles of clothing, vests, plate carriers, backpacks, packs, platforms, and other carriers.

[0003] It is generally known to removably attach such items using a MOLLE or other similar attachment system. The term MOLLE (Modular Lightweight Load-carrying Equipment) is used to generically describe load bearing systems and subsystems that utilize corresponding rows of woven webbing for modular pouch, pocket, and accessory attachment.

[0004] The MOLLE system is a modular system that incorporates the use of corresponding rows of webbing stitched onto a piece of equipment, such as a vest, and the various MOLLE compatible pouches, pockets, and accessories, each accessory having mating rows of stitched webbing. MOLLE compatible pouches, pockets, and accessories of various utility can then be attached or coupled wherever MOLLE webbing exists on the equipment.

[0005] The terms "MOLLE-compatible" or "MOLLE" system are not used to describe a specific system, but to generically describe accessory attachment systems that utilize interwoven PALS (Pouch Attachment Ladder System) webbing for modular accessory attachment.

[0006] As illustrated in **FIGS. 1-2**, an exemplary MOLLE compatible carrier portion **10** includes a plurality of substantially parallel rows of spaced apart, horizontal carrier webbing elements **23**. Each of the carrier webbing elements **23** is secured to a backing or carrier material **12**, by vertical stitching **24**, at spaced apart locations, such that a tunnel segment **27** is formed between the carrier material **12** and the carrier webbing elements **23** between each secured location of the carrier webbing elements **23**. Each of the tunnel segments **27** is formed substantially perpendicular to a longitudinal axis or direction of the carrier webbing elements **23**.

[0007] The MOLLE compatible carrier portion **10**, or MOLLE system grid, typically consists of horizontal rows of 1 inch (2.5 cm) webbing, spaced 1 inch apart, and attached or coupled to the carrier material **12** at 1.5 inch (3.8 cm) intervals.

[0008] An exemplary accessory **81** includes a plurality of substantially parallel, spaced apart accessory webbing elements **83**. The accessory webbing elements **83** are spaced apart so as to correspond to the spaces between the spaced apart carrier webbing elements **23**. The accessory webbing elements **83** are secured to the accessory **81** at spaced apart locations, such that an accessory tunnel segment **87** is formed between the accessory **81**

and the accessory webbing element **83** between each secured location of the accessory webbing element **83**. Each of the accessory tunnel segments **87** is formed substantially perpendicular to a longitudinal direction of the accessory webbing elements **83**.

[0009] When the accessory **81** is placed adjacent the carrier material **12** such that the accessory webbing elements **83** are within the spaces between the spaced apart carrier webbing elements **23** (and the carrier webbing elements **23** are within the spaces between the spaced apart accessory webbing elements **83**) and corresponding tunnel segments **27** and accessory tunnel segments **87** are aligned, a strap or coupling element may be interwoven between the aligned tunnel segments **27** and accessory tunnel segments **87** (alternating between horizontal carrier webbing element **23** portions on the host or carrier material **12** and horizontal webbing portions on the accessory **81**) to removably attach the accessory **81** to the carrier material **12**.

[0010] Thus, through the use of a MOLLE or MOLLE-type system, an accessory **81** may be mounted to a variety of carrier materials **12**. Likewise, if a particular carrier material **12** includes a MOLLE compatible system, a variety of accessories may be interchangeably mounted to the platform to accommodate a variety of desired configurations.

[0011] MOLLE compatible systems allow, for example, various pouch arrangements to be specifically tailored to a desired configuration and then reconfigured, if desired. Various desired pouches, pockets, and accessories can be added and undesired or unnecessary pouches, pockets, or accessories can be removed.

[0012] Any discussion of documents, acts, materials, devices, articles, or the like, which has been included in the present specification is not to be taken as an admission that any or all of these matters form part of the prior art base or were common general knowledge in the field relevant to the present disclosure as it existed before the priority date of each claim of this application.

[0013] However, the typical "MOLLE-compatible" or "MOLLE" system arrangement has various shortcomings. For example, known "MOLLE-compatible" or "MOLLE" systems only allow for attachment of accessories in a single orientation relative to the carrier webbing elements. In most applications, this results in only vertical attachment of accessories to the MOLLE system, i.e., attachment perpendicular to the longitudinal axis, A_L , of the carrier webbing elements.

[0014] In various exemplary, non-limiting embodiments, the modular attachment aperture array of the presently disclosed systems, methods, and/or apparatuses provides an aperture array layer that allows MOLLE-compatible or similar accessories to be attached or coupled to the aperture array layer in a vertical, horizontal, oblique, or diagonal manner, relative to a row, column, or other pattern of spaced apart array apertures.

[0015] In various exemplary, nonlimiting embodiments, the modular attachment aperture array of the

present disclosure comprises at least some of a portion of carrier material; and an aperture array layer, wherein the aperture array layer comprises a plurality of spaced apart array apertures, wherein each array aperture is formed of two substantially equal length, substantially parallel sides, an arcuate side joining respective upper terminal ends of the substantially parallel sides, and an arcuate side joining respective lower terminal ends of the substantially parallel sides, wherein each of the array apertures is formed through the aperture array layer, and wherein the array apertures are arranged in a repeating sequence of spaced rows and spaced columns, and wherein the aperture array layer is at least partially attached or coupled to at least a portion of the carrier material.

[0016] In certain exemplary, nonlimiting embodiments, the plurality of spaced apart array apertures are arranged in a repeating sequence of equally spaced rows of the array apertures and equally spaced columns of the array apertures.

[0017] In certain exemplary, nonlimiting embodiments, aperture array tunnel segments are created between adjacent array apertures.

[0018] In certain exemplary, nonlimiting embodiments, aperture array tunnel segments are created between vertically adjacent array apertures, between horizontally adjacent array apertures, between obliquely adjacent array apertures, and/or between diagonally adjacent array apertures.

[0019] In certain exemplary, nonlimiting embodiments, each of the array apertures is defined by one or more continuous edge portions.

[0020] In certain exemplary, nonlimiting embodiments, each adjacent column of spaced apart array apertures is offset such that at least edge portions or proximate centers of adjacent array apertures are offset by approximately $\pm 33^\circ$.

[0021] In certain exemplary, nonlimiting embodiments, each column of spaced apart array apertures at least partially overlaps an adjacent column of spaced apart array apertures.

[0022] In certain exemplary, nonlimiting embodiments, each array aperture is separated from each other array aperture by a distance that is less than a width of each array aperture.

[0023] In certain exemplary, nonlimiting embodiments, the aperture array layer comprises chlorosulfonated polyethylene (CSPE) synthetic rubber (CSM).

[0024] In certain exemplary, nonlimiting embodiments, the aperture array layer comprises a portion of Hypalon fabric or a nylon laminate.

[0025] In various exemplary, nonlimiting embodiments, the modular attachment aperture array of the present disclosure comprises at least some of an aperture array layer, wherein the aperture array layer comprises a plurality of spaced apart array apertures, wherein each array aperture is formed of two substantially equal length, substantially parallel side portions, an upper arcuate side joining respective upper terminal ends of the substantially parallel side portions, and a lower arcuate side joining respective lower terminal ends of the substantially parallel side portions, wherein each of the array apertures is formed through at least a portion of the aperture array layer, and wherein the array apertures are arranged in a repeating sequence of spaced rows and spaced columns, and wherein the aperture array layer is at least partially attached or coupled to at least a portion of the carrier material.

cuate side joining respective upper terminal ends of the substantially parallel side portions, and a lower arcuate side joining respective lower terminal ends of the substantially parallel side portions, wherein each of the array apertures is formed through at least a portion of the aperture array layer, and wherein the array apertures are arranged in a repeating sequence of spaced rows and spaced columns, and wherein the aperture array layer is at least partially attached or coupled to at least a portion of the carrier material.

[0026] In certain exemplary, nonlimiting embodiments, the aperture array layer is at least partially attached or coupled to at least a portion of a carrier material.

[0027] In various exemplary, nonlimiting embodiments, the modular attachment aperture array of the present disclosure comprises at least some of an aperture array layer, wherein the aperture array layer comprises a plurality of spaced apart array apertures, wherein the array apertures are formed as substantially elongated oval shaped array apertures arranged in a repeating sequence of equally spaced rows of the array apertures and equally spaced columns of the array apertures.

[0028] Accordingly, the presently disclosed systems, methods, and/or apparatuses separately and optionally provide a modular attachment aperture array that allows a user to readily attach MOLLE-compatible or similar accessories to the aperture array layer in a vertical, horizontal, oblique, or diagonal manner.

[0029] The presently disclosed systems, methods, and/or apparatuses separately and optionally provide a modular attachment aperture array that allows a user to attach an accessory to the aperture array layer by interweaving an accessory coupling element between aligned aperture array tunnel segments and accessory tunnel segments to removably attach the accessory to the aperture array layer.

[0030] These and other aspects, features, and advantages of the presently disclosed systems, methods, and/or apparatuses are described in or are apparent from the following detailed description of the exemplary, non-limiting embodiments of the presently disclosed systems, methods, and/or apparatuses and the accompanying figures. Other aspects and features of embodiments of the presently disclosed systems, methods, and/or apparatuses will become apparent to those of ordinary skill in the art upon reviewing the following description of specific, exemplary embodiments of the presently disclosed systems, methods, and/or apparatuses in concert with the figures.

[0031] While features of the presently disclosed systems, methods, and/or apparatuses may be discussed relative to certain embodiments and figures, all embodiments of the presently disclosed systems, methods, and/or apparatuses can include one or more of the features discussed herein. Further, while one or more embodiments may be discussed as having certain advantageous features, one or more of such features may also be used with the various embodiments of the systems,

methods, and/or apparatuses discussed herein. In similar fashion, while exemplary embodiments may be discussed below as device, system, or method embodiments, it is to be understood that such exemplary embodiments can be implemented in various devices, systems, and methods of the presently disclosed systems, methods, and/or apparatuses.

[0032] Any benefits, advantages, or solutions to problems that are described herein with regard to specific embodiments are not intended to be construed as a critical, required, or essential feature(s) or element(s) of the presently disclosed systems, methods, and/or apparatuses or the claims.

[0033] As required, detailed exemplary embodiments of the presently disclosed systems, methods, and/or apparatuses are disclosed herein; however, it is to be understood that the disclosed embodiments are merely exemplary of the presently disclosed systems, methods, and/or apparatuses that may be embodied in various and alternative forms, within the scope of the presently disclosed systems, methods, and/or apparatuses. The figures are not necessarily to scale; some features may be exaggerated or minimized to illustrate details of particular components. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to employ the presently disclosed systems, methods, and/or apparatuses.

[0034] The exemplary embodiments of the presently disclosed systems, methods, and/or apparatuses will be described in detail, with reference to the following figures, wherein like reference numerals refer to like parts throughout the several views, and wherein:

FIG. 1 illustrates a portion of a known MOLLE compatible carrier portion attached or coupled to a carrier material;

FIG. 2 illustrates a MOLLE-compatible accessory being attached or coupled to a portion of a known MOLLE compatible carrier portion;

FIG. 3 illustrates an exemplary embodiment of the modular attachment aperture array attached or coupled to a carrier material, according to the presently disclosed systems, methods, and/or apparatuses;

FIG. 4 illustrates a more detailed view of an exemplary embodiment of the modular attachment aperture array, wherein the modular attachment aperture array comprises substantially octagonally shaped array apertures, arranged according to an exemplary embodiment of the presently disclosed systems, methods, and/or apparatuses;

FIG. 5 illustrates a more detailed view of the interaction between the aperture array layer of the modular attachment aperture array and the accessory coupling element of an exemplary accessory, according to the presently disclosed systems, methods, and/or apparatuses;

FIG. 6 illustrates an exemplary accessory attached or coupled to the aperture array layer of the modular attachment aperture array, according to the presently disclosed systems, methods, and/or apparatuses; **FIG. 7** illustrates a more detailed view of the interaction between the aperture array layer of the modular attachment aperture array and the accessory coupling element of an exemplary accessory, according to the presently disclosed systems, methods, and/or apparatuses;

FIG. 8 illustrates a more detailed view of the interaction between the aperture array layer of the modular attachment aperture array, the accessory coupling element of an exemplary accessory, and the accessory webbing element of the exemplary accessory, according to the presently disclosed systems, methods, and/or apparatuses;

FIG. 9 illustrates an exemplary accessory attached or coupled to the aperture array layer of the modular attachment aperture array, according to the presently disclosed systems, methods, and/or apparatuses;

FIG. 10 illustrates a more detailed view of the interaction between the aperture array layer of the modular attachment aperture array and the accessory coupling element of an exemplary accessory, according to the presently disclosed systems, methods, and/or apparatuses;

FIG. 11 illustrates a more detailed view of the interaction between the aperture array layer of the modular attachment aperture array and the accessory coupling element of an exemplary accessory, according to the presently disclosed systems, methods, and/or apparatuses;

FIG. 12 illustrates an exemplary accessory attached or coupled to the aperture array layer of the modular attachment aperture array, according to the presently disclosed systems, methods, and/or apparatuses;

FIG. 13 illustrates an exemplary embodiment of the modular attachment aperture array attached or coupled to a carrier material, wherein the modular attachment aperture array comprises substantially hexagonally shaped array apertures, arranged according to an exemplary embodiment of the presently disclosed systems, methods, and/or apparatuses;

FIG. 14 illustrates an exemplary embodiment of the modular attachment aperture array attached or coupled to a carrier material, wherein the modular attachment aperture array comprises substantially circular shaped array apertures, arranged according to an exemplary embodiment of the presently disclosed systems, methods, and/or apparatuses;

FIG. 15 illustrates an exemplary embodiment of the modular attachment aperture array attached or coupled to a carrier material, wherein the modular attachment aperture array comprises substantially octagonally shaped array apertures, arranged according to an exemplary embodiment of the presently disclosed systems, methods, and/or apparatuses;

5

10

15

20

25

30

35

40

45

50

reference to various exemplary embodiments of a modular attachment aperture array according to the presently

[0035] For simplicity and clarification, the design factors and operating principles of the modular attachment aperture array according to the presently disclosed systems, methods, and/or apparatuses are explained with reference to various exemplary embodiments of a modular attachment aperture array according to the presently

disclosed systems, methods, and/or apparatuses. The basic explanation of the design factors and operating principles of the modular attachment aperture array is applicable for the understanding, design, and operation of the modular attachment aperture array of the presently disclosed systems, methods, and/or apparatuses. It should be appreciated that the modular attachment aperture array can be adapted to many applications where a modular attachment aperture array can be used.

[0036] As used herein, the word "may" is meant to convey a permissive sense (i.e., meaning "having the potential to"), rather than a mandatory sense (i.e., meaning "must"). Unless stated otherwise, terms such as "first" and "second" are used to arbitrarily distinguish between the exemplary embodiments and/or elements such terms describe. Thus, these terms are not necessarily intended to indicate temporal or other prioritization of such exemplary embodiments and/or elements.

[0037] As used herein, and unless the context dictates otherwise, the term "coupled" is intended to include both direct coupling (in which two elements that are coupled to each other contact each other) and indirect coupling (in which at least one additional element is located between the two elements). The term coupled, as used herein, is defined as connected, although not necessarily directly, and not necessarily mechanically. The terms "a" and "an" are defined as one or more unless stated otherwise.

[0038] Throughout this application, the terms "comprise" (and any form of comprise, such as "comprises" and "comprising"), "have" (and any form of have, such as "has" and "having"), "include", (and any form of include, such as "includes" and "including") and "contain" (and any form of contain, such as "contains" and "containing") are used as open-ended linking verbs. It will be understood that these terms are meant to imply the inclusion of a stated element, integer, step, or group of elements, integers, or steps, but not the exclusion of any other element, integer, step, or group of elements, integers, or steps. As a result, a system, method, or apparatus that "comprises", "has", "includes", or "contains" one or more elements possesses those one or more elements but is not limited to possessing only those one or more elements. Similarly, a method or process that "comprises", "has", "includes" or "contains" one or more operations possesses those one or more operations but is not limited to possessing only those one or more operations.

[0039] It should also be appreciated that the terms "modular attachment aperture array", "aperture array layer", "carrier material", and "accessory" are used for basic explanation and understanding of the operation of the systems, methods, and apparatuses of the presently disclosed systems, methods, and/or apparatuses. Therefore, the terms "modular attachment aperture array", "aperture array layer", "carrier material", and "accessory" are not to be construed as limiting the systems, methods, and apparatuses of the presently disclosed systems,

methods, and/or apparatuses.

[0040] For simplicity and clarification, the modular attachment aperture array of the presently disclosed systems, methods, and/or apparatuses will be shown and/or described as being used in conjunction with a side portion or surface of an exemplary bag or pack being utilized as an exemplary carrier material. However, it should be appreciated that these are merely exemplary embodiments of the modular attachment aperture array and are not to be construed as limiting the presently disclosed systems, methods, and/or apparatuses. Thus, the modular attachment aperture array of the presently disclosed systems, methods, and/or apparatuses may be utilized in conjunction with any object or device.

[0041] Additionally, the modular attachment aperture array of the presently disclosed systems, methods, and/or apparatuses will be shown and described as being used in conjunction with a compatible accessory **81**, having at least one accessory webbing element **83**, and at least one accessory coupling element **88**. It should be appreciated that the compatible accessory **81** is merely an exemplary accessory and that any MOLLE compatible or similar accessory may be utilized in conjunction with the modular attachment aperture array of the present disclosure.

[0042] Turning now to the appended drawing figures, **FIGS. 1-2** illustrate certain elements and/or aspects of a portion of a known MOLLE compatible carrier portion **10** attached or coupled to a carrier material **12** and a MOLLE-compatible accessory **81** being attached or coupled to a portion of a known MOLLE compatible carrier portion **10**, **FIGS. 3-19** illustrate certain elements and/or aspects of an exemplary embodiment of the modular attachment aperture array **100**, **FIGS. 20-22** illustrate certain elements and/or aspects of an exemplary embodiment of the modular attachment aperture array **100**, and **FIGS. 23-37** illustrate certain elements and/or aspects of an exemplary embodiment of the modular attachment aperture array **300**, according to the presently disclosed systems, methods, and/or apparatuses.

[0043] In certain illustrative, non-limiting embodiment(s) of the presently disclosed systems, methods, and/or apparatuses, as illustrated in **FIGS. 3-19**, the modular attachment aperture array **100** comprises at least some of an aperture array layer **110** having a plurality of spaced apart matrix array apertures **120** formed there-through.

[0044] In certain exemplary embodiments, the aperture array layer **110** is formed of a portion of a fabric-type or other material, such as, for example, chlorosulfonated polyethylene (CSPE) synthetic rubber (CSM). In certain exemplary embodiments, the aperture array layer **110** is formed of a portion of Hypalon fabric or a nylon laminate. However, the present disclosure is not so limited. For example, in certain exemplary embodiments, the aperture array layer **110** may be formed of a rigid material, a semi-rigid material, or a substantially flexible material.

[0045] In various exemplary, non-limiting embodi-

ments, all or portions of the aperture array layer **110** may be made of any fabric or other material, such as, for example, woven fabrics, canvas, acrylics, sheet fabrics, films, nylon, spandex, vinyl, Polyvinyl Chloride (PVC), neoprene, or the like. Alternatively, all or portions of the aperture array layer **110** may be formed from multiple, similar or dissimilar materials. In various exemplary, non-limiting embodiments, the aperture array layer **110** may be water-resistant or may include a cushion material.

[0046] As a further example, in certain exemplary embodiments, the aperture array layer **110** may be formed of a substantially rigid material, such as plastic, having an appropriate, workable thickness. Alternate materials of construction of the aperture array layer **110** may include one or more of the following: steel, stainless steel, aluminum, titanium, polytetrafluoroethylene, and/or other metals, as well as various alloys and composites thereof, glass-hardened polymers, polymeric composites, polymer or fiber reinforced metals, carbon fiber or glass fiber composites, continuous fibers in combination with thermoset and thermoplastic resins, chopped glass or carbon fibers used for injection molding compounds, laminate glass or carbon fiber, epoxy laminates, woven glass fiber laminates, impregnate fibers, polyester resins, epoxy resins, phenolic resins, polyimide resins, cyanate resins, high-strength plastics, nylon, glass, or polymer fiber reinforced plastics, thermoform and/or thermoset materials, and/or various combinations of the foregoing. Thus, it should be understood that the material or materials used to form the aperture array layer **110** is a design choice based on the desired appearance and functionality of the aperture array layer **110**.

[0047] It should be appreciated that the terms fabric and material are to be given their broadest meanings and that the particular fabric(s) or material(s) used to form the aperture array layer **110** is a design choice based on the desired appearance and/or functionality of the modular attachment aperture array **100**. In general, the material used to form the aperture array layer **110** is selected for its ability to allow a MOLLE-type accessory to be attached or coupled thereto.

[0048] The modular attachment aperture array **100** of the present disclosure is operable with as few as two matrix array apertures **120**. Thus, the size and shape of the aperture array layer **110** is a design choice, based upon, for example, the size and shape of the carrier material **12** or portion of carrier material **12** that is desired to potentially accept attachment or coupling of accessories.

[0049] In various exemplary embodiments, as illustrated in **FIG. 4**, the matrix array apertures **120** are generally formed as apertures through the aperture array layer **110**. Each matrix array aperture **120** is defined by one or more continuous edges. In various exemplary embodiments, each matrix array aperture **120** may optionally be formed in the shape of an octagon. However, it should be appreciated that each of the matrix array apertures **120** may generally be formed in the shape of a triangle, a square,

a rectangle, a pentagon, a hexagon (as illustrated in **FIG. 13**), a heptagon, an octagon (as illustrated in **FIGS. 15-19**), a nanogon, a decagon, a pentadecagon, an icosagon, a circle (as illustrated in **FIG. 14**), an oval, a dumbbell/barbell shape, or any other desired shape or configuration. Thus, it should be appreciated that the size and shape of each of the matrix array apertures **120** is a design choice based upon the desired functionality and/or appearance of the modular attachment aperture array **100** and/or the aperture array layer **110**.

[0050] The size or diameter of each matrix array aperture **120** is also a design choice. In certain exemplary embodiments, the size or diameter of each matrix array aperture **120** is influenced or dictated by the width of the accessory coupling element of a compatible accessory, such as, for example, the accessory coupling element **88** of a compatible accessory **81**. For example, if the accessory coupling element **88** has a width of approximately 1 inch, the size or diameter of each matrix array aperture **120** may optionally be approximately 1 inch, so as to allow the accessory coupling element **88** to be fitted within and interwoven between two or more matrix array apertures **120**. Alternatively, the size or diameter of each matrix array aperture **120** may be created such that only certain accessories are compatible with the aperture array layer **110** and the modular attachment aperture array **100**.

[0051] The matrix array apertures **120** are arranged in a repeating or semi-repeating series or sequence of spaced apart, repeating patterns. In various exemplary embodiments, the matrix array apertures **120** are arranged in a repeating or semi-repeating series or sequence of spaced apart rows **113** and columns **112**. In various exemplary embodiments, the matrix array apertures **120** are arranged in a series of equally spaced rows **113** and equally spaced columns **112**.

[0052] In certain exemplary embodiments, each of the rows **113** is spaced at a distance that is the same as the spacing between each of the columns **112**. Alternatively, the spacing between each of the rows **113** is greater than or less than the spacing between each of the columns **112**.

[0053] In various exemplary embodiments, the spacing between either edges or proximate centers of adjacent matrix array apertures **120** (whether vertically, horizontally, obliquely, or diagonally adjacent) is influenced or dictated by the width of the accessory webbing element **83** of a compatible accessory **81**. For example, if the accessory webbing element **83** has a width of approximately 1 inch, the spacing between either edges or proximate centers of adjacent matrix array apertures **120** may optionally be approximately 1 inch, so as to allow the accessory webbing element(s) **83** to be appropriately aligned between every other matrix array aperture **120** in a vertical, horizontal, oblique, or diagonal direction. Alternatively, the spacing between either edges or proximate centers of adjacent matrix array apertures **120** may be created such that only certain accessories are com-

patible with the aperture array layer **110** and the modular attachment aperture array **100**.

[0054] It should be appreciated that two or more adjacent matrix array apertures **120** may comprise a row **113** and two or more adjacent matrix array apertures **120** may comprise a column **112**. Thus, it should be appreciated that the number of matrix array apertures **120** formed in the aperture array layer **110** is a design choice based upon the desired size and/or functionality of the aperture array layer **110**.

[0055] In various exemplary, nonlimiting embodiments, each adjacent row **113** and/or column **112** of spaced apart matrix array apertures **120** is offset such that either edges or proximate centers of adjacent matrix array apertures **120** are offset by approximately $\pm 45^\circ$ (as illustrated in **FIG. 4**) or approximately $\pm 90^\circ$ (as illustrated in **FIG. 18**). If for example, either edges or proximate centers of adjacent matrix array apertures **120** are offset by $\pm 45^\circ$ or $\pm 90^\circ$, an attached or coupled accessory **81** can be attached or coupled at least at $\pm 0^\circ$, $\pm 90^\circ$, or $\pm 45^\circ$. Thus, it should be appreciated that the offset of adjacent rows **113** and/or columns **112** dictates the angle of oblique attachment of accessories.

[0056] In certain exemplary, nonlimiting embodiments, each matrix array aperture **120** is separated from each other matrix array aperture **120** by a distance that is equal to or greater than a width of each matrix array aperture **120**.

[0057] By arranging the matrix array apertures **120** in a repeating or semi-repeating series or sequence, aperture array tunnel segments **135** are created between adjacent matrix array apertures **120** (whether vertically, horizontally, obliquely, or diagonally adjacent).

[0058] It is possible for the matrix array layer **110** to operate as a stand-alone element, such as, for example, a sheet of matrix array layer **110** material, to which compatible accessories may be attached or coupled. However, in various exemplary embodiments, the matrix array layer **110** is at least partially attached or coupled to at least a portion of a carrier or carrier material, such as, for example, a carrier material **12**. Thus, the matrix array layer **110** may be at least partially attached or coupled to an exemplary carrier (such as, for example, exemplary carrier material **12**), for example, an article of clothing, a vest, a plate carrier, a backpack, a pack, a bag, a platform, or another flexible, semi-rigid, or rigid carrier.

[0059] As illustrated, for example, in **FIGS. 3** and **5-12**, the matrix array layer **110** is illustrated as comprising a somewhat rectangular portion of matrix array layer **110** material that is at least partially attached or coupled to an exemplary bag. As illustrated, the matrix array layer **110** is attached or coupled to a portion of the exemplary bag by matrix array layer attachment elements **130**, such as stitching proximate a perimeter of the matrix array layer **110**. The matrix array layer **110** may then optionally be further attached or coupled to the carrier material **12**, via additional matrix array layer attachment elements **130**. The matrix array layer attachment elements **130** are

spaced apart, as necessary or desirable, in order to further secure, attach, or couple the matrix array layer **110** to the carrier material **12**. The number and placement of additional matrix array layer attachment elements **130** is a design choice based upon the desired level of securement of the matrix array layer **110** to the carrier material **12** and/or to further ensure that the matrix array layer **110** will not separate or pull away from the carrier material **12**, particularly if accessories are attached or coupled to the matrix array layer **110**.

[0060] In certain exemplary embodiments, the matrix array layer attachment elements **130** comprise stitching. Alternatively, the matrix array layer **110** may be attached or coupled to the carrier material **12** at one or more matrix array layer attachment elements **130** via adhesive bonding, welding, screws, rivets, pins, mating hook and loop portions, snap or releasable fasteners, or other known or later developed means or methods for permanently or releasably attaching or coupling the matrix array layer **110** to the carrier material **12**. The one or more matrix array layer attachment elements **130** may be formed or positioned proximate a perimeter of the matrix array layer **110** or in one or more areas located within the one or more matrix array layers **110**.

[0061] In addition to the variability of size and shape of the matrix array layer **110**, the orientation of the matrix array layer **110**, relative to the carrier material **12**, is also a design choice. Thus, as illustrated in **FIGS. 3** and **5-12**, the matrix array layer **110** is illustrated as being attached or coupled to the carrier material **12**, such that the rows **113** of matrix array apertures **120** are substantially parallel to the longitudinal axis, along the length, of the exemplary bag, while the columns **112** of matrix array apertures **120** are substantially perpendicular to the longitudinal axis of the exemplary bag. It should be appreciated that this is merely exemplary and the matrix array layer **110** may be attached at any desired angular or rotational orientation relative to a surface of the bag or carrier material **12**.

[0062] The portions of material of the matrix array layer **110** between adjacent matrix array apertures **120** form matrix array tunnel segments **135**. If the matrix array layer **110** is attached to a carrier material **12**, the matrix array tunnel segments **135** are formed between the matrix array layer **110** and the surface of the carrier material **12**. The matrix array tunnel segments **135** provide areas for securing the accessory coupling element **88** of an accessory **81** to the matrix array layer **110**. In this manner, an accessory coupling element **88** may be interwoven between the aligned matrix array tunnel segments **135** to removably attach the accessory **81** to the carrier material **12**.

[0063] During attachment of an exemplary accessory **81**, as illustrated most clearly in **FIGS. 5-12**, the accessory **81** is aligned with the matrix array layer **110** in a desired orientation. As illustrated in **FIGS. 5-12**, the accessory **81** may optionally be aligned with the matrix array layer **110** in a generally vertical manner, as illustrated in

FIGS. 7-9, the accessory **81** may optionally be aligned with the matrix array layer **110** in a generally horizontal manner, or as illustrated in **FIGS. 10-12**, the accessory **81** may optionally be aligned with the matrix array layer **110** in a generally oblique or diagonal manner. It should be understood that these orientations are relative to the orientation of the matrix array layer **110** and the orientation of the matrix array layer **110** relative to the carrier material **12**.

[0064] As further illustrated, the exemplary accessory **81** includes one or more substantially parallel, spaced apart accessory webbing elements **83**. If more than one accessory webbing element **83** is included, the accessory webbing elements **83** are spaced apart so as to correspond to the spaces between the spaced apart matrix array apertures **120**.

[0065] When the accessory **81** is placed adjacent the matrix array layer **110** such that at least a portion of the accessory webbing elements **83** are within a portion of the spaces between the spaced apart matrix array apertures **120** (and at least a portion of the matrix array apertures **120** are within the spaces between the spaced apart accessory webbing elements **83**) and corresponding matrix array tunnel segments **135** and accessory tunnel segments **87** are aligned, the accessory coupling element **88** may be interwoven between the aligned matrix array tunnel segments **135** and accessory tunnel segments **87** (alternating between adjacent matrix array apertures **120** of the matrix array layer **110** and accessory webbing elements **83** on the accessory **81**) to removably attach the accessory **81** to the matrix array layer **110**.

[0066] Thus, an accessory **81** may be mounted to the matrix array layer **110** in a variety of orientations. Likewise, if a particular carrier material **12** includes a matrix array layer **110**, a variety of accessories may be interchangeably mounted to the matrix array layer **110** to accommodate a variety of desired configurations.

[0067] It should be appreciated that a more detailed explanation of the instructions regarding how to interweave the accessory coupling element **88** between the matrix array apertures **120** and accessory webbing elements **83** is not provided herein because, while the matrix array layer **110** provides more orientation options and other features, accessories are generally attached to the matrix array layer **110** in a manner similar to the manner in which accessories are attached to a portion of MOLLE webbing. Therefore, it is believed that the level of description provided herein is sufficient to enable one of ordinary skill in the art to understand and practice the systems, methods, and apparatuses, as described.

[0068] **FIGS. 13-19** illustrate various exemplary embodiments of a matrix array layer **110** and a modular attachment matrix array **100**, according to the present disclosure. As illustrated, the modular attachment matrix array **100** includes a matrix array layer **110** having two or more matrix array apertures **120** formed therethrough at spaced apart locations and arranged in one or more rows **113** and/or columns **112**. The matrix array layer **110** is

at least partially attached or coupled to a carrier material **12** and tunnel segments **135** are formed between adjacent matrix array apertures **120**.

[0069] It should be understood that each of these elements corresponds to and operates similarly to the modular attachment matrix array **100**, matrix array layer **110**, matrix array apertures **120**, and tunnel segments **135**, as described above with reference to the modular attachment matrix array **100** of **FIGS. 3-12**.

[0070] However, **FIG. 13** illustrates an exemplary embodiment of the modular attachment matrix array **100**, wherein the modular attachment matrix array **100** comprises substantially hexagonally shaped matrix array apertures **120**, while **FIG. 14** illustrates an exemplary embodiment of the modular attachment matrix array **100**, wherein the modular attachment matrix array **100** comprises substantially circular shaped matrix array apertures **120**.

[0071] **FIG. 15** illustrates an exemplary embodiment of the modular attachment matrix array **100** attached or coupled to a carrier material **12**. As illustrated, the modular attachment matrix array **100** comprises five substantially octagonally shaped matrix array apertures **120**, arranged or grouped such that exemplary tunnel segments **135** are formed in a relatively horizontal, relatively vertical, and relatively diagonal manner. **FIG. 16** illustrates an exemplary embodiment of the modular attachment matrix array **100** attached or coupled to a carrier material **12**, wherein the modular attachment matrix array **100** comprises a plurality of substantially octagonally shaped matrix array apertures **120**, as illustrated in **FIG. 15**. However, as illustrated in **FIG. 16**, the grouping of five matrix array apertures **120** is expanded to a plurality of arranged matrix array apertures **120**. Therefore, it should be appreciated that the total number of matrix array apertures **120** used to form the modular attachment matrix array **100** of the matrix array layer **110** is a design choice, based upon the desired area that the modular attachment matrix array **100** is to cover, whether attached to a carrier material **12** or as a standalone matrix array layer **110**.

[0072] **FIG. 17** illustrates an exemplary embodiment of the modular attachment matrix array **100** attached or coupled to a carrier material **12**, wherein the modular attachment matrix array **100** comprises four, spaced apart, substantially octagonally shaped matrix array apertures **120**. As illustrated, the positioning of the matrix array apertures **120** still provides relatively horizontal, relatively vertical, and relatively diagonal tunnel segments **135**. It should be appreciated that the arrangement or grouping of matrix array apertures **120**, as illustrated in **FIG. 17**, may be duplicated to create a matrix array layer **110** of any desired size and including any number of desired matrix array apertures **120**, as illustrated, for example, in **FIG. 18**.

[0073] As further illustrated in **FIG. 19**, the arrangement or grouping of matrix array apertures **120** may be applied to the matrix array layer **110** in any desired arrangement. For example, while the matrix array aper-

tures **120** are arranged in a repeating or semi-repeating series or sequence of equally spaced rows **113** and equally spaced columns **112**, the length of each row **113** or column **112** may be varied to produce a desired arrangement of matrix array apertures **120**.

[0074] As further illustrated in in **FIG. 19**, the arrangement or grouping of matrix array apertures **120** includes a number of partial matrix array apertures **120'**. Each partial matrix array aperture **120'** is formed of a partial or incomplete matrix array aperture. While the partial matrix array apertures **120'** are each illustrated as being positioned at a beginning or end of a given row **113**, it should be appreciated that partial matrix array apertures **120'** may optionally be included at a beginning or an end of one or more rows **113**, one or more columns **112**, or within a given row **113** or column **112**.

[0075] **FIGS. 20-22** illustrate various exemplary embodiments of an aperture array layer **110** and a modular attachment aperture array **100**, according to the present disclosure. As illustrated, the modular attachment aperture array **100** includes an aperture array layer **110** having two or more array apertures **220** formed therethrough at spaced apart locations and arranged in one or more rows **113** and/or columns **112**. The aperture array layer **110** is at least partially attached or coupled to a carrier material **12** and tunnel segments **135** are formed between adjacent array apertures **220**.

[0076] It should be understood that each of these elements corresponds to and operates similarly to the modular attachment aperture array **100**, aperture array layer **110**, array apertures **120**, and tunnel segments **135**, as described herein with reference to the modular attachment aperture array **100** of **FIGS. 3-19**.

[0077] However, **FIGS. 20-22**, illustrate an exemplary embodiment of an array aperture **220** that can be utilized in place of an array aperture **120** to form the modular attachment aperture array **100** and/or the aperture array layer **110**. As illustrated, the array aperture **220** is formed of two substantially equal length, substantially parallel side portions or sides **223**. It should be appreciated that the length or spacing, S_w , between of each of the side portions or sides **223** is a design choice based upon the desired functionality and/or appearance of the array aperture **220**.

[0078] An arcuate side **225** joins respective upper terminal ends of each of the side portions or sides **223**, while an arcuate side **225** joins respective lower terminal ends of each of the sides **223**. For example, an upper arcuate side **225** joins respective upper terminal ends of each of the sides **223**, while a lower arcuate side **225** joins respective lower terminal ends of each of the sides **223**.

[0079] In various exemplary embodiments, the height or spacing, S_H , between apexes of each of the sides **223** is equal to or substantially equal to the length or spacing, S_w , between of each of the sides **223**. However, it should be appreciated that the height or spacing, S_H , between apexes of each of the sides **223** is a design choice based upon the desired functionality and/or appearance of the

array aperture **220**. Thus, the angle of each arc forming each arcuate side **225** may be formed based upon the desired functionality and/or appearance of each array aperture **220**.

[0080] Each array aperture **220** is generally formed as an aperture or hole through the aperture array layer **110**. It is possible for the aperture array layer **110** to operate as a stand-alone element, such as, for example, a sheet of aperture array layer **110** material, to which compatible accessories may be attached or coupled. However, in various exemplary embodiments, the aperture array layer **110** is at least partially attached or coupled to at least a portion of a carrier or carrier material, such as, for example, a carrier material **12**. Thus, the aperture array layer **110** may be at least partially attached or coupled to an exemplary carrier, for example, an article of clothing, a vest, a plate carrier, a backpack, a pack, a bag, a platform, or another flexible, semi-rigid, or rigid carrier.

[0081] The overall size of each array aperture **220** is also a design choice. In certain exemplary embodiments, the size of each array aperture **220** is influenced or dictated by the width of the accessory coupling element of a compatible accessory, such as, for example, the accessory coupling element **88** of a compatible accessory **81**. For example, if the accessory coupling element **88** has a width of approximately 1 inch, the length or spacing, S_w , between of each of the sides **223** and the height or spacing, S_H , between apexes of each of the sides **223** may optionally be approximately 1 inch, so as to allow the accessory coupling element **88** to be fitted within and interwoven between two or more array apertures **220**. Alternatively, the length or spacing, S_w , between of each of the sides **223** and the height or spacing, S_H , between apexes of each of the sides **223** may be such that only certain accessories are compatible with the aperture array layer **110** and the modular attachment aperture array **100**.

[0082] The array apertures **220** are arranged in a repeating or semi-repeating series or sequence of spaced apart, repeating patterns. In various exemplary embodiments, the array apertures **220** are arranged in a repeating or semi-repeating series or sequence of spaced apart rows **113** and columns **112**. In various exemplary embodiments, the array apertures **220** are arranged in a series of equally spaced rows **113** and equally spaced columns **112**.

[0083] In certain exemplary embodiments, each of the rows **113** is spaced at a distance that is the same as the spacing between each of the columns **112**. Alternatively, the spacing between each of the rows **113** is greater than or less than the spacing between each of the columns **112**.

[0084] In various exemplary embodiments, the spacing between either edges or proximate centers of adjacent array apertures **220** (whether vertically, horizontally, obliquely, or diagonally adjacent) is influenced or dictated by the width of the accessory webbing element **83** of a compatible accessory **81**. For example, if the accessory

webbing element **83** has a width of approximately 1 inch, the spacing between either edges or proximate centers of adjacent array apertures **220** may optionally be approximately 1 inch, so as to allow the accessory webbing element(s) **83** to be appropriately aligned between every other array aperture **220** in a vertical, horizontal, oblique, or diagonal direction. Alternatively, the spacing between either edges or proximate centers of adjacent array apertures **220** may be created such that only certain accessories are compatible with the aperture array layer **110** and the modular attachment aperture array **100**.

[0085] It should be appreciated that two or more adjacent array apertures **220** may comprise a row **113** and two or more adjacent array apertures **220** may comprise a column **112**. Thus, it should be appreciated that the number of array apertures **220** formed in the aperture array layer **110** is a design choice based upon the desired size and/or functionality of the aperture array layer **110**.

[0086] In various exemplary, nonlimiting embodiments, each adjacent row **113** and/or column **112** of spaced apart array apertures **220** is offset such that either edges or proximate centers of adjacent array apertures **220** are offset by approximately $\pm 45^\circ$ or approximately $\pm 90^\circ$. If for example, either edges or proximate centers of adjacent array apertures **220** are offset by $\pm 45^\circ$ or $\pm 90^\circ$, an attached or coupled accessory **81** may be attached or coupled at least at $\pm 0^\circ$, $\pm 90^\circ$, or $\pm 45^\circ$. Thus, it should be appreciated that the offset of adjacent rows **113** and/or columns **112** dictates the angle of oblique attachment of accessories.

[0087] In certain exemplary, nonlimiting embodiments, each array aperture **220** may be separated from each other array aperture **220** by a distance that is equal to or greater than a width of each array aperture **220**. Alternatively, each array aperture **220** may be separated from each other array aperture **220** by a distance that is equal to or greater than a width of each array aperture **220**.

[0088] By arranging the array apertures **220** in a repeating or semi-repeating series or sequence, aperture array tunnel segments **135** are created between adjacent array apertures **220** (whether vertically, horizontally, obliquely, acutely, or diagonally adjacent).

[0089] In various exemplary, nonlimiting embodiments, the aperture array layer **110** comprises a portion of aperture array layer **110** material that is at least partially attached or coupled to a carrier material **12** by aperture array layer attachment elements (not illustrated), such as stitching proximate a perimeter of the aperture array layer **110**. The aperture array layer **110** may optionally be attached or coupled or further attached or coupled to the carrier material **12**, via additional aperture array layer attachment elements (not illustrated). The aperture array layer attachment elements (not illustrated) may be spaced apart, as necessary or desirable, in order to further secure, attach, or couple the aperture array layer **110** to the carrier material **12**. The number and placement of additional aperture array layer attachment elements (not illustrated) is a design choice based upon the desired

level of securement of the aperture array layer **110** to the carrier material **12** and/or to further ensure that the aperture array layer **110** will not separate or pull away from the carrier material **12**, particularly if accessories are attached or coupled to the aperture array layer **110**.

[0090] In certain exemplary embodiments, the aperture array layer attachment elements (not illustrated) comprise stitching. Alternatively, the aperture array layer **110** may be attached or coupled to the carrier material **12** at one or more aperture array layer attachment elements (not illustrated) via adhesive bonding, welding, screws, rivets, pins, mating hook and loop portions, snap or releasable fasteners, or other known or later developed means or methods for permanently or releasably attaching or coupling the aperture array layer **110** to the carrier material **12**. The one or more aperture array layer attachment elements (not illustrated) may be formed or positioned proximate a perimeter of the aperture array layer **110** or in one or more areas located within the one or more aperture array layers **110**.

[0091] In addition to the variability of size and shape of the aperture array layer **110**, the orientation of the aperture array layer **110**, relative to the carrier material **12**, is also a design choice. Thus, the aperture array layer **110** may optionally be attached or coupled to the carrier material **12**, such that the rows **113** of array apertures **220** are substantially parallel to a longitudinal or other axis, along the length, of the exemplary carrier material **12**, while the columns **112** of array apertures **220** are substantially perpendicular to the longitudinal or other axis of the carrier material **12**. It should be appreciated that this is merely exemplary and the aperture array layer **110** may be attached at any desired angular or rotational orientation relative to the carrier material **12**.

[0092] The portions of material of the aperture array layer **110** between adjacent array apertures **220** form aperture array tunnel segments **135**. If the aperture array layer **110** is attached to a carrier material **12**, the aperture array tunnel segments **135** are formed between at least portions of the aperture array layer **110** and at least portions of the surface of the carrier material **12**. The aperture array tunnel segments **135** provide areas for securing the accessory coupling element **88** of an accessory **81** to the aperture array layer **110**. In this manner, an accessory coupling element **88** may be interwoven between the aligned aperture array tunnel segments **135** to removably attach the accessory **81** to the carrier material **12**.

[0093] During attachment of an exemplary accessory **81**, the accessory **81** is aligned with the aperture array layer **110** in a desired orientation. The accessory **81** may optionally be aligned with the aperture array layer **110** in a generally vertical manner, in a generally horizontal manner, or in a generally oblique or diagonal manner. It should be understood that these orientations are relative to the orientation of the aperture array layer **110** and the orientation of the aperture array layer **110** relative to the carrier material **12**.

[0094] The exemplary accessory **81** may optionally include one or more substantially parallel, spaced apart accessory webbing elements **83**. If more than one accessory webbing element **83** is included, the accessory webbing elements **83** are spaced apart so as to correspond to the spaces between the spaced apart array apertures **220**.

[0095] When the accessory **81** is placed adjacent the aperture array layer **110** such that at least a portion of the accessory webbing elements **83** are within a portion of the spaces between the spaced apart array apertures **220** (and at least a portion of the array apertures **220** are within the spaces between the spaced apart accessory webbing elements **83**) and corresponding aperture array tunnel segments **135** and accessory tunnel segments **87** are aligned, the accessory coupling element **88** may be interwoven between the aligned aperture array tunnel segments **135** and accessory tunnel segments **87** (alternating between adjacent array apertures **220** and/or alternate attachment apertures **121** of the aperture array layer **110** and accessory webbing elements **83** on the accessory **81**) to removably attach the accessory **81** to the aperture array layer **110**.

[0096] Thus, an accessory **81** may be mounted to the aperture array layer **110** in a variety of orientations. Likewise, if a particular carrier material **12** includes an aperture array layer **110**, a variety of accessories may be interchangeably mounted to the aperture array layer **110** to accommodate a variety of desired configurations.

[0097] It should be appreciated that a more detailed explanation of the instructions regarding how to interweave the accessory coupling element **88** between the array apertures **220** and accessory webbing elements **83** is not provided herein because, while the aperture array layer **110** provides more orientation options and other features, accessories are generally attached to the aperture array layer **110** in a manner similar to the manner in which accessories are attached to a portion of MOLLE webbing. Therefore, it is believed that the level of description provided herein is sufficient to enable one of ordinary skill in the art to understand and practice the systems, methods, and apparatuses, as described.

[0098] **FIGS. 23-37** illustrate certain elements and/or aspects of an exemplary embodiment of a modular attachment aperture array **300**, according to the presently disclosed systems, methods, and/or apparatuses.

[0099] In certain illustrative, non-limiting embodiment(s) of the presently disclosed systems, methods, and/or apparatuses, as illustrated in **FIGS. 23-37**, the modular attachment aperture array **300** comprises at least some of an aperture array layer **310** having a plurality of spaced apart array apertures **320** formed there-through, with tunnel segments **335** formed between certain of the spaced apart array apertures **320**, as described herein. The modular attachment aperture array **300** may optionally be at least partially attached or coupled to at least a portion of a carrier or carrier material, such as, for example, a carrier material **12**.

[0100] It should be understood that each of these elements corresponds to and operates similarly to the modular attachment aperture array **100**, aperture array layer **110**, matrix array apertures **120**, and tunnel segments **135**, as described above with reference to the modular attachment aperture array **100** of **FIGS. 3-19**.

[0101] However, **FIGS. 23-37** illustrate an exemplary embodiment of the modular attachment aperture array **300**, wherein each array aperture **320** is formed in the shape of an elongated octagon, truncated oval, or oval.

[0102] In certain exemplary embodiments, the aperture array layer **310** is formed of a portion of a fabric-type or other material, such as, for example, chlorosulfonated polyethylene (CSPE) synthetic rubber (CSM). In certain exemplary embodiments, the aperture array layer **310** is formed of a portion of Hypalon fabric or a nylon laminate. However, the present disclosure is not so limited. For example, in certain exemplary embodiments, the aperture array layer **310** may be formed of a rigid material, a semi-rigid material, or a substantially flexible material.

[0103] In various exemplary, non-limiting embodiments, all or portions of the aperture array layer **310** may be made of any fabric or other material, such as, for example, woven fabrics, canvas, acrylics, sheet fabrics, films, nylon, spandex, vinyl, Polyvinyl Chloride (PVC), neoprene, or the like. Alternatively, all or portions of the aperture array layer **310** may be formed from multiple, similar or dissimilar materials. In various exemplary, non-limiting embodiments, the aperture array layer **310** may be water-resistant or may include a cushion material.

[0104] As a further example, in certain exemplary embodiments, the aperture array layer **310** may be formed of a substantially rigid material, such as plastic, having an appropriate, workable thickness. Alternate materials of construction of the aperture array layer **310** may include one or more of the following: steel, stainless steel, aluminum, titanium, polytetrafluoroethylene, and/or other metals, as well as various alloys and composites thereof, glass-hardened polymers, polymeric composites, polymer or fiber reinforced metals, carbon fiber or glass fiber composites, continuous fibers in combination with thermoset and thermoplastic resins, chopped glass or carbon fibers used for injection molding compounds, laminate glass or carbon fiber, epoxy laminates, woven glass fiber laminates, impregnate fibers, polyester resins, epoxy resins, phenolic resins, polyimide resins, cyanate resins, high-strength plastics, nylon, glass, or polymer fiber reinforced plastics, thermoform and/or thermoset materials, and/or various combinations of the foregoing. Thus, it should be understood that the material or materials used to form the aperture array layer **310** is a design choice based on the desired appearance and functionality of the aperture array layer **310**.

[0105] It should be appreciated that the terms fabric and material are to be given their broadest meanings and that the particular fabric(s) or material(s) used to form the aperture array layer **310** is a design choice based on the desired appearance and/or functionality of the mod-

ular attachment aperture array **300**. In general, the material used to form the aperture array layer **310** is selected for its ability to allow a MOLLE-type accessory to be attached or coupled thereto.

[0106] The modular attachment aperture array **300** of the present disclosure is operable with as few as two array apertures **320**. Thus, the size and shape of the aperture array layer **310** is a design choice, based upon, for example, the size and shape of the carrier material **12** or portion of carrier material **12** that is desired to potentially accept attachment or coupling of accessories.

[0107] In various exemplary embodiments, the array apertures **320** are generally formed as apertures through the aperture array layer **310**. Each array aperture **320** is defined by one or more continuous edges or edge portions. In various exemplary embodiments, each array aperture **320** is formed in the shape of an elongated octagon. The edges or edge portions of each array aperture **320** is/are defined by a first height, H_1 , which extends so as to be defined between opposing edge portions **322** and **329**. A second height, H_2 , is defined by the lengths of opposing edge portions **325** and **326**. The first height, H_1 , is greater than the second height, H_2 .

[0108] The edges or edge portions of each array aperture **320** is/are further defined by a first width, W_1 , which extends so as to be defined between opposing edge portions **325** and **326**. A second width, W_2 , is defined by the lengths of the opposing edge portions **322** and **329**. The first width, W_1 , is greater than the second width, W_2 .

[0109] Opposing edge portions **322** and **329** are substantially parallel to one another, while opposing edge portions **325** and **326** are substantially parallel to one another. Edge portion **323** extends between edge portions **325** and **322**, edge portion **324** extends between edge portions **326** and **322**, edge portion **327** extends between edge portions **325** and **329**, and edge portion **328** extends between edge portions **326** and **329**. Thus, the array aperture **320** takes the form of a substantially elongated octagon defined by edge portions **322**, **323**, **324**, **325**, **326**, **327**, **328**, and **329**.

[0110] However, it should also be appreciated that each of the array apertures **320** may generally be formed in the shape of an elongated octagon, wherein edge portions **322**, **323**, **324**, **325**, **326**, **327**, **328**, and **329** join each other at rounded corners or edges (as illustrated in **FIG. 25**), an elongated octagon, wherein one or more edge portions **322**, **323**, **324**, **325**, **326**, **327**, **328**, and **329** comprise a rounded or curved edge portions (as illustrated in **FIG. 26**), or an elongated octagon, wherein the lengths of the first height, H_1 , the second height, H_2 , the first width, W_1 , and/or the second width, W_2 , is varied (as illustrated in **FIG. 27**). Thus, it should be appreciated that the size and shape of each of the array apertures **320** is a design choice based upon the desired functionality and/or appearance of the modular attachment aperture array **300** and/or the aperture array layer **310**.

[0111] The overall size of each array aperture **320** is also a design choice. In certain exemplary embodiments,

the size of each array aperture **320** is influenced or dictated by the width of the accessory coupling element of a compatible accessory, such as, for example, the accessory coupling element **88** of a compatible accessory **81**. For example, if the accessory coupling element **88** has a width of approximately 1 inch, the first width, W_1 , of each array aperture **320** may optionally be approximately 1 inch, so as to allow the accessory coupling element **88** to be interwoven between two or more array apertures **320** and fitted within an aperture array tunnel segment **335** are created between array apertures **320**. Alternatively, the size of each array aperture **320** may be created such that only certain accessories are compatible with the aperture array layer **310** and the modular attachment aperture array **300**.

[0112] The array apertures **320** are arranged in a repeating, alternating, staggered, or semi-repeating series or sequence of spaced apart, repeating patterns. In various exemplary embodiments, the array apertures **320** are arranged in a repeating, alternating, staggered, or semi-repeating series or sequence of spaced apart rows **313** and columns **312**. In various exemplary embodiments, the array apertures **320** are arranged in a series of equally spaced rows **313** and alternatingly offset, equally spaced columns **312**.

[0113] In various exemplary embodiments, as illustrated in **FIGS. 24, 28, and 29**, the columns **312** are arranged such that each column **312** at least partially overlaps an adjacent column **312**. It should be appreciated that the degree or amount of overlap of adjacent columns **312** is a design choice based upon the desired compatibility of certain accessories with the aperture array layer **310** and the modular attachment aperture array **300**. By providing columns **312** that overlap one another, the number and spacing of positioning possibilities of attached accessories can be increased. Thus, the incremental shift of accessory attachment possibilities can be decreased. For example, instead of being restricted to attaching accessories at approximately $1\frac{1}{2}$ inch increments (with known MOLLE webbing) overlapping columns **312** may, for example, allow attachment of accessories at approximately $\frac{1}{2}$ inch, $\frac{3}{4}$ inch, or 1 inch increments. It should be appreciated that the incremental attachment options are a design choice based upon the desired degree of overlap, if any, of the columns **312**.

[0114] In certain exemplary embodiments, the spacing between each of the rows **313** is less than or greater than the spacing between each of the columns **312**.

[0115] In various exemplary embodiments, the spacing between either edge portions or proximate centers of adjacent array apertures **320** (whether vertically, horizontally, obliquely, or diagonally adjacent) is influenced or dictated by the width of the accessory webbing element **83** of a compatible accessory **81**. For example, if the accessory webbing element **83** has a width of approximately 1 inch, the spacing between either edges or proximate centers of adjacent array apertures **320** may optionally be approximately 1 inch, so as to allow the accessory

webbing element(s) **83** to be appropriately aligned between every or every other array aperture **320** in a vertical, horizontal, oblique, or diagonal direction. Alternatively, the spacing between either edge portions or proximate centers of adjacent array apertures **320** may be created such that only certain accessories are compatible with the aperture array layer **310** and the modular attachment aperture array **300**.

[0116] It should be appreciated that two or more adjacent array apertures **320** may comprise a row **313** and two or more adjacent array apertures **320** may comprise a column **312**, as illustrated, for example, in in **FIG. 29**. Thus, it should be appreciated that the number of array apertures **320** formed in the aperture array layer **310** is a design choice based upon the desired size and/or functionality of the aperture array layer **310**.

[0117] In various exemplary, nonlimiting embodiments, each adjacent row **313** and/or column **312** of spaced apart array apertures **320** is offset such that either edges or proximate centers of adjacent array apertures **320** are offset by an angle, θ , of approximately $\pm 33^\circ$ (as illustrated in **FIG. 24**). **FIG. 28** illustrates an alternative spacing of the rows **313** and columns **312** forming the aperture array layer **310**.

[0118] It should be appreciated that the spacing between adjacent array apertures **320** and/or the offset of adjacent rows **313** and/or columns **312** dictates the angle of attachment of accessories to the aperture array layer **310**.

[0119] In certain exemplary, nonlimiting embodiments, each array aperture **320** is separated from each other array aperture **320** by a distance that is less than the first width, W_1 , of each array aperture **320**.

[0120] By arranging the array apertures **320** in a repeating, alternating, staggered, or semi-repeating series or sequence, aperture array tunnel segments **335** are created between adjacent array apertures **320** (whether vertically, horizontally, obliquely, or diagonally adjacent).

[0121] In various exemplary embodiments, the aperture array layer **310** is formed as a stand-alone element, such as, for example, a sheet of aperture array layer **310** material, to which compatible accessories may be attached or coupled. Alternatively, the aperture array layer **310** may optionally be utilized as a portion of material used to form an accessory, such as, for example, a pouch or carrier. For example, a portion of aperture array layer **310** may be utilized as a wall segment of a magazine or other pouch. In still other alternative embodiments, several array apertures **320** may be formed in a portion of material, such that the portion of material constitutes a portion of aperture array layer **310**.

[0122] In still other exemplary, nonlimiting embodiments, the aperture array layer **310** may optionally be at least partially attached or coupled to at least a portion of a carrier or carrier material, such as, for example, a carrier material **12**. Thus, the aperture array layer **310** may be at least partially attached or coupled to an exemplary carrier (such as, for example, exemplary carrier material

12), for example, an article of clothing, a vest, a plate carrier, a backpack, a pack, a bag, a platform, or another flexible, semi-rigid, or rigid carrier.

[0123] As illustrated, for example, in **FIG. 24**, the aperture array layer **310** is attached or coupled to a portion of carrier material **12**, via stitching or other aperture array layer attachment elements (not illustrated). The aperture array layer attachment elements (not illustrated) may optionally be spaced apart, as necessary or desirable, in order to further secure, attach, or couple the aperture array layer **310** to the carrier material **12**. The number and placement of aperture array layer attachment elements (not illustrated) is a design choice based upon the desired level of securement of the aperture array layer **310** to the carrier material **12** and/or to further ensure that the aperture array layer **310** will not separate or pull away from the carrier material **12**, particularly if accessories are attached or coupled to the aperture array layer **310**.

[0124] In certain exemplary embodiments, the aperture array layer attachment elements (not illustrated) comprise stitching. Alternatively, the aperture array layer **310** may be attached or coupled to the carrier material **12** at one or more aperture array layer attachment elements (not illustrated) via adhesive bonding, welding, screws, rivets, pins, mating hook and loop portions, snap or releasable fasteners, or other known or later developed means or methods for permanently or releasably attaching or coupling the aperture array layer **310** to the carrier material **12**. The one or more aperture array layer attachment elements (not illustrated) may be formed or positioned proximate a perimeter of the aperture array layer **310** or in one or more areas located within the one or more aperture array layers **310**.

[0125] In addition to the variability of size and shape of the aperture array layer **310**, the orientation of the aperture array layer **310**, relative to the carrier material **12**, is also a design choice. Thus, the array apertures **320** are illustrated as being arranged or oriented in a particular manner, relative to the aperture array layer **310**, such that the rows **313** of array apertures **320** are arranged in an exemplary, horizontal fashion, while the columns **312** of array apertures **320** are arranged in an exemplary, vertical fashion. It should be appreciated that this is merely exemplary and the aperture array layer **310** may be formed, attach, or coupled at any desired angular or rotational orientation relative to a surface of the carrier material **12**.

[0126] The portions of material of the aperture array layer **310** between adjacent array apertures **320** form aperture array tunnel segments **335**. If the aperture array layer **310** is attached to a carrier material **12**, the aperture array tunnel segments **335** are formed between the aperture array layer **310** and the surface of the carrier material **12**. The aperture array tunnel segments **335** provide areas for securing the accessory coupling element **88** of an accessory **81** to the aperture array layer **310**. In this manner, an accessory coupling element **88** may be in-

terwoven between the aligned aperture array tunnel segments **335** to removably attach the accessory **81** to the carrier material **12**.

[0127] FIGS. **30-37** illustrate an exemplary embodiment of an array aperture **320** and a modular attachment aperture array **300**, according to the present disclosure. As illustrated, the modular attachment aperture array **300** includes an aperture array layer **310** having two or more array apertures **320** formed therethrough at spaced apart locations and arranged in one or more rows **313** and/or columns **312**. The aperture array layer **310** is at least partially attached or coupled to a carrier material **12** and tunnel segments **335** are formed between adjacent array apertures **320**.

[0128] It should be understood that each of these elements corresponds to and operates similarly to the modular attachment aperture array **300**, aperture array layer **310**, array apertures **320**, and tunnel segments **335**, as described above with reference to the modular attachment aperture array **300** of FIGS. **34-29**.

[0129] However, FIGS. **30-37**, illustrate an exemplary embodiment of an array aperture **320** that can be utilized in place of an array aperture **120** to form the modular attachment aperture array **100** and/or the aperture array layer **310**. As illustrated, the array aperture **320** includes a first height, H_1 , a second height, H_2 , and a first width, W_1 . Each array aperture **320** is formed of two substantially equal length, parallel sides **323**, each having a height, H_2 . It should be appreciated that the width, W_1 , between of each of the sides **323** is a design choice based upon the desired functionality and/or appearance of the array aperture **320**.

[0130] An arcuate side **325** joins respective upper terminal ends and respective lower terminal ends of each of the sides **323**. In various exemplary embodiments, the height, H_1 , is formed between apexes of each of the sides **323**. It should be appreciated that the height, H_1 , between apexes of each of the sides **323** is a design choice based upon the desired functionality and/or appearance of the array aperture **320**. Thus, the angle of each arc forming each arcuate side **325** may be formed based upon the desired functionality and/or appearance of each array aperture **320**.

[0131] Each array aperture **320** is generally formed as an aperture or hole through the aperture array layer **310**. It is possible for the aperture array layer **310** to operate as a stand-alone element, such as, for example, a sheet of aperture array layer **310** material, to which compatible accessories may be attached or coupled. However, in various exemplary embodiments, the aperture array layer **310** is at least partially attached or coupled to at least a portion of a carrier or carrier material, such as, for example, a carrier material **12**. Thus, the aperture array layer **310** may be at least partially attached or coupled to an exemplary carrier, for example, an article of clothing, a vest, a plate carrier, a backpack, a pack, a bag, a platform, or another flexible, semi-rigid, or rigid carrier.

[0132] The overall size of each array aperture **320** is

also a design choice. In certain exemplary embodiments, the size of each array aperture **320** is influenced or dictated by the width of the accessory coupling element of a compatible accessory, such as, for example, the accessory coupling element **88** of a compatible accessory **81**. For example, if the accessory coupling element **88** has a width of approximately 1 inch, the width, W_1 , between of each of the sides **323** may optionally be approximately 1 inch, so as to allow the accessory coupling element **88** to be fitted within and interwoven between two or more array apertures **320**. Alternatively, the width, W_1 , between of each of the sides **323** may be such that only certain accessories are compatible with the aperture array layer **310** and the modular attachment aperture array **100**.

[0133] As illustrated in FIGS. **31-33**, the array apertures **320** may be arranged in a repeating or semi-repeating series or sequence of spaced apart, repeating patterns. In various exemplary embodiments, the array apertures **320** are arranged in a repeating or semi-repeating series or sequence of spaced apart rows **313** and columns **312**. In various exemplary embodiments, the array apertures **320** are arranged in a series of equally spaced rows **313** and equally spaced columns **312**.

[0134] In certain exemplary embodiments, each of the rows **313** is spaced at a distance that is the same as the spacing between each of the columns **312**. Alternatively, the spacing between each of the rows **313** is greater than or less than the spacing between each of the columns **312**.

[0135] In various exemplary embodiments, the spacing between either edges or proximate centers of adjacent array apertures **320** (whether vertically, horizontally, obliquely, or diagonally adjacent) is influenced or dictated by the width of the accessory webbing element **83** of a compatible accessory **81**. For example, if the accessory webbing element **83** has a width of approximately 1 inch, the spacing between either edges or proximate centers of adjacent array apertures **320** may optionally be approximately 1 inch, so as to allow the accessory webbing element(s) **83** to be appropriately aligned between every other array aperture **320** in a vertical, horizontal, oblique, or diagonal direction. Alternatively, the spacing between either edges or proximate centers of adjacent array apertures **320** may be created such that only certain accessories are compatible with the aperture array layer **310** and the modular attachment aperture array **100**.

[0136] It should be appreciated that two or more adjacent array apertures **320** may comprise a row **313** and two or more adjacent array apertures **320** may comprise a column **312**. Thus, it should be appreciated that the number of array apertures **320** formed in the aperture array layer **310** is a design choice based upon the desired size and/or functionality of the aperture array layer **310**.

[0137] In various exemplary, nonlimiting embodiments, each adjacent row **313** and/or column **312** of spaced apart array apertures **320** is offset such that either edges or proximate centers of adjacent array apertures

320 are offset by approximately $\pm 45^\circ$, approximately $\pm 33^\circ$, or approximately $\pm 90^\circ$. If for example, either edges or proximate centers of adjacent array apertures **320** are offset by $\pm 45^\circ$, $\pm 33^\circ$, or $\pm 90^\circ$, an attached or coupled accessory **81** may be attached or coupled at least at $\pm 0^\circ$, $\pm 90^\circ$, $\pm 33^\circ$, or $\pm 45^\circ$. Thus, it should be appreciated that the offset of adjacent rows **313** and/or columns **312** dictates the angle of oblique attachment of accessories.

[0138] In certain exemplary, nonlimiting embodiments, each array aperture **320** may be separated from each other array aperture **320** by a distance that is equal to or greater than a width of each array aperture **320**. Alternatively, each array aperture **320** may be separated from each other array aperture **320** by a distance that is equal to or greater than a width of each array aperture **320**.

[0139] By arranging the array apertures **320** in a repeating or semi-repeating series or sequence, aperture array tunnel segments **135** are created between adjacent array apertures **320** (whether vertically, horizontally, obliquely, acutely, or diagonally adjacent).

[0140] In various exemplary, nonlimiting embodiments, the aperture array layer **310** comprises a portion of aperture array layer **310** material that is at least partially attached or coupled to a carrier material **12** by aperture array layer attachment elements (not illustrated), such as stitching proximate a perimeter of the aperture array layer **310**. The aperture array layer **310** may optionally be attached or coupled or further attached or coupled to the carrier material **12**, via additional aperture array layer attachment elements (not illustrated). The aperture array layer attachment elements (not illustrated) may be spaced apart, as necessary or desirable, in order to further secure, attach, or couple the aperture array layer **310** to the carrier material **12**. The number and placement of additional aperture array layer attachment elements (not illustrated) is a design choice based upon the desired level of securement of the aperture array layer **310** to the carrier material **12** and/or to further ensure that the aperture array layer **310** will not separate or pull away from the carrier material **12**, particularly if accessories are attached or coupled to the aperture array layer **310**.

[0141] In certain exemplary embodiments, the aperture array layer attachment elements (not illustrated) comprise stitching. Alternatively, the aperture array layer **310** may be attached or coupled to the carrier material **12** at one or more aperture array layer attachment elements (not illustrated) via adhesive bonding, welding, screws, rivets, pins, mating hook and loop portions, snap or releasable fasteners, or other known or later developed means or methods for permanently or releasably attaching or coupling the aperture array layer **310** to the carrier material **12**. The one or more aperture array layer attachment elements (not illustrated) may be formed or positioned proximate a perimeter of the aperture array layer **310** or in one or more areas located within the one or more aperture array layers **310**.

[0142] In addition to the variability of size and shape of the aperture array layer **310**, the orientation of the ap-

erture array layer **310**, relative to the carrier material **12**, is also a design choice. Thus, the aperture array layer **310** may optionally be attached or coupled to the carrier material **12**, such that the rows **313** of array apertures **320** are substantially parallel to a longitudinal or other axis, along the length, of the exemplary carrier material **12**, while the columns **312** of array apertures **320** are substantially perpendicular to the longitudinal or other axis of the carrier material **12**. It should be appreciated that this is merely exemplary and the aperture array layer **310** may be attached at any desired angular or rotational orientation relative to the carrier material **12**.

[0143] The portions of material of the aperture array layer **310** between adjacent array apertures **320** form aperture array tunnel segments **135**. If the aperture array layer **310** is attached to a carrier material **12**, the aperture array tunnel segments **135** are formed between at least portions of the aperture array layer **310** and at least portions of the surface of the carrier material **12**. The aperture array tunnel segments **135** provide areas for securing the accessory coupling element **88** of an accessory **81** to the aperture array layer **310**. In this manner, an accessory coupling element **88** may be interwoven between the aligned aperture array tunnel segments **135** to removably attach the accessory **81** to the carrier material **12**.

[0144] **FIGS. 34-36**, illustrate an exemplary embodiment of an array aperture **320** that can be utilized in place of an array aperture **120** to form the modular attachment aperture array **100** and/or the aperture array layer **310**. As illustrated, the array aperture **320** includes a height, H_1 and a width, W_1 . Each array aperture **320** is formed of an oval shape having a height, H_1 and a width, W_1 . The height and width of each array aperture **320** is a design choice based upon the desired functionality and/or appearance of the array aperture **320**.

[0145] In various exemplary embodiments, the height, H_1 , is formed between vertical apexes of the array aperture **320** and the width, W_1 , is formed between horizontal apexes of the array aperture **320**. It should be appreciated that the height, H_1 , between apexes of each of the sides **323** is a design choice based upon the desired functionality and/or appearance of the array aperture **320**. Thus, the angle of each arc forming each arcuate side **325** may be formed based upon the desired functionality and/or appearance of each array aperture **320**.

[0146] As illustrated in **FIGS. 35-36**, the array apertures **320** may be arranged in a repeating or semi-repeating series or sequence of spaced apart, repeating patterns.

[0147] As illustrated in **FIG. 37**, array apertures **320** of varying designs may be arranged in a repeating or semi-repeating series or sequence of spaced apart, repeating patterns.

[0148] During attachment of an exemplary accessory **81**, the accessory **81** is aligned with the aperture array layer **310** in a desired orientation, similar to the fashion illustrated in **FIGS. 5-12**. The accessory **81** may option-

ally be aligned with the aperture array layer **310** in a generally vertical or horizontal manner or a generally oblique or diagonal manner. It should be understood that these orientations are relative to the orientation of the aperture array layer **310** and the orientation of the aperture array layer **310** relative to any optional carrier material **12**.

[0149] The exemplary accessory **81** includes one or more substantially parallel, spaced apart accessory webbing elements **83**. If more than one accessory webbing element **83** is included, the accessory webbing elements **83** are spaced apart so as to correspond to the spaces between the spaced apart array apertures **320**.

[0150] When the accessory **81** is placed adjacent the aperture array layer **310** such that at least a portion of the accessory webbing elements **83** are within a portion of the spaces between the spaced apart array apertures **320** (and at least a portion of the array apertures **320** are within the spaces between the spaced apart accessory webbing elements **83**) and corresponding aperture array tunnel segments **335** and accessory tunnel segments **87** are aligned, the accessory coupling element **88** may be interwoven between the aligned aperture array tunnel segments **335** and accessory tunnel segments **87** (alternating between adjacent array apertures **320** and/or alternate attachment apertures **321** of the aperture array layer **310** and accessory webbing elements **83** on the accessory **81**) to removably attach the accessory **81** to the aperture array layer **310**.

[0151] Thus, an accessory **81** may be mounted to the aperture array layer **310** in a variety of orientations. Likewise, if a particular carrier material **12** includes an aperture array layer **310**, a variety of accessories may be interchangeably mounted to the aperture array layer **310** to accommodate a variety of desired configurations.

[0152] It should be appreciated that a more detailed explanation of the instructions regarding how to interweave the accessory coupling element **88** between the array apertures **320** and accessory webbing elements **83** is not provided herein because, while the aperture array layer **310** provides more orientation options and other features, accessories are generally attached to the aperture array layer **310** in a manner similar to the manner in which accessories are attached to a portion of MOLLE webbing. Therefore, it is believed that the level of description provided herein is sufficient to enable one of ordinary skill in the art to understand and practice the systems, methods, and apparatuses, as described.

[0153] While the presently disclosed systems, methods, and/or apparatuses has been described in conjunction with the exemplary embodiments outlined above, the foregoing description of exemplary embodiments of the presently disclosed systems, methods, and/or apparatuses, as set forth above, are intended to be illustrative, not limiting and the fundamental disclosed systems, methods, and/or apparatuses should not be considered to be necessarily so constrained. It is evident that the presently disclosed systems, methods, and/or apparatuses is not limited to the particular variation set forth and

many alternatives, adaptations modifications, and/or variations will be apparent to those skilled in the art.

[0154] Furthermore, where a range of values is provided, it is understood that every intervening value, between the upper and lower limit of that range and any other stated or intervening value in that stated range is encompassed within the presently disclosed systems, methods, and/or apparatuses. The upper and lower limits of these smaller ranges may independently be included in the smaller ranges and is also encompassed within the presently disclosed systems, methods, and/or apparatuses, subject to any specifically excluded limit in the stated range. Where the stated range includes one or both of the limits, ranges excluding either or both of those included limits are also included in the presently disclosed systems, methods, and/or apparatuses.

[0155] It is to be understood that the phraseology of terminology employed herein is for the purpose of description and not of limitation. Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which the presently disclosed systems, methods, and/or apparatuses belongs.

[0156] In addition, it is contemplated that any optional feature of the inventive variations described herein may be set forth and claimed independently, or in combination with any one or more of the features described herein.

[0157] Accordingly, the foregoing description of exemplary embodiments will reveal the general nature of the presently disclosed systems, methods, and/or apparatuses, such that others may, by applying current knowledge, change, vary, modify, and/or adapt these exemplary, non-limiting embodiments for various applications without departing from the spirit and scope of the presently disclosed systems, methods, and/or apparatuses and elements or methods similar or equivalent to those described herein can be used in practicing the presently disclosed systems, methods, and/or apparatuses. Any and all such changes, variations, modifications, and/or adaptations should and are intended to be comprehended within the meaning and range of equivalents of the disclosed exemplary embodiments and may be substituted without departing from the true spirit and scope of the presently disclosed systems, methods, and/or apparatuses.

[0158] Also, it is noted that as used herein and in the appended claims, the singular forms "a", "and", "said", and "the" include plural referents unless the context clearly dictates otherwise. Conversely, it is contemplated that the claims may be so-drafted to require singular elements or exclude any optional element indicated to be so here in the text or drawings. This statement is intended to serve as antecedent basis for use of such exclusive terminology as "solely", "only", and the like in connection with the recitation of claim elements or the use of a "negative" claim limitation(s).

Claims

1. A modular attachment aperture array, comprising:

a portion of carrier material; and
 an aperture array layer, wherein said aperture array layer comprises a plurality of spaced apart array apertures, wherein each array aperture is formed of two substantially equal length, substantially parallel sides, an arcuate side joining respective upper terminal ends of said substantially parallel sides, and an arcuate side joining respective lower terminal ends of said substantially parallel sides, wherein each of said array apertures is formed through said aperture array layer, and wherein said array apertures are arranged in a repeating sequence of spaced rows and spaced columns, and wherein said aperture array layer is at least partially attached or coupled to at least a portion of said carrier material.

2. A modular attachment aperture array, comprising:
 an aperture array layer, wherein said aperture array layer comprises a plurality of spaced apart array apertures, wherein each array aperture is formed of two substantially equal length, substantially parallel side portions, an upper arcuate side joining respective upper terminal ends of said substantially parallel side portions, and a lower arcuate side joining respective lower terminal ends of said substantially parallel side portions, wherein each of said array apertures is formed through at least a portion of said aperture array layer, and wherein said array apertures are arranged in a repeating sequence of spaced rows and spaced columns, and wherein said aperture array layer is at least partially attached or coupled to at least a portion of said carrier material.

3. A modular attachment aperture array, comprising:
 an aperture array layer, wherein said aperture array layer comprises a plurality of spaced apart array apertures, wherein said array apertures are formed as substantially elongated oval shaped array apertures arranged in a repeating sequence of equally spaced rows of said array apertures and equally spaced columns of said array apertures.

4. The modular attachment aperture array of claim 2 or claim 3, wherein said aperture array layer is at least partially attached or coupled to at least a portion of a carrier material.

5. The modular attachment aperture array of any one of the preceding claims, wherein aperture array tunnel segments are created between adjacent array apertures.

6. The modular attachment aperture array of claim 8,

wherein aperture array tunnel segments are created between vertically adjacent array apertures, between horizontally adjacent array apertures, between obliquely adjacent array apertures, and/or between diagonally adjacent array apertures.

7. The modular attachment aperture array of any one of the preceding claims, wherein each of said array apertures is defined by one or more continuous edge portions.

8. The modular attachment aperture array of any one of the preceding claims, wherein each array aperture is separated from each other array aperture by a distance that is less than a width of each array aperture.



9. The modular attachment aperture array of any one of the preceding claims, wherein said aperture array layer comprises chlorosulfonated polyethylene (CSPE) synthetic rubber (CSM).

10. The modular attachment aperture array of any one of the preceding claims, wherein said aperture array layer comprises a portion of Hypalon fabric or a nylon laminate.

11. The modular attachment aperture array of any one of the preceding claims, wherein each adjacent column of spaced apart array apertures is offset such that at least edge portions or proximate centers of adjacent array apertures are offset by approximately $\pm 33^\circ$.

12. The modular attachment aperture array of any one of the preceding claims, wherein each column of spaced apart array apertures at least partially overlaps an adjacent column of spaced apart array apertures.

13. The modular attachment aperture array of any one of the preceding claims, wherein said plurality of spaced apart array apertures are arranged in a repeating sequence of equally spaced rows of said array apertures and equally spaced columns of said array apertures.






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8







FIG. 9






FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21






FIG. 22






FIG. 25




FIG. 26






FIG. 27






FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37