



H. Fisher,

Fan Attachment

N^o 50,926.

Patented Nov. 14, 1865.



Witnesses;
Charles Alexander
John P. Jacobs

Inventor;
H. Fisher
per
Alexander Mason
att'y

UNITED STATES PATENT OFFICE.

HENRY FISHER, OF CANTON, OHIO.

FLY-BRUSH FOR TABLES.

Specification forming part of Letters Patent No. **50,926**, dated November 14, 1865.

To all whom it may concern:

Be it known that I, HENRY FISHER, of Canton, in the county of Stark and State of Ohio, have invented certain new and useful Improvements in Fly-Brushes for Tables; and I do hereby declare that the following is a full, clear, and exact description of the same, reference being had to the accompanying drawing, and to the letters of reference marked thereon.

The nature of my invention consists in the arrangement of certain devices for brushing flies from tables in the manner hereinafter described.

In the annexed drawing, A represents an ordinary dining-table.

B represents an upright which has secured near its lower end a metallic piece, *a*, which is provided with jaws which embrace the edges of the table-leaf, and are secured in this position by means of a set-screw, *c*. To the upper end of the upright B is hinged an arm, C. This arm is not only hinged but is secured in the position in which it stands in the figure by means of a pin, *x*.

To the outer end of the arm C is a pendant,

D, which is pinned to the said arm C, so that its lower end will have a pendulous motion, and to this said lower end is secured a cross-bar, to which fly-brushes are secured. The fly-brush moves backward and forward a short distance above the table.

Near the center of the pendant D is secured a cord, E, which passes to the upright *d* and around a pulley on said upright, and then down through a loop, *i*, to the end of a treadle, G, and secures to it at one end. The treadle is beneath the table and is operated by the foot of a person at the table, for the purpose of vibrating the pendant D, thus keeping off the flies.

I claim—

The arrangement of the upright B, arm C, pendant D, cord E, pulley *d*, and treadle G, the several parts being constructed as and for the purpose specified.

In witness that I claim the foregoing I have hereunto set my hand.

HENRY FISHER.

Witnesses:

A. W. RAYMOND,
DANIEL PRINCE.