

(12) PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 199933980 B2
(10) Patent No. 750656

(54) Title
Inspection of container mouth using infrared energy emitted by the container bottom

(51)⁷ International Patent Classification(s)
G01N 021/90 G01N 021/84

(21) Application No: **199933980**

(22) Application Date: **1999.06.09**

(30) Priority Data

(31) Number	(32) Date	(33) Country
09/098492	1998.06.17	US

(43) Publication Date : **2000.01.06**

(43) Publication Journal Date : **2000.01.06**

(44) Accepted Journal Date : **2002.07.25**

(71) Applicant(s)
Owens-Brockway Glass Container Inc

(72) Inventor(s)
William T. Shepherd

(74) Agent/Attorney
BALDWIN SHELSTON WATERS,Level 21,60 Margaret Street,SYDNEY NSW 2000

(56) Related Art
US 5583337
US 5461228
EP 101246

ABSTRACT OF THE DISCLOSURE

Apparatus (12) and method for inspecting a container (16) having an open mouth (14) and a closed bottom (24) spaced from the container mouth, while the container is hot from its manufacture, includes a light sensor (28) disposed with respect to the

5 container to view the container bottom through the container mouth. Infrared light energy emitted from the container bottom that travels through the container mouth is directed onto the light sensor, and the inside diameter of the container mouth is measured as a function of the light energy directed onto the sensor. The light sensor (28) preferably comprises an area array sensor for developing a two-dimensional image of the

10 container mouth, and the infrared light energy is directed onto the sensor by a telecentric lens arrangement (36). The area array sensor is disposed within a camera that has an entrance pupil (30) and the telecentric lens arrangement has one focus at infinity directed toward the container bottom and a second focus at the entrance pupil of the camera. The area array sensor is coupled to image processing electronics (38) for determining or

15 calculating a circle of greatest diameter that will fit into a two-dimensional image of the container mouth, and treating such circle as indicative of the effective inside diameter of the container mouth.

AUSTRALIA

PATENTS ACT 1990

COMPLETE SPECIFICATION

FOR A STANDARD PATENT

ORIGINAL

Name of Applicant/s: Owens-Brockway Glass Container Inc

Actual Inventor/s: William T. Shepherd

Address for Service: BALDWIN SHELSTON WATERS
60 MARGARET STREET
SYDNEY NSW 2000

Invention Title: "INSPECTION OF CONTAINER MOUTH USING INFRARED
ENERGY EMITTED BY THE CONTAINER BOTTOM"

The following statement is a full description of this invention, including the best method of performing it known to me/us:-

File: 22397.00

INSPECTION OF CONTAINER MOUTH USING INFRARED ENERGY

EMITTED BY THE CONTAINER BOTTOM


The present invention is directed to non-contact measurement of container dimensional parameters, and more particularly to an apparatus and method for measuring
5 inside diameter of a container mouth at the hot end of the container manufacturing process.

Background and Objects of the Invention





Any discussion of the prior art throughout the specification should in no way be considered as an admission that such prior art is widely known or forms part of common
10 general knowledge in the field.

In the manufacture of translucent containers such as clear or colored glass bottles, it is important to maintain dimensional parameters of each container within design specifications for both functional and aesthetic reasons. For example, it is important that the finish of the container, including particularly the container mouth, possess desired
15 geometric characteristics so that the container can be accepted by automatic filling and capping equipment without damage to the equipment, fracture of the container or jamming of the process line.

U.S. Patent 3,313,409, assigned to the assignee hereof, discloses a container inspection system in which containers are routed in sequence through a plurality of
20 inspection stations at which various geometric and other properties are measured. At one such station, an attempt is made to insert a plug of predetermined size into the mouth of the container. The diameter of the plug is coordinated with the minimum container mouth diameter for mating with container filling equipment, for example. If the plug cannot be so inserted into the container mouth, the container is rejected. At other stations of the inspection system, container dimensional parameters are measured by



monitoring the positions of rollers in contact with the container as the container is rotated. However, the inspection techniques that require physical contact with the container are slow, and are subject to mechanical wear of the rollers and plugs, for example. The reciprocating motions needed to bring the plugs and rollers into and out of
5 contact with the container draw substantial amounts of electrical power. Furthermore, physical contact of



measuring equipment with the container is not desirable at the so-called hot end of the manufacturing process, at which the containers are still soft.

To address some of the deficiencies of the mechanical inspection techniques so described, U.S. Patent 5,461,228, also assigned to the assignee hereof, discloses an apparatus and method for electro-optically measuring dimensional parameters of a container, such as inside diameter of the container mouth. A light source directs light energy into the container, and a light sensor is disposed with respect to the light source and the container to receive light energy transmitted out of the container through the container mouth. A telecentric lens directs onto the light sensor only light energy transmitted through the container mouth substantially axially of the container mouth. The light energy is focused through an iris onto a matrix array sensor, which develops a two-dimensional image of the container mouth. The matrix array sensor is coupled to image processing electronics for determining or calculating a circle of greatest diameter that will fit within the two-dimensional image of the container mouth, and treating such circle as indicative of the effective inside diameter of the container mouth.

In conventional glassware manufacturing processes, glassware is molded in an individual section machine and then placed while still hot on a linear conveyor for transport to an annealinglehr. After stress relief within the lehr, the glassware is transported to various stations for inspection, filling and/or packaging. The lehr divides the hot end of the manufacturing process in which the containers are molded from the cold end of the process in which the containers are inspected and packaged. The techniques for measuring diameter of the container mouth described above are specifically suited for use at the cold end of the manufacturing process. However, it is desirable to implement inspection at the hot end of the manufacturing process so that information on containers having undesirable variations can be obtained quickly and the process corrected. It is therefore a general objective of the present invention to provide a method and apparatus for inspecting containers, particularly for measuring the inside diameter of the container

mouth, that can be implemented at the hot end of the manufacturing process. When the containers are directed onto the conveyor following the molding process, the containers are hot, emitting radiation in both the visible and infrared ranges. As the containers travel toward the annealing Lehr, they gradually cool, with the rate of cooling depending upon thickness of the individual portions of the container. For example, the container finish and mouth, which are relatively thin, cool more rapidly than the container bottom and heel, which are relatively thick. It has heretofore been proposed to measure infrared radiation emitted by a container at the hot end of the manufacturing process to determine or infer wall thickness of different portions of the container. See, for example, U.S. Patents 2,915,638 and 3,356,212.

Summary of the Invention




It is an object of the present invention to overcome or ameliorate at least one of the disadvantages of the prior art, or to provide a useful alternative.

According to a first aspect, the present invention provides a method of inspecting for commercial variations in a first portion of a container that comprises the steps of:

directing light energy onto the first container portion under inspection, viewing the first container portion onto which light energy is directed with light sensing means that provides an output as a function of optical characteristics of the viewed container portion, and identifying the commercial variations in the first container portion as a function of said output,

wherein said step of directing light energy is accomplished by a second portion of the container at elevated temperature that directs infrared light energy onto the first container portion.

Unless the context clearly requires otherwise, throughout the description and the claims, the words 'comprise', 'comprising', and the like are to be construed in an






inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in the sense of "including, but not limited to".

According to another aspect, the present invention provides an apparatus for inspecting a container having an open mouth, which comprises:




- 5 a light source for directing light energy into the container, and light sensing means disposed with respect to said light source and the container to receive light energy transmitted through the container mouth,

wherein said light source comprises a wall portion of the container at a temperature such that said wall portion transmits infrared light energy into the container and to which
10 said light sensing means is responsive.

A method of inspecting containers manufactured in a process from which the containers emerge at elevated temperature, and after which portions of the container cool at different rates as a function of thickness, contemplates in accordance with a presently preferred embodiment of the invention optically viewing a first portion of the container
15 against a background that includes a second portion of the container at higher temperature than the first portion, such that the first portion is effectively illuminated by infrared energy from the second portion of the container. Commercial variations in the second portion of the container, consisting of variations that affect commercial acceptability of the container, are identified in the second portion of the container as a
20 function of variations in the infrared energy caused by the second portion of the container. The first portion of the container is viewed by a light sensor that provides an output as a function of optical characteristics of the first container portion, and commercial variations are detected as a function of such signals.



In a particularly preferred implementation of the invention for inspecting the open mouth of a container, the light sensor is directed to view the bottom of the container through the



open container mouth so as to obtain an image of the container mouth as illuminated by infrared energy radiated by the container bottom. The infrared energy emerging from the container mouth is directed onto the sensor by a telecentric lens in accordance with the preferred embodiment of the invention, so that only light energy that emerges axially from the container mouth is directed onto the sensor. The sensor is coupled to image processing electronics for determining or calculating a circle of greatest diameter that will fit within the two-dimensional image of the container mouth, and treating such circle as indicative of the effective inside diameter of the container mouth.

Apparatus for inspecting a container having an open mouth and a closed bottom spaced from the container mouth, while the container is hot from its manufacture in accordance with another aspect of the present invention, includes a light sensor disposed with respect to the container to view the container bottom through the container mouth. Infrared light energy emitted from the container bottom that travels through the container mouth is directed onto the light sensor, and the inside diameter of the container mouth is measured as a function of the light energy directed onto the sensor. The light sensor preferably comprises an area array sensor for developing a two-dimensional image of the container mouth, and the infrared light energy is directed onto the sensor by a telecentric lens arrangement. The area array sensor is disposed within a camera that has an entrance pupil, and the telecentric lens arrangement has one focus at infinity directed toward the container bottom and a second focus at the entrance pupil of the camera. The matrix array sensor is coupled to image processing electronics for determining or calculating a circle of greatest diameter that will fit into the two-dimensional image of the container mouth, and treating such circle as indicative of the effective inside diameter of the container mouth.

Thus, in accordance with yet another aspect of the present invention, there are provided a method and apparatus for inspecting for commercial variations in a container, including

dimensional characteristics of the container such as inside diameter of the container mouth. The method and apparatus in accordance with this aspect of the invention contemplates directing light energy onto a first portion of the container under inspection, viewing the first portion of the container with a light sensor that provides an output as a function of the optical characteristics of the viewed container portion, and identifying commercial variations in the first portion of a container as a function of such output. In accordance with the invention, the step of illuminating the first portion of the container is accomplished by a second portion of the container at elevated temperature so as to transmit infrared energy onto the first container portion and thereby effectively illuminate the first container portion for inspection.

10 **Brief Description of the Drawings**

The invention, together with additional objects, features and advantages thereof, will be best understood from the following description, the appended claims and the accompanying drawings in which:

FIG. 1 is a schematic diagram of an electro-optical non-contact system for measuring inside diameter of a container mouth in accordance with a presently preferred implementation of the invention;

FIG. 2 is a fragmentary schematic diagram of a portion of FIG. 1 on an enlarged scale; and

FIG. 3 is a schematic diagram that illustrates calculation of effective inside diameter from a two-dimensional image of the container mouth.

Detailed Description of Preferred Embodiments

FIG. 1 illustrates a glassware manufacturing system 10 that includes apparatus 12 for inspecting or measuring the inside diameter of the mouth 14 of a container 16 at the hot end of the manufacturing process in accordance with a presently preferred embodiment of the invention. Containers 16 are manufactured in a so-called individual section machine 18 under control of machine control electronics 20. Individual section machine 18 may be as disclosed, for example, in U.S. Patent 4,362,544. U.S. Patents 4,152,134 and 4,369,052 illustrate exemplary machine control electronics 20. Containers manufactured by machine 18 are placed on a conveyor 22 for transport in a linear sequence to an annealing Lehr. Immediately after manufacture, the containers 16 are hot, emitting radiation in both the visible and infrared regions. As the containers are transported toward the annealing Lehr, the containers cool, with different portions of the containers cooling at differing rates depending upon thickness. For example, the finish portion of the container around mouth 14 is relatively thin and cools relatively rapidly, while the bottom 24 of the container is relatively thick and cools more slowly. Closely following machine 18 where the sidewall and mouth of the container are relatively cool, the bottom is typically still bright red, emitting radiation in the infrared range of about 0.4 to 100 microns. In accordance with the present invention, a hot and infrared-emitting portion of the container, such as bottom 24, is used as a light source for illuminating a portion of the container to be inspected, such as mouth 14.

A camera 26 is positioned above conveyor 22 and oriented downwardly for viewing the mouths 14 of containers 16 as they are transported beneath camera 26 in sequence. Camera 26 includes an area array CCD sensor 28, an entrance pupil 30, and lenses 32, 34 associated with the entrance pupil. Sensor 28 is responsive to infrared energy in the range of 0.4 to 1.1 microns. A telecentric lens 36 is positioned between camera 26 and containers 16 as they pass in sequence. Telecentric lens 36 has a first focus in the direction of containers 16 at infinity,

and a second focus at entrance pupil 30. That is, camera 26 is positioned with respect to lens 36 so that entrance pupil 30 is spaced from lens 36 by the focal distance of the lens. Thus, pupil 30 with lenses 32, 34 functions as an iris in combination with lens 36 for focusing onto sensor 28 essentially only light rays that emerge from container mouth 14 parallel to the axis of the container, lens and camera. That is, light rays that emerge from the container mouth in a direction not parallel to the container and optical axis, and light rays generated by other portions of the container that may still be hot and emitting infrared radiation, will be directed by lens 36 other than through pupil 30, and thus effectively blocked from impingement on sensor 28. In this way, a clear image of the container mouth is focused onto area array sensor 28. Sensor 28 is connected to information processing electronics 38 for scanning the sensor and developing a two-dimensional image of the container mouth. As illustrated in FIG. 3, the glass that defines the container mouth will appear as a dark image against a bright background formed by the infrared light energy transmitted from container bottom 24 through the container mouth. This is because the glass of the container reflects or refracts light transmitted onto the body of the container, this reflected or refracted light will not be parallel to the optical axis and thus not directed onto sensor 28. Exemplary techniques for scanning an area array sensor and developing a two-dimensional image of the container mouth are disclosed in U.S. Patent 4,958,223.

FIGS. 2-3 illustrate operation of the invention in connection with a container 16a having a mouth 14a with a choked region 14b. As illustrated in FIG. 2, the choked region 14b blocks a portion of the light rays emerging from the container mouth parallel to the container/optical axis, thereby creating at sensor 28 and information processor 38 a two-dimensional image as illustrated in FIG. 3. Information processor 38 analyzes the image of FIG. 3 by calculating a circle 14c of greatest diameter that will fit within the image of mouth 14a, including choked region 14b. The calculated circle 14c is then treated as the effective inside diameter of the container mouth. In the event that such effective diameter is less than a minimum

desired inside diameter, information processor 38 supplies an appropriate signal to a reject mechanism for removing container 16a from conveyor 22. Information processor 38 is also coupled to a display 40 for displaying to an operator the two-dimensional image of the container under inspection, or other appropriate inspection information. Information processor 38 is also coupled to machine control electronics 20 for controlling positioning and operation of operating mechanisms in the individual section machine so as to correct the process variation if possible, or to terminate operation of individual molds or sections at which the container 16a is manufactured. In this connection, it will be appreciated that the containers are placed on conveyor 22 by machine 18 in a predetermined and continuous sequence, so that the section and molds at which a particular container 16 or 16a originated can be readily determined. See, for example, U.S. Patent 4,762,544.

The invention may also be employed for measuring other container parameters and geometric characteristics. For example, a so-called "leaner" container - i.e., a container in which the mouth 14 is cocked with respect to the optical axis of the inspection apparatus, will produce an image of two overlapping circles from opposing edges of the container mouth at the top and bottom of the container neck. If the effective diameter across these overlapping circles is too small, the container would be rejected as having a container mouth diameter less than the desired minimum. The apparatus of the invention may also be employed to detect and reject a container having a so-called "bird swing" variation if the variation is sufficiently large to be viewed across the mouth of the container.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:-

1. A method of inspecting for commercial variations in a first portion of a container that comprises the steps of:

directing light energy onto the first container portion under inspection, viewing the
5 first container portion onto which light energy is directed with light sensing means that provides an output as a function of optical characteristics of the viewed container portion, and identifying the commercial variations in the first container portion as a function of said output,

wherein said step of directing light energy is accomplished by a second portion of
10 the container at elevated temperature that directs infrared light energy onto the first container portion.

2. The method set forth in claim 1 for inspecting containers manufactured in a process from which the containers emerge at elevated temperature, and after which portions of the containers cool at different rates as a function of thickness, said method
15 comprising the steps of:

(a) optically viewing said first portion of the container against a background that includes said second portion of the container at higher temperature than said first portion, such that said first portion is effectively illuminated by infrared energy emitted by said second portion, and



(b) identifying commercial variations in the second portion of the container as a function of variations in said infrared energy caused by said second portion of the container.

3. The method set forth in claim 2 wherein said step (a) is carried out by
5 viewing the first container portion with light sensing means that provides an output as a function of optical characteristics of said first portion as illuminated by said second portion, and when said step (b) is carried out as a function of said signals.

4. The method set forth in claim 3 for inspecting a container having an open
mouth and a container bottom spaced from said mouth, wherein said step (a) comprises
10 the step of viewing the container bottom through the open mouth to obtain an image of the container mouth as illuminated by infrared energy from the container bottom.

5. Apparatus for inspecting a container having an open mouth, which
comprises:

a light source for directing light energy into the container, and light
15 sensing means disposed with respect to said light source and the container to receive light energy transmitted through the container mouth,

wherein said light source comprises a wall portion of the container at a temperature such that said wall portion transmits infrared light energy into the container and to which said light sensing means is responsive.

6. The apparatus set forth in claim 5 for inspecting a container having an open mouth
5 and a closed bottom spaced from the container mouth while the container is hot from its manufacture,

said light sensing means being disposed with respect to the container to view the container bottom through the container mouth,

- means for directing onto said light sensing means infrared light energy emitted by
10 the container bottom that travels through said mouth, and


means for measuring inside diameter of the container mouth as a function of the infrared light energy directed into said light sensing means.

7. The apparatus set forth in claim 6 wherein said light sensing means comprises an array sensor, and wherein said light directing means comprises telecentric lens means for
15 directing into said array sensor only infrared light energy from the container bottom that emerges substantially axially through the container mouth.

8. The apparatus set forth in claim 7 wherein said light sensing means comprises a camera having an entrance pupil, and wherein said telecentric lens means has one focus at infinity directed toward the container bottom and a second focus at said entrance
20 pupil.

9. The apparatus set forth in claim 8 wherein said light sensor comprises an area array sensor and means coupled to said sensor for developing a two-dimensional image of the container mouth.

10. The apparatus set forth in claim 9 wherein said measuring means comprises means for analyzing said image to determine inside diameter of the container mouth.



11. The apparatus set forth in claim 10 wherein said analysing means comprises means for determining a circle of greatest diameter that will fit within said image.

12. The apparatus set forth in claim 11 further comprising means for indicating acceptability of the container as a function of said circle of greatest diameter.

5 13. A method of inspecting for commercial variations in a container substantially as herein described with reference to any one of the embodiments of the invention illustrated in the accompanying drawings.

14. Apparatus for inspecting a container having an open mouth substantially as herein described with reference to any one of the embodiments of the invention illustrated in
10 the accompanying drawings.

Dated this 3rd day of July 2001

OWENS-BROCKWAY GLASS CONTAINER INC.

Attorney: KENNETH W. BOLTON
Registered Patent and Trade Mark Attorney of Australia
of BALDWIN SHELSTON WATERS

15







FIG. 3

FIG. 2