




US 20170108653A1

(19) **United States**(12) **Patent Application Publication**
Anderson et al.(10) **Pub. No.: US 2017/0108653 A1**(43) **Pub. Date: Apr. 20, 2017**(54) **MANAGED FIBER CONNECTIVITY
SYSTEMS****Publication Classification**(71) Applicants: **CommScope Technologies LLC**,
Hickory, NC (US); **CommScope
Connectivity UK Limited**, Swindon
(GB)(51) **Int. Cl.**
G02B 6/38 (2006.01)
G06K 7/10 (2006.01)
(52) **U.S. Cl.**
CPC **G02B 6/3895** (2013.01); **G02B 6/3874**
(2013.01); **G02B 6/3831** (2013.01); **G02B**
6/3887 (2013.01); **G02B 6/3825** (2013.01);
G06K 7/10366 (2013.01); **G06K 2007/10485**
(2013.01)(72) Inventors: **David J. Anderson**, Bloomington, MN
(US); **Stephen Lambourn**, Swindon
(GB)(21) Appl. No.: **15/275,798**(22) Filed: **Sep. 26, 2016****Related U.S. Application Data**(63) Continuation of application No. 13/939,826, filed on
Jul. 11, 2013, now Pat. No. 9,453,971.(60) Provisional application No. 61/670,366, filed on Jul.
11, 2012.(57) **ABSTRACT**

A communications connection system includes an SC fiber optic connector including a storage device having memory configured to store physical layer information. The storage device also includes electrical contacts or an RFID antenna coil connected to the memory for transmitting information to a management system. The communications connection system also includes a fiber optic adapter module having one or more media reading interfaces. Each media reading interface is configured to read physical layer information stored on one of the fiber optic connectors received at the adapter module. Example media reading interfaces include electrical contacts and RFID readers.






FIG. 2





FIG. 3






FIG. 5





FIG. 6






FIG. 7




FIG. 8




FIG. 10





FIG. 11






FIG. 12





FIG. 13






FIG. 15





FIG. 16



MANAGED FIBER CONNECTIVITY SYSTEMS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of application Ser. No. 13/939,826, filed Jul. 11, 2013, which application claims the benefit of provisional application Ser. No. 61/670,366, filed Jul. 11, 2012, which applications are incorporated herein by reference in their entirety.

BACKGROUND

[0002] In communications infrastructure installations, a variety of communications devices can be used for switching, cross-connecting, and interconnecting communications signal transmission paths in a communications network. Some such communications devices are installed in one or more equipment racks to permit organized, high-density installations to be achieved in a limited space.

[0003] Communications devices can be organized into communications networks, which typically include numerous logical communication links between various items of equipment. Often a single logical communication link is implemented using several pieces of physical communication media. For example, a logical communication link between a computer and an inter-networking device such as a hub or router can be implemented as follows. A first cable connects the computer to a jack mounted in a wall. A second cable connects the wall-mounted jack to a port of a patch panel, and a third cable connects the inter-networking device to another port of a patch panel. A “patch cord” cross connects the two together. In other words, a single logical communication link is often implemented using several segments of physical communication media.

[0004] Network management systems (NMS) are typically aware of logical communication links that exist in a communications network, but typically do not have information about the specific physical layer media (e.g., the communications devices, cables, couplers, etc.) that are used to implement the logical communication links. Indeed, NMS systems typically do not have the ability to display or otherwise provide information about how logical communication links are implemented at the physical layer level.

SUMMARY

[0005] The present disclosure relates to optical adapters and optical connectors that provide physical layer management capabilities. In accordance with certain aspects, the disclosure relates to SC-type optical adapters and SC-type optical connectors.

[0006] In some implementations, a fiber optic connector includes an inner body, an outer body, and a storage device. The inner body is configured to retain a ferrule that extends longitudinally through the inner body. The inner body defines a recess that extends longitudinally along an exterior surface of the inner body. The outer body slideably received about the inner body. The outer body defines a cut-out extending rearwardly from a front of the outer body. The cut-out is aligned with the recess defined in the inner body. The storage device is disposed in the recess of the inner body. At least a portion of the storage device extends from the recess at least partially through the cut-out of the outer body. The storage device includes memory configured to

store physical layer information. The storage device also includes at least one contact member that is electrically connected to the memory.

[0007] In certain implementations, a front edge of the storage device is disposed flush with a front edge of the inner body. In other implementations, a front edge of the storage device is disposed rearwardly offset with a front edge of the inner body.

[0008] A fiber optic adapter module includes a housing, a cover, and a media reading interface. The housing defines at least one passageway extending between the front and the rear to define first and second ports. The housing is configured to retain a fiber optic connector at each port. The housing also defines at least a first opening leading through a first end wall to the passageway. The cover is configured to couple to the housing at the first end to cover the first opening. The cover and the housing cooperate to define an end wall at the first end of the housing. The cover defines a majority of the end wall. The cover defines at least one slot that extends along a central axis of the cover. The slot also extends through the cover to provide access between the passageway and an exterior of the housing when the cover is mounted to the housing. The first media reading interface is positioned in the cover and has at least a first contact location and a second contact location. The first media reading interface is configured so that the second contact location is accessible from within the passageway and the first contact locations is accessible through the slot from the exterior of the housing when the cover is coupled to the housing.

[0009] In accordance with other aspects, a cover arrangement for mounting to an optical adapter includes a cover body and at least a first contact member of a first media reading interface. The cover body defines at least a first slot that extends in a forward-rearward direction along a central longitudinal axis of the cover body. The first slot extends through two planar surfaces of the cover. The first contact member of the first media reading interface is disposed in the first slot. The first contact member has a first moveable section and a second moveable section. The first moveable section is configured to extend through the first slot past a first of the planar surfaces. The second moveable section is configured to extend through the first slot past a second of the planar surfaces.

[0010] A variety of additional inventive aspects will be set forth in the description that follows. The inventive aspects can relate to individual features and to combinations of features. It is to be understood that both the forgoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the broad inventive concepts upon which the embodiments disclosed herein are based.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] The accompanying drawings, which are incorporated in and constitute a part of the description, illustrate several aspects of the present disclosure. A brief description of the drawings is as follows:

[0012] FIG. 1 is a block diagram of one embodiment of a communications management system that includes PLI functionality as well as PLM functionality in accordance with aspects of the present disclosure;

[0013] FIG. 2 is a block diagram of one high-level example of a coupler assembly and media reading interface

that are suitable for use in the management system of FIG. 1 in accordance with aspects of the present disclosure;

[0014] FIG. 3 illustrates a first example implementation of a connector system including a first example optical adapter and fiber optic connectors having PLI functionality as well as PLM functionality;

[0015] FIG. 4 is a front perspective view of an SC-type optical connector on which a storage device is flush-mounted to provide PLI and PLM functionality;

[0016] FIG. 5 is an axial cross-sectional view of the optical connector of FIG. 4;

[0017] FIG. 6 is an axial cross-sectional view of the connector system of FIG. 3;

[0018] FIG. 7 is a top plan view of an example storage device suitable for mounting to any of the optical connectors disclosed herein;

[0019] FIG. 8 is a side elevational view of the storage device of FIG. 7;

[0020] FIG. 9 illustrates one example contact member of a media reading interface suitable for use with any optical adapter disclosed herein;

[0021] FIG. 10 illustrates a second example implementation of an SC-type optical connector suitable for use in a system having PLI functionality as well as PLM functionality;

[0022] FIG. 11 is an axial cross-sectional view of another example implementation of an SC-type adapter receiving two of the SC connectors of FIG. 10;

[0023] FIG. 12 is an enlarged view of the front of the SC optical connector shown in FIG. 10 with another example storage device mounted thereto;

[0024] FIG. 13 is a front perspective view of an example SC optical connector including an embedded storage device;

[0025] FIG. 14 shows the storage device and a cover exploded from the SC optical connector of FIG. 13;

[0026] FIG. 15 is a front end view of the SC-type optical connector of FIG. 13;

[0027] FIG. 16 is a rear perspective view of an example LC connector having a rear slot for receiving a memory storage device; and

[0028] FIG. 17 is a front perspective view of another example LC connector having a rear slot for receiving a memory storage device.

DETAILED DESCRIPTION

[0029] Reference will now be made in detail to exemplary aspects of the present disclosure that are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

[0030] Reference will now be made in detail to exemplary aspects of the present disclosure that are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

[0031] In accordance with some aspects of the disclosure, an example communications and data management system includes at least part of a communications network along which communications signals pass. Media segments connect equipment of the communications network. Non-limiting examples of media segments include optical cables, electrical cables, and hybrid cables. This disclosure will focus on optical media segments. The media segments may

be terminated with optical plug connectors, media converters, or other optical termination components.

[0032] In accordance with aspects of the disclosure, the communications and data management system provides physical layer information (PLI) functionality as well as physical layer management (PLM) functionality. As the term is used herein, “PLI functionality” refers to the ability of a physical component or system to identify or otherwise associate physical layer information with some or all of the physical components used to implement the physical layer of the system. As the term is used herein, “PLM functionality” refers to the ability of a component or system to manipulate or to enable others to manipulate the physical components used to implement the physical layer of the system (e.g., to track what is connected to each component, to trace connections that are made using the components, or to provide visual indications to a user at a selected component).

[0033] As the term is used herein, “physical layer information” refers to information about the identity, attributes, and/or status of the physical components used to implement the physical layer of the communications system. Physical layer information of the communications system can include media information, device information, and location information. Media information refers to physical layer information pertaining to cables, plugs, connectors, and other such physical media. Non-limiting examples of media information include a part number, a serial number, a plug type, a conductor type, a cable length, cable polarity, a cable pass-through capacity, a date of manufacture, a manufacturing lot number, the color or shape of the plug connector, an insertion count, and testing or performance information. Device information refers to physical layer information pertaining to the communications panels, inter-networking devices, media converters, computers, servers, wall outlets, and other physical communications devices to which the media segments attach. Location information refers to physical layer information pertaining to a physical layout of a building or buildings in which the network is deployed.

[0034] In accordance with some aspects, one or more of the components (e.g., media segments, equipment, etc.) of the communications network are configured to store physical layer information pertaining to the component as will be disclosed in more detail herein. Some components include media reading interfaces that are configured to read stored physical layer information from the components. The physical layer information obtained by the media reading interface may be communicated over the network for processing and/or storage.

[0035] FIG. 1 is a block diagram of one example implementation of a communications management system **200** that includes PLI functionality as well as PLM functionality. The management system **200** comprises a plurality of connector assemblies **202** (e.g., patch panels, blades, optical adapters, electrical jacks, media converters, transceivers, etc.), connected to an IP network **218**. Each connector assembly **202** includes one or more ports **204**, each of which is configured to receive a media segment for connection to other media segments or equipment of the management system **200**. For the purposes of this disclosure, optical connector assemblies **202** and optical media segments will be described. In other implementations, however, electrical connector assemblies and media segments may be used.

[0036] At least some of the connector assemblies **202** are designed for use with optical cables that have physical layer information stored in or on them. The physical layer information is configured to be read by a programmable processor **206** associated with one or more connector assemblies **202**. In general, the programmable processor **206** communicates with memory of an optical cable using a media reading interface **208**. In some implementations, each of the ports **204** of the connector assemblies **202** includes a respective media reading interface **208**. In other implementations, a single media reading interface **208** may correspond to two or more ports **204**.

[0037] In FIG. 1, four example types of connector assembly configurations **210**, **212**, **214**, and **215** are shown. In the first connector assembly configuration **210**, each connector assembly **202** includes its own respective programmable processor **206** and its own respective network interface **216** that is used to communicatively couple that connector assembly **202** to an Internet Protocol (IP) network **218**. In the second type of connector assembly configuration **212**, connector assemblies **202** are grouped together in proximity to each other (e.g., in a rack, rack system, patch panel, chassis, or equipment closet). Each connector assembly **202** of the group includes its own respective programmable processor **206**. However, not all of the connector assemblies **202** include their own respective network interfaces **216**.

[0038] In the third type of connector assembly configuration **214**, some of the connector assemblies **202** (e.g., “masters”) in the group include their own programmable processors **206** and network interfaces **216**, while others of the connector assemblies **202** (e.g., “slaves”) do not include their own programmable processors **206** or network interfaces **216**. Each programmable processor **206** is able to carry out the PLM functions for both the connector assembly **202** of which it is a part and any of the slave connector assemblies **202** to which the master connector assembly **202** is connected via the local connections.

[0039] In the fourth type of connector assembly configuration **215**, each of the connector assemblies **202** in a group includes its own “slave” programmable processors **206**. Each slave programmable processor **206** is configured to manage the media reading interfaces **208** to determine if physical communication media segments are attached to the port **204** and to read the physical layer information stored in or on the attached physical communication media segments (if the attached segments have such information stored therein or thereon). Each of the slave programmable processors **206** in the group also is communicatively coupled to a common “master” programmable processor **217**. The master processor **217** communicates the physical layer information read from by the slave processors **206** to devices that are coupled to the IP network **218**. For example, the master programmable processor **217** may be coupled to a network interface **216** that couples the master processor **217** to the IP network **218**.

[0040] In accordance with some aspects, the communications management system **200** includes functionality that enables the physical layer information captured by the connector assemblies **202** to be used by application-layer functionality outside of the traditional physical-layer management application domain. For example, the management system **200** may include an aggregation point **220** that is communicatively coupled to the connector assemblies **202** via the IP network **218**. The aggregation point **220** can be

implemented on a standalone network node or can be integrated along with other network functionality.

[0041] The aggregation point **220** includes functionality that obtains physical layer information from the connector assemblies **202** (and other devices) and stores the physical layer information in a data store. The aggregation point **220** also can be used to obtain other types of physical layer information. For example, this information can be provided to the aggregation point **220**, for example, by manually entering such information into a file (e.g., a spreadsheet) and then uploading the file to the aggregation point **220** (e.g., using a web browser) in connection with the initial installation of each of the various items. Such information can also, for example, be directly entered using a user interface provided by the aggregation point **220** (e.g., using a web browser).

[0042] The management system **200** also may include a network management system (NMS) **230** includes PLI functionality **232** that is configured to retrieve physical layer information from the aggregation point **220** and provide it to the other parts of the NMS **230** for use thereby. The NMS **230** uses the retrieved physical layer information to perform one or more network management functions. In certain implementations, the NMS **230** communicates with the aggregation point **220** over the IP network **218**. In other implementations, the NMS **230** may be directly connected to the aggregation point **220**.

[0043] An application **234** executing on a computer **236** also can use the API implemented by the aggregation point **220** to access the PLI information maintained by the aggregation point **220** (e.g., to retrieve such information from the aggregation point **220** and/or to supply such information to the aggregation point **220**). The computer **236** is coupled to the IP network **218** and accesses the aggregation point **220** over the IP network **218**.

[0044] One or more inter-networking devices **238** used to implement the IP network **218** include physical layer information (PLI) functionality **240**. The PLI functionality **240** of the inter-networking device **238** is configured to retrieve physical layer information from the aggregation point **220** and use the retrieved physical layer information to perform one or more inter-networking functions. Examples of inter-networking functions include Layer 1, Layer 2, and Layer 3 (of the OSI model) inter-networking functions such as the routing, switching, repeating, bridging, and grooming of communication traffic that is received at the inter-networking device.

[0045] Additional details pertaining to example communications management system **200** can be found in U.S. application Ser. No. 13/025,841, filed Feb. 11, 2011, and titled “Managed Fiber Connectivity Systems,” the disclosure of which is hereby incorporated herein by reference.

[0046] FIG. 2 is a schematic diagram of one example connector assembly **110** configured to collect physical layer information from a connector arrangement **120** terminating a media segment **122**. The example connector assembly **120** of FIG. 2 is configured to connect segments of optical physical communications media in a physical layer management system. The connector assembly **110** includes a fiber optic adapter defining at least one connection opening **111** having a first port end **112** and a second port end **114**. A sleeve (e.g., a split sleeve) **103** is arranged within the connection opening **111** of the adapter **110** between the first and second port ends **112**, **114**. Each port end **112**, **114** is

configured to receive a connector arrangement as will be described in more detail herein.

[0047] A first example segment of optical physical communication media includes a first optical fiber 122 terminated by a first connector arrangement 120. A second example segment of optical physical communication media includes a second optical fiber 132 terminated by a second connector arrangement 130. The first connector arrangement 120 is plugged into the first port end 112 and the second connector arrangement 130 is plugged into the second port end 114. Each fiber connector arrangement 120, 130 includes a ferrule 124, 134 through which optical signals from the optical fiber 122, 132, respectively, pass.

[0048] The ferrules 124, 134 of the connector arrangements 120, 130 are aligned by the sleeve 103 when the connector arrangements 120, 130 are inserted into the connection opening 111 of the adapter 110. Aligning the ferrules 124, 134 provides optical coupling between the optical fibers 122, 132. In some implementations, each segment of optical physical communication media (e.g., each optical fiber 122, 132) carries communication signals. The aligned ferrules 124, 134 of the connector arrangements 120, 130 create an optical path along which the communication signals may be carried.

[0049] In some implementations, the first connector arrangement 120 may include a storage device 125 that is configured to store physical layer information (e.g., an identifier and/or attribute information) pertaining to the segment of physical communications media (e.g., the first connector arrangement 120 and/or the fiber optic cable 122 terminated thereby). In some implementations, the connector arrangement 130 also includes a storage device 135 that is configured to store information (e.g., an identifier and/or attribute information) pertaining to the second connector arrangement 130 and/or the second optic cable 132 terminated thereby.

[0050] In one implementation, each of the storage devices 125, 135 is implemented using an EEPROM (e.g., a PCB surface-mount EEPROM). In other implementations, the storage devices 125, 135 are implemented using other non-volatile memory device. Each storage device 125, 135 is arranged and configured so that it does not interfere or interact with the communications signals communicated over the media segments 122, 132.

[0051] In accordance with some aspects, the adapter 110 is coupled to at least a first media reading interface 116. In certain implementations, the adapter 110 also is coupled to at least a second media interface 118. In some implementations, the adapter 110 is coupled to multiple media reading interfaces. In certain implementations, the adapter 110 includes a media reading interface for each port end defined by the adapter 110. In other implementations, the adapter 110 includes a media reading interface for each connection opening 111 defined by the adapter 110. In still other implementations, the adapter 110 includes a media reading interface for each connector arrangement that the adapter 110 is configured to receive. In still other implementations, the adapter 110 includes a media reading interface for only a portion of the connector arrangement that the adapter 110 is configured to receive.

[0052] In some implementations, at least the first media reading interface 116 is mounted to a printed circuit board 115. In the example shown, the first media reading interface 116 of the printed circuit board 115 is associated with the

first port end 112 of the adapter 110. In some implementations, the printed circuit board 115 also can include the second media reading interface 118. In one such implementation, the second media reading interface 118 is associated with the second port end 114 of the adapter 110.

[0053] The printed circuit board 115 of the connector assembly 110 can be communicatively connected to one or more programmable processors (e.g., processors 216 of FIG. 1) and/or to one or more network interfaces (e.g., network interfaces 216 of FIG. 1). The network interface may be configured to send the physical layer information to a physical layer management network (e.g., see IP network 218 of FIG. 1). In one implementation, one or more such processors and interfaces can be arranged as components on the printed circuit board 115. In another implementation, one or more such processor and interfaces can be arranged on separate circuit boards that are coupled together. For example, the printed circuit board 115 can couple to other circuit boards via a card edge type connection, a connector-to-connector type connection, a cable connection, etc.

[0054] When the first connector arrangement 120 is received in the first port end 112 of the adapter 110, the first media reading interface 116 is configured to enable reading (e.g., by the processor) of the information stored in the storage device 125. The information read from the first connector arrangement 120 can be transferred through the printed circuit board 115 to a physical layer management network, e.g., network 218 of FIG. 1, etc. When the second connector arrangement 130 is received in the second port end 114 of the adapter 110, the second media reading interface 118 is configured to enable reading (e.g., by the processor) of the information stored in the storage device 135. The information read from the second connector arrangement 130 can be transferred through the printed circuit board 115 or another circuit board to the physical layer management network.

[0055] In some such implementations, the storage devices 125, 135 and the media reading interfaces 116, 118 each comprise three (3) leads—a power lead, a ground lead, and a data lead. The three leads of the storage devices 125, 135 come into electrical contact with three (3) corresponding leads of the media reading interfaces 116, 118 when the corresponding media segment is inserted in the corresponding port. In certain example implementations, a two-line interface is used with a simple charge pump. In still other implementations, additional leads can be provided (e.g., for potential future applications). Accordingly, the storage devices 125, 135 and the media reading interfaces 116, 118 may each include four (4) leads, five (5) leads, six (6) leads, etc.

[0056] FIGS. 4-5 illustrate an example implementation of a connector system 300 that can be utilized on a connector assembly (e.g., a communications panel) having PLI functionality as well as PLM functionality. One example connector assembly on which the connector system 300 can be implemented is a bladed chassis. Examples of bladed chassis can be found in U.S. application Ser. No. 13/025,750, filed Feb. 11, 2011, and titled “Communications Bladed Panel System,” the disclosure of which is hereby incorporated herein by reference in its entirety. The connector system 300 includes at least one example communications coupler assembly 310 and at least two connector arrangements 320.

[0057] The communications coupler assembly 310 is configured to be mounted to a connector assembly, such as a

communications blade or a communications panel. One or more connector arrangements 320, which each terminate at least one segment of communications media 325 (FIG. 4), are configured to communicatively couple to other segments of physical communications media at the coupler assembly 310 (e.g., see FIG. 3). Accordingly, communications data signals carried by a media segment 325 terminated by a first connector arrangement 320 can be propagated to another media segment (e.g., terminated by a second connector arrangement 320) through the communications coupler assembly 310.

[0058] In accordance with some aspects, each communications coupler assembly 310 is configured to form a single link between segments of physical communications media. For example, each communications coupler assembly 310 can define a single passage at which a first connector arrangement 320A is coupled to a second connector arrangement 320B (see FIG. 3). In accordance with other aspects, however, each communications coupler assembly 310 is configured to form two or more links between segments 325 of physical communications media.

[0059] In accordance with some aspects, each connector arrangement 320 is configured to terminate a single segment of physical communications media. For example, each connector arrangement 320 can include a single optical connector that terminate a single optical fiber 325 or a single electrical conductor. In one example implementation, each connector arrangement 320 includes a single SC-type fiber optic connector 320 that terminates a single optical fiber 325 (see FIG. 4). In other implementations, the connector 320 can be an LC-type, an ST-type, an FC-type, an LX.5-type, etc.

[0060] FIG. 4 is a front perspective view an example fiber optic connector arrangement 320 including an SC-type connector. The connector 320 includes an outer body 321 surrounding an inner body 322. The inner body 322 holds a ferrule 323, which retains an optical fiber 325. The outer body 321 is configured to move relative to the inner body 322 along a longitudinal axis L of the ferrule 323. The ferrule 323 also is configured to move within the inner body 322 against a spring bias. A boot 324 extends rearwardly from the outer connector body 321 to provide bend protection to the optical fiber 325. For example, the boot 324 may be secured between the outer body 321 and the inner body 322.

[0061] The outer housing 321 defines two slots 329 on opposite sides thereof through which raised portions of the inner housing 322 are visible. The outer housing 321 also defines a key 328 located on a side perpendicular to the sides containing the slots 329. The key 328 is configured to engage a keyway of coupler assembly 310 to properly position the connector 320 at a port of the coupler assembly 310. The outer body 321 also includes a knurled handle or other grip section at a rear of the outer body 321. In certain implementations, the grip section defines a textured surface (e.g., ridges).

[0062] Additional details regarding an example connector 320 can be found in U.S. Pat. No. 5,317,663, issued May 31, 1994 to Beard et al., and titled "One-Piece SC Adapter," the disclosure of which is hereby incorporated herein by reference in its entirety.

[0063] Each connector arrangement 320 is configured to store physical layer information. For example, a storage device 330 (FIGS. 7 and 8) may be installed on or in the fiber

optic connector 320. One example storage device 330 includes a printed circuit board 331 on which memory circuitry can be arranged. Electrical contacts 332 also may be arranged on the printed circuit board 331 for interaction with a media reading interface of the communications coupler assembly 310 (described in more detail herein). In one example implementation, the storage device 330 includes an EEPROM circuit 333 arranged on the printed circuit board 331. In other implementations, however, the storage device 330 can include any suitable type of non-volatile memory.

[0064] The storage device 330 shown in FIGS. 7 and 8 includes generally planar contacts 332 positioned on a generally planar circuit board 331. In the example shown, the contacts extend over an elongated dimension of the board 331. In other implementations, however, the board 331 may have a square geometry or the contacts may be otherwise arranged on the board. Memory 333 (FIG. 8) of the storage device 330, which is located on the non-visible side of the board in FIGS. 4 and 7, is accessed by engaging the tops of the contacts 332 with one or more electrically conductive contact members of a media reading interface (e.g., media reading interface 116 of FIG. 2). In certain implementations, the contact member slides or wipes across the memory contacts 332.

[0065] In some implementations, the contacts 332 have the same length. In other implementations, one or more of the contacts 332 may have different lengths. In some implementations, the contacts 332 have the same shape. For example, in some implementation, the contacts 332 may be generally rounded at one or both ends of the contact members. In other implementations, one or more of the contacts 332 may have different shapes. For example, in certain implementations, some of the contacts 332 are straight and some of the contacts 332 are generally L-shaped. In one example implementation, the L-shaped contacts may be longer than the rounded end contacts. In some implementations, the contacts 332 may be positioned in a staggered configuration. In other implementations, the contacts 332 may be laterally aligned.

[0066] As shown in FIGS. 4 and 5, the inner body 322 of the connector 320 may define a recessed section 326 in which the storage device 330 may be disposed. In some implementations, the cavity 326 faces away from the key 328 of the outer body 321. In another implementation, the cavity 326 may be provided on the same side as the key 328. In some implementations, the cavity 326 is formed at a front, center location of the connector 320. For example, the cavity 326 may open to a front side of the connector 320. In some such implementations, a front edge of the circuit board 331 may be disposed flush with a front edge of the inner body 322 when the storage device 330 is mounted at the cavity 326. In other implementations, the cavity 326 may be formed at a front location laterally offset from the center.

[0067] In the example shown, the cavity 326 is formed by a depression in a side of the inner body 322 (e.g., the side opposite the key 328). The depression is generally sized and configured to receive the printed circuit board 331 of the storage device 330. In some implementations, the cavity 326 has a stepped configuration to facilitate positioning of the storage device 330. For example, a well may be formed at one location in the depression. The well is sufficiently deep to accommodate an EEPROM circuit 333 coupled to one side of the circuit board 331. In some implementations, the

depression may be sufficiently deep to enable electrical contacts 332 provided on the circuit board 331 to be generally flush with the outer surface of the inner body 322.

[0068] In other implementations, however, the depression is shallow so that a top of the printed circuit board 331 extends outwardly from the inner body 322. In such implementations, the outer body 321 may define a cut-out 327 that is sized to accommodate the storage device 330 (e.g., see FIGS. 4 and 5). The cut-out 327 aligns with the depression 326 in the inner body so that the cut-out 327 accommodates the storage device 330. For example, the cut-out 327 may be formed by removing a front, center portion of the outer body 321 to enable the storage device 330 to extend through the outer body 321. In certain implementations, the cut-out 327 extends sufficiently rearward to accommodate rearward movement of the storage device 330 relative to the outer body 321 (e.g., when the inner body 322 moves relative to the outer body 321).

[0069] FIGS. 3 and 6 show one example implementation of a communications coupler assembly 310 implemented as a fiber optic adapter. The example communications coupler assembly 310 includes an adapter housing 311 defining one or more passages configured to align and interface two or more fiber optic connectors 320. In other example implementations, however, one or more passages can be configured to communicatively couple together a fiber optic connector 320 with a media converter (not shown) to convert the optical data signals into electrical data signals, wireless data signals, or other such data signals. In still other implementations, the communications coupler assembly 310 can include an electrical termination block that is configured to receive punch-down wires, electrical plugs (e.g., for electrical jacks), or other types of electrical connectors.

[0070] The example adapter housing 311 includes opposing side walls interconnected by at least one end wall. The side walls and end walls each extend between a front end and a rear end. The adapter housing 311 defines one or more axial passages extending between the front and rear ends. Each passage defines a first port 313 and a second port 314 at the front and rear ends, respectively. Each port 313, 314 is configured to receive a connector 320. In the example shown, the adapter housing 311 defines a single axial passage. In other implementations, however, the adapter housing 311 may define one, two, three, six, eight, ten, twelve, sixteen, or even more axial passages.

[0071] Sleeves (e.g., split sleeves) 319 may be positioned within the axial passages to receive and align the ferrules 323 of fiber optic connectors 320 (see FIG. 6). In some implementations, the sleeve 319 is monolithically formed with the adapter housing 311. For example, in some implementations, one of the end walls of the adapter housing 311 defines an opening 312 leading to the axial passage (see FIG. 3). The opening 312 in the end wall may enable an injection molding machine access to the axial passage to form the sleeve 319. A cover 315 may be coupled (e.g., latched, welded, fastened, adhered, etc.) to the adapter housing 311 to close the opening 312 and protect the interior of the adapter housing 311. In other implementations, the sleeve 319 is formed separately from the adapter housing 311 and subsequently inserted into the axial passage through the opening 312. In still other implementations, neither of the end walls defines an opening 312. Rather, the sleeve 319 may be inserted into the axial passage through one of the ports 313, 314.

[0072] One or more guides may be defined at an interior of adapter housing 311. The guides, which extend longitudinally along the interior corners of the axial passage, guide the fiber optic connector 320 through the port 313, 314. In certain embodiments, the guides may define ramped entry surfaces to facilitate insertion of the connector 320 within the adapter passage. One of the end walls of the adapter housing 311 defines at least one keyway 317 sized and shaped to receive a corresponding key 328 of the SC-type fiber optic connector 320 (see FIG. 6). In certain implementations, a keyway 317 is defined in the end wall at both ports 313, 314 (e.g., see FIG. 6).

[0073] In some implementations, flanges may extend outwardly from the side walls of the adapter housing 311 (see FIG. 3). The flanges aid in supporting the adapter housing 311 on or against a planar surface, such as that of a bulkhead. In some implementations, one or both side walls of the adapter housing 1210 also include a flexible cantilever arm defining outwardly protruding tabs that are configured to cooperate with the flanges to capture the adapter housing 311 against a bulkhead. In other implementations, the side walls of the adapter housing 311 define solid surfaces. In still other implementations, recesses may be provided in the side walls to permit the use of alternative fasteners, such as a flexible clip.

[0074] The coupler assembly 310 includes one or more media reading interfaces 318 (see FIG. 6). Each media reading interface 318 is configured to acquire the physical layer information from the storage device 330 of a fiber optic connector 320 plugged into the fiber optic adapter 310. For example, in one implementation, the adapter housing 310 can hold or retain a media reading interface 318 for each passage. In another implementation, the adapter housing 310 can hold or retain a media reading interface 318 for each port 313, 314 of each passage. For example, the adapter 310 shown in FIG. 6 includes a first media reading interface 318 associated with the front port 313 of the passage and a second media reading interface 318 associated with the rear port of the passage. In still other implementations, the adapter housing 310 can include a media reading interface 318 associated with each set of passages that accommodate a duplex connector arrangement 310. In other implementations, the adapter housing 310 can include any desired combination of front and rear media reading interfaces 318.

[0075] In certain implementations, the orientation of the first media reading interface 318 is flipped 180° from the orientation of the second media reading interface 318. In some implementations, the first media reading interface 318 is laterally offset from the second media reading interface 318. For example, the first and second media reading interfaces 318 may be positioned side-by-side. In other implementations, the first and second media reading interfaces 318 may be axially aligned. In some implementations, the first and second media reading interfaces 318 may be laterally aligned. In other implementations, the first media reading interfaces 318 may be offset towards the front of the adapter housing 310 and the second media reading interface 318 may be offset towards the rear of the adapter housing 310.

[0076] In general, each media reading interface 318 is formed from one or more contact members 340 (FIG. 9). In some implementations, the media reading interface 318 includes at least a first contact member 340 that transfers power, at least a second contact member 340 that transfers

data, and at least a third contact member **340** that provides grounding. In one implementation, the media reading interface **318** includes a fourth contact member **340**. In other implementations, the media reading interface **318** include greater or fewer contact members **340**.

[0077] In some implementations, the cover **315** defines slots **316** configured to receive one or more contact members **340**. At least a portion of each slot **316** extends through the cover **315** to the axial passage of the adapter housing **311**. In some implementations, the entirety of each slot **316** extends through the cover **315** from top to bottom. In other implementations, only portions of the slot **316** extend from the top to the bottom of the cover **315**. For example, each slot **316** may define a recess in the top surface of the cover **315** in which the contact members can be positioned. Openings defined in a bottom of the cover **315** enable portions of the contact members **340** to extend into a respective adapter passageway.

[0078] The media reading interfaces **318** are positioned in the slots **316** of the cover **315** to connect a storage device **330** of a connector **3210** received at the adapter housing **310** with a circuit board coupled to the adapter housing **310**. For example, a circuit board may be secured (e.g., via fasteners) to the adapter housing **310** so as to extend over the slots **316** of the cover **315**. Each media reading interface **318** held by the cover **315** extends between the circuit board and a respective axial passage of the adapter housing **310**. Portions of each contact member **340** engage tracings and contacts on the circuit board. Other portions of the contact members **340** engage the electrical contacts **332** of the storage members **330** attached to any connector **320** plugged into the adapter housing **310**. The circuit board electrically connects to a data processor and/or to a network interface (e.g., the processor **217** and network interface **216** of FIG. 1). It is further to be understood that multiple adapter housings **310** can be connected to the printed circuit board within a connector assembly (e.g., a bladed panel). A processor coupled to the circuit board can access the memory **333** of each connector arrangement **320** coupled to the adapter housing **310** through corresponding ones of the contact members **340**, **332**.

[0079] In certain implementations, the slots **316** of the cover **315** are sized to hold individual contacts **340**. The adapter housing **311** has internal structure that holds the contacts **340** in the slots **316**. The slots **316** position the contact members **340** in alignment with the contact pads **332** of a connector storage device **330** mounted to a connector **320** received at the adapter housing **310**. The slots **316** may be separated by intermediate walls to inhibit touching between adjacent contact members **340**. In other implementations, all of the contact members **340** in a single media reading interface **318** may be retained in a single slot **316**. In certain implementations, the slots **316** are sized to accommodate multiple contact members **340** mounted to a support body.

[0080] In some implementations, the contact members **340** of a single media reading interface **318** are positioned in a staggered configuration. For example, alternating ones of the contact members **340** are moved axially forward or axially rearward. In some implementations, the slots **316** accommodating the staggered contact members **340** also are staggered (e.g., in a front to rear direction). In other implementations, however, the slots **316** may have a common length. In still other implementations, the front and rear ends of the

contact members **340** of a single media reading interface **318** are transversely aligned within similarly transversely aligned slots **316**.

[0081] In some implementations, the cover **315** is sufficiently thick to enable the media reading interface contacts **340** to be substantially positioned in the cover **315**. In some implementations, the material height of the cover **315** is at least 0.76 mm (0.03 inches). Indeed, in some implementations, the material height of the cover **315** is at least 1.02 mm (0.04 inches). In certain implementations, the material height of the cover **315** is at least 1.27 mm (0.05 inches). In some implementations, a height **H1** (FIG. 27) of the adapter housing **310** is at least 9.4 mm. In certain implementations, the height **H1** is at least 10 mm. Indeed, in certain implementations, the height **H1** is at least 10 mm. In one example implementation, the height **H1** is about 10.4 mm.

[0082] In other implementations, the slots **316** for accommodating the media reading interface **318** may be defined in the adapter housing **311** instead of in the cover **315**. In certain implementations, the slots **316** may be defined in a side wall of the adapter housing **311** located opposite the cover **315**. Alternatively, certain types of adapters **310** do not include a cover **315**. Some such example implementations include a monolithic adapter housing. Other such example implementations include two-piece (e.g., front and rear) housings. In other implementations, the slots **316** may be defined in two or more side walls of the adapter housing **311**.

[0083] One example type of contact member **340** is shown in FIG. 9. Each contact member **340** includes at least two moveable (e.g., flexible) contact sections defining contact surfaces. In certain implementations, one or more contact members **340** include three moveable (e.g., flexible) contact sections. The flexibility of the contact sections provides tolerance for differences in spacing between the contact member **340** and the adapter printed circuit board. Certain types of contact members **340** also include at least one stationary contact having a contact surface. For example, each contact member **340** may have two stationary contact sections. The ability of the first contact section to flex relative to the stationary contact provides tolerance for placement of the contact member **340** relative to the circuit board.

[0084] When the contact member **340** is mounted to the adapter **310**, the first moveable contact section and the stationary contact sections extend through the adapter slot **316** to engage the adapter circuit board. The second moveable contact section is configured to extend into the axial passage of the adapter housing **310** and engage a connector **320** plugged into one of the ports **313**, **314**. If a storage device **330** is installed on the connector **320**, then the second contact surface is configured to engage the contact pads **332** of the storage device **330**.

[0085] In certain implementations, the third moveable contact section selectively extends through the slot **316** and engages the adapter circuit board. For example, the third contact section may be configured to engage the circuit board only when a connector **320** is plugged into the port **313**, **314** corresponding with the contact member **340**. The third contact section may be resiliently biased to extend within the adapter housing **310**. For example, certain types of contact members **340** may include a resilient section that transfers force applied to second moveable contact section to the third moveable contact section. Accordingly, the resilient section may transfers a force pushing the second section

towards the slot 316 to the third section, thereby pushing the third contact section through the slot 316 (e.g., toward the circuit board).

[0086] In certain implementations, a circumferential edge of each contact member 340 defines the contact surface of each contact section. In some implementations, the edge has a substantially continuous thickness. In various implementations, the thickness ranges from about 0.05 inches to about 0.005 inches. In some implementation, the thickness is less than about 0.012 inches. In one example implementation, the thickness is about 0.008 inches. In other implementations, the thickness may vary across the body of the contact member 340.

[0087] In one implementation, the contact member 340 is formed monolithically (e.g., from a continuous sheet of metal or other material). For example, in some implementations, the contact member 340 may be manufactured by cutting a planar sheet of metal or other material. In other implementations, the contact member 340 may be manufactured by etching a planar sheet of metal or other material. In other implementations, the contact member 340 may be manufactured by laser trimming a planar sheet of metal or other material. In still other implementations, the contact member 340 may be manufactured by stamping a planar sheet of metal or other material. In still other implementations, the contact member 340 may be formed from wire stock.

[0088] The contact member 340 shown and described herein is formed from a single piece. In other implementations, however, two or more separate pieces may operate together to perform the functions of the contact member 340. For example, a first piece may form the first moveable contact section and a second piece may form the third moveable contact section. Either of the pieces may form the second moveable contact section. Insertion of a connector 320 into a respective port of the adapter housing 310 may push one of the pieces into electrical contact with the other of the pieces to electrically connect the first and second contact sections.

[0089] When a connector 320 is fully inserted into the adapter housing 310 at one of the ports 313, 314, the connector ferrule 323 is received within one end of the ferrule sleeve 319 inside the adapter housing 310. In some implementations, the connector 320 may be releasably locked to the housing 310. For example, flexible latching hooks disposed within the interior of the housing 310 may engage the slots 329 defined in the outer body 321 of the connector 320 to releasably hold the connector 320 at the adapter port 313, 314. When the connector 320 includes a storage device 330, the contacts 332 of the storage device 330 are configured to align with the slots 316 defined in the adapter housing 310. Accordingly, the media reading interface contact members 340 held within the slots 316 align with the contacts 332 of the connector storage device 330 to establish an electrical connection between the storage device 330 and the adapter circuit board.

[0090] In accordance with some aspects, each media reading interface 318 of the adapter 310 is configured to detect the presence of a connector arrangement 320 plugged into a port 313, 314 of the adapter housing 310. For example, the contact members 340 of a media reading interface 318 can function as presence detection sensors or trigger switches. In some implementations, the contact members 340 of a media reading interface 318 are configured to form a complete

circuit with the adapter circuit board only when a connector 320 is plugged into a respective port 313, 314. For example, each contact member 340 may contact the circuit board only after being pushed toward the circuit board by a connector 320 received at the adapter 310. In other example implementations, the connector 320 may push the contact members 340 away from the circuit board or from a shorting rod. In accordance with other aspects, however, certain types of contact members 340 may form a complete circuit with the circuit board regardless of whether a connector 320 is received at the adapter 310.

[0091] As discussed above, a processor (e.g., processor 217 of FIG. 2) or other such equipment also can be electrically coupled to the printed circuit board. Accordingly, the processor can communicate with the memory circuitry 333 on the connector storage device 330 via the contact members 340 and the printed circuit board. In accordance with some aspects, the processor is configured to obtain physical layer information from the connector storage device 330. In accordance with other aspects, the processor is configured to write physical layer information to the connector storage device 330. In accordance with other aspects, the processor is configured to delete physical layer information from the connector storage device 330. In still other implementations, the processor detects the presence or absence of a connector 320 at each port 313, 314.

[0092] When removing the fiber optic connector 320, the slidable outer body 321 of the connector 320 is slid axially relative to the inner body 322 away from the adapter housing 310 until the flexible latching hooks of the adapter housing 310 are released from the slots 329 defined on the outer body 321 of the connector 320. When released, the connector 320 may be slide rearwardly through the port 313, 314 to remove the connector 320 from the adapter housing 310.

[0093] Removing the connector 320 from the port 313, 314 releases the second moveable contact portion of the contact member 340, thereby allowing the third moveable contact portion to move back to the initial position. Dropping the third moveable contact portion disengages the third contact surface from the circuit board, thereby interrupting the circuit created by the contact member 340. Interrupting the circuit enables a processor connected to the circuit board to determine that the connector 320 has been removed from the port 313, 314. In some implementations, the storage device 330 is not moved out of alignment with the media reading interface 318 until the connector 320 is released. In other implementations, however, moving the outer body 321 rearwardly applies sufficient force to the inner body 322 to move the storage device 330 out of alignment with the media reading interface 318.

[0094] FIGS. 10 and 11 illustrate another example implementation of a connector system 400 (FIG. 11) that can be utilized on a connector assembly (e.g., a communications panel) having PLI functionality as well as PLM functionality. The connector system 400 includes at least one example optical adapter 410 and at least two optical connector arrangements 420. The optical connector 420 shown is an SC-type optical connector having an outer body 421 that is axially moveable relative to an inner body 422. The inner body 422 holds a ferrule 423 through which at least one optical fiber extends. The optical connector 420 shown in FIGS. 10-12 is substantially the same as the optical connector 320 disclosed above, except for certain features discussed below.

[0095] As shown in FIGS. 10 and 11, a storage device 430 is coupled to the connector 420 at a recessed portion 426 of the inner body 422. However, the location on the inner body 422 at which the storage device 430 is disposed is rearwardly offset compared to the location of the storage device 330 on the inner body 322 of the optical connector 320 disclosed above. For example, a front edge of the storage device 430 is rearwardly offset from the front edge of the inner body 422. In certain implementations, the recess does not extend sufficiently forward to open through the front edge of the inner body 422.

[0096] The optical adapter 410 shown in FIG. 11 is substantially the same as the optical adapter 310 disclosed above, except for certain features discussed below. The axial positioning of the storage device 330, 430 on the inner body 322, 422 of the connector 320, 420 determines or is influenced by the axial positioning of the media reading interfaces 318 in the adapter 310, 410. Accordingly, the slots 416 defined in the adapter 410 shown in FIG. 11 are spaced farther apart in the axial direction as compared to the slots 316 of the adapter 320 shown in FIG. 3.

[0097] FIG. 12 illustrates another example storage device 450 disposed on the optical connector 420 of FIG. 10. The storage device 450 is offset rearwardly from a front of the inner body 422 of the connector 420. In the example shown, the storage device 450 includes contacts 452 disposed on one side of a printed circuit board 451. In certain implementations, the memory (e.g., EEPROM) is disposed at an opposite side of the circuit board 451. In other implementations, the memory can be disposed on the same side of the circuit board 451 as the contacts 452.

[0098] In certain implementations, the contacts 452 are uniformly disposed on the board 451. In the example shown in FIG. 12, however, two of the contacts are shorter than another two of the contacts. Also in the example shown, two of the contacts are L-shaped and two of the contacts extend in a straight line. In other implementations, however, other types of contacts 452 may be disposed on the circuit board 451. For example, square contacts may be arranged in a grid pattern.

[0099] The embodiments described above make use of a contact-based interface for reading from and/or writing information to a storage device 330 attached to the connector 320, 420. In accordance with other aspects of the disclosure, however, contact-less or wireless interfaces also can be used with the optical systems described above. In some such alternative embodiments, RFID technology is used. In one such RFID embodiment, the storage device 330, 430 attached to the connector 320, 420 is implemented as an RFID tag. In such an embodiment, the storage device 330 does not include an EEPROM 333 and contacts 332. Rather, the RFID tag includes memory and an antenna.

[0100] Also, in such an embodiment, the adapter contacts 340 of the media reading interfaces 318, 418 are replaced with an RFID coil or antenna. The RFID coils in the adapter ports are connected to one or more RFID readers (using a suitable multiplexing mechanism if needed). In order to read information from an RFID tag, the RFID reader outputs an RF interrogation signal via the RFID coil associated with the appropriate adapter port. For example, the RFID reader may output such an RF interrogation signal in response to an optical connector 320, 420 being inserted into the adapter port 313, 314, 413, 414.

[0101] The RFID tag on the optical connector receives the RFID interrogation signal, which causes the RFID tag to power on, to retrieve information (e.g., physical layer information) stored in the RFID tag, and to transmit the read information. The transmission from the RFID tag is received by the RFID reader using the RFID coil in the adapter port. The information included in such transmissions can be provided to a controller included in the patch panel or other optical system associated with the adapter 310, 410. The information also can be communicated to the aggregation point 220 in an IP network 218 as described above. Other contact-less or wireless embodiments can be implemented in other ways.

[0102] FIGS. 13-15 illustrate another example optical connector 500 having a storage device 525. The optical connector 500 has a front 501, a rear 502, a first side 503, a second side 504, a top 505, and a bottom 506. The connector 500 includes an outer body 510 defining grip surfaces 514 and a connection mechanism 516. For example, a grip surface 514 and a connection component can be formed on each side 503, 504 of the outer body 510. An inner body is configured to move (e.g., slide) relative to the outer body 510. An optical fiber tip is held at the inner body and accessible from the front 501 of the connector 500 (e.g., via a ferrule). In the example shown, a dust cap 515 covers the optical fiber tip. A strain-relief boot 518 can extend rearwardly from the outer body 510.

[0103] In some implementations, the storage device 525 is disposed internally within the connector body 510. For example, the connector body 510 can define a storage compartment 520 to hold the storage device 525. As shown in FIG. 14, the storage compartment 520 includes a cavity 521 extending into the connector body 510 from the front 501. In an example, the cavity 521 is defined in the connector body 510 between the top 505 of the body 510 and the internal passage in which the optical fiber is disposed. The connector body 510 forms shelves 522 that partially define the cavity 521. A notch 523 can be provided in the connector body 510 at the front 501 to be continuous with the cavity 521.

[0104] In certain implementations, the shelves 522 are separated by a gap 524 (see FIG. 15). The inner body also defines a gap 519. The gaps 519, 524 provide sufficient room to inhibit interference between the shelves 522 and other components. In some implementations, the gaps 519, 524 enable components within an optical adapter to fit with the connector 500. For example, in certain implementations, the gaps 519, 524 provide sufficient room for a split sleeve or other structure disposed within an optical adapter to surround the optical tip of the connector 500 when the connector 500 is received at a port of the optical adapter. In other implementations, the gaps 519, 524 provide sufficient room for a dust cap to be mounted over the optical tip.

[0105] The storage device 525 is configured to be advanced into the cavity 521 from the front 501 of the connector 500 (see FIG. 14). For example, the storage device 525 can be slid edge-wise into the cavity 521 along the shelves 522. A plug piece 526 can be coupled to the connector body 510 to close the storage device 525 within the cavity 521. For example, the plug piece 526 can be welded, glued, overmolded, or otherwise secured to the body 510. The plug piece 526 includes a front member 527 that extends across the opening to the cavity 521, two arms 528 extending rearwardly from the front member 527, and

a lug 529 that extends outwardly from the front member 527. The arms 528 are sized and configured to slide into the cavity 521 on opposite sides of the storage device 525. The lug 529 is sized and configured to fit within the notch 523. In an example, the storage device 525 can be glued into position within the cavity 525. In another example, the storage device 525 can be held into position using a vacuum until the plug piece 526 is added.

[0106] In some implementations, the storage device 525 includes an RFID tag. In such implementations, the storage device 525 can be fully sealed within the connector body 510. In other implementations, the storage device 525 includes a circuit board including memory and contact pads. In such implementations, openings are defined in the top 505 of the connector body 500 to provide access to the contact pads.

[0107] In other implementations, a cavity can be defined in the top surface 505 of the connector body 510. The storage device 525 can be disposed within the cavity. A cover can be added to close the cavity. In an example, the storage device 525 can be glued into position within the cavity. In another example, the storage device 525 can be held into position using a vacuum until a cover is added. For example, the cavity section of the connector body 510 and storage device 525 can be overmolded (e.g., using injection molded plastic) to close the cavity. In certain implementations, the storage device 525 includes an RFID tag that can be sealed within the cavity by the cover. In other implementations, the storage device 525 can include a circuit board including memory and contact pads. In such implementations, the contact pads are left accessible through the cover. For example, the contact pads can be pressed against the mold during an overmolding process to prevent the contact pads from being overmolded.

[0108] FIGS. 16 and 17 illustrate various example LC connectors 600, 650 having rear slots sized and configured to hold a storage device (e.g., an RFID tag, a circuit board and EEPROM, etc.). For example, the LC connector 600 includes a single-piece body 610 including a latch 615 for securing the connector 600 to an adapter. The body 610 also includes a trigger 616 to facilitate depression of the latch 615. A distal tip of an optical fiber protrudes from a front of the body 610 and an optical cable extends from a rear of the body 610. A strain-relief boot can be mounted to the rear of the body 610. The body 610 defines a slot 620 leading to a cavity defined in the body 610 of the connector 600. In an example, the cavity opens into a longitudinal bore extending through the connector body 610. In another example, the cavity is separate from the bore. A storage device can be inserted edge-wise within the cavity and the slot 620 can be closed. In an example, the slot 620 can be overmolded shut. In another example, a plug can be inserted into the slot 620. In another example, the boot can cover the slot 620.

[0109] FIG. 17 shows an LC connector 650 having a two-piece housing including a front housing piece 652 and a rear housing piece 654. The front housing piece 652 includes a latch 665 and the rear housing piece 654 includes a trigger 666. In some implementations, a slot (e.g., slot 620) can be defined in the rear housing piece 654. The slot leads to a cavity in the rear housing piece 654. The storage device can be inserted edge-wise within the cavity and the slot can be sealed to close the storage device within the cavity. In an example, the slot can be overmolded shut. In another

example, a plug can be inserted into the slot. In another example, the boot can cover the slot.

[0110] The above specification, examples and data provide a complete description of the manufacture and use of the composition of the invention. Since many implementations can be made without departing from the spirit and scope of the invention, the invention resides in the claims hereinafter appended.

1-4. (canceled)

5. A fiber optic connector comprising:

a first connector housing;

an optical fiber extending through the first connector housing;

a second connector housing that is movably coupled to the first connector housing so that the first connector housing is slidable relative to the second connector housing; and

a radio-frequency identification device mounted to one of the first and second connector housings.

6. The fiber optic connector of claim 5, wherein the radio-frequency identification device is mounted to the first connector housing.

7. The fiber optic connector of claim 5, wherein the radio-frequency identification device is mounted to the second connector housing.

8. The fiber optic connector of claim 5, wherein the second connector housing at least partially surrounds the first connector housing.

9. The fiber optic connector of claim 8, wherein the radio-frequency identification device is mounted to the first connector housing.

10. The fiber optic connector of claim 8, wherein the radio-frequency identification device is mounted to the second connector housing.

11. The fiber optic connector of claim 5, wherein the fiber optic connector is an SC connector, wherein the first connector housing is an inner housing; and wherein the second connector housing is an outer grip housing.

12. The fiber optic connector of claim 5, wherein the radio-frequency identification device is exposed at an exterior of the fiber optic connector.

13. The fiber optic connector of claim 5, wherein the radio-frequency identification device is embedded within the fiber optic connector.

14. The fiber optic connector of claim 5, further comprising a ferrule being held by the first connector housing, the ferrule holding and providing access to the optical fiber.

15. A fiber optic connector configured to be received at an optical adapter, the fiber optic connector comprising:

an inner body configured to retain a ferrule that extends longitudinally through the inner body;

an outer body slideably received about the inner body, the outer body defining a cavity opening in a forward-facing slot;

a storage device disposed in the recess of the inner body, at least a portion of the storage device extending above an outer surface of the inner body and at least partially through the cut-out of the outer body, the storage device including memory configured to store physical layer information, the storage device also including a transmission member for communicating information from memory to a data management system;

a plug piece sized to close the slot defined in the outer body.

16. The fiber optic connector of claim **15**, wherein the plug piece is formed by overmolding the outer body at the slot.

17. The fiber optic connector of claim **15**, wherein the plug piece includes a separate part that is attached to the outer body.

18. The fiber optic connector of claim **17**, wherein the plug piece is welded to the outer body.

19. The fiber optic connector of claim **17**, wherein the plug piece is glued to the outer body.

20. The fiber optic connector of claim **15**, wherein the cavity of the outer body is partially defined by two shelves separated by a gap facing the inner body.

21. The fiber optic connector of claim **20**, wherein the inner body defines a channel that extends longitudinally along an exterior surface of the inner body in alignment with the gap between the two shelves.

22. The fiber optic connector of claim **15**, wherein the storage device includes an RFID tag.

23. The fiber optic connector of claim **15**, wherein the storage device includes a circuit board and EEPROM.

* * * * *