



PCT

- | | |
|---|--|
| <p>(51) International Patent Classification:
 <i>E21B 19/00</i> (2006.01) <i>E21B 19/14</i> (2006.01)</p> | <p>(74) Agent: EGBERT, John, S.; Egbert Law Offices PLLC,
 412 Main St., 7th Floor, Houston, TX 77002 (US).</p> |
| <p>(21) International Application Number:
 PCT/US2009/062220</p> | <p>(81) Designated States (<i>unless otherwise indicated, for every kind of national protection available</i>): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.</p> |
| <p>(22) International Filing Date:
 27 October 2009 (27.10.2009)</p> | |
| <p>(25) Filing Language: English</p> | |
| <p>(26) Publication Language: English</p> | |
| <p>(30) Priority Data:
 12/259,245 27 October 2008 (27.10.2008) US</p> | |
| <p>(71) Applicant (<i>for all designated States except US</i>): T&T ENGINEERING SERVICES [US/US]; 13430 Northwest Freeway, Suite 204, Houston, TX 77040 (US).</p> | <p>(84) Designated States (<i>unless otherwise indicated, for every kind of regional protection available</i>): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,</p> |
| <p>(72) Inventor; and</p> | |
| <p>(71) Applicant : ORGERON, Keith, J. [US/US]; 13430 Northwest Freeway, Suite 204, Houston, TX 77040 (US).</p> | |

[Continued on next page]

- (54) Title:** PIPE HANDLING APPARATUS WITH ARM STIFFENING




FIG. 10

- (57) Abstract:** A pipe handling apparatus (10) has a supporting structure (16), an arm (24) pivotally interconnected to the supporting structure (16) such that the supporting structure (16) and the arm (24) are movable between a first position and a second position within a single degree of freedom, and a stiffener cooperative with the arm (24) when the arm (24) and the supporting structure (16) are in the second position. The stiffener applies a mechanical resistance to the arm (24) in the second position. The second position is at an end of the travel of the supporting structure (16) and the arm (24). The stiffener applies a variable resistance to the arm (24) as the arm (24) moves from the first position to the second position. This variable resistance is at its greatest when the arm (24) is in the second position.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, **Published:**
ML, MR, NE, SN, TD, TG).

— *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*

PIPE HANDLING APPARATUS WITH ARM STIFFENING

FIELD OF THE INVENTION

[0001] The present invention relates to a tubular, or pipe, handling apparatus and casing stabbing apparatus. More particularly, the present invention relates to a pipe handling apparatus for moving a pipe from a horizontal orientation to a vertical orientation. Additionally, the present invention relates to pipe handling apparatus for installing pipes and casing upon a drilling rig. The present invention also relates to pipe handling apparatus that moves the pipe with a single degree of freedom. The present invention further relates to stiffening systems for preventing springback when loads are released.

BACKGROUND OF THE INVENTION

[0002] Drill rigs have utilized several methods for transferring tubular members from a pipe rack adjacent to the drill floor to a mousehole in the drill floor or the well bore for connection to a previously transferred tubular or tubular string. The term "tubular" or "pipe" as used herein includes all forms of drill pipe, drill collars, casing, liner, bottom hole assemblies (BHA), and other types of tubulars known in the art.

[0003] Conventionally, drill rigs have utilized a combination of the rig cranes and the traveling system for transferring a tubular from the pipe rack to a vertical position above the center of the well. The obvious disadvantage with the prior art systems is that there is a significant manual involvement in attaching the pipe elevators to the tubular and moving the pipe from the drill rack to the rotary table. This manual transfer operation in the vicinity of workers is potentially dangerous and has caused numerous injuries in drilling operations. Further, the hoisting system may allow the tubular to come into contact with the catwalk or other portions of the rig as the tubular is transferred from the pipe rack to the drill floor. This can damage the tubular and may affect the integrity of the connections between successive tubulars in the well.

[0004] One method of transferring pipe from the rack to the well platform comprises tying one end of a line on the rig around a selected pipe on the pipe rack. The pipe is thereafter lifted up onto the platform and the lower end thereof is placed into the mousehole. The mousehole is simply an upright, elongate cylindrical container adjacent to the rotary table which supports the pipe temporally. When it is necessary to add the pipe to the drill string, slips are secured about the drill

string on the rotary table thereby supporting the same in the well bore. The pipe is disconnected from the traveling equipment, and the elevators, or the kelly, are connected to the pipe in the mousehole. Next, the traveling block is raised by positioning the pipe over the drill string. Tongs are used to secure the pipe to the upper end of the drill string. The drill pipe elevators suspend the drill pipe from a collar, which is formed around one end of the pipe and does not clamp the pipe, thereby permitting rotational pipe movement in order to threadably engage the same to the drill string.

[0005] A prior art technique for moving joints of casing from racks adjacent to the drilling rig comprises tying a line from the rig onto one end of a selected casing joint on the rack. The line is raised by lifting the casing joint up a ramp leading to the rig platform. As the rope lifts the casing from the rack, the lower end of the casing swings across the platform in a dangerous manner. The danger increases when a floating system is used in connection with drilling. Because the rope is tied around the casing at one end thereof, the casing does not hang vertically, but rather tilts somewhat. A man working on a platform elevated above the rig floor must hold the top of the casing and straighten it out while the casing is threaded into the casing string which is suspended in the well bore by slips positioned on the rotary table.

[0006] It is desirable to be able to grip casing or pipe positioned on a rack adjacent a drilling well, move the same into vertical orientation over the well bore, and thereafter lower the same onto the string suspended in the well bore.

[0007] In the past, various devices have been created which mechanically move a pipe from a horizontal orientation to a vertical orientation such that the vertically oriented pipe can be installed into the well bore. Typically, these devices have utilized several interconnected arms that are associated with a supporting structure. In order to move the pipe, a succession of individual movements of the levers, arms, and other components of the supporting structure must be performed in a coordinated manner in order to achieve the desired result. Typically, a wide variety of hydraulic actuators are connected to each of the components so as to carry out the prescribed movement. A complex control mechanism is connected to each of these actuators so as to achieve the desired movement. Advanced programming is required of the controller in order to properly coordinate the movements in order to achieve this desired result.

[0008] Unfortunately, with such systems, the hydraulic actuators, along with other components, can become worn with time. Furthermore, the hydraulic integrity of each of the actuators can become compromised over time. As such, small variations in each of the actuators can occur. These variations, as they occur, can make the complex mechanism rather inaccurate. The failure of one hydraulic component can exacerbate the problems associated with the alignment of the pipe in a vertical orientation. Adjustments of the programming are often necessary to as to continue to achieve the desired results. Fundamentally, the more hydraulic actuators that are incorporated into such a system, the more likely it is to have errors, inaccuracies, and deviations in the desired delivery profile of the tubular. Typically, very experienced and knowledgeable operators are required so as to carry out this pipe movement operation. This adds significantly to the cost associated with pipe delivery.

[0009] In the past, pipe handling apparatus have not been used for the installation of casing. The problem associated with casing is that the threads of the casing are formed on an inner wall and on an outer wall at the ends of each of the casing sections. Whenever these threads are formed, the relatively thin wall thickness of the casing is further minimized. Additionally, great precision is required so as to properly thread the threads of one casing section within the threads of an adjacent casing section. The amount of accuracy required for the delivery of the casing by a pipe handling apparatus, in the past, has not been sufficient so as to achieve the desired degree of accuracy for the installation of the casing sections in their threaded connection. The improper installation of one casing section upon another casing section can potentially damage the threads associated with such casing sections. Additionally, in the past, the pipe handling apparatus could potentially damage the thin-walled casing sections during the delivery. As such, a need has developed to adapt a pipe handling apparatus so as to achieve the desired amount of accuracy for the installation of casing sections.

[0010] It is an object of the present invention to provide a pipe handling and casing stabbing apparatus and method which minimizes the amount of calibration required in order to move the pipe from a horizontal orientation to a vertical orientation.

[0011] It is another object of the present invention to provide a pipe handling and casing stabbing apparatus which operates with a single degree of freedom so as to move the pipe without adjustments

between the components.

[0012] It is a further object of the present invention to provide a pipe handling and casing stabbing apparatus and method which avoids springback of the arm upon release of the load.

[0013] It is still an additional object of the present invention to provide a pipe handling and casing stabbing apparatus and method which achieves greater precision in the delivery and installation of pipes and/or casing.

[0014] It is still another object of the present invention to provide a pipe handling and casing stabbing apparatus and method which increases the structural stiffness of the apparatus.

[0015] These and other objects and advantages of the present invention will become apparent from a reading of the attached specification and appended claims.

BRIEF SUMMARY OF THE INVENTION

[0016] The present invention is a pipe handling apparatus for moving a pipe to a drill floor that comprises a supporting structure, an arm extending from the supporting structure such that the arm is movable between a first position away from the drill floor and a second position over the drill floor, and a stiffening means cooperative with the arm when the arm and the supporting structure are in the second position. The stiffening means applies a mechanical resistance to the arm in the second position.

[0017] In the present invention, the second position is an end of travel of the supporting structure and the arm. The stiffening means is cooperative with an end of the arm opposite the supporting structure. The stiffening means applies a variable resistance to the arm as the arm moves from the first position to the second position. The variable resistance is greatest when the arm is in the second position.

[0018] A gripper means is affixed to an end of the arm opposite the supporting structure. The gripper means receives a pipe therein. The gripper means supports the pipe in a vertical orientation when the supporting structure and the arm are in the second position. The gripping means also is for grasping a horizontally oriented pipe when the arm and the supporting structure are in the first position. The supporting structure has an opening interior area. The gripper means is connected to the arm such that the pipe moves through the open interior area as the supporting structure and the arm move from the first position to the second position.

[0019] In the preferred embodiment of the present invention, the stiffening means comprises a first cable assembly having one end connected to the arm and an opposite end fixedly mounted such that the first cable assembly extends from one side of the arm and a second cable assembly having one end interconnected to the arm and an opposite end fixedly mounted such that the second cable assembly extends from an opposite side of the arm. Each of the first and second cable assemblies includes a link member pivotally mounted to the arm, a cable affixed to the link member at one end thereof, a spring pod affixed to an opposite end of the cable, and a member having one end connected to the spring pod and an opposite end fixedly mounted. The spring pipe includes a connector element affixed to the opposite end of the cable and to the one end of the member, and a resilient means interconnected to the connector member. The resilient means urges the connector element in a direction away from alignment of the member with the cable.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0020] FIGURE 1 is a side elevation view showing the pipe handling apparatus in accordance with the teachings of the preferred embodiment of the present invention.

[0021] FIGURE 2 is a side elevational view showing the pipe handling apparatus of the present invention in a first position.

[0022] FIGURE 3 is a side elevational view showing the pipe handling apparatus moving from the first position toward the second position.

[0023] FIGURE 4 is a side elevation view of the pipe handling apparatus showing the pipe handling apparatus as moving the pipe further to the second position.

[0024] FIGURE 5 is a side elevational view showing the pipe handling apparatus in its second position in which the pipe extends in a vertical orientation.

[0025] FIGURE 6 is an illustration of the gripper assembly as vertically translating the pipe.

[0026] FIGURE 7 is a side elevational view of a first alternative embodiment of the gripper assembly of the present invention.

[0027] FIGURE 8 is a side elevational view showing a second alternative embodiment of the gripper assembly of the present invention.

[0028] FIGURE 9 is a side elevational view showing a third alternative embodiment of the gripper

assembly of the present invention.

[0029] FIGURE 10 shows a perspective view in which the stiffener system is applied to the arm of the pipe handling apparatus in accordance with the teachings of the present invention

[0030] FIGURE 11 is a diagrammatic illustration of the resilient means utilized to deflect the cables associated with the stiffener system of the present invention.

[0031] FIGURE 12 is a perspective view showing the orientation of the stiffener system of the present invention when the supporting structure is in a generally horizontal orientation.

[0032] FIGURE 13 is a perspective view of the stiffener system of the present invention as the supporting structure moves from the horizontal orientation toward the vertical orientation.

DETAILED DESCRIPTION OF THE INVENTION

[0033] Referring to FIGURE 1, there is shown the pipe handling apparatus 10 for moving a pipe 18 to a drill floor 64 in accordance with the preferred embodiment of the present invention. The pipe handling apparatus 10 is mounted on a skid 12 that is supported upon the bed 14 of a vehicle, such as a truck. The pipe handling apparatus 10 in particular includes a supporting structure 16. The supporting structure 16 can be a boom that is pivotally mounted to an underlying structure, such as the skid 12. The supporting structure 16 is movable between a first position and a second position. In FIGURE 1, an intermediate position of the pipe handling apparatus 10 is particularly shown. In this position, the pipe 18 is illustrated in its position prior to installation on the drill rig 20. A lever assembly 22 is pivotally connected to the supporting structure 16. An arm 24 is pivotally connected to an end of the lever assembly 22 opposite the supporting structure 16. The arm 24 can be made to be extendable in length. The arm 24 can also be made so as to have a fixed length. A gripping means 26 is fixedly connected to an opposite end of the arm 24 opposite the lever assembly 22. The gripping means 26 includes a body 28 and grippers 30 and 32. A link 34 has one end pivotally connected to the skid 12 and an opposite end pivotally connected to the end of the lever assembly 22 opposite the arm 24. A brace 36 is pivotally connected to the supporting structure 16 and also pivotally connected to the arm 24 between the lever assembly 22 and the body 28 of gripping means 26.

[0034] In the present invention, the supporting structure 16 is a structural framework of struts, cross members and beams. In particular, in the present invention, the supporting structure 16 is configured

so as to have an open interior such that the pipe 18 will be able to be lifted in a manner so as to pass through the interior of the supporting structure 16. As such, the end 38 of the supporting structure 16 should be strongly reinforced so as to provide the necessary structural integrity to the supporting structure 16. A lug 40 extends outwardly from one side of the supporting structure 16. This lug 40 is suitable for pivotable connection to the lever assembly 22. The supporting structure 16 is pivotally connected at the opposite end 42 to a location on the skid 12. The pivotable connection at end 42 of the supporting structure 16 is located in offset relationship and above the pivotable connection 44 of the link 34 with the skid 12. A small frame member 46 extends outwardly from the side of the supporting structure 16 opposite the link 34. This frame assembly 46 has a pivotable connection with the brace 36.

[0035] The lever assembly 22 includes a first portion 48 and a second portion 50. The first portion 48 extends at an obtuse angle with respect to the second portion 50. The link 34 is pivotally connected to the end of the second portion 50 opposite the first portion 48. The arm 24 is pivotally connected to the end of the first portion 48 opposite the second portion 50. The lug 40 of the supporting structure 16 is pivotally connected in an area generally between the first portion 48 and the second portion 50. This unique arrangement of the lever assembly 22 facilitates the ability of the present invention to carry out the movement of the pipe 18 between the horizontal orientation and the vertical orientation.

[0036] The arm 24 has an end pivotally connected to the end of the first portion 48 of the lever assembly 22. The opposite end of the arm 24 is connected to the gripping means 26. In particular, a pair of pin connections engage a surface of the body 28 of the gripping means 26 so as to fixedly position the gripping means 26 with respect to the end of the arm 24. The pin connections 52 and 54 can be in the nature of bolts, or other fasteners, so as to strongly connect the body 28 of the gripping means 26 with the arm 24. The bolts associated with pin connections 52 and 54 can be removed such that other gripping means 26 can be affixed to the end of the arm 24. As such, the pipe handling apparatus 10 of the present invention can be adaptable to various sizes of pipe 18 and various heights of drilling rigs 20.

[0037] The gripping means 26 includes the body 28 with the grippers 30 and 32 translatable along the length of the body 28. This vertical translation of the grippers 30 and 32 allows the pipe 18 to

be properly moved upwardly and downwardly once the vertical orientation of the pipe 18 is achieved. The grippers 30 and 32 are in the nature of conventional grippers which can open and close so as to engage the outer diameter of the pipe 18, as desired.

[0038] The link 34 is an elongate member that extends from the pivotable connection 44 to the pivotable connection 68 of the second portion 50 of the lever assembly 22. The link 34 is non-extensible and extends generally adjacent to the opposite side from the supporting structure 16 from that of the arm 24. The link 34 will generally move relative to the movement of the supporting structure 16. The brace 36 is pivotally connected to the small framework 46 associated with supporting structure 16 and also pivotally connected at a location along the arm 26 between the ends thereof. Brace 36 provides structural support to the arm 24 and also facilitates the desired movement of the arm 24 during the movement of the pipe 18 between the horizontal orientation and the vertical orientation.

[0039] Actuators 56 and 58 are illustrated as having one end connected to the skid 12 and an opposite end connected to the supporting structure 16 in a location above the end 42. When the actuators 56 and 58 are activated, they will pivot the supporting structure 16 upwardly from the horizontal orientation ultimately to a position beyond vertical so as to cause the pipe 18 to achieve a vertical orientation. Within the concept of the present invention, a single hydraulic actuator can be utilized instead of the pair of hydraulic actuators 56 and 58, as illustrated in FIGURE 1.

[0040] The drilling rig 20 is illustrated as having drill pipes 60 and 62 extending upwardly so as to have an end above the drill floor 64. When the pipe 18 is in its vertical orientation, the translatable movement of the grippers 30 and 32 can be utilized so as to cause the end of the pipe 18 to engage with the box of one of the drill pipes 60 and 62.

[0041] In FIGURE 1, the general movement of the bottom end of the pipe 18 is illustrated by line 66. The movement of the pivot point 68 of the connection between the lever assembly 22 and the link 34 is illustrated by line 70. Curved line 72 illustrates the movement of the pivotable connection 40 between the supporting structure 16 and the lever assembly 22.

[0042] In the present invention, the coordinated movement of each of the non-extensible members of the apparatus 10 is achieved with proper sizing and angular relationships. In essence, the present invention provides a four-bar link between the various components. As a result, the movement of

the drill pipe 18 between a horizontal orientation and a vertical orientation can be achieved purely through the mechanics associated with the various components. As can be seen, only a single hydraulic actuator may be necessary so as to achieve this desired movement. There does not need to be coordinated movement of hydraulic actuators. The hydraulic actuators are only used for the pivoting of the supporting structure. Since the skid 12 is located on the bed of a vehicle 14, the vehicle 14 can be maneuvered into place so as to properly align with the centerline of the drill pipe 60 and 62 of the drilling rig 20. Once the proper alignment is achieved by the vehicle 14, the apparatus 10 can be operated so as to effectively move the drill pipe to its desired position. The gripper assemblies of the present invention allow the drill pipe 18 to be moved upwardly and downwardly for the proper stabbing of the drill pipes 60 and 62. The present invention is adaptable to various links of pipe 18.

[0043] Various types of gripping means 26 can be installed on the end of the arm 24 so as to properly accommodate longer lengths of pipe 18. These variations are illustrated herein in connections FIGURES 6–9.

[0044] As such, instead of the complex control mechanisms that are required with prior art systems, the present invention achieves its results by simple maneuvering of the vehicle 14, along with operation of the hydraulic cylinders 56 and 58. All other linkages and movement of the pipe 18 are achieved purely because of the mechanical connections between the various components. As such, the present invention assures a precise, self-centering of the pipe 18 with respect to the desired connecting pipe.

[0045] FIGURE 2 illustrates the drill pipe 18 in a generally horizontal orientation. In the present invention, it is important to note that the drill pipe can be delivered to the apparatus 10 in a position below the supporting structure 16. In particular, the drill pipe can be loaded upon the skid 12 in a location generally adjacent to the grippers 30 and 32 associated with the gripping means 26. As such, the present invention facilitates the easy delivery of the drill pipe to the desired location. The gripper 30 and 32 will grip the outer diameter of the pipe 18 in this horizontal orientation.

[0046] In FIGURE 2, it can be seen that the supporting structure 16 resides above the drill pipe 18 and in generally parallel relationship to the top surface of the skid 12. The lever assembly 22 is suitably pivoted so that the arm 24 extends through the interior of the framework of the supporting

structure 16 and such that the gripping means 26 engages the pipe 18. The brace 36 resides in connection with the small framework of the supporting structure 16 and also is pivotally connected to the arm 24. The link 34 will reside below the supporting structure 16 generally adjacent to the upper surface of the skid 12 and is connected to the second portion 50 of the lever assembly 22 below the supporting structure 16.

[0047] FIGURE 3 shows an intermediate position of the drill pipe 18 during the movement from the horizontal orientation to the vertical orientation. As can be seen, the gripping means 26 has engaged with the pipe 18. The lever assembly 22 is pivoting so that the end 70 of pipe 18 will pass through the interior of the framework of the supporting structure 16. Also, the arm associated with the gripping means 26 serves to move the body 28 of the gripping means 26 through the interior of the framework of the supporting structure 16. The brace 36 is pulling on the first portion 48 of lever assembly 22 so as cause this motion to occur. The link 34 is pulling on the end of the second portion 50 of the lever assembly 22 so as to draw the first portion 48 upwardly and to cause the movement of the body 28 of the gripping means 26. The hydraulic actuators 56 and 58 have been operated so as to urge the supporting structure 16 pivotally upwardly.

[0048] FIGURE 4 shows a further intermediate movement of the drill pipe 18. Once again, the hydraulic actuators 56 and 58 urge the supporting structure 16 angularly upwardly away from the top surface of the skid 12. This causes the link 34 to have a pulling force on the pivotal connection 68 of the second portion 50 of the lever assembly 22. This causes the first portion 48 of the lever assembly 22 to move upwardly thereby causing the arm 24, in combination with the brace 36 to lift the gripping means 26 further upwardly and draw the pipe 18 completely through the interior of the supporting structure 16. As can be seen, the relative size and relation of the various components of the present invention achieve the movement of the pipe 18 without the need for separate hydraulic actuators.

[0049] FIGURE 5 illustrates the drill pipe 18 in its vertical orientation. As can be seen, the drill pipe 18 is positioned directly above the underlying pipe 62 on the drilling rig 20. The further upward pivotal movement of the supporting structure 16 is caused by the hydraulic cylinders 56 and 58. This causes the link 34 to rotate and draw the end of the second portion 50 of the lever assembly 22 downwardly. The lever assembly 22 rotates about the pivot point 40 such that the first portion 48

of the lever assembly 22 has a pivot 72 at its upper end. The brace 36 is now rotated in a position so as to provide support for the arm 24 in this upper position. The gripping means 26 has grippers 30 and 32 aligned vertically and in spaced parallel relationship to each other. If any further precise movement is required between the bottom end 80 of the pipe 18 and the upper end 82 of pipe 62, then the vehicle 14 can be moved slightly so as to achieve further precise movement. In the manner described hereinbefore, the drill pipe 18 has achieved a completely vertical orientation by virtue of the interrelationship of the various components of the present invention and without the need for complex control mechanisms and hydraulics.

[0050] In order to install the drill pipe 18 upon the pipe 62, it is only necessary to vertically translate the grippers 30 and 32 within the body 28 of the gripping means 26. As such, the end 80 can be stabbed into the box connection 82 of pipe 62. Suitable tongs, spinners, or other mechanisms can be utilized so as to rotate the pipe 18 in order to achieve a desired connection. The grippers 30 and 32 can then be released from the exterior of the pipe 18 and returned back to the original position such that another length of drill pipe can be installed.

[0051] FIGURE 6 is a detailed view of the gripping means 26 of the present invention. In FIGURE 6 the pin connections 52 and 54 have been installed into alternative holes formed on the body 28 of the gripping means 26. The holes, such as hole 84 can be formed in a surface of the body 28 so as to allow selective connection between the end of the arm 24 and the body 28 of gripping means 26. As such, the position of the gripping means 26 in relation to the arm 24 can be adapted to various circumstances.

[0052] It can be seen that the pipe 18 is engaged by grippers 30 and 32 of the gripping means 26. The configuration of the grippers 30 and 32, as shown in FIGURE 6, is particularly designed for short length (approximately 30 feet) of drill pipe. In FIGURE 6, it can be seen that the grippers 30 and 32 are translated relative to the body 28 so as to lower end 80 of pipe 18 downwardly for connection to an underlying pipe.

[0053] Occasionally, it is necessary to accommodate longer lengths of pipe. In other circumstances, it is desirable to accommodate pipes that are already assembled in an extended length. In FIGURE 7, it can be seen that the drill pipe 18 is formed of separate sections 90, 92, 94 and 96 that are joined in end-to-end connection so as to form an extended length of the of the pipe 18. When such pipe

arrangements are required, the gripping means 26 of the present invention will have to be adapted so as to accommodate such extended lengths. Fortunately, the structure of the apparatus 10 of the present invention can accommodate such an arrangement. As can be seen in FIGURE 7, the arm 24 is connected to a first gripper assembly 100 and connected by stab frame 102 to a second gripper assembly 104. The second gripper assembly 104 is located directly below and vertically aligned with the first gripper assembly 100. The stab frame 102 includes a suitable pin connection for engaging the body 106 of the second gripper assembly 104. The first gripper assembly 100 has body 108 that is directly connected to the pin connections associated with the arm 24. The gripping assembly 100 includes grippers 110 and 112 which engage in intermediate position along the length of pipe 18. The grippers 114 and 116 of the second gripper assembly 104 engage the lower portion of the pipe 18. The method of moving the pipe 18 from the horizontal position to the vertical position is similar to that described hereinbefore.

[0054] It should be noted that the arm 24 can extend at various angles with respect to the gripper assemblies 100 and 104. In the preferred embodiment, the arm 24 will be generally transverse to the length of the body associated with the gripper assemblies 100 and 104. However, if needed to accommodate certain drilling rig height and arrangements, the arm 24 can be angled up to 30° from transverse with respect to the body associated with the gripper assemblies 100 and 104.

[0055] In FIGURE 8, it can be seen that the arm 24 has a first stab frame 120 extending upwardly from the top of the arm 24 and a second stab frame 122 extending below the arm 24. The first stab frame 120 includes a gripper assembly 124 affixed thereto. The second stab frame 122 includes a gripper assembly 126 connected thereto. The arm 24 will include suitable pin connections located on the top surface thereof and on the bottom surface thereof so as to engage with the stab frames 120 and 122. The gripper assembly 124 has suitable grippers 128 and 130 for engaging an upper portion of the pipe 132. The gripper assembly 126 includes grippers 134 and 136 for engaging with a lower portion of the pipe 132. As illustrated in FIGURE 8, the pipe 132 is a multiple section pipe. However, pipe 132 can be an extended length of a single pipe section.

[0056] FIGURE 9 shows still another embodiment of the gripper assembly structure of the present invention. In FIGURE 9, the arm 24 is connected to the upper stab frame 150 and to the lower stab frame 152. Gripping assemblies 154, 156 and 158 are provided. The gripper assembly 154 is

connected to an upper end of the upper stab frame 150. The gripper assembly 158 is connected to a lower end of the lower stab frame 152. The gripper assembly 156 is intermediately located directly on the opposite side of the end of the arm 24 and connected to the lower end of the upper stab frame 150 and to the upper end of the lower stab frame 152. As such, the present invention provides up to three gripper assemblies 154, 156, and 158 to be connected. This can be utilized so as to accommodate even longer lengths of pipe, if needed.

[0057] The present invention achieves a number of advantages over the prior art. Most importantly, the present invention provides a pipe handling apparatus and method that minimizes the number of control mechanisms, sensors and hydraulic systems associated with the pipe handling system. Since the movement of the pipe is achieved in a purely mechanical way, only a single hydraulic actuator is necessary for the movement of the supporting structure. All of the other movements are achieved by the interrelationship of the various components. As such, the present invention achieves freedom from the errors and deviations that can occur through the use of multiple hydraulic systems. The simplicity of the present invention facilitates the ability of a relatively unskilled worker to operate the pipe handling system. The amount of calibration is relatively minimal. Since the skid 12 associated with the present invention can be transported by a truck, various fine movements and the location of the pipe handling apparatus 10 can be achieved through the simple movement of the vehicle. The pipe handling apparatus 10 of the present invention is independent of the drilling rig. As such, a single pipe handling apparatus that is built in accordance with the teachings of the present invention can be utilized on a number of rigs and can be utilized at any time when required. There is no need to modify the drilling rig, in any way, to accommodate the pipe handling apparatus of the present invention. Since the pipes are loaded beneath the supporting structure, the providing of the pipe to the pipe handling apparatus can be achieved in a very simple manner. There is no need to lift the pipes to a particular elevation or orientation in order to initiate the pipe handling system.

[0058] Referring to FIGURE 10 there is shown the pipe handling and casing stabbing apparatus 200 in accordance with the teachings of the present invention. The pipe handling and casing stabbing apparatus 200 has a configuration of supporting structure 202, arm 204, brace 206, link 208 and skid 210 similar to the construction described herein previously. The pipe handling and casing stabbing apparatus 200 includes the addition of a stiffener means 211 applied to the arm 204 and to the skid

210.

[0059] The stiffener means 211 includes a first cable assembly 214 and a second cable assembly 216 which are affixed on opposite sides of the arm 204. In particular, the first cable assembly 214 is affixed to a link member 218 that is fixedly pivotally mounted on the arm 204. A stop 220 extends outwardly from the side of the arm 204. The stop 220 serves to stop rotational movement of the link member 218 as the arm 204 moves in a proper direction for the delivery of pipe and/or casing. The cable assembly 214 also includes a cable 222 that has one end affixed to the link member 218 opposite the pivotal connection 224 with arm 204. The cable 222 extends downwardly from the arm 204 so as to be interconnected to the skid 210. In FIGURE 10, the cable assemblies 214 and 216 are shown as applying a mechanical resistance to the arm 204. This mechanical resistance serves to offset the load of the pipe as received by the grippers which are affixed to the end 226 of arm 204 (not shown). The second cable assembly 216 has a configuration identical to that of first cable assembly 214.

[0060] Importantly, a first spring pod 228 is connected to the end of the cable 222 opposite the arm 204. A second spring pod 230 is affixed to the cable 232 associated with the second cable assembly 216. The spring pods 228 and 230 serve to apply an angular deflection to each of the cable assemblies 214 and 216 so as to selectively supply a mechanical resistance to the arm 204.

[0061] As can be seen, a connector element 234 is connected to the end of cable 222. Connector element 234 is also connected to a resilient means 236. An elongate member 238 joins the connector element 234 to the skid 210. Similarly, the cable 232 has an end opposite the arm 204 connected to the connector element 240. Another resilient means 242 is joined to the connector element 240 so as to cause a deflection in the cable assembly 216. The resilient means 242 is fixed positioned on the skid 210. Another elongate member 244 joins the connector element 240 to the skid 210.

[0062] In normal use, the resilient means 236 and 242 serves to exert a resilient force which urges each of the cable assemblies 214 and 216 slightly out of linear alignment between the respective cable 222 and 232 with the elongate members 238 and 240. By pulling the connector elements 234 and 240, respectively, toward the resilient means 236 and 242, a greater degree of mechanical resistance can be applied to the cable assemblies 214 and 216 and, in turn, to the arm 204.

[0063] In the present invention, the degree of mechanical resistance is greatest at the end of the travel

of the arm 204. In other words, when the arm 204 extends into a proper position in which the pipe is in vertical alignment with the wellhead, the mechanical resistance is the greatest. As such, the arm of the present invention receives the greatest stiffness at the point where the pipe will be released. **[0064]** The system of the is particularly applicable to single and multiple degree of freedom systems. The pre-loading is not repeatable without a single degree of system. In multiple degree of freedom systems, one would have to pre-load all of the degrees of freedom. In a multiple degree of freedom systems, in one failure can cause catastrophic problems for the rest of the system. In the present invention, the stiffness is variable as the system operates. The maximum degree of stiffness occurs when the arm is in its second position at the end of travel. This stiffness can be achieved either through tension loading, such as through the use of the cable assemblies 214 and 216 described herein or by compression loading. Such compression loading could occur by the use of header installed within a V-door of a rig assembly. In other words resistance would applied to the top of the arm rather than from the bottom of the arm. The present invention is also usable in association with the installation of horizontal pipe. The single degree of freedom system can be utilized so as to lay pipelines. Once again, the mechanical resistance can be applied to the mechanical system at the end of the travel of such a system for installing pipe horizontally.

[0065] As used herein, each of the resilient means 236 and 242 can be in the form of spring assemblies, as illustrated in FIGURE 10, or can be in the nature of a pneumatic cylinder.

[0066] In particular, in FIGURE 11, it can be seen how the cable 222 is connected to the connector element 234 and to a pair of elongate members 238 and 250. The first elongate member 238 extends at an acute angle with respect to the second elongate member 250. The resilient means 236 is in the form of a pneumatic cylinder 252. A source of pneumatic pressure 254 communicates with the interior of the pneumatic cylinder 252 so as to allow for the adjustment of the degree of movement of the piston 256. As the piston 256 is drawn into the pneumatic cylinder 252, the piston 256 will draw the connector element 234 toward the pneumatic cylinder 252 and increase the amount of deflection between the elongate members 238 and 250 relative to the cable 222. The pneumatic cylinder 252 is affixed to the skid 210 at an end opposite the connector element 234.

[0067] The pre-loading system 200, as shown in FIGURES 10 and 11 greatly enhances the ability to avoid springback and to establish greater precision in the delivery of pipe and/or casing to the

drilling rig. It has been found, that in experimental tests, that 0.03 inches of total lateral motion applied to the cable assemblies 214 and 216 allows for the removal or addition of 10,000 pounds (the maximum payload) of load applied to the arm 204. The ability to avoid the springback and to achieve this maximum accuracy allows the present invention to stab casing within a 1/16 of an inch tolerance. This deflection of the cable assemblies 214 and 216 increases the stiffness of the pipe handling apparatus of the present invention by a factor of 300. The load is shifted directly from the arm 204 toward the stop and the anchoring on the skid 210 instead of directly on the arm.

[0068] FIGURE 12 shows the supporting structure 202 in its generally horizontal orientation upon the skid 210. In this position, the gripper assemblies associated with the arm 204 are in position to receive a pipe or casing therein. It can be seen that the link members 218 and 260 are in a position away from the respective stops. The link members 218 and 260 will rotate about the pivot point 224 during the movement of the arm 204 and during the movement of the supporting structure 202. The respective cable assemblies 214 and 216 will generally drape along the outside of the supporting structure 202.

[0069] FIGURE 13 shows the movement of the supporting structure 202 from the position adjacent to the skid to the vertical position. As can be seen, the arm 204 is pivoting with respect to lever assembly 262. The link member 218 is pivotable and rotatable about the pivot point 224 during this movement. It can be seen that the arm 204 will move upwardly between the respective cable assemblies 214 and 216. Eventually, the arm 204 will assume a generally horizontal orientation when it is necessary to position the pipe and/or casing into a desired position. This causes the link member 218 to contact the stop 220. As a result, the tensioning of the arm 204 can begin.

[0070] Importantly, the enhanced accuracy and the ability to avoid deflection of the arm 204 during the installation and release of the pipe and/or casing enhances the ability to present invention to deliver casing to the drilling rig. Since the casing must be delivered with extreme accuracy, the avoidance of deflection, as caused by the present invention, will allow the maximum amount of deflection to be merely 0.07 inches. When the weight of the pipe and/or casing is released, any deflection is absorbed by the stop 220 and by an anchor, such as the skid 210. The arm 204 will be maintained in a generally fixed position at this time, rather than springing back.

[0071] The foregoing disclosure and description of the invention is illustrative and explanatory

thereof. Various changes in the details of the illustrated construction can be made within the scope of the appended claims without departing from the true spirit of the invention. The present invention should only be limited by the following claims and their legal equivalents.

CLAIMS

I claim:

1. A pipe handling apparatus (10) for moving a pipe (18) to a drill floor comprising:
a supporting structure (16);
an arm (24) extending from said supporting structure (16), said arm (24) movable between a first position away from the drill floor and a second position over the drill floor; and
a stiffening means (211) cooperative with said arm (24) when said arm (24) and said supporting structure (16) are in said second position, said stiffening means (211) for applying a resistance to said arm (24) in said second position.
2. The pipe handling apparatus (10) of Claim 1, said second position being an end of travel of said supporting structure (16) and said arm (24), said arm (24) having an extendable length.
3. The pipe handling apparatus (10) of Claim 1, said arm (24) moving between said first and second positions within a single degree of freedom, said supporting structure (16) being a boom pivotally mounted to an underlying surface.
4. The pipe handling apparatus (10) of Claim 1, said stiffening means (211) being cooperative with an end of said arm (24) opposite said supporting structure (16), said stiffening means (211) for applying a variable resistance to said arm (24) as said arm (24) moves from said first position to said second position, said variable resistance being greatest when said arm (24) is in said second position.
5. The pipe handling apparatus (10) of Claim 1, further comprising:
a gripper means (26) affixed to an end of said arm (24) opposite said supporting structure (16), said gripper means (26) for receiving the pipe (18) therein, said gripper means (26) for supporting the pipe (18) in a vertical orientation when said supporting structure (16) and said arm (24) are in said second position.
6. The pipe handling apparatus (10) of Claim 5, said gripping means for grasping a horizontally oriented pipe (18) when said arm (24) and said supporting structure (16) are in said first position, said arm (24) having a fixed length.

7. The pipe handling apparatus (10) of Claim 5, said supporting structure (16) having an opening interior area, said gripper means (26) being connected to said arm (24) such that the pipe (18) moves through said open interior area as said supporting structure (16) and said arm (24) move from said first position to said second position.

8. The pipe handling apparatus (10) of Claim 1, said stiffening means (211) comprising:

a first cable assembly (214) having one end connected to said arm (24) and an opposite end fixedly mounted, said first cable assembly extending from one side of the arm (24); and

a second cable assembly (216) having one end interconnected to the arm (24) and an opposite end fixedly mounted, said second cable assembly extending from an opposite side of the arm (24).

9. The pipe handling apparatus (10) of Claim 8, each of said first and second cable assemblies comprising:

a link member (218) pivotally mounted to said arm (24);

a cable (222) affixed to said link member at one end thereof;

a spring pod (228) affixed to an opposite end of said cable; and

a member having one end connected to said spring pod and an opposite end fixedly mounted.

10. The pipe handling apparatus (10) of Claim 9, said spring pipe comprising:

a connector element (234) affixed to said opposite end of said cable and to said one end of said member; and

a resilient means (236) interconnected to said connector element, said resilient means for urging said connector element in a direction away from alignment of said member with said cable.

11. A pipe handling apparatus (10) for moving a pipe (18) to a drill floor comprising:
a supporting structure (16);
an arm (24) extending from said supporting structure (16), said arm (24) being movable between a first position away from the drill floor and a second position over the drill floor;
and

a stiffening means (211) cooperative with said arm (24) when said arm (24) and said supporting structure (16) are in said second position, said stiffening means (211) for applying a variable resistance to said arm (24) and said supporting structure (16) as said supporting structure (16) and said arm (24) move from said first position to said second position, said variable resistance being greatest when said arm (24) is in said second position.

12. The pipe handling apparatus (10) of Claim 11, said supporting structure (16) and said arm (24) moving between said first position to said second position within a single degree of freedom, said supporting structure (16) being a boom pivotally mounted to an underlying surface.

13. The pipe handling apparatus (10) of Claim 12, said boom having an open interior area, said arm (24) moving through said open interior as said boom and said arm (24) move from said first position and said second position.

14. The pipe handling apparatus (10) of Claim 11, said second position being an end of travel of said supporting structure (16) and said arm (24), said arm (24) having an extendable length.

15. The pipe handling apparatus (10) of Claim 11, said stiffening means (211) being cooperative with an end of said arm (24) opposite said supporting structure (16), said arm (24) having a fixed length.

16. The pipe handling apparatus (10) of Claim 11, further comprising:
a gripper means (26) affixed to an end of said arm (24) opposite said supporting structure (16), said gripper means (26) for receiving a pipe (18) therein, said gripper means (26) for supporting the pipe (18) in a vertical orientation when said supporting structure (16) and said arm (24) are in said second position.

17. The pipe handling apparatus (10) of Claim 16, said gripping means for grasping a horizontally oriented pipe (18) when said arm (24) and said supporting structure (16) are in said first position.

18. The pipe handling apparatus (10) of Claim 11, said stiffening means (211) comprising:
a first cable assembly (214) having one end connected to the arm (24) and an opposite end fixedly mounted, said first cable assembly extending from one side of the arm (24); and
a second cable assembly (216) having one end interconnected to said arm (24) and an opposite end fixedly mounted, said second cable assembly extending from an opposite side of said arm (24).

19. The pipe handling apparatus (10) of Claim 18, each of said first and second cable assemblies comprising:
a link member (218) pivotally mounted to the arm (24);
a cable (222) affixed to said link member at one end thereof;
a spring pod (228) affixed to an opposite end of said cable; and
a member having one end connected to said spring pod and an opposite end fixedly mounted.

20. The pipe handling apparatus (10) of Claim 19, said spring pod comprising:
a connector element (234) affixed to said opposite end of said cable and to said one end of said member; and
a resilient means (236) interconnected to said connector element, said resilient means for urging connector element in a direction away from alignment of said member with said cable.

1/7




FIG. 1




FIG. 2

2/7




FIG. 3




FIG. 4

3/7




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

5/7




FIG. 10

6/7




FIG. 11




FIG. 12

7/7




FIG. 13