




(86) Date de dépôt PCT/PCT Filing Date: 2015/08/18
(87) Date publication PCT/PCT Publication Date: 2016/02/25
(45) Date de délivrance/Issue Date: 2023/01/03
(85) Entrée phase nationale/National Entry: 2017/01/23
(86) N° demande PCT/PCT Application No.: US 2015/045663
(87) N° publication PCT/PCT Publication No.: 2016/028759
(30) Priorités/Priorities: 2014/08/18 (US62/038,684);
2015/08/17 (US14/828,008)

(51) Cl.Int./Int.Cl. *A61M 5/14* (2006.01),
G16H 20/17 (2018.01)
(72) Inventeur/Inventor:
CHEN, HOWARD Z., US
(73) Propriétaire/Owner:
ICU MEDICAL, INC., US
(74) Agent: MBM INTELLECTUAL PROPERTY LAW LLP

(54) Titre : SYSTEME D'ALIMENTATION, DE COMMANDE ET DE COMMUNICATION INTEGRE DE POTENCE POUR INTRA VEINEUSE ET PROCEDE POUR UNE POMPE DE PERFUSION
(54) Title: INTRAVENOUS POLE INTEGRATED POWER, CONTROL, AND COMMUNICATION SYSTEM AND METHOD FOR AN INFUSION PUMP



(57) Abrégé/Abstract:

An infusion system includes an intravenous pole, a pump device, a power supply device, a computer processing device, and conduit. The intravenous pole includes a bottom portion adjacent a bottom end, an upper portion adjacent a top end, and a hollow shaft. The pump device is attached to the upper portion of the intravenous pole. The power supply device is attached to the bottom portion of the intravenous pole. The computer processing device is attached to the bottom portion of the intravenous pole. The conduit extends within the hollow shaft of the intravenous pole. The conduit connects the pump device, the power supply device, and the computer processing device.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(10) International Publication Number
WO 2016/028759 A1

(43) International Publication Date
25 February 2016 (25.02.2016)

(51) International Patent Classification:
G06Q 10/00 (2012.01)

(21) International Application Number:
PCT/US2015/045663

(22) International Filing Date:
18 August 2015 (18.08.2015)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
62/038,684 18 August 2014 (18.08.2014) US
14/828,008 17 August 2015 (17.08.2015) US

(71) Applicant: **HOSPIRA, INC.** [US/US]; 275 N. Field Drive, Dept. NLEG, Bldg. H1-4S, Lake Forest, Illinois 60045 (US).

(72) Inventor: **CHEN, Howard Z.**; 6627 Wildwood Court, San Jose, California 95120 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: INTRAVENOUS POLE INTEGRATED POWER, CONTROL, AND COMMUNICATION SYSTEM AND METHOD FOR AN INFUSION PUMP




FIG. 1

(57) Abstract: An infusion system includes an intravenous pole, a pump device, a power supply device, a computer processing device, and conduit. The intravenous pole includes a bottom portion adjacent a bottom end, an upper portion adjacent a top end, and a hollow shaft. The pump device is attached to the upper portion of the intravenous pole. The power supply device is attached to the bottom portion of the intravenous pole. The computer processing device is attached to the bottom portion of the intravenous pole. The conduit extends within the hollow shaft of the intravenous pole. The conduit connects the pump device, the power supply device, and the computer processing device.

WO 2016/028759 A1



Published:

— *with international search report (Art. 21(3))*

INTRAVENOUS POLE INTEGRATED POWER, CONTROL, AND COMMUNICATION SYSTEM AND METHOD FOR AN INFUSION PUMP

FIELD OF THE DISCLOSURE

[001] The disclosure relates to an intravenous (IV) pole-mounted integrated infusion system and method in which the power, control, and communication devices are attached as one or more different units to the intravenous pole in one or more different locations remote from the pump device. More particularly, the disclosure relates to providing physical support of the pump device with the IV pole, while moving power, control, and communication systems out of the pump and out of physical supporting relationship with the pump. Furthermore, the disclosure relates to arranging an infusion system to eliminate single points of failure and to reduce the risk of tipping when the pump device is attached to an IV pole, especially a wheeled, portable IV pole.

BACKGROUND OF THE DISCLOSURE

[002] Infusion systems and methods are used to deliver infusion fluid into a patient's body. Typically infusion systems and methods utilize a single integrated or modular system, containing a pump, a computer processor, a communication unit, an alarm device, and a power-delivery device, attached to an upper portion of an intravenous pole. However, containing these functions all in one device may result in single points of failures, may make maintenance difficult, may decrease optimization, and may lead to reliability or stability issues. Other modular device systems typically include a master unit interface

module and attachable functional units such as pump and patient monitoring modules. However, the modules need to be attached to the master user interface module for power and command. The resulting system often still have reliability and stability issues.

[003] An infusion system and method is needed to resolve one or more issues of one or more of the existing infusion systems or methods.

SUMMARY OF THE DISCLOSURE

[004] In one embodiment of the disclosure, an infusion system includes an intravenous pole, a pump device, a power supply device, a computer processing device, and conduit. The intravenous pole includes a bottom portion adjacent a bottom end, an upper portion adjacent a top end, and a hollow shaft. The pump device is attached to the upper portion of the intravenous pole. The power supply device is attached to the bottom portion of the intravenous pole. The computer processing device is attached to the bottom portion of the intravenous pole. The conduit extends within the hollow shaft of the intravenous pole. The conduit connects the pump device, the power supply device, and the computer processing device.

[005] In another embodiment of the disclosure, an infusion system includes an intravenous pole, a pump device, a display device, an input device, a power supply device, an alarm device, a computer processing device, a wireless communication device, an impedance matching circuit, and conduit. The intravenous pole includes an antenna, a bottom portion adjacent a bottom end,

an upper portion adjacent a top end, and a hollow shaft. The pump device is attached to the upper portion of the intravenous pole. The display device is attached to the upper portion of the intravenous pole. The input device is attached to the upper portion of the intravenous pole. The power supply device, including a plurality of redundant power supply devices, is attached to the bottom portion of the intravenous pole. The alarm device, including a plurality of redundant alarm devices, is attached to the bottom portion of the intravenous pole. The computer processing device, including a plurality of redundant computer processing devices, is attached to the bottom portion of the intravenous pole. The wireless communication device includes the intravenous pole itself, an antenna embedded within the intravenous pole, or is attached to the bottom portion of the intravenous pole. The impedance matching circuit is attached to the intravenous pole. The conduit extends within the hollow shaft of the intravenous pole. The conduit connects the pump device, the display device, the input device, the power supply device, the alarm device, the computer processing device, the wireless communication device, and the impedance matching circuit.

[006] In still another embodiment of the disclosure, a method of manufacturing, setting up, or using an infusion system is disclosed. In one step, a pump device is attached to an upper portion, adjacent a top end, of an intravenous pole. In another step, a power supply device and a computer processing device are attached to a bottom portion, adjacent a bottom end, of the intravenous pole. In an additional step, conduit is extended within a hollow

shaft of the intravenous pole to connect the pump device, the power supply, and the computer processing device.

[007] These and other features, aspects and advantages of the disclosure will become better understood with reference to the following drawings, description and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[008] Figure 1 illustrates a back view of one embodiment of an infusion system; and

[009] Figure 2 illustrates a flowchart of one embodiment of a method for manufacturing, setting up, or using an infusion system.

DETAILED DESCRIPTION OF THE DISCLOSURE

[010] The following detailed description is of the best currently contemplated modes of carrying out the disclosure. The description is not to be taken in a limiting sense, but is made merely for the purpose of illustrating the general principles of the disclosure, since the scope of the disclosure is best defined by the appended claims. It is noted that the Figures are purely for illustrative purposes and are not to scale.

[011] The disclosure relates to an integrated intravenous pole based infusion system in which power, control, switch, alarm, and communication devices are attached to an intravenous pole at a separate location as a pump device, an input device, and a display device. This allows for separate optimization of the

pump device, the input device, and the display device relative to the power, control, switch, alarm, and communication devices allowing for improved reliability of the infusion system and easier maintenance and upgrade ability. In one embodiment, the power, control, switch, alarm, and communication devices may comprise one integrated unit attached at a bottom portion of the intravenous pole and the pump device, the input device, and the display device may comprise a second integrated unit attached at an upper portion of the intravenous pole. In another embodiment, the power, control, switch, alarm, and communication devices may each comprise separate devices attached at the bottom portion of the intravenous pole and the pump device, the input device, and the display device may comprise separate devices attached at the upper portion of the intravenous pole. The stability of the intravenous pole is improved by attaching the power, control, switch, alarm, and communication devices at the bottom portion of the intravenous pole while the pump device, the input device, and the display device are attached at the upper portion of the intravenous pole.

[012] Figure 1 illustrates a back view of one embodiment of an infusion system 10. The infusion system 10 comprises an information reader 7, an intravenous pole 12, a securement device 11, a pump device 14, an input device 15, a display device 17, a server 13, a power supply device 16, a computer processing device 18, conduit 20, a switch device 21, an alarm device 22, a communication device 24, an impedance matching circuit 27, and one or more wheels 29. In other embodiments, any number of these components may be

used, one or more of these components may not be used, one or more of these components may be combined into one component, or one or more additional components may be added. For instance, in one embodiment server 13 may include power supply device 16, computer processing device 18, switch device 21, alarm device 22, communication device 24, and impedance matching circuit 27 as one integrated component. Similarly, in one embodiment pump device 14, input device 15, and display device 17 may comprise one integrated component. In other embodiments, a plurality of the pump devices 14 can be attached to the same intravenous pole 12 using a power and data bus architecture with the same conduit 20. In still other embodiments, each of these components may comprise separate integrated components, or the components can be combined, integrated, or separated in any possible combination.

[013] The intravenous pole 12 comprises a bottom portion 12A adjacent a bottom end 12B, an upper portion 12C adjacent a top end 12D, a hollow shaft 12E, and mounting devices 12F. In one embodiment, the bottom portion 12A is defined as being in a range of 10 to 50 percent of the bottom length of the intravenous pole 12, and the upper portion 12C is defined as being in a range of 10 to 50 percent of the top length of the intravenous pole 12. In another embodiment, the bottom portion 12A is defined as being in a range of 10 to 30 percent of the bottom length of the intravenous pole 12, and the upper portion 12C is defined as being in a range of 10 to 30 percent of the top length of the intravenous pole 12. In still other embodiments, the percent lengths of the bottom portion 12A and the upper portion 12C of the intravenous pole 12 may

vary.

[014] The bottom end 12B of the intravenous pole 12 comprises a base to which the wheels 29 are attached. The wheels 29 are configured to roll on a ground or floor surface 26 with the intravenous pole 12 extending vertically upwards from the ground or floor surface 26. The mounting devices 12F are used to mount the information reader 7, the securement device 11, the server 13, the pump device 14, the input device 15, the display device 17, the power supply device 16, the computer processing device 18, the switch device 21, the alarm device 22, the communication device 24, and the wheels 29 to the intravenous pole 12. The mounting devices 12F may comprise fasteners, clamps, or other types of attachment devices.

[015] The intravenous pole 12 itself comprises a monopole antenna. In one embodiment, the intravenous pole 12 may be metallic. In another embodiment, the intravenous pole 12 may be non-metallic, such as a PVC pipe, and may comprise an embedded antenna 12H within the intravenous pole 12. The communication device 24 is attached to the bottom portion 12A of the intravenous pole 12. The communication device 24 comprises a wireless transmitter and a wireless receiver, with an appropriate antenna impedance matching circuit 27, which may comprise a single component or separate components. In other embodiments, any number of wireless transmitters and wireless receivers may be utilized. In still other embodiments, the antenna impedance matching circuit 27 may comprise a portion of the intravenous pole 12. Through the monopole antenna of the intravenous pole 12 itself and the

communication device 24, the infusion system 12 may be configured to transmit and receive information between the computer processing device 18 and one or more remote devices 25 wirelessly. The one or more remote devices 25 may comprise a display, an input device, an output device, a computer, a phone, a tablet, a personal digital assistant, a portable device, a handheld personal device, a wireless device, or another type of remote device. In other embodiments, the intravenous pole 12 and the communication device 24 may vary in quantity, configuration, attachment, location, and function.

[016] The conduit 20 extends within the hollow shaft 12E of the intravenous pole 12. The hollow shaft 12E may extend from the bottom end 12B to the top end 12D of the intravenous pole 12. In other embodiments, the configuration of the hollow shaft 12E may vary. The conduit 20 connects the information reader 7, the server 13, the pump device 14, the input device 15, the display device 17, the power supply device 16, the computer processing device 18, the switch device 21, the alarm device 22, and the communication device 24. In other embodiments, one or more of the components may be attached to one another wirelessly using WiFi, Bluetooth, RF or other technology. The conduit 20 comprises data and power cables. The conduit 20 may be retractable and may be configured to extend from the hollow shaft 12E through the top end 12D of the intravenous pole 12 to connect to any of the components. The conduit 20 may also be configured to extend through any number of openings 12G in the intravenous pole 12 to connect to any of the components. In other embodiments, the conduit 20 may vary in quantity, configuration, attachment,

location, and function.

[017] The pump device 14 is attached to the upper portion 12C of the intravenous pole 12. The pump device 14 is configured to pump infusion fluid from an infusion container 9 through tubing (not shown) to a patient. The securement device 11 is attached to the intravenous pole 12 and holds the infusion container 9. The securement device 11 may comprise a hook, a clip, a clamp, or any type of securement device. An information reader 7 is attached to the securement device 11. The information reader 7 is configured to read information 9a (such as included in a bar-code label or other type of label) off the infusion container 9 regarding the infusion fluid located within the infusion container 9 and transmit the information 9a to the computer processing device 18 for use in operating the pump device 14. The information reader 7 may comprise a bar code reader, a digital reader, an optical reader, or another type of reader.

[018] The pump device 14 may comprise a motor 14A for pumping infusion fluid, a pumping chamber 14B through which the infusion fluid is pumped, a local controller 14C for controlling the input device 15 and the display device 17, and sensors 14D for detecting the infusion fluid within the pumping chamber 14B and for monitoring the motor 14A. The input device 15 which is configured to allow entry of information, and the display device 17 which is configured to display information both may be in wired communication with the pump device 14 and the computer processing device 18. In one embodiment, the pump device 14 may include the input device 15 and the display device 17. In other

embodiments, the pump device 14, input device 15, and display device 17 may comprise separate components which are all attached to the upper portion 12C of the intravenous pole 12. In still other embodiments, the pump device 14, input device 15, and display device 17 may vary in quantity, configuration, attachment, location, and function.

[019] The power supply device 16 is attached to the bottom portion 12A of the intravenous pole 12. The power supply device 16 is configured to supply power to the information reader 7, to the pump device 14, to the input device 15, to the display device 17, to the computer processing device 18, to the switch device 21, to the alarm device 22, and to the communication device 24. The power supply device 16 may comprise a plurality of redundant power supply devices. The power supply device 16 may comprise a plurality of alternating current and direct current power supplies, a plurality of alternating current and direct current converter modules, and a plurality of batteries. A $m + n$ (m and n comprising integers) protection scheme may be used to back-up the primary power supply. Moreover, a $m+n$ (m and n comprising integers) protection scheme may be used to back-up the primary battery. All power supplies may be switched on and when one primary power supply fails the output may be switched to the backup power supply. In one embodiment, IEC-60601-1 ed.2 and ed.3 alternating current and direct current converter modules may be utilized. The power supply device 16 may comprise a smart battery charger for an entire battery pack. The power supply device 16 may utilize any type or number of batteries. In other embodiments, the power supply device 16 may vary in

quantity, configuration, attachment, location, and function.

[020] The computer processing device 18 is attached to the bottom portion 12A of the intravenous pole 12. The computer processing device 18 is configured to control the information reader 7, the pump device 14, the input device 15, the display device 17, the power supply device 16, the switch device 21, the alarm device 22, and the communication device 24. The computer processing device 18 may comprise a plurality of redundant computer processing devices. A $m + n$ (m and n comprising integers) protection scheme may be used to back-up the primary computer processing device. All the redundant computer processing devices may be turned on at the same time and may be hot swappable. The redundant computer processing devices may comprise a plurality of redundant central processing unit boards and a plurality of redundant solid state memories such as static-random-access-memory or flash. A $m + n$ (m and n comprising integers) protection scheme may be used to back-up the primary memory module. The redundant computer processing devices may comprise a plurality of redundant hard disk drives. A $m + n$ (m and n comprising integers) protection scheme may be used to back-up the primary hard disk.

[021] The switch device 21 is configured to switch between redundant components such as redundant power supply devices 16, redundant computer processing devices 18, redundant alarm devices 22, and redundant communication devices 24 in order to control/determine which redundant component is being used. In other embodiments, any of the components of the infusion system 10 may be made redundant and the switch device 21 may

control which redundant component is being used at any given time.

[022] All versions of infusion pump device software that may be used for the pump device 14 may be installed in one or more databases that resides in the computer processing device 18. When a new or updated pump device 14 is connected to the conduit 20 the appropriate software version may automatically be identified, and the infusion system 10 may automatically configure with the matched pair of the new or updated pump device 14 and the appropriate identified software version. The pump device 14 may be separately optimized for any computer processing device 18 design. The computer processing device 18 may be separately optimized for any pump device 14 design.

Upgrade of the pump device 14 and upgrade of the computer processing device 18 may be completely independent of one another. In other embodiments, the computer processing device 18 may vary in quantity, configuration, attachment, location, and function.

[023] The alarm device 22 is attached to the bottom portion 12A of the intravenous pole 12. The alarm device 22 is configured to sound or visualize an alarm when one or more conditions of the pump device 14 are met as ascertained by the computer processing device 18. The alarm device 22 may comprise a plurality of redundant alarm devices. In other embodiments, the alarm device 22 may vary in quantity, configuration, attachment, location, and function.

[024] IEC-60601-1 ed.3 requires that intravenous poles be mechanically stable so that they do not tip over. The attachment of the power supply device 16, the

computer processing device 18, the switch device 21, the alarm device 22, and the communication device 24 at the bottom portion 12A of the intravenous pole 12 increases the stability of the infusion system 10, especially when the wheels 29 are used to move the infusion system 10 over the ground or floor surface 26.

[025] In other embodiments, the infusion system 10 may vary in configuration, components, and function.

[026] Figure 2 illustrates a flowchart of one embodiment of a method 30 for manufacturing, setting up, and/or using an infusion system. The infusion system 10 of Figure 1 may be utilized in implementing the method 30 of Figure 2. In other embodiments, the method 30 of Figure 2 may utilize varying infusion systems. In step 32, an information reader, a pump device, an input device, and a display device are attached to an upper portion, adjacent a top end, of an intravenous pole. In one embodiment, the pump device may include the input device and the display device. In another embodiment, the pump device, the input device, and the display device may comprise varying components. In still other embodiments, the pump device, the input device, and the display device may be combined or separated in any combination. In step 34, a server including a power supply device, a computer processing device, a switch device, an alarm device, and a communication device (which may include an impedance matching circuit) is attached to a bottom portion, adjacent a bottom end, of the intravenous pole. In one embodiment, the power supply device, the computer processing device, the switch device, the alarm device, and the communication device may all comprise the same device comprising the server.

In another embodiment, the power supply device, the computer processing device, the switch device, the alarm device, and the communication device may comprise separate devices or may be combined or separated in any combination. Any of the power supply device, the computer processing device, the switch device, the alarm device, and the communication device, or any other components of the infusion system, may comprise multiple devices which are redundant.

[027] In step 36, conduit is extended within a hollow shaft of the intravenous pole to connect the information reader, the pump device, the input device, the display device, the power supply device, the computer processing device, the switch device, the alarm device, and the communication device (which may include an impedance matching circuit). In one embodiment, step 36 may comprise extending retractable conduit from the hollow shaft of the intravenous pole through a top end of the intravenous pole to connect to any of the components of the infusion system. In another embodiment, step 36 may comprise extending the conduit through one or more varied location openings of the intravenous pole to connect the conduit to any of the components of the infusion system.

[028] In step 38, the information reader, the pump device, the input device, the display device, the computer processing device, the switch device, the alarm device, and the communication device (which may include an impedance matching circuit) are powered with the power supply device. In one embodiment, step 38 may comprise powering the information reader, the pump

device, the input device, the display device, the computer processing device, the switch device, the alarm device, and the communication device with redundant power supply devices with the switch device controlling which redundant component is used at any given time. In one embodiment, the power supply device may comprise a plurality of alternating current and direct current power supplies, a plurality of alternating current and direct current converter modules, and a plurality of batteries. In other embodiments, the power supply device may vary.

[029] In step 40, the information reader, the pump device, the input device, the display device, the power supply device, the switch device, the alarm device, and the communication device are controlled with the computer processing device. In another embodiment, step 40 may comprise controlling the information reader, the pump device, the input device, the display device, the power supply device, the switch device, the alarm device, and the communication device with redundant computer processing devices.

[030] In step 42, information is entered into the input device and the information is utilized by the computer processing device to control the pump device. In one embodiment, step 42 may further comprise displaying information on the display device. In step 44, signals containing information are transmitted and received between the computer processing device and one or more remote devices using the intravenous pole as an antenna and/or using the communication device, either of which may include an impedance matching circuit. The communication device may comprise a wireless transmitter and a

wireless receiver which may comprise the same or different components.

[031] In other embodiments, one or more of the steps of the method 30 may be varied in substance or order, one or more of the steps of the method 30 may not be followed, or one or more additional steps may be added to the method 30.

In still other embodiments, the method 30 may vary further.

[032] It should be understood, of course, that the foregoing relates to exemplary embodiments of the disclosure and that modifications may be made without departing from the scope of the disclosure as set forth in the following claims. It is noted for construction of the claims that the multiple devices of any single claim can be combined with one another into one integrated device, can comprise separate devices, or can be combined, integrated, or separated in any combination unless otherwise explicitly specified in the claim.

THE EMBODIMENTS OF THE INVENTION FOR WHICH AN EXCLUSIVE PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

1. An infusion system comprising:
 - an intravenous pole comprising a bottom portion adjacent a bottom end, an upper portion adjacent a top end, and a hollow shaft;
 - a pump device positioned on the upper portion of the intravenous pole, the pump device configured to be attached to the upper portion of the intravenous pole by a first mounting device;
 - a power supply device positioned on the bottom portion of the intravenous pole, the power supply device configured to provide energy to the pump device;
 - a computer processing device positioned on the bottom portion of the intravenous pole, the computing processing device configured to be attached to the bottom portion of the intravenous pole by a second mounting device;
 - a conduit extending within the hollow shaft of the intravenous pole, wherein the conduit connects the pump device, the power supply device, and the computer processing device; and
 - wherein the power supply device and the computer processing device comprise a single integrated bottom unit.
2. The infusion system of claim 1 wherein the intravenous pole comprises an antenna.
3. The infusion system of claim 1 further comprising a wireless communication device comprising the intravenous pole itself or attached to the bottom portion of the intravenous pole.
4. The infusion system of claim 1 further comprising a display device and an input device both attached to the upper portion of the intravenous pole.
5. The infusion system of claim 1 wherein the power supply device comprises a plurality of redundant power supply devices.
6. The infusion system of claim 1 wherein the power supply device comprises a plurality of alternating current and direct current power supplies, a plurality of alternating current and direct current converter modules, and a plurality of batteries.
7. The infusion system of claim 1 wherein the computer processing

device comprises a plurality of redundant computer processing devices.

8. The infusion system of claim 1 further comprising an alarm device attached to the bottom portion of the intravenous pole.

9. The infusion system of claim 8 wherein redundant alarm devices are attached to the bottom portion of the intravenous pole.

10. The infusion system of claim 1 wherein the conduit is retractable and extends from the hollow shaft through the top end on the intravenous pole.

11. The infusion system of claim 1 further comprising an impedance matching circuit comprising or attached to the intravenous pole.

12. A method of manufacturing, setting up, or using an infusion system comprising:

positioning a pump device on an upper portion, adjacent a top end, of an intravenous pole, the pump device attached by a first mounting device;

positioning a power supply device and a computer processing device on a bottom portion, adjacent a bottom end, of the intravenous pole, the power supply device attached by a second mounting device, wherein the power supply device and the computer processing device comprise a single integrated bottom unit; and

extending a conduit within a hollow shaft of the intravenous pole to connect the pump device, the power supply, and the computer processing device.

13. The method of claim 12 further comprising powering the pump device and the computer processing device with the power supply device, and controlling the pump device with the computer processing device.

14. The method of claim 12 further comprising transmitting or receiving signals using the intravenous pole as an antenna.

15. The method of claim 12 further comprising attaching a communication device to the bottom portion of the intravenous pole, and transmitting and receiving signals using the communication device.

16. The method of claim 15 further comprising attaching an impedance matching circuit to the intravenous pole.


17. The method of claim 12 further comprising attaching an alarm device to the bottom portion of the intravenous pole, connecting the alarm device to the power supply device and the computer processing device with the conduit, powering the alarm device with the power supply device, and controlling the alarm device with the computer processing device.

18. The infusion system of Claim 1, wherein the single integrated bottom unit is tapered such that a base portion is wider than a top portion.


19. The infusion system of Claim 4, wherein the pump device, display device, and input device comprise a single integrated top unit.

20. The infusion system of Claim 19, wherein the top integrated unit is positioned directly over the bottom integrated unit.

1/2

**FIG. 1**

2/2

**FIG. 2**

